



Class II Permissive Change Portable Cellular Phone SAR Test Report

Tests Requested By: Motorola Mobility, Inc.
600 N. US Highway 45
Libertyville, IL 60048

Test Report #: 23908-2F Class II Permissive Change Rev B report
Date of Report: 19 Apr, 2011
Date of Test: 13 – 19 Apr, 2011
FCC ID #: IHDP56LD1
Generic Name: MRQ6-334411F11

Test Laboratory: Motorola Mobility, Inc. - Product Safety & Compliance Laboratory
600 N. US Highway 45
Libertyville, IL 60048

Report Author: Steven Hauswirth
Distinguished Member of the Technical Staff

This laboratory is accredited to ISO/IEC 17025-2005 to perform the following tests:

Accreditation:



2404

| | |
|--|---|
| <u>Tests:</u> | <u>Procedures:</u> |
| Electromagnetic Specific Absorption Rate | IEC 62209-1 |
| | RSS-102 |
| | IEEE 1528 - 2003 |
| | FCC OET Bulletin 65 (including Supplement C) |
| | Australian Communications Authority Radio |
| | Communications (Electromagnetic Radiation – Human |
| | Exposure) Standard 2003 |
| | CENELEC EN 50360 |
| | ARIB Std. T-56 (2002) |

On the following products or types of products:

Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

Statement of Compliance:

Motorola declares under its sole responsibility that the portable cellular telephone model to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093) as well as with CENELEC en50360:2001 and ANSI / IEEE C95.1. It also declares that the product was tested in accordance with IEEE 1528 / CENELEC EN62209-1 (2006), as well as other appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola, Inc. 2011

This test report shall not be reproduced except in full, without written approval of the laboratory. The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report. Motorola encourages all feedback, both positive and negative, on this test report.

Table of Contents

| | |
|--|-----------|
| 1. Introduction | 3 |
| 2. Description of the Device Under Test | 3 |
| 2.1 Antenna description | 3 |
| 2.3 Device Conducted Power Measurements | 6 |
| 2.3.3 Wi-Fi 802.11 modes | 7 |
| 3. Test Equipment Used | 8 |
| 3.1 Dosimetric System | 8 |
| 3.2 Additional Equipment | 8 |
| 4. Electrical parameters of the tissue simulating liquid | 9 |
| 5. System Accuracy Verification | 10 |
| 6. Test Results | 11 |
| 6.1 Head Adjacent Test Results | 11 |
| References | 16 |
| Appendix 1: SAR distribution comparison for the system accuracy verification | |
| Appendix 2: SAR distribution plots for Body Worn Configuration (WiFi Hot Spot Mode) | |
| Appendix 3: Probe Calibration Certificate | |
| Appendix 4: Measurement Uncertainty Budget | |
| Appendix 5: Dipole Characterization Certificate | |

1. Introduction

The Motorola Mobile Devices Business Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of the portable cellular phone covered by this test report when used in the WiFi hotspot mode. The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with [1], [4] and [5]. The SAR values measured for the portable cellular phone are below the maximum recommended levels of 1.6 W/kg in a 1 g average set in [3] and 2.0 W/kg in a 10 g average set in [2].

For ANSI / IEEE C95.1 (1 g), the final stand-alone SAR readings for this phone are 1.55 W/kg for body-worn use. These measurements were performed using a Dasy4™ v4.7 system manufactured by Schmid & Partner Engineering AG (SPEAG), of Zurich Switzerland.

2. Description of the Device Under Test

2.1 Antenna description

Antenna for 1800/1900 MHz Bands

| | | |
|-------------------|-------------------------|-------|
| Type | Internal | |
| Location | Top Rear of Transceiver | |
| Dimensions | Length | 56 mm |
| | Width | 13 mm |


Antenna for 850/900 MHz Bands

| | | |
|-------------------|----------------------------|-------|
| Type | Internal | |
| Location | Bottom Rear of Transceiver | |
| Dimensions | Length | 54 mm |
| | Width | 12 mm |

Antenna for Bluetooth/Wi-Fi

| | | |
|-------------------|--------------------------------|-------|
| Type | Internal | |
| Location | Right-Side Rear of Transceiver | |
| Dimensions | Length | 15 mm |
| | Width | 2 mm |

Antenna Positions



2.2 Device description¹

| | | | | | | | | |
|--|-----------------------------------|-------------------|---------------------|---------------------|-------------------|---------------------|---------------------|---------------------|
| Serial Number(s) | 351574040016601 | | | | | | | |
| Mode(s) of Operation | GSM 850 | GSM 900 | GSM 1800 | GSM 1900 | WCDMA 850 | WCDMA 1900 | Wi-Fi 802.11b/g/n | Bluetooth |
| Modulation Mode(s) | GMSK | GMSK | GMSK | GMSK | QPSK | QPSK | BPSK | GFSK |
| Maximum Output Power Setting | 33.0 dBm | 33.0 dBm | 30.5 dBm | 30.5 dBm | 24.0 dBm | 23.5 dBm | 20 dBm | 10 dBm |
| Duty Cycle | 1:8 | 1:8 | 1:8 | 1:8 | 1:1 | 1:1 | 1:1 | 1:1 |
| Transmitting Frequency Range(s) | 824.2 - 848.8 MHz | 880.2 - 914.8 MHz | 1710.2 - 1784.8 MHz | 1850.2 - 1909.8 MHz | 826.4 - 846.6 MHz | 1852.4 - 1907.6 MHz | 2412.0 - 2462.5 MHz | 2402.0 - 2483.5 MHz |
| Production Unit or Identical Prototype (47 CFR §2.908) | Identical Prototype | | | | | | | |
| Device Category | Portable | | | | | | | |
| RF Exposure Limits | General Population / Uncontrolled | | | | | | | |

| | | | | | | | | | | | | | | | | |
|---------------------------------|-------------------|-------------|------|------|-------------------|-------------|------|------|---------------------|-------------|------|------|---------------------|-------------|------|------|
| Mode(s) of Operation | GPRS 850 | | | | GPRS 900 | | | | GPRS 1800 | | | | GPRS 1900 | | | |
| Modulation | GMSK | | | | GMSK | | | | GMSK | | | | GMSK | | | |
| Maximum Output Power Setting | 33.0 | 31.0 | 29.0 | 27.0 | 33.0 | 31.0 | 29.0 | 27.0 | 30.5 | 28.5 | 26.5 | 24.5 | 30.5 | 28.5 | 26.5 | 24.5 |
| Duty Cycle | 1:8 | 2:8 | 3:8 | 4:8 | 1:8 | 2:8 | 3:8 | 4:8 | 1:8 | 2:8 | 3:8 | 4:8 | 1:8 | 2:8 | 3:8 | 4:8 |
| Transmitting Frequency Range(s) | 824.2 - 848.8 MHz | | | | 880.2 - 914.8 MHz | | | | 1710.2 - 1784.8 MHz | | | | 1850.2 - 1909.8 MHz | | | |

| | | | | | | | | | | | | | | | | |
|---------------------------------|-------------------|-------------|------|------|-------------------|-------------|------|------|---------------------|-------------|------|------|---------------------|-------------|------|------|
| Mode(s) of Operation | EDGE 850 | | | | EDGE 900 | | | | EDGE 1800 | | | | EDGE 1900 | | | |
| Modulation | 8PSK | | | | 8PSK | | | | 8PSK | | | | 8PSK | | | |
| Maximum Output Power Setting | 28.5 | 26.5 | 24.5 | 22.5 | 28.5 | 26.5 | 24.5 | 22.5 | 27.5 | 25.5 | 23.5 | 21.5 | 27.5 | 25.5 | 23.5 | 21.5 |
| Duty Cycle | 1:8 | 2:8 | 3:8 | 4:8 | 1:8 | 2:8 | 3:8 | 4:8 | 1:8 | 2:8 | 3:8 | 4:8 | 1:8 | 2:8 | 3:8 | 4:8 |
| Transmitting Frequency Range(s) | 824.2 - 848.8 MHz | | | | 880.2 - 914.8 MHz | | | | 1710.2 - 1784.8 MHz | | | | 1850.2 - 1909.8 MHz | | | |

¹ **Bolded** entries in the tables indicate data mode configurations of highest time-average power output per band and data mode type, and thus were utilized for SAR testing in this report.

2.3 Device Conducted Power Measurements

2.3.1 WCDMA modes

Per the “SAR Measurement Procedures for 3G Devices” released in October, 2007, 12.2 kbps RMC, 12.2 kbps AMR, HS-DPCCH Sub-test 1-4, and E-DCH Sub-test 1-5 modes were considered. The conducted power measurements (per section 5.2 of 3GPP TS 34.121) for each mode are shown in the table below.

| Band | Channel | Conducted power (dBm) for WCDMA modes | | Conducted Power (dBm) for WCDMA – HSDPA (Rel 5) Modes | | | | Conducted Power (dBm) for WCDMA – HSPA (HSUPA/HSDPA-Rel 6) Modes | | | | |
|------------|---------|---------------------------------------|-------|---|-----------|-----------|-----------|--|-----------|-----------|-----------|-----------|
| | | RMC | AMR | Subtest 1 | Subtest 2 | Subtest 3 | Subtest 4 | Subtest 1 | Subtest 2 | Subtest 3 | Subtest 4 | Subtest 5 |
| WCDMA 850 | 4132 | 24.08 | 24.08 | 24.13 | 24.12 | 24.10 | 24.16 | 24.08 | 24.12 | 24.07 | 24.12 | 24.12 |
| | 4180 | 24.18 | 24.07 | 24.06 | 24.19 | 24.19 | 24.19 | 24.02 | 24.21 | 24.20 | 24.17 | 24.18 |
| | 4233 | 24.02 | 23.95 | 23.96 | 23.88 | 23.97 | 23.90 | 24.02 | 23.90 | 23.93 | 23.88 | 23.97 |
| WCDMA 1900 | 9262 | 23.99 | 23.99 | 24.15 | 24.12 | 24.24 | 24.21 | 24.10 | 24.13 | 24.21 | 24.18 | 24.24 |
| | 9400 | 23.98 | 23.96 | 24.05 | 24.05 | 24.14 | 24.09 | 24.01 | 24.00 | 24.08 | 24.07 | 24.10 |
| | 9538 | 23.90 | 23.89 | 23.86 | 23.89 | 23.91 | 23.86 | 23.93 | 23.96 | 23.98 | 24.00 | 24.00 |

Maximum Power Reduction (MPR)

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

| UE transmit channel configuration | CM (dB) | MPR (dB) |
|---|----------------------|---------------|
| For all combinations of; DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH | $0 \leq CM \leq 3.5$ | MAX (CM-1, 0) |
| Note 1: $CM = 1$ for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference. | | |

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to-average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present, the beta gains on those channels are reduced first to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done. However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a mechanism to compensate for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

2.3.2 Wi-Fi 802.11 modes

Per “SAR Measurement Procedures for 802.11 a/b/g Transmitters” (FCC KDB 248227), power measurements were performed for 802.11 operational modes. The conducted power measurements for each mode are shown in the table below. SAR testing for 802.11 modes was performed with the transmitter mode and data rate set to the configurations highlighted in bold below.

| Band | Channel | Conducted Power (dBm) for 802.11b Mode Data Rates | | | |
|-------------------|---------|---|--------|----------|---------|
| | | 1 Mbps | 2 Mbps | 5.5 Mbps | 11 Mbps |
| Wi-Fi 2450 MHz | 1 | 17.46 | 17.40 | 17.23 | 17.17 |
| | 6 | 18.07 | 18.06 | 17.95 | 17.85 |
| | 11 | 18.49 | 18.56 | 18.32 | 18.59 |

| Band | Chnl | Conducted Power (dBm) for 802.11g Mode Data Rates | | | | | | | |
|-------------------|------|---|--------|---------|---------|---------|---------|---------|---------|
| | | 6 Mbps | 9 Mbps | 12 Mbps | 18 Mbps | 24 Mbps | 36 Mbps | 48 Mbps | 54 Mbps |
| Wi-Fi 2450 MHz | 1 | 14.62 | 14.32 | 14.27 | 14.07 | 14.00 | 13.95 | 12.43 | 12.47 |
| | 6 | 17.47 | 17.28 | 16.87 | 16.49 | 14.52 | 14.68 | 13.08 | 13.25 |
| | 11 | 17.98 | 17.83 | 17.56 | 17.16 | 15.30 | 15.25 | 13.82 | 13.84 |

| Band | Chnl | Conducted Power (dBm) for 802.11n Mode Data Rates (20 MHz Channel, 800 ns Guard Interval) | | | | | | | |
|-------------------|------|--|---------|-----------|---------|---------|---------|-----------|---------|
| | | 6.5 Mbps | 13 Mbps | 19.5 Mbps | 26 Mbps | 39 Mbps | 52 Mbps | 58.5 Mbps | 65 Mbps |
| Wi-Fi 2450 MHz | 1 | 14.21 | 14.24 | 13.77 | 13.91 | 13.81 | 12.30 | 12.34 | 11.47 |
| | 6 | 17.10 | 16.64 | 16.29 | 14.58 | 14.57 | 13.11 | 12.97 | 12.05 |
| | 11 | 17.97 | 17.32 | 17.00 | 15.30 | 15.21 | 13.76 | 13.67 | 12.89 |

| Band | Chnl | Conducted Power (dBm) for 802.11n Mode Data Rates (20 MHz Channel, 400 ns Guard Interval) | | | | | | | |
|-------------------|------|--|-----------|-----------|-----------|-----------|-----------|---------|-----------|
| | | 7.2 Mbps | 14.4 Mbps | 21.6 Mbps | 28.8 Mbps | 43.3 Mbps | 57.7 Mbps | 65 Mbps | 72.2 Mbps |
| Wi-Fi 2450 MHz | 1 | 14.14 | 14.24 | 13.64 | 13.84 | 13.68 | 12.20 | 12.25 | 11.35 |
| | 6 | 17.06 | 16.60 | 16.17 | 14.55 | 14.40 | 12.89 | 12.94 | 12.04 |
| | 11 | 17.72 | 17.26 | 16.80 | 15.13 | 15.03 | 13.51 | 13.52 | 12.59 |

3. Test Equipment Used

3.1 Dosimetric System

The Motorola Mobile Devices Business Product Safety & Compliance Laboratory utilizes a Dosimetric Assessment System (Dasy4™ v4.7) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All the SAR measurements are taken within a shielded enclosure. The overall 10 g RSS uncertainty of the measurement system is $\pm 10.8\%$ (K=1) with an expanded uncertainty of $\pm 21.6\%$ (K=2). The overall 1 g RSS uncertainty of the measurement system is $\pm 11.1\%$ (K=1) with an expanded uncertainty of $\pm 22.2\%$ (K=2). The measurement uncertainty budget is given in Appendix 4. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4 W/kg to 10 W/kg.

The list of calibrated equipment used for the measurements is shown in the following table.

| Description | Serial Number | Cal Date | Cal Due Date |
|---------------------------------|---------------|-------------|--------------|
| DASY4™ DAE V3 | 434 | Jan-13-2011 | Jan-13-2012 |
| E-Field Probe ES3DV3 | 3124 | Aug-11-2010 | Aug-11-2011 |
| DASY4™ DAE V3 | 661 | Jan-13-2011 | Jan-13-2012 |
| E-Field Probe ES3DV3 | 3183 | Jul-14-2010 | Jul-14-2011 |
| Dipole Validation Kit, DV835V2 | 422TR | Mar-18-2011 | Mar-18-2013 |
| Dipole Validation Kit, DV835V2 | 436TR | Mar-18-2011 | Mar-18-2013 |
| Dipole Validation Kit, DV1800V2 | 259TR | Mar-17-2011 | Mar-17-2013 |
| Dipole Validation Kit, DV1800V2 | 271TR | Mar-08-2011 | Mar-08-2013 |
| Dipole Validation Kit, DV2450V2 | 863 | Mar-17-2011 | Mar-17-2013 |
| Dipole Validation Kit, DV2450V2 | 740 | Mar-17-2011 | Mar-17-2013 |

3.2 Additional Equipment

| Description | Serial Number | Cal Due Date |
|-------------------------------|---------------|--------------|
| Signal Generator HP8648C | 3847A04810 | Oct-30-2011 |
| Power Meter E4419B | GB39511087 | Dec-22-2011 |
| Power Sensor #1 - E9301A | US39211006 | Oct-25-2011 |
| Power Sensor #2 - E9301A | US39210934 | Oct-25-2011 |
| Network Analyzer HP8753ES | US39172529 | Jun-04-2011 |
| Dielectric Probe Kit HP85070C | US99360070 | |

4. Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity, ϵ_r , and the conductivity, σ , of the tissue simulating liquids were measured with a HP85070 Dielectric Probe Kit. These values, along with the temperature of the simulated tissue are shown in the table below. The recommended limits for permittivity and conductivity are also shown. A mass density of $\rho = 1 \text{ g/cm}^3$ was entered into the system in all the cases. It can be seen that the measured parameters are within tolerance of the recommended limits specified in [1] and [5].

E-field probes calibrated at 1810 MHz were used for "1900 MHz" band (1850 MHz - 1910 MHz) SAR measurements. FCC KDB 450824 provides additional requirements on page 3 of 6 for SAR testing that is performed with probe calibration points that are more than 50 MHz removed from the measured bands. The KDB requires; "(2) When nominal tissue dielectric parameters are specified in the probe calibration data, the tissue dielectric parameters measured for routine measurements should be less than the target ϵ_r and higher than the target Sigma values to minimize SAR underestimations". The 1900 MHz simulated tissues listed below meet this criteria.

| f (MHz) | Tissue type | Limits / Measured | Dielectric Parameters | | |
|---------|-------------|-----------------------|-----------------------|----------------|-----------|
| | | | ϵ_r | σ (S/m) | Temp (°C) |
| 835 | Body | Measured, Apr-14-2011 | 53.9 | 0.97 | 20.2 |
| | | Measured, Apr-15-2011 | 55.2 | 0.99 | 19.5 |
| | | Recommended Limits | 55.2 ±5% | 0.97 ±5% | 18-25 |
| 1880 | Body | Measured, Apr-13-2011 | 51.6 | 1.59 | 20.0 |
| | | Measured, Apr-15-2011 | 51.7 | 1.59 | 19.1 |
| | | Recommended Limits | 53.3 ±5% | 1.52 ±5% | 18-25 |
| 2450 | Body | Measured, Apr-16-2011 | 48.3 | 2.02 | 19.7 |
| | | Measured, Apr-19-2011 | 48.2 | 2.03 | 19.9 |
| | | Recommended Limits | 52.7 ±10% | 1.95 ±5% | 18-25 |

The list of ingredients and the percent composition used for the simulated tissues are indicated in the table below.

| Ingredient | 835 MHz / 900 MHz Head | 835 MHz / 900 MHz Body | 1800 MHz / 1900 MHz Head | 1800 MHz / 1900 MHz Body | 2450 MHz Head | 2450 MHz Body |
|------------|------------------------|------------------------|--------------------------|--------------------------|---------------|---------------|
| Sugar | 57 | 44.9 | -- | -- | -- | -- |
| DGBE | -- | -- | 47 | 30.8 | -- | 30 |
| Diacetin | -- | -- | -- | -- | 51 | -- |
| Water | 40.45 | 53.06 | 52.62 | 68.8 | 48.75 | 70 |
| Salt | 1.45 | 0.94 | 0.38 | 0.4 | 0.15 | -- |
| HEC | 1 | 1 | -- | -- | -- | -- |
| Bact. | 0.1 | 0.1 | -- | -- | 0.1 | -- |

5. System Accuracy Verification

A system accuracy verification of the DASY4™ was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within the flat section of the SAM phantom.

A SAR measurement was performed to verify the measured SAR was within $\pm 10\%$ from the target SAR indicated in Appendix 5. These frequencies are within $\pm 10\%$ of the compliance test mid-band frequency as required in [1] and [5]. The test was conducted on the same days as the measurement of the DUT. Recommended limits for permittivity and conductivity, specified in [5], are shown in the table below. The obtained results from the system accuracy verification are also displayed in the table below. SAR values are normalized to 1 W forward power delivered to the dipole. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). The tissue stimulant depth was verified to be 15.0 cm \pm 0.5 cm. Z-axis scans showing the SAR penetration are also included in Appendix 1.

| f (MHz) | Description | SAR (W/kg), 1 gram | Dielectric Parameters | | Ambient Temp (°C) | Tissue Temp (°C) |
|------------|-----------------------|-----------------------|-----------------------|----------------|----------------------|---------------------|
| | | | ϵ_r | σ (S/m) | | |
| 835 | Measured, Apr-14-2011 | 9.80 | 53.9 | 0.97 | 20.3 | 20.7 |
| | Recommended Limits | 10.10 | 55.2 $\pm 5\%$ | 0.97 $\pm 5\%$ | 18-25 | 18-25 |
| | Measured, Apr-15-2011 | 9.90 | 55.2 | 0.99 | 20.3 | 20.7 |
| | Recommended Limits | 9.77 | 55.2 $\pm 5\%$ | 0.97 $\pm 5\%$ | 18-25 | 18-25 |
| 1800 | Measured, Apr-13-2010 | 39.55 | 52.0 | 1.48 | 20.7 | 19.4 |
| | Recommended Limits | 37.90 | 53.3 $\pm 5\%$ | 1.52 $\pm 5\%$ | 18-25 | 18-25 |
| | Measured, Apr-15-2010 | 39.80 | 52.0 | 1.49 | 20.3 | 19.4 |
| | Recommended Limits | 37.50 | 53.3 $\pm 5\%$ | 1.52 $\pm 5\%$ | 18-25 | 18-25 |
| 2450 | Measured, Apr-16-2011 | 57.50 | 48.3 | 2.03 | 20.3 | 19.4 |
| | Recommended Limits | 52.80 | 52.7 $\pm 10\%$ | 1.95 $\pm 5\%$ | 18-25 | 18-25 |
| | Measured, Apr-19-2011 | 56.00 | 48.2 | 2.04 | 20.2 | 19.1 |
| | Recommended Limits | 51.30 | 52.7 $\pm 10\%$ | 1.95 $\pm 5\%$ | 18-25 | 18-25 |

The following probe conversion factors were used on the E-Field probe(s) used for the system accuracy verification measurements:

| Description | Serial Number | f (MHz) | Conversion Factor | Cal Cert pg # |
|-------------------------|---------------|------------|-------------------|------------------|
| E-Field Probe ES3DV3 | 3124 | 835 | 5.86 | 8 of 9 |
| | | 1800 | 4.76 | 8 of 9 |
| | | 2450 | 4.19 | 8 of 9 |
| | 3183 | 2450 | 4.36 | 8 of 9 |

6. Test Results

The test sample was operated using an actual transmission through a base station simulator. The base station simulator was set up to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in [1], [4] and [5]. The phone was positioned into these configurations using the device holder supplied with the DASY4™ SAR measurement system. The default settings for the “coarse” and “cube” scans were chosen and used for measurements. The grid spacing of the course scan was set to 15 mm or less as shown in the SAR plots included in Appendix 2. Please refer to the DASY4™ manual for additional information on SAR scanning procedures and algorithms used.

The Cellular Phone model covered by this report has the following battery options:
Model SNN5877A - 1500 mAH Battery

This battery was used to do all of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery.

The location of peak SAR for a handset is a function of the type of antenna implemented, the frequencies of transmission, the configuration of phone placement against the measurement phantom, the shape of the measurement phantom, any unintended secondary radiating elements on the DUT, etc.. Therefore the location of peak SAR may not coincide with the location of the transmitting antenna.

6.1 Body Worn - Mobile Hotspot Test Results

The DUT is capable of functioning as a Wi-Fi to Cellular mobile hotspot. Additional SAR testing was performed according to the interim test guidelines provided at the October 2010 TCB Workshop. Testing was performed with a separation of 25 mm between the DUT and the “flat” phantom. The DUT was positioned for SAR tests with the front and back surfaces facing the phantom, and also with the edges facing the phantom in which the transmitting antenna is < 2.5 cm from the edge. Each transmit band was utilized for SAR testing, but only the “mode” within each band that exhibited the highest SAR results from section 6.2 was used.

The SAR results shown in tables 1 through 6 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to [6]. Also shown are the temperature of the simulated tissue after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is $\text{Extrapolated SAR} = \text{Measured SAR} * 10^{-(\text{drift}/10)}$. The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test.

The test conditions that produced the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 2. All other test conditions measured lower SAR values than those included in Appendix 2.

A “flat” phantom was for the body-worn tests. This “flat” phantom is made out of 1” thick natural High Density Polyethylene with a thickness at the bottom equal to 2.0 mm. It measures 52.7 cm(long) x 26.7 cm(wide) x 21.2 cm(tall).

The simulated tissue depth was verified to be 15.0 cm ± 0.5 cm. The same device holder described in section 6 was used for positioning the phone.

The following probe conversion factors were used on the E-Field probe(s) used for the body-worn mobile hotspot measurements:

| Description | Serial Number | f (MHz) | Conversion Factor | Cal Cert pg # |
|----------------------|---------------|---------|-------------------|---------------|
| E-Field Probe ES3DV3 | 3124 | 835 | 5.86 | 8 of 9 |
| | | 1800 | 4.76 | 8 of 9 |
| | | 2450 | 4.19 | 8 of 9 |
| | 3183 | 2450 | 4.36 | 8 of 9 |

| GPRS 850 Class 10, Body-Worn, Phone 10 mm from Phantom | | | | | | | |
|--|---------|-------------|--------------|-----------------|---------------------|-----------------|---------------------|
| 10mm Separation between Phantom and ? | Channel | Temp (°C) | Drift (dB) | 10 g SAR value | | 1 g SAR value | |
| | | | | Measured (W/kg) | Extrapolated (W/kg) | Measured (W/kg) | Extrapolated (W/kg) |
| Front of DUT | 128 | | | | | | |
| | 190 | 19.4 | -0.0756 | 0.403 | 0.41 | 0.551 | 0.56 |
| | 251 | | | | | | |
| Back of DUT | 128 | 19.6 | 0.026 | 0.832 | 0.83 | 1.17 | 1.17 |
| | 190 | 19.6 | -0.00726 | 0.83 | 0.83 | 1.17 | 1.17 |
| | 251 | 19.1 | 0.0178 | 0.687 | 0.69 | 0.988 | 0.99 |
| Bottom Edge of DUT | 128 | | | | | | |
| | 190 | 19.5 | 0.00443 | 0.0613 | 0.06 | 0.107 | 0.11 |
| | 251 | | | | | | |
| Left Edge of DUT | 128 | | | | | | |
| | 190 | 19.0 | 0.0203 | 0.252 | 0.25 | 0.368 | 0.37 |
| | 251 | | | | | | |
| Right Edge of DUT | 128 | | | | | | |
| | 190 | 19.3 | -0.0668 | 0.237 | 0.24 | 0.338 | 0.34 |
| | 251 | | | | | | |

Table 1: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| GPRS 1900 Class 10, Body-Worn, Phone 11 mm from Phantom | | | | | | | |
|---|---------|-------------|--------------|-----------------|---------------------|-----------------|---------------------|
| 11mm Separation between Phantom and ? | Channel | Temp (°C) | Drift (dB) | 10 g SAR value | | 1 g SAR value | |
| | | | | Measured (W/kg) | Extrapolated (W/kg) | Measured (W/kg) | Extrapolated (W/kg) |
| Front of DUT | 512 | | | | | | |
| | 661 | 19.1 | -0.0423 | 0.125 | 0.13 | 0.212 | 0.21 |
| | 810 | | | | | | |
| Back of DUT | 512 | 19.1 | -0.00381 | 0.519 | 0.52 | 1.01 | 1.01 |
| | 661 | 19.1 | 0.0218 | 0.66 | 0.66 | 1.33 | 1.33 |
| | 810 | 19.1 | 0.074 | 0.731 | 0.73 | 1.49 | 1.49 |
| Left Edge of DUT | 512 | | | | | | |
| | 661 | 19.0 | -0.0316 | 0.0824 | 0.08 | 0.134 | 0.13 |
| | 810 | | | | | | |
| Right Edge of DUT | 512 | | | | | | |
| | 661 | 19.0 | -0.0005 | 0.0818 | 0.08 | 0.133 | 0.13 |
| | 810 | | | | | | |
| Top Edge of DUT | 512 | 19.0 | -0.00029 | 0.409 | 0.41 | 0.807 | 0.81 |
| | 661 | 19.0 | -0.0279 | 0.535 | 0.54 | 1.07 | 1.08 |
| | 810 | 19.0 | -0.0221 | 0.538 | 0.54 | 1.09 | 1.10 |

Table 2: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| WCDMA 850, Body-Worn, Phone 10 mm from Phantom | | | | | | | |
|--|---------|-------------|---------------|-----------------|---------------------|-----------------|---------------------|
| 10mm Separation between Phantom and ? | Channel | Temp (°C) | Drift (dB) | 10 g SAR value | | 1 g SAR value | |
| | | | | Measured (W/kg) | Extrapolated (W/kg) | Measured (W/kg) | Extrapolated (W/kg) |
| Front of DUT | 4132 | | | | | | |
| | 4180 | 19.5 | 0.0165 | 0.535 | 0.54 | 0.733 | 0.73 |
| | 4233 | | | | | | |
| Back of DUT | 4132 | 19.7 | -0.144 | 1.04 | 1.04 | 1.44 | 1.44 |
| | 4180 | 19.5 | 0.00583 | 0.749 | 0.75 | 1.04 | 1.04 |
| | 4233 | 19.5 | -0.219 | 0.922 | 0.97 | 1.28 | 1.35 |
| Bottom Edge of DUT | 4132 | | | | | | |
| | 4180 | 20.0 | -0.0101 | 0.0635 | 0.06 | 0.11 | 0.11 |
| | 4233 | | | | | | |
| Left Edge of DUT | 4132 | | | | | | |
| | 4180 | 20.0 | -0.0934 | 0.425 | 0.43 | 0.611 | 0.62 |
| | 4233 | | | | | | |
| Right Edge of DUT | 4132 | | | | | | |
| | 4180 | 20.0 | -0.00953 | 0.412 | 0.41 | 0.586 | 0.59 |
| | 4233 | | | | | | |

Table 3: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| WCDMA 1900, Body-Worn, Phone 15 mm from Phantom | | | | | | | |
|---|---------|-------------|---------------|-----------------|---------------------|-----------------|---------------------|
| 15mm Separation between Phantom and ? | Channel | Temp (°C) | Drift (dB) | 10 g SAR value | | 1 g SAR value | |
| | | | | Measured (W/kg) | Extrapolated (W/kg) | Measured (W/kg) | Extrapolated (W/kg) |
| Front of DUT | 9262 | | | | | | |
| | 9400 | 19.1 | 0.0526 | 0.137 | 0.14 | 0.226 | 0.23 |
| | 9538 | | | | | | |
| Back of DUT | 9262 | 19.1 | 0.0392 | 0.594 | 0.59 | 1.08 | 1.08 |
| | 9400 | 19.1 | 0.0356 | 0.745 | 0.75 | 1.39 | 1.39 |
| | 9538 | 19.1 | 0.0425 | 0.818 | 0.82 | 1.55 | 1.55 |
| Left Edge of DUT | 9262 | | | | | | |
| | 9400 | 19.0 | -0.053 | 0.0576 | 0.06 | 0.0878 | 0.09 |
| | 9538 | | | | | | |
| Right Edge of DUT | 9262 | | | | | | |
| | 9400 | 19.0 | 0.0184 | 0.111 | 0.11 | 0.179 | 0.18 |
| | 9538 | | | | | | |
| Top Edge of DUT | 9262 | 19.0 | 0.0768 | 0.503 | 0.50 | 0.929 | 0.93 |
| | 9400 | 19.0 | 0.0329 | 0.621 | 0.62 | 1.15 | 1.15 |
| | 9538 | 19.0 | 0.00306 | 0.679 | 0.68 | 1.28 | 1.28 |

Table 4: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| WiFi 2450, Body-Worn, Phone 10 mm from Phantom | | | | | | | |
|--|---------|-------------|---------------|-----------------|---------------------|-----------------|---------------------|
| 10mm Separation between Phantom and ? | Channel | Temp (°C) | Drift (dB) | 10 g SAR value | | 1 g SAR value | |
| | | | | Measured (W/kg) | Extrapolated (W/kg) | Measured (W/kg) | Extrapolated (W/kg) |
| Front of DUT | 1 | | | | | | |
| | 6 | 19.0 | -0.054 | 0.0317 | 0.03 | 0.0548 | 0.06 |
| | 11 | | | | | | |
| Back of DUT | 1 | | | | | | |
| | 6 | 19.0 | 0.0691 | 0.0737 | 0.07 | 0.125 | 0.13 |
| | 11 | | | | | | |
| Right Edge of DUT | 1 | | | | | | |
| | 6 | 19.0 | 0.00288 | 0.0536 | 0.05 | 0.107 | 0.11 |
| | 11 | | | | | | |
| Top Edge of DUT | 1 | | | | | | |
| | 6 | 19.0 | -0.0759 | 0.0214 | 0.02 | 0.038 | 0.04 |
| | 11 | | | | | | |

Table 5: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

| WiFi 2450, Body-Worn, Back of Device towards Phantom | | | | | | | |
|--|---------|-----------|------------|-----------------|---------------------|-----------------|---------------------|
| Separation between Phantom and DUT | Channel | Temp (°C) | Drift (dB) | 10 g SAR value | | 1 g SAR value | |
| | | | | Measured (W/kg) | Extrapolated (W/kg) | Measured (W/kg) | Extrapolated (W/kg) |
| 11mm | 1 | | | | | | |
| | 6 | 19.2 | -0.0192 | 0.0547 | 0.05 | 0.107 | 0.107 |
| | 11 | | | | | | |
| 15mm | 1 | | | | | | |
| | 6 | 19.2 | -0.06 | 0.011 | 0.011 | 0.0304 | 0.03 |
| | 11 | | | | | | |

Table 6: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

References

- [1] CENELEC, en62209-1:2006 “Human Exposure to Radio Frequency Fields From Hand - Held and Body - Mounted Wireless Communication Devices – Human Models, Instrumentation, and Procedures”
- [2] CENELEC, en50360:2001 “Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)”.
- [3] ANSI / IEEE, C95.1 1992 Edition “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”
- [4] FCC OET Bulletin 65 Supplement C 01-01
- [5] IEEE 1528 2003 Edition “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”
- [6] ICNIRP Guidelines “Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz)”

Appendix 1

SAR distribution comparison for the system accuracy verification

Test Laboratory: Motorola 835 MHz System Performance Check

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:436TR;

Procedure Notes: PM1 Power = 200mW Refl.Pwr PM3 = -23.9dB [Sim.Temp@SPC](#) = 20.7*C Room Temp @ SPC = 20.3*C

Communication System: CW - Dipole; Frequency: 835 MHz; Communication System Channel Number: 3; Duty Cycle: 1:1

Medium: Validation *BODY Tissue* ; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.97 \text{ mho/m}$; $\epsilon_r = 53.9$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(5.86, 5.86, 5.86); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.2, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Daily SPC Check/Dipole Area Scan (9x4x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.86 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$


Reference Value = 47.2 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 2.88 W/kg

SAR(1 g) = 1.96 mW/g; SAR(10 g) = 1.29 mW/g


Maximum value of SAR (measured) = 2.12 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$, $dz=5\text{mm}$



SAR(x,y,z,f0)

SAR; Z-Axis Retraction: Value Along Z, X=0, Y=0



Test Laboratory: Motorola 835 MHz System Performance Check

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:422;

Procedure Notes: PM1 Power = 200mW Refl.Pwr PM3 = -23.9dB [Sim.Temp@SPC](#) = 20.7°C Room Temp @ SPC = 20.3°C

Communication System: CW - Dipole; Frequency: 835 MHz; Communication System Channel Number: 3; Duty Cycle: 1:1

Medium: Validation *BODY Tissue* ; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(5.86, 5.86, 5.86); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.2, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Daily SPC Check/Dipole Area Scan (9x4x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.89 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 46.5 V/m; Power Drift = -0.021 dB


Peak SAR (extrapolated) = 2.92 W/kg

SAR(1 g) = 1.98 mW/g; SAR(10 g) = 1.3 mW/g

Maximum value of SAR (measured) = 2.15 mW/g


Daily SPC Check/Z-Axis Retraction (1x1x31): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$, $dz=5\text{mm}$

Maximum value of SAR (measured) = 2.14 mW/g



SAR(x,y,z,f0)

SAR; Z-Axis Retraction: Value Along Z, X=0, Y=0



Test Laboratory: Motorola 1800 MHz System Performance Check

DUT: Dipole 1800 MHz; Type: D1800V2; Serial: D1800V2 - SN:271TR;

Procedure Notes: PM1 Power = 200mW Refl.Pwr PM3 = -19.4dB [Sim.Temp@SPC](#) = 19.4°C Room Temp @ SPC = 20.7°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Communication System Channel Number: 8; Duty Cycle: 1:1

Medium: Validation *BODY Tissue* ; Medium parameters used: $f = 1800$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(4.76, 4.76, 4.76); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.1, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Daily SPC Check/Dipole Area Scan (9x4x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 8.06 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 75.0 V/m; Power Drift = -0.067 dB


Peak SAR (extrapolated) = 13.7 W/kg

SAR(1 g) = 7.91 mW/g; SAR(10 g) = 4.21 mW/g

Maximum value of SAR (measured) = 8.86 mW/g


Daily SPC Check/Z-Axis Retraction (1x1x31): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 8.96 mW/g



SAR(x,y,z,f0)

SAR; Z-Axis Retraction: Value Along Z, X=0, Y=0



Test Laboratory: Motorola 1800 MHz System Performance Check

DUT: Dipole 1800 MHz; Type: D1800V2; Serial: D1800V2 - SN:259TR;

Procedure Notes: PM1 Power = 200mW Refl.Pwr PM3 = -20.3dB [Sim.Temp@SPC](#) = 19.4°C Room Temp @ SPC = 20.3°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Communication System Channel Number: 8; Duty Cycle: 1:1

Medium: Validation *BODY Tissue* ; Medium parameters used: $f = 1800$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(4.76, 4.76, 4.76); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.1, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Daily SPC Check/Dipole Area Scan (9x4x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 8.31 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 73.5 V/m; Power Drift = -0.013 dB


Peak SAR (extrapolated) = 14.0 W/kg

SAR(1 g) = 7.96 mW/g; SAR(10 g) = 4.22 mW/g

Maximum value of SAR (measured) = 8.81 mW/g


Daily SPC Check/Z-Axis Retraction (1x1x31): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 8.98 mW/g



SAR(x,y,z,f0)

SAR; Z-Axis Retraction: Value Along Z, X=0, Y=0



Test Laboratory: Motorola 2450 MHz System Performance Check

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:863;

Procedure Notes: PM1 Power = 200mW Refl.Pwr PM3 = -24.5dB [Sim.Temp@SPC](#) = 19.4°C Room Temp @ SPC = 20.3°C

Communication System: CW - Dipole; Frequency: 2450 MHz; Communication System Channel Number: 11; Duty Cycle: 1:1

Medium: Validation *BODY Tissue* ; Medium parameters used: $f = 2450$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 48.3$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(4.19, 4.19, 4.19); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.1, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Daily SPC Check/Dipole Area Scan (9x4x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 10.9 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 73.4 V/m; Power Drift = -0.002 dB


Peak SAR (extrapolated) = 24.2 W/kg

SAR(1 g) = 11.5 mW/g; SAR(10 g) = 5.26 mW/g


Maximum value of SAR (measured) = 12.9 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 13.1 mW/g



0 dB = 13.1mW/g



Test Laboratory: Motorola 2450 MHz System Performance Check

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:740;

Procedure Notes: PM1 Power = 200 mW Refl.Pwr PM3 = -24.12dB [Sim.Temp@SPC](#) = 19.1 Room Temp @ SPC = 20.2

Communication System: CW - Dipole; Frequency: 2450 MHz; Communication System Channel Number: 11; Duty Cycle: 1:1

Medium: Validation *BODY Tissue* ; Medium parameters used: $f = 2450$ MHz; $\sigma = 2.04$ mho/m; $\epsilon_r = 48.2$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3183; ConvF(4.36, 4.36, 4.36); Calibrated: 7/14/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn661; Calibrated: 1/13/2011
- Phantom: R1_ Section 2, Amy Twin, Rev3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Daily SPC Check/Dipole Area Scan (9x4x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.32 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 79.2 V/m; Power Drift = -0.013 dB


Peak SAR (extrapolated) = 23.8 W/kg

SAR(1 g) = 11.2 mW/g; SAR(10 g) = 5.12 mW/g

Maximum value of SAR (measured) = 12.7 mW/g


Daily SPC Check/Z-Axis Retraction (1x1x31): Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 12.8 mW/g



SAR(x,y,z,f0)

SAR; Z-Axis Retraction: Value Along Z, X=0, Y=0



Appendix 2

SAR distribution plots for Body Worn Configuration (WiFi Hot Spot Mode)

Test Laboratory: Motorola GPRS 850 MHz WiFi hotspot testing

DUT Serial: 351574040016601; FCC ID: IHDP56LD1

Procedure Notes: Pwr Step: 5 Battery Model #: SNN5877A Accessory Model # = Back of Phone 10mm from Phantom
Communication System: GPRS 850 Class 10; Frequency: 824.2 MHz; Communication System Channel Number:
128; Duty Cycle: 1:8.3

Medium: Low Freq Body; Medium parameters used: $f = 835$ MHz; $\sigma = 0.97$ mho/m; $\epsilon_r = 53.9$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(5.86, 5.86, 5.86); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.2, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Amy Twin Phone Template/Area Scan - Normal Extended Body (15mm) (16x7x1): Measurement grid:
dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.20 mW/g


Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0: Measurement grid: dx=8mm,
dy=8mm, dz=5mm

Reference Value = 34.8 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 1.17 mW/g; SAR(10 g) = 0.832 mW/g

Maximum value of SAR (measured) = 1.24 mW/g



Test Laboratory: Motorola WCDMA 850 MHz WiFi hotspot testing

DUT Serial: 351574040016601; FCC ID: IHDP56LD1

Procedure Notes: Pwr Step: All Up Bits Battery Model #: SNN5877A Accessory Model # = Back of Phone 10mm from Phantom

Communication System: 3G-WCDMA 850; Frequency: 826.4 MHz; Communication System Channel Number: 4132; Duty Cycle: 1:1

Medium: Low Freq Body; Medium parameters used: $f = 835$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 55.2$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(5.86, 5.86, 5.86); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.2, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Amy Twin Phone Template/Area Scan - Full Body (15mm) (18x8x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 1.52 mW/g

Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 39.9 V/m; Power Drift = -0.144 dB

Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 1.44 mW/g; SAR(10 g) = 1.04 mW/g



Test Laboratory: Motorola GPRS 1900 MHz WiFi hotspot test

DUT Serial: 351574040016601; FCC ID: IHDP56LD1

Procedure Notes: Pwr Step: 0, Battery Model #: SNN5877A Accessory Model # = Back of Phone 11mm from Phantom

Communication System: GPRS 1900 - Class 10; Frequency: 1909.8 MHz; Communication System Channel Number: 810; Duty Cycle: 1:4.15

Medium: Regular Glycol Body 1750/1880; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 51.6$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(4.76, 4.76, 4.76); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.1, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.52 mW/g


Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.7 V/m; Power Drift = 0.074 dB

Peak SAR (extrapolated) = 2.69 W/kg

SAR(1 g) = 1.49 mW/g; SAR(10 g) = 0.731 mW/g

Maximum value of SAR (measured) = 1.63 mW/g..



Test Laboratory: Motorola WCDMA 1900 MHz WiFi hotspot testing

DUT Serial: 351574040016601; FCC ID: IHDP56LD1

Procedure Notes: Pwr Step: ALL UP BITS Battery Model #: SNN5877A Accessory Model # = Back of Phone 15mm from Phantom

Communication System: 3G/WCDMA 1900; Frequency: 1907.5 MHz; Communication System Channel Number: 9538; Duty Cycle: 1:1

Medium: Regular Glycol Body 1750/1880; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(4.76, 4.76, 4.76); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.1, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.65 mW/g

Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.3 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 2.63 W/kg

SAR(1 g) = 1.55 mW/g; SAR(10 g) = 0.818 mW/g

Maximum value of SAR (measured) = 1.70 mW/g



Test Laboratory: Motorola 2450 MHz WiFi hotspot test

DUT Serial: 351574040016601; FCC ID: IHDP56LD1

Procedure Notes: 802.11b 1Mbps Battery Model #: SNN5877A Accessory Model # = Back of Phone 10mm from Phantom

Communication System: Wi-Fi 2450; Frequency: 2437 MHz; Communication System Channel Number: 6; Duty Cycle: 1:1

Medium: 2450 Glycol Body; Medium parameters used: $f = 2450$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 48.3$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3124; ConvF(4.19, 4.19, 4.19); Calibrated: 8/11/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn434; Calibrated: 1/13/2011
- Phantom: R4 : Sect.1, Amy Twin, Rev.3 (3-Feb-10); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.119 mW/g


Amy Twin Phone Template/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.82 V/m; Power Drift = 0.069 dB

Peak SAR (extrapolated) = 0.215 W/kg

SAR(1 g) = 0.125 mW/g; SAR(10 g) = 0.074 mW/g

Maximum value of SAR (measured) = 0.135 mW/g



Appendix 3

Probe Calibration Certificate



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola MDb**

Certificate No: **ES3-3183_Jul10**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3183**

Calibration procedure(s) **QA CAL-01.v6, QA CAL-23.v3 and QA CAL-25.v2
Calibration procedure for dosimetric E-field probes**

Calibration date: **July 14, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B | GB41293874 | 1-Apr-10 (No. 217-01136) | Apr-11 |
| Power sensor E4412A | MY41495277 | 1-Apr-10 (No. 217-01136) | Apr-11 |
| Power sensor E4412A | MY41498087 | 1-Apr-10 (No. 217-01136) | Apr-11 |
| Reference 3 dB Attenuator | SN: S5054 (3c) | 30-Mar-10 (No. 217-01159) | Mar-11 |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 30-Mar-10 (No. 217-01161) | Mar-11 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 30-Mar-10 (No. 217-01160) | Mar-11 |
| Reference Probe ES3DV2 | SN: 3013 | 30-Dec-09 (No. ES3-3013_Dec09) | Dec-10 |
| DAE4 | SN: 660 | 20-Apr-10 (No. DAE4-660_Apr10) | Apr-11 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| RF generator HP 8648C | US3642U01700 | 4-Aug-99 (in house check Oct-09) | In house check: Oct-11 |
| Network Analyzer HP 8753E | US37390585 | 18-Oct-01 (in house check Oct-09) | In house check: Oct10 |

| | | | |
|----------------|-----------------------|------------------------------|--|
| Calibrated by: | Jeton Kastrali | Laboratory Technician | |
| Approved by: | Katja Pokovic | Technical Manager | |

Issued: July 15, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|--------------------------|---|
| TSL | tissue simulating liquid |
| NORM _{x,y,z} | sensitivity in free space |
| ConvF | sensitivity in TSL / NORM _{x,y,z} |
| DCP | diode compression point |
| CF | crest factor (1/duty_cycle) of the RF signal |
| A, B, C | modulation dependent linearization parameters |
| Polarization φ | φ rotation around probe axis |
| Polarization ϑ | ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3183

| | |
|------------------|-----------------|
| Manufactured: | March 25, 2008 |
| Last calibrated: | August 17, 2009 |
| Recalibrated: | July 14, 2010 |

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 SN:3183**Basic Calibration Parameters**

| | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|---|----------|----------|----------|--------------|
| Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A | 1.21 | 1.15 | 1.07 | $\pm 10.1\%$ |
| DCP (mV) ^B | 88.6 | 86.9 | 89.5 | |

Modulation Calibration Parameters

| UID | Communication System Name | PAR | | A dB | B dBuV | C | VR mV | Unc ^E (k=2) |
|-------|---------------------------|------|---|---------|-----------|------|----------|---------------------------|
| 10000 | CW | 0.00 | X | 0.00 | 0.00 | 1.00 | 300.0 | $\pm 1.5\%$ |
| | | | Y | 0.00 | 0.00 | 1.00 | 300.0 | |
| | | | Z | 0.00 | 0.00 | 1.00 | 300.0 | |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL. (see Pages 5 and 6).

^B Numerical linearization parameter; uncertainty not required.

^E Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 SN:3183

Calibration Parameter Determined in Head Tissue Simulating Media

| f [MHz] | Validity [MHz] ^c | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 835 | ± 50 / ± 100 | 41.5 ± 5% | 0.90 ± 5% | 6.11 | 6.11 | 6.11 | 0.99 | 1.04 ± 11.0% |
| 1810 | ± 50 / ± 100 | 40.0 ± 5% | 1.40 ± 5% | 5.05 | 5.05 | 5.05 | 0.58 | 1.33 ± 11.0% |
| 1950 | ± 50 / ± 100 | 40.0 ± 5% | 1.40 ± 5% | 4.82 | 4.82 | 4.82 | 0.54 | 1.37 ± 11.0% |
| 2450 | ± 50 / ± 100 | 39.2 ± 5% | 1.80 ± 5% | 4.49 | 4.49 | 4.49 | 0.44 | 1.70 ± 11.0% |

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

DASY/EASY - Parameters of Probe: ES3DV3 SN:3183


Calibration Parameter Determined in Body Tissue Simulating Media

| f [MHz] | Validity [MHz] ^c | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 835 | ± 50 / ± 100 | 55.2 ± 5% | 0.97 ± 5% | 6.15 | 6.15 | 6.15 | 0.95 | 1.10 ± 11.0% |
| 1810 | ± 50 / ± 100 | 53.3 ± 5% | 1.52 ± 5% | 4.84 | 4.84 | 4.84 | 0.39 | 1.87 ± 11.0% |
| 1950 | ± 50 / ± 100 | 53.3 ± 5% | 1.52 ± 5% | 4.86 | 4.86 | 4.86 | 0.28 | 2.80 ± 11.0% |
| 2450 | ± 50 / ± 100 | 52.7 ± 5% | 1.95 ± 5% | 4.36 | 4.36 | 4.36 | 0.69 | 1.31 ± 11.0% |

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in HSL

Error (ϕ , θ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ (k=2)

Other Probe Parameters

| | |
|---|----------------|
| Sensor Arrangement | Triangular |
| Connector Angle (°) | Not applicable |
| Mechanical Surface Detection Mode | enabled |
| Optical Surface Detection Mode | disabled |
| Probe Overall Length | 337 mm |
| Probe Body Diameter | 10 mm |
| Tip Length | 10 mm |
| Tip Diameter | 4.0 mm |
| Probe Tip to Sensor X Calibration Point | 2 mm |
| Probe Tip to Sensor Y Calibration Point | 2 mm |
| Probe Tip to Sensor Z Calibration Point | 2 mm |
| Recommended Measurement Distance from Surface | 3 mm |



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola MDb**

Certificate No: **ES3-3124_Aug10**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3124**

Calibration procedure(s) **QA CAL-01.v6, QA CAL-23.v3 and QA CAL-25.v2
Calibration procedure for dosimetric E-field probes**

Calibration date: **August 11, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B | GB41293874 | 1-Apr-10 (No. 217-01136) | Apr-11 |
| Power sensor E4412A | MY41495277 | 1-Apr-10 (No. 217-01136) | Apr-11 |
| Power sensor E4412A | MY41498087 | 1-Apr-10 (No. 217-01136) | Apr-11 |
| Reference 3 dB Attenuator | SN: S5054 (3c) | 30-Mar-10 (No. 217-01159) | Mar-11 |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 30-Mar-10 (No. 217-01161) | Mar-11 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 30-Mar-10 (No. 217-01160) | Mar-11 |
| Reference Probe ES3DV2 | SN: 3013 | 30-Dec-09 (No. ES3-3013_Dec09) | Dec-10 |
| DAE4 | SN: 660 | 20-Apr-10 (No. DAE4-660_Apr10) | Apr-11 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| RF generator HP 8648C | US3642U01700 | 4-Aug-99 (in house check Oct-09) | In house check: Oct-11 |
| Network Analyzer HP 8753E | US37390585 | 18-Oct-01 (in house check Oct-09) | In house check: Oct10 |

Calibrated by: **Claudio Leubler** **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** **Technical Manager**

Issued: August 14, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|--------------------------|---|
| TSL | tissue simulating liquid |
| NORM _{x,y,z} | sensitivity in free space |
| ConvF | sensitivity in TSL / NORM _{x,y,z} |
| DCP | diode compression point |
| CF | crest factor (1/duty_cycle) of the RF signal |
| A, B, C | modulation dependent linearization parameters |
| Polarization φ | φ rotation around probe axis |
| Polarization ϑ | ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}, VR_{x,y,z}; A, B, C** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3124

| | |
|------------------|-----------------|
| Manufactured: | July 11, 2006 |
| Last calibrated: | April 21, 2009 |
| Recalibrated: | August 11, 2010 |

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 SN:3124

Basic Calibration Parameters

| | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|---|----------|----------|----------|-----------|
| Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A | 1.26 | 1.33 | 1.34 | ± 10.1% |
| DCP (mV) ^B | 92.9 | 96.4 | 96.7 | |

Modulation Calibration Parameters

| UID | Communication System Name | PAR | | A dB | B dBuV | C | VR mV | Unc ^E (k=2) |
|-------|---------------------------|------|---|---------|-----------|------|----------|---------------------------|
| 10000 | CW | 0.00 | X | 0.00 | 0.00 | 1.00 | 300.0 | ± 1.5% |
| | | | Y | 0.00 | 0.00 | 1.00 | 300.0 | |
| | | | Z | 0.00 | 0.00 | 1.00 | 300.0 | |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the maximum deviation from linear response applying recatangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 SN:3124

Calibration Parameter Determined in Head Tissue Simulating Media

| f [MHz] | Validity [MHz] ^c | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 835 | ± 50 / ± 100 | 41.5 ± 5% | 0.90 ± 5% | 5.89 | 5.89 | 5.89 | 0.97 | 1.07 ± 11.0% |
| 1810 | ± 50 / ± 100 | 40.0 ± 5% | 1.40 ± 5% | 4.89 | 4.89 | 4.89 | 0.49 | 1.54 ± 11.0% |
| 1950 | ± 50 / ± 100 | 40.0 ± 5% | 1.40 ± 5% | 4.68 | 4.68 | 4.68 | 0.50 | 1.52 ± 11.0% |
| 2450 | ± 50 / ± 100 | 39.2 ± 5% | 1.80 ± 5% | 4.35 | 4.35 | 4.35 | 0.45 | 1.78 ± 11.0% |

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

DASY/EASY - Parameters of Probe: ES3DV3 SN:3124


Calibration Parameter Determined in Body Tissue Simulating Media

| f [MHz] | Validity [MHz] ^c | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 835 | ± 50 / ± 100 | 55.2 ± 5% | 0.97 ± 5% | 5.86 | 5.86 | 5.86 | 0.96 | 1.11 ± 11.0% |
| 1810 | ± 50 / ± 100 | 53.3 ± 5% | 1.52 ± 5% | 4.76 | 4.76 | 4.76 | 0.41 | 1.84 ± 11.0% |
| 1950 | ± 50 / ± 100 | 53.3 ± 5% | 1.52 ± 5% | 4.78 | 4.78 | 4.78 | 0.32 | 2.33 ± 11.0% |
| 2450 | ± 50 / ± 100 | 52.7 ± 5% | 1.95 ± 5% | 4.19 | 4.19 | 4.19 | 0.69 | 1.29 ± 11.0% |

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head}) (Waveguide R22, f = 1800 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in HSL

Error (ϕ , θ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ (k=2)

Other Probe Parameters

| | |
|---|----------------|
| Sensor Arrangement | Triangular |
| Connector Angle (°) | Not applicable |
| Mechanical Surface Detection Mode | enabled |
| Optical Surface Detection Mode | disabled |
| Probe Overall Length | 337 mm |
| Probe Body Diameter | 10 mm |
| Tip Length | 10 mm |
| Tip Diameter | 4.0 mm |
| Probe Tip to Sensor X Calibration Point | 2 mm |
| Probe Tip to Sensor Y Calibration Point | 2 mm |
| Probe Tip to Sensor Z Calibration Point | 2 mm |
| Recommended Measurement Distance from Surface | 3 mm |

Appendix 4

Measurement Uncertainty Budget

| <i>a</i> | <i>b</i> | <i>c</i> | <i>d</i> | $e = f(d,k)$ | <i>f</i> | <i>g</i> | $h = c \times f / e$ | $i = c \times g / e$ | <i>k</i> |
|--|-------------------|-----------------|-----------|--------------|-------------|--------------|----------------------|-----------------------|----------|
| Uncertainty Component | IEEE 1528 section | Tol. (\pm %) | Prob Dist | Div. | c_i (1 g) | c_i (10 g) | 1 g u_i (\pm %) | 10 g u_i (\pm %) | v_i |
| Measurement System | | | | | | | | | |
| Probe Calibration | E.2.1 | 5.9 | N | 1.00 | 1 | 1 | 5.9 | 5.9 | ∞ |
| Axial Isotropy | E.2.2 | 4.7 | R | 1.73 | 0.707 | 0.707 | 1.9 | 1.9 | ∞ |
| Hemispherical Isotropy | E.2.2 | 9.6 | R | 1.73 | 0.707 | 0.707 | 3.9 | 3.9 | ∞ |
| Boundary Effect | E.2.3 | 1.0 | R | 1.73 | 1 | 1 | 0.6 | 0.6 | ∞ |
| Linearity | E.2.4 | 4.7 | R | 1.73 | 1 | 1 | 2.7 | 2.7 | ∞ |
| System Detection Limits | E.2.5 | 1.0 | R | 1.73 | 1 | 1 | 0.6 | 0.6 | ∞ |
| Readout Electronics | E.2.6 | 0.3 | N | 1.00 | 1 | 1 | 0.3 | 0.3 | ∞ |
| Response Time | E.2.7 | 1.1 | R | 1.73 | 1 | 1 | 0.6 | 0.6 | ∞ |
| Integration Time | E.2.8 | 1.1 | R | 1.73 | 1 | 1 | 0.6 | 0.6 | ∞ |
| RF Ambient Conditions - Noise | E.6.1 | 3.0 | R | 1.73 | 1 | 1 | 1.7 | 1.7 | ∞ |
| RF Ambient Conditions - Reflections | E.6.1 | 0.0 | R | 1.73 | 1 | 1 | 0.0 | 0.0 | ∞ |
| Probe Positioner Mech. Tolerance | E.6.2 | 0.4 | R | 1.73 | 1 | 1 | 0.2 | 0.2 | ∞ |
| Probe Positioning w.r.t Phantom | E.6.3 | 1.4 | R | 1.73 | 1 | 1 | 0.8 | 0.8 | ∞ |
| Max. SAR Evaluation (ext., int., avg.) | E.5 | 3.4 | R | 1.73 | 1 | 1 | 2.0 | 2.0 | ∞ |
| Test sample Related | | | | | | | | | |
| Test Sample Positioning | E.4.2 | 3.2 | N | 1.00 | 1 | 1 | 3.2 | 3.2 | 29 |
| Device Holder Uncertainty | E.4.1 | 4.0 | N | 1.00 | 1 | 1 | 4.0 | 4.0 | 8 |
| SAR drift | 6.6.2 | 5.0 | R | 1.73 | 1 | 1 | 2.9 | 2.9 | ∞ |
| Phantom and Tissue Parameters | | | | | | | | | |
| Phantom Uncertainty | E.3.1 | 4.0 | R | 1.73 | 1 | 1 | 2.3 | 2.3 | ∞ |
| Liquid Conductivity (target) | E.3.2 | 5.0 | R | 1.73 | 0.64 | 0.43 | 1.8 | 1.2 | ∞ |
| Liquid Conductivity (measurement) | E.3.3 | 3.3 | N | 1.00 | 0.64 | 0.43 | 2.1 | 1.4 | ∞ |
| Liquid Permittivity (target) | E.3.2 | 5.0 | R | 1.73 | 0.6 | 0.49 | 1.7 | 1.4 | ∞ |
| Liquid Permittivity (measurement) | E.3.3 | 1.9 | N | 1.00 | 0.6 | 0.49 | 1.1 | 0.9 | ∞ |
| Combined Standard Uncertainty | | | RSS | | | | 11.1 | 10.8 | 411 |
| Expanded Uncertainty (95% CONFIDENCE LEVEL) | | | $k=2$ | | | | 22.2 | 21.6 | |

Appendix 5

Dipole Characterization Certificate



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola MDb**

Certificate No: **D2450V2-863_Mar11**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 863**

Calibration procedure(s) **QA CAL-05.v8
Calibration procedure for dipole validation kits**

Calibration date: **March 17, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-----------------------------|--------------------|--------------------------------|-----------------------|
| Power meter EPM-442A | GB37480704 | 06-Oct-10 (No. 217-01266) | Oct-11 |
| Power sensor HP 8481A | US37292783 | 06-Oct-10 (No. 217-01266) | Oct-11 |
| Reference 20 dB Attenuator | SN: 5086 (20g) | 30-Mar-10 (No. 217-01158) | Mar-11 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 30-Mar-10 (No. 217-01162) | Mar-11 |
| Reference Probe ES3DV3 | SN: 3205 | 30-Apr-10 (No. ES3-3205_Apr10) | Apr-11 |
| DAE4 | SN: 601 | 10-Jun-10 (No. DAE4-601_Jun10) | Jun-11 |

| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
|---------------------------|------------------|-----------------------------------|------------------------|
| Power sensor HP 8481A | MY41092317 | 18-Oct-02 (in house check Oct-09) | In house check: Oct-11 |
| RF generator R&S SMT-06 | 100005 | 4-Aug-99 (in house check Oct-09) | In house check: Oct-11 |
| Network Analyzer HP 8753E | US37390585 S4206 | 18-Oct-01 (in house check Oct-10) | In house check: Oct-11 |

| | Name | Function | Signature |
|----------------|---------------|-----------------------|-----------|
| Calibrated by: | Dimce Iliev | Laboratory Technician | |
| Approved by: | Katja Pokovic | Technical Manager | |

Issued: March 17, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|-------|---------------------------------|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|-------------------------------------|---------------------------|-------------|
| DASY Version | DASY5 | V52.6.2 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom V5.0 | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 2450 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 39.2 | 1.80 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 38.7 ± 6 % | 1.72 mho/m ± 6 % |
| Head TSL temperature during test | (22.0 ± 0.2) °C | ---- | ---- |

SAR result with Head TSL

| SAR averaged over 1 cm³ (1 g) of Head TSL | Condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 13.3 mW / g |
| SAR normalized | normalized to 1W | 53.2 mW / g |
| SAR for nominal Head TSL parameters | normalized to 1W | 54.2 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm³ (10 g) of Head TSL | condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 6.23 mW / g |
| SAR normalized | normalized to 1W | 24.9 mW / g |
| SAR for nominal Head TSL parameters | normalized to 1W | 25.1 mW / g ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|----------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 52.7 | 1.95 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 51.5 ± 6 % | 1.92 mho/m ± 6 % |
| Body TSL temperature during test | (21.0 ± 0.2) °C | ---- | ---- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 13.2 mW / g |
| SAR normalized | normalized to 1W | 52.8 mW / g |
| SAR for nominal Body TSL parameters | normalized to 1W | 52.8 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 6.11 mW / g |
| SAR normalized | normalized to 1W | 24.4 mW / g |
| SAR for nominal Body TSL parameters | normalized to 1W | 24.4 mW / g ± 16.5 % (k=2) |

Appendix

Antenna Parameters with Head TSL

| | |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.1 Ω + 2.9 j Ω |
| Return Loss | - 27.7 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.5 Ω + 5.2 j Ω |
| Return Loss | - 25.2 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.165 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|----------------|
| Manufactured by | SPEAG |
| Manufactured on | April 23, 2010 |

DASY5 Validation Report for Head TSL

Date/Time: 17.03.2011 13:48:21

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:863

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL U12 BB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.72$ mho/m; $\epsilon_r = 38.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- Measurement SW: DASY52, V52.6.2 Build (424)
- Postprocessing SW: SEMCAD X, V14.4.4 Build (2829)

Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe) /Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.8 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 27.215 W/kg

SAR(1 g) = 13.3 mW/g; SAR(10 g) = 6.23 mW/g

Maximum value of SAR (measured) = 17.128 mW/g




Impedance Measurement Plot for Head TSL

17 Mar 2011 10:52:35

[CH1] S11 1 U FS 2: 53.113 Ω 2.8770 Ω 186.89 μH 2 450.000 000 MHz

*
Del
CA




CH1 Markers
1: 44.096 Ω
-23.182 Ω
2: 2.25000 GHz

Avg
16
↑

CH2 S11 LOG 5 dB/REF -20 dB 2:-27.714 dB 2 450.000 000 MHz

CA
Avg
16
↑



CH2 Markers
1:-10.394 dB
2: 2.25000 GHz

START 2 250.000 000 MHz

STOP 2 650.000 000 MHz

DASY5 Validation Report for Body TSL

Date/Time: 08.03.2011 15:14:58

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:863

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL U12 BB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.93$ mho/m; $\epsilon_r = 51.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.31, 4.31, 4.31); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY52, V52.6.2 Build (424)
- Postprocessing SW: SEMCAD X, V14.4.4 Build (2829)


Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.651 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 27.947 W/kg

SAR(1 g) = 13.2 mW/g; SAR(10 g) = 6.11 mW/g

Maximum value of SAR (measured) = 17.459 mW/g




0 dB = 17.460mW/g

Impedance Measurement Plot for Body TSL

8 Mar 2011 18:09:08

[CH1] S11 1 U FS 1: 48.518 Ω 5.2188 Ω 339.02 μ H 2 450.000 000 MHz

*
Del
Cor



Avg
16


↑

CH2 S11 LOG 5 dB/REF -20 dB 1: -25.200 dB 2 450.000 000 MHz

Cor

Avg
16

↑



START 2 250.000 000 MHz

STOP 2 650.000 000 MHz



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola MDb**

Certificate No: **D2450V2-740_Mar11**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 740**

Calibration procedure(s) **QA CAL-05.v8
Calibration procedure for dipole validation kits**

Calibration date: **March 17, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A | GB37480704 | 06-Oct-10 (No. 217-01266) | Oct-11 |
| Power sensor HP 8481A | US37292783 | 06-Oct-10 (No. 217-01266) | Oct-11 |
| Reference 20 dB Attenuator | SN: 5086 (20g) | 30-Mar-10 (No. 217-01158) | Mar-11 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 30-Mar-10 (No. 217-01162) | Mar-11 |
| Reference Probe ES3DV3 | SN: 3205 | 30-Apr-10 (No. ES3-3205_Apr10) | Apr-11 |
| DAE4 | SN: 601 | 10-Jun-10 (No. DAE4-601_Jun10) | Jun-11 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| Power sensor HP 8481A | MY41092317 | 18-Oct-02 (in house check Oct-09) | In house check: Oct-11 |
| RF generator R&S SMT-06 | 100005 | 4-Aug-99 (in house check Oct-09) | In house check: Oct-11 |
| Network Analyzer HP 8753E | US37390585 S4206 | 18-Oct-01 (in house check Oct-10) | In house check: Oct-11 |

| | | | |
|----------------|--------------------------------|--|---------------|
| Calibrated by: | Name Claudio Leubler | Function Laboratory Technician | Signature |
| Approved by: | Name Katja Pokovic | Function Technical Manager | |

Issued: March 21, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|-------|---------------------------------|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|-------------------------------------|---------------------------|-------------|
| DASY Version | DASY5 | V52.6.2 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom V5.0 | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 2450 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 39.2 | 1.80 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 38.7 ± 6 % | 1.72 mho/m ± 6 % |
| Head TSL temperature during test | (22.0 ± 0.2) °C | ---- | ---- |

SAR result with Head TSL

| SAR averaged over 1 cm³ (1 g) of Head TSL | Condition | |
|---|--------------------|----------------------------------|
| SAR measured | 250 mW input power | 13.2 mW / g |
| SAR normalized | normalized to 1W | 52.8 mW / g |
| SAR for nominal Head TSL parameters | normalized to 1W | 53.8 mW /g ± 17.0 % (k=2) |

| SAR averaged over 10 cm³ (10 g) of Head TSL | condition | |
|---|--------------------|----------------------------------|
| SAR measured | 250 mW input power | 6.16 mW / g |
| SAR normalized | normalized to 1W | 24.6 mW / g |
| SAR for nominal Head TSL parameters | normalized to 1W | 24.8 mW /g ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|----------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 52.7 | 1.95 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 51.5 ± 6 % | 1.92 mho/m ± 6 % |
| Body TSL temperature during test | (22.0 ± 0.2) °C | ---- | ---- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 12.8 mW / g |
| SAR normalized | normalized to 1W | 51.2 mW / g |
| SAR for nominal Body TSL parameters | normalized to 1W | 51.3 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 5.88 mW / g |
| SAR normalized | normalized to 1W | 23.5 mW / g |
| SAR for nominal Body TSL parameters | normalized to 1W | 23.5 mW / g ± 16.5 % (k=2) |

Appendix

Antenna Parameters with Head TSL

| | |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.3 \Omega + 2.6 j\Omega$ |
| Return Loss | - 27.7 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $48.9 \Omega + 5.3 j\Omega$ |
| Return Loss | - 25.3 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.164 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|--------------------|
| Manufactured by | SPEAG |
| Manufactured on | September 18, 2003 |

DASY5 Validation Report for Head TSL

Date/Time: 17.03.2011 12:12:34

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:740

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL U12 BB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.72$ mho/m; $\epsilon_r = 38.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- Measurement SW: DASY52, V52.6.2 Build (424)
- Postprocessing SW: SEMCAD X, V14.4.4 Build (2829)

Head/d=10mm, Pin=250 mW, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.2 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 26.990 W/kg

SAR(1 g) = 13.2 mW/g; SAR(10 g) = 6.16 mW/g

Maximum value of SAR (measured) = 17.012 mW/g




0 dB = 17.010mW/g

Impedance Measurement Plot for Head TSL

17 Mar 2011 10:36:32

[CH1] S11 1 U FS 2: 53.330 Ω 2.6309 Ω 170.90 μ H 2 450.000 000 MHz

*
De1
Cor



CH1 Markers
1: 56.641 Ω
-138.16 Ω
1.80000 GHz

Avg
16


↑

CH2 S11 LOG 5 dB/REF -20 dB 2: -27.736 dB 2 450.000 000 MHz

Cor

Avg
16

↑



CH2 Markers
1: -2.0199 dB
1.80000 GHz

START 1 600.000 000 MHz

STOP 2 650.000 000 MHz

DASY5 Validation Report for Body TSL

Date/Time: 17.03.2011 14:38:41

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:740

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL U12 BB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.92$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.31, 4.31, 4.31); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY52, V52.6.2 Build (424)
- Postprocessing SW: SEMCAD X, V14.4.4 Build (2829)

Body/d=10mm, Pin=250 mW, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.402 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 27.038 W/kg


SAR(1 g) = 12.8 mW/g; SAR(10 g) = 5.88 mW/g

Maximum value of SAR (measured) = 16.855 mW/g



0 dB = 16.850mW/g

Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola MDb**

Certificate No: **D1800V2-271_Mar11**

CALIBRATION CERTIFICATE

Object **D1800V2 - SN: 271**

Calibration procedure(s) **QA CAL-05.v8
Calibration procedure for dipole validation kits**

Calibration date: **March 08, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A | GB37480704 | 06-Oct-10 (No. 217-01266) | Oct-11 |
| Power sensor HP 8481A | US37292783 | 06-Oct-10 (No. 217-01266) | Oct-11 |
| Reference 20 dB Attenuator | SN: 5086 (20g) | 30-Mar-10 (No. 217-01158) | Mar-11 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 30-Mar-10 (No. 217-01162) | Mar-11 |
| Reference Probe ES3DV3 | SN: 3205 | 30-Apr-10 (No. ES3-3205_Apr10) | Apr-11 |
| DAE4 | SN: 601 | 10-Jun-10 (No. DAE4-601_Jun10) | Jun-11 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| Power sensor HP 8481A | MY41092317 | 18-Oct-02 (in house check Oct-09) | In house check: Oct-11 |
| RF generator R&S SMT-06 | 100005 | 4-Aug-99 (in house check Oct-09) | In house check: Oct-11 |
| Network Analyzer HP 8753E | US37390585 S4206 | 18-Oct-01 (in house check Oct-10) | In house check: Oct-11 |

Calibrated by: **Dimce Iliev** Laboratory Technician *D. Iliev*

Approved by: **Katja Pokovic** Technical Manager *K. Pokovic*

Issued: March 9, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|-------|---------------------------------|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|-------------------------------------|---------------------------|-------------|
| DASY Version | DASY5 | V52.6.2 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom V5.0 | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 1800 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 40.0 | 1.40 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 39.4 ± 6 % | 1.35 mho/m ± 6 % |
| Head TSL temperature during test | (21.0 ± 0.2) °C | ---- | ---- |

SAR result with Head TSL

| SAR averaged over 1 cm³ (1 g) of Head TSL | Condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 9.41 mW / g |
| SAR normalized | normalized to 1W | 37.6 mW / g |
| SAR for nominal Head TSL parameters | normalized to 1W | 38.5 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm³ (10 g) of Head TSL | condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 4.96 mW / g |
| SAR normalized | normalized to 1W | 19.8 mW / g |
| SAR for nominal Head TSL parameters | normalized to 1W | 20.0 mW / g ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|----------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 53.3 | 1.52 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 52.2 ± 6 % | 1.45 mho/m ± 6 % |
| Body TSL temperature during test | (21.0 ± 0.2) °C | ---- | ---- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 9.25 mW / g |
| SAR normalized | normalized to 1W | 37.0 mW / g |
| SAR for nominal Body TSL parameters | normalized to 1W | 37.9 mW / g ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | |
|---|--------------------|-----------------------------------|
| SAR measured | 250 mW input power | 4.94 mW / g |
| SAR normalized | normalized to 1W | 19.8 mW / g |
| SAR for nominal Body TSL parameters | normalized to 1W | 20.0 mW / g ± 16.5 % (k=2) |

Appendix

Antenna Parameters with Head TSL

| | |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $51.7 \Omega + 4.2 j\Omega$ |
| Return Loss | - 27.1 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $47.2 \Omega + 3.9 j\Omega$ |
| Return Loss | - 26.1 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.198 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Design Modification by End User

The dipole has been modified with Teflon Rings (TR) placed within identified markings close to the end of each dipole arm. Calibration has been performed with TR attached to the dipole.

Additional EUT Data

| | |
|-----------------|-----------------|
| Manufactured by | SPEAG |
| Manufactured on | August 21, 2000 |

DASY5 Validation Report for Head TSL

Date/Time: 07.03.2011 12:42:07

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1800 MHz; Type: D1800V2; Serial: D1800V2 - SN:271

Communication System: CW; Frequency: 1800 MHz; Duty Cycle: 1:1

Medium: HSL U12 BB

Medium parameters used: $f = 1800$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.05, 5.05, 5.05); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- Measurement SW: DASY52, V52.6.2 Build (424)
- Postprocessing SW: SEMCAD X, V14.4.4 Build (2829)

Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.375 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 17.081 W/kg

SAR(1 g) = 9.41 mW/g; SAR(10 g) = 4.96 mW/g

Maximum value of SAR (measured) = 11.630 mW/g




Impedance Measurement Plot for Head TSL

7 Mar 2011 10:39:16

[CH1] S11 1 U FS 3: 51.660 $\hat{\omega}$ 4.1504 $\hat{\omega}$ 366.97 pH 1 800.000 000 MHz


*
De l
CA



Avg
16
↑

CH2 S11 LOG 5 dB/REF -20 dB 3:-27.140 dB 1 800.000 000 MHz

CA
Avg
16
↑



START 1 600.000 000 MHz

STOP 2 000.000 000 MHz