



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC PART 15.247 / IC RSS-210 WLAN 802.11a/n

Applicant Name:
Motorola Mobility, Inc.
8000 West Sunrise Blvd.
Plantation, FL 33322
United States

Date of Testing:
03/21/12 - 05/17/2012
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0Y1203200316.IHD

FCC ID:	IHDP56MB4
APPLICANT:	Motorola Mobility, Inc.

Application Type: Certification
EUT Type: Portable Handset
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15.247
IC Specification(s): RSS-210 Issue 8
Test Procedure(s): ANSI C63.4-2003, KDB 558074

Mode	Tx Frequency (MHz)	Avg Conducted		Peak Conducted	
		Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)
802.11a	5745 - 5825	26.853	14.29	76.560	18.84
802.11n (20MHz)	5745 - 5825	27.479	14.39	73.790	18.68
802.11n (40MHz)	5755 - 5815	16.711	12.23	57.148	17.57

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortañez
President




FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 1 of 39	

TABLE OF CONTENTS

FCC PART 15.247 MEASUREMENT REPORT.....		3
1.0 INTRODUCTION.....		4
1.1 SCOPE.....		4
1.2 PCTEST TEST LOCATION.....		4
2.0 PRODUCT INFORMATION.....		5
2.1 EQUIPMENT DESCRIPTION.....		5
2.2 DEVICE CAPABILITIES.....		5
2.3 TEST CONFIGURATION.....		5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....		5
2.5 LABELING REQUIREMENTS.....		5
3.0 DESCRIPTION OF TEST.....		6
3.1 EVALUATION PROCEDURE.....		6
3.2 AC LINE CONDUCTED EMISSIONS.....		6
3.3 RADIATED EMISSIONS.....		7
4.0 ANTENNA REQUIREMENTS.....		8
5.0 TEST EQUIPMENT CALIBRATION DATA.....		9
6.0 TEST RESULTS.....		10
6.1 SUMMARY.....		10
6.2 6DB BANDWIDTH MEASUREMENT – 802.11A/B/G/N.....		11
6.3 OUTPUT POWER MEASUREMENT – 802.11A/N (5GHZ).....		17
6.4 POWER SPECTRAL DENSITY (802.11A/N).....		19
6.5 CONDUCTED EMISSIONS AT THE BAND EDGE.....		25
6.6 CONDUCTED SPURIOUS EMISSIONS.....		29
6.7 RADIATED SPURIOUS EMISSION MEASUREMENTS.....		33
7.0 CONCLUSION.....		39

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 2 of 39	



MEASUREMENT REPORT

FCC Part 15.247



§ 2.1033 General Information

APPLICANT: Motorola Mobility, Inc.

APPLICANT ADDRESS: 8000 West Sunrise Blvd.
Plantation, FL 33322, United States

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA

FCC RULE PART(S): Part 15.247

IC SPECIFICATION(S): RSS-210 Issue 8

FCC ID: IHDP56MB4

Test Device Serial No.: N/A Production Pre-Production Engineering


FCC CLASSIFICATION: Digital Transmission System (DTS)

DATE(S) OF TEST: 03/21/12 - 05/17/2012

TEST REPORT S/N: 0Y1203200316.IHD

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 3 of 39	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 10, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 4 of 39	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Motorola Portable Handset FCC ID: IHDP56MB4**. The test data contained in this report pertains only to the emissions due to the EUT's DTS transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

802.11a/n WLAN (*), 802.11a/n UNII (*)

* UNII and 802.11n 5GHz WLAN support 20MHz and 40MHz channel bandwidths.

2.3 Test Configuration

The Motorola Portable Handset FCC ID: IHDP56MB4 was tested per the guidance of KDB 558074. See Sections 3.2, 3.3, and 6.1 of this test report for a description of the AC line conducted emissions, radiated emissions, and antenna port conducted emissions test setups, respectively.

2.4 EMI Suppression Device(s)/Modifications



No EMI suppression device(s) were added and/or no modifications were made during testing.

2.5 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 5 of 39	

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and the guidance provided in KDB 558074 were used in the measurement of the **Motorola Portable Handset FCC ID: IHDP56MB4**.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions




Figure 3-1. Shielded Enclosure Line-Conducted Test Facility

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see Figure 3-1). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see Figure 3-2). Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 3-3). Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of ½”.




Figure 3-2. Line Conducted Emission Test Set-Up

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (see Figure 3-4). All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.




Figure 3-3. Wooden Table & Bonded LISNs

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements. The bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission emission. Each emission was maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz bandwidth for final measurements. Each emission reported was calibrated using a signal generator.




Figure 3-4. LISN Schematic Diagram

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 6 of 39	

3.3 Radiated Emissions




Figure 3-5. 3-Meter Test Site

The radiated test facilities consisted of an indoor semi-anechoic chamber used for exploratory measurements and an open area test site (OATS) used for final measurements. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies higher than the upper frequency range of the broadband antenna used for testing, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used.




Figure 3-6. Dimensions of Outdoor Test Site

Exploratory measurements were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of a 0.8 meter high non-metallic 1 x 1.5 meter table (see Figure 3-7). The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth, and receive antenna height was noted for each frequency found. To record the exploratory measurements, the analyzers' detector function was set to peak mode and the bandwidth was set to 100kHz.




Figure 3-7. Turntable and System Setup

Final measurements were made on the OATS at 3 meter test range using calibrated, linearly polarized broadband or horn antennas (see Figure 3-5). The measurement area is situated on an 18 meter x 20 meter galvanized 1/2" hardware cloth as the conducting ground plane. This material is sewn together in sections 4 feet wide and 60 feet long. A total of eighteen sections are required to cover the entire measurement area. Sections are laid across the width of the pad, overlapped 1" and sewn and soldered together at intervals of 3" (7.6 cm.) The terrain of the test site is reasonably flat and level. Power and cable to the test site are buried 18" deep into the ground outside the perimeter of the site. An all-weather non-metallic housing is situated on a 2 x 3 meter area adjacent to the measurement area to house the test equipment (see Figure 3-6). The test set-up was again placed on top of the same a 0.8 meter high non-metallic 1 x 1.5 meter table on the OATS as used for exploratory measurements in the indoor chamber. The test set-up was re-configured to the same setup that was previously determined through exploratory measurements to have produced the worst case emissions. The spectrum analyzer was set to the frequencies found to have caused the highest radiated disturbances with respect to the limit during preliminary radiated measurements. The turntable containing the system was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was re-maximized by varying: the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment, powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable, and changing the polarity of the receive antenna, whichever produced the worst-case emissions. To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. For average measurements above 1GHz, the analyzer was set to peak detector with a reduced VBW setting (RBW = 1MHz, VBW = 10Hz). Each emission reported was calibrated using a signal generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3-8.




Figure 3-8. Normalized Site Attenuation Curves (H&V)

FCC ID: IHDP56MB4	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 7 of 39

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **Motorola Portable Handset FCC ID: IHDP56MB4** unit complies with the requirement of §15.203.

Ch.	BW (MHz)	Frequency (MHz)
149	20	5745
151	20 / 40	5755
153	20	5765
155	20 / 40	5775
157	20	5785

Ch.	BW (MHz)	Frequency (MHz)
159	20 / 40	5795
161	20	5805
163	20 / 40	5815
165	20	5825

Table 4-1. 802.11a/n WLAN Frequency/ Channel Operations

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/7/2011	Annual	6/7/2012	N/A
-	WL25-1	WLAN Cable Set (25GHz)	2/13/2012	Annual	2/13/2013	N/A
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	2/13/2012	Annual	2/13/2013	N/A
-	40G-1R	40GHz Radiated Cable Set	2/23/2012	Annual	2/23/2013	N/A
-	WL40-1	WLAN Cable Set (40GHz)	2/24/2012	Annual	2/24/2013	N/A
Agilent	E4448A	PSA (3Hz-50GHz) Spectrum Analyzer	2/15/2012	Annual	2/15/2013	US42510244
Agilent	N9020A	MXA Signal Analyzer	10/10/2011	Annual	10/10/2012	US46470561
Agilent	N9030A	PXA Signal Analyzer	2/23/2012	Annual	2/23/2013	MY49432391
Anritsu	ML2495A	Power Meter	10/13/2011	Annual	10/13/2012	1039008
Emco	3116	Horn Antenna (18 - 40GHz)	1/20/2012	Triennial	1/20/2015	9203-2178
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Annual	7/22/2012	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/31/2011	Annual	5/31/2012	135427
Mini-Circuits	VHF-8400+	3.4GHz - 9.9GHz High Pass Filter	2/28/2012	Annual	2/28/2013	31048
Rohde & Schwarz	RS-PR18	1-18 GHz Pre-Amplifier	6/9/2011	Annual	6/9/2012	100071
Rohde & Schwarz	RS-PR26	18-26.5 GHz Pre-Amplifier	6/9/2011	Annual	6/9/2012	100040
Rohde & Schwarz	ESU26	EMI Test Receiver	4/27/2011	Annual	4/27/2012	100342
Solar Electronics	8012-50-R-24-BNC	LISN	6/23/2011	Biennial	6/23/2013	310233

Table 5-1. Annual Test Equipment Calibration Schedule

Note: The EMI Test Receiver was used before the calibration date of 4/27/2012.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 9 of 39	

6.0 TEST RESULTS

6.1 Summary

Company Name: Motorola Mobility, Inc.

FCC ID: IHDP56MB4

FCC Classification: Digital Transmission System (DTS)



Data Rate(s) Tested: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (a)
6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps,
52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n – 20MHz)
13.5/15Mbps, 27/30Mbps, 40.5/45Mbps, 54/60Mbps, 81/90Mbps, 108/120Mbps,
121.5/135Mbps, 135/150Mbps (802.11n – 40MHz BW)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
15.247(a)(2)	RSS-210 [A8.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 6.2
15.247(b)(3)	RSS-210 [A8.4]	Transmitter Output Power	< 1 Watt		PASS	Sections 6.3
15.247(e)	RSS-210 [A8.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 6.4
15.247(d)	RSS-210 [A8.5]	Band Edge / Out-of-Band Emissions	Conducted < 20dBc		PASS	Sections 6.5, 6.6
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Sections 6.7
15.207	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 6.8
RECEIVER MODE (RX) / DIGITAL EMISSIONS						
15.107	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.107 limits	LINE CONDUCTED	PASS	Part 15B Test Report
15.109	RSS-Gen [7.2.3.2]	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.109 limits	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS	Part 15B Test Report

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 10 of 39	

6.2 6dB Bandwidth Measurement – 802.11a/n §15.247(a)(2); RSS-210 [A8.2]

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. **The minimum permissible 6dB bandwidth is 500 kHz.**

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
5745	149	a	6	16.48	0.500	Pass
5785	157	a	6	16.48	0.500	Pass
5825	165	a	6	16.44	0.500	Pass
5745	149	n (20MHz)	6.5/7.2 (MCS0)	17.70	0.500	Pass
5785	157	n (20MHz)	6.5/7.2 (MCS0)	17.76	0.500	Pass
5825	165	n (20MHz)	6.5/7.2 (MCS0)	17.75	0.500	Pass
5755	151	n (40MHz)	13/15 (MCS0)	36.32	0.500	Pass
5775	155	n (40MHz)	13/15 (MCS0)	36.08	0.500	Pass
5815	163	n (40MHz)	13/15 (MCS0)	36.17	0.500	Pass

Table 6-2. Conducted Bandwidth Measurements








Figure 6-1. Test Instrument & Measurement Setup

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 11 of 39	




Plot 6-1. 6dB Bandwidth Plot (802.11a – Ch. 149)




Plot 6-2. 6dB Bandwidth Plot (802.11a – Ch. 157)

FCC ID: IHDP56MB4	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 12 of 39




Plot 6-3. 6dB Bandwidth Plot (802.11a – Ch. 165)




Plot 6-4. 6dB Bandwidth Plot (802.11n (5.8GHz – 20MHz BW) – Ch. 149)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 13 of 39




Plot 6-5. 6dB Bandwidth Plot (802.11n (5.8GHz – 20MHz BW) – Ch. 157)




Plot 6-6. 6dB Bandwidth Plot (802.11n (5.8GHz – 20MHz BW) – Ch. 165)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 14 of 39




Plot 6-7. 6dB Bandwidth Plot (802.11n (5.8GHz – 40MHz BW) – Ch. 151)



Plot 6-8. 6dB Bandwidth Plot (802.11n (5.8GHz – 40MHz BW) – Ch. 155)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 15 of 39



Plot 6-9. 6dB Bandwidth Plot (802.11n (5.8GHz – 40MHz BW) – Ch. 163)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 16 of 39

6.3 Output Power Measurement – 802.11a/n (5GHz)

§15.247(b)(3); RSS-210 [A8.4]

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average power measurements while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible conducted output power is 1 Watt.**

Mode	Freq [MHz]	Channel	Detector	802.11a (20MHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6	9	12	18	24	36	48	54
802.11a	5745	149	AVG	14.27	14.29	12.90	12.84	12.69	12.98	12.01	12.19
			PEAK	18.57	18.84	18.05	18.31	18.21	18.19	17.89	17.99
802.11a	5765	153	AVG	14.21	14.19	12.78	12.72	12.57	12.86	11.86	12.06
			PEAK	18.51	18.76	17.96	18.23	18.13	18.11	17.80	17.92
802.11a	5785	157	AVG	14.06	14.09	12.64	12.57	12.48	12.72	11.71	11.91
			PEAK	18.40	18.67	17.85	18.11	18.03	17.99	17.68	17.80
802.11a	5805	161	AVG	13.16	13.15	12.51	12.43	12.29	12.23	11.55	11.76
			PEAK	18.05	18.36	17.74	17.97	17.87	17.83	17.54	17.66
802.11a	5825	165	AVG	12.98	13.01	12.22	12.18	12.11	12.37	11.34	11.53
			PEAK	17.88	17.75	17.81	17.79	17.72	17.69	17.37	17.47


Table 6-3. 802.11a (20MHz BW) Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	802.11n (20MHz - 800ns) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2
802.11n	5745	149	AVG	14.31	14.39	12.71	12.91	12.83	12.79	11.92	12.09
			PEAK	18.68	18.51	18.40	18.23	18.14	18.13	17.78	18.10
802.11n	5765	153	AVG	14.12	14.06	12.57	12.77	12.71	12.53	11.81	11.94
			PEAK	18.55	18.32	18.29	18.14	18.05	18.06	17.72	18.05
802.11n	5785	157	AVG	14.17	14.13	12.64	12.73	12.69	12.49	11.81	11.94
			PEAK	18.58	18.56	18.34	18.07	18.01	18.06	17.71	18.05
802.11n	5805	161	AVG	13.15	13.28	12.17	12.44	12.37	12.22	11.51	11.66
			PEAK	18.14	17.99	18.02	17.89	17.81	17.79	17.46	17.83
802.11n	5825	165	AVG	12.97	13.02	12.10	12.29	12.24	12.04	11.34	11.39
			PEAK	17.98	17.8	17.92	17.75	17.66	17.68	17.32	17.60

Table 6-4. 802.11n (20MHz BW – 800ns) Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	802.11n (20MHz - 400ns) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2
802.11n	5745	149	AVG	14.16	14.21	12.94	12.71	12.72	12.66	11.81	12.21
			PEAK	18.27	18.29	17.70	17.76	17.62	17.70	17.18	17.16
802.11n	5765	153	AVG	14.06	14.17	12.82	12.61	12.53	12.67	11.68	12.09
			PEAK	18.23	18.22	17.59	17.64	17.51	17.58	16.99	17.12
802.11n	5785	157	AVG	13.98	14.08	12.83	12.51	12.45	12.36	11.49	11.91
			PEAK	18.11	18.14	17.51	17.52	17.41	17.39	16.85	16.88
802.11n	5805	161	AVG	13.06	13.10	12.28	12.37	12.31	12.33	11.34	11.79
			PEAK	17.69	17.69	17.39	17.34	17.23	17.36	16.75	16.78
802.11n	5825	165	AVG	12.89	12.98	12.34	12.10	12.17	12.13	11.29	11.60
			PEAK	17.56	17.61	17.14	17.18	17.18	17.26	16.62	16.59

Table 6-5. 802.11n (20MHz BW – 400ns) Conducted Output Power Measurements

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 17 of 39

Mode	Freq [MHz]	Channel	Detector	802.11n (40MHz - 400ns) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2
802.11n	5755	151	AVG	12.01	12.03	12.07	12.02	11.93	11.89	12.04	11.97
			PEAK	17.44	17.48	17.51	17.49	17.41	17.41	17.36	17.32
802.11n	5775	155	AVG	12.21	12.22	12.23	12.15	12.12	12.14	12.17	12.04
			PEAK	17.41	17.49	17.31	17.46	17.42	17.32	17.33	17.17
802.11n	5795	159	AVG	12.11	12.17	12.19	12.16	12.08	12.06	12.14	11.99
			PEAK	17.1	17.37	17.26	17.29	17.29	17.21	17.25	17.06
802.11n	5815	163	AVG	11.63	11.57	11.61	11.52	11.47	11.45	11.59	11.51
			PEAK	17.04	17.11	17.19	17.09	17.05	17.01	16.92	16.91

Table 6-6. 802.11n (40MHz BW – 800ns) Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	802.11n (40MHz - 800ns) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2
802.11n	5755	151	AVG	12.03	12.09	12.07	11.99	11.94	11.89	12.08	11.92
			PEAK	17.40	17.38	17.51	17.37	17.57	17.31	17.42	17.49
802.11n	5775	155	AVG	12.19	12.16	12.21	12.18	12.11	12.14	12.13	12.09
			PEAK	17.39	17.54	17.29	17.32	17.28	17.31	17.29	17.22
802.11n	5795	159	AVG	12.09	12.11	12.17	12.19	12.07	12.08	12.13	12.04
			PEAK	17.08	17.31	17.24	17.23	17.15	17.19	17.21	17.11
802.11n	5815	163	AVG	11.57	11.61	11.56	11.49	11.48	11.52	11.61	11.47
			PEAK	16.98	17.08	17.18	16.98	17.19	17.12	16.93	16.93

Table 6-7. 802.11n (40MHz BW – 400ns) Conducted Output Power Measurements






Figure 6-2. Test Instrument & Measurement Setup

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 18 of 39	

6.4 Power Spectral Density (802.11a/n) §15.247(e); RSS-210 [A8.2]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible power spectral density is 8 dBm in any 3 kHz band.**

Per the guidance on power spectral density measurements given in KDB 558074, the spectrum is measured with a 100kHz bandwidth using a peak detector. The measured spectrum is compared to the 8dBm/3kHz limit given in 15.247(e) by applying a bandwidth correction factor equal to $10\log(3\text{kHz}/100\text{kHz}) = -15.23\text{dB}$.

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Spectral Density [dBm]	Bandwidth Correction Factor [dB]	Corrected Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
5745	149	a	6	-0.222	-15.23	-15.451	8.0	-23.45
5785	157	a	6	-0.660	-15.23	-15.889	8.0	-23.89
5825	165	a	6	-1.932	-15.23	-17.161	8.0	-25.16
5745	149	n (20MHz)	6.5/7.2 (MCS0)	-0.114	-15.23	-15.343	8.0	-23.34
5785	157	n (20MHz)	6.5/7.2 (MCS0)	-0.600	-15.23	-15.829	8.0	-23.83
5825	165	n (20MHz)	6.5/7.2 (MCS0)	-1.758	-15.23	-16.987	8.0	-24.99
5755	151	n (40MHz)	13/15 (MCS0)	-1.912	-15.23	-17.141	8.0	-25.14
5775	155	n (40MHz)	13/15 (MCS0)	-1.670	-15.23	-16.899	8.0	-24.90
5815	163	n (40MHz)	13/15 (MCS0)	-2.436	-15.23	-17.665	8.0	-25.66

Table 6-8. Conducted Power Density Measurements








Figure 6-3. Test Instrument & Measurement Setup



FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 19 of 39	




Plot 6-10. Power Spectral Density Plot (802.11a – Ch. 149)




Plot 6-11. Power Spectral Density Plot (802.11a – Ch. 157)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 20 of 39




Plot 6-14. Power Spectral Density Plot (802.11n (5.8GHz – 20MHz BW) – Ch. 157)




Plot 6-15. Power Spectral Density Plot (802.11n (5.8GHz – 20MHz BW) – Ch. 165)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 22 of 39




Plot 6-16. Power Spectral Density Plot (802.11n (5.8GHz – 40MHz BW) – Ch. 151)





Plot 6-17. Power Spectral Density Plot (802.11n (5.8GHz – 40MHz BW) – Ch. 155)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 23 of 39



Plot 6-18. Power Spectral Density Plot (802.11n (5.8GHz – 40MHz BW) – Ch. 163)


FCC ID: IHDP56MB4	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 24 of 39	

6.5 Conducted Emissions at the Band Edge

§15.247(d); RSS-210 [A8.5]

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate of 6 Mbps for “a” mode, and 6.5/7.2Mbps for “n” mode. These settings produced the worst-case emissions.

Per the guidance of KDB 558074, section 5.4.1.1, the reference level of 20dBc for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in Section 6.6.




Plot 6-19. Band Edge Plot (802.11a – Ch. 149)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 25 of 39




Plot 6-20. Band Edge Plot (802.11a – Ch. 165)




Plot 6-21. Band Edge Plot (802.11n (5.8GHz – 20MHz) – Ch. 149)

FCC ID: IHDP56MB4	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 26 of 39




Plot 6-22. Band Edge Plot (802.11n (5.8GHz – 20MHz) – Ch. 165)



Plot 6-23. Band Edge Plot (802.11n (5.8GHz – 40MHz) – Ch. 151)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 27 of 39



6-24. Band Edge Plot (802.11n (5.8GHz – 40MHz) – Ch. 163)

FCC ID: IHDP56MB4	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 28 of 39

6.6 Conducted Spurious Emissions

§15.247(d); RSS-210 [A8.5]


For the following out of band conducted spurious emissions plots, the EUT was investigated in all available data rates for “a”, and “n” modes. The worst case spurious emissions for the 5.8GHz band were found while transmitting in “a” mode at 6 Mbps and are shown in the plots below.


The limit shown in the following table denotes the limit at 20dB below the fundamental emission level measured in section 6.4. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

Channel	Range	Frequency [MHz]	Peak Amplitude	Limit [dBm]	Margin
149	30 MHz - 20 GHz	15501	-33.46	-20.22	-13.24
	20 GHz - 40 GHz	37507	-38.60	-20.22	-18.38
157	30 MHz - 20 GHz	14961	-33.52	-20.66	-12.86
	20 GHz - 40 GHz	37735	-38.69	-20.66	-18.03
165	30 MHz - 20 GHz	14877	-33.84	-21.93	-11.91
	20 GHz - 40 GHz	38199	-38.32	-21.93	-16.39


Table 6-9. Conducted Spurious Emissions data

Note: Data was taken using the PSA spectrum analyzer with the following settings: RBW = 1MHz, VBW = 3MHz. 81,922 sweep points from 30MHz to 40GHz were used to ensure compliance.



FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 29 of 39	




Plot 6-25. Conducted Spurious Plot (802.11a – Ch. 149)




Plot 6-26. Conducted Spurious Plot (802.11a – Ch. 149)



FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 30 of 39	




Plot 6-27. Conducted Spurious Plot (802.11a – Ch. 157)




Plot 6-28. Conducted Spurious Plot (802.11a – Ch. 157)



FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 31 of 39	



Plot 6-29. Conducted Spurious Plot (802.11a – Ch. 165)



Plot 6-30. Conducted Spurious Plot (802.11a – Ch. 165)

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 32 of 39	

6.7 Radiated Spurious Emission Measurements

§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]

The EUT was tested from 9kHz up to the tenth harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-10 per Section 15.209.



All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section. All measurements shown in this section were obtained using traditional radiated test methods. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 were not used to evaluate this device.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-10. Radiated Limits

Sample Calculation

- Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] – Limit [$\text{dB}_{\mu\text{V/m}}$]

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 33 of 39	

Radiated Spurious Emission Measurements (Cont'd)
§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]



Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meter
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
11490.00	-112.79	Avg	H	46.63	40.8	53.98	-13.15
11490.00	-100.48	Peak	H	46.63	53.1	73.98	-20.84
22980.00	-135.00	Avg	H	42.61	14.6	53.98	-39.37
22980.00	-125.00	Peak	H	42.61	24.6	73.98	-49.37

Table 6-11. Radiated Measurements @ 3 meter

NOTES:

- All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-10.
- Average measurements > 1GHz are performed using RBW = 1MHz and VBW = 10Hz. Peak measurements > 1GHz are performed using RBW = 1MHz, VBW = 3MHz.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500 µV/m (54dBµ/m) at 3 meters radiated.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 34 of 39	

Radiated Spurious Emission Measurements (Cont'd)
§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]


Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 3 Meter
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
11570.00	-112.00	Avg	H	46.79	41.8	53.98	-12.19
11570.00	-100.36	Peak	H	46.79	53.4	73.98	-20.55

Table 6-12. Radiated Measurements @ 3 meter

NOTES:

- All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-10.
- Average measurements > 1GHz are performed using RBW = 1MHz and VBW = 10Hz. Peak measurements > 1GHz are performed using RBW = 1MHz, VBW = 3MHz.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 35 of 39	

6.8 Radiated Spurious Emission Measurements

§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meter

Operating Frequency: 5825MHz



Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
11650.00	-111.96	Avg	H	46.89	41.9	53.98	-12.04
11650.00	-99.87	Peak	H	46.89	54.0	73.98	-19.95

Table 6-13. Radiated Measurements @ 3 meter


NOTES:

- All emissions shown lie in the restricted bands specified in §15.205 are below the limit shown in Table 6-10.
- Average measurements > 1GHz are performed using RBW = 1MHz and VBW = 10Hz. Peak measurements > 1GHz are performed using RBW = 1MHz, VBW = 3MHz.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset	Page 36 of 39	

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



— FCC Part 15 Class B Voltage on Mains QP.LimitLine
 — FCC Part 15 Class B Voltage on Mains AV.LimitLine
 — Preview Result 1-PK+
▼ Final Result 1-QPK
 ◆ Final Result 2-AVG

Plot 6-31. Line Conducted Plot with 802.11a

Frequency MHz	Line	Bandwidth kHz	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
2.121	L1	9	38.30	56.00	17.70	26.90	46.00	19.10
2.240	L1	9	37.40	56.00	18.60	26.00	46.00	20.00
2.279	L1	9	38.50	56.00	17.50	25.30	46.00	20.70
2.679	L1	9	38.90	56.00	17.10	26.90	46.00	19.10
2.841	L1	9	38.60	56.00	17.40	25.70	46.00	20.30
4.643	L1	9	35.90	56.00	20.10	24.40	46.00	21.60
4.684	L1	9	33.80	56.00	22.20	24.10	46.00	21.90
4.805	L1	9	35.70	56.00	20.30	25.40	46.00	20.60
4.819	L1	9	37.40	56.00	18.60	26.00	46.00	20.00
4.859	L1	9	36.70	56.00	19.30	25.60	46.00	20.40

Table 6-14. Line Conducted Data with 802.11a


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 1Mbps on Channel 6. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Line L1 = Phase; Line N = Neutral
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Level (dBµV) – Limit (dBµV)
- Traces shown in plot are made using a peak detector.

FCC ID: IHDP56MB4	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 37 of 39

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



— FCC Part 15 Class B Voltage on Mains QP.LimitLine — FCC Part 15 Class B Voltage on Mains AV.LimitLine — Preview Result 1-PK+
▼ Final Result 1-QPK ◆ Final Result 2-AVG

Plot 6-32. Line Conducted Plot with 802.11a

Frequency MHz	Line	Bandwidth kHz	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.521	N	9	41.40	56.00	14.60	33.20	46.00	12.80
2.445	N	9	42.10	56.00	13.90	28.00	46.00	18.00
2.564	N	9	41.30	56.00	14.70	28.00	46.00	18.00
4.619	N	9	42.20	56.00	13.80	29.70	46.00	16.30
4.657	N	9	42.40	56.00	13.60	29.60	46.00	16.40
4.740	N	9	42.40	56.00	13.60	29.30	46.00	16.70
4.778	N	9	41.80	56.00	14.20	29.60	46.00	16.40
4.979	N	9	42.40	56.00	13.60	29.40	46.00	16.60
5.901	N	9	43.40	60.00	16.60	30.50	50.00	19.50
6.061	N	9	43.50	60.00	16.50	29.20	50.00	20.80

Table 6-15. Line Conducted Data with 802.11a



Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 1Mbps on Channel 6. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Line L1 = Phase; Line N = Neutral
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Level (dBµV) – Limit (dBµV)
- Traces shown in plot are made using a peak detector.

FCC ID: IHDP56MB4	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 38 of 39

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Motorola Portable Handset FCC ID: IHDP56MB4** is in compliance with Part 15C of the FCC Rules and RSS-210 of the Industry Canada Rules.

FCC ID: IHDP56MB4		FCC Pt. 15.247 802.11a/n MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1203200316.IHD	Test Dates: 03/21/12 - 05/17/2012	EUT Type: Portable Handset		Page 39 of 39