



849 NW State Road 45
Newberry, Fl 32669 USA
Phone: 888.472.2424 or 352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

**COMPLIANCE TEST REPORT
PER FCC PT 15 B CLASS B
AND ICES-003**

Applicant	MOTOROLA MOBILITY, INC.
Address	600 NORTH U.S. HWY 45 LIBERTYVILLE ILLINOIS 60048-5343 USA
FCC ID	IHDP56MS1
IC CERTIFICATION	1090-P56MS1
Model Number	H2021B51014A
Product Description	i867 iDEN PHONE
Date Sample Received	10/10/2011
Date Tested	10/28/2011
Tested By	John A. Day
Approved By	Mario R. de Aranzeta
Report Number	2331ET11TestReport i867 iDEN 15B.doc
Test Results	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate # 0955-01



TABLE OF CONTENTS

ATTESTATIONS.....	3
REPORT SUMMARY	4
TEST ENVIRONMENT	4
TEST SETUP SUMMARY	4
SUPPORTING PERIPHERAL EQUIPMENT	4
DUT SPECIFICATION.....	5
TEST EQUIPMENT LIST.....	6
TEST PROCEDURES.....	7
RADIATED SPURIOUS EMISSIONS	8
RADIATED EMISSIONS TEST SET UP PHOTO	10
DECLARATION OF CONFORMITY INFORMATION	11
MOTOROLA MOBILITY, INC.	12
DECLARATION OF CONFORMITY (SAMPLE ONLY)	12

ATTESTATIONS

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669

Authorized Signatory Name:



Handwritten signature in blue ink over a circular stamp.

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: 10/27/2011



REPORT SUMMARY

Disclaimer	The test results relate only to the items tested.
Purpose of Test	To demonstrate compliance with FCC CFR 47, Part 15.109 requirements. To demonstrate compliance with IC ICES-003 requirements.
Test Standards	Pt 15.109, Pt 15.107, ANSI C63.4: 2003, ICES-003

TEST ENVIRONMENT

Test Facility	Timco Engineering, Inc. 849 NW State Road 45 Newberry, FL 32669 USA.
Test Condition in the laboratory	Temperature: 26°C Relative humidity: 50%

TEST SETUP SUMMARY

Test Setup Diagram/Description	The DUT was placed on the turntable per setup per ANSI C63.4: 2003. A test set up photo is provided for clarification.
Deviation from the standard/procedure	No deviation
Modification of DUT	No modification

SUPPORTING PERIPHERAL EQUIPMENT

Mfg	Description	Model Number	Serial Number	Cable
Dell	Laptop	P1A	N/A	Shielded

DUT SPECIFICATION

DUT Description	i867 iDEN TX
FCC ID	IHDP56MS1
IC CERTIFICATION	1090-P56MS1
Model Number	H2021B51014A
Serial Number	364BMS008N
Hardware	PL-1
Software	DD8.00.13
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz
	<input type="checkbox"/> DC Power
	<input checked="" type="checkbox"/> Battery Operated
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed
	<input type="checkbox"/> Mobile
	<input checked="" type="checkbox"/> Portable



TEST EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 5/10/10	5/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 6/12/11	6/12/13
Antenna: Active Loop	ETS-Lindgren	6502	00062529	CAL 9/23/10	9/23/12
Antenna: Passive Loop	EMC Test Systems	EMCO 6512	9706-1211	CAL. 10/1/09	10/2/11
Frequency Counter	HP	5385A	2730A03025	CAL 8/17/11	8/17/13
Hygro- Thermometer	Extech	445703	0602	CAL 6/15/11	6/15/13
Modulation Analyzer	HP	8901A	3435A06868	CAL 7/18/11	7/18/13
Digital Multimeter	Fluke	FLUKE-77	35053830	CAL 9/9/11	9/9/13
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi- Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12
Antenna	ETS	3117	41534	9/22/2010	9/22/2012
Antenna	Electro metrics	LPA-25	1122	5/04/2011	5/04/2013
Antenna	Electro metrics	BIA-25	1171	1/15/2010	1/15/2012

APPLICANT: MOTOROLA MOBILITY, INC.

FCC ID: IHDP56MS1 IC: 1090-P56MS1

Z:\M\MOTOROLA IL LL\2331ET11\2331ET11TestReport i867 iDEN 15B.doc

Page 6 of 12



TEST PROCEDURES

Power line conducted Emission: The test procedure used was ANSI C63.4-2003. The spectrum was scanned from 0.15 to 30 MHz.

Radiation Interference: The test procedure used was ANSI C63.4-2003 using a spectrum analyzer with preselector. The resolution bandwidth used was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The video bandwidth was always greater than or equal to the RBW.

The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The frequency was scanned from 30 MHz to 1.0 GHz. The DUT was measured in three (3) orthogonal planes when necessary.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBμV) to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dBμV	+ 10.36 dB/m	+0.40 dB	=30.76 dBμV/m @ 3m



RADIATED SPURIOUS EMISSIONS

Rules Part No.: 15.109

Requirements:

Frequency MHz	Limits
30 – 88	40.0 dB μ V/m measured @ 3 meters
88 – 216	43.5 dB μ V/m measured @ 3 meters
216 – 960	46.0 dB μ V/m measured @ 3 meters
Above 960	54.0 dB μ V/m measured @ 3 meters

Test Configuration:

Connected to computer, Berbug mode, SIM EMI Command, SKN6278A (micro USB data cable), battery

NOTE DUT emissions measured from 30 MHz to 5 GHz

Test Data:

Emission Frequency MHz	Meter Reading dB μ V	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
35.89	1.7	H	0.43	11.29	13.42	26.58
35.89	8.1	V	0.43	11.29	19.82	20.18
51.75	1.6	H	0.51	10.94	13.05	26.95
51.75	8.3	V	0.51	10.94	19.75	20.25
65.01	14.0	V	0.55	9.90	24.45	15.55
65.01	17.0	H	0.55	9.90	27.45	12.55
80.38	5.6	H	0.60	6.35	12.55	27.45
80.38	9.5	V	0.60	6.35	16.45	23.55
85.79	7.1	H	0.61	7.09	14.80	25.20
85.79	12.4	V	0.61	7.09	20.10	19.90
105.45	6.9	H	0.66	11.73	19.29	24.21
105.45	8.9	V	0.66	11.73	21.29	22.21
121.66	7.0	V	0.67	13.10	20.77	22.73
121.66	8.5	H	0.67	13.10	22.27	21.23
133.10	17.4	V	0.68	12.90	30.98	12.52
133.10	22.3	H	0.68	12.90	35.88	7.62
144.08	7.3	V	0.69	13.41	21.40	22.10
144.08	7.9	H	0.69	13.41	22.00	21.50
159.97	5.4	V	0.74	13.90	20.04	23.46
159.97	6.3	H	0.74	13.90	20.94	22.56
193.28	9.3	V	0.87	17.23	27.40	16.10
193.28	10.0	H	0.87	17.23	28.10	15.40

APPLICANT: MOTOROLA MOBILITY, INC.

FCC ID: IHDP56MS1 IC: 1090-P56MS1

Z:\M\MOTOROLA IL LL\2331ET11\2331ET11TestReport i867 iDEN 15B.doc

TEST DATA CONT'D.

Emission Frequency MHz	Meter Reading dBμV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
214.86	16.9	V	0.93	11.91	29.74	13.76
214.86	19.4	H	0.93	11.91	32.24	11.26
221.72	25.1	V	0.94	11.68	37.72	8.28
221.72	28.1	H	0.94	11.68	40.72	5.28
333.03	14.0	V	1.13	14.65	29.78	16.22
333.03	20.0	H	1.13	14.65	35.78	10.22
398.94	21.2	V	1.20	16.28	38.68	7.32
398.94	24.3	H	1.20	16.28	41.78	4.22
455.07	21.1	V	1.26	17.55	39.91	6.09
531.62	11.2	V	1.39	18.62	31.21	14.79
531.62	12.3	H	1.39	18.62	32.31	13.69
930.00	9.0	V	2.00	24.00	35.00	11.01
930.00	12.4	H	2.00	24.00	38.40	7.61
1,461.40	6.3	H	2.47	28.05	36.82	17.18
1,461.40	6.5	V	2.47	28.05	37.02	16.98
4,825.70	-6.5	V	4.91	33.97	32.38	21.62
4,825.70	-6.2	H	4.91	33.97	32.68	21.32

APPLICANT: MOTOROLA MOBILITY, INC.

FCC ID: IHDP56MS1 IC: 1090-P56MS1

Z:\M\MOTOROLA IL LL\2331ET11\2331ET11TestReport i867 iDEN 15B.doc

RADIATED EMISSIONS TEST SET UP PHOTO





DECLARATION OF CONFORMITY INFORMATION

The following FCC rules are applicable to product subject to the declaration of conformity process:

§ 2.1077 Compliance information

(a) If a product must be tested and authorized under a Declaration of Conformity, a compliance information statement shall be supplied with the product at the time of marketing or importation, containing the following information:

(1) Identification of the product, e.g., name and model number;

(2) A statement, similar to that contained in §15.19(a)(3) of this chapter, that the product complies with part 15 of this chapters; and

(3) The identification, by name, address and telephone number, of the responsible party, as defined in §2.909. The responsible party for a Declaration of Conformity must be located within the United States.

...

(c) The compliance information statement shall be included in the user's manual or as a separate sheet.

§ 2.909 Responsible party

...

(c) In the case of equipment subject to authorization under the Declaration of Conformity procedure:

(1) The manufacturer or, if the equipment is assembled from individual component parts and the resulting system is subject to authorization under a Declaration of Conformity, the assembler.

(2) If the equipment, by itself, is subject to a Declaration of Conformity and that equipment is imported, the importer.

(3) Retailers or original equipment manufacturers may enter into an agreement with the responsible party designated in paragraph (c)(1) or (c)(2) of this section to assume the responsibilities to ensure compliance of equipment and become the new responsible party.

(4) If the radio frequency equipment is modified by any party not working under the authority of the responsible party, the party performing the modifications, if located within the U.S., or the importer, if the equipment is imported subsequent to the modifications, becomes the new responsible party.

...

Please find on the following page, a sample compliance information statement:

APPLICANT: MOTOROLA MOBILITY, INC.

FCC ID: IHDP56MS1 IC: 1090-P56MS1

Z:\M\MOTOROLA IL LL\2331ET11\2331ET11TestReport i867 iDEN 15B.doc

Page 11 of 12

MOTOROLA MOBILITY, INC.
DECLARATION OF CONFORMITY (SAMPLE ONLY)

The responsible party declares that this device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Responsible Party:	MOTOROLA MOBILITY, INC.
Address:	600 NORTH U.S. HWY 45 LIBERTYVILLE ILLINOIS 60048-5343 USA
Tel:	
Fax:	
Printed Name/Title:	
Signature:	
Product Description:	I867 iDEN ODM PHONE
Model Name:	H2011B51015A
Trade/Brand Name:	MOTOROLA
Applicant:	MOTOROLA MOBILITY, INC.
Address:	600 NORTH U.S. HWY 45 LIBERTYVILLE ILLINOIS 60048-5343 USA
Report Number:	2331ET11TestReport i867 iDEN 15B.doc
Date:	10/27/2011