MOTOROLA

Date: August 11, 2008

Subject: Request for additional information regarding FCC ID: IHDP6JF1

Reference:
Correspondence Reference Number: IHD80653
Confirmation Number: 807210653
Date of Original Email: August 1, 2008

Prepared by:
Andrew Bachler, Principal Staff Engineer
Motorola Mobile Device Business
Libertyville, Illinois 60048

Questions and responses follow:

1. The Developers Guide lists the incorrect FCC ID on Page viii "Host Label Requirement".

   Response: Please refer to the revised Developers Guide, exhibit 8.

2. Developers Guide Page x lists the antenna gain at maximum of 6dBi and that the output power must not exceed 1 Watt. Please correct this paragraph to list the maximum antenna gain at 3dBi as tested.

   Response: Please refer to the revised Developers Guide, exhibit 8.

3. Page 31 of the Developers Guide "Antenna Interface" or Page x must provide information on the exact antenna that was tested and approved with the device. A statement that antennas of the same type with equal or lesser gain is acceptable.

   Response: Please refer to the revised Developers Guide, exhibit 8.

4. Page 1 and 2 of the Developers Guide describes a stacked configuration with another transmitter module. Please note that the grant for this device will include a note that this module may not be co-located or operate in conjunction with other transmitters. Any co-location condition would require a separate approval.

The Developers Guide should instruct the integrator or installer of this condition during installation.

Response: Please refer to the revised Developers Guide, exhibit 8.

5. Modular Approval Letter item iv must be updated to list the antenna approved with the unit.

   Response: The module was tested with a 3dBi antenna. Please refer to the revised Modular Approval Letter.

6. The Modular Approval Letter states that the device is DC powered and therefore conducted emissions was not performed. Please note that FCC Part 15.207 states that compliance with the conducted limits must be shown even if the device obtains it's power through another device connected to the AC mains. Please provide AC power line conducted emissions test data.

   Response: Please refer to the revised test report (submitted on 7-21-08).

7. MPE report uses a combined cable loss and antenna gain of 7.9dBi. Please update the MPE report using the maximum approved antenna gain of 3dBi antenna.

   Response: Please refer to the revised rf exposure report (submitted on 7-21-08).