

# Specification Description

## Motorola H780

|                                   |  |                                |
|-----------------------------------|--|--------------------------------|
| Frequency                         | CE   | From 2400 to 2483.5 MHz        |
|                                   | FCC  | From 2400 to 2483.5 MHz        |
| Type of modulation                | 2 GFSK ,BT:0.5, Modulation index:0.28~0.35 |                                |
| Number of Channels                | CE   | 79(f=2402+kMHz, k=0,1,2...,78) |
|                                   | FCC  | 79(f=2402+kMHz, k=0,1,2...,78) |
| Carrier Frequency of each channel | 79 (f=2402+kMHz, k=0,1,2...,78)            |                                |
| Bandwith of each channel          | 1MHz                                       |                                |
| IF & LO Frequency                 |  |                                |
| Transmitter or Transceiver        | 0dBm(Class 2)                              |                                |
| Rating of Power                   | +3.7V                                      |                                |
| Maximum Output Power to Antenna   | 0dBm                                       |                                |
| Duty Cycle                        | N/A  |                                |
| Basic Function of Product         | 1.Audio Gateway                            |                                |
|                                   | 2.Bluetooth Series Port                    |                                |
|                                   | 3.Dial-up Networking                       |                                |
|                                   | 4.Network Access                           |                                |
|                                   | 5.PIM Item Transfer                        |                                |
|                                   | 6.Fax                                      |                                |
|                                   | 7.File Transfer                            |                                |
|                                   | 8.PIM Synchronization                      |                                |
|                                   | 9.Handset                                  |                                |
| Operation                         | -10~60°C                                   |                                |
| Antenna Connector Type            | No Antenna Connector                       |                                |
| Connetctor Type                   | USB  |                                |
| Antenna Type                      | On-Boars Printed Antenna                   |                                |
| Antenna Gain                      | 0dBi                                       |                                |