

**SUBMITTED MEASURED DATA INDEX**

RF Power Output .....6A  
Audio Response .....6B  
Post Limiter Low Pass Filter Response - Graph .....6C  
Signaling Channel Audio Roll-Off Filter Response - Graph.....6D  
Modulation Limiting (Compressor In) - Graph.....6E1  
Modulation Limiting (Compressor Out) - Graph.....6E2  
Occupied Bandwidth, Audio - Photograph .....6F1  
Occupied Bandwidth, Audio and SAT - Graph .....6F2  
Occupied Bandwidth, Wideband Data - Graph .....6F3  
Occupied Bandwidth, Signaling Tone and SAT - Graph.....6F4  
Occupied Bandwidth, 1900 MHz Digital - Graph .....6F5  
Occupied Bandwidth, 800 MHz Digital - Graph .....6F6  
Analog Conducted Spurious and Harmonic Emissions - Graph .....6G1  
Digital Conducted Spurious and Harmonic Emissions, 1900 MHz - Graph.....6G2  
Digital Conducted Spurious and Harmonic Emissions, 800 MHz- Graph.....6G3  
Analog Radiated Spurious and Harmonic Emissions - Graph .....6H1  
Digital Radiated Spurious and Harmonic Emissions, 1900 MHz - Graph.....6H2  
Digital Radiated Spurious and Harmonic Emissions, 800 MHz - Graph.....6H3  
Analog Frequency Change vs. Temperature .....6J1  
Digital Frequency Change vs. Temperature, 1900 MHz.....6J2  
Digital Frequency Change vs. Temperature, 800 MHz.....6J3  
Analog Frequency Change vs. Supply Voltage .....6K1  
Digital Frequency Change vs. Supply Voltage, 1900 MHz .....6K2  
Digital Frequency Change vs. Supply Voltage, 800 MHz .....6K3  
Measurement Techniques .....6L

**RF POWER OUTPUT DATA**

The input supply to the transmitter was set at 3.5 Volts. The RF power output was measured with the indicated voltage and current applied into the final RF amplifying device(s).

**ANALOG MODE**

Measured RF output: 0.548W  
Measured DC voltage: 3.5V  
Measured DC current: 490mA  
Measured RF input: 2.24mW

**800 Mhz Digital CDMA**

In Digital Mode the values measured for RF Output, DC Current and RF Input Power are all average values which reflect a 100% transmit duty cycle in CDMA operation.

Measured RF output: 0.264 W  
Measured DC voltage: 3.5V  
Measured DC current: 470mA.  
Measured RF input: 1.26mW

**1900 Mhz Digital CDMA**

In Digital Mode the values measured for RF Output, DC Current and RF Input Power are all average values which reflect a 100% transmit duty cycle in CDMA operation.

Measured RF output: 0.252 W  
Measured DC voltage: 3.5V  
Measured DC current: 580mA.  
Measured RF input: 2.82mW

**EFFECTIVE RADIATED POWER**


Since the unit is intended for use with a provided antenna (and “non standard” RF connector), ERP/ERIP is measured. The dipole antenna substitution method was used. The result indicated is the maximum ERP (800 MHz band) and EIRP (PCS band) found over the channels and radio orientations tested.

Maximum Effective Radiated Power: Analog Mode 25.48 dBm (0.353 W)


Maximum Effective Radiated Power: 800 Digital CDMA Mode 24.58 dBm (0.287 W)

Maximum Effective Isotropic Radiated Power: 1900 Digital CDMA Mode 27.36 dBm (0.545 W)


**Audio Frequency Response**




**Post Limiter Low Pass Filter Response Graph**




**Signaling Channel Audio Roll-Off Filter Response Graph**



Modulation Limiting (Componder In)



Modulation Limiting (Componder out)




**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F8W**  
 DEVIATION OF THE CARRIER WITH 2500 Hz. AUDIO MODULATION

HORIZONTAL SCALE = 20 kHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 24.2 dBm)  
 RESOLUTION BANDWIDTH = 300 Hz  
 VIDEO BANDWIDTH = 300 Hz  
 AUDIO LEVEL = 16 dB GREATER THAN LEVEL REQUIRED TO PRODUCE +/- 6 kHz  
 POWER LEVEL = 0.532 W

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with the 2500 Hz. Tone, 16 dB greater than that required to produce +/- 6 kHz modulation. Photograph the sideband display while it is superimposed upon the unmodulated carrier.




SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or 63 + 10 log<sub>10</sub> (mean output power in Watts) dB, whichever is the smaller attenuation.

**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F8W**  
**DEVIATION OF THE CARRIER WITH 2500 Hz AUDIO MODULATION AND SUPERVISORY AUDIO TONE**

HORIZONTAL SCALE = 20 kHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 24.2 dBm)  
 RESOLUTION BANDWIDTH = 300 Hz  
 VIDEO BANDWIDTH = 300 Hz

MEASURED DATA:



1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain the unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with 2500 Hz tone, 16 dB greater than that required to produce +/- 6kHz of deviation and add SAT with +/- 2kHz of deviation. Photograph the sideband display while it is superimposed upon the unmodulated carrier.

SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or  $63 + 10 \log_{10}$  (mean output power in Watts) dB, whichever is the smaller attenuation.

**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F1D**

DEVIATION OF THE CARRIER WITH WIDE BAND DATA

HORIZONTAL SCALE = 20 kHz / DIVISION

VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 24.2 dBm)


RESOLUTION BANDWIDTH = 300 Hz

VIDEO BANDWIDTH = 300 Hz

POWER LEVEL = 548.3 mW

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain the unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with wide band data with +/- 8 kHz. Photograph the sideband display while it is superimposed upon the unmodulated carrier.



SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90 kHz, the sideband is at least 45 dB below the carrier.
- c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or  $63 + 10 \log_{10}$  (mean output power in Watts) dB, whichever is the smaller attenuation.

**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F1D**

DEVIATION OF THE CARRIER WITH 10 kHz SIGNALING TONE AND SUPERVISORY AUDIO TONE

HORIZONTAL SCALE = 20 kHz / DIVISION

VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 24.2 dBm)


RESOLUTION BANDWIDTH = 300 Hz

VIDEO BANDWIDTH = 300 Hz

POWER LEVEL = 548.3 mW

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain the unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with signaling tone with +/- 8 kHz deviation and add SAT with +/- 2kHz of deviation. Photograph the sideband display while it is superimposed upon the unmodulated carrier.



SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90 kHz, the sideband is at least 45 dB below the carrier.
- c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or 63+10 log10 (mean output power in Watts) dB, whichever is the smaller attenuation.


**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F9W**

**DEVIATION OF THE CARRIER WITH OQPSK MODULATION**

HORIZONTAL SCALE = 1MHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (ATTENUATION)  
 RESOLUTION BANDWIDTH = 30 kHz  
 VIDEO BANDWIDTH = 100 Hz  
 POWER LEVEL = 251.8 mW (Average Power in transmitter)

**MEASURED DATA:**

1. Modulate the transmitter with OQPSK modulation, using pseudo random data. Obtain image on spectrum analyzer.




**COMMENTS:**

Modulation products in a bandwidth of 30 kHz ,centered +/- 1.25 MHz from the channel center frequency should be at least 45 dB and should be at least 42 dB below the mean output power level.

**ANALOG CONDUCTED SPURIOUS AND HARMONIC EMISSIONS - GRAPH**

Analog Transmitter Conducted Spurious Emissions

- \* Each reported emission reflects the highest absolute level found among all power levels, channels, power amplifier configurations tested.
- \* All emissions not reported are more than 20 dB below the FCC specification
- \* No signals greater than -80 dBm were found in the 869 to 894 MHz band
- \* Spectrum was searched from 30 kHz to the 10th Harmonic of the transmitter




**ANALOG CONDUCTED SPURIOUS AND HARMONIC EMISSIONS – GRAPH**

10: 46: 37 MAY 17, 2000

MARKER  
1.675 GHz  
-35.52 dBm

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 1.675 GHz  
-35.52 dBm

LOG REF 25.3 dBm



START 1.000 GHz

#IF BW 1.0 MHz

#AVG BW 1 MHz

STOP 2.900 GHz

SWP 38.0 msec



**1900 CDMA Digital Conducted Spurious and Harmonic Emissions**

Carrier Power: 208.45 mW


Carrier Frequency: 1888

\* Each reported emission reflects the highest absolute level found among all power levels, channels, power amplifier configurations tested.

\* All emissions not reported are more than 20 dB below the FCC specification  
Spectrum was searched from 30 kHz to the 10th Harmonic of the transmitter

10:20:55 MAY 17, 2000

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG




**1900 CDMA Digital Conducted Spurious and Harmonic Emissions**

10: 12: 02 MAY 17, 2000

MARKER  
1.888 GHz  
23.19 dBm


ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 1.888 GHz  
23.19 dBm



**1900 CDMA Digital Conducted Spurious and Harmonic Emissions**

10:17:18 MAY 17, 2000

ACTV DET: PEAK  
MEAS DET: PEAK GP AVG



**ANALOG RADIATED SPURIOUS AND HARMONIC EMISSIONS**


Carrier Power: 0.548 W to 4.8 mW in 4 dB steps.

Carrier Frequency: 824.04 to 848.97 MHz in 30 kHz steps


\* All emissions not reported are more than 20 dB below the FCC specification

\* No signals greater than -80 dBm were found in the 869 to 894 MHz band

Spectrum was searched from 30 kHz to the 10th Harmonic of the transmitter



**ANALOG RADIATED SPURIOUS AND HARMONIC EMISSIONS**




**1800 MHZ DIGITAL RADIATED SPURIOUS AND HARMONIC EMISSIONS**

Carrier Power: 251.8 mW


Carrier Frequency: 1850 to 1910 MHz in 50 kHz steps

\* All emissions not reported are more than 20 dB below the FCC specification


Spectrum was searched from 30 kHz to the 10th Harmonic of the transmitter




**1800 MHZ DIGITAL RADIATED SPURIOUS AND HARMONIC EMISSIONS**




**1800 MHZ DIGITAL RADIATED SPURIOUS AND HARMONIC EMISSIONS**




**800 CDMA RADIATED SPURIOUS AND HARMONIC EMISSIONS - GRAPH**




**800 CDMA RADIATED SPURIOUS AND HARMONIC EMISSIONS - GRAPH**




**Frequency Change vs. Temperature (Amps)-Graph**




**Frequency Change vs. Temperature (Digital 1900 CDMA)-Graph**




**Frequency Change vs. Temperature (Digital 800 CDMA)-Graph**




**Frequency Change vs. Supply Voltage (Amps)-Graph**



**Frequency Change vs. Supply Voltage (Digital Mode 1900)-Graph**



**Frequency Change vs. Supply Voltage (Digital Mode 800 Mhz)-Graph**



**MEASUREMENT TECHNIQUES****2.1051 Measurements Required:** Conducted Spurious and Harmonic Emissions at Antenna Terminals (Analog Mode)

Graph attached  
EXHIBIT 6G1

**Definition** - (as used herein) Spurious radiations are the radio frequency voltages or power generated within the equipment and appearing at the equipment's output terminals when properly loaded with its characteristic radiating antenna.

**Minimum standard** Conducted spurious and harmonic emissions shall be attenuated 43dB + 10 Log10(the mean power output). In the range of frequencies between 869.04MHz and 893.97MHz, and from 1930 MHz to 1990 MHz, no spur shall exceed -80dBm.

**Method of Measurement** The antenna port of the sample was directly coupled to the input of the EMI receiver through a special coupling cable. Scans were then performed from 30 MHz to 1 GHz, while observing the fundamental signal level, plus low order harmonics or other spurious signals. The frequency range of 1 to 2.9GHz was then inspected, and lastly, 2.9 GHz to the 10<sup>th</sup> harmonic was graphed and the level of the harmonics was measured and recorded. The bandwidth was initially set to 1MHz for signature scans, and then reduced to 30 kHz to measure individual signal strengths.

**Measurements Required:** Conducted Spurious and Harmonic Emissions at Antenna Terminals (Digital Mode)

Graph Attached  
EXHIBIT 6G2 and 6G3

**Definition** - (as used herein) Spurious radiations are the radio frequency voltages or power generated within the equipment and appearing at the equipment's output terminals when properly matched with its characteristic radiating antenna.

**Minimum standard** Conducted spurious and harmonic emissions shall be attenuated 43dB + 10 Log10(the mean power output). In the range of frequencies between 869.04MHz and 893.97MHz, and from 1930 MHz to 1990 MHz, no spur shall exceed -80dBm.

**Method of Measurement** - The transmitter was modulated with OQPSK modulation using pseudo random data. The antenna port of the sample was directly coupled to the input of the EMI receiver through a special coupling cable. Scans were then performed from 30 MHz to 1 GHz, while observing the fundamental signal level, plus low order harmonics or other spurious signals. The frequency range of 1 to 2.9GHz was then inspected, and lastly, 2.9 GHz to the 10<sup>th</sup> harmonic was graphed and the level of the harmonics was measured and recorded. The bandwidth was initially set to 1MHz for signature scans, and then reduced to 30 kHz to measure individual signal strengths.

2.1053 Measurements Required: Radiated Spurious and Harmonic Radiation (Analog and Digital Modes)

Graph attached  
EXHIBIT 6H1, 6H2 and 6H3

Definition - Radiated spurious and harmonic emissions are frequencies from the equipment when loaded into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to insure transmission of information of required quality for the class of communications desired. The reduction in the level of these spurious emissions will not effect the quality of the information being transmitted.

Minimum standard - Radiated spurious emissions and harmonic emissions shall be attenuated 43dB 10 Log10(the mean power output). In the range of frequencies between 869.04MHz and 893.97MHz, and from 1930 MHz to 1990 MHz, no spur shall exceed -80dBm.

Method of Measurement:

Test Site – Under Writer’s Laboratory, Melville, New York, A 10-meter Anechoic Chamber has been constructed to a special design which minimizes disturbances to RF radiation patterns. The chamber housed only the equipment under test while all the control and measurement equipment remained external to the measurement environment.

Installation of Equipment:

The equipment under test is placed on the turntable, and then placed in normal operation using the intended power source. A receiving antenna located 3 meters from the turntable picks up any signal radiated from the transmitter and its operating accessories. The antenna is adjustable in height and can be horizontally and vertically polarized. Tunable receivers covering the necessary frequency range are used to detect and measure any radiation picked up by the antenna.

Measurement Procedure

The equipment is adjustable to obtain peak readings of received signals wherever they occur in the spectrum by:

1. Rotating the transmitter under test.
2. Adjusting the antenna height.

The testing procedure is repeated for both horizontal and vertical polarization of the receiving antenna. Relative signal strength is indicated on meters built into the receiver. To obtain actual radiated signal strength, a standard signal generator with calibrated output is substituted for the transmitter under test. The signal generator is adjusted in output until a reading identical to that obtained with the actual transmitter is obtained at the receiver. Signal strength is then read directly from the generator. Actual measurements are recorded on the attached graph.

## 2.1055 Measurements Required: Frequency Stability (Analog and Digital Modes)

Definition - The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

Minimum standard - In the analog modes, the minimum frequency stability shall be  $\pm 0.000075\%$  referenced to a received carrier frequency from a base station. This meets the requirement for operational accuracy of 0.00025. In digital mode, the minimum frequency stability shall be  $\pm 300$  Hz referenced to a received carrier frequency from a base station. This meets the requirement for operational accuracy of 0.00005% in digital mode.

Method of Measurement - Frequency measurements shall be made at the extremes of the temperature range  $-30^{\circ}$  to  $+60^{\circ}\text{C}$  and at intervals of not more than  $10^{\circ}\text{C}$  throughout the range. A period of time sufficient to stabilize all of the components in the equipment shall be allowed prior to each frequency measurement. The frequency of the transmitter shall be measured by extracting a sample of the carrier and measuring its center frequency by equipment having a degree of accuracy of at least 10 times that of the minimum to be measured.

The frequency stability of transmitting equipment shall be checked with variations in:

- (a) Temperature: Vary the ambient from  $-30^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$ .

Tables attached EXHIBITS

- (b) Primary Supply Voltage:

Vary the primary supply voltage over the specified battery voltage range.

Tables attached EXHIBITS

### Timing Period and Procedure for Frequency Stability Measurements

1. The equipment was then subjected to an overnight soak at  $-30^{\circ}\text{C}$  without any power applied.
2. After an overnight soak at  $-30^{\circ}\text{C}$ , measurement of the carrier frequency of the transmitter was made within a three minute interval or a period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level after applying power to the transmitter.
3. Frequency measurements were made at each  $10^{\circ}\text{C}$  interval ( $-30^{\circ}$ ,  $-20^{\circ}$ ,  $-10^{\circ}$ ,  $0^{\circ}$ ,  $+10^{\circ}$ ,  $+20^{\circ}$ ,  $+30^{\circ}$ ,  $+40^{\circ}$ ,  $+50^{\circ}$ ,  $+60^{\circ}$ ). A period of at least one hour was provided to allow stabilization of the equipment at each temperature level.
4. In all measurements, at the various temperature intervals, the temperature was held to  $\pm 1^{\circ}\text{C}$  from the temperature level.
5. The Base Station test set was mounted external to the temperature chamber.