



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2451-3
FCC ID : IHDT56AP8
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Mar. 30, 2024 ~ Apr. 10, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 8

 1.6. Test Location 8

 1.7. Test Software 9

 1.8. Applicable Standards 9

 1.9. Specification of Accessory 9

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 10

 2.1. Test Mode 10

 2.2. Connection Diagram of Test System 12

 2.3. Support Unit used in test configuration and system 12

 2.4. EUT Operation Test Setup 13

3. TEST RESULT 14

 3.1. Test of AC Conducted Emission Measurement 14

 3.2. Test of Radiated Emission Measurement 18

4. LIST OF MEASURING EQUIPMENT 23

5. MEASUREMENT UNCERTAINTY 24

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC420703-01	Rev. 01	Initial issue of report	Apr. 30, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 5.24 dB at 0.210 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 6.00 dB at 82.380 MHz

Conformity Assessment Condition:

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1. Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2451-3
FCC ID	IHDT56AP8
EUT supports Radios application	GSM/CDMA/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ac VHT20/VHT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 2.4GHz 802.11be (EHT20/ EHT40) WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 WLAN 5GHz 802.11be (EHT20/EHT40/EHT80/EHT160) WLAN 6GHz 802.11a/ax HE20/HE40/HE80/HE160 WLAN 6GHz 802.11be (EHT20/EHT40/EHT80/EHT160/EHT320) Bluetooth BR/EDR/LE GNSS/NFC/WPT
IMEI Code	Conduction: 355473450020359/355473450020367 Radiation: 355473450020391/355473450020409
HW Version	DVT2
SW Version	U3UX34.16
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



	1024QAM / 4096QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : π /4-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK WPT: ASK
--	--

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH05-SZ	CN1256	421272

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH05-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.9. Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Chenyang)	Model Name	MC-681N
AC Adapter 1(EU)	Brand Name	Motorola (Chenyang)	Model Name	MC-682N
AC Adapter 1(UK)	Brand Name	Motorola (Chenyang)	Model Name	MC-683N
AC Adapter 1(AU)	Brand Name	Motorola (Chenyang)	Model Name	MC-685N
AC Adapter 1(AR)	Brand Name	Motorola (Chenyang)	Model Name	MC-686N
AC Adapter 1(BR)	Brand Name	Motorola (Chenyang)	Model Name	MC-687N
AC Adapter 1(CHILE)	Brand Name	Motorola (Chenyang)	Model Name	MC-689N
AC Adapter 1(KR)	Brand Name	Motorola (Chenyang)	Model Name	MC-680N
AC Adapter 2(US)	Brand Name	Motorola (Acbel)	Model Name	MC-681N
AC Adapter 2(EU)	Brand Name	Motorola (Acbel)	Model Name	MC-682N
AC Adapter 2(UK)	Brand Name	Motorola (Acbel)	Model Name	MC-683N
AC Adapter 2(AU)	Brand Name	Motorola (Acbel)	Model Name	MC-685N
AC Adapter 2(AR)	Brand Name	Motorola (Acbel)	Model Name	MC-686N
AC Adapter 2(BR)	Brand Name	Motorola (Acbel)	Model Name	MC-687N
AC Adapter 3(IN)	Brand Name	Motorola (Acbel)	Model Name	MC-684N
Battery 1	Brand Name	Motorola(ATL)	Model Name	QR10
Battery 2	Brand Name	Motorola(ATL)	Model Name	QR30
USB Cable 1	Brand Name	Motorola(SAIBAO)	Model Name	SC18D71644
USB Cable 2	Brand Name	Motorola(Luxshare)	Model Name	SC18E08104
Wireless Earphones	Brand Name	Motorola	Model Name	XT2441-1



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Idle(Middle CH) + BT link + Camera(Rear) + Open + USB Cable 1 (Charging from Adapter 1) + Battery + SIM 1
	Mode 2: WCDMA Band 5 Idle(Low CH) + BT link + Camera(Front) + Open + USB Cable 2 (Charging from Adapter 2) + Battery + E-SIM
	Mode 3: LTE Band 12 Idle(Middle CH) + BT link + MPEG4(Run Color Bar) + Open + USB Cable 1 (Charging from Adapter 3) + Battery 1 + SIM 1
	Mode 4: NR SA n71 (High CH) + BT idle + Camera(Rear) + Open + USB Cable 1 (Data Link with Notebook) + EUT (eMMC) USB Data Link to NB +Battery+ SIM 1
	Mode 5: LTE Band 13 (High CH) + BT link + Camera(Rear) + Open + USB Cable 1 (Data Link with Notebook) + NB USB Data Link to EUT (eMMC) + E-SIM + Battery
	Mode 6: NR SA n71 (High CH) + BT idle + Camera(Rear) + Open + USB Cable 2 (Data Link with Notebook) + (EUT (eMMC) USB Data Link to NB) + Battery + SIM 1
	Mode 7: NR SA n71 (High CH) + BT idle + Camera(Rear) + Open + USB Cable 1 (Charging from Wireless charging) + Battery + SIM 1
	Mode 8: NR SA n71 (High CH) + BT idle + Reverse charge + Open + USB Cable 1 (Charging from Adapter 1) + Battery + SIM 1
	Mode 9: NR SA n71 (High CH) + BT idle + Camera(Rear) + Fold Up + USB Cable 1 (Data Link with Notebook) + EUT (eMMC) USB Data Link to NB + SIM 1 +Battery



Radiated Emissions	<p>Mode 1: GSM 850 Idle(Middle CH) + BT link + Camera(Rear) + Open + USB Cable 1 (Charging from Adapter 1) + Battery + SIM 1</p> <p>Mode 2: WCDMA Band 5 Idle(Low CH) + BT idle + Camera(Front) + Open + USB Cable 2 (Charging from Adapter 2) + Battery + E-SIM</p> <p>Mode 3: LTE Band 12 Idle(Middle CH) + BT link + MPEG4(Run Color Bar) + Open + USB Cable 1 (Charging from Adapter 3) + Battery + SIM 1</p> <p>Mode 4: NR SA n71 (High CH) + BT idle + Camera(Rear) + Open + USB Cable 1 (Data Link with Notebook) + EUT (eMMC) USB Data Link to NB + Battery + SIM 1</p> <p>Mode 5: LTE Band 13 (High CH) + BT link + Camera(Rear) + Open + USB Cable 1 (Data Link with Notebook) + NB USB Data Link to EUT (eMMC) + Battery + E-SIM</p> <p>Mode 6: GSM 850 Idle(Middle CH) + BT idle + Camera(Rear) + Open + USB Cable 2 (Data Link with Notebook) + (EUT (eMMC) USB Data Link to NB) + Battery + SIM 1</p> <p>Mode 7: GSM 850 Idle(Middle CH) + BT link + MPEG4(Run Color Bar) + Open + Type C Earphone + Battery + SIM 1</p> <p>Mode 8: GSM 850 Idle(Middle CH) + BT link + Camera(Rear) + Open + USB Cable 1(Charging from Wireless charging) + Battery + SIM 1</p> <p>Mode 9: GSM 850 Idle(Middle CH) + BT link + Reverse charge + Open + USB Cable 1(Charging from Adapter 1) + Battery + SIM 1</p> <p>Mode 10 : GSM 850 Idle(Middle CH) + BT link + Camera(Rear)+ Fold Up + USB Cable (1) (Charging from Adapter 1) + Battery + SIM 1</p>
<p>Remark:</p> <ol style="list-style-type: none"> 1. The worst case of AC is mode 4; only the test data of this mode is reported. 2. The worst case of RE is mode 1; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 4. Pre-scanned Low/Middle/High channel, the worst channel was recorded in this report. 5. Fold Up mode is verified worse case of Open modes. 6. Battery 1 and Battery 2 used simultaneously in the phone. 	

2.2. Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded,1.8m
3.	Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded,1.8m
4.	Notebook	DELL	3400	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
5.	Notebook	Thinkpad	Thinkpad E14	N/A	N/A	N/A
6.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
7.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,2.7m with Core
8.	iPod	apple	N/A	MC69029/A	N/A	N/A
9.	iPod	Apple	MC525 ZP/A	Fcc DoC	N/A	Shielded, 1.0m
10.	Wireless charging	Samsung	EP-NG920	N/A	N/A	N/A
11.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
12.	Mobile phone	N/A	N/A	N/A	N/A	N/A
13.	Earphone	apple	N/A	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE or 5G NR idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Wireless Charge from a Wireless Charger.
5. Wireless Charge for the other phone.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-SZ
 Condition: FCC 15B_QP AC LISN 100063_L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.17	41.49	-13.37	54.86	21.10	10.25	10.14	Average
2	0.17	59.39	-5.47	64.86	39.00	10.25	10.14	QP
3	0.21	38.58	-14.74	53.32	18.00	10.43	10.15	Average
4 *	0.21	58.08	-5.24	63.32	37.50	10.43	10.15	QP
5	0.26	27.27	-24.29	51.56	7.00	10.12	10.15	Average
6	0.26	45.67	-15.89	61.56	25.40	10.12	10.15	QP
7	3.90	32.02	-13.98	46.00	11.50	10.20	10.32	Average
8	3.90	45.42	-10.58	56.00	24.90	10.20	10.32	QP
9	5.00	33.78	-16.22	50.00	13.20	10.23	10.35	Average
10	5.00	43.98	-16.02	60.00	23.40	10.23	10.35	QP
11	8.50	31.40	-18.60	50.00	10.70	10.33	10.37	Average
12	8.50	40.90	-19.10	60.00	20.20	10.33	10.37	QP



Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15B_QP AC LISN 100063_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17	40.21	-14.51	54.72	19.60	10.47	10.14	Average
2 *	0.17	58.41	-6.31	64.72	37.80	10.47	10.14	QP
3	0.24	30.93	-21.33	52.26	10.60	10.18	10.15	Average
4	0.24	53.13	-9.13	62.26	32.80	10.18	10.15	QP
5	0.27	26.37	-24.61	50.98	5.90	10.32	10.15	Average
6	0.27	43.97	-17.01	60.98	23.50	10.32	10.15	QP
7	3.16	29.07	-16.93	46.00	8.30	10.48	10.29	Average
8	3.16	42.17	-13.83	56.00	21.40	10.48	10.29	QP
9	3.82	32.29	-13.71	46.00	11.50	10.48	10.31	Average
10	3.82	44.99	-11.01	56.00	24.20	10.48	10.31	QP
11	5.17	33.83	-16.17	50.00	13.20	10.28	10.35	Average
12	5.17	44.43	-15.57	60.00	23.80	10.28	10.35	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	ZhanSheng Liu	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#7 is system simulator signals which can be ignored. #8 is RF signal which comes from Bluetooth used to connect the EUT, and which can be ignored.		




Site : 03CH05-SZ
Condition : FCC CLASS-B 3m VULB9168-01003 HORIZONTAL

Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	88.20	27.40	-16.10	43.50	46.25	13.96	1.97	34.78	---	---	Peak
2	152.22	22.64	-20.86	43.50	36.14	18.86	2.34	34.70	---	---	Peak
3	258.92	27.05	-18.95	46.00	40.84	17.84	3.05	34.68	---	---	Peak
4	286.08	26.88	-19.12	46.00	39.66	18.69	3.16	34.63	---	---	Peak
5	438.37	25.26	-20.74	46.00	33.89	22.44	3.43	34.50	---	---	Peak
6	766.23	28.52	-17.48	46.00	31.27	27.67	3.95	34.37	---	---	Peak
7 *	881.66	49.36			50.56	28.69	4.41	34.30	---	---	Peak
8	2402.00	60.73			70.67	33.33	7.17	50.44	---	---	Peak
9	3136.00	41.89	-32.11	74.00	49.03	33.84	8.84	49.82	---	---	Peak
10	4656.00	43.48	-30.52	74.00	47.73	35.99	9.33	49.57	---	---	Peak
11	6696.00	45.07	-28.93	74.00	46.70	36.90	10.88	49.41	---	---	Peak
12	10755.00	42.91	-31.09	74.00	38.18	39.55	13.38	48.20	---	---	Peak
13	13878.00	46.95	-27.05	74.00	39.14	40.83	14.51	47.53	---	---	Peak
14	15975.00	45.95	-28.05	74.00	39.18	42.58	15.57	51.38	---	---	Peak



Test Engineer :	ZhanSheng Liu	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Remark :	#7 is system simulator signals which can be ignored. #8 is RF signal which comes from Bluetooth used to connect the EUT, and which can be ignored.		



Site : 03CH05-SZ
Condition : FCC CLASS-B 3m VULB9168-01003 VERTICAL

Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	55.22	29.89	-10.11	40.00	43.78	19.37	1.69	34.95	---	---	Peak
2	82.38	34.00	-6.00	40.00	52.06	14.73	1.93	34.72	---	---	Peak
3	154.16	32.66	-10.84	43.50	46.26	18.75	2.35	34.70	---	---	Peak
4	178.41	31.37	-12.13	43.50	46.30	17.28	2.49	34.70	---	---	Peak
5	261.83	28.72	-17.28	46.00	42.41	17.93	3.06	34.68	---	---	Peak
6	305.48	28.30	-17.70	46.00	40.41	19.25	3.24	34.60	---	---	Peak
7 *	881.66	49.58			50.78	28.69	4.41	34.30	---	---	Peak
8	2402.00	61.25			71.19	33.33	7.17	50.44	---	---	Peak
9	3136.00	42.90	-31.10	74.00	50.04	33.84	8.84	49.82	---	---	Peak
10	4784.00	44.57	-29.43	74.00	48.62	36.08	9.41	49.54	---	---	Peak
11	6648.00	46.04	-27.96	74.00	47.60	36.90	10.82	49.28	---	---	Peak
12	10557.00	43.53	-30.47	74.00	38.95	39.51	13.42	48.35	---	---	Peak
13	13590.00	46.96	-27.04	74.00	39.03	40.66	14.40	47.13	---	---	Peak
14	17001.00	46.28	-27.72	74.00	38.55	43.90	15.23	51.40	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	102261	9kHz~7GHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010B	MY59071191	10Hz~44GHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
Log-periodic Antenna	SCHWARZBECK	VULB 9168	01001	20MHz~1.5GHz	Jul. 08, 2023	Mar. 30, 2024	Jul. 07, 2024	Radiation (03CH05-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-2206	1GHz~18GHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	00983	15GHz~40GHz	Apr. 08, 2023	Mar. 30, 2024	Apr. 07, 2024	Radiation (03CH05-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz~3000MHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
HF Amplifier	EM Electronics	EM01G18GA	060781	1GHz~18GHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
HF Amplifier	EM Electronics	EM18G40G	060778	18GHz~40GHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
Amplifier	Keysight	83017A	MY53270357	500MHz~26.5GHz	Apr. 04, 2023	Mar. 30, 2024	Apr. 03, 2024	Radiation (03CH05-SZ)
AC Power Source	APC	AFV-S-600	F119050013	N/A	Oct. 18, 2023	Mar. 30, 2024	Oct. 17, 2024	Radiation (03CH05-SZ)
Turn Table	EMEC	T-200-S-1	060925-T	0~360 degree	NCR	Mar. 30, 2024	NCR	Radiation (03CH05-SZ)
Antenna Mast	EMEC	MBS-400-1	060927	1 m~4 m	NCR	Mar. 30, 2024	NCR	Radiation (03CH05-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 06, 2023	Apr. 10, 2024	Jul. 05, 2024	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Aug. 21, 2023	Apr. 10, 2024	Aug. 20, 2024	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 16, 2023	Apr. 10, 2024	Oct. 15, 2024	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 07, 2023	Apr. 10, 2024	Jul. 06, 2024	Conduction (CO01-SZ)

NCR: No Calibration Required



5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.1 dB
---	--------

----- THE END -----