



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : M-51E(XT2453-8)
FCC ID : IHDT56AQ9
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Jun. 24, 2024 ~ Jul. 08, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Specification of Accessory 7

 1.7. Test Location 8

 1.8. Test Software 8

 1.9. Applicable Standards 8

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1. Test Mode 9

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system 10

 2.4. EUT Operation Test Setup 11

3. TEST RESULT 12

 3.1. Test of AC Conducted Emission Measurement 12

 3.2. Test of Radiated Emission Measurement 16

4. LIST OF MEASURING EQUIPMENT 21

5. MEASUREMENT UNCERTAINTY 22

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 9.44 dB at 0.15 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 7.77 dB at 69.77 MHz

Conformity Assessment Condition:

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1. Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	M-51E(XT2453-8)
FCC ID	IHDT56AQ9
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 WLAN 5GHz 802.11ax HE20/HE40/HE80 WLAN 6GHz 802.11ax HE20/HE40/HE80 Bluetooth BR/EDR/LE GNSS/NFC/WPT
IMEI Code	Conduction: 352282910007119/352282910007127 Radiation: 352282910005113/352282910005121
HW Version	DVT2
SW Version	UUC34.94
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



	802.11b/g/n/ax: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac/ax: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz 802.11ax: 5925 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz WPT: 110 kHz ~ 148 kHz GNSS : 1559 MHz ~ 1610 MHz, 1164 MHz ~ 1215 MHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN_ANT5 : Metal Antenna WLAN_ANT7 : IFA Antenna Bluetooth : IFA Antenna GNSS: IFA Antenna NFC: Coil loop Antenna WPT: Copper Coil Antenna
Type of Modulation	GSM/GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK HSPA : QPSK HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM / 256QAM 5G NR: DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM) CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM) 802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) :π/4-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK WPT: ASK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Specification of Accessory

Accessories Information				
Battery 1	Brand Name	Motorola	Model Name	RD11
Battery 2	Brand Name	Motorola	Model Name	RD29

1.7. Test Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH05-SZ	CN1256	421272

1.8. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH05-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.9. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (2.4G) Idle + Camera(Rear) + Battery + open folding screen + USB Cable (Charging from Adapter) + SIM 1
	Mode 2: WCDMA Band 5 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (5G) Idle + Camera(Front) + Battery + open folding screen + USB Cable (Data Link with Notebook) + EUT (eMMC) USB Data Link to Notebook + ESIM
	Mode 3: LTE Band 12 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (2.4G) Idle + NFC On + Battery + open folding screen + USB Cable (Data Link with Notebook) + Notebook USB Data Link to EUT (eMMC) + SIM 1
	Mode 4: LTE Band 17 Rx(Low) + Bluetooth Idle With BT Earphone + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + open folding screen + USB Cable (Data Link with Notebook) + EUT (eMMC) USB Data Link to Notebook + SIM 1
	Mode 5: n5 Rx(Low) + Bluetooth Idle With BT Earphone + WLAN 6E Idle + GNSS Rx1+GNSS Rx2 + Battery + open folding screen + USB Cable (EUT Charging from Wireless charger) + Adapter Connect to Wireless charger + SIM1
	Mode 6: WCDMA Band 5 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (5G) Idle + Camera(Front) + Battery + Closed folding screen + USB Cable (Data Link with Notebook) + EUT (eMMC) USB Data Link to Notebook + ESIM
Radiated Emissions	Mode 1: GSM 850 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (2.4G) Idle + Camera(Rear) + Battery + open folding screen + USB Cable (Charging from Adapter) + SIM 1
	Mode 2: WCDMA Band 5 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (5G) Idle + Camera(Front) + Battery + open folding screen + USB Cable (Data Link with Notebook) + EUT (eMMC) USB Data Link to Notebook + ESIM
	Mode 3: LTE Band 12 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (2.4G) Idle + NFC On + Battery + open folding screen + USB Cable (Data Link with Notebook) + Notebook USB Data Link to EUT (eMMC) + SIM 1
	Mode 4: LTE Band 17 Rx(Low) + Bluetooth Idle With BT Earphone + WLAN (5G) Idle + MPEG4(Run Color Bar) + Earphone + Battery + open folding screen + SIM 1
	Mode 5: LTE Band 26 Rx(High) + Bluetooth Idle With BT Earphone + WLAN 6E Idle + GNSS Rx1+GNSS Rx2 + Battery + open folding screen + USB Cable (EUT Charging from Wireless charger) + Adapter Connect to Wireless charger + SIM 1
	Mode 6: n5 Rx(Low) + Bluetooth Idle With BT Earphone + Stand alone + Battery + open folding screen + EUT Wireless Charge the BT Earphone + SIM 1
	Mode 7: GSM 850 Rx(Middle) + Bluetooth Idle With BT Earphone + WLAN (2.4G) Idle + Camera(Rear) + Battery + open folding screen + USB Cable (Charging from Adapter) + SIM 1
Remark:	
<ol style="list-style-type: none"> 1. The worst case of AC is mode 2; only the test data of this mode is reported. 2. The worst case of RE is mode 1; only the test data of this mode is reported. 3. Data Link with Notebook means data transferred mode between EUT and Notebook. 4. Pre-scanned Low/Middle/High channel, the worst channel was recorded in this report. 	

2.2. Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded,1.8m
2.	Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	Unshielded AC I/P cable 1.8m
4.	Notebook	Acer	N20C5	N/A	N/A	N/A
5.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
6.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
7.	SD Card	Kingston	8GB	N/A	N/A	N/A
8.	Hard disk	KINGSHARE	KSP6120G	N/A	N/A	N/A
9.	Signal Generator	R&S	SMBV100A	N/A	N/A	N/A
10.	Adapter	Motorola	N/A	N/A	N/A	N/A
11.	USB Cable	Motorola	N/A	N/A	Shielded,1.2m	N/A
12.	Earphone	Lenovo	N/A	N/A	Unshielded,1.2m	N/A
13.	Wireless charger	Motorola	N/A	N/A	N/A	N/A
14.	Bluetooth Earphone	Motorola	N/A	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE or 5G NRidle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
5. Turn on NFC function
6. Wireless Charge from a Wireless Charger.
7. Wireless Charge for the BT Earphone.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-SZ
 Condition: FCC 15B_QP AC LISN 100063_L LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	39.72	-16.28	56.00	19.20	10.39	10.13	Average
2 *	0.15	56.12	-9.88	66.00	35.60	10.39	10.13	QP
3	0.17	34.39	-20.69	55.08	14.00	10.25	10.14	Average
4	0.17	53.59	-11.49	65.08	33.20	10.25	10.14	QP
5	0.21	32.78	-20.54	53.32	12.20	10.43	10.15	Average
6	0.21	51.08	-12.24	63.32	30.50	10.43	10.15	QP
7	0.27	27.85	-23.35	51.20	7.60	10.10	10.15	Average
8	0.27	43.75	-17.45	61.20	23.50	10.10	10.15	QP
9	3.99	32.23	-13.77	46.00	11.70	10.21	10.32	Average
10	3.99	41.53	-14.47	56.00	21.00	10.21	10.32	QP
11	4.57	30.86	-15.14	46.00	10.30	10.22	10.34	Average
12	4.57	37.06	-18.94	56.00	16.50	10.22	10.34	QP



Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15B_QP AC LISN 100063_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	42.06	-13.94	56.00	21.80	10.13	10.13	Average
2 *	0.15	56.56	-9.44	66.00	36.30	10.13	10.13	QP
3	0.17	35.21	-19.51	54.72	14.60	10.47	10.14	Average
4	0.17	53.11	-11.61	64.72	32.50	10.47	10.14	QP
5	0.22	34.88	-18.04	52.92	14.51	10.22	10.15	Average
6	0.22	50.58	-12.34	62.92	30.21	10.22	10.15	QP
7	0.27	27.32	-23.93	51.25	6.91	10.26	10.15	Average
8	0.27	42.62	-18.63	61.25	22.21	10.26	10.15	QP
9	3.40	30.38	-15.62	46.00	9.60	10.48	10.30	Average
10	3.40	38.58	-17.42	56.00	17.80	10.48	10.30	QP
11	4.16	32.97	-13.03	46.00	12.19	10.45	10.33	Average
12	4.16	41.77	-14.23	56.00	20.99	10.45	10.33	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	TaoZhang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#7 is system simulator signal which can be ignored. #9 is WLAN 2.4G RF signal which can be ignored.		




Site : 03CH05-SZ
Condition : FCC CLASS-B 3m VULB9168--01003 HORIZONTAL

Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	86.26	23.49	-16.51	40.00	42.51	14.12	1.96	35.10	---	---	Peak
2	160.95	19.07	-24.43	43.50	33.35	18.31	2.39	34.98	---	---	Peak
3	323.91	19.88	-26.12	46.00	31.57	19.79	3.32	34.80	---	---	Peak
4	452.92	22.87	-23.13	46.00	31.07	23.04	3.46	34.70	---	---	Peak
5	640.13	26.12	-19.88	46.00	30.75	26.22	3.65	34.50	---	---	Peak
6	805.03	29.24	-16.76	46.00	29.92	29.13	4.39	34.20	---	---	Peak
7 *	881.66	53.69			54.51	28.97	4.41	34.20	---	---	Peak
8	2080.00	44.21	-29.79	74.00	68.23	32.52	6.90	63.44	---	---	Peak
9	2437.00	61.49			84.39	33.47	7.22	63.59	---	---	Peak
10	5800.00	45.73	-28.27	74.00	64.06	36.41	10.12	64.86	---	---	Peak
11	8344.00	45.52	-28.48	74.00	60.67	37.74	11.74	64.63	---	---	Peak
12	9504.00	46.73	-27.27	74.00	58.85	38.90	12.97	63.99	---	---	Peak
13	14211.00	46.50	-27.50	74.00	54.59	41.02	14.78	63.89	---	---	Peak
14	17541.00	47.09	-26.91	74.00	52.76	44.53	15.26	65.46	---	---	Peak



Test Engineer :	TaoZhang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Remark :	#7 is system simulator signal which can be ignored. #9 is WLAN 2.4G RF signal which can be ignored.		



Site : 03CH05-SZ
Condition : FCC CLASS-B 3m VULB9168--01003 VERTICAL

Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	26.98	-13.02	40.00	42.74	17.83	1.21	34.80	---	---	Peak
2	69.77	32.23	-7.77	40.00	48.49	17.00	1.84	35.10	---	---	Peak
3	165.80	25.74	-17.76	43.50	40.26	18.04	2.41	34.97	---	---	Peak
4	317.12	19.83	-26.17	46.00	31.71	19.66	3.29	34.83	---	---	Peak
5	538.28	23.79	-22.21	46.00	30.64	24.30	3.47	34.62	---	---	Peak
6	809.88	30.58	-15.42	46.00	31.27	29.12	4.39	34.20	---	---	Peak
7 *	881.66	51.48			52.30	28.97	4.41	34.20	---	---	Peak
8	1992.00	44.07	-29.93	74.00	68.40	32.20	6.87	63.40	---	---	Peak
9	2437.00	63.19			86.09	33.47	7.22	63.59	---	---	Peak
10	4072.00	46.70	-27.30	74.00	66.99	34.90	9.37	64.56	---	---	Peak
11	7472.00	45.00	-29.00	74.00	63.12	35.84	10.90	64.86	---	---	Peak
12	9441.00	46.70	-27.30	74.00	59.01	38.87	12.84	64.02	---	---	Peak
13	13410.00	45.61	-28.39	74.00	54.57	40.55	14.31	63.82	---	---	Peak
14	16641.00	47.45	-26.55	74.00	53.66	43.25	15.35	64.81	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	102261	9kHz~7GHz	Apr. 09, 2024	Jul. 08, 2024	Apr. 08, 2025	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Aug. 21, 2023	Jul. 08, 2024	Aug. 20, 2024	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 16, 2023	Jul. 08, 2024	Oct. 15, 2024	Conduction (CO01-SZ)
AC Power Source	APC	AFV-S-600	F119050013	N/A	Oct. 18, 2023	Jul. 08, 2024	Oct. 17, 2024	Conduction (CO01-SZ)
EMI Test Receiver	R&S	ESR7	102261	9kHz~7GHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010B	MY59071191	10Hz~44GHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
Log-periodic Antenna	SCHWARZBECK	VULB 9168	01001	20MHz~1.5GHz	Jul. 08, 2023	Jun. 24, 2024	Jul. 07, 2024	Radiation (03CH05-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-2206	1GHz~18GHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	00983	15GHz~40GHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz ~3000MHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
HF Amplifier	EM Electronics	EM01G18GA	060781	1GHz~18GHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
HF Amplifier	EM Electronics	EM18G40G	060778	18GHz~40GHz	Apr. 09, 2024	Jun. 24, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
AC Power Source	APC	AFV-S-600	F119050013	N/A	Oct. 18, 2023	Jun. 24, 2024	Oct. 17, 2024	Radiation (03CH05-SZ)
Turn Table	EMEC	T-200-S-1	060925-T	0~360 degree	NCR	Jun. 24, 2024	NCR	Radiation (03CH05-SZ)
Antenna Mast	EMEC	MBS-400-1	060927	1 m~4 m	NCR	Jun. 24, 2024	NCR	Radiation (03CH05-SZ)

NCR: No Calibration Required



5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.1dB
---	-------

----- THE END -----