



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2507-1
FCC ID : IHDT56AU3
STANDARD : 47 CFR Part 22(H), 24(E), 27(L), 27(M), 27(N), 27(O)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Feb. 19, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY... 3
SUMMARY OF TEST RESULT ... 4
1 GENERAL DESCRIPTION ... 5
1.1 Applicant ... 5
1.2 Manufacturer ... 5
1.3 Product Feature of Equipment Under Test ... 5
1.4 Product Specification of Equipment Under Test ... 5
1.5 Modification of EUT ... 6
1.6 Testing Location ... 6
1.7 Test Software ... 6
1.8 Applicable Standards ... 7
1.9 Specification of Accessory ... 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ... 8
2.1 Test Mode ... 8
2.2 Connection Diagram of Test System ... 9
2.3 Support Unit used in test configuration and system ... 9
2.4 Frequency List of Low/Middle/High Channels ... 10
3 RADIATED TEST ITEMS ... 15
3.1 Measuring Instruments ... 15
3.2 Test Setup ... 15
3.3 Test Result of Radiated Test ... 16
3.4 Radiated Spurious Emission ... 17
4 LIST OF MEASURING EQUIPMENT ... 18
5 MEASUREMENT UNCERTAINTY ... 19
APPENDIX A. TEST RESULTS OF RADIATED TEST
APPENDIX B. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Radiated Spurious Emission (LTE Band 2, 4, 5, 66) (5G NR n5, n71)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 24.34 dB at 10104.00 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (LTE Band 7) (5G NR n7, n41)	$< 55+10\log_{10}(P[\text{Watts}])$		
	§2.1053 §27.53 (l)(2)	Radiated Spurious Emission (5G NR n78)	$< 43+10\log_{10}(P[\text{Watts}])$		

Remark : The conducted test items of inter band CA were cover by LTE/5G NR single carrier due to the CA power is reduced according to 3GPP MPR.

Conformity Assessment Condition:
<ol style="list-style-type: none"> The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"
Disclaimer:
The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2507-1
FCC ID	IHDT56AU3
IMEI Code	Radiation: 358346690030072/358346690030080
HW Version	DVT2
SW Version	V2VV35.35
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 7 : 2500 MHz ~ 2570 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n7 : 2500 MHz ~ 2570 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n71: 663 MHz ~ 698 MHz 5G NR n78: 3700 MHz ~ 3800 MHz
Rx Frequency	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 7 : 2620 MHz ~ 2690 MHz LTE Band 66 : 2110 MHz~ 2200 MHz 5G NR n5 : 869 MHz ~ 894 MHz 5G NR n7 : 2620 MHz ~ 2690 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n71: 617 MHz ~ 652 MHz 5G NR n78: 3700 MHz ~ 3800 MHz
Uplink CA Bands (LTE)	2A-4A, 2A-7A, 2A-66A, 4A-5A, 4A-7A, 5A-7A, 5A-66A
Uplink CA Bands (5G NR)	n5A- n78A, n7A- n78A, n71A- n78A, n41A- n71A



Type of Modulation	LTE: QPSK / 16QAM / 64QAM / 256QAM 5G NR: DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM) CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM)
---------------------------	---

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 22(H), 24(E), 27(L), 27(M), 27(N), 27(O)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Accessories Information				
AC Adapter 1(US)	Brand Name	Motorola(Salcomp)	Model Name	MC-901
AC Adapter 1(EU)	Brand Name	Motorola(Salcomp)	Model Name	MC-902
AC Adapter 1(UK)	Brand Name	Motorola(Salcomp)	Model Name	MC-903
AC Adapter 1(AU)	Brand Name	Motorola(Salcomp)	Model Name	MC-905
AC Adapter 1(AR)	Brand Name	Motorola(Salcomp)	Model Name	MC-906
AC Adapter 1(BR)	Brand Name	Motorola(Salcomp)	Model Name	MC-907
AC Adapter 1(CHILE)	Brand Name	Motorola(Salcomp)	Model Name	MC-909
AC Adapter 2(US)	Brand Name	Motorola(AOHAI)	Model Name	MC-901
AC Adapter 2(EU)	Brand Name	Motorola(AOHAI)	Model Name	MC-902
AC Adapter 2(UK)	Brand Name	Motorola(AOHAI)	Model Name	MC-903
AC Adapter 2(AU)	Brand Name	Motorola(AOHAI)	Model Name	MC-905
AC Adapter 2(AR)	Brand Name	Motorola(AOHAI)	Model Name	MC-906
AC Adapter 2(BR)	Brand Name	Motorola(AOHAI)	Model Name	MC-907
AC Adapter 2(CHILE)	Brand Name	Motorola(AOHAI)	Model Name	MC-909
Battery	Brand Name	Motorola(ATL)	Model Name	RE60
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D71644
USB Cable 2	Brand Name	Motorola(Luxshare)	Model Name	SC18E08104
USB Cable 3	Brand Name	Motorola(Saibao)	Model Name	SC18D86731
USB Cable 4	Brand Name	Motorola(Luxshare)	Model Name	SC18E08103



2 Test Configuration of Equipment Under Test

2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Z/Y-Plane)

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel			Test Plane			
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H				
Radiated Spurious Emission	2A-4A	Worst Case																	v		Z
	2A-5A	Worst Case																	v		Z
	2A-7A	Worst Case																	v		Y
	2A-66A	Worst Case																	v		Z
	4A-5A	Worst Case																	v		Z
	4A-7A	Worst Case																	v		Y
	5A-66A	Worst Case																	v		Y
5A-7A	Worst Case																	v		Y	
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																				

Test Items	5G NR	Bandwidth (MHz)													Modulation			RB #		Test Channel			Test Plane
		5	10	15	20	25	30	40	50	60	70	80	90	100	PI/2 BPSK	QPSK	16 QAM	64 QAM	256 QAM	1	Full	L	
Radiated Spurious Emission	n5A- n78A	Worst Case																	v		Y		
	n7A- n78A	Worst Case																	v		Y		
	n71A- n78A	Worst Case																	v		Y		
	n41A- n71A	Worst Case																	v		Y		
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																						

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m



2.4 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3



5G NR n5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	166800	167300	167800
	Frequency	834	836.5	839
15	Channel	166300	167300	168300
	Frequency	831.5	836.5	841.5
10	Channel	165800	167300	168800
	Frequency	829	836.5	844
5	Channel	165300	167300	169300
	Frequency	826.5	836.5	846.5

5G NR n7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
50	Channel	505000	507000	509000
	Frequency	2525	2535	2545
40	Channel	504000	507000	510000
	Frequency	2520	2535	2550
35	Channel	503500	507000	510500
	Frequency	2517.5	2535	2552.5
30	Channel	503000	507000	511000
	Frequency	2515	2535	2555
25	Channel	502500	507000	511500
	Frequency	2512.5	2535	2557.5
20	Channel	502000	507000	512000
	Frequency	2510	2535	2560
15	Channel	501500	507000	512500
	Frequency	2507.5	2535	2562.5
10	Channel	501000	507000	513000
	Frequency	2505	2535	2565
5	Channel	500500	507000	513500
	Frequency	2502.5	2535	2567.5



5G NR n41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	509202	518598	528000
	Frequency	2546.01	2592.99	2640
90	Channel	508200	518598	528996
	Frequency	2541	2592.99	2644.98
80	Channel	507204	518598	529998
	Frequency	2536.02	2592.99	2649.99
70	Channel	506202	518598	531000
	Frequency	2531.01	2592.99	2655
60	Channel	505200	518598	531996
	Frequency	2526	2592.99	2659.98
50	Channel	504204	518598	532998
	Frequency	2521.02	2592.99	2664.99
45	Channel	503700	518598	533496
	Frequency	2518.5	2592.99	2667.48
40	Channel	503202	518598	534000
	Frequency	2516.01	2592.99	2670
35	Channel	502704	518598	534498
	Frequency	2513.52	2592.99	2672.49
30	Channel	502200	518598	534996
	Frequency	2511	2592.99	2674.98
25	Channel	501702	518598	535500
	Frequency	2508.51	2592.99	2677.5
20	Channel	501204	518598	535998
	Frequency	2506.02	2592.99	2679.99
15	Channel	500700	518598	536496
	Frequency	2503.5	2592.99	2682.48
10	Channel	500202	518598	537000
	Frequency	2501.01	2592.99	2685



5G NR n71 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	134600	136100	137600
	Frequency	673	680.5	688
15	Channel	134100	136100	138100
	Frequency	670.5	680.5	690.5
10	Channel	133600	136100	138600
	Frequency	668	680.5	693
5	Channel	133100	136100	139100
	Frequency	665.5	680.5	695.5

5G n78 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	650000		
	Frequency	3750		
90	Channel	649668	650000	650332
	Frequency	3745.02	3750	3754.98
80	Channel	649334	650000	650666
	Frequency	3740.01	3750	3759.99
70	Channel	649000	650000	651000
	Frequency	3735	3750	3765
60	Channel	648668	650000	651332
	Frequency	3730.02	3750	3769.98
50	Channel	648334	650000	651666
	Frequency	3725.01	3750	3774.99
40	Channel	648000	650000	652000
	Frequency	3720	3750	3780
30	Channel	647668	650000	652332
	Frequency	3715.02	3750	3784.98
25	Channel	647500	650000	652500
	Frequency	3712.5	3750	3787.5
20	Channel	647334	650000	652666
	Frequency	3710.01	3750	3789.99
15	Channel	647168	650000	652832
	Frequency	3707.52	3750	3792.48
10	Channel	647000	650000	653000
	Frequency	3705	3750	3795


3 Radiated Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 For radiated test below 30MHz



3.2.2 For radiated test from 30MHz to 1GHz



3.2.3 For radiated test above 1GHz



3.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix A.



3.4 Radiated Spurious Emission

3.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7, 5G NR n7, n41,

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11. $ERP (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2024	Feb. 19, 2025	Jul. 02, 2025	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Feb. 19, 2025	Dec. 27, 2025	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Feb. 19, 2025	Oct. 23, 2025	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Feb. 19, 2025	Jul. 04, 2025	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2024	Feb. 19, 2025	Jul. 03, 2025	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 09, 2024	Feb. 19, 2025	Apr. 08, 2025	Radiation (03CH02-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 18, 2024	Feb. 19, 2025	Oct. 17, 2025	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 14, 2024	Feb. 19, 2025	Oct. 13, 2025	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 18, 2024	Feb. 19, 2025	Oct. 17, 2025	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Feb. 19, 2025	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Feb. 19, 2025	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.47dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.31dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.72dB
---	--------



Appendix A. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Kuang Jia	Temperature :	22~25°C
		Relative Humidity :	48~52%

Pre-scanned harmonic for the different antenna combinations, we choose the worst antenna mode to perform final test and record in the report.

ULCA_2A-4A (ANT2+1)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742	-61.70	-13	-48.70	-80.28	-68.45	5.85	12.60	H
	5613	-57.70	-13	-44.70	-80.09	-63.50	7.30	13.10	H
	7484	-54.98	-13	-41.98	-81.91	-58.13	8.35	11.50	H
	3742	-61.84	-13	-48.84	-80.34	-68.59	5.85	12.60	V
	5613	-56.93	-13	-43.93	-79.51	-62.73	7.30	13.10	V
	7484	-54.92	-13	-41.92	-81.84	-58.07	8.35	11.50	V
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447	-57.27	-13	-44.27	-74.04	-64.12	5.65	12.50	H
	5170.5	-59.82	-13	-46.82	-81.65	-65.49	7.13	12.80	H
	6894	-56.86	-13	-43.86	-82.43	-60.26	8.40	11.80	H
	3447	-58.85	-13	-45.85	-75.66	-65.70	5.65	12.50	V
	5170.5	-60.64	-13	-47.64	-82.74	-66.31	7.13	12.80	V
	6894	-56.54	-13	-43.54	-82.59	-59.94	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_2A-5A (ANT2+1)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742	-60.05	-13	-47.05	-78.63	-66.80	5.85	12.60	H
	5613	-58.53	-13	-45.53	-80.92	-64.33	7.30	13.10	H
	7484	-54.31	-13	-41.31	-81.24	-57.46	8.35	11.50	H
	3742	-57.61	-13	-44.61	-76.11	-64.36	5.85	12.60	V
	5613	-56.70	-13	-43.70	-79.28	-62.50	7.30	13.10	V
	7484	-54.40	-13	-41.40	-81.32	-57.55	8.35	11.50	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664	-65.32	-13	-52.32	-75.26	-68.57	4.00	9.40	H
	2496	-62.73	-13	-49.73	-77.17	-66.30	4.88	10.60	H
	3328	-62.20	-13	-49.20	-78.36	-67.13	5.52	12.60	H
	1664	-65.88	-13	-52.88	-75.42	-69.13	4.00	9.40	V
	2496	-62.50	-13	-49.50	-76.90	-66.07	4.88	10.60	V
	3328	-62.23	-13	-49.23	-78.15	-67.16	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_2A-66A (ANT2+1)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742	-62.17	-13	-49.17	-80.75	-68.92	5.85	12.60	H
	5613	-57.76	-13	-44.76	-80.15	-63.56	7.30	13.10	H
	7484	-55.24	-13	-42.24	-82.17	-58.39	8.35	11.50	H
	3742	-61.87	-13	-48.87	-80.37	-68.62	5.85	12.60	V
	5613	-58.01	-13	-45.01	-80.59	-63.81	7.30	13.10	V
	7484	-55.13	-13	-42.13	-82.05	-58.28	8.35	11.50	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-56.57	-13	-43.57	-73.47	-63.42	5.65	12.50	H
	5208	-59.59	-13	-46.59	-81.32	-65.26	7.13	12.80	H
	6944	-56.94	-13	-43.94	-82.86	-60.34	8.40	11.80	H
	3472	-59.44	-13	-46.44	-76.36	-66.29	5.65	12.50	V
	5208	-61.18	-13	-48.18	-83.16	-66.85	7.13	12.80	V
	6944	-56.26	-13	-43.26	-82.65	-59.66	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_2A-7A (ANT2+9)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742	-61.68	-13	-48.68	-80.26	-68.43	5.85	12.60	H
	5613	-56.96	-13	-43.96	-79.35	-62.76	7.30	13.10	H
	7484	-55.18	-13	-42.18	-82.11	-58.33	8.35	11.50	H
	3742	-61.76	-13	-48.76	-80.26	-68.51	5.85	12.60	V
	5613	-55.30	-13	-42.30	-77.88	-61.10	7.30	13.10	V
	7484	-54.60	-13	-41.60	-81.52	-57.75	8.35	11.50	V
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.00	-58.56	-25	-33.56	-80.57	-64.12	7.14	12.70	H
	7578.00	-53.76	-25	-28.76	-80.41	-57.06	8.30	11.60	H
	10104.00	-50.69	-25	-25.69	-82.10	-52.21	10.48	12.00	H
	5052.00	-57.03	-25	-32.03	-79.16	-62.59	7.14	12.70	V
	7578.00	-54.24	-25	-29.24	-80.85	-57.54	8.30	11.60	V
	10104.00	-52.25	-25	-27.25	-82.26	-53.77	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_4A-5A (ANT2+0)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447	-59.13	-13	-46.13	-75.90	-65.98	5.65	12.50	H
	5170.5	-59.00	-13	-46.00	-80.83	-64.67	7.13	12.80	H
	6894	-57.06	-13	-44.06	-82.63	-60.46	8.40	11.80	H
	3447	-60.31	-13	-47.31	-77.12	-67.16	5.65	12.50	V
	5170.5	-60.11	-13	-47.11	-82.21	-65.78	7.13	12.80	V
	6894	-56.59	-13	-43.59	-82.64	-59.99	8.40	11.80	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664	-65.69	-13	-52.69	-75.63	-68.94	4.00	9.40	H
	2496	-62.96	-13	-49.96	-77.40	-66.53	4.88	10.60	H
	3328	-62.72	-13	-49.72	-78.88	-67.65	5.52	12.60	H
	1664	-66.02	-13	-53.02	-75.56	-69.27	4.00	9.40	V
	2496	-63.13	-13	-50.13	-77.53	-66.70	4.88	10.60	V
	3328	-62.89	-13	-49.89	-78.81	-67.82	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_4A-7A (ANT2+9)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447	-61.27	-13	-48.27	-78.04	-68.12	5.65	12.50	H
	5170.5	-59.44	-13	-46.44	-81.27	-65.11	7.13	12.80	H
	6894	-55.89	-13	-42.89	-81.46	-59.29	8.40	11.80	H
	3447	-61.16	-13	-48.16	-77.97	-68.01	5.65	12.50	V
	5170.5	-59.43	-13	-46.43	-81.53	-65.10	7.13	12.80	V
	6894	-55.43	-13	-42.43	-81.48	-58.83	8.40	11.80	V
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.00	-59.95	-25	-34.95	-81.96	-65.51	7.14	12.70	H
	7578.00	-53.88	-25	-28.88	-80.53	-57.18	8.30	11.60	H
	10104.00	-49.34	-25	-24.34	-80.75	-50.86	10.48	12.00	H
	5052.00	-59.76	-25	-34.76	-81.89	-65.32	7.14	12.70	V
	7578.00	-54.04	-25	-29.04	-80.65	-57.34	8.30	11.60	V
	10104.00	-50.83	-25	-25.83	-80.84	-52.35	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_5A-7A (ANT0+9)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664	-65.51	-13	-52.51	-75.45	-68.76	4.00	9.40	H
	2496	-62.26	-13	-49.26	-76.70	-65.83	4.88	10.60	H
	3328	-62.60	-13	-49.60	-78.76	-67.53	5.52	12.60	H
	1664	-66.26	-13	-53.26	-75.80	-69.51	4.00	9.40	V
	2496	-62.67	-13	-49.67	-77.07	-66.24	4.88	10.60	V
	3328	-62.94	-13	-49.94	-78.86	-67.87	5.52	12.60	V
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.00	-57.64	-25	-32.64	-79.65	-63.20	7.14	12.70	H
	7578.00	-53.09	-25	-28.09	-79.74	-56.39	8.30	11.60	H
	10104.00	-50.26	-25	-25.26	-81.67	-51.78	10.48	12.00	H
	5052.00	-56.65	-25	-31.65	-78.78	-62.21	7.14	12.70	V
	7578.00	-53.66	-25	-28.66	-80.27	-56.96	8.30	11.60	V
	10104.00	-51.66	-25	-26.66	-81.67	-53.18	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_5A-66A (ANT0+2)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA. Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664	-65.59	-13	-52.59	-75.53	-68.84	4.00	9.40	H
	2496	-62.81	-13	-49.81	-77.25	-66.38	4.88	10.60	H
	3328	-61.35	-13	-48.35	-77.51	-66.28	5.52	12.60	H
	1664	-66.12	-13	-53.12	-75.66	-69.37	4.00	9.40	V
	2496	-62.99	-13	-49.99	-77.39	-66.56	4.88	10.60	V
	3328	-61.95	-13	-48.95	-77.87	-66.88	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-55.78	-13	-42.78	-72.68	-62.63	5.65	12.50	H
	5208	-58.67	-13	-45.67	-80.40	-64.34	7.13	12.80	H
	6944	-55.15	-13	-42.15	-81.07	-58.55	8.40	11.80	H
	3472	-57.69	-13	-44.69	-74.61	-64.54	5.65	12.50	V
	5208	-59.64	-13	-46.64	-81.62	-65.31	7.13	12.80	V
	6944	-55.06	-13	-42.06	-81.45	-58.46	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_n5A- n78A (ANT0+7)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n5 BW 20MHz Middle 1RB0,QPSK	1655	-65.77	-13	-52.77	-75.70	-69.02	4.00	9.40	H
	2482.5	-62.87	-13	-49.87	-77.36	-66.44	4.88	10.60	H
	3310	-61.65	-13	-48.65	-77.98	-66.58	5.52	12.60	H
	1655	-66.08	-13	-53.08	-75.61	-69.33	4.00	9.40	V
	2482.5	-62.85	-13	-49.85	-77.31	-66.42	4.88	10.60	V
	3310	-62.04	-13	-49.04	-78.15	-66.97	5.52	12.60	V
NR n78 BW 100MHz Middle 1RB0,QPSK	7404.00	-55.96	-13	-42.96	-55.07	-59.26	8.30	11.60	H
	11106.00	-49.26	-13	-36.26	-54.59	-50.78	10.48	12.00	H
	14808.00	-50.09	-13	-37.09	-60.36	-51.79	11.80	13.50	H
	7404.00	-56.92	-13	-43.92	-56.05	-60.22	8.30	11.60	V
	11106.00	-52.98	-13	-39.98	-58.02	-54.50	10.48	12.00	V
	14808.00	-50.98	-13	-37.98	-60.70	-52.68	11.80	13.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_n7A- n78A (ANT2+7)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n7 BW 50MHz Middle 1RB0,QPSK	5022.00	-59.55	-25	-34.55	-81.58	-65.11	7.14	12.70	H
	7533.00	-54.65	-25	-29.65	-53.39	-57.95	8.30	11.60	H
	10044.00	-55.93	-25	-30.93	-57.97	-57.45	10.48	12.00	H
	5022.00	-59.34	-25	-34.34	-81.46	-64.90	7.14	12.70	V
	7533.00	-53.99	-25	-28.99	-52.71	-57.29	8.30	11.60	V
	10044.00	-57.39	-25	-32.39	-57.87	-58.91	10.48	12.00	V
NR n78 BW 100MHz Middle 1RB0,QPSK	7404.00	-57.51	-13	-44.51	-56.62	-60.81	8.30	11.60	H
	11106.00	-51.56	-13	-38.56	-56.89	-53.08	10.48	12.00	H
	14808.00	-50.08	-13	-37.08	-60.35	-51.78	11.80	13.50	H
	7404.00	-57.01	-13	-44.01	-56.14	-60.31	8.30	11.60	V
	11106.00	-53.74	-13	-40.74	-58.78	-55.26	10.48	12.00	V
	14808.00	-50.64	-13	-37.64	-60.36	-52.34	11.80	13.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_ n71A- n78A (ANT0+7)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n71 BW 20MHz Middle 1RB0,QPSK	1343	-65.31	-13	-52.31	-75.70	-75.37	4.00	9.40	H
	2014.5	-65.07	-13	-52.07	-77.36	-76.43	4.88	10.60	H
	2686	-62.12	-13	-49.12	-77.98	-77.37	5.52	12.60	H
	1343	-65.77	-13	-52.77	-75.61	-75.46	4.00	9.40	V
	2014.5	-65.41	-13	-52.41	-77.31	-76.66	4.88	10.60	V
	2686	-62.20	-13	-49.20	-78.15	-77.47	5.52	12.60	V
NR n78 BW 100MHz Middle 1RB0,QPSK	7404.00	-58.17	-13	-45.17	-57.28	-61.47	8.30	11.60	H
	11106.00	-52.65	-13	-39.65	-57.98	-54.17	10.48	12.00	H
	14808.00	-50.34	-13	-37.34	-60.61	-52.04	11.80	13.50	H
	7404.00	-56.57	-13	-43.57	-55.7	-59.87	8.30	11.60	V
	11106.00	-55.07	-13	-42.07	-60.11	-56.59	10.48	12.00	V
	14808.00	-50.78	-13	-37.78	-60.50	-52.48	11.80	13.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_ n41A- n71A (ANT9+0)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
NR n41 BW 100MHz Middle 1RB0,QPSK	5090.00	-58.95	-25	-33.95	-80.87	-64.51	7.14	12.70	H
	7635.00	-52.08	-25	-27.08	-78.72	-55.38	8.30	11.60	H
	10180.00	-49.38	-25	-24.38	-80.69	-50.90	10.48	12.00	H
	5090.00	-55.38	-25	-30.38	-77.48	-60.94	7.14	12.70	V
	7635.00	-51.02	-25	-26.02	-77.58	-54.32	8.30	11.60	V
	10180.00	-50.34	-25	-25.34	-80.4	-51.86	10.48	12.00	V
NR n71 BW 20MHz Middle 1RB0,QPSK	1343	-64.56	-13	-51.56	-75.70	-74.62	4.00	9.40	H
	2014.5	-64.44	-13	-51.44	-77.36	-75.80	4.88	10.60	H
	2686	-61.37	-13	-48.37	-77.98	-76.62	5.52	12.60	H
	1343	-65.19	-13	-52.19	-75.61	-74.88	4.00	9.40	V
	2014.5	-64.76	-13	-51.76	-77.31	-76.01	4.88	10.60	V
	2686	-58.75	-13	-45.75	-78.15	-74.02	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.