

# FCC TEST REPORT

**Name of Sample:** Mobile Cellular Phone  
**Model of Sample:** XT2507-1  
**Applicant:** Motorola Mobility LLC  
**Issue Date:** 2025-03-11



**ADR TEST AND CERTIFICATION CENTER**  
**Motorola Mobility LLC, a Lenovo Company**

**Add: No. 19, Gao Xin 4th Road Wuhan, People's Republic of China 430205**

**Phone: (86) 13696970830**

**E-mail: [suyj3@motorola.com](mailto:suyj3@motorola.com)**

<b>Name of Client</b>	Motorola Mobility LLC		
<b>Address of Client</b>	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA		
<b>Trademark</b>	Motorola	<b>Type Name or ID</b>	FCC ID: IHDT56AU3
<b>Applicant No.</b>	RF187831	<b>Sample No.</b>	1#: NEPR270108 2#: NEPR270117
<b>Delivering Date</b>	2025-01-13	<b>Test Date</b>	2025-01-15 to 2025-03-11
<b>Sample Illustration</b>	None		
<b>Standard</b>	47 CFR Part 2; 47 CFR Part 22; 47 CFR Part 24; 47 CFR Part 27; 47 CFR Part 90;		
<b>Conclusion</b>	Pass		
<b>Remarks</b>	N/A		

**Editor:** Wangzhenyu

**Reviewer:** Hexiaolin

**Signatory:** HuangshengLin

*Wangzhenyu*

*Hexiaolin*

*Eric Lin*

### Matters Needing Attention

- a) The electronic report shall be valid after encryption.
- b) The paper report shall be valid after being stamped with the official seal of the company.
- c) The report is invalid without the signature of the Editor, Reviewer and Signatory.
- d) The test report is invalid if there is any evidence of erasure and/or falsification.
- e) If there is any dissidence for the test report, please file objection to the lab within 15 days from the date of receiving the test report.
- f) The test report is only responsible for the tested model/sample. The sample(s) presented in this report are provided by client.
- g) Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the lab.

### Revision History

Report No.	Version	Description	Issued Date
TR-25ADRTCC7004	Rev.01	Initial issue of report	2025-02-21
TR-25ADRTCC7004	Rev.02	1, Update n38A Ant1 Gain to -4.00dBi. 2, Add n41 UL MMO data. 3, Add n77/n78 Ant10 EIRP.	2025-03-11
TR-25ADRTCC7004	Rev.03	1, Add other PA description on Page7.	2025-03-11
TR-25ADRTCC7004	Rev.04	1, Add n41 UL MIMO test antenna description on Page7.	2025-03-12
TR-25ADRTCC7004	Rev.05	Update appendix list on page25.	2025-03-28

# Catalogue

- 1. TEST SUMMARY ..... 5**
  - 1.1. 5G NR BAND N2 ..... 5
  - 1.2. 5G NR BAND N5/N26 ..... 5
  - 1.3. 5G NR BAND N26 (814-824) ..... 5
  - 1.4. 5G NR BAND N7/N38/N41 ..... 6
  - 1.5. 5G NR BAND N66 ..... 6
  - 1.6. 5G NR BAND N71 ..... 7
  - 1.7. 5G NR BAND N77 (3700-3980)/N78 (3700-3800) ..... 7
- 2. MAXIMUM EFFECTIVE RADIATED (ISOTROPIC) POWER AND EMISSION DESIGNATOR ..... 8**
  - 2.1. NR SYSTEM ..... 8
- 3. GENERAL INFORMATION ..... 14**
  - 3.1. GENERAL DESCRIPTION OF EUT ..... 14
  - 3.2. TEST ENVIRONMENT ..... 14
  - 3.3. SPECIFICATION OF ACCESSORIES ..... 14
- 4. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 15**
  - 4.1. TEST MODE FOR NR CONFIGURATION ..... 15
  - 4.2. TEST FREQUENCIES ..... 17
- 5. DESCRIPTION OF TESTS ..... 20**
  - 5.1. CONDUCTED OUTPUT POWER MEASUREMENT ..... 20
  - 5.2. EFFECTIVE (ISOTROPIC) RADIATED POWER ..... 20
  - 5.3. PEAK-TO-AVERAGE RATIO MEASUREMENT ..... 21
  - 5.4. 99% OCCUPIED BANDWIDTH & 26DB EMISSION BANDWIDTH ..... 21
  - 5.5. CONDUCTED BAND EDGE MEASUREMENT ..... 22
  - 5.6. CONDUCTED SPURIOUS EMISSION MEASUREMENT ..... 23
  - 5.7. FREQUENCY STABILITY MEASUREMENT ..... 23
- 6. LIST OF MEASURING EQUIPMENT ..... 24**
- 7. MEASUREMENT UNCERTAINTY ..... 24**
  - 7.1. UNCERTAINTY OF CONDUCTED MEASUREMENT ..... 24
- 8. APPENDIXES ..... 25**

## 1. Test Summary

### 1.1. 5G NR Band n2

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Isotropic Radiated Power	§24.232(c)	EIRP < 2W		
Peak-Average Ratio	§24.232(d)	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §24.238(a)	< -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §24.238(a)	< -13 dBm/MHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
Frequency Stability	§24.235	< ±2.5 ppm	Section 7 of Appendix B	Pass

### 1.2. 5G NR Band n5/n26

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Radiated Power	§22.913(a)(5)	ERP < 7W		
Peak-Average Ratio	§22.913(d)	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §22.917(a)	< -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §22.917(a)	< -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges	Section 6 of Appendix B	Pass
Frequency Stability	§2.1055 §22.355	< ±2.5ppm	Section 7 of Appendix B	Pass

### 1.3. 5G NR Band n26 (814-824)

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046 §90.635	Report Only	Section 1 of Appendix B	PASS
Peak-Average Ratio	---	<13 dB	Section 2 of Appendix B	PASS
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	PASS
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	PASS
26dB Emission Bandwidth		No limit		
Emission Mask	§2.1051 § 90.691	For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log <sub>10</sub> (f/6.1) decibels or 50+10Log <sub>10</sub> (P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the	Section 5 of Appendix B	PASS

Test Item	Rule No.	Requirements	Test Result	Verdict
		center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.		
Conducted Spurious Emission	§2.1051 §90.691	< 43 + 10Log10(P[Watts]) for all out-of-band emissions	Section 6 of Appendix B	PASS
Frequency Stability	§90.213	< ±2.5ppm	Section 7 of Appendix B	PASS

#### 1.4. 5G NR Band n7/n38/n41

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Isotropic Radiated Power	§27.50(h) (2)	EIRP < 2W		
Peak-Average Ratio	§27.50(a)	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §27.53(m) (4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section In addition, the attenuation factor shall not be less than 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5MHz.	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §27.53(m) (4)	< -25 dBm/MHz for outside Band Edge Range	Section 6 of Appendix B	Pass
Frequency Stability	§27.54	Within authorized bands	Section 7 of Appendix B	Pass

#### 1.5. 5G NR Band n66

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Isotropic Radiated Power	§27.50(d)	EIRP < 1W		
Peak-Average Ratio	---	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §27.53(h)	< -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §27.53(h)	< -13 dBm/MHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges	Section 6 of Appendix B	Pass
Frequency Stability	§27.54	Within authorized bands	Section 7 of Appendix B	Pass

**1.6. 5G NR Band n71**

Test Item	Rule No	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Radiated Power	§27.50(c)(10)	ERP < 3W		
Peak-Average Ratio	---	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §27.53(g)	< -13 dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to the frequency block	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §27.53(g)	< -13 dBm/100kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges	Section 6 of Appendix B	Pass
Frequency Stability	§27.54	Within authorized bands	Section 7 of Appendix B	Pass

**1.7. 5G NR Band n77 (3700-3980)/n78 (3700-3800)**

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Isotropic Radiated Power	§27.50(j) (3)	EIRP < 1W		
Peak-Average Ratio	§27.50(j) (4)	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §27.53(l) (2)	< -13 dBm/MHz	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §27.53(l) (2)	< -13 dBm/MHz	Section 6 of Appendix B	Pass
Frequency Stability	§27.54	Within authorized bands	Section 7 of Appendix B	Pass

## Remark:

- Only 5G NR Bands conducted test performed and the data displayed in this report, the radiated spurious emission refer to the report (FG510906H).
- The device support two PAs for 5G NR (Main PA and other PA), both PAs were evaluated, but only the worst band data displayed in this report. The SA mode for n2/n5/n7/n26/n38/n41/n66/n71/n77/n78 and NSA mode for n5/n26/n71/n77/n78 worked with the main PA, and NSA mode for n2/n7/n38/n41/n66 worked with the other PA.
- The maximum E(I)RP is calculated from max output power and max antenna gain, only the max E(I)RP data displayed in this report, n5/n26/n71 for Antenna 0; n2/n7/n38/n41/n66 for Antenna 2; n77/n78 for antenna 7;
- n41 UL MIMO support Ant1+Ant2/Ant9+Ant0/Ant9+Ant1, according to the max power, only Ant1+Ant2 combination was fully evaluated and the data displayed in this report
- 5G NR Bands support SA mode for n2/n5/n7/n26/n38/n41/n66/n71/n77/n78 and NSA mode for n2/n5/n7/n38/n41/n66/n77/n78.
- The test has been assessed on SA and NSA mode, but only the worst mode performed the whole conducted test items by referring to the max conducted power.
- The ENDC combination could be referred to the product specification.
- 5G NR n77/n78 supports HPUE mode.

## 2. Maximum Effective Radiated (Isotropic) Power and Emission Designator

### 2.1. NR System

#### 2.1.1. NR Band n2 (1850-1910)

5G SA (n2A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
5MHz	1852.5-1907.5	0.092257	4M48G7D	0.074302	4M48W7D
10MHz	1855.0-1905.0	0.092897	9M29G7D	0.075858	9M29W7D
15MHz	1857.5-1902.5	0.092470	14M1G7D	0.075683	14M2W7D
20MHz	1860.0-1900.0	0.092045	18M9G7D	0.076208	18M9W7D
25MHz	1862.5-1897.5	0.092683	23M7G7D	0.073114	23M7W7D
30MHz	1865.0-1895.0	0.092045	28M6G7D	0.074817	28M7W7D
35MHz	1867.5-1892.5	0.091201	33M6G7D	0.076736	33M7W7D
40MHz	1870.0-1890.0	0.092897	38M6G7D	0.075509	38M6W7D

5G NR NSA (DC_66A_n2A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
5MHz	1852.5-1907.5	0.094406	4M48G7D	0.076560	4M48W7D
10MHz	1855.0-1905.0	0.093111	9M29G7D	0.079068	9M29W7D
15MHz	1857.5-1902.5	0.093972	14M1G7D	0.076208	14M2W7D
20MHz	1860.0-1900.0	0.093325	18M9G7D	0.078705	18M9W7D
25MHz	1862.5-1897.5	0.094842	23M8G7D	0.077446	23M8W7D
30MHz	1865.0-1895.0	0.094406	28M6G7D	0.078705	28M6W7D
35MHz	1867.5-1892.5	0.092683	33M6G7D	0.079250	33M6W7D
40MHz	1870.0-1890.0	0.092470	38M6G7D	0.079250	38M6W7D

#### 2.1.2. NR Band n5 (824-849)

5G NR SA (n5A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum ERP (W)	Emission Designator (99% OBW)	Maximum ERP (W)	Emission Designator (99% OBW)
5MHz	826.5-846.5	0.030269	4M49G7D	0.023768	4M48W7D
10MHz	829.0-844.0	0.029717	9M29G7D	0.024491	9M29W7D
15MHz	831.5-841.5	0.029717	14M1G7D	0.024322	14M1W7D
20MHz	834.0-839.0	0.029717	18M9G7D	0.024210	19M0W7D

## 2.1.3. NR Band n7 (2500-2570)

5G NR SA (n7A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum ERP (W)	Emission Designator (99% OBW)	Maximum ERP (W)	Emission Designator (99% OBW)
5MHz	2502.5-2567.5	0.112720	4M49G7D	0.099312	4M48W7D
10MHz	2505.0-2565.0	0.112460	9M27G7D	0.099541	9M29W7D
15MHz	2507.5-2562.5	0.113501	14M1G7D	0.097949	14M2W7D
20MHz	2510.0-2560.0	0.114551	18M9G7D	0.099541	18M9W7D
25MHz	2512.5-2557.5	0.115878	23M8G7D	0.097724	23M7W7D
30MHz	2515.0-2555.0	0.116681	28M6G7D	0.097724	28M5W7D
35MHz	2517.5-2552.5	0.114551	33M6G7D	0.096383	33M6W7D
40MHz	2520.0-2550.0	0.117220	38M5G7D	0.098628	38M5W7D
50MHz	2525.0-2545.0	0.118032	48M3G7D	0.099312	48M3W7D

5G NR NSA (DC_66A_n7A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum ERP (W)	Emission Designator (99% OBW)	Maximum ERP (W)	Emission Designator (99% OBW)
5MHz	2502.5-2567.5	0.090157	4M48G7D	0.077625	4M48W7D
10MHz	2505.0-2565.0	0.089331	9M27G7D	0.097499	9M29W7D
15MHz	2507.5-2562.5	0.094842	14M1G7D	0.076913	14M2W7D
20MHz	2510.0-2560.0	0.087700	18M9G7D	0.099541	18M9W7D
25MHz	2512.5-2557.5	0.092683	23M8G7D	0.097499	23M8W7D
30MHz	2515.0-2555.0	0.090365	28M5G7D	0.078886	28M6W7D
35MHz	2517.5-2552.5	0.092257	33M6G7D	0.078705	33M6W7D
40MHz	2520.0-2550.0	0.092470	38M6G7D	0.079250	38M6W7D
50MHz	2525.0-2545.0	0.090573	48M2G7D	0.078524	48M3W7D

## 2.1.4. NR Band n26 (814-824)

5G NR SA (n26A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum Conducted Power (W)	Emission Designator (99% OBW)	Maximum Conducted Power (W)	Emission Designator (99% OBW)
5MHz	816.5-821.5	0.215278	4M50G7D	0.174181	4M47W7D
10MHz	819.0	0.214289	9M27G7D	0.176604	9M29W7D
15MHz	821.5	0.211349	14M1G7D	0.174985	14M1W7D
20MHz	824.0	0.211836	18M9G7D	0.176604	18M9W7D

**2.1.5. NR Band n26 (824-849)**

5G NR SA (n26A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum ERP (W)	Emission Designator (99% OBW)	Maximum ERP (W)	Emission Designator (99% OBW)
5MHz	826.5-846.5	0.033497	4M49G7D	0.026546	4M48W7D
10MHz	829.0-844.0	0.032659	9M29G7D	0.027290	9M29W7D
15MHz	831.5-841.5	0.032584	14M1G7D	0.027102	14M2W7D
20MHz	834.0-839.0	0.032509	18M9G7D	0.026363	18M9W7D

**2.1.6. NR Band n38 (2570-2620)**

5G NR SA (n38A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	2575.0-2615.0	0.117761	8M59G7D	0.095280	8M59W7D
15MHz	2577.5-2612.5	0.119124	13M6G7D	0.097499	13M7W7D
20MHz	2580.0-2610.0	0.108143	18M2G7D	0.098628	18M2W7D
25MHz	2582.5-2607.5	0.103753	23M1G7D	0.096161	23M2W7D
30MHz	2585.0-2605.0	0.118304	27M8G7D	0.098401	27M9W7D
40MHz	2590.0-2600.0	0.115878	37M8G7D	0.091411	37M9W7D

5G NR NSA (DC_66A_n38A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	2575.0-2615.0	0.117220	8M59G7D	0.099083	8M59W7D
15MHz	2577.5-2612.5	0.116950	13M6G7D	0.098628	13M6W7D
20MHz	2580.0-2610.0	0.117490	18M2G7D	0.098401	18M2W7D
25MHz	2582.5-2607.5	0.118577	23M1G7D	0.097724	23M2W7D
30MHz	2585.0-2605.0	0.119399	27M8G7D	0.099312	27M9W7D
40MHz	2590.0-2600.0	0.118032	37M8G7D	0.097949	37M9W7D

2.1.7. NR Band n41 (2496-2690)

5G NR SA (n41A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	2501.01-2685.00	0.105439	8M57G7D	0.098855	8M59W7D
15MHz	2503.50-2682.48	0.116950	13M6G7D	0.097499	13M6W7D
20MHz	2506.02-2679.99	0.112202	18M2G7D	0.097724	18M2W7D
25MHz	2508.50-2677.50	0.112202	23M2G7D	0.095940	23M3W7D
30MHz	2511.00-2674.98	0.111944	27M8G7D	0.097051	27M9W7D
35MHz	2513.50-2672.50	0.113763	32M9G7D	0.097499	32M9W7D
40MHz	2516.01-2670.00	0.118577	37M8G7D	0.099541	37M9W7D
45MHz	2518.50-2667.50	0.119124	42M4G7D	0.097724	42M5W7D
50MHz	2521.02-2664.99	0.117490	47M5G7D	0.098855	47M5W7D
60MHz	2526.00-2659.98	0.119674	57M8G7D	0.098175	58M0W7D
70MHz	2531.01-2655.00	0.120504	67M4G7D	0.098175	67M4W7D
80MHz	2536.02-2649.99	0.118577	77M4G7D	0.098628	77M4W7D
90MHz	2541.00-2644.98	0.125026	87M2G7D	0.099312	87M2W7D
100MHz	2546.01-2640.00	0.125314	97M1G7D	0.099541	97M3W7D

5G NR SA (n41A UL MIMO)		QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	2501.01-2685.00	0.076736	8M57G7D	0.068865	8M57W7D
15MHz	2503.50-2682.48	0.076033	13M6G7D	0.069343	13M6W7D
20MHz	2506.02-2679.99	0.076208	18M2G7D	0.068234	18M2W7D
25MHz	2508.50-2677.50	0.075683	23M2G7D	0.067920	23M3W7D
30MHz	2511.00-2674.98	0.076033	27M8G7D	0.069024	27M9W7D
35MHz	2513.50-2672.50	0.074989	32M8G7D	0.068707	32M9W7D
40MHz	2516.01-2670.00	0.074989	37M8G7D	0.070469	37M8W7D
45MHz	2518.50-2667.50	0.074989	42M4G7D	0.068234	42M6W7D
50MHz	2521.02-2664.99	0.074989	47M4G7D	0.067920	47M5W7D
60MHz	2526.00-2659.98	0.074302	57M9G7D	0.067920	57M8W7D
70MHz	2531.01-2655.00	0.077446	67M4G7D	0.069343	67M6W7D
80MHz	2536.02-2649.99	0.077090	77M2G7D	0.069823	77M5W7D
90MHz	2541.00-2644.98	0.076208	87M4G7D	0.069024	87M6W7D
100MHz	2546.01-2640.00	0.075683	97M3G7D	0.068549	97M3W7D

5G NR NSA (DC_66A_n41A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	2501.01-2685.00	0.096605	8M57G7D	0.078524	8M59W7D
15MHz	2503.50-2682.48	0.092045	13M6G7D	0.078524	13M7W7D
20MHz	2506.02-2679.99	0.092470	18M2G7D	0.078163	18M2W7D
25MHz	2508.50-2677.50	0.095499	23M2G7D	0.079068	23M2W7D
30MHz	2511.00-2674.98	0.090782	27M8G7D	0.078705	27M9W7D
35MHz	2513.50-2672.50	0.094189	32M9G7D	0.078524	32M9W7D
40MHz	2516.01-2670.00	0.091622	37M8G7D	0.079250	37M8W7D
45MHz	2518.50-2667.50	0.093111	42M4G7D	0.079068	42M5W7D
50MHz	2521.02-2664.99	0.093541	47M5G7D	0.077446	47M5W7D
60MHz	2526.00-2659.98	0.096383	58M0G7D	0.076913	58M0W7D
70MHz	2531.01-2655.00	0.096383	67M6G7D	0.077804	67M4W7D
80MHz	2536.02-2649.99	0.097275	77M4G7D	0.077804	77M4W7D
90MHz	2541.00-2644.98	0.098855	87M4G7D	0.078524	87M4W7D
100MHz	2546.01-2640.00	0.098175	97M3G7D	0.077446	97M3W7D

### 2.1.1. NR Band n66 (1710-1780)

5G NR SA (n66A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
5MHz	1712.5-1777.5	0.115080	4M49G7D	0.099312	4M48W7D
10MHz	1715.0-1775.0	0.118577	9M29G7D	0.097275	9M37W7D
15MHz	1717.5-1772.5	0.118577	14M1G7D	0.099541	14M2W7D
20MHz	1720.0-1770.0	0.117490	18M9G7D	0.096828	18M9W7D
25MHz	1722.5-1767.5	0.116681	23M7G7D	0.094624	23M7W7D
30MHz	1725.0-1765.0	0.115611	28M6G7D	0.095719	28M5W7D
35MHz	1727.5-1762.5	0.114815	33M5G7D	0.095060	33M6W7D
40MHz	1730.0-1760.0	0.115080	38M5G7D	0.096161	38M5W7D

5G NR NSA (DC_7A_n66A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
5MHz	1712.5-1777.5	0.094842	4M49G7D	0.074989	4M48W7D
10MHz	1715.0-1775.0	0.092470	9M29G7D	0.077268	9M29W7D
15MHz	1717.5-1772.5	0.092897	14M1G7D	0.076560	14M2W7D
20MHz	1720.0-1770.0	0.093111	18M9G7D	0.077268	18M9W7D
25MHz	1722.5-1767.5	0.094406	23M7G7D	0.077804	23M8W7D
30MHz	1725.0-1765.0	0.093541	28M5G7D	0.078524	28M5W7D
35MHz	1727.5-1762.5	0.093325	33M6G7D	0.077446	33M6W7D
40MHz	1730.0-1760.0	0.093111	38M6G7D	0.076736	38M5W7D

**2.1.2. NR Band n71 (663-698)**

5G NR SA (n71A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum ERP (W)	Emission Designator (99% OBW)	Maximum ERP (W)	Emission Designator (99% OBW)
5MHz	665.50-695.50	0.042073	4M49G7D	0.033420	4M47W7D
10MHz	668.00-693.00	0.042170	9M27G7D	0.033651	9M29W7D
15MHz	670.50-690.50	0.042364	14M1G7D	0.033884	14M2W7D
20MHz	673.00-688.00	0.042073	18M9G7D	0.033497	18M9W7D

**2.1.3. NR Band n77 (3700-3980)**

5G NR SA (n77A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	3705.00-3975.00	0.862979	8M57G7D	0.687068	8M59W7D
15MHz	3707.52-3972.48	0.866962	13M6G7D	0.676083	13M6W7D
20MHz	3710.01-3969.99	0.855067	18M2G7D	0.671429	18M2W7D
25MHz	3712.50-3967.50	0.855067	23M2G7D	0.695024	23M2W7D
30MHz	3715.02-3964.98	0.859014	27M8G7D	0.687068	27M9W7D
40MHz	3720.00-3960.00	0.864968	37M8G7D	0.676083	37M8W7D
50MHz	3725.01-3954.99	0.866962	47M5G7D	0.676083	47M5W7D
60MHz	3730.02-3949.98	0.839460	57M9G7D	0.662217	57M9W7D
70MHz	3735.00-3945.00	0.831764	67M6G7D	0.656145	67M4W7D
80MHz	3740.01-3939.99	0.843335	77M4G7D	0.647143	77M5W7D
90MHz	3745.02-3934.98	0.837529	87M4G7D	0.654636	87M4W7D
100MHz	3750.00-3930.00	0.860994	97M3G7D	0.682339	97M5W7D

**2.1.4. NR Band n78 (3700-3800)**

5G NR SA (n78A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	3705.00-3795.00	0.636796	8M57G7D	0.503501	8M59W7D
15MHz	3707.52-3792.48	0.638263	13M6G7D	0.501187	13M6W7D
20MHz	3710.01-3789.99	0.641210	18M2G7D	0.501187	18M2W7D
25MHz	3712.50-3787.50	0.663743	23M1G7D	0.517607	23M2W7D
30MHz	3715.02-3784.98	0.666807	27M8G7D	0.521195	27M9W7D
40MHz	3720.00-3780.00	0.674528	37M8G7D	0.526017	37M9W7D
50MHz	3725.01-3774.99	0.677642	47M6G7D	0.517607	47M5W7D
60MHz	3730.02-3769.98	0.679204	58M0G7D	0.537032	58M0W7D
70MHz	3735.00-3765.00	0.680769	67M6G7D	0.518800	67M6W7D
80MHz	3740.01-3759.99	0.696627	77M4G7D	0.543250	77M4W7D
90MHz	3745.02-3754.98	0.696627	87M4G7D	0.537032	87M6W7D
100MHz	3750.00	0.701455	97M3G7D	0.534564	97M5W7D

### 3. General Information

#### 3.1. General Description of EUT

EUT Description:	Mobile Cellular Phone
Brand Name:	Motorola
Model Name:	XT2507-1
FCC ID:	IHDT56AU3
IMEI Code:	1#: 358346690023259/358346690023267 (Conducted); 2#: 358346690023333/358346690023341 (Conducted);
Hardware Version:	DVT2
Software Version:	V2VV35.35
NR Modulation:	DFT-s-OFDM: <input checked="" type="checkbox"/> Pi/2BPSK; <input checked="" type="checkbox"/> QPSK; <input checked="" type="checkbox"/> 16QAM; <input checked="" type="checkbox"/> 64QAM; <input checked="" type="checkbox"/> 256QAM; CP-OFDM: <input checked="" type="checkbox"/> QPSK; <input checked="" type="checkbox"/> 16QAM; <input checked="" type="checkbox"/> 64QAM; <input checked="" type="checkbox"/> 256QAM;
Sample Type:	<input checked="" type="checkbox"/> Portable Device, <input type="checkbox"/> Module
Antenna Type:	<input type="checkbox"/> External, <input checked="" type="checkbox"/> Integrated
Antenna Gain:	n2 (1850-1910): -4.00dBi (Ant1); -4.00dBi (Ant2); n5 (824-849): -6.00dBi (Ant0); -7.00dBi (Ant1); n7 (2500-2570): -4.00dBi (Ant1); -3.00dBi (Ant2); n26 (814-849): -6.00dBi (Ant0); -7.00dBi (Ant1); n38 (2570-2620): -3.00dBi (Ant0); -4.00dBi (Ant1); -3.00dBi (Ant2); -8.00dBi (Ant9); n41 (2496-2690): -3.00dBi (Ant0); -4.00dBi (Ant1); -3.00dBi (Ant2); -7.00dBi (Ant9); n66 (1710-1780): -4.00dBi (Ant1); -3.00dBi (Ant2); n71 (663-698): -5.00dBi (Ant0); -8.00dBi (Ant1); n77 (3700-3980): -2.00dBi (Ant4); 0.00dBi (Ant7); -5.00dBi (Ant8); 3.00dBi (Ant10); n78 (3700-3800): -2.00dBi (Ant4); -1.00dBi (Ant7); -6.00dBi (Ant8); 2.00dBi (Ant10);

#### Remark

- The information above was declared by manufacture. Please refer to the specifications or user manual for more detailed description.

#### 3.2. Test Environment

Relative Humidity:	52.0% - 62.0%	
Atmospheric Pressure:	101.32 KPa	
Temperature:	NT (normal temperature)	25.0 °C – 27.5 °C
Voltage:	LV (Low voltage)	3.60V
	NV (Nominal voltage)	3.88V
	HV (High voltage)	4.53V

#### 3.3. Specification of Accessories

Accessory	Brand Name	Model Name
AC Adapter 1 (US)	Salcomp (Motorola)	MC-901
AC Adapter 1 (EU)	Salcomp (Motorola)	MC-902
AC Adapter 1 (UK)	Salcomp (Motorola)	MC-903
AC Adapter 1 (AU)	Salcomp (Motorola)	MC-905
AC Adapter 1 (AR)	Salcomp (Motorola)	MC-906
AC Adapter 1 (BR)	Salcomp (Motorola)	MC-907
AC Adapter 1 (CHILE)	Salcomp (Motorola)	MC-909

AC Adapter 2 (US)	AOHAI (Motorola)	MC-901
AC Adapter 2 (EU)	AOHAI (Motorola)	MC-902
AC Adapter 2 (UK)	AOHAI (Motorola)	MC-903
AC Adapter 2 (AU)	AOHAI (Motorola)	MC-905
AC Adapter 2 (AR)	AOHAI (Motorola)	MC-906
AC Adapter 2 (BR)	AOHAI (Motorola)	MC-907
AC Adapter 2 (CHILE)	AOHAI (Motorola)	MC-909
Battery 1	Motorola (ATL)	RE60
Battery 2	Motorola (SUNWODA)	RE60
USB Cable 1	SAIBAO (Motorola)	SC18D71644
USB Cable 2	Luxshare (Motorola)	SC18E08104
USB Cable 3	SAIBAO (Motorola)	SC18D86731
USB Cable 4	Luxshare (Motorola)	SC18E08103

### 4. Test Configuration of Equipment Under Test

#### 4.1. Test Mode for NR Configuration

Test Case	5G NR	SCS		Bandwidth	Modulation					Channel			RB	
		15KHz	30KHz		PI/2BPSK	QPSK	16QAM	64QAM	256QAM	LCH	MCH	HCH	1	Full
Effective Isotropic Radiated Power	N2 (1850-1910)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N5 (824-849)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N7 (2500-2570)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N26 (814-824)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N26 (824-849)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N38 (2570-2620)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N41 (2496-2690)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N66 (1710-1780)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N71 (663-698)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N77 (3700-3980)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
N78 (3700-3800)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●	
Peak-Average Ratio	N2 (1850-1910)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N5 (824-849)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N7 (2500-2570)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N26 (814-824)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N26 (824-849)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N38 (2570-2620)	○	●	Highest BW	●	●	○	○	○	●	●	●	○	●
	N41 (2496-2690)	○	●	Highest BW	●	●	○	○	○	●	●	●	○	●
	N66 (1710-1780)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N71 (663-698)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N77 (3700-3980)	○	●	Highest BW	●	●	○	○	○	●	●	●	○	●
N78 (3700-3800)	○	●	Highest BW	●	●	○	○	○	●	●	●	○	●	
Modulation Characteristics	N2 (1850-1910)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N5 (824-849)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N7 (2500-2570)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●

	N26 (814-824)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N26 (824-849)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N38 (2570-2620)	○	●	Highest BW	●	●	●	●	●	○	●	○	○	●
	N41 (2496-2690)	○	●	Highest BW	●	●	●	●	●	○	●	○	○	●
	N66 (1710-1780)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N71 (663-698)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N77 (3700-3980)	○	●	Highest BW	●	●	●	●	●	○	●	○	○	●
	N78 (3700-3800)	○	●	Highest BW	●	●	●	●	●	○	●	○	○	●
Occupied Bandwidth & 26dB Emission Bandwidth	N2 (1850-1910)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N5 (824-849)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N7 (2500-2570)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N26 (814-824)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N26 (824-849)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N38 (2570-2620)	○	●	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N41 (2496-2690)	○	●	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N66 (1710-1780)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N71 (663-698)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N77 (3700-3980)	○	●	All Supported BW	●	●	●	●	●	○	●	○	○	●
N78 (3700-3800)	○	●	All Supported BW	●	●	●	●	●	○	●	○	○	●	
Conducted Band Edges	N2 (1850-1910)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N5 (824-849)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N7 (2500-2570)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N26 (814-824)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N26 (824-849)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N38 (2570-2620)	○	●	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N41 (2496-2690)	○	●	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N66 (1710-1780)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N71 (663-698)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N77 (3700-3980)	○	●	All Supported BW	●	●	○	○	○	●	○	●	●	●
N78 (3700-3800)	○	●	All Supported BW	●	●	○	○	○	●	○	●	●	●	
Conducted Spurious Emission	N2 (1850-1910)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N5 (824-849)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N7 (2500-2570)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N26 (814-824)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N26 (824-849)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N38 (2570-2620)	○	●	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N41 (2496-2690)	○	●	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N66 (1710-1780)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N71 (663-698)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N77 (3700-3980)	○	●	All Supported BW	●	●	○	○	○	●	●	●	●	○
N78 (3700-3800)	○	●	All Supported BW	●	●	○	○	○	●	●	●	●	○	
Frequency Stability	N2 (1850-1910)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N5 (824-849)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N7 (2500-2570)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●

	N26 (814-824)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N26 (824-849)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N38 (2570-2620)	○	●	Highest BW	○	●	○	○	○	○	●	○	○	●
	N41 (2496-2690)	○	●	Highest BW	○	●	○	○	○	○	●	○	○	●
	N66 (1710-1780)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N71 (663-698)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N77 (3700-3980)	○	●	Highest BW	○	●	○	○	○	○	●	○	○	●
	N78 (3700-3800)	○	●	Highest BW	○	●	○	○	○	○	●	○	○	●

Remark:

- 1, the mark “●” means this configuration was chosen for testing, mark “○” means not selected, and the mark “✕” means not applicable.
- 2, All Supported BW means all supported bandwidth for selected SCS configuration.

**4.2. Test Frequencies**

**4.2.1 5G NR System**

**4.2.1.1. NR Band n2 (1850-1910)**

**4.2.1.1.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	370500	1852.5	376000	1880.0	381500	1907.5
10MHz	371000	1855.0	376000	1880.0	381000	1905.0
15MHz	371500	1857.5	376000	1880.0	380500	1902.5
20MHz	372000	1860.0	376000	1880.0	380000	1900.0
25MHz	372500	1862.5	376000	1880.0	379500	1897.5
30MHz	373000	1865.0	376000	1880.0	379000	1895.0
35MHz	373500	1867.5	376000	1880.0	378500	1892.5
40MHz	374000	1870.0	376000	1880.0	378000	1890.0

**4.2.1.2. NR Band n5 (824-849)**

**4.2.1.2.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	165300	826.5	167300	836.5	169300	846.5
10MHz	165800	829.0	167300	836.5	168800	844.0
15MHz	166300	831.5	167300	836.5	168300	841.5
20MHz	166800	834.0	167300	836.5	167800	839.0

**4.2.1.3. NR Band n7 (2500-2570)**

**4.2.1.3.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	500500	2502.5	507000	2535.0	513500	2567.5
10MHz	501000	2505.0	507000	2535.0	513000	2565.0
15MHz	501500	2507.5	507000	2535.0	512500	2562.5
20MHz	502000	2510.0	507000	2535.0	512000	2560.0

25MHz	502500	2512.5	507000	2535.0	511500	2557.5
30MHz	503000	2515.0	507000	2535.0	511000	2555.0
35MHz	503500	2517.5	507000	2535.0	510500	2552.5
40MHz	504000	2520.0	507000	2535.0	510000	2550.0
50MHz	505000	2525.0	507000	2535.0	509000	2545.0

**4.2.1.4. NR Band n26 (814-824)**

**4.2.1.4.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	163300	816.5	163800	819.0	164300	821.5
10MHz	163800	819.0	163800	819.0	163800	819.0
15MHz	164300	821.5	164300	821.5	164300	821.5
20MHz	164800	824.0	164800	824.0	164800	824.0

**4.2.1.5. NR Band n26 (824-849)**

**4.2.1.5.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	165300	826.5	167300	836.5	169300	846.5
10MHz	165800	829.0	167300	836.5	168800	844.0
15MHz	166300	831.5	167300	836.5	168300	841.5
20MHz	166800	834.0	167300	836.5	167800	839.0

**4.2.1.6. NR Band n38 (2570-2620)**

**4.2.1.6.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	515000	2575.0	519000	2595.0	525000	2625.0
15MHz	515500	2577.5	519000	2595.0	524500	2622.5
20MHz	516000	2580.0	519000	2595.0	522000	2610.0
25MHz	516500	2582.5	519000	2595.0	521500	2607.5
30MHz	517000	2585.0	519000	2595.0	521000	2605.0
40MHz	518000	2590.0	519000	2595.0	520000	2600.0

**4.2.1.7. NR Band n41 (2496-2690)**

**4.2.1.7.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	500202	2501.01	518598	2592.99	537000	2685.00
15MHz	500700	2503.50	518598	2592.99	536496	2682.48
20MHz	501204	2506.02	518598	2592.99	535998	2679.99
25MHz	501700	2508.50	518598	2592.99	535500	2677.50
30MHz	502200	2511.00	518598	2592.99	534996	2674.98

35MHz	502700	2513.50	518598	2592.99	534500	2672.50
40MHz	503202	2516.01	518598	2592.99	534000	2670.00
45MHz	503700	2518.50	518598	2592.99	533500	2667.50
50MHz	504204	2521.02	518598	2592.99	532998	2664.99
60MHz	505200	2526.00	518598	2592.99	531996	2659.98
70MHz	506202	2531.01	518598	2592.99	531000	2655.00
80MHz	507204	2536.02	518598	2592.99	529998	2649.99
90MHz	508200	2541.00	518598	2592.99	528996	2644.98
100MHz	509202	2546.01	518598	2592.99	528000	2640.00

**4.2.1.8. NR Band n66 (1710-1780)****4.2.1.8.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	342500	1712.5	349000	1745.0	355500	1777.5
10MHz	343000	1715.0	349000	1745.0	355000	1775.0
15MHz	343500	1717.5	349000	1745.0	354500	1772.5
20MHz	344000	1720.0	349000	1745.0	354000	1770.0
25MHz	344500	1722.5	349000	1745.0	353500	1767.5
30MHz	345000	1725.0	349000	1745.0	353000	1765.0
35MHz	345500	1727.5	349000	1745.0	352500	1762.5
40MHz	346000	1730.0	349000	1745.0	352000	1760.0

**4.2.1.9. NR Band n71 (663-698)****4.2.1.9.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	133100	665.5	136100	680.5	139100	695.5
10MHz	133600	668.0	136100	680.5	138600	693.0
15MHz	134100	670.5	136100	680.5	138100	690.5
20MHz	134600	673.0	136100	680.5	137600	688.0

**4.2.1.10. NR Band N77 (3700-3980)****4.2.1.10.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	741000	3705.00	656000	3840.00	665000	3975.00
15MHz	741504	3707.52	656000	3840.00	664832	3972.48
20MHz	647334	3710.01	656000	3840.00	664666	3969.99
25MHz	742500	3712.50	656000	3840.00	664500	3967.50
30MHz	647668	3715.02	656000	3840.00	664332	3964.98
40MHz	648000	3720.00	656000	3840.00	664000	3960.00
50MHz	648334	3725.01	656000	3840.00	663666	3954.99
60MHz	648668	3730.02	656000	3840.00	663332	3949.98

70MHz	649000	3735.00	656000	3840.00	663000	3945.00
80MHz	649334	3740.01	656000	3840.00	662666	3939.99
90MHz	649668	3745.02	656000	3840.00	662332	3934.98
100MHz	650000	3750.00	656000	3840.00	662000	3930.00

#### 4.2.1.11. NR Band N78 (3700-3800)

##### 4.2.1.11.1. SCS=30KHz

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	741000	3705.00	650000	3750.00	653000	3795.00
15MHz	741504	3707.52	650000	3750.00	652832	3792.48
20MHz	647334	3710.01	650000	3750.00	652666	3789.99
25MHz	742500	3712.50	650000	3750.00	652500	3787.50
30MHz	647668	3715.02	650000	3750.00	652332	3784.98
40MHz	648000	3720.00	650000	3750.00	652000	3780.00
50MHz	648334	3725.01	650000	3750.00	651666	3774.99
60MHz	648668	3730.02	650000	3750.00	651332	3769.98
70MHz	649000	3735.00	650000	3750.00	651000	3765.00
80MHz	649334	3740.01	650000	3750.00	650666	3759.99
90MHz	649668	3745.02	650000	3750.00	650332	3754.98
100MHz	650000	3750.00	650000	3750.00	650000	3750.00

## 5. Description of Tests

### 5.1. Conducted Output Power Measurement

#### 5.1.1. Description of Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT, Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

#### 5.1.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.2.
- 2, The transmitter output port was connected to the system simulator.
- 3, Set EUT at maximum power through the system simulator.
- 4, Select lowest, Middle, Highest channels for each band and each modulation.
- 5, Record the reading power from the system simulator.

### 5.2. Effective (Isotropic) Radiated Power

Measurement Procedure: ANSI C63.26

Calculate power in dBm by the following formula:

ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd)

EIRP (dBm) = Conducted Power (dBm) + antenna gain (dBi)

EIRP=ERP+2.15dB

### 5.3. Peak-to-Average Ratio Measurement

#### 5.3.1. Description of PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

#### 5.3.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.2.3.4(CCDF)
- 2, Refer to instrument's analyser instruction manual for details on how to use the power statistics/CCDF function.
- 3, Centre Frequency = Carrier centre frequency.
- 4, Set resolution bandwidth  $\geq$  signal's occupied bandwidth.
- 5, Set the number of counts to a value that stabilizes the measured CCDF curve.
- 6, Set the measurement interval as follows:
  - 1) for continuous transmissions (>98% duty cycle), set to 1ms.
  - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- 7, Record the maximum PAR level associated with a probability of 0.1%.

#### 5.3.3. Alternate procedure for PAR

Measurement Procedure: 5.2.6 of ANSI C63.26

Some regulatory requirements specify a PAR limit when the output power limits are specified in terms of average power. If it becomes necessary to provide measurement data to demonstrate compliance to a PAR limit, then the appropriate procedure from those provided in 5.2.3 shall be utilized to determine the peak power (or peak PSD) and the appropriate procedure from those provided in 5.2.4 shall be used to determine the average power (or average PSD). The data from these measurements is then used in Equation (2) to determine the PAR of a narrowband CW-like signal. See 5.2.3.4 for guidance on determining the PAR of a broadband noise-like signal.

$$\text{PAR (dB)} = P_{\text{Pk}} (\text{dBm or dBW}) - P_{\text{Avg}} (\text{dBm or dBW})$$

where

PAR peak-to-average power ratio, in dB

$P_{\text{Pk}}$  measured peak power or peak PSD level, in dBm or dBW

$P_{\text{Avg}}$  measured average power or average PSD level, in dBm or dBW

### 5.4. 99% Occupied Bandwidth & 26dB Emission Bandwidth

#### 5.4.1. Description of 99% Occupied Bandwidth & 26dB Emission Bandwidth Measurement

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyser shall be set to

capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

#### 5.4.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.4
- 2, The signal analyzer's automatic measurement capability was used to perform the 99% occupied bandwidth and the 26dB emission bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 3,  $RBW \geq 1\% - 5\%$  of the expected OBW.
- 4,  $VBW \geq 3 * RBW$
- 5, Detector=Peak
- 6, Trace Mode= Max Hold.
- 7, Sweep Time=Auto
- 8, The trace was allowed to stabilize.
- 9, If necessary, steps 2-7 were repeated after changing the RBW such that it would be within 1%-5% of the 99% occupied bandwidth observed in step 7.

#### 5.5. Conducted Band Edge Measurement

##### 5.5.1. Description of Conducted Band Edge Measurement

The transmitter output was connected to a calibrated coaxial cable, attenuator and spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emissions are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyser was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

##### 5.5.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.7
- 2, Start and stop frequency were set such that the band edge would be placed in the centre of the spectrum analyzer screen.
- 3, Span was set large enough to capture all out of band emissions near the band edge.
- 4,  $RBW \geq 1\%$  of the emission bandwidth (2% of the emission bandwidth for n7/n38/n41 except when 1MHz band is 2495-2496MHz);
- 5,  $VBW \geq 3 * RBW$
- 6, Detector=RMS
- 7, Trace Mode=Trace Average for continuous emissions, Max Hold for pulse emissions.
- 8, Sweep Points  $\geq 2 * \text{Span}/RBW$
- 9, Sweep Time = Auto
- 10, The trace was allowed to stabilize.

## 5.6. Conducted Spurious Emission Measurement

### 5.6.1. Description of Conducted Spurious Emission Measurement

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyser. The spectrum is scanned from 9KHz up to a frequency including its 10th harmonic or 40GHz, which is lower.

### 5.6.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.7
- 2, RBW  $\geq 100\text{KHz}$  for emissions below 1GHz, 1MHz for emissions above 1GHz.
- 3, VBW  $\geq 3 * \text{RBW}$
- 4, Detector = RMS
- 5, Trace Mode = Average.
- 6, Sweep Points  $\geq 2 * \text{Span/RBW}$
- 7, Sweep Time = Auto
- 8, The trace was allowed to stabilize.

## 5.7. Frequency Stability Measurement

### 5.7.1. Description of Frequency Stability Measurement

The Frequency Stability should be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emissions stays within the authorized frequency block.

### 5.7.2. Measurement Procedure for Temperature Variation

- 1, The testing follows ANSI C63.26 section 5.6.4.
- 2, The EUT was set up in the thermal chamber and connected with the system simulator.
- 3, With power off, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 4, With power off, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum change in frequency was recorded within one minute.

### 5.7.3. Measurement Procedure for Voltage Variation

- 1, The testing follows ANSI C63.26 section 5.6.5.
- 2, The EUT was placed in a thermal chamber at  $20 \pm 5^{\circ}\text{C}$  and connected with the system simulator.
- 3, The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 4, For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- 5, The variation in frequency was measured for the worst case.

**6. List of Measuring Equipment**

Equipment	Model	Manufacture	Device No.	Cal Date	Cal Due
Radio Communication Analyzer	MT8000A	Anritsu	6272427164	2024-11-15	2025-11-14
	MT8000A	Anritsu	6272478367	2024-07-03	2025-07-02
	MT8821C	Anritsu	6272374630	2024-11-15	2025-11-14
Spectrum Analyzer (50Hz-40GHz)	FSV	R&S	101046	2024-11-15	2025-11-14
Spectrum Analyzer (50Hz-40GHz)	FSV	R&S	101334	2024-11-15	2025-11-14
Power Supply	2036	Keithley	4058748	2024-11-15	2025-11-14
Temperature Chamber	C/64/40/3	Weiss	56246017780020	2024-04-01	2025-03-31
Power Divider	-	WOKEN	0120A04051801O	NCR	
Power Divider	-	WOKEN	0120A02051801M	NCR	

Remark:

- 1, For equipment listed above that has a calibration date or calibration due date that falls within the test date range, and the equipment was used after calibrate date and before calibrate due date.
- 2, "NCR" means no calibration required.

**7. Measurement Uncertainty**

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26. All the measurement uncertainties value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be directly to specified limit to determine compliance.

**7.1. Uncertainty of Conducted Measurement**

Contribution	Expanded Uncertainty
Conducted Power	± 1.09 dB
Peak-to-Average Ratio	± 2.28 dB
Channel Bandwidth	± 0.15% MHz
Conducted Emission (f <1GHz)	± 2.23 dB
Conducted Emission (1GHz < f <18GHz)	± 2.24 dB
Conducted Emission (18GHz < f <40GHz)	± 2.11 dB
Frequency	± 0.02 KHz

**8. Appendixes**

Appendix B.1	NR Band n2A (1850-1910)
Appendix B.2	NR Band n5A (824-849)
Appendix B.3	NR Band n7A (2500-2570)
Appendix B.4	NR Band n26A (814-824)
Appendix B.5	NR Band n26A (824-849)
Appendix B.6	NR Band n38A (2570-2620)
Appendix B.7	NR Band n41A (2496-2690)
Appendix B.8	NR Band n41A (2496-2690)_2x2MIMO
Appendix B.9	NR Band n66A (1710-1780)
Appendix B.10	NR Band n71A (663-698)
Appendix B.11	NR Band n77A (3700-3980)
Appendix B.12	NR Band n78A (3700-3800)
Appendix B.13	NR Band DC_66A_n2A (1850-1910)
Appendix B.14	NR Band DC_66A_n7A (2500-2570)
Appendix B.15	NR Band DC_66A_n38A (2570-2620)
Appendix B.16	NR Band DC_66A_n41A (2496-2690)
Appendix B.17	NR Band DC_7A_n66A (1710-1780)

The End