



November 03, 2003

Supplement to SAR Test Report for Motorola portable cellular phone (FCC ID IHDT56DH1)

Prepared by:

Firass Badaruzzaman

Motorola Personal Communications Sector Product Safety Laboratory

Libertyville, Illinois

2. We note that several of the recently submitted SAR plots list values for the conductivity and dielectric constant that differ from the values listed in the Table on p.4. Please address.

Response: The simulate is measured twice on the same day having an interval of approximately ten hours. The table in the original SAR report is incomplete. Certain SAR plots provided in appendix 2 of the original SAR report were taken after the simulate was measured the second time on **October 1, 2003**. The conductivity and dielectric values for those particular plots are included in the below table in bold letter.

The SAR plots provided in the first supplemental report had a similar reason for having different conductivity and dielectric values for **October 2, 2003**. The missing data for both days has been provided in the below updated table.

<i>f</i> (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			ϵ_r	σ (S/m)	Temp (°C)
835	Head	Measured, 09/30/2003	43.2	0.93	19.4-20.5
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
		Measured,10/01/2003	42.7	0.92	19.4-20.5
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
		Measured,10/01/2003	43.2	0.93	19.4-20.5
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
		Measured,10/02/2003	42.3	0.91	19.4-20.5
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
		Measured,10/02/2003	42.7	0.92	19.4-20.5
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
835	Body	Measured, 10/02/2003	55	0.97	19.4-20.5
		Recommended Limits	55.2 ±5%	0.97 ±5%	18-25
1880	Head	Measured, 10/02/2003	38.7	1.46	19.4-20.5
		Recommended Limits	40.0 ±5%	1.40 ±5%	18-25
		Measured, 10/03/2003	38.2	1.45	19.4-20.5
		Recommended Limits	40.0 ±5%	1.40 ±5%	18-25
	Body	Measured, 10/03/2003	51.1	1.58	19.4-20.5
		Recommended Limits	53.3 ±5%	1.52 ±5%	18-25