



**MOTOROLA**

Exhibit 11: SAR Test Report IHDT56EA1

**Date of test:** 6 & 10 August, 2004  
**Date of Report:** 25 August, 2004

**Laboratory:** Motorola Personal Communications Sector Product Safety & Compliance Laboratory  
 600 N. US Highway 45  
 Room: MW113  
 Libertyville, Illinois 60048

**Test Responsible:** Steven Hauswirth  
 Principal Staff Engineer

**Accreditation:** This laboratory is accredited to ISO/IEC 17025-1999 to perform the following tests:



<p><u>Tests:</u>                  Electromagnetic Specific Absorption Rate</p> <p>Simulated Tissue Preparation                  RF Power Measurement</p>	<p><u>Procedures:</u>                  ANSI/IEEE C95.1-1992, 1999                  (SAR) IEEE C95.3-1991                  IEEE P1528 (<i>DRAFT</i>)                  FCC OET Bulletin 65 (<i>including Supplements A, B, C</i>)                  Australian Communications Authority Radio                  Communications (Electromagnetic Radiation – Human                  Exposure) Standard 1999                  CENELEC EN 50361 (2001)                  APP-0247                  DOI-0876, 0900, 0902, 0904, 0915</p>
--	---

On the following products or types of products:  
 Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

A2LA certificate #1651-01

**Statement of Compliance:** Motorola declares under its sole responsibility that portable cellular telephone FCC ID IHDT56EA1 to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093). It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola, Inc. 2004

This test report shall not be reproduced except in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Motorola encourages all feedback, both positive and negative, on this test report.

**Table of Contents**

**1. INTRODUCTION..... 3**

**2. DESCRIPTION OF THE DEVICE UNDER TEST ..... 3**

**2.1 Antenna description .....3**

**2.2 Device description.....3**

**3. TEST EQUIPMENT USED..... 3**

**3.1 Dosimetric System .....3**

**3.2 Additional Equipment.....4**

**4. ELECTRICAL PARAMETERS OF THE TISSUE SIMULATING LIQUID ..... 4**

**5. SYSTEM ACCURACY VERIFICATION..... 5**

**6. TEST RESULTS ..... 5**

**6.1 Head Adjacent Test Results.....6**

**6.2 Body Worn Test Results .....7**

**APPENDIX 1: SAR DISTRIBUTION COMPARISON FOR SYSTEM ACCURACY VERIFICATION .... 10**

**APPENDIX 2: SAR DISTRIBUTION PLOTS FOR PHANTOM HEAD ADJACENT USE ..... 11**

**APPENDIX 3: SAR DISTRIBUTION PLOTS FOR BODY WORN CONFIGURATION..... 14**

**APPENDIX 4: PROBE CALIBRATION CERTIFICATE ..... 16**

**APPENDIX 5: DIPOLE CHARACTERIZATION CERTIFICATE..... 17**

**APPENDIX 6: MEASUREMENT UNCERTAINTY BUDGET..... 18**

**APPENDIX 7: PHOTOGRAPHS OF DEVICE UNDER TEST ..... 21**

## 1 Introduction

The Motorola Personal Communications Sector Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of portable cellular phone (FCC ID IHDT56EA1). The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with FCC OET Bulletin 65 Supplement C 01-01.

## 2 Description of the Device Under Test

### 2.1 Antenna description

<b>Type</b>	External	
<b>Location</b>	Upper Right Corner	
<b>Dimensions</b>	Length	22mm
	Width	10mm
<b>Configuration</b>	Helix	

### 2.2 Device description

<b>FCC ID Number</b>	<b>IHDT56EA1</b>													
<b>Serial number</b>	4400007583659													
<b>Mode(s) of Operation</b>	GSM 850	GSM 900	GSM 1800	GSM 1900	GPRS 850	GPRS 900	GPRS 1800	GPRS 1900	EDGE 850	EDGE 900	EDGE 1800	EDGE 1900	Blue Tooth	
<b>Modulation Mode(s)</b>	GSM	GSM	GSM	GSM	GSM	GSM	GSM	GSM	EDGE	EDGE	EDGE	EDGE	Blue Tooth	
<b>Maximum Output Power Setting</b>	32.50 dBm	32.50 dBm	29.70 dBm	29.70 dBm	32.50 dBm	32.50 dBm	29.70 dBm	29.70 dBm	28.00 dBm	28.00 dBm	27.00 dBm	27.00 dBm	4.00 dBm	
<b>Duty Cycle</b>	1:8	1:8	1:8	1:8	2:8	2:8	2:8	2:8	1:8	1:8	1:8	1:8	1:1	
<b>Transmitting Frequency Rang(s)</b>	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.20 – 1909.80 MHz	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.20 – 1909.80 MHz	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.20 – 1909.80 MHz	2400 - 2483.5 MHz	
<b>Production Unit or Identical Prototype (47 CFR §2..908)</b>	Identical Prototype													
<b>Device Category</b>	Portable													
<b>RF Exposure Limits</b>	General Population / Uncontrolled													

## 3 Test Equipment Used

### 3.1 Dosimetric System

The Motorola Personal Communications Sector Product Safety & Compliance Laboratory utilizes a Dosimetric Assessment System (Dasy3™ v3.1d) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All the SAR measurements are taken within a shielded enclosure. The overall RSS uncertainty of the

measurement system is  $\pm 11.7\%$  (K=1) with an expanded uncertainty of  $\pm 23.0\%$  (K=2). The measurement uncertainty budget is given in Appendix 6. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4 W/kg to 10 W/kg. The list of calibrated equipment used for the measurements is shown below.

Description	Serial Number	Cal Due Date
DASY3 DAE V1	SN3037	10-Oct-04
E-Field Probe ET3DV6	SN440	9-Feb-05
Dipole Validation Kit, D900V2	SN425TR	2-Apr-05
S.A.M. Phantom used for 800MHz	TP-1005	
Dipole Validation Kit, D1800V2	SN259TR	2-Apr-05
S.A.M. Phantom used for 1900MHz	TP-1154	

### 3.2 Additional Equipment

Description	Serial Number	Cal Due Date
Signal Generator HP8648C	3847A04822	6-Feb-05
Power Meter E4419B	GB39511087	5-Apr-05
Power Sensor #1 - E9301A	US39211009	5-Aug-05
Power Sensor #2 - E9301A	US39210915	5-Aug-05
Network Analyzer HP8753ES	US39171846	29-Oct-04
Dielectric Probe Kit HP85070B	US99360074	N/A

## 4 Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity,  $\epsilon_r$ , and the conductivity,  $\sigma$ , of the tissue simulating liquids were measured with the HP85070 Dielectric Probe Kit. These values, along with the temperature of the tissue simulate are shown in the table below. The recommended limits for maximum permittivity and minimum conductivity are also shown. These come from the Federal Communication Commission, OET Bulletin 65 Supplement C 01-01. It is seen that the measured parameters are satisfactory for compliance testing.

f (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			$\epsilon_r$	$\sigma$ (S/m)	Temp (°C)
835	Head	Measured, 6-Aug-04	42.8	0.92	18.9
		Recommended Limits	41.5 $\pm$ 5%	0.90 $\pm$ 5%	18-25
	Body	Measured, 6-Aug-04	55.1	0.98	19.3
		Measured, 10-Aug-04	55.1	0.98	19.1
		Recommended Limits	55.2 $\pm$ 5%	0.97 $\pm$ 5%	18-25
1880	Head	Measured, 6-Aug-04	40	1.46	19.2
		Recommended Limits	40.0 $\pm$ 5%	1.40 $\pm$ 5%	18-25
	Body	Measured, 6-Aug-04	51.9	1.59	19.4
		Measured, 10-Aug-04	51.0	1.58	19.1
		Recommended Limits	53.3 $\pm$ 5%	1.52 $\pm$ 5%	18-25

The list of ingredients and the percent composition used for the tissue simulates are indicated in the table below.

Ingredient	800MHz Head	800MHz Body	1900MHz Head	1900MHz Body
Sugar	57.0	44.9	--	30.80
DGBE	--	--	47.0	--
Water	40.45	53.06	52.8	68.91
Salt	1.45	0.94	0.2	0.29
HEC	1.0	1.0	--	--
Bact.	0.1	0.1	--	--

## 5 System Accuracy Verification

A system accuracy verification of the DASY3 was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within center section of the SAM phantom.

A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR indicated on the dipole certification sheet. These tests were done at 900MHz and/or 1800MHz. These frequencies are within 100MHz of the mid-band frequency of the test device. This is within the allowable window given in Supplement C 01-01 Appendix D System Verification section item #5. The test was conducted on the same days as the measurement of the DUT. Recommended limits for maximum permittivity, minimum conductivity are shown in the table below. These come from the Federal Communication Commission, OET Bulletin 65 Supplement C 01-01. The obtained results from the system accuracy verification are displayed in the table below. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). The tissue stimulant depth was verified to be 15.0cm ±0.5cm. Z-axis scans showing the SAR penetration are also included in Appendix 1. SAR values are normalized to 1W forward power delivered to the dipole.

f (MHz)	Description	SAR (W/kg), 1gram	Dielectric Parameters		Ambient Temp (°C)	Tissue Temp (°C)
			ε <sub>r</sub>	σ (S/m)		
835	Measured, 6-Aug-04	9.55	42.6	0.92	20	19.3
	Measured, 10-Aug-04	9.50	42.2	0.91	20	19.1
	Recommended Limits	10.00	41.5 ±5%	0.90 ±5%	18-25	18-25
1800	Measured, 6-Aug-04	38.3	40.5	1.37	20	19.2
	Measured, 10-Aug-04	38.3	38.6	1.35	20	19.2
	Recommended Limits	40.7	40.0 ±5%	1.4 ±5%	18-25	18-25

The following probe conversion factors were used on the E-Field probe(s) used for the system accuracy verification measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN3037	900	6.10	7 of 10
		1800	4.90	7 of 10

## 6 Test Results

The test sample was operated in a test mode that allows control of the transmitter without the need to place actual phone calls. For the purposes of this test the unit is commanded to test mode and manually set to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in OET Bulletin 65 Supplement C 01-01. Motorola also followed the requirements in Supplement C / Appendix D: SAR Measurement Procedures, section titled “Devices Operating Next To A Person’s Ear “. These directions state “The device should be tested on the left and right side of the head phantom in the “Cheek/Touch”

and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tile/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).“

The DASY v3.1d SAR measurement system specified in section 3.1 was utilized within the intended operations as set by the SPEAG™ setup. The phone was positioned into the measurement configurations using the positioner supplied with the DASY 3.1d SAR measurement system. The measured dielectric constant of the material used for the positioner is less than 2.9 and the loss tangent is less than 0.02 (± 30%) at 850MHz. The default settings for the “coarse” and “cube” scans were chosen and use for measurements. The grid spacing of the course scan was set to 15cm as shown in the SAR plots included in appendix 2 and 3. Please refer to the DASY manual for additional information on SAR scanning procedures and algorithms used.


The Cellular Phone (FCC ID IHDT56EA1) has the SNN5683A as the only available battery option. This battery was used to do all of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery.

### 6.1 Head Adjacent Test Results

To aid in positioning repeatability, the ear reference line of the device and the axis reference line of the device have been physically added using a non-metallic marker.

- Per Figure 1, the "Ear Reference Line" is centered vertically through the center of the listening area (as defined by the speaker holes in the housing).
- The "Axis Reference Line" bisects the front surface of the device at its top and bottom edges.
- The intersection of these two lines defines the location of the "Ear Reference Point".

The lines drawn on the device extended to the outside edges, as shown in blue in the figure below, & wrap around the sides of the device.



The SAR results shown in tables 1 and 2 are maximum SAR values averaged over 1 gram of phantom tissue. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is  $New\ SAR = Old\ SAR * 10^{(-drift/10)}$ . The SAR reported at the end of the measurement process by the DASY™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may

exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test. The test conditions indicated as bold numbers in the following table are included in Appendix 2

The SAR measurements were performed using the SAM phantoms listed in section 3.1. Since same phantoms and tissue simulate are used for the system accuracy verification as the device SAR measurements, the Z-axis scans included in within Appendix 1 are applicable for verification of tissue simulate depth to be 15.0cm ±0.5cm. All other test conditions measured lower SAR values than those included in Appendix 2.

The following probe conversion factors were used on the E-Field probe(s) used for the head adjacent measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN3037	835	6.10	7 of 10
		1900	4.90	7 of 10

f (MHz)	Description	Conducted Output Power (dBm)	Cheek / Touch Position							
			Left Head				Right Head			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Digital 800MHz	Channel 128	32.71	0.958	-0.29	1.02	19.1	1.06	-0.30	1.14	18.9
	Channel 189	32.75	1.06	-0.29	1.13	19.1	1.16	-0.33	1.25	18.9
	Channel 251	32.61	1.19	-0.28	1.27	19.1	<b>1.30</b>	<b>-0.31</b>	<b>1.40</b>	<b>18.5</b>
Digital 1900MHz	Channel 512	29.98					0.738	-0.09	0.75	19.2
	Channel 661	30.13	0.703	-0.52	0.79	19.2	<b>0.740</b>	<b>-0.47</b>	<b>0.82</b>	<b>19.2</b>
	Channel 810	30.14					0.780	0.10	0.78	19.2

**Table 1: SAR measurement results for the portable cellular telephone FCC ID IHDT56EA1 at highest possible output power. Measured against the left head in the Cheek/Touch Position.**

f (MHz)	Description	Conducted Output Power (dBm)	15° Tilt Position							
			Left Head				Right Head			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Digital 800MHz	Channel 128	32.71								
	Channel 189	32.75	0.297	-0.08	0.30	19.0	<b>0.323</b>	<b>0.0</b>	<b>0.32</b>	<b>19.0</b>
	Channel 251	32.61								
Digital 1900MHz	Channel 512	29.98								
	Channel 661	30.13	<b>0.354</b>	<b>0.05</b>	<b>0.35</b>	<b>19.2</b>	0.352	0.08	0.35	18.7
	Channel 810	30.14								

**Table 2: SAR measurement results for the portable cellular telephone FCC ID IHDT56EA1 at highest possible output power. Measured against the left head in the 15° Tilt Position.**

## 6.2 Body Worn Test Results

The SAR results shown in tables 5 through 7 are the maximum SAR values averaged over 1 gram of phantom tissue. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is  $New\ SAR = Old\ SAR * 10^{(-drift/10)}$ . The SAR reported at the end of the measurement process by the DASY™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test.

The test conditions indicated as bold numbers in the following table are included in Appendix 3. Note that 800MHz digital mode SAR measurements were performed in accordance with OET Bulletin 65 Supplement C 01-01. All other test conditions measured lower SAR values than those included in Appendix 3.

A “flat” phantom was for the body-worn tests. This “flat” phantom is made out of 1” thick natural High Density Polyethylene with a thickness at the bottom equal to 2.0mm. It measures 52.7cm(long) x 26.7cm(wide) x 21.2cm(tall). The measured dielectric constant of the material used is less than 2.3 and the loss tangent is less than 0.0046 all the way up to 2.184GHz.

The tissue stimulant depth was verified to be 15.0cm ±0.5cm. The same device holder described in section 6 was used for positioning the phone. The functional accessories were divided into two categories, the ones with metal components and the ones with non-metal components. For non-metallic component accessories’, testing was performed on the accessory that displayed the closest proximity to the flat phantom. Each metallic component accessory, if any, was checked for uniqueness of metal component so that each is tested with the device. If multiple accessories shared an identical metal component, only the accessory that dictates the closest spacing to the body was tested. The cellular phone was tested with a headset connected to the device for all body-worn SAR measurements.

The following probe conversion factors were used on the E-Field probe(s) used for the body worn measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN3037	835	5.9	8 of 10
		1900	4.7	8 of 10

f (MHz)	Description	Conducted Output Power (dBm)	Body Worn							
			Front of Phone 15mm Below Phantom				Back of Phone 15mm Below Phantom			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Digital 800MHz	Channel 128	32.71								
	Channel 189	32.75	0.18	0.02	0.18	19.6	<b>0.502</b>	<b>-0.02</b>	<b>0.50</b>	<b>19.5</b>
	Channel 251	32.61								
Digital 1900MHz	Channel 512	29.98								
	Channel 661	30.13	0.102	-0.11	0.10	19.7	<b>0.295</b>	<b>-0.05</b>	<b>0.30</b>	<b>19.4</b>
	Channel 810	30.14								

**Table 5: SAR measurement results for the portable cellular telephone FCC ID IHDT56EA1 at highest possible output power. Measured against the body.**

f (MHz)	Description	Conducted Output Power (dBm)	Body Worn							
			Bluetooth				GPRS Class 10			
			Back of Phone 15mm Below Phantom				Back of phone 25mm below Phantom			
Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)	Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)			
Digital 800MHz	Channel 128	32.71								
	Channel 189	32.75	<b>0.565</b>	<b>-0.01</b>	<b>0.57</b>	<b>19.3</b>	<b>0.406</b>	<b>-0.03</b>	<b>0.41</b>	<b>19.1</b>
	Channel 251	32.61								
Digital 1900MHz	Channel 512	29.98								
	Channel 661	30.13	<b>0.306</b>	<b>-0.05</b>	<b>0.31</b>	<b>19.3</b>	<b>0.222</b>	<b>-0.06</b>	<b>0.23</b>	<b>19.1</b>
	Channel 810	30.14								

**Table 6: SAR measurement results for the portable cellular telephone FCC ID IHDT56EA1 at highest possible output power. Measured against the body.**

f (MHz)	Description	Conducted Output Power (dBm)	<b>Body Worn</b>			
			EDGE Class 8			
			Back of phone 25mm below Phantom			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Digital 800MHz	Channel 128	27.90				
	Channel 189	27.90	0.0844	-0.05	0.09	19.1
	Channel 251	27.90				
Digital 1900MHz	Channel 512	27.25				
	Channel 661	27.25	0.0612	-0.12	0.06	19.1
	Channel 810	27.25				

**Table 7: SAR measurement results for the portable cellular telephone FCC ID IHDT56EA1 at highest possible output power. Measured against the body.**

## **Appendix 1**

### **SAR distribution comparison for the system accuracy verification**

# Dipole 835 MHz

835MHz System Performance Check / Dipole Sn# 425TR

PM2 Power = 202mW Refl.Pwr PM3= -23.06dB

Sim.Temp@SPC = 19.3 Room Temp @ SPC = 20


R1 TP-1005 SUGAR SAM Expanded (Rev. 2)-9Jan03; Flat

Probe: ES3DV3 - SN3037 - Validation4; ConvF(6.10,6.10,6.10); Crest factor: 1.0; 835 MHz VALIDATION:  $\sigma = 0.92$  mho/m  $\epsilon_r = 42.6$   $\rho = 1.00$  g/cm<sup>3</sup>

Cubes (2): Peak: 2.86 mW/g  $\pm 0.15$  dB, SAR (1g): 1.93 mW/g  $\pm 0.09$  dB, SAR (10g): 1.27 mW/g  $\pm 0.07$  dB, (Worst-case extrapolation)

Penetration depth: 13.0 (12.3, 13.8) [mm]

Powerdrift: 0.00 dB



# Dipole 835 MHz

835MHz System Performance Check / Dipole Sn# 425TR

PM2 Power = 202mW Refl.Pwr PM3= -23.06dB

Sim.Temp@SPC = 19.3 Room Temp @ SPC = 20


R1 TP-1005 SUGAR SAM Expanded (Rev. 2)-9Jan03 Phantom; Section; Position: ; Frequency: 835 MHz

Probe: ES3DV3 - SN3037 - Validation4; ConvF(6.10,6.10,6.10); Crest factor: 1.0; 835 MHz VALIDATION:  $\sigma = 0.92$  mho/m  $\epsilon_r = 42.6$   $\rho = 1.00$  g/cm<sup>3</sup>

: , , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 13.5 (13.2, 14.0) [mm]



# Dipole 1800 MHz

1800 MHz System Performance Check / Dipole Sn# 259tr

PM2 Power = 199mW Refl.Pwr PM3 = -25.04dB

Sim.Temp@SPC = 19.2 Room Temp @ SPC = 20


R#1 TP-1154 GLYCOL SAM Expanded (Rev. 2)-9Jan03; Flat

Probe: ES3DV3 - SN3037 - Validation4; ConvF(4.90,4.90,4.90); Crest factor: 1.0; 1800 MHz VALIDATION:  $\sigma = 1.37$  mho/m  $\epsilon_r = 40.5$   $\rho = 1.00$  g/cm<sup>3</sup>

Cubes (2): Peak: 13.5 mW/g  $\pm 0.16$  dB, SAR (1g): 7.63 mW/g  $\pm 0.10$  dB, SAR (10g): 4.08 mW/g  $\pm 0.07$  dB, (Worst-case extrapolation)

Penetration depth: 8.8 (8.6, 9.4) [mm]

Powerdrift: 0.02 dB



# Dipole 1800 MHz

1800 MHz System Performance Check / Dipole Sn# 259tr

PM2 Power = 199mW Refl.Pwr PM3 = -25.04dB

Sim.Temp@SPC = 19.2 Room Temp @ SPC = 20


R#1 TP-1154 GLYCOL SAM Expanded (Rev. 2)-9Jan03 Phantom; Section; Position: ; Frequency: 1800 MHz

Probe: ES3DV3 - SN3037 - Validation4; ConvF(4.90,4.90,4.90); Crest factor: 1.0; 1800 MHz VALIDATION:  $\sigma = 1.37$  mho/m  $\epsilon_r = 40.5$   $\rho = 1.00$  g/cm<sup>3</sup>

: , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 9.3 (9.1, 9.7) [mm]



# Dipole 835 MHz

835 MHz System Performance Check / Dipole Sn# 425TR

PM2 Power = 202mW Refl.Pwr PM3= -23.5dB

Sim.Temp@SPC = 19.1C Room Temp @ SPC = 20C


R1 TP-1005 SUGAR SAM Expanded (Rev. 2)-9Jan03; Flat

Probe: ES3DV3 - SN3037 - Validation4; ConvF(6.10,6.10,6.10); Crest factor: 1.0; 835 MHz VALIDATION:  $\sigma = 0.91$  mho/m  $\epsilon_r = 42.2$   $\rho = 1.00$  g/cm<sup>3</sup>

Cubes (2): Peak: 2.83 mW/g  $\pm 0.08$  dB, SAR (1g): 1.92 mW/g  $\pm 0.01$  dB, SAR (10g): 1.27 mW/g  $\pm 0.02$  dB, (Worst-case extrapolation)

Penetration depth: 13.1 (12.4, 13.9) [mm]

Powerdrift: 0.07 dB



# Dipole 835 MHz

835 MHz System Performance Check / Dipole Sn# 425TR

PM2 Power = 202mW      Refl.Pwr PM3= -23.5dB

Sim.Temp@SPC = 19.1C      Room Temp @ SPC = 20C


R1 TP-1005 SUGAR SAM Expanded (Rev. 2)-9Jan03 Phantom; Section; Position: ; Frequency: 835 MHz

Probe: ES3DV3 - SN3037 - Validation4; ConvF(6.10,6.10,6.10); Crest factor: 1.0; 835 MHz VALIDATION:  $\sigma = 0.91$  mho/m  $\epsilon_r = 42.2$   $\rho = 1.00$  g/cm<sup>3</sup>

: , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 13.6 (13.3, 14.0) [mm]



# Dipole 1800 MHz

1800 MHz System Performance Check / Dipole Sn# 259TR

PM2 Power = 205mW      Refl.Pwr PM3= -22.79dB

Sim.Temp@SPC = 19.2C      Room Temp @ SPC = 20C


R1 Amy Twin Phantom Rev.4 (22Aug02); section 2

Probe: ES3DV3 - SN3037 - Validation4; ConvF(4.90,4.90,4.90); Crest factor: 1.0; 1800 MHz VALIDATION:  $\sigma = 1.35$  mho/m  $\epsilon_r = 38.6$   $\rho = 1.00$  g/cm<sup>3</sup>

Cubes (2): Peak: 13.8 mW/g  $\pm 0.18$  dB, SAR (1g): 7.85 mW/g  $\pm 0.10$  dB, SAR (10g): 4.22 mW/g  $\pm 0.06$  dB, (Worst-case extrapolation)

Penetration depth: 9.4 (9.2, 9.9) [mm]

Powerdrift: -0.06 dB



# Dipole 1800 MHz

1800 MHz System Performance Check / Dipole Sn# 259TR

PM2 Power = 205mW      Refl.Pwr PM3= -22.79dB

Sim.Temp@SPC = 19.2C      Room Temp @ SPC = 20C


R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; Section; Position: ; Frequency: 1800 MHz

Probe: ES3DV3 - SN3037 - Validation4; ConvF(4.90,4.90,4.90); Crest factor: 1.0; 1800 MHz VALIDATION:  $\sigma = 1.35$  mho/m  $\epsilon_r = 38.6$   $\rho = 1.00$  g/cm<sup>3</sup>

: , ()

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Penetration depth: 8.8 (8.6, 9.4) [mm]



## Appendix 2

### SAR distribution plots for Phantom Head Adjacent Use

s/n: 4400007583659

Ch# 251 / Pwr Step: 5 OTA  
Type of Modulation: 850 GSMAntenna Position: FIXED  
Battery Model #: SNN5683A

DEVICE POSITION (cheek or rotated): CHEEK

R1 TP-1005 SUGAR SAM Expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 849 MHz


Probe: ES3DV3 - SN3037 - IEEE Head; ConvF(6.10,6.10,6.10); Crest factor: 8.0; 835 MHz Head & Body:  $\sigma = 0.92$  mho/m  $\epsilon_r = 42.8$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 1.30 mW/g, SAR (10g): 0.860 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 14.8 (13.2, 16.6) [mm]

Powerdrift: -0.31 dB



s/n: 4400007583659

Ch# 661 / Pwr Step: 0

Type of Modulation: 1900 GSM

DEVICE POSITION (cheek or rotated): CHEEK

Antenna Position: FIXED

Battery Model #: SNN5683A

R#1 TP-1154 GLYCOL SAM Expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 1880 MHz


Probe: ES3DV3 - SN3037 - IEEE Head; ConvF(4.90,4.90,4.90); Crest factor: 8.0; 1880 MHz Head & Body:  $\sigma = 1.46$  mho/m  $\epsilon_r = 40.0$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.740 mW/g, SAR (10g): 0.412 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 11.1 (10.9, 11.3) [mm]

Powerdrift: -0.47 dB






Figure 1. Typical 800MHz Head Adjacent Contour Overlaid on Phone (Cheek Touch)




Figure 2. Typical 1900MHz Head Adjacent Contour Overlaid on Phone (Cheek Touch)

s/n: 4400007583659

Ch# 189 / Pwr Step: 5 OTA  
Type of Modulation: 850 GSM

Antenna Position: FIXED  
Battery Model #: SNN5683A

DEVICE POSITION (cheek or rotated): TILTED

R1 TP-1005 SUGAR SAM Expanded (Rev. 2)-9Jan03 Phantom; Right Hand Section; Position: (90°,180°); Frequency: 836 MHz


Probe: ES3DV3 - SN3037 - IEEE Head; ConvF(6.10,6.10,6.10); Crest factor: 8.0; 835 MHz Head & Body:  $\sigma = 0.92$  mho/m  $\epsilon_r = 42.8$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.323 mW/g, SAR (10g): 0.249 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 15.0

Penetration depth: 21.7 (20.8, 22.6) [mm]

Powerdrift: 0.00 dB



s/n: 4400007583659

Ch# 661 / Pwr Step: 0

Type of Modulation: 1900 GSM

DEVICE POSITION (cheek or rotated): TILTED

Antenna Position: FIXED

Battery Model #: SNN5683A

R#1 TP-1154 GLYCOL SAM Expanded (Rev. 2)-9Jan03 Phantom; Left Hand Section; Position: (90°,180°); Frequency: 1880 MHz


Probe: ES3DV3 - SN3037 - IEEE Head; ConvF(4.90,4.90,4.90); Crest factor: 8.0; 1880 MHz Head & Body:  $\sigma = 1.46$  mho/m  $\epsilon_r = 40.0$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.354 mW/g, SAR (10g): 0.222 mW/g, (Worst-case extrapolation)

Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0

Penetration depth: 12.1 (12.0, 12.3) [mm]

Powerdrift: 0.05 dB






Figure 3. Typical 800MHz Head Adjacent Contour Overlaid on Phone (15 ° Tilt)




Figure 4. Typical 1900MHz Head Adjacent Contour Overlaid on Phone (15 ° Tilt)

### **Appendix 3**

#### **SAR distribution plots for Body Worn Configuration**

s/n: 4400007583659

Ch# 189 / Pwr Step: 5 OTA

Type of Modulation: 850 GSM

Accessory Model #: BACK OF PHONE 15MM AWAY FROM FLAT PHANTOM

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 1 Section; Position: (0°,0°); Frequency: 836 MHz

Probe: ES3DV3 - SN3037 - FCC Body; ConvF(5.90,5.90,5.90); Crest factor: 8.0; 835 MHz Head & Body:  $\sigma = 0.98$  mho/m  $\epsilon_r = 55.1$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.502 mW/g, SAR (10g): 0.349 mW/g, (Worst-case extrapolation)



Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 16.2 (15.6, 16.9) [mm]

Powerdrift: -0.02 dB

Antenna Position: FIXED

Battery Model #: SNN5683A

SAR<sub>Tot</sub> [mW/g]

s/n: 4400007583659

Ch# 189 / Pwr Step: 5 OTA

Antenna Position: FIXED

Type of Modulation: 850 GSM (BLUETOOTH)

Battery Model #: SNN5683A

Accessory Model #: BACK OF PHONE 15MM AWAY FROM FLAT PHANTOM

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 1 Section; Position: (0°,0°); Frequency: 836 MHz


Probe: ES3DV3 - SN3037 - FCC Body; ConvF(5.90,5.90,5.90); Crest factor: 8.0; 835 MHz Head & Body:  $\sigma = 0.98$  mho/m  $\epsilon_r = 55.1$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.565 mW/g, SAR (10g): 0.397 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 16.8 (16.4, 17.2) [mm]

Powerdrift: -0.01 dB



s/n: 4400007583659

Ch# 189 / Pwr Step: 5 OTA

Type of Modulation: GPRS850

Accessory Model #: BACK OF PHONE 25mm AWAY FROM FLAT PHANTOM

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 1 Section; Position: (0°,0°); Frequency: 836 MHz

Probe: ES3DV3 - SN3037 - FCC Body; ConvF(5.90,5.90,5.90); Crest factor: 4.0; 835 MHz Head & Body:  $\sigma = 0.98$  mho/m  $\epsilon_r = 55.1$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.406 mW/g, SAR (10g): 0.294 mW/g, (Worst-case extrapolation)



Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 17.9 (17.7, 18.2) [mm]

Powerdrift: -0.03 dB

Antenna Position: FIXED

Battery Model #: SNN5683A

SAR<sub>Tot</sub> [mW/g]

s/n: 4400007583659

Ch# 189 / Pwr Step: 08 (TM)

Type of Modulation: 850 GSM EDGE

Antenna Position: FIXED

Battery Model #: SNN5683A

Accessory Model #: Back of Phone 1" Away from Flat Phantom

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 1 Section; Position: (0°,0°); Frequency: 836 MHz


Probe: ES3DV3 - SN3037 - FCC Body; ConvF(5.90,5.90,5.90); Crest factor: 8.0; 835 MHz Head & Body:  $\sigma = 0.98$  mho/m  $\epsilon_r = 55.1$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.0844 mW/g, SAR (10g): 0.0618 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 18.7 (18.1, 19.0) [mm]

Powerdrift: -0.05 dB



s/n: 4400007583659

Ch# 661 / Pwr Step: 0 OTA

Type of Modulation: 1900 GSM

Accessory Model #: Back of Phone 15mm Away from Phantom

Antenna Position: FIXED

Battery Model #: SNN5683A

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 2 Section; Position: (0°,0°); Frequency: 1880 MHz


Probe: ES3DV3 - SN3037 - FCC Body; ConvF(4.70,4.70,4.70); Crest factor: 8.0; 1880 MHz Head & Body:  $\sigma = 1.59$  mho/m  $\epsilon_r = 51.9$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.295 mW/g, SAR (10g): 0.173 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 10.8 (10.6, 11.1) [mm]

Powerdrift: -0.05 dB



s/n: 4400007583659

Ch# 661 / Pwr Step: 0 OTA

Antenna Position: FIXED

Type of Modulation: 1900 GSM (BLUETOOTH) Battery Model #: SNN5683A

Accessory Model #: Back of Phone 15mm Away from Phantom

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 2 Section; Position: (0°,0°); Frequency: 1880 MHz


Probe: ES3DV3 - SN3037 - FCC Body; ConvF(4.70,4.70,4.70); Crest factor: 8.0; 1880 MHz Head & Body:  $\sigma = 1.59$  mho/m  $\epsilon_r = 51.9$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.306 mW/g, SAR (10g): 0.182 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 11.1 (10.8, 11.6) [mm]

Powerdrift: -0.05 dB



s/n: 4400007583659

Ch# 661 / Pwr Step: 0 OTA

Type of Modulation: GPRS1900

Accessory Model #: Back of Phone 25mm Away from Phantom

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 2 Section; Position: (0°,0°); Frequency: 1880 MHz

Probe: ES3DV3 - SN3037 - FCC Body; ConvF(4.70,4.70,4.70); Crest factor: 4.0; 1880 MHz Head & Body:  $\sigma = 1.59$  mho/m  $\epsilon_r = 51.9$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.222 mW/g, SAR (10g): 0.142 mW/g, (Worst-case extrapolation)


Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 12.6 (11.6, 14.0) [mm]

Powerdrift: -0.06 dB

Antenna Position: FIXED

Battery Model #: SNN5683A

SAR<sub>Tot</sub> [mW/g]

2.30E-1

2.07E-1

1.84E-1

1.61E-1

1.38E-1

1.15E-1

9.20E-2

6.90E-2

4.60E-2

2.30E-2

s/n: 4400007583659

Ch# 661 / Pwr Step: 02 (TM)

Antenna Position: FIXED

Type of Modulation: 1900 GSM EDGE

Battery Model #: SNN5683A

Accessory Model #: Back of Phone 1" Away from Flat Phantom

R1 Amy Twin Phantom Rev.4 (22Aug02) Phantom; section 2 Section; Position: (0°,0°); Frequency: 1880 MHz


Probe: ES3DV3 - SN3037 - FCC Body; ConvF(4.70,4.70,4.70); Crest factor: 8.0; 1880 MHz Head & Body:  $\sigma = 1.58$  mho/m  $\epsilon_r = 51.0$   $\rho = 1.00$  g/cm<sup>3</sup>

Cube 7x7x7: SAR (1g): 0.0612 mW/g, SAR (10g): 0.0392 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Penetration depth: 12.7 (10.2, 16.4) [mm]

Powerdrift: -0.12 dB






Figure 5. Typical 800 MHz Body-Worn Contour Overlaid on Phone




Figure 6. Typical 1900 MHz Body-Worn Contour Overlaid on Phone

**Appendix 4**  
**Probe Calibration Certificate**

Client

Motorola MRO

**CALIBRATION CERTIFICATE**

Object(s) **ES3DV3 - SN 3037**

Calibration procedure(s) **QA CAL-01 v2  
 Calibration procedure for dosimetric E-field probes**

Calibration date: **October 10, 2003**



Condition of the calibrated item **In Tolerance (according to the specific calibration document)**

This calibration statement documents traceability of M&TE used in the calibration procedures and conformity of the procedures with the ISO/IEC 17025 international standard.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

Model Type	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM E4419B	GB41293874	2-Apr-03 (METAS, No 252-0250)	Apr-04
Power sensor E4412A	MY41495277	2-Apr-03 (METAS, No 252-0250)	Apr-04
Reference 20 dB Attenuator	SN: 5086 (20b)	3-Apr-03 (METAS No. 251-0340)	Apr-04
Fluke Process Calibrator Type 702	SN: 6295803	8-Sep-03 (Sintrel SCS No. E-030020)	Sep-04
Power sensor HP 8481A	MY41092180	18-Sep-02 (Agilent, No. 20020918)	In house check: Oct 03
RF generator HP 8684C	US3642U01700	4-Aug-99 (SPEAG, in house check Aug-02)	In house check: Aug-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (Agilent, No. 24BR1033101)	In house check: Oct 03

	Name	Function	Signature
Calibrated by:	Katja Pokovic	Laboratory Director	
Approved by:	Fin Bernholt	R&D Director	

Date issued: October 10, 2003

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

# Probe ES3DV3

**SN:3037**

**Manufactured: August 21, 2003**  
**Last calibration: October 10, 2003**

**Calibrated for DASY Systems**

**(Note: non-compatible with DASY2 system!)**

**DASY - Parameters of Probe: ES3DV3 SN:3037****Sensitivity in Free Space**

NormX	<b>1.13</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	<b>0.85</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	<b>0.95</b> $\mu\text{V}/(\text{V}/\text{m})^2$

**Diode Compression**

DCP X	<b>100</b> mV
DCP Y	<b>100</b> mV
DCP Z	<b>100</b> mV

**Sensitivity in Tissue Simulating Liquid**

**Head**                    **900 MHz**                     $\epsilon_r = 41.5 \pm 5\%$                      $\sigma = 0.97 \pm 5\%$  mho/m  
**Valid for f=800-1000 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X**

ConvF X	<b>6.1</b> $\pm 9.5\%$ (k=2)	Boundary effect:	
ConvF Y	<b>6.1</b> $\pm 9.5\%$ (k=2)	Alpha	<b>0.31</b>
ConvF Z	<b>6.1</b> $\pm 9.5\%$ (k=2)	Depth	<b>1.75</b>

**Head**                    **1800 MHz**                     $\epsilon_r = 40.0 \pm 5\%$                      $\sigma = 1.40 \pm 5\%$  mho/m  
**Valid for f=1710-1910 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X**

ConvF X	<b>4.9</b> $\pm 9.5\%$ (k=2)	Boundary effect:	
ConvF Y	<b>4.9</b> $\pm 9.5\%$ (k=2)	Alpha	<b>0.24</b>
ConvF Z	<b>4.9</b> $\pm 9.5\%$ (k=2)	Depth	<b>2.68</b>

**Boundary Effect**

<b>Head</b>	<b>900 MHz</b>	<b>Typical SAR gradient: 5 % per mm</b>	
	Probe Tip to Boundary	<b>1 mm</b>	<b>2 mm</b>
	SAR <sub>be</sub> [%] Without Correction Algorithm	<b>6.0</b>	<b>3.0</b>
	SAR <sub>be</sub> [%] With Correction Algorithm	<b>0.1</b>	<b>0.3</b>


<b>Head</b>	<b>1800 MHz</b>	<b>Typical SAR gradient: 10 % per mm</b>	
	Probe Tip to Boundary	<b>1 mm</b>	<b>2 mm</b>
	SAR <sub>be</sub> [%] Without Correction Algorithm	<b>8.5</b>	<b>5.5</b>
	SAR <sub>be</sub> [%] With Correction Algorithm	<b>0.1</b>	<b>0.2</b>

**Sensor Offset**


Probe Tip to Sensor Center                    **2.0**                    mm

### Receiving Pattern ( $\phi$ , $\theta = 0^\circ$ )


**f = 30 MHz, TEM cell ifi110**




**f = 100 MHz, TEM cell ifi110**





**f = 300 MHz, TEM cell ifi110**




**f = 900 MHz, TEM cell ifi110**






**Isotropy Error ( $\phi$ ),  $\theta = 0^\circ$**





# Frequency Response of E-Field


( TEM-Cell:ifi110, Waveguide R22)



# Dynamic Range f(SAR<sub>brain</sub>) ( Waveguide R22 )




# Conversion Factor Assessment



<b>Head</b>	<b>900 MHz</b>	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
Valid for f=800-1000 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X			
ConvF X	<b>6.1</b>	$\pm 9.5\% (k=2)$	Boundary effect:
ConvF Y	<b>6.1</b>	$\pm 9.5\% (k=2)$	Alpha <b>0.31</b>
ConvF Z	<b>6.1</b>	$\pm 9.5\% (k=2)$	Depth <b>1.75</b>

<b>Head</b>	<b>1800 MHz</b>	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
Valid for f=1710-1910 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X			
ConvF X	<b>4.9</b>	$\pm 9.5\% (k=2)$	Boundary effect:
ConvF Y	<b>4.9</b>	$\pm 9.5\% (k=2)$	Alpha <b>0.24</b>
ConvF Z	<b>4.9</b>	$\pm 9.5\% (k=2)$	Depth <b>2.68</b>

# Conversion Factor Assessment



**Body**                      **900 MHz**                       $\epsilon_r = 55.0 \pm 5\%$                        $\sigma = 1.05 \pm 5\% \text{ mho/m}$

Valid for f=800-1000 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C


ConvF X	<b>5.9</b> $\pm$ 9.5% (k=2)	Boundary effect:	
ConvF Y	<b>5.9</b> $\pm$ 9.5% (k=2)	Alpha	<b>0.29</b>
ConvF Z	<b>5.9</b> $\pm$ 9.5% (k=2)	Depth	<b>1.91</b>

**Body**                      **1800 MHz**                       $\epsilon_r = 53.3 \pm 5\%$                        $\sigma = 1.52 \pm 5\% \text{ mho/m}$

Valid for f=1710-1910 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C

ConvF X	<b>4.7</b> $\pm$ 9.5% (k=2)	Boundary effect:	
ConvF Y	<b>4.7</b> $\pm$ 9.5% (k=2)	Alpha	<b>0.25</b>
ConvF Z	<b>4.7</b> $\pm$ 9.5% (k=2)	Depth	<b>2.80</b>

# Conversion Factor Assessment



**Head                      1950 MHz                       $\epsilon_r = 40.0 \pm 5\%$                        $\sigma = 1.40 \pm 5\%$  mho/m**

**Valid for f=1900-2000 MHz with Head Tissue Simulating Liquid according to EN 50361, P1528-200X**

ConvF X	<b>4.7</b> $\pm$ 9.5% (k=2)	Boundary effect:	
ConvF Y	<b>4.7</b> $\pm$ 9.5% (k=2)	Alpha	<b>0.28</b>
ConvF Z	<b>4.7</b> $\pm$ 9.5% (k=2)	Depth	<b>2.26</b>


**Body                      1950 MHz                       $\epsilon_r = 53.3 \pm 5\%$                        $\sigma = 1.52 \pm 5\%$  mho/m**

**Valid for f=1900-2000 MHz with Body Tissue Simulating Liquid according to OET 65 Suppl. C**

ConvF X	<b>4.5</b> $\pm$ 9.5% (k=2)	Boundary effect:	
ConvF Y	<b>4.5</b> $\pm$ 9.5% (k=2)	Alpha	<b>0.31</b>
ConvF Z	<b>4.5</b> $\pm$ 9.5% (k=2)	Depth	<b>2.24</b>

# Deviation from Isotropy in HSL

Error ( $\theta, \phi$ ),  $f = 900$  MHz



**Appendix 5**  
**Dipole Characterization Certificate**

# Certification of System Performance Check Targets

Based on APP-0396

-Historical Data-

	835MHz	900MHz	1800MHz	1900MHz	
IEEE1528 Target: Advanced Extrapolation	9.5	10.8	38.1	39.7	(W/kg)
Measurement Uncertainty (k=1):	9.0%	9.0%	9.0%	9.0%	
Measurement Period:	1-July-03 to 1-Apr-04	1-July-03 to 1-Apr-04	1-July-03 to 1-Apr-04	1-July-03 to 1-Apr-04	
# of tests performed:	214	1148	1135	62	
Grand Average: Worst Case Extrapolation	10.0	11.4	40.7	42.0	(W/kg)
% Delta (Average - IEEE1528 Target)	5.3%	5.6%	6.8%	5.8%	
Is % Delta <= Measurement Uncertainty?	Yes	Yes	Yes	Yes	
Accept/Reject <u>Average</u> as new system performance check target?	<b>ACCEPT</b>	<b>ACCEPT</b>	<b>ACCEPT</b>	<b>ACCEPT</b>	
	Applicable 835MHz Dipole Serial Numbers:	Applicable 900MHz Dipole Serial Numbers:	Applicable 1800MHz Dipole Serial Numbers:	Applicable 1900MHz Dipole Serial Numbers:	
	420(TR), 421(TR)	77, 78	246(TR), 250(TR)	514(TR), 518(TR)	
	422(TR), 423(TR)	79, 80	251(TR), 258(TR)	519(TR), 520(TR)	
	424(TR), 425(TR)	91, 92	259(TR), 262(TR)	523(TR), 524(TR)	
	431(TR), 432(TR)	93, 94	263(TR), 271(TR)	526(TR), 527(TR)	
	433(TR), 434(TR)	95, 96	272(TR), 273(TR)	528(TR), 529(TR)	
	436(TR)	97, 55	276(TR), 277(TR)	530(TR), 533(TR)	
			279(TR), 280(TR)		
			281(TR), 282(TR)		
			283(TR), 284(TR)		


-New System Performance Check Targets- per APP-0396

(based on analysis of historical data)

Frequency	SAR Target (W/kg)	Permittivity	Conductivity (S/m)
835MHz	10.0	41.5 ± 5%	0.90 ± 5%
900MHz	11.4	41.5 ± 5%	0.97 ± 5%
1800MHz	40.7	40.0 ± 5%	1.40 ± 5%
1900MHz	42.0	40.0 ± 5%	1.40 ± 5%

-Approvals-

Submitted by:  Date:

Signed: 

Comments:

Approved by:  Date:

Signed: 

Comments:

**Appendix 6**  
**Measurement Uncertainty Budget**

<b>Uncertainty Budget for Device Under Test</b>									
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
<b>Uncertainty Component</b>	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c<sub>i</sub></i> (1 g)	<i>c<sub>i</sub></i> (10 g)	1 g <i>u<sub>i</sub></i> (±%)	10 g <i>u<sub>i</sub></i> (±%)	<i>v<sub>i</sub></i>
<b>Measurement System</b>									
Probe Calibration	E.2.1	9.5	N	2.00	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	5.8	R	1.73	1	1	3.3	3.3	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1.00	1	1	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1	1	0.5	0.5	∞
Integration Time	E.2.8	1.3	R	1.73	1	1	0.8	0.8	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.3	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	1.1	R	1.73	1	1	0.6	0.6	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	3.9	R	1.73	1	1	2.3	2.3	∞
<b>Test sample Related</b>									
Test Sample Positioning	E.4.2	3.6	N	1.00	1	1	3.6	3.6	29
Device Holder Uncertainty	E.4.1	2.8	N	1.00	1	1	2.8	2.8	8
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	10.0	R	1.73	0.64	0.43	3.7	2.5	∞
Liquid Permittivity - deviation from target values	E.3.2	10.0	R	1.73	0.6	0.49	3.5	2.8	∞
Liquid Permittivity - measurement uncertainty	E.3.3	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
<b>Combined Standard Uncertainty</b>			RSS				11.72	11.09	1363
<b>Expanded Uncertainty (95% CONFIDENCE LEVEL)</b>			<i>k</i> =2				22.98	21.75	

**Uncertainty Budget for System Performance Check (dipole & flat phantom)**

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>f</i>	<i>g</i>	$h = c \times f / e$	$i = c \times g / e$	<i>k</i>
<b>Uncertainty Component</b>	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c<sub>i</sub></i> (1 g)	<i>c<sub>i</sub></i> (10 g)	1 g <i>u<sub>i</sub></i> (±%)	10 g <i>u<sub>i</sub></i> (±%)	<i>v<sub>i</sub></i>
<b>Measurement System</b>									
Probe Calibration	E.2.1	9.5	N	2.00	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	5.8	R	1.73	1	1	3.3	3.3	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1.00	1	1	1.0	1.0	∞
Response Time	E.2.7	0.0	R	1.73	1	1	0.0	0.0	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.3	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	1.1	R	1.73	1	1	0.6	0.6	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	3.9	R	1.73	1	1	2.3	2.3	∞
<b>Dipole</b>									
Dipole Axis to Liquid Distance	8, E.4.2	1.0	R	1.73	1	1	0.6	0.6	∞
Input Power and SAR Drift Measurement	8, 6.6.2	4.7	R	1.73	1	1	2.7	2.7	∞
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	10.0	R	1.73	0.64	0.43	3.7	2.5	∞
Liquid Permittivity - deviation from target values	E.3.2	10.0	R	1.73	0.6	0.49	3.5	2.8	∞
Liquid Permittivity - measurement uncertainty	E.3.3	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
<b>Combined Standard Uncertainty</b>			RSS				10.16	9.43	99999
<b>Expanded Uncertainty (95% CONFIDENCE LEVEL)</b>			<i>k</i> =2				19.92	18.48	

## **Appendix 7**

### **Photographs of the device under test**







