



July 21, 2005

Supplement to SAR Test Report for Motorola portable cellular phone (FCC ID IHDT56FF1)

Prepared by:

Paul Ma

Motorola Personal Communications Sector Product Safety Laboratory

Libertyville, Illinois

FCC Request for Corrections

There has been a request for corrections regarding the Edge power values in the two tables below. Changes have been made to the first table as follows:

Max Output Power Setting: Edge 850, 900, 1800, &1900 to 29.0, 29.0, 28.0, & 28.0 dBm, respectively.

FCC ID Number	IHDT56FF1												
Serial number	TA19000430												
Mode(s) of Operation	GSM 850	GSM 900	GSM 1800	GSM 1900	GPRS 850	GPRS 900	GPRS 1800	GPRS 1900	EDGE 850	EDGE 900	EDGE 1800	EDGE 1900	BlueTooth
Modulation Mode(s)	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	8PSK	8PSK	8PSK	8PSK	GMSK
Maximum Output Power Setting	33.00 dBm	33.00 dBm	30.00 dBm	30.00 dBm	33.00 dBm	33.00 dBm	30.00 dBm	30.00 dBm	29.00 dBm	29.00 dBm	28.00 dBm	28.00 dBm	0.00 - 4.00 dBm
Duty Cycle	1:8	1:8	1:8	1:8	2:8	2:8	2:8	2:8	2:8	2:8	2:8	2:8	1:1
Transmitting Frequency Rang(s)	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.2 - 1909.8 MHz	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.2 - 1909.8 MHz	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.2 - 1909.8 MHz	2400 - 2483.5 MHz
Production Unit or Identical Prototype (47 CFR §2.908)	Identical Prototype												
Device Category	Portable												
RF Exposure Limits	General Population / Uncontrolled												

Changes have been made to the Body worn SAR table as follows:

Conducted Output Power: 850MHz to 27.98 dBm and 1900 MHz to 27.97 dBm

f (MHz)	Description	Conducted Output Power (dBm)	Body Worn			
			Back of phone 25 mm away from phantom (EDGE Class 6)			
			Measured (W/kg)	Drift (dB)	Extrapolated (W/kg)	Simulate Temp (°C)
Digital 850MHz	Channel 128					
	Channel 190	27.98	0.085	-0.09	0.09	20.0
	Channel 251					
Digital 1900MHz	Channel 512					
	Channel 661	27.97	0.125	-0.13	0.13	20.1
	Channel 810					