



**MOTOROLA**

**MOBILE DEVICES BUSINESS**

**PRODUCT SAFETY AND COMPLIANCE  
EMC LABORATORY**

**EMC TEST REPORT**

**Test Report Number** – 16757-1

**Report Date** – August 23, 2005

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

A handwritten signature in blue ink that reads "Michael E. Hill".

Signature

Name: Michael E. Hill

Title: Senior Staff Electrical Engineer

Date: August 23, 2005

This report must not be reproduced, except in full, without written approval from this laboratory.

THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.

A2LA Certificate Number: 1846-01



**Table of Contents**

<u>Description</u>	<u>Page</u>
Test Report Details	4
Applicable Standards	4
Summary of Testing	5
General and Special Conditions	5
Equipment and Cable Configurations	6
Measuring Equipment and Calibration Information	7
Measurement Procedures and Data	
RF Power Output	7
Radiated Power (ERP)	9
Occupied Bandwidth	10
GSM 850 Reference Plot	11
GSM 850 Occupied Bandwidth Plot	11
GSM 850 Ch128 Lower Band Edge	12
GSM 850 Ch251 Upper Band Edge	12
GSM 1900 Reference Plot	13
GSM 1900 Occupied Bandwidth Plot	13
GSM 1900 Ch512 Lower Band Edge	14
GSM 1900 Ch810 Upper Band Edge	14
GSM 850 Edge Occupied Bandwidth Plot	15
GSM 850 Edge Lower Band Edge	15
GSM 850 Edge Upper Band Edge	16
GSM 1900 Edge Occupied Bandwidth Plot	17
GSM 1900 Edge Lower Band Edge	17
GSM 1900 Edge Upper Band Edge	18
Spurious Emissions at Antenna Terminals	19
GSM 850 Tabular and Graphical Data	20
GSM 1900 Tabular and Graphical Data	21
Field Strength of Spurious Emissions	22
GSM 850 Tabular and Graphical Data	23
GSM 1900 Tabular and Graphical Data	24

Frequency Stability	25
GSM 850 Tabular and Graphical Data	26
GSM 1900 Tabular and Graphical Data	27
Field Strength of Spurious Emissions from Unintentional Radiators	28
GSM 850 Tabular and Graphical Data	29
GSM 1900 Tabular and Graphical Data	30
Appendix A - Radiated Emissions Test Setup Photos	
Figure A.1 – Radiated Emissions Measurement	31
Figure A.2 – Substitution Measurement	31

**Test Report Details**

Tests Performed By: Motorola Mobile Devices business  
 Product Safety and Compliance Group  
 600 North US Hwy 45  
 Libertyville, IL 60048  
 PH (847) 523-6167 Fax (847) 523-4538  
 Motorola MDB FRN: 0004321311  
 FCC Registration Number: 316588  
 Industry Canada Number: IC3908

Tests Requested By: Motorola Inc.  
 Mobile Devices business  
 600 North US Hwy 45  
 Libertyville, IL 60048

Product Type: Cellular Phone

Signaling Capability: GSM 850, 1900  
 Model Number: V6

Version: SJUG0076SA

Serial Numbers: 004400013926090,  
 004400013926264,004400013926140

Testing Complete Date: August 21, 2005

**Applicable Standards**

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

- Part 15 Subpart B – Unintentional Radiators
- Part 22 Subpart H - Public Mobile Services
- Part 24 - Personal Communications Services
- Part 90 - Private Land Mobile Radio Service

Applicable Standards: TIA EIA 137-A, TIA EIA 98-C, ANSI 63.4 2001, RSS-118 (AMPS), RSS-128 (TDMA), RSS-129 (CDMA), RSS-133 (PCS)

**Summary of Testing**

Test #	Test Name	Pass/Fail
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	Pass
3	Modulation Characteristics	NA
4	Occupied Bandwidth	Pass
5	Spurious Emissions at Antenna Terminal	Pass
6	Field Strength of Spurious Emissions	Pass
7	Frequency Stability	Pass
8	Field Strength of Spurious Emissions from Unintentional Radiators	Pass

Test #	Test Name	Margin with respect to the Limit
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	3.07
3	Modulation Characteristics	NA
4	Occupied Bandwidth	See Plots
5	Spurious Emissions at Antenna Terminal	21.3 dB
6	Field Strength of Spurious Emissions	1.8 dB
7	Frequency Stability	26.4 Hz
8	Field Strength of Spurious Emissions from Unintentional Radiators	Below noise floor

The margin with respect to the limit is the minimum margin for all modes and bands. ( ) indicates the margin at which the product exceeds the limit.

**General and Special Conditions**

The EUT was tested using a fully charged battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment with an average temperature of 22° C and relative humidity of 50%.

**Equipment and Cable Configurations**

The EUT was tested in a stand-alone configuration that is representative of typical use.

<b>Manufacturer</b>	<b>Equipment Type</b>	<b>Model No.</b>	<b>Serial Number</b>	<b>Cal. Due Date</b>
Rohde & Schwarz	Receiver	ESI26	838786/010	2/7/2006
Hewlett-Packard	EMC Analyzer	8593EM	3536A00118	10/2/2005
Hewlett-Packard	EMC Analyzer	7405	US39440191	11/13/2005
ETS	DRG Horn Antenna	265	2455	5/25/2006
ETS	DRG Horn Antenna	3115	6222	2/9/2006
ETS	Log-Periodic Antenna	3148	1188	6/14/2006
ETS	Biconical Antenna	3110B	3370	2/16/2006
Attenuator	Weinschel	AS-6	6675	10/14/2005
Attenuator	Weinschel	AS-6	6677	11/4/2005
Rohde & Schwarz	Mobile Test Set	CMD 80	DE29008	N/A
Hewlett-Packard	Signal Generator	83623B	3844A01195	5/23/2006
Thermotron	Environmental Chamber	S-4	31580	1/18/2006
Giga-Tronics	Power Meter	8651A	8650508	12/27/2005

All equipment is on a one-year calibration cycle.

**Measurement Procedures and Data**

**RF POWER OUTPUT**

**Measurement Procedure**

The RF output port of the equipment under test is directly coupled to the input of a HPE4406A Vector Signal Analyzer through a 10dB passive attenuator, adaptor (if needed), and specialized RF connector. The peak power output is measured for all channels.

CFR47 Part 2.1046

**Measurement Results**

**GSM 850**

Frequency (MHz)	Power (dBm)
824.2	32.97
836.6	32.98
848.8	32.93

**GSM 1900**

Frequency (MHz)	Power (dBm)
1850.20	30.00
1880.00	29.94
1909.80	29.96

## RADIATED (ERP)

### Measurement Procedure

The phone was tested in a 16' anechoic chamber with a 2-axis position system that permits taking complete spherical scans of the EUT's radiation patterns. For all tests, the phone was supported in a free space type environment, vertically oriented in the chamber. Tests were done for GSM 850 three frequencies (824.2, 836.6 and 848.8 MHz) and GSM 1900 three frequencies (1850.2, 1880.00, and 1909.80 MHz) with antenna stubby.

GSM measurements were made with the phone placed in a call using the Agilent 8960 mobile station test set. The phone was weakly coupled to the test set and configured to transmit in full data rate mode. Radiated power was measured at each 15 degree step. The radiated power was measured using a Gigatronics 8542C power meter in "Burst Avg" mode. From these measurements, the software calculates the angle at which maximum radiated power occurs for each case, and the radiated power at this angle was extracted from the data. The max radiated power results for the IHDT56FE1 follows, as EIRP in dBm. To get ERP (effective radiated power referenced to a half-wave dipole), subtract 2.1 dB from these numbers.

### Measurement Results

Data not supplied by EMC Lab

GSM 850:	
824.2 MHz	30.19 dBm
836.6 MHz	31.22 dBm
848.8 MHz	32.03 dBm

GSM 1900:	
1850.2 MHz:	32.82 dBm
1880.0 MHz:	32.31 dBm
1909.8 MHz:	32.32 dBm

For all measurements, calibration was performed via gain substitution with a half-wave dipole.

The max EIRP in GSM 850 mode is 32.03 dBm (**max ERP is 29.93 dBm**)  
**The max EIRP in GSM 1900 mode is 32.82 dBm** (max ERP is 30.72 dBm)

## OCCUPIED BANDWIDTH

CFR Part 2.1049, 22.917, 24.238

### Measurement Procedure

The RF output port of the equipment under test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. The amplitude of the spectrum analyzer is corrected for the attenuator and any other applicable losses. The analyzer is set for Peak Detector and each trace is set for Max Hold. A fully charged battery was used for the supply voltage.

The middle channel within the designated frequency block was measured. For digital modulation, the lower and upper band edge plots are displayed.

### Equipment Settings

Plot	Resolution Bandwidth (kHz)	Video Bandwidth (kHz)	Sweep Points (#)	Trace Mode	Detector	Samples (≥ #)
Reference Plot - GSM 850	300	Auto	1001	Max Hold	Peak	30
OCBW - GSM 850	3	Auto	1001	Max Hold	Peak	30
Lower Band Edge - GSM 850	1	Auto	2004	Max Hold	Peak	30
Upper Band Edge - GSM 850	1	Auto	2004	Max Hold	Peak	30
Reference Plot - GSM 1900	300	Auto	1001	Max Hold	Peak	30
OCBW - GSM 1900	3	Auto	1001	Max Hold	Peak	30
Lower Band Edge - GSM 1900	1	Auto	2004	Max Hold	Peak	30
Upper Band Edge - GSM 1900	1	Auto	2004	Max Hold	Peak	30


- Notes: 1) When the video bandwidth is set to Auto the video bandwidth self adjusts for <sup>3</sup> the resolution bandwidth.  
 2) The plotted data shown for the band edge measurements is representative of data taken with a true 3 kHz resolution bandwidth filter. The raw data was taken using a 1 kHz resolution bandwidth and was integrated to produce a response representative of data taken using a true 3 kHz resolution bandwidth filter.

### Measurement Results


Attached

### Measurement Results – GSM 850


#### GSM 850 Reference Level




#### GSM 850 Occupied Bandwidth



### GSM 850 Ch128 Lower Band Edge




### GSM 850 Ch251 Upper Band Edge




### Measurement Results – GSM 1900


#### GSM/PCS 1900 Reference Level




#### GSM/PCS 1900 Occupied Bandwidth



### GSM/PCS 1900 Ch512 Lower Band Edge



### GSM/PCS 1900 Ch810 Upper Band Edge



## **SPURIOUS EMISSIONS AT ANTENNA TERMINALS**

CFR47 Part 2.1051, 24.238

### **Measurement Procedure**

The RF output port of the Equipment Under Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

The spectrum was investigated from the lowest frequency signal generated, without going below 9 kHz, up to at least the tenth harmonic of the fundamental or 40 GHz, whichever is lower.

Measurements were made at the middle channel within the frequency band and within the base station frequency range (869-894 MHz) for cellular.

The spectrum analyzer settings were as follows:

Units	dBm
Divisions	10 dB
Resolution Bandwidth	1 MHz
Video Bandwidth (AVG)	Auto
Sweep Time	Auto


### **Measurement Results**

Attached

**Measurement Results**  
**Modulation: GSM 850**

**Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-39.5
3rd harmonic	-13	-39.8
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	-41.3
9th harmonic	-13	*
10th harmonic	-13	*




Notes:

- \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
- Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

**Measurement Results**  
**Modulation: GSM 1900**

**Conducted Spurious and Harmonic Emissions**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-39.8
3rd harmonic	-13	*
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	-34.3
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	-38.7



Notes:

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

## **FIELD STRENGTH OF SPURIOUS EMISSIONS**

CFR47 Part 2.1053, 22.917, 24.238

### **Measurement Procedure**

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum reading on the spectrum analyzer. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The equipment under test is then replaced with a substitution antenna fed by a signal generator. With the signal generator tuned to a particular spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters to obtain a maximum reading at the spectrum analyzer. The output of the signal generator is then adjusted until a reading identical to that obtained with the actual transmitter is achieved.

The power in dBm of each spurious emission is calculated by correcting the signal generator level for cable loss and gain of the substitution antenna referenced to a dipole. A fully charged battery was used for the supply voltage.

The settings of the receiver were as follows:

Units	dBm
Divisions	5 dB
Resolution Bandwidth	1 MHz
Video Bandwidth (AVG)	Auto
Sweep Time	Auto


### **Measurement Results**

Attached

**Measurement Results**  
**Modulation: GSM 850**

**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	-41.0	-31.9
3rd harmonic	-13	-20.3	-14.8
4th harmonic	-13	-32.5	-34.5
5th harmonic	-13	-25.2	-27.5
6th harmonic	-13	-42.5	-51.3
7th harmonic	-13	-43.7	-42.3
8th harmonic	-13	*	*
9th harmonic	-13	-36.7	-39.9
10th harmonic	-13	*	*



Notes:


1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

**Measurement Results**

**Modulation: GSM 1900**

**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	-22.8
3rd harmonic	-13	-29.4	-18.1
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*



Notes:

1. \* Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

## FREQUENCY STABILITY

CFR47 Part 2.1055, 24.235

### **Measurement Procedure**

The equipment under test is placed in an environmental chamber. The antenna port of the Equipment Under Test is directly coupled to the input of the measurement equipment through a specialized RF connector. A power supply is attached as the primary voltage supply.

Frequency measurements are made at the extremes of the temperature range -30° C to +60° C and at intervals of 10° C with the primary supply voltage set to the nominal battery operating voltage. A period of time sufficient to stabilize all components of the equipment is allowed at each frequency measurement. The maximum variation of frequency is measured.

At room temperature, the primary supply voltage is reduced to the battery operating endpoint of the equipment under test. The maximum variation of frequency is measured. A battery eliminator was used for the input supply voltage.

### **Measurement Results**


Attached

**Measurement Results**  
**Modulation: GSM850**

**Frequency Stability**

Mode: GSM 850      Operating Frequency: 836.6 MHz  
 Channel: 190      Deviation Limit (PPM): 0.1 ppm

Temperature C	Frequency Error HZ	Frequency Error (PPM)	Voltage (%)	Voltage (VDC)
-30 C	-3.16	-0.002	100%	3.60
-20 C	1.77	0.001	100%	3.60
-10 C	-1.22	-0.001	100%	3.60
0 C	-1.06	-0.001	100%	3.60
10 C	2.76	0.001	100%	3.60
20 C	-1.03	-0.001	100%	3.60
30 C	-1.06	-0.001	100%	3.60
40 C	-6.01	-0.003	100%	3.60
50 C	-6.19	-0.003	100%	3.60
60 C	-13.51	-0.007	100%	3.60
20 C	-1.78	-0.001	Battery Endpoint	3.20




**Measurement Results**  
**Modulation: GSM1900**

**Frequency Stability**

**Mode:** GSM 1900      **Operating Frequency:** 1880.0 MHz  
**Channel:** 661      **Deviation Limit (PPM):** 0.1 ppm

Temperature C	Frequency Error HZ	Frequency Error (PPM)	Voltage (%)	Voltage (VDC)
-30 C	14.74	0.008	100%	3.60
-20 C	16.56	0.009	100%	3.60
-10 C	17.58	0.009	100%	3.60
0 C	-3.34	-0.002	100%	3.60
10 C	-17.72	-0.009	100%	3.60
20 C	-22.10	-0.012	100%	3.60
30 C	-26.40	-0.014	100%	3.60
40 C	11.27	0.006	100%	3.60
50 C	6.07	0.003	100%	3.60
60 C	4.61	0.002	100%	3.60
20 C	24.13	0.013	Battery Endpoint	3.20



## FIELD STRENGTH OF EMISSIONS FROM UNINTENTIONAL RADIATORS

CFR Part 15.109

### Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each radiated emission, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum peak reading on the spectrum analyzer. The radiated emissions are then measured using an EMI receiver employing a CISPR quasi-peak detector function below 1000 MHz and an average detector function above 1000 MHz. This is repeated for both horizontal and vertical polarizations of the receive antenna. A fully charged battery was used for the supply voltage.

The field strength of each radiated emission is calculated by correcting the EMI receiver level for cable loss, amplifier gain, and antenna correction factors.

$$\text{Field Strength (dBuV/m)} = \text{EMI Receiver Level (dBuV)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)} + \text{Antenna Correction Factor (1/m)}$$


The receiver settings were as follows:

Units	dBuV
Resolution Bandwidth	30 kHz
Video Bandwidth (AVG)	Auto
Sweep Time	auto
Attenuation	10 dB
Detector	Peak

### Measurement Results


Attached

**Measurement Results**  
**Modulation: GSM 850**




### Measurement Results


### Modulation: GSM 1900



**Appendix A – Radiated Emissions Test Setup Photos**



A.1 Radiated Emissions Measurement



A.2 Substitution Measurement

**End of Test Report**