



December 06, 2005

Supplement to SAR Test Report for Motorola portable cellular phone (FCC ID IHDT56FY1)

Prepared by:

Albert Patapack

Motorola Personal Communications Sector Product Safety Laboratory

Libertyville, Illinois

Summary of FCC request for additional information

There was a request for additional information regarding Motorola’s SAR Test Report for Motorola portable cellular phone (FCC ID IHDT56FY1). The requested information is addressed below in the same numbering sequence received.

1. On p.9 of the SAR report, it is stated that a 2.5 cm separation distance was used for SAR body tests, however, the SAR Table on that page, as well as the SAR plot pages, list 1.5 cm. Please address.

**Response:** The statement on p.9 of the SAR report is a generic statement stating the maximum test separation distance at which a phone without an accessory will be tested. The actual test separation distance may be less than that. The separation stated in the body worn data tables, as well as on any body worn SAR plots, is the separation at which the phone was actually tested.

2. Please verify that the EUT is not capable of multi-slot GPRS operation.

**Response:** The table on p.3 of the test report does not contain GPRS information. The table has been correct and is attached below. As the corrected table shows, the EUT is capable of only single time-slot GPRS operation (Class 8 GPRS).

<b>FCC ID Number</b>	<b>IHDT56FY1</b>			
<b>Serial number</b>	Phone 1			
<b>Mode(s) of Operation</b>	GSM 850	GSM 1900	GPRS 850	GPRS 1900
<b>Modulation Mode(s)</b>	GSM	GSM	GSM	GSM
<b>Target Value for Maximum Output Power Setting</b>	32.40 dBm	30.20 dBm	32.40 dBm	30.20 dBm
<b>Duty Cycle</b>	1:8	1:8	1:8	1:8
<b>Transmitting Frequency Rang(s)</b>	824.2-848.8 MHz	1850.2-1909.8 MHz	824.2-848.8 MHz	1850.2-1909.8 MHz
<b>Device Category</b>	Portable			
<b>RF Exposure Limits</b>	General Population / Uncontrolled			