

Exhibit 6a. Part 90 Measured Data -- Pursuant 47 CFR. 2.1041

6a.1 Land Mobile Transmitter Power

The transmitter is a variable power type used in a SMR trunking system. Output power (as defined in 47 CFR 90.7) is dynamically controlled as described in Exhibit 12.

6a.1.1 Maximum Output Power Rating -- Pursuant 47 CFR 2.1033(c)(7) and 90.635(d)

Maximum output power rating: 640 milliwatts (28.06 dBm), pulse average power. Output power will vary from 0.22 to 640 milliwatts (pulse average power).

Note 1: Nominal output power rating: 600 milliwatts (27.78 dBm) (Pulse average power).

Note 2: These ratings are compliant with the FCC maximum of 100 watts (50 dBm) for Mobile stations

Note 3: The term pulse average power is used to specify the power that would be measured during the intervals of recurrent TDM transmission pulses by an average responding RF power meter. Power expressed in this manner is independent of the TDM duty cycle, and facilitates RF system coverage analysis.

6a.1.2 Operating output power range -- Pursuant 47 CFR 2.1033(c)(6)

Maximum tuned output power will vary over a range of 500 to 640 milliwatts (maximum pulse average power) to a minimum power of 34 dB below maximum tuned output power.

6a.1.3 DC power used by final amplifier device -- Pursuant 47 CFR 2.1033(c)(8)

In order to prevent the malfunctions that can occur due to directly measuring the DC characteristics of the final RF amplifying stage, data was obtained by measuring the entire radio DC current and is reported herein for the entire radio.

The DC current and the RF output power was measured with a special RF/DC test fixture set to supply the radio with the nominal battery voltage of 4V. The characteristics were measured during a transmission pulse and are listed in the Table below.

Characteristics	800 MHz		900 MHz	
	maximum	minimum	maximum	minimum
DC Voltage (Volts)	4.0	4.0	4.0	4.0
DC Current (A)	2.34	0.72	2	0.72
Output Power (mW)	642	0.22	638	0.22

Table 6-1 Characteristics for 800 and 900 MHz bands