



MOBILE DEVICES BUSINESS

**PRODUCT SAFETY AND COMPLIANCE
EMC LABORATORY**

EMC TEST REPORT

Test Report Number – 23695-1 WLAN

Report Date – May 17, 2010

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Signature:

A handwritten signature in black ink that reads 'Albert J. Patapack'.

Name: Albert J. Patapack

Title: EMC Engineer

Date: May 17, 2010

This report must not be reproduced, except in full, without written approval from this laboratory.

THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.

A2LA Certificate Number: 2518-02

Table of Contents

Test Report Details	3
Applicable Standards	3
Summary of Testing.....	4
General and Special Conditions.....	4
Equipment and Cable Configurations	5
Measuring Equipment and Calibration Information	5
Description of WLAN Transmitter	5
Measurement Procedures and Data.....	6
Spectrum Bandwidth.....	6
Measurement Procedure.....	6
Measurement Results	6
Peak Output Power	13
Measurement Procedure.....	13
Measurement Results	13
Power Spectral Density	17
Measurement Procedure.....	17
Measurement Results	17
Spurious RF Conducted Emissions.....	18
Measurement Procedure.....	18
Measurement Results	18
AC Line Conducted Emissions	33
Measurement Procedure.....	33
Measurement Results	33

Test Report Details

Tests Performed By: Motorola Mobile Devices business (MDb)
Product Safety and Compliance Group
600 North US Hwy 45
Libertyville, IL 60048
PH (847) 523-6167 Fax (847) 523-4538
Motorola MDb FRN: 0004321311
FCC Registration Number: 316588
Industry Canada Number: 1090-1

Tests Requested By: Motorola Inc.
Mobile Devices Business
600 North US Hwy 45
Libertyville, IL 60048

Product Type : Cellular Phone

Signaling Capability: CDMA 800, CDMA 1X/EV-DO Release 0,
Bluetooth Class 1, Version 2.1+EDR
802.11b, 802.11g

FCC ID: IHDT56LH2

Serial Numbers: TA2310004L

Testing Complete Date: May 17, 2010

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

 X Part 15 Subpart C – Intentional Radiators

Applicable Standards: ANSI 63.4 2003, RSS-210 Issue 7

Summary of Testing

Test	Test Name	Pass/Fail
1	Spectrum Bandwidth	Pass
2	Peak Power	Pass
3	Power Spectral Density	Pass
4	Spurious RF Conducted Emissions	Pass
5	AC Line Conducted Emissions	Pass

Test	Test Name	Results
1	Spectrum Bandwidth	See plots
2	Peak Power	See plots
3	Power Spectral Density	See tables
4	Spurious RF Conducted Emissions	See plots
5	AC Line Conducted Emissions	See Plots

General and Special Conditions

The Cellular Phone hereinafter referred to as the Equipment under Test or EUT was tested using a fully charged battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment. The temperature and the relative humidity were maintained within the ANSI C63.4 2003 Standard requirements during the entire duration of testing.

Equipment and Cable Configurations

The EUT was tested in a stand-alone configuration that is representative of typical use.

Measuring Equipment and Calibration Information

Manufacturer	Equipment Type	Model No.	Serial Number	Calibration Due Date
Rohde Schwarz	Receiver	ESI26	838786/010	5/01/10
Agilent	Signal Analyzer	N9020A	US46470586	12/18/10
Attenuator	Weinschel	AS-6	6675	NCR
Attenuator	Weinschel	AS-6	6677	NCR
ETS	LISN	3810/2NM	0023630	10/05/10
ETS	LISN	3810/2NM	2179	10/06/10

All test equipment was within their calibration date during the time of testing. When equipment went out of calibration during testing it was replaced using a similar piece of calibrated equipment. All these equipments are listed in the equipment list. All equipment is on a one-year calibration cycle.

Description of WLAN Transmitter

The EUT offers WLAN as a feature. The WLAN antenna is mounted inside of the EUT. The antenna installation is permanent. For a more thorough description of the functionality please refer to Exhibit 12 of this package.

As a WLAN transmitter, it is designed operate with other WLAN devices as defined by the industrial standard. In this application, the device is battery operated.

De Facto EIRP Limit – Pursuant 47 CFR 15.247(b)(4); RSS-210 Section A8.4.

Criterion: The conducted output power limit of 1-watt is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The antenna employed by this transmitter is intended to be omni-directional, and thus will not exhibit directional gain in excess of 6 dBi. The conducted power is less than the limits set forth (see elsewhere in this report for details).

Measurement Procedures and Data

Spectrum Bandwidth

CFR 47 Part 15.247

Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.



The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer used the following settings:


1. RBW $\geq$ 100 kHz
2. VBW $\geq$ RBW
3. Sweep = auto
4. Detector function = peak
5. Trace = max hold

The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate. The marker-to-peak function was used to set the marker to the peak of the emission. The marker-delta function was used to measure 6 dB down one side of the emission. The marker-delta function and marker was moved to the other side of the emission until it was even with the reference marker. The marker-delta reading at this point was the 6 dB bandwidth of the emission. The same procedure was repeated for 20 dB bandwidth.


Measurement Results

See attached


802.11 b**6 dB Bandwidth Channel 1 @ 1 Mbps****6 dB Bandwidth Channel 6 @ 1 Mbps**




6 dB Bandwidth Channel 11 @ 1 Mbps





20 dB Bandwidth Channel 1 @ 11 Mbps




20 dB Bandwidth Channel 6 @ 11 Mbps




20 dB Bandwidth Channel 11 @ 11 Mbps


802.11 g Mode**6 dB Bandwidth Channel 1 @ 6 Mbps****6 dB Bandwidth Channel 6 @ 6 Mbps**




6 dB Bandwidth Channel 11 @ 6 Mbps



20 dB Bandwidth Channel 1 @ 6 Mbps



20 dB Bandwidth Channel 6 @ 6 Mbps



20 dB Bandwidth Channel 11 @ 6 Mbps

PEAK OUTPUT POWER



CFR 47 Part 15.247


Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the Spectrum analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

Measurement Results


See Attached

802.11 b @ 11 Mbps**Max. Power Channel 1 @ 11 Mbps****Max. Power Channel 6 @ 11 Mbps**




Max. Power Channel 11 @ 11 Mbps


802.11 g @ 6 Mbps



Max. Power Channel 1 @ 6 Mbps



Max. Power Channel 6 @ 6 Mbps



Max. Power Channel 11 @ 6 Mbps

Power Spectral Density

CFR 47 Part 15.247

Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

The WLAN DSSS function of the EUT was enabled. The spectrum analyzer used the following settings:

1. Span = 300 kHz
2. VBW = 30 kHz
3. RBW = 3 kHz
4. Sweep = 50 ms
5. Detector function = peak
6. Trace = max hold

The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate.

Measurement Results

2412 MHz	2437MHz	2462MHz
-5.318dbm	-5.612dbm	-6.091dbm

802.11 b @ 11 Mbps

2412 MHz	2437MHz	2462MHz
-13.059dbm	-12.075dbm	-14.165dbm

802.11 g @ 6 Mbps

SPURIOUS RF CONDUCTED EMISSIONS



CFR 47 Part 15.247



Measurement Procedure



The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.



Measurement Results


See attached:

802.11 b @ 11Mbps**Conducted Spurious Emissions 30-3000 MHz (Low Channel)****Conducted Spurious Emissions 2-10 GHz (Low Channel)**


**Conducted Spurious Emissions 10-20 GHz (Low Channel)****Conducted Spurious Emissions 20-26.5 GHz (Low Channel)**

**Conducted Spurious Emissions 30-3000 MHz (Mid Channel)****Conducted Spurious Emissions 2-10 GHz (Mid Channel)**


**Conducted Spurious Emissions 10-20 GHz (Mid Channel)****Conducted Spurious Emissions 20-26.5 GHz (Mid Channel)**




Conducted Spurious Emissions 30-3000 MHz (High Channel)





Conducted Spurious Emissions 2-10 GHz (High Channel)




Conducted Spurious Emissions 10-20 GHz (High Channel)




Conducted Spurious Emissions 20-26.5 GHz (High Channel)



802.11 g @ 6 Mbps**Conducted Spurious Emissions 30-3000 MHz (Low Channel)****Conducted Spurious Emissions 2-10 GHz (Low Channel)**







Conducted Spurious Emissions 10-20 GHz (Low Channel)




Conducted Spurious Emissions 20-26.5 GHz (Low Channel)


**Conducted Spurious Emissions 30-3000 MHz (Mid Channel)****Conducted Spurious Emissions 2-10 GHz (Mid Channel)**

**Conducted Spurious Emissions 10-20 GHz (Mid Channel)****Conducted Spurious Emissions 20-26.5 GHz (Mid Channel)**



**Conducted Spurious Emissions 30-3000 MHz (High Channel)****Conducted Spurious Emissions 2-10 GHz (High Channel)**





Conducted Spurious Emissions 10-20 GHz (High Channel)



Conducted Spurious Emissions 20-26.5 GHz (High Channel)

802.11 b @ 11 Mbps Band edge**Channel 1 @ 11 Mbps – Lower Band Edge****Channel 11 @ 11 Mbps – Upper Band Edge**

802.11 g @ 6 Mbps Band Edge**Channel 1 @ 6 Mbps – Lower Band Edge****Channel 11 @ 6 Mbps – Upper Band Edge**

AC LINE CONDUCTED EMISSIONS

CFR 47 Part 15.207

Measurement Procedure

Measured levels of ac power line conducted emission shall be the radio-noise voltage from the line probe or across the 50 Ω LISN port, where permitted, terminated into a 50 Ω noise meter, or where permitted or required, the radio-noise current on the power line sensed by a current probe.


All radio-noise voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN. Equipment shall be tested with power cords that are normally supplied using an LISN, the 50 Ω measuring port is terminated by a 50 Ω radio-noise meter or a 50 Ω resistive load. All other ports are terminated in 50 Ω .

Detectors – Quasi Peak and Average Detector.


Measurement Results

See attached:


802.11b @ 11Mbps




WLAN Channel 1 - Tx Mode - Neutral Coupling





WLAN Channel 1 - Tx Mode – Line Coupling




WLAN Channel 6 - Tx Mode - Line Coupling




WLAN Channel 6 - Tx Mode - Neutral Coupling

**WLAN Channel 11 - Tx Mode - Line Coupling****WLAN Channel 11 - Tx Mode - Neutral Coupling**


802.11g @ 6 Mbps




WLAN Channel 1 - Tx Mode - Neutral Coupling




WLAN Channel 1 - Tx Mode - Line Coupling




WLAN Channel 6 - Tx Mode - Line Coupling



WLAN Channel 6 - Tx Mode - Neutral Coupling



WLAN Channel 11 - Tx Mode - Line Coupling



WLAN Channel 11 - Tx Mode - Neutral Coupling

End of Test Report