APPLICANT: MOTOROLA INC. FCC ID: IHDT56MB1

SPECIFICATION COMPLIANCE STATEMENT

Transceiver type (IHDT56MB1) has been tested in accordance with the requirements contained in the appropriate Commission regulations. To the best of my knowledge, these tests were performed using measurement procedures consistent with industry or Commission standards and demonstrate that this equipment complies with the appropriate standards. Each unit manufactured imported or marketed, will conform to the sample tested within the variations that can be expected due to quantity production and testing on a statistical basis.

NAME: Jongsoo Hwang

TITLE: Engineering Manager

Motorola

Mobile Mobility, Inc.

Date: Mar 30, 2011

Page 1 EXHIBIT 2

APPLICANT: MOTOROLA INC. FCC ID: IHDT56MB1

STATEMENT OF CERTIFICATION

I hereby certify that the above application was prepared under my direction and that to the best of my knowledge and belief, the facts set forth in this application and accompanying technical data are true and correct.

The technical data supplied with this application was taken under my supervision and is hereby duly certified. I also certify that this transmit equipment (IHDT56MB1) is in compliance with all applicable parts of the FCC Rules.

NAME: Jongsoo Hwang

TITLE: Engineering Manager

Motorola

Mobile Mobility, Inc.

Date: Mar 30, 2011

Page 2 EXHIBIT 2

APPLICANT: MOTOROLA INC. FCC ID: IHDT56MB1

ATTESTATION STATEMENT

This device contains an embedded Bluetooth device that Motorola confirms compliance with the following Part 15 regulations.

15.247(a)(1)

- the hopping sequence must be pseudorandom
- all Channels are used equally on average
- the receiver input bandwidth is approximately equal to the transmit bandwidth
- the receiver hops in sequence with the transmitted signal

15.247(g)

the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information)

15.247(h)

the system does not coordinate its channel selection/hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters

NAME: Jongsoo Hwang TITLE: Engineering Manager

Motorola

Motorola Mobility, Inc.

Date: Mar 30, 2011

Page 3 EXHIBIT 2

Available Carry Accessory and Spacing

Motorola Mobility attests that it is aware of carry accessories currently on the market that provide at least 25-mm of spacing between the user's body and the transceiver. As such, it is appropriate to apply the standards of Supplement C (Edition 01-01) to OET Bulletin 65, as shown in the attached RF Exposure test report.

NAME: John Lewczak

SIGNATURE:

DATE 28-Feb-2011

TITLE: Engineering Manager, Product Safety and Compliance

Page 4

DECLARATION

FCC ID: IHDT56MB1

We, Motorola Mobility, Inc. declare that GSM/GPRS 1900 is the only network used in the US territory for this product. The TD-SCDMA network functions have been disabled by the firmware and are SIM locked by all US operators on this product.

NAME: Jongsoo_Hwang TITLE: Engineering Manager

Motorola Mobility, Inc.

Date: 5/24/2011

Page 5 EXHIBIT 2