

FCC RF Test Report

APPLICANT : Motorola Mobility Inc
EQUIPMENT : Mobile phone
BRAND NAME : Motorola
MODEL NAME : WX306
TYPE NAME : M0C42
FCC ID : IHDT56MZ3
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Aug. 05, 2011 and completely tested on Aug. 12, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Testing Site.....	6
1.5 Applied Standards	6
1.6 Ancillary Equipment List	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 RF Output Power.....	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 RF Utility	10
3 TEST RESULT	11
3.1 Number of Channel Measurement	11
3.2 20dB Bandwidth Measurement	13
3.3 Hopping Channel Separation Measurement	20
3.4 Dwell Time Measurement.....	23
3.5 Peak Output Power Measurement	25
3.6 Band Edges Measurement.....	32
3.7 Spurious Emission Measurement.....	40
3.8 AC Conducted Emission Measurement.....	44
3.9 Radiated Emission Measurement.....	48
3.10 Antenna Requirements.....	57
4 LIST OF MEASURING EQUIPMENT.....	58
5 UNCERTAINTY OF EVALUATION.....	59
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR180510-01	Rev. 01	Initial issue of report	Aug. 19, 2011

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.3	15.247(a)(1)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.8	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 20.36 dB at 0.59 MHz
3.9	15.247(d)	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 13.41 dB at 43.5 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Motorola Mobility Inc

No.1 Wang Jing East Road, Chao Yang District, 100102 Beijing, P. R. China

1.2 Manufacturer

Gongqingcheng Cellon Communication Technology Co., LTD

New industrial park, GongQingCheng, Jiujiang city, Jiangxi Province, China. Postal code: 332020

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Mobile phone
Brand Name	Motorola
Model Name	WX306
Type Name	M0C42
FCC ID	IHDT56MZ3
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 7.19 dBm (0.0052 W) Bluetooth EDR (2Mbps) : 6.33 dBm (0.0043 W) Bluetooth EDR (3Mbps) : 6.60 dBm (0.0046 W)
Antenna Type	PIFA Antenna with gain 2 dBi
HW Version	B1
SW Version	BUNTNG3_U_08.0E.2RDS
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Production Unit

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		
	TH01-KS	CO01-KS	03CH01-KS

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC Public Notice DA 00-705
- ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (Certification), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power					
		Data Rate / Modulation					
		GFSK		$\pi/4$ -DQPSK		8-DPSK	
		1Mbps		2Mbps		3Mbps	
Ch00	2402MHz	7.01	dBm	6.26	dBm	6.54	dBm
Ch39	2441MHz	6.92	dBm	6.11	dBm	6.40	dBm
Ch78	2480MHz	7.19	dBm	6.33	dBm	6.60	dBm

Remark:

1. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	N/A	N/A
AC Conducted Emission	Mode 1 :GSM 850 Idle + Bluetooth Link + Adapter + Earphone + Camera		
Remark:			
1. For radiated TCs, the data rate was set in 1Mbps due to the highest RF output power; only the data of these modes was reported.			
2. For conducted emission, the worst case is mode 1; only the test data of this mode was reported.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

For Bluetooth function, the RF utility, “* #3646633 #” was installed in EUT which was programmed in order to make the EUT into the engineering modes to contact with Bluetooth base station for transmitting and receiving signals continuously.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; $RBW \geq 1\%$ of the span; $VBW \geq RBW$; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.


3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 1~3	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 12.AUG.2011 17:28:50



Date: 12.AUG.2011 17:35:35

3.2 20dB Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.940
39	2441	0.944
78	2480	0.856


20 dB Bandwidth Plot on Channel 00



Date: 12.AUG.2011 16:46:33




20 dB Bandwidth Plot on Channel 39



Date: 12.AUG.2011 16:50:14

20 dB Bandwidth Plot on Channel 78




Date: 12.AUG.2011 16:53:24



Test Mode :	Mode 4, 5, 6	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.260
39	2441	1.266
78	2480	1.224


20 dB Bandwidth Plot on Channel 00



Date: 12.AUG.2011 17:05:33




20 dB Bandwidth Plot on Channel 39



Date: 12.AUG.2011 17:05:53


20 dB Bandwidth Plot on Channel 78




Date: 12.AUG.2011 17:06:11

Test Mode :	Mode 7, 8, 9	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.254
39	2441	1.242
78	2480	1.236

20 dB Bandwidth Plot on Channel 00


Date: 12.AUG.2011 17:11:47

20 dB Bandwidth Plot on Channel 39


Date: 12.AUG.2011 17:12:03

20 dB Bandwidth Plot on Channel 78


Date: 12.AUG.2011 17:12:20

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup




3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 1, 2, 3	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.62667	Pass
39	2441	1.008	0.62933	Pass
78	2480	1.002	0.57067	Pass

Channel Separation Plot on Channel 00 - 01




Date: 12.AUG.2011 16:47:18

Channel Separation Plot on Channel 39 - 40



Date: 12.AUG.2011 16:51:00

Channel Separation Plot on Channel 77 - 78



Date: 12.AUG.2011 16:56:45

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup




3.4.5 Test Result of Dwell Time

Test Mode :	Mode 2	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	3.20	2920.00	0.30	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)

DH5 Dwell Time (One Pulse) Plot on Channel 39


Date: 12.AUG.2011 17:52:05

DH5 Dwell Time (Count Pulses) Plot on Channel 39


Date: 12.AUG.2011 16:44:54

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (20.97dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power


Test Mode :	Mode 1, 2, 3	Temperature :	24~25℃
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits	Pass/Fail
		1 Mbps	(dBm)	
00	2402	7.01	20.97	Pass
39	2441	6.92	20.97	Pass
78	2480	7.19	20.97	Pass


Peak Output Power Plot on Channel 00



Date: 12.AUG.2011 16:00:28

Peak Output Power Plot on Channel 39



Date: 12.AUG.2011 16:02:46

Peak Output Power Plot on Channel 78



Date: 12.AUG.2011 16:10:11

Test Mode :	Mode 4, 5, 6	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%


Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	6.26	20.97	Pass
39	2441	6.11	20.97	Pass
78	2480	6.33	20.97	Pass

Peak Output Power Plot on Channel 00


Date: 12.AUG.2011 16:01:14

Peak Output Power Plot on Channel 39



Date: 12.AUG.2011 16:03:41

Peak Output Power Plot on Channel 78



Date: 12.AUG.2011 16:10:51

Test Mode :	Mode 7, 8, 9	Temperature :	24~25°C
Test Engineer :	Zhi Lu	Relative Humidity :	47~48%


Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	6.54	20.97	Pass
39	2441	6.40	20.97	Pass
78	2480	6.60	20.97	Pass

Peak Output Power Plot on Channel 00


Date: 12.AUG.2011 16:01:56

Peak Output Power Plot on Channel 39


Date: 12.AUG.2011 16:04:25

Peak Output Power Plot on Channel 78


Date: 12.AUG.2011 16:11:32

3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) $\geq$ RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	43~44%
		Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2338.88	50.35	-23.65	74	48.18	32.78	3.33	33.94	100	12	Peak
2338.88	37.39	-16.61	54	35.22	32.78	3.33	33.94	100	12	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2315.89	50.58	-23.42	74	48.49	32.73	3.22	33.86	100	112	Peak
2315.89	37.07	-16.93	54	34.98	32.73	3.22	33.86	100	112	Average


Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	78	Relative Humidity :	43~44%
		Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.536	50.63	-23.37	74	48.14	33.01	3.68	34.2	100	63	Peak
2483.536	35.7	-18.3	54	33.21	33.01	3.68	34.2	100	63	Average

Summary results of marker-delta method:


Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	91.09	55.39	35.7	54	-18.3	Pass
Hopping Mode	91.09	57.61	33.48	54	-20.52	Pass

Note : Average result = Maximum field strength – Delta result

Test Plots:



Site : 03CH01-KS
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL
 Project : (FR) 180510-01
 Mode : mode 3
 Plane : H

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	106.36	32.36	74.00	103.87	33.01	3.68	34.20	100	19	Peak
2 X	2480.00	91.09	37.09	54.00	88.60	33.01	3.68	34.20	100	19	Average



Site : 03CH01-KS
Condition: FCC PART 15C 3m HF ANI-100803 HORIZONTAL
Project : (FR) 180510-01
Mode : mode 3
Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	106.02	32.02	74.00	103.53	3.68	34.20	100	60	Peak
2	2483.54	50.63	-23.37	74.00	48.14	3.68	34.20	100	63	Peak



Site : 03CH01-KS
Condition: FCC PART 15C 3m HF ANI-100803 HORIZONTAL
Project : (FR) 180510-01
Mode : mode 3
Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	105.74	31.74	74.00	103.25	3.68	34.20	100	86	Peak
2	2483.90	48.13	-25.87	74.00	45.64	3.68	34.20	100	65	Peak


ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.656	46.2	-27.8	74	43.71	33.01	3.68	34.2	120	126	Peak
2483.656	31.36	-22.64	54	28.87	33.01	3.68	34.2	120	126	Average

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	84.86	53.75	31.11	54	-22.89	Pass
Hopping Mode	84.86	53.5	31.36	54	-22.64	Pass


Note : Average result = Maximum field strength – Delta result

Test Plots:




Site : 03CH01-KS
Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL
Project : (FR) 180510-01
Mode : mode 3
Plane : H

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	98.86	24.86	74.00	96.37	33.01	3.68	34.20	100	125	Peak
2 X	2480.00	84.86	30.86	54.00	82.37	33.01	3.68	34.20	100	125	Average



Site : 03CH01-KS
Condition: FCC PART 15C 3m HF ANI-100803 VERTICAL
Project : (FR) 180510-01
Mode : mode 3
Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	100.51	26.51	74.00	98.02	3.68	34.20	200	128	Peak
2	2483.87	46.76	-27.24	74.00	44.27	3.68	34.20	100	26	Peak




Site : 03CH01-KS
Condition: FCC PART 15C 3m HF ANI-100803 VERTICAL
Project : (FR) 180510-01
Mode : mode 3
Plane : H

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	99.70	25.70	74.00	97.21	3.68	34.20	120	26	Peak
2	2483.66	46.20	-27.80	74.00	43.71	3.68	34.20	120	26	Peak

3.6.6 Test Result of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	24~25℃
Test Channel :	00 and 78	Relative Humidity :	47~48%
		Test Engineer :	Zhi Lu

Low Band Edge Plot on Channel 00



Date: 12.AUG.2011 16:47:55

High Band Edge Plot on Channel 78



Date: 12.AUG.2011 17:03:22

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.7.4 Test Setup



3.7.5 Test Result


Test Mode :	Mode 1	Temperature :	24~25℃
Test Channel :	00	Relative Humidity :	47~48%
		Test Engineer :	Zhi Lu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz




Date: 12.AUG.2011 16:49:29

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 12.AUG.2011 16:49:50

Test Mode :	Mode 2	Temperature :	24~25℃
Test Channel :	39	Relative Humidity :	47~48%
		Test Engineer :	Zhi Lu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 12.AUG.2011 16:52:04

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz



Date: 12.AUG.2011 16:52:26



Test Mode :	Mode 3	Temperature :	24~25℃
Test Channel :	78	Relative Humidity :	47~48%
		Test Engineer :	Zhi Lu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz

Date: 12.AUG.2011 17:04:15

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz

Date: 12.AUG.2011 17:04:37

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.8.4 Test Setup



3.8.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	22~23℃
Test Engineer :	Chenmy Cheng	Relative Humidity :	43~44%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM 850 Idle + Bluetooth Link + Adapter + Earphone + Camera		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
Condition: FCC PART15C LISN-100807 LINE
Project : (FR) 180510-01
mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
				dBuV	dBuV	dB	dB	
1	0.17	27.27	-27.63	54.90	17.20	-0.07	10.14	Average
2	0.17	41.37	-23.53	64.90	31.30	-0.07	10.14	QP
3	0.20	23.78	-29.98	53.76	13.70	-0.07	10.15	Average
4	0.20	37.88	-25.88	63.76	27.80	-0.07	10.15	QP
5	0.23	35.88	-26.69	62.57	25.79	-0.07	10.16	QP
6	0.23	21.98	-30.59	52.57	11.89	-0.07	10.16	Average
7	0.59	23.64	-22.36	46.00	13.51	-0.09	10.22	Average
8	0.59	35.64	-20.36	56.00	25.51	-0.09	10.22	QP
9	2.22	21.33	-24.67	46.00	11.10	-0.11	10.34	Average
10	2.22	32.53	-23.47	56.00	22.30	-0.11	10.34	QP
11	3.01	30.55	-25.45	56.00	20.30	-0.12	10.37	QP
12	3.01	19.95	-26.05	46.00	9.70	-0.12	10.37	Average

Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	Chenmy Cheng	Relative Humidity :	43~44%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM 850 Idle + Bluetooth Link + Adapter + Earphone + Camera		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
 Condition: FCC PART15C LISN-100807 NEUTRAL
 Project : (FR) 180510-01
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.48	24.33	-21.94	46.27	14.20	-0.08	10.21	Average
2	0.48	34.73	-21.54	56.27	24.60	-0.08	10.21	QP
3	0.56	22.93	-23.07	46.00	12.79	-0.08	10.22	Average
4	0.56	33.63	-22.37	56.00	23.49	-0.08	10.22	QP
5	1.60	31.40	-24.60	56.00	21.19	-0.10	10.31	QP
6	1.60	19.40	-26.60	46.00	9.19	-0.10	10.31	Average
7	2.21	22.53	-23.47	46.00	12.30	-0.11	10.34	Average
8	2.21	33.13	-22.87	56.00	22.90	-0.11	10.34	QP
9	2.46	19.14	-26.86	46.00	8.90	-0.11	10.35	Average
10	2.46	31.64	-24.36	56.00	21.40	-0.11	10.35	QP
11	3.01	33.15	-22.85	56.00	22.90	-0.12	10.37	QP
12	3.01	21.75	-24.25	46.00	11.50	-0.12	10.37	Average

3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


- The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.
- Measured average value for the peak value is greater than 54 dBuV/m

3.9.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Chenmy Cheng	Temperature :	22~23°C	
		Relative Humidity :	43~44%	
Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.9.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	43~44%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.35	20.12	-19.88	40	32.66	17.29	0.25	30.08			Peak
59.16	16.45	-23.55	40	40.84	5.44	0.31	30.14			Peak
172.02	16.94	-26.56	43.5	37.21	9.08	0.55	29.9			Peak
761.3	22.88	-23.12	46	31.35	19.89	1.19	29.55			Peak
871.2	25.09	-20.91	46	32.9	20.49	1.29	29.59			Peak
890.8	31.68	-14.32	46	39.43	20.46	1.3	29.51	100	36	Peak
2338.88	50.35	-23.65	74	48.18	32.78	3.33	33.94	100	12	Peak
2338.88	37.39	-16.61	54	35.22	32.78	3.33	33.94	100	12	Average
2402	105.76			103.48	32.86	3.47	34.05	100	0	Peak
2402	89.94			87.66	32.86	3.47	34.05	100	0	Average
2484.8	49.51	-24.49	74	47.02	33.01	3.68	34.2	100	26	Peak
2484.8	37.45	-16.55	54	34.96	33.01	3.68	34.2	100	26	Average

Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	43~44%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
44.04	25.98	-14.02	40	45.79	10.03	0.27	30.11	100	28	Peak
60.51	24.91	-15.09	40	49.44	5.3	0.31	30.14			Peak
134.49	23.3	-20.2	43.5	41.51	11.3	0.48	29.99			Peak
838.3	23.22	-22.78	46	31.22	20.38	1.27	29.65			Peak
871.2	24.67	-21.33	46	32.48	20.49	1.29	29.59			Peak
890.8	27.46	-18.54	46	35.21	20.46	1.3	29.51			Peak
2315.89	50.58	-23.42	74	48.49	32.73	3.22	33.86	100	112	Peak
2315.89	37.07	-16.93	54	34.98	32.73	3.22	33.86	100	112	Average
2402	99.32			97.04	32.86	3.47	34.05	115	16	Peak
2402	86.45			84.17	32.86	3.47	34.05	115	16	Average
2483.85	49.83	-24.17	74	47.34	33.01	3.68	34.2	100	166	Peak
2483.85	37.26	-16.74	54	34.77	33.01	3.68	34.2	100	166	Average

Test Mode :	Mode 2	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	43~44%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	19.95	-20.05	40	32.49	17.29	0.25	30.08			Peak
59.16	16.47	-23.53	40	40.86	5.44	0.31	30.14			Peak
163.11	16.76	-26.74	43.5	36.67	9.49	0.53	29.93			Peak
757.1	23.36	-22.64	46	31.83	19.89	1.19	29.55			Peak
876.1	24.06	-21.94	46	31.85	20.48	1.29	29.56			Peak
894.3	31.24	-14.76	46	38.98	20.46	1.3	29.5	100	62	Peak
2320.45	49.98	-24.02	74	47.85	32.76	3.27	33.9	100	126	Peak
2320.45	37.26	-16.74	54	35.13	32.76	3.27	33.9	100	126	Average
2441	105.31			102.91	32.95	3.6	34.15	100	14	Peak
2441	89.51			87.11	32.95	3.6	34.15	100	14	Average
2484.23	49.62	-24.38	74	47.13	33.01	3.68	34.2	100	146	Peak
2484.23	37.34	-16.66	54	34.85	33.01	3.68	34.2	100	146	Average

Test Mode :	Mode 2	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	43~44%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
44.85	26.32	-13.68	40	46.58	9.6	0.27	30.13	100	156	Peak
59.7	25.23	-14.77	40	49.76	5.3	0.31	30.14			Peak
133.95	23.96	-19.54	43.5	42.08	11.39	0.48	29.99			Peak
761.3	22.51	-23.49	46	30.98	19.89	1.19	29.55			Peak
849.5	23.09	-22.91	46	30.96	20.51	1.28	29.66			Peak
871.2	25.09	-20.91	46	32.9	20.49	1.29	29.59			Peak
2320.26	50.1	-23.9	74	47.97	32.76	3.27	33.9	200	30	Peak
2320.26	37.3	-16.7	54	35.17	32.76	3.27	33.9	200	30	Average
2441	100.52			98.12	32.95	3.6	34.15	168	37	Peak
2441	87.66			85.26	32.95	3.6	34.15	168	37	Average
2485.94	49.76	-24.24	74	47.27	33.01	3.68	34.2	100	166	Peak
2485.94	37.25	-16.75	54	34.76	33.01	3.68	34.2	100	166	Average

Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	78	Relative Humidity :	43~44%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.89	19.55	-20.45	40	32.85	16.55	0.24	30.09	100	210	Peak
59.43	17.05	-22.95	40	41.44	5.44	0.31	30.14			Peak
239.25	17.54	-28.46	46	35.19	11.51	0.66	29.82			Peak
663.3	22.01	-23.99	46	31.59	18.99	1.1	29.67			Peak
837.6	23.16	-22.84	46	31.16	20.38	1.27	29.65			Peak
871.2	24.65	-21.35	46	32.46	20.49	1.29	29.59			Peak
2346	49.19	-24.81	74	47.02	32.78	3.33	33.94	100	169	Peak
2346	37.43	-16.57	54	35.26	32.78	3.33	33.94	100	169	Average
2480	106.36			103.87	33.01	3.68	34.2	100	19	Peak
2480	91.09			88.6	33.01	3.68	34.2	100	19	Average
2483.536	50.63	-23.37	74	48.14	33.01	3.68	34.2	100	63	Peak
2483.536	35.7	-18.3	54	33.21	33.01	3.68	34.2	100	63	Average

Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	78	Relative Humidity :	43~44%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
43.5	26.59	-13.41	40	46.4	10.03	0.27	30.11	100	262	Peak
59.97	25.5	-14.5	40	50.03	5.3	0.31	30.14			Peak
134.49	22.53	-20.97	43.5	40.74	11.3	0.48	29.99			Peak
790.7	22.84	-23.16	46	31.32	19.86	1.24	29.58			Peak
871.2	24.8	-21.2	46	32.61	20.49	1.29	29.59			Peak
892.9	24.45	-21.55	46	32.19	20.46	1.3	29.5			Peak
2356	49.37	-24.63	74	47.16	32.81	3.38	33.98	200	138	Peak
2356	37.33	-16.67	54	35.12	32.81	3.38	33.98	200	138	Average
2480	98.86			96.37	33.01	3.68	34.2	100	125	Peak
2480	84.86			82.37	33.01	3.68	34.2	100	125	Average
2483.656	46.2	-27.8	74	43.71	33.01	3.68	34.2	120	126	Peak
2483.656	31.36	-22.64	54	28.87	33.01	3.68	34.2	120	126	Average

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY45101555	N/A	Aug. 24, 2010	Aug. 23, 2011	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY44421198	N/A	Aug. 24, 2010	Aug. 23, 2011	Conducted (TH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 02, 2011	Jun. 01, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	N/A	Nov. 10, 2010	Nov. 09, 2011	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 16, 2010	Nov. 15, 2011	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2010	Dec. 06, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 09, 2010	Dec. 08, 2011	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Active horn antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 09, 2010	Nov. 08, 2011	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 06, 2011	Jan. 05, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 15, 2010	Oct. 14, 2011	Radiation (03CH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	Aug. 16, 2012	-
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 07, 2011	Jan. 06, 2012	-

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP180510-01 as below.