



PRODUCT SAFETY AND COMPLIANCE EMC LABORATORY

EMC TEST REPORT - Addendum

Test Report Number –24974-1

Report Date – 2012-04-27

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

Signature:

Name: Hongpeng Yin

Title: EMC Project Manager

Test: 2012-04-09 to 2012-04-27

As the responsible test lab manager, I hereby declare that the model tested as specified in this report conforms to the requirements indicated.

Signature:

Name: Yilin Zhao

Title: Test Lab Manager

Date: 2012-05-06

This report must not be reproduced, except in full, without written approval from this laboratory.

FCC Registration Number: 402854
IC Registration Number: 109AW-1

ADR Testing Service location ADR BJ
ISO/IEC-17025:2005 accredited by UKAS



UKAS Certificate Number: 2404

Table of Contents

<u>Test Report Details</u>	3
<u>Summary of Testing</u>	4
<u>General and Special Conditions</u>	4
<u>Equipment and Cable Configurations</u>	5
<u>Measurement Procedures and Data</u>	5
<u>RF POWER OUTPUT</u>	7
<u>RADIATED POWER (EIRP AND ERP)</u>	9
<u>OCCUPIED BANDWIDTH</u>	10
<u>SPURIOUS EMISSIONS AT ANTENNA TERMINALS</u>	16
<u>FIELD STRENGTH OF SPURIOUS EMISSIONS</u>	19
<u>FREQUENCY STABILITY</u>	22

Test Report Details

Tests Performed By: Motorola (Beijing) Mobility Technologies Co., Ltd.
Asia Global Compliance Labs
No.1 Wang Jing East Road
Chao Yang District
Beijing, 100102, P. R. China
Phone: +86 10 8473 2610
FCC Registration Number: 402854
IC Registration Number: 109AW-1

Tests Requested By: MOTOROLA MOBILITY, INC.
600 North US Hwy 45
Libertyville, IL 60048
United States

Product Type: Cell phone

Signaling Capability: WCDMA850/1700,HSDPA14.4Mbps/HSUPA5.76M
bps,GSM 850 /1900, Edge850/ 1900, Bluetooth,
802.11 b & g & n

IMEI: 352206050003117; 352206050003125; 352206050003091

FCC ID: IHDT56HN4

Project number: 24974-1

Testing Complete Date: 2012-04-27

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

☒ Part 2
☒ Part 22 Subpart H – Public Mobile Services
☒ Part 24 Subpart E – Personal Communications Services
☒ Part 27 Subpart L – Miscellaneous wireless communications services

Applicable Standards: ANSI C63.4-2003, ANSI/TIA-603-C-2004, RSS-Gen Issue 3, RSS132 Issue 2, RSS-133 Issue 5.

Summary of Testing

Test #	Test Name	Pass/Fail
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	Pass
3	EIRP (Effective Isotropic Radiated Power)	Pass
4	Occupied Bandwidth	Pass
5	Spurious Emissions at Antenna Terminal	Pass
6	Field Strength of Spurious Emissions	Pass
7	Frequency Stability	Pass

Test #	Test Name	Margin with respect to the Limit
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	See results
3	EIRP (Effective Isotropic Radiated Power)	See results
4	Occupied Bandwidth	See Plots
5	Spurious Emissions at Antenna Terminal	See results
6	Field Strength of Spurious Emissions	See results
7	Frequency Stability	See results

The margin with respect to the limit is the minimum margin for all modes and bands.

General and Special Conditions

The EUT was tested using a fully charged model SNN5899A_EB20 1750mAh battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment. The temperature and the relative humidity were maintained within the ANSI C63.4-2003 Standard requirements during the entire duration of testing.

Equipment and Cable Configurations

The EUT was tested in a stand-alone configuration that is representative of typical use.

Equipment	Model/type	Serial number	Operational range	Date of calibration
EMI analyzers	ESU 40	100036	20 Hz – 40 GHz	11.08.2011
Pre Amplifiers	PA-02-0001:	2007343	(10 kHz – 3 GHz)	07.04.2010
	PA-02-218	2007344	3 GHz – 18 GHz	07.04.2010
	PA-02-5	2007345	18 GHz – 40 GHz	07.04.2010
Radio com. Tester	CMU 200	112790	GSM 850/900/1800/1900 UMTS, CDMA, Bluetooth	N/A
Band Reject Filter	WRCD	N/A	GSM 850/900/1800/1900 UMTS, CDMA	N/A
	4N45-24241/3/6	N/A	WLAN	N/A
EMI analyzers	R&S ESCI	100650	9 kHz – 3 GHz	03.13.2012
Spectrum analyzer	R&S FSU	200353	20 Hz – 26.5 GHz	03.03.2012
LISN	ENV216	100055	9 kHz – 30 MHz	12.19.2010
Environment Chamber	Votsch VT4004	3546270300000 20	-50 ⁰ C -150 ⁰ C	10.27.2011
DC Power Supply	Agilent E3632A	My40021519	15V/7A	07.20.2011
Power meter	Agilent E4416A	MY451000906	NA	03.03.2011
Power sensor	Agilent E9323A	MY44420783	50MHz-6GHz	03.03.2011

The antennas used in the various tests are listed in the below table.

Antenna	Type	Serial number	Operational range	Date of calibration
Hybrid-log periodic	TDK HLP 3003C	130408	30 MHz – 3 GHz	11.14.2011
Double ridged Horn	TDK HRN0118	130303	1 GHz – 18 GHz	11.22.2011
Double ridged Horn	ETS HRN3116	00071938	18 GHz – 40 GHz	07.13.2011

All test equipments was within their calibration date during the time of testing. When equipment went out of calibration during testing it was replaced using a similar piece of calibrated equipment. All these equipments are listed in the equipment list.

Note that the Agilent power meter, power sensor and the preamplifier are on two-year calibration cycle. The LISN is on a two-year calibration. The antennas are on the three-year calibration cycle. All other equipments are on a one-year calibration cycle.

Measurement Procedures and Data

RF POWER OUTPUT

Measurement Procedure

The RF output port of the equipment under test is directly coupled to the input of an Agilent power meter through a 30dB passive attenuator, adaptor (if needed), and specialized RF connector.

Measurement Results

GSM 850

Frequency (MHz)	Power (dBm)
824.2	33.62
836.6	33.28
848.8	33.32

GSM 1900

Frequency (MHz)	Power (dBm)
1850.2	30.56
1880	30.51
1909.8	30.62

EDGE 850

Frequency (MHz)	Power (dBm)
824.2	27.78
836.6	28.13
848.8	27.77

EDGE 1900

Frequency (MHz)	Power (dBm)
1850.2	26.89
1880	26.87
1909.8	27.19

Band	Channel	(dBm) for WCDMA		Conducted Power (dBm) for WCDMA – HSDPA (Rel 5) Modes				Conducted Power (dBm) for Modes				
		RMC	AMR	Subtest 1	Subtest 2	Subtest 3	Subtest 4	Subtest 1	Subtest 2	Subtest 3	Subtest 4	Subtest 5
WCDMA 1700	1312	24.03	23.97	23.87	23.86	23.93	23.86	24.09	24.08	23.95	23.95	24.04
	1413	23.98	23.95	23.81	23.81	23.85	23.78	23.96	24	23.91	23.88	23.97
	1513	24.13	23.98	23.85	23.82	23.89	23.83	24.1	24.15	24.07	24.01	24.11

Band	Channel	Conducted power (dBm) for WCDMA modes			Conducted Power (dBm) for WCDMA – HSDPA (Rel 5) Modes				Conducted Power (dBm) for WCDMA – HSPA (HSUPA/HSDPA-Rel 6) Modes				
		RMC	RMC + 0.25dB	AMR	Subtest 1	Subtest 2	Subtest 3	Subtest 4	Subtest 1	Subtest 2	Subtest 3	Subtest 4	Subtest 5
WCDMA 850	4132	24.1	24.35	23.95	24.04	24.06	24.07	24	24.03	24.04	24.13	24.16	24.06
	4180	24.13	24.38	23.94	24.02	24	23.99	23.94	24.04	24.02	24.07	24.11	24.04
	4233	24.08	24.33	23.91	23.98	23.96	23.93	23.91	24.03	24.01	24.06	24.07	24.1

All WCDMA testing was done in RMC mode.

RADIATED POWER (EIRP AND ERP)

Measurement Procedure

The phone was tested in a 16' anechoic chamber with a 2-axis position system that permits taking complete spherical scans of the EUT's radiation patterns. For all tests, the phone was supported in a free space type environment, vertically oriented in the chamber.


All measurements were made with the phone placed in a call using a mobile station test set. The phone was weakly coupled to the test set and configured to transmit in full data rate mode. Radiated power was measured at each 15 degree step. The radiated power was measured using a peak detector for all bands in the Spectrum Analyzers. From these measurements, the software calculates the angle at which maximum radiated power occurs for each case, and the radiated power at this angle was extracted from the data. To get ERP (effective radiated power referenced to a half-wave dipole), subtract 2.1 dB from these

A peak detector was used for measurements in the GSM850 EDGE850, WCDMA 850/1700
A average detector was used for measurements in GSM 1900, EDGE 1900.

Measurement Results


Band	EIRP dBm	ERP dBm
GSM850	32.8	30.7
GSM1900	32.61	30.51
Edge 850	31.2	29.1
Edge 1900	29.7	27.6
WCDMA850	22.5	20.4
WCDMA1700	25.6	23.5

GSM1900 PAR_Plot



Date: 27.APR.2012 14:56:11

Edge1900 PAR_Plot



Date: 27.APR.2012 15:21:02

OCCUPIED BANDWIDTH

CFR Part 2.1049, 22.917, 24.238

Measurement Procedure


The RF output port of the equipment under test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 20dB passive attenuator for GSM850, PCS1900, WCDMA850, WCDMA1700 spectrum analyzer is corrected for the attenuator and any other applicable losses. The analyzer is set for Peak Detector and each trace is set for Max Hold. A fully charged battery was used for the supply voltage.

The middle channel within the designated frequency block was measured. For digital modulation, the lower and upper band edge plots are displayed.

Measurement Results


Measurement Results – GSM 850

GSM 850 – Reference Level Plot – Channel 190 (836.6 MHz)




Date: 17.APR.2012 10:24:09

GSM 850 – Channel 190 (836.6 MHz)– Occupied Bandwidth




Date: 17.APR.2012 10:25:11

GSM 850 – Lower Band Edge – Channel 128 (824.2 MHz)



Date: 17.APR.2012 10:27:12


GSM 850 – Upper Band Edge – Channel 251 (848.8 MHz)



Date: 17.APR.2012 10:28:14

Measurement Results – PCS 1900

GSM 1900(PCS) – Reference Level Plot – Channel 661 (1880.00 MHz)



Date: 17.APR.2012 10:38:46

Ref 30.2 dBm Att 20 dB SWT 35 ms

*RBW 3 kHz *VBW 10 kHz

Marker 1 [T1] 19.16 dBm

1.880018600 GHz

30.2 Offset 28 1 dB

OBW 241.200000000 kHz

Temp 1 [T1 OBW] 4.07 dBm

1.879879400 GHz

Temp 2 [T1 OBW] 2.06 dBm


1.880020600 GHz

1 PK MAXH

Center 1.88 GHz 30 kHz/ Span 300 kHz


Date: 17.APR.2012 10:39:47

GSM 1900(PCS) – Lower Band Edge – Channel 512 (1850.2 MHz)



Date: 17.APR.2012 10:41:03


GSM 1900(PCS) – Upper Band Edge – Channel 810 (1909.8 MHz)



Date: 17.APR.2012 10:42:09


Measurement Results – EDGE 850

EDGE 850 – Reference Level Plot – Channel 190 (836.6 MHz)




Date: 17.APR.2012 10:11:47

EDGE 850 – Channel 190 (836.6 MHz)– Occupied Bandwidth




Date: 17.APR.2012 10:18:10

EDGE 850 – Lower Band Edge – Channel 128 (824.2 MHz)



Date: 17.APR.2012 10:19:07


EDGE850 – Upper Band Edge – Channel 251 (848.8 MHz)



Date: 17.APR.2012 10:19:56


Measurement Results – EDGE 1900

EDGE 1900(PCS) – Reference Level Plot – Channel 661 (1880.00 MHz)




Date: 17.APR.2012 10:38:46

EDGE 1900(PCS) – Channel 661 (1880.00 MHz) – Occupied Bandwidth




Date: 17.APR.2012 10:39:47

EDGE 1900(PCS) – Lower Band Edge – Channel 512 (1850.2 MHz)



Date: 17.APR.2012 10:41:03


EDGE 1900(PCS) – Upper Band Edge – Channel 810 (1909.8 MHz)



Date: 17.APR.2012 10:42:09


Measurement Results – WCDMA 850

WCDMA 850 – Reference Level Plot – Channel 4180 (836.0 MHz)




Date: 17.APR.2012 12:57:24

WCDMA 850 – Channel 4180 (836.0 MHz)– Occupied Bandwidth




Date: 17.APR.2012 12:58:37

WCDMA 850 – Lower Band Edge – Channel 4132 (826.4 MHz)



Date: 17.APR.2012 13:00:22


WCDMA 850 – Upper Band Edge – Channel 4233 (848.6 MHz)



Date: 17.APR.2012 13:01:10


Measurement Results – WCDMA 1700

WCDMA 1700 – Reference Level Plot – Channel 1413 (1732.5 MHz)




Date: 17.APR.2012 13:06:10

WCDMA 1700 – Channel 1413 (1732.5 MHz) – Occupied Bandwidth




Date: 17.APR.2012 13:11:54

WCDMA 1700 – Lower Band Edge – Channel 1312 (1712.4 MHz)



Date: 17.APR.2012 13:09:04

WCDMA 1700 – Extended Upper Band Edge – Channel 1513 (1752.6 MHz)



Date: 17.APR.2012 13:10:44

SPURIOUS EMISSIONS AT ANTENNA TERMINALS**Measurement Procedure**

The RF output port of the Equipment Under Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 20dB passive attenuator. For all testing the EUT was powered through the computer's USB.

The spectrum was investigated from the lowest frequency signal generated, without going below 9 kHz, up to at least the tenth harmonic of the fundamental or 40 GHz, whichever is lower.


The spectrum analyzer settings were as follows:

Units	dBm
Divisions	10 dB
Detector	Peak Detector
Resolution Bandwidth	1 MHz
Video Bandwidth (AVG)	Auto
Sweep Time	Auto

Measurement Results

Attached

Measurement Results – GSM 850




The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – GSM 1900**Conducted Spurious and Harmonic Emissions**

Submission # 24974-1

PCS1900

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-35.31
3rd harmonic	-13	-33.33
4th harmonic	-13	-31.19
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – EDGE850

Conducted Spurious and Harmonic Emissions
Submission # 24974-1 **EDGE850**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-24.31
3rd harmonic	-13	-30.96
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*

**Notes:**

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental


The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – EDGE 1900**Conducted Spurious and Harmonic Emissions**

Submission # 24974-1

EDGEPCS

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-35.43
3rd harmonic	-13	-35.37
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – WCDMA850

Conducted Spurious and Harmonic Emissions
Submission # 24974-1 **WCDMA850**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-31.41
3rd harmonic	-13	-36.27
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – WCDMA1700

Conducted Spurious and Harmonic Emissions
Submission # 24974-1 **WCDMA1700**

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-33.91
3rd harmonic	-13	-39.12
4th harmonic	-13	*
5th harmonic	-13	*
6th harmonic	-13	*
7th harmonic	-13	*
8th harmonic	-13	*
9th harmonic	-13	*
10th harmonic	-13	*

**Notes:**

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental

The margin with respect to the limit is the minimum margin for all modes and bands.

FIELD STRENGTH OF SPURIOUS EMISSIONS**Measurement Procedure**

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum reading on the spectrum analyzer. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The equipment under test is then replaced with a substitution antenna fed by a signal generator. With the signal generator tuned to a particular spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters to obtain a maximum reading at the spectrum analyzer. The output of the signal generator is then adjusted until a reading identical to that obtained with the actual transmitter is achieved.

The power in dBm of each spurious emission is calculated by correcting the signal generator level for cable loss and gain of the substitution antenna referenced to a dipole. A fully charged battery was used for the supply voltage.


The settings of the receiver were as follows:

Units	dBm
Divisions	5 dB
Detector	Peak Detector
Resolution Bandwidth	1 MHz
Video Bandwidth (AVG)	Auto
Sweep Time	Auto

Measurement Results
Attached

Measurement Results – GSM 850**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	-26.4	-21.1
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – GSM 1900**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	-45.3	-47.9
3rd harmonic	-13	-35.7	-31.2
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – EDGE 850**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – EDGE 1900**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – WCDMA850**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*

**Notes:**


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

Measurement Results – WCDMA1700**Radiated Spurious and Harmonic Emissions**

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	*	*
3rd harmonic	-13	*	*
4th harmonic	-13	*	*
5th harmonic	-13	*	*
6th harmonic	-13	*	*
7th harmonic	-13	*	*
8th harmonic	-13	*	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*
Other Spurs	-13	*	*

**Notes:**

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients or the emissions are lower than -33 dBm.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Emissions below -33dBm are not shown.

The margin with respect to the limit is the minimum margin for all modes and bands.

FREQUENCY STABILITY**Measurement Procedure**


The equipment under test is placed in an environmental chamber. The antenna port of the Equipment Under Test is directly coupled to the input of the measurement equipment through a specialized RF connector. A power supply is attached as the primary voltage supply.

Frequency measurements are made at the extremes of the temperature range -30° C to +60° C and at intervals of 10° C with the primary supply voltage set to the nominal battery operating voltage. A period of time sufficient to stabilize all components of the equipment is allowed at each frequency measurement. The maximum variation of frequency is measured.

At room temperature, the primary supply voltage is reduced to the battery operating endpoint of the equipment under test. The maximum variation of frequency is measured. A battery eliminator was used for the input supply voltage.

Measurement Results

Attached


Measurement Results – GSM 850


Measurement Results – GSM 1900**Frequency Stability**


Mode: GSM 1900
Channel: 661

Operating Frequency: 1880.0 MHz
Deviation Limit (PPM): 0.1ppm

Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	56.00	0.030	100%	3.90
-20 C	66.00	0.035	100%	3.90
-10 C	50.00	0.027	100%	3.90
0 C	80.00	0.043	100%	3.90
10 C	49.00	0.026	100%	3.90
20 C	42.00	0.022	100%	3.90
30 C	-34.00	-0.018	100%	3.90
40 C	-34.00	-0.018	100%	3.90
50 C	-18.00	-0.010	100%	3.90
60 C	119.00	0.063	100%	3.90
		0		
20 C	34.00	0.018	Battery Endpoint	3.50



Measurement Results – EDGE 850

Measurement Results – EDGE 1900

Measurement Results – WCDMA850**Frequency Stability**


Mode: WCDMA 850


Operating Frequency: 836 MHz

Channel: 4180

Deviation Limit (PPM): 0.1 ppm

Temperature	Frequency Error	Frequency Error	Voltage	Voltage
C	HZ	(PPM)	(%)	(VDC)
-30 C	-24.00	-0.029	100%	3.90
-20 C	-18.00	-0.022	100%	3.90
-10 C	-24.00	-0.029	100%	3.90
0 C	-19.00	-0.023	100%	3.90
10 C	-16.00	-0.019	100%	3.90
20 C	-24.00	-0.029	100%	3.90
30 C	-21.00	-0.025	100%	3.90
40 C	-22.00	-0.026	100%	3.90
50 C	-14.00	-0.017	100%	3.90
60 C	21.00	0.025	100%	3.90
20 C	-16.00	-0.019	Battery Endpoint	3.50



Measurement Results – WCDMA1700

End of Test Report