



# FCC RF Test Report

**APPLICANT** : Motorola Mobility, Inc.  
**EQUIPMENT** : Quad GSM/GPRS/EDGE(downlink only) and Dual band WCDMA UMTS850/1900 mobile phone with BT/Wi-Fi  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT550  
**MARKETING NAME** : MOTOSMART™ MIX  
**TYPE NAME** : M0D25  
**GPPD NUMBER** : 3365  
**FCC ID** : IHDT56NM2  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)  
**Tx/Rx FREQUENCY RANGE** : GSM850 : 824.2 ~ 848.8 MHz /  
869.2 ~ 893.8 MHz  
GSM1900 : 1850.2 ~ 1909.8 MHz /  
1930.2 ~ 1989.8 MHz  
WCDMA Band V : 826.4 ~ 846.6 MHz /  
871.4 ~ 891.6 MHz  
WCDMA Band II : 1852.4 ~ 1907.6 MHz /  
1932.4 ~ 1987.6 MHz  
**MAX. ERP/EIRP POWER** : GSM850 (GSM) : 0.9226 W  
GSM1900 (GPRS 8) : 1.9364 W  
WCDMA Band V (RMC 12.2Kbps) : 0.1352 W  
WCDMA Band II (RMC 12.2Kbps) : 0.4227 W

The product was received on Mar. 15, 2012 and completely tested on May 08, 2012. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : IHDT56NM2

Page Number : 1 of 66

Report Issued Date : May 09, 2012

Report Version : Rev. 02



## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Emission Designator and Maximum ERP/EIRP Power .....	6
1.5 Testing Site.....	6
1.6 Applied Standards .....	6
1.7 Ancillary Equipment List.....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System .....	9
<b>3 TEST RESULT .....</b>	<b>10</b>
3.1 Conducted Output Power Measurement.....	10
3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	12
3.3 Occupied Bandwidth Measurement .....	16
3.4 Band Edge Measurement.....	29
3.5 Conducted Emission Measurement .....	38
3.6 Field Strength of Spurious Radiation Measurement .....	49
3.7 Frequency Stability Measurement.....	59
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>65</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>66</b>





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 39.78 dB at 11280.000 MHz
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



# 1 General Description

## 1.1 Applicant

Motorola Mobility, Inc.

No. 1, Wang Jing East Road, Chao Yang District, 100102 Beijing, P. R. China

## 1.2 Manufacturer

Gongqingcheng Cellon Communication Technology Co., LTD.

New industrial park, GongQingCheng, Jiujiang city, Jiangxi Province, China. Postal code: 332020

## 1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Quad GSM/GPRS/EDGE(downlink only) and Dual band WCDMA UMTS850/1900 mobile phone with BT/Wi-Fi
Brand Name	Motorola
Model Name	XT550
Marketing Name	MOTOSMART™ MIX
Type Name	M0D25
FCC ID	IHDT56NM2
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 33.28 dBm GSM1900 : 30.28 dBm WCDMA Band V : 24.14 dBm WCDMA Band II : 24.13 dBm
Antenna Type	Monopole Antenna
HW Version	B2
SW Version	ARGONS_4_02.07.02RDD
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSKE (Downlink Only) WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink)
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Emission Designator and Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Emission Designator	Maximum ERP/EIRP
Part 22	GSM850 GSM	GMSK	252KGXW	0.9226 W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	4M18F9W	0.1352 W
Part 24	GSM1900 GPRS 8	GMSK	246KGXW	1.9364 W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	4M20F9W	0.4227 W

### 1.5 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.		
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC/IC Registration No.</b>
	TH01-KS	03CH01-KS	149928/4086E-1

### 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v01
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GPRS 8 Link	■ GPRS 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

**Note:**


1. The maximum power levels are GSM or GPRS multi-slot class 8 mode for GSM link, RMC 12.2Kbps mode for WCDMA band V and WCDMA band II, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN, WLAN, and Bluetooth, the co-location test modes are not required.

The conducted power tables are as follows:

Band	GSM850			GSM1900		
	Channel	128	189	251	512	661
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	33.26	33.27	33.28	30.24	30.23	30.23
GPRS 8	33.25	33.25	33.26	30.25	30.28	30.21
GPRS 10	30.16	30.12	30.12	28.47	28.50	28.46
GPRS 12	27.17	27.12	27.11	24.95	25.01	24.97

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
	Channel	4132	4182	4233	9262	9400
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	24.14	24.11	24.12	23.95	24.11	24.13
HSDPA Subtest-1	23.94	24.01	23.99	23.66	23.75	23.73
HSDPA Subtest-2	23.83	23.95	23.83	23.56	23.62	23.62
HSDPA Subtest-3	23.40	23.41	23.40	23.12	23.21	23.20
HSDPA Subtest-4	23.35	23.40	23.37	23.08	23.17	23.20

## 2.2 Connection Diagram of Test System



### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

##### 3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	GSM850 (GSM)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	33.26	33.27	33.28	24.14	24.11	24.12
Conducted Power (Watts)	2.12	2.12	2.13	0.26	0.26	0.26

Cellular Band						
Modes	GSM1900 (GPRS 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	30.25	30.28	30.21	23.95	24.11	24.13
Conducted Power (Watts)	1.06	1.07	1.05	0.25	0.26	0.26



## 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

### 3.2.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

$P_s$  (dBm) : Input power to substitution antenna.

$G_s$  (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

$AF$  (dB/m) : Receive antenna factor

$R_t$  : The highest received signal in spectrum analyzer for EUT.

$R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.2.4 Test Setup





3.2.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.34	-48.12	0.00	-1.08	28.70	0.7413
836.40	-18.00	-48.28	0.00	-0.93	29.35	0.8610
848.80	-17.94	-48.35	0.00	-0.76	29.65	0.9226
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-31.37	-47.97	0.00	-1.08	15.52	0.0356
836.40	-30.42	-48.01	0.00	-0.93	16.66	0.0463
848.80	-29.83	-48.05	0.00	-0.76	17.46	0.0557

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-26.79	-48.12	0.00	-1.08	20.25	0.1059
836.40	-26.21	-48.28	0.00	-0.93	21.14	0.1300
846.60	-26.28	-48.35	0.00	-0.76	21.31	0.1352
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-39.30	-47.97	0.00	-1.08	7.59	0.0057
836.40	-38.23	-48.01	0.00	-0.93	8.85	0.0077
846.60	-38.07	-48.05	0.00	-0.76	9.22	0.0084



3.2.6 Test Result of EIRP

GSM1900 (GPRS 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-21.77	-51.88	0.00	1.96	32.07	1.6106
1880.00	-22.12	-52.99	0.00	2.00	32.87	1.9364
1909.80	-23.80	-54.28	0.00	1.98	32.46	1.7620
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-22.30	-52.13	0.00	1.96	31.79	1.5101
1880.00	-23.01	-53.17	0.00	2.00	32.16	1.6444
1909.80	-24.18	-54.13	0.00	1.98	31.93	1.5596

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-28.00	-51.88	0.00	1.96	25.84	0.3837
1880.00	-28.73	-52.99	0.00	2.00	26.26	0.4227
1907.60	-30.02	-54.28	0.00	1.98	26.24	0.4207
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-28.43	-52.13	0.00	1.96	25.66	0.3681
1880.00	-29.68	-53.17	0.00	2.00	25.49	0.3540
1907.60	-30.51	-54.13	0.00	1.98	25.60	0.3631

### 3.3 Occupied Bandwidth Measurement

#### 3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

#### 3.3.4 Test Setup






### 3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 128



Date: 24.MAR.2012 10:52:27


26dB Bandwidth Plot on Channel 128



Date: 24.MAR.2012 10:41:39




99% Occupied Bandwidth Plot on Channel 189



Date: 24.MAR.2012 10:52:53


26dB Bandwidth Plot on Channel 189



Date: 24.MAR.2012 10:42:06




99% Occupied Bandwidth Plot on Channel 251



Date: 24.MAR.2012 10:53:19

26dB Bandwidth Plot on Channel 251




Date: 24.MAR.2012 10:42:32




<b>Band :</b>	GSM 1900	<b>Power Stage :</b>	High
<b>Test Mode :</b>	GPRS 8 Link		

99% Occupied Bandwidth Plot on Channel 512



Date: 24.MAR.2012 11:04:35


26dB Bandwidth Plot on Channel 512



Date: 24.MAR.2012 11:03:16




99% Occupied Bandwidth Plot on Channel 661



Date: 24.MAR.2012 11:05:03


26dB Bandwidth Plot on Channel 661



Date: 24.MAR.2012 11:03:42




99% Occupied Bandwidth Plot on Channel 810



Date: 24.MAR.2012 11:05:28

26dB Bandwidth Plot on Channel 810




Date: 24.MAR.2012 11:04:08




<b>Band :</b>	WCDMA Band V	<b>Power Stage :</b>	High
<b>Test Mode :</b>	RMC 12.2Kbps Link		

**99% Occupied Bandwidth Plot on Channel 4132**



Date: 24.MAR.2012 11:32:29


**26dB Bandwidth Plot on Channel 4132**



Date: 24.MAR.2012 11:31:11




### 99% Occupied Bandwidth Plot on Channel 4182



Date: 24.MAR.2012 11:32:54


### 26dB Bandwidth Plot on Channel 4182



Date: 24.MAR.2012 11:31:37




### 99% Occupied Bandwidth Plot on Channel 4233



Date: 24.MAR.2012 11:33:20

### 26dB Bandwidth Plot on Channel 4233




Date: 24.MAR.2012 11:32:03




<b>Band :</b>	WCDMA Band II	<b>Power Stage :</b>	High
<b>Test Mode :</b>	RMC 12.2Kbps Link		

**99% Occupied Bandwidth Plot on Channel 9262**



Date: 24.MAR.2012 12:12:03


**26dB Bandwidth Plot on Channel 9262**



Date: 24.MAR.2012 12:10:44




### 99% Occupied Bandwidth Plot on Channel 9400



Date: 24.MAR.2012 12:12:29


### 26dB Bandwidth Plot on Channel 9400



Date: 24.MAR.2012 12:11:10




### 99% Occupied Bandwidth Plot on Channel 9538



Date: 24.MAR.2012 12:12:55

### 26dB Bandwidth Plot on Channel 9538



Date: 24.MAR.2012 12:11:37

## 3.4 Band Edge Measurement

### 3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly  $BW/100$ .


### 3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link	Maximum 26dB Bandwidth :	0.316MHz
Correction Factor :	0.23dB	Measurement Value :	-17.24dBm
Band Edge :	-17.01dBm		

Lower Band Edge Plot on Channel 128




Date: 24.MAR.2012 10:45:15

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link	Maximum 26dB Bandwidth :	0.316MHz
Correction Factor :	0.23dB	Measurement Value :	-17.77dBm
Band Edge :	-17.54dBm		

Higher Band Edge Plot on Channel 251




Date: 24.MAR.2012 10:45:41

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Power Stage :	High
Test Mode :	GPRS 8 Link	Maximum 26dB Bandwidth :	0.312MHz
Correction Factor :	0.17dB	Measurement Value :	-20.11dBm
Band Edge :	-19.94dBm		

Lower Band Edge Plot on Channel 512




Date: 24.MAR.2012 11:06:53

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Power Stage :	High
Test Mode :	GPRS 8 Link	Maximum 26dB Bandwidth :	0.312MHz
Correction Factor :	0.17dB	Measurement Value :	-19.77dBm
Band Edge :	-19.60dBm		

Higher Band Edge Plot on Channel 810




Date: 24.MAR.2012 11:07:19

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link	Maximum 26dB Bandwidth :	4.68MHz
Correction Factor :	-3.30dB	Measurement Value :	-26.54dBm
Band Edge :	-29.84dBm		

Lower Band Edge Plot on Channel 4132




Date: 24.MAR.2012 11:34:47

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link	Maximum 26dB Bandwidth :	4.68MHz
Correction Factor :	-3.30dB	Measurement Value :	-26.21dBm
Band Edge :	-29.51dBm		

Higher Band Edge Plot on Channel 4233




Date: 24.MAR.2012 11:35:13

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link	Maximum 26dB Bandwidth :	4.68MHz
Correction Factor :	-3.30dB	Measurement Value :	-27.99dBm
Band Edge :	-31.29dBm		

Lower Band Edge Plot on Channel 9262




Date: 24.MAR.2012 12:14:24

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link	Maximum 26dB Bandwidth :	4.68MHz
Correction Factor :	-3.30dB	Measurement Value :	-26.32dBm
Band Edge :	-29.62dBm		

Higher Band Edge Plot on Channel 9538



Date: 24.MAR.2012 12:14:50

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

## 3.5 Conducted Emission Measurement

### 3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.5.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

### 3.5.4 Test Setup






### 3.5.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.MAR.2012 10:57:18


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.MAR.2012 10:58:49




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.MAR.2012 10:59:36

### Conducted Emission Plot between 7GHz ~ 9GHz




Date: 24.MAR.2012 11:00:27




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.MAR.2012 11:17:03


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.MAR.2012 11:18:45




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.MAR.2012 11:19:43


### Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 24.MAR.2012 11:20:21



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 24.MAR.2012 11:20:57




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.MAR.2012 11:46:22


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.MAR.2012 11:53:14




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.MAR.2012 11:54:33

### Conducted Emission Plot between 7GHz ~ 9GHz




Date: 24.MAR.2012 11:55:40




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.MAR.2012 12:52:52


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.MAR.2012 12:54:17




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.MAR.2012 12:55:53


### Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 24.MAR.2012 12:56:27



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 24.MAR.2012 12:56:59

## 3.6 Field Strength of Spurious Radiation Measurement

### 3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.6.3 Test Procedures


4. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
5. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
6. The table was rotated 360 degrees to determine the position of the highest spurious emission.
7. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
8. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
9. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
10. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
11. Taking the record of output power at antenna port.
12. Repeat step 7 to step 8 for another polarization.
13.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
14.  $ERP \text{ (dBm)} = EIRP - 2.15$

### 3.6.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz




### 3.6.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.6.6 Test Result of Field Strength of Spurious Radiated

<b>Band :</b>	GSM850	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	GSM Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL  
 Project : (FG) 211239-02  
 plan : E2

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-55.30	-13	-42.30	-52.93	-55.95	0.57	3.37	H	Pass
2510	-58.20	-13	-45.20	-60.45	-60.43	0.78	5.16	H	Pass
3345	-61.31	-13	-48.31	-63.25	-64.95	0.87	6.66	H	Pass
4182	-61.09	-13	-48.09	-63.83	-65.68	0.97	7.71	H	Pass
5018	-56.66	-13	-43.66	-62.86	-62.33	1.09	8.91	H	Pass
5854	-57.25	-13	-44.25	-65.96	-63.69	1.22	9.81	H	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	GSM Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL  
 Project : (FG) 211239-02  
 plan : E2

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1674	-61.63	-13	-48.63	-57.28	-62.28	0.57	3.37	V	Pass
2510	-56.47	-13	-43.47	-59.58	-58.70	0.78	5.16	V	Pass
3345	-61.73	-13	-48.73	-63.71	-65.37	0.87	6.66	V	Pass
4182	-57.83	-13	-44.83	-61.67	-62.42	0.97	7.71	V	Pass
5016	-56.00	-13	-43.00	-60.94	-61.67	1.09	8.91	V	Pass
5854	-56.72	-13	-43.72	-64.71	-63.16	1.22	9.81	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	GPRS 8 Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL  
 Project : (FG) 211239-02  
 plan : E2

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-61.94	-13	-48.94	-62.91	-68.32	0.78	7.16	H	Pass
5640	-60.16	-13	-47.16	-64.34	-68.70	1.04	9.58	H	Pass
7520	-59.78	-13	-46.78	-64.91	-69.89	1.35	11.46	H	Pass
9400	-60.38	-13	-47.38	-63.64	-71.44	1.75	12.81	H	Pass
11280	-53.16	-13	-40.16	-64.65	-64.25	2.00	13.09	H	Pass
13160	-53.03	-13	-40.03	-64.33	-64.74	2.04	13.75	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	GPRS 8 Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL  
 Project : (FG) 211239-02  
 plan : E2

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-62.01	-13	-49.01	-63.38	-68.39	0.78	7.16	V	Pass
5640	-61.84	-13	-48.84	-65.06	-70.38	1.04	9.58	V	Pass
7520	-60.35	-13	-47.35	-64.84	-70.46	1.35	11.46	V	Pass
9400	-63.51	-13	-50.51	-64.73	-74.57	1.75	12.81	V	Pass
11280	-53.52	-13	-40.52	-64.76	-64.61	2.00	13.09	V	Pass
13160	-53.90	-13	-40.90	-65.09	-65.61	2.04	13.75	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL  
 Project : (FG) 211239-02  
 Plan : E2

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-67.60	-13	-54.60	-63.38	-68.25	0.57	3.37	H	Pass
2509	-62.82	-13	-49.82	-65.07	-65.05	0.78	5.16	H	Pass
3345	-62.26	-13	-49.26	-64.20	-65.90	0.87	6.66	H	Pass
4182	-62.79	-13	-49.79	-65.53	-67.38	0.97	7.71	H	Pass
5018	-59.23	-13	-46.23	-65.43	-64.90	1.09	8.91	H	Pass
5854	-56.53	-13	-43.53	-65.24	-62.97	1.22	9.81	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL  
 Project : (FG) 211239-02  
 Plan : E2

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-67.67	-13	-54.67	-63.32	-68.32	0.57	3.37	V	Pass
2509	-60.69	-13	-47.69	-63.80	-62.92	0.78	5.16	V	Pass
3345	-61.56	-13	-48.56	-63.54	-65.20	0.87	6.66	V	Pass
4182	-60.75	-13	-47.75	-64.59	-65.34	0.97	7.71	V	Pass
5018	-59.77	-13	-46.77	-64.71	-65.44	1.09	8.91	V	Pass
5854	-56.35	-13	-43.35	-64.34	-62.79	1.22	9.81	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL  
 Project : (FG) 211239-02  
 Plan : E2

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3762	-55.69	-13	-42.69	-56.66	-62.07	0.78	7.16	H	Pass
5640	-60.82	-13	-47.82	-65.00	-69.36	1.04	9.58	H	Pass
7520	-59.60	-13	-46.60	-64.73	-69.71	1.35	11.46	H	Pass
9400	-60.71	-13	-47.71	-63.97	-71.77	1.75	12.81	H	Pass
11280	-52.78	-13	-39.78	-64.27	-63.87	2.00	13.09	H	Pass
13160	-53.44	-13	-40.44	-64.74	-65.15	2.04	13.75	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	21~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	41~46%
<b>Test Engineer :</b>	Chenmy Cheng and Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS  
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL  
 Project : (FG) 211239-02  
 Plan : E2

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3762	-54.56	-13	-41.56	-55.93	-60.94	0.78	7.16	V	Pass
5640	-61.67	-13	-48.67	-64.89	-70.21	1.04	9.58	V	Pass
7520	-59.02	-13	-46.02	-63.51	-69.13	1.35	11.46	V	Pass
9400	-62.30	-13	-49.30	-63.52	-73.36	1.75	12.81	V	Pass
11280	-53.13	-13	-40.13	-64.37	-64.22	2.00	13.09	V	Pass
13160	-53.25	-13	-40.25	-64.44	-64.96	2.04	13.75	V	Pass

## 3.7 Frequency Stability Measurement

### 3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at  $-30^{\circ}\text{C}$ , the testing lowest temperature will be raised in  $10^{\circ}\text{C}$  step until the EUT can be turned on.

### 3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.7.5 Test Setup



### 3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		
Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-36	-0.04	
0	-31	-0.04	
10	-37	-0.04	
20	-39	-0.05	
30	-42	-0.05	
40	-45	-0.05	
50	-48	-0.06	
55	-51	-0.06	

**Note:** The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-35	-0.02	
0	-48	-0.03	
10	-36	-0.02	
20	-54	-0.03	
30	-46	-0.02	
40	-45	-0.02	
50	-42	-0.02	
55	-38	-0.02	

**Note:** The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-9	-0.01	
0	16	0.02	
10	15	0.02	
20	19	0.02	
30	21	0.02	
40	23	0.03	
50	25	0.03	
55	17	0.02	

**Note:** The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-29	-0.02	
0	-53	-0.03	
10	-46	-0.02	
20	-39	-0.02	
30	-36	-0.02	
40	-42	-0.02	
50	-41	-0.02	
55	-48	-0.03	

**Note:** The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	-39	-0.05	2.5	PASS
		BEP	-41	-0.05		
		4.35	-36	-0.04		
GSM 1900 CH661	GPRS 8	3.8	-53	-0.03		
		BEP	-57	-0.03		
		4.35	-63	-0.03		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	14	0.02		
		BEP	17	0.02		
		4.35	13	0.02		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	24	0.01		
		BEP	-25	-0.01		
		4.35	-15	-0.01		

Note:

- 1. Normal Voltage = 3.8V.
- 2. Battery End Point (BEP) = 3.5 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Mar. 24, 2012 ~ May 08, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 30, 2011	Mar. 24, 2012 ~ May 08, 2012	Dec. 29, 2012	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	GSM/GPRS850/900/1800/1900,	Dec. 30, 2011	Mar. 24, 2012 ~ May 08, 2012	Dec. 29, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jun. 02, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Jun. 01, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Mar. 24, 2012 ~ Mar. 25, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060029	9KHz~2GHz	Jan. 06, 2012	Mar. 24, 2012 ~ Mar. 25, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 30, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 07, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Nov. 06, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 11, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Oct. 10, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Mar. 24, 2012 ~ Mar. 25, 2012	Jul. 28, 2012	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	837587/066	GSM/GPRS850/900/1800/1900,	Dec. 30, 2011	Mar. 24, 2012 ~ Mar. 25, 2012	Dec. 29, 2012	Radiation (03CH01-KS)

## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.27</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.54</b>		

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$	$C_i$	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	$\pm 0.10$	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	$\pm 1.70$	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	$\pm 0.50$	Normal (k=2)	0.25	1	0.25
Receiver Correction	$\pm 2.00$	Rectangular	1.15	1	1.15
Antenna Factor Directional	$\pm 1.50$	Rectangular	0.87	1	0.87
Site Imperfection	$\pm 2.80$	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>2.36</b>				
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>4.72</b>				