

FCC SAR Test Report

APPLICANT : Motorola Mobility, Inc.
EQUIPMENT : CDMA/GSM Dual-SIM Dual-Standby Dual-Active digital mobile phone with BT/ Wi-Fi
BRAND NAME : Motorola
MODEL NAME : XT788
MARKETING NAME : MOTOLUXE XT XT788
TYPE NAME : M0D71
GPPD NUMBER : 3441
FCC ID : IHDT56NY1
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003
FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was completely tested on Sep. 15, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
2.1 Testing Laboratory	5
2.2 Applicant	5
2.3 Manufacturer	5
2.4 Application Details	5
3. General Information	6
3.1 Description of Equipment Under Test (EUT)	6
3.2 Product Photos	7
3.3 Applied Standard	7
3.4 Device Category and SAR Limits	7
3.5 Test Conditions	7
4. Specific Absorption Rate (SAR)	8
4.1 Introduction	8
4.2 SAR Definition	8
5. SAR Measurement System	9
5.1 E-Field Probe	10
5.2 Data Acquisition Electronics (DAE)	11
5.3 Robot	11
5.4 Measurement Server	11
5.5 Phantom	12
5.6 Device Holder	13
5.7 Data Storage and Evaluation	14
5.8 Test Equipment List	16
6. Tissue Simulating Liquids	17
7. SAR Measurement Evaluation	19
7.1 Purpose of System Performance check	19
7.2 System Setup	19
7.3 Validation Results	20
8. EUT Testing Position	21
8.1 Define two imaginary lines on the handset	21
8.2 Cheek Position	22
8.3 Tilted Position	22
8.4 Body Worn Position	23
9. Measurement Procedures	24
9.1 Spatial Peak SAR Evaluation	24
9.2 Area & Zoom Scan Procedures	24
9.3 Volume Scan Procedures	25
9.4 SAR Averaged Methods	25
9.5 Power Drift Monitoring	25
10. SAR Test Configurations	26
10.1 Exposure Positions Consideration	26
10.2 Conducted RF Output Power (Unit: dBm)	28
11. SAR Test Results	31
11.1 Test Records for Head SAR Test	31
11.2 Test Records for Hotspot SAR Test	32
11.3 Test Records for Body-worn SAR Test	33
11.4 Simultaneous Multi-band Transmission Analysis	34
11.5 Simultaneous analysis - SPLSR calculation	38
12. Uncertainty Assessment	39
13. References	41
Appendix A. Plots of System Performance Check	
Appendix B. Plots of SAR Measurement	
Appendix C. DASYS Calibration Certificate	

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility, Inc. CDMA/GSM Dual-SIM Dual-Standby Dual-Active digital mobile phone with BT/ Wi-Fi Motorola XT788** are as follows.

<Standalone SAR>

Band	Position	SAR_{1g} (W/kg)	Scaled SAR_{1a} (W/kg)
GSM1900	Head	0.320	0.327
CDMA2000 BC0	Head	1.08	1.165
WLAN 2.4G	Head	0.114	0.119
GSM1900	Hotspot (1 cm Gap)	0.539	0.550
CDMA2000 BC0	Hotspot (1 cm Gap)	0.961	1.032
WLAN 2.4G	Hotspot (1 cm Gap)	0.124	0.129
GSM1900	Body-worn (1 cm Gap)	0.518	0.529
CDMA2000 BC0	Body-worn (1 cm Gap)	1.05	1.125
WLAN 2.4G	Body-worn (1 cm Gap)	0.124	0.129

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).



2. Administration Data

2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958

2.2 Applicant

Company Name	Motorola Mobility, Inc.
Address	9F., No.9, Songgao Rd., Taipei 110, Taiwan, R.O.C.

2.3 Manufacturer

Company Name	Huizhou BYD Electronic Co., Ltd.
Address	Xiangshui River, Economic Development Zone, Daya Bay, Huizhou, Guangdong

2.4 Application Details

Date of Start during the Test	Sep. 08, 2012
Date of End during the Test	Sep. 15, 2012

3. General Information

3.1 Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT	CDMA/GSM Dual-SIM Dual-Standby Dual-Active digital mobile phone with BT/ Wi-Fi
Brand Name	Motorola
Model Name	XT788
Marketing Name	MOTOLUXE XT XT788
Type Name	M0D71
FCC ID	IHDT56NY1
Tx Frequency	GSM1900: 1850.2 MHz ~ 1909.8MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz WLAN2.4G: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM1900: 1930.2 MHz ~ 1989.8 MHz CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz WLAN2.4G: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Maximum Average Output Power to Antenna	GSM1900: 30.34 dBm CDMA2000 BC0: 24.90 dBm 802.11b: 13.33 dBm 802.11g: 9.41 dBm 802.11n (11n-HT20) (2.4GHz): 8.72 dBm Bluetooth: 8.03 dBm
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna
HW Version	B2
SW Version	IRPMCT_B_02.41.00RDD
Uplink Modulation	GSM: GMSK GPRS: GMSK CDMA2000 : QPSK CDMA2000 1xEV-DO : 8PSK 802.11b: DSSS (BPSK / QPSK / CCK) 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth (1Mbps) : GFSK Bluetooth 2.1 EDR (2Mbps) : π /4-DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK
Dual Transfer Mode (DTM) Category	Class B – DUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	



3.2 Product Photos

Please refer to Appendix D.

3.3 Applied Standard

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 447498 D01 v04
- FCC KDB 648474 D01 v01r05
- FCC KDB 941225 D01 v02
- FCC KDB 941225 D03 v01
- FCC KDB 941225 D06 v01
- FCC KDB 248227 D01 v01r02

3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

3.5 Test Conditions

3.5.1 Ambient Condition

Ambient Temperature	20 to 24 °C
Humidity	< 60 %

3.5.2 Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests.

For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.

4. Specific Absorption Rate (SAR)

4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

5. SAR Measurement System




Fig 5.1 SPEAG DASY System Configurations

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Component details are described in in the following sub-sections.

5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

5.1.1 E-Field Probe Specification

<EX3DV4 Probe>


Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Fig 5.2 Photo of EX3DV4

5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.3 Photo of DAE

5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig 5.4 Photo of DASY5

5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Fig 5.5 Photo of Server for DASY5

5.5 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
Measurement Areas	Left Hand, Right Hand, Flat Phantom



Fig 5.6 Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI4 Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)
Filling Volume	Approx. 30 liters
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm




Fig 5.7 Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

5.6 Device Holder

<Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.8 Device Holder

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.




Fig 5.9 Laptop Extension Kit

5.7 Data Storage and Evaluation

5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

Probe parameters :	- Sensitivity	Norm _i , a _{i0} , a _{i1} , a _{i2}
	- Conversion factor	ConvF _i
	- Diode compression point	dcp _i
Device parameters :	- Frequency	f
	- Crest factor	cf
	Media parameters :	- Conductivity
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i, (i = x, y, z)
 U_i = input signal of channel i, (i = x, y, z)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated :

$$\text{E-field Probes : } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field Probes : } H_i = \sqrt{V_i \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}}$$

with V_i = compensated signal of channel i, (i = x, y, z)
 Norm_i = sensor sensitivity of channel i, (i = x, y, z), $\mu\text{V}/(\text{V/m})^2$ for E-field Probes
 ConvF = sensitivity enhancement in solution
 a_{ij} = sensor sensitivity factors for H-field probes
 f = carrier frequency [GHz]
 E_i = electric field strength of channel i in V/m
 H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm³

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.



5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 18, 2011	Nov. 17, 2012
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2011	Nov. 20, 2012
SPEAG	2450MHz System Validation Kit	D2450V2	736	Jul. 25, 2011	Jul. 24, 2013
SPEAG	Data Acquisition Electronics	DAE4	1210	Nov. 18, 2011	Nov. 17, 2012
SPEAG	Dosimetric E-Field Probe	EX3DV4	3857	Jun. 20,2012	Jun. 19, 2013
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1477	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1479	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201074235	Nov. 30, 2011	Nov. 29, 2013
Agilent	Wireless Communication Test Set	E5515C	GB47050646	Aug. 18, 2011	Aug. 17, 2013
Agilent	Wireless Communication Test Set	E5515C	MY48367160	Oct. 26, 2011	Oct. 25, 2013
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	Apr. 13, 2012	Apr. 12, 2013
R&S	Signal Generator	SMR40	100455	Dec. 30, 2011	Dec. 29, 2012
Agilent	Power Meter	E4416A	MY45101555	Aug. 22, 2012	Aug. 21, 2013
Agilent	Power Sensor	E9327A	MY44421198	Aug. 22, 2012	Aug. 21, 2013
R&S	Spectrum Analyzer	FSP30	101399	Jun. 01, 2012	May 31, 2013

Table 5.1 Test Equipment List

Note:

1. The calibration certificate of DASY can be referred to appendix C of this report.
2. Referring to KDB 450824 D02, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole D2450V2, SN: 736, can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.



Fig 6.1 Photo of Liquid Height for Head SAR



Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7

Table 6.1 Recipes of Tissue Simulating Liquid



The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

The following table shows the measuring results for simulating liquid.

Freq. (MHz)	Liquid Type	Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	21.6	0.913	40.859	0.9	41.5	1.44	-1.54	±5	Sep. 09, 2012
835	Head	21.2	0.927	42.674	0.9	41.5	3.00	2.83	±5	Sep. 11, 2012
1900	Head	21.1	1.419	40.609	1.40	40.0	1.36	1.52	±5	Sep. 08, 2012
1900	Head	21.1	1.415	40.527	1.40	40.0	1.07	1.32	±5	Sep. 12, 2012
2450	Head	21.4	1.856	37.685	1.8	39.2	3.11	-3.86	±5	Sep. 14, 2012
835	Body	21.2	0.974	54.111	0.97	55.2	0.41	-1.97	±5	Sep. 10, 2012
835	Body	21.3	0.994	55.57	0.97	55.2	2.47	0.67	±5	Sep. 14, 2012
1900	Body	21.5	1.531	54.671	1.52	53.3	0.72	2.57	±5	Sep. 09, 2012
1900	Body	21.4	1.512	53.903	1.52	53.3	-0.53	1.13	±5	Sep. 14, 2012
2450	Body	21.5	1.951	53.859	1.95	52.7	0.05	2.20	±5	Sep. 15, 2012

Table 6.2 Measuring Results for Simulating Liquid

7. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

7.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

7.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 7.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 24 dBm (250 mW) before dipole is connected.



Fig 7.2 Photo of Dipole Setup

7.3 Validation Results

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 7.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Frequency (MHz)	Liquid Type	Targeted SAR _{1g} (W/kg)	Measured SAR _{1g} (W/kg)	Normalized SAR _{1g} (W/kg)	Deviation (%)
Sep. 09, 2012	835	Head	9.4	2.42	9.68	2.98
Sep. 11, 2012	835	Head	9.4	2.46	9.84	4.68
Sep. 08, 2012	1900	Head	40.3	9.77	39.08	-3.03
Sep. 12, 2012	1900	Head	40.3	9.74	38.96	-3.33
Sep. 14, 2012	2450	Head	54.8	14.2	56.80	3.65
Sep. 10, 2012	835	Body	9.42	2.49	9.96	5.73
Sep. 14, 2012	835	Body	9.42	2.54	10.16	7.86
Sep. 09, 2012	1900	Body	41.8	10.1	40.40	-3.35
Sep. 14, 2012	1900	Body	41.8	9.98	39.92	-4.50
Sep. 15, 2012	2450	Body	52.3	13.4	53.60	2.49

Table 7.1 Target and Measurement SAR after Normalized

8. EUT Testing Position

This EUT was tested in ten different positions. They are right cheek, right tilted, left cheek, left tilted, Front of the EUT with phantom 1 cm gap, Back of the EUT with phantom 1 cm gap, Top Side of the EUT with phantom 1 cm gap, Bottom Side of the EUT with phantom 1 cm gap, Right Side of the EUT with phantom 1 cm gap, and Left Side of the EUT with phantom 1 cm gap, as illustrated below:

8.1 Define two imaginary lines on the handset

- The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig 8.1 Illustration for Handset Vertical and Horizontal Reference Lines

8.2 Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).




Fig 8.2 Illustration for Cheek Position

8.3 Tilted Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).




Fig 8.3 Illustration for Tilted Position

8.4 Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1 cm.




Fig 8.4 Illustration for Body Worn Position

<EUT Setup Photos>

Please refer to Appendix E for the test setup photos.



9. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% EUTy factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Appendix E demonstrates.
- (e) Set scan area, grid size and other setting on the DASY software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.



9.3 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remains in the same test position for all measurements and all volume scans use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scans are completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculate the multiband SAR.

9.4 SAR Averaged Methods

In DASy, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.


Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

9.5 Power Drift Monitoring

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

10. SAR Test Configurations

10.1 Exposure Positions Consideration



Antennas	Wireless Interface
GSM Antenna (Tx / Rx)	GSM1900
CDMA Antenna (Tx / Rx)	CDMA2000 BC 0
WLAN & Bluetooth Antenna (Tx / Rx)	WLAN 2.4GHz Bluetooth



Sides for SAR tests; Hotspot mode						
Test distance: 10 mm						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
GSM	YES	YES	NO	YES	YES	YES
CDMA	YES	YES	YES	NO	YES	YES
WLAN & Bluetooth	YES	YES	NO	YES	YES	NO

Note:

1. Head/Body-worn/Hotspot mode SAR assessments are required.
2. Referring to KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
3. For GSM antenna, SAR measurements at Top side are not required since the distance between EUT and flat phantom $> 25\text{mm}$.
4. For CDMA antenna, SAR measurements at Bottom side are not required since the distance between EUT and flat phantom $> 25\text{mm}$.
5. For WLAN & BT antenna, SAR measurements Top/Left sides are not required since the distance between EUT and flat phantom $> 25\text{mm}$.



10.2 Conducted RF Output Power (Unit: dBm)

<GSM>

Burst Average Power			
Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM (1 Uplink)	30.32	30.33	30.25
GPRS 8 (1 Uplink) – CS1	30.32	30.34	30.23
GPRS 10 (2 Uplink) – CS1	30.30	30.31	30.21

Source-Based Time-Averaged Power			
Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM (1 Uplink)	21.32	21.33	21.25
GPRS 8 (1 Uplink) – CS1	21.32	21.34	21.23
GPRS 10 (2 Uplink) – CS1	24.30	24.31	24.21

Remark: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time averaged power = Maximum burst averaged power (1 Uplink) - 9 dB

Source based time averaged power = Maximum burst averaged power (2 Uplink) - 6 dB

Note:

1. For Head/Body-worn SAR testing, GSM and GPRS are measured for GSM850 and GSM1900, but the DUT was set in GPRS 10 due to its highest source-based time-average power.
2. For hotspot SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS 10 for GSM850 and GSM1900 due to its highest source-based time-average power.
3. Per KDB 648474, the maximum output power channel is used for SAR testing and for further SAR test reduction.
4. The DUT do not support DTM function.



<CDMA2000>

Burst Average Power			
Band	CDMA2000 BC0		
Channel	1013	384	777
Frequency (MHz)	824.70	836.52	848.31
1xRTT RC1+SO55	24.89	24.86	24.84
1xRTT RC3+SO55	24.88	24.83	24.86
1xRTT RC3+SO32(+ F-SCH)	24.90	24.88	24.86
1xRTT RC3+SO32(+SCH)	24.87	24.8	24.88
1xEVDO RTAP 9.6	24.83	24.85	24.83
1xEVDO RETAP 38.4	24.86	24.86	24.83
1xEVDO RTAP 153.6	24.89	24.82	24.87
1xEVDO RETAP 128	24.81	24.80	24.88
1xEVDO RTAP 516	24.87	24.83	24.82
1xEVDO RETAP 1024	24.80	24.80	24.81
1xEVDO RTAP 2048	24.83	24.87	24.84
1xEVDO RETAP 4096	24.80	24.85	24.85

Note:

1. According to KDB 941225 D01, CDMA Head SAR is measured on RC3+SO55, and body-worn SAR is measured on RC3+SO32.
2. According to KDB 941225 D01, 1xEVDO data device SAR is measured on Rev.0 RTAP153.6 kbps; in the scenario this device acts as a data device SAR is measured on EVDO Rev.0.
3. Per KDB 648474, the maximum output power channel is used for SAR testing and for further SAR test reduction.



<WLAN 2.4GHz>

Mode	Channel	Frequency (MHz)	Average power (dBm)			
			Data Rate (bps)			
			1M	2M	5.5M	11M
802.11b	CH 01	2412	12.99	12.97	13.19	13.03
	CH 06	2437	13.07	13.06	13.26	13.13
	CH 11	2462	13.33	13.19	13.31	13.26

Mode	Channel	Frequency (MHz)	Average power (dBm)							
			Data Rate (bps)							
			6M	9M	12M	18M	24M	36M	48M	54M
802.11g	CH 01	2412	7.13	7.18	7.21	7.33	8.55	8.76	8.94	9.19
	CH 06	2437	7.16	7.22	7.25	7.40	8.59	8.82	8.96	9.21
	CH 11	2462	7.36	7.42	7.46	7.60	8.76	8.99	9.13	9.41

Mode	Channel	Frequency (MHz)	Average power (dBm)							
			Data Rate (bps)							
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n HT20	CH 01	2412	6.34	6.59	6.72	8.01	8.18	8.37	8.53	8.49
	CH 06	2437	6.43	6.63	6.77	8.10	8.24	8.41	8.58	8.56
	CH 11	2462	6.62	6.84	6.97	8.25	8.39	8.62	8.72	8.70

Note:

1. Per KDB 248227, choose the lowest data rate, highest output power channel to test SAR and determine further SAR exclusion; CH11 1Mbps was chosen.
2. Per KDB 248227, 11g and 11n-HT20 output power is less than 1/4 dB higher than 11b mode, thus the SAR can be excluded.
3. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4 dB higher than those measured at the lowest data rate.

<Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power (dBm)								
			Package Type								
			DH1	DH3	DH5	2DH1	2DH3	2DH5	3DH1	3DH3	3DH5
Bluetooth	CH 00	2402	6.82	6.96	6.97	5.82	5.80	5.72	5.80	5.75	5.68
	CH 39	2441	7.59	7.72	7.78	6.54	6.45	6.47	6.57	6.53	6.45
	CH 78	2480	7.88	7.97	8.03	6.75	6.71	6.72	6.71	6.61	6.69



11. SAR Test Results

11.1 Test Records for Head SAR Test

<GSM>

Plot No.	Band	Mode	Test Position	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
1	GSM1900	GSM	Right Cheek	661	30.33	30.4	1.016	0.080	0.081	0.047
2	GSM1900	GSM	Right Tilted	661	30.33	30.4	1.016	0.036	0.037	0.019
3	GSM1900	GSM	Left Cheek	661	30.33	30.4	1.016	0.146	0.148	0.082
4	GSM1900	GSM	Left Tilted	661	30.33	30.4	1.016	0.032	0.033	0.016
5	GSM1900	GPRS10	Right Cheek	661	30.31	30.4	1.021	0.172	0.176	0.098
6	GSM1900	GPRS10	Right Tilted	661	30.31	30.4	1.021	0.071	0.072	0.038
7	GSM1900	GPRS10	Left Cheek	661	30.31	30.4	1.021	0.320	0.327	0.180
8	GSM1900	GPRS10	Left Tilted	661	30.31	30.4	1.021	0.067	0.068	0.036

Note: Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<CDMA2000>

Plot No.	Band	Mode	Test Position	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
9	CDMA2000 BC0	RC3 SO55	Right Cheek	1013	24.88	25.2	1.076	0.700	0.754	0.503
10	CDMA2000 BC0	RC3 SO55	Right Tilted	1013	24.88	25.2	1.076	0.634	0.682	0.413
11	CDMA2000 BC0	RC3 SO55	Left Cheek	1013	24.88	25.2	1.076	0.958	1.031	0.575
12	CDMA2000 BC0	RC3 SO55	Left Cheek	384	24.83	25.2	1.089	1.03	1.122	0.616
13	CDMA2000 BC0	RC3 SO55	Left Cheek	777	24.86	25.2	1.081	1.05	1.136	0.627
14	CDMA2000 BC0	RC3 SO55	Left Tilted	1013	24.88	25.2	1.076	0.932	1.003	0.516
15	CDMA2000 BC0	RC3 SO55	Left Tilted	384	24.83	25.2	1.089	1.02	1.111	0.567
16	CDMA2000 BC0	RC3 SO55	Left Tilted	777	24.86	25.2	1.081	0.990	1.071	0.551
25	CDMA2000 BC0	RTAP153.6	Right Cheek	1013	24.89	25.2	1.074	0.642	0.690	0.451
26	CDMA2000 BC0	RTAP153.6	Right Tilted	1013	24.89	25.2	1.074	0.659	0.708	0.427
27	CDMA2000 BC0	RTAP153.6	Left Cheek	1013	24.89	25.2	1.074	0.979	1.051	0.576
28	CDMA2000 BC0	RTAP153.6	Left Cheek	384	24.82	25.2	1.091	1.01	1.102	0.582
29	CDMA2000 BC0	RTAP153.6	Left Cheek	777	24.87	25.2	1.079	1.08	1.165	0.646
30	CDMA2000 BC0	RTAP153.6	Left Tilted	1013	24.89	25.2	1.074	0.917	0.985	0.505
31	CDMA2000 BC0	RTAP153.6	Left Tilted	384	24.82	25.2	1.091	1.04	1.135	0.539
32	CDMA2000 BC0	RTAP153.6	Left Tilted	777	24.87	25.2	1.079	1.05	1.133	0.568

Note: Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
33	WLAN2.4G	802.11b	Right Cheek	11	13.33	13.5	1.040	0.114	0.119	0.059
34	WLAN2.4G	802.11b	Right Tilted	11	13.33	13.5	1.040	0.058	0.060	0.026
35	WLAN2.4G	802.11b	Left Cheek	11	13.33	13.5	1.040	0.083	0.086	0.044
36	WLAN2.4G	802.11b	Left Tilted	11	13.33	13.5	1.040	0.030	0.031	0.014

Note: Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

11.2 Test Records for Hotspot SAR Test

<GSM>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
43	GSM1900	GPRS10	Front	1	661	30.31	30.4	1.021	0.410	0.419	0.252
44	GSM1900	GPRS10	Back	1	661	30.31	30.4	1.021	0.514	0.525	0.280
46	GSM1900	GPRS10	Left Side	1	661	30.31	30.4	1.021	0.262	0.267	0.146
47	GSM1900	GPRS10	Right Side	1	661	30.31	30.4	1.021	0.046	0.047	0.028
48	GSM1900	GPRS10	Bottom Side	1	661	30.31	30.4	1.021	0.539	0.550	0.288

Note:

1. Per KDB 941225 D06, for EUT dimension $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
2. As in (1), SAR for Front/Back/Bottom Side/Left Side/Right Side is necessary.
3. Per KDB 648474 if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<CDMA2000>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
73	CDMA2000 BC0	RTAP153.6	Front	1	1013	24.89	25.2	1.074	0.431	0.463	0.336
74	CDMA2000 BC0	RTAP153.6	Back	1	1013	24.89	25.2	1.074	0.961	1.032	0.729
75	CDMA2000 BC0	RTAP153.6	Back	1	384	24.82	25.2	1.091	0.892	0.974	0.620
76	CDMA2000 BC0	RTAP153.6	Back	1	777	24.87	25.2	1.079	0.841	0.907	0.650
80	CDMA2000 BC0	RTAP153.6	Left Side	1	1013	24.89	25.2	1.074	0.699	0.751	0.479
81	CDMA2000 BC0	RTAP153.6	Right Side	1	1013	24.89	25.2	1.074	0.858	0.921	0.588
82	CDMA2000 BC0	RTAP153.6	Right Side	1	384	24.82	25.2	1.091	0.786	0.858	0.540
83	CDMA2000 BC0	RTAP153.6	Right Side	1	777	24.87	25.2	1.079	0.707	0.763	0.484
84	CDMA2000 BC0	RTAP153.6	Top Side	1	1013	24.89	25.2	1.074	0.329	0.353	0.198

Note:

1. Per KDB 941225 D06, for EUT dimension $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
2. As in (1), SAR for Front/Back/Top Side/Left Side/Right Side is necessary.
3. Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
85	WLAN2.4G	802.11b	Front	1	11	13.33	13.5	1.040	0.115	0.120	0.056
87	WLAN2.4G	802.11b	Back	1	11	13.33	13.5	1.040	0.124	0.129	0.063
88	WLAN2.4G	802.11b	Right Side	1	11	13.33	13.5	1.040	0.076	0.079	0.041
89	WLAN2.4G	802.11b	Bottom Side	1	11	13.33	13.5	1.040	0.080	0.083	0.042

Note:

1. Per KDB 941225 D06, for EUT dimension $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
2. As in (1), SAR for Front/Back/Bottom Side/Right Side is necessary.
3. Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.



11.3 Test Records for Body-worn SAR Test

<GSM>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
37	GSM1900	GSM	Front	1	661	30.33	30.4	1.016	0.207	0.210	0.131
38	GSM1900	GSM	Back	1	661	30.33	30.4	1.016	0.274	0.278	0.149
39	GSM1900	GSM	Back w/ headset	1	661	30.33	30.4	1.016	0.285	0.290	0.153
43	GSM1900	GPRS10	Front	1	661	30.31	30.4	1.021	0.410	0.419	0.252
44	GSM1900	GPRS10	Back	1	661	30.31	30.4	1.021	0.514	0.525	0.280
45	GSM1900	GPRS10	Back w/ headset	1	661	30.31	30.4	1.021	0.518	0.529	0.282

Note: Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<CDMA2000>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
61	CDMA2000 BC0	RC3 SO32	Front	1	1013	24.9	25.2	1.072	0.462	0.495	0.363
62	CDMA2000 BC0	RC3 SO32	Back	1	1013	24.9	25.2	1.072	1.05	1.125	0.810
63	CDMA2000 BC0	RC3 SO32	Back	1	384	24.88	25.2	1.076	1	1.076	0.778
64	CDMA2000 BC0	RC3 SO32	Back	1	777	24.86	25.2	1.081	0.949	1.026	0.734
65	CDMA2000 BC0	RC3 SO32	Back w/ headset	1	1013	24.9	25.2	1.072	0.914	0.979	0.705
66	CDMA2000 BC0	RC3 SO32	Back w/ headset	1	384	24.88	25.2	1.076	0.800	0.861	0.611
67	CDMA2000 BC0	RC3 SO32	Back w/ headset	1	777	24.86	25.2	1.081	0.680	0.735	0.510
73	CDMA2000 BC0	RTAP153.6	Front	1	1013	24.89	25.2	1.074	0.431	0.463	0.336
74	CDMA2000 BC0	RTAP153.6	Back	1	1013	24.89	25.2	1.074	0.961	1.032	0.729
75	CDMA2000 BC0	RTAP153.6	Back	1	384	24.82	25.2	1.091	0.892	0.974	0.620
76	CDMA2000 BC0	RTAP153.6	Back	1	777	24.87	25.2	1.079	0.841	0.907	0.650
77	CDMA2000 BC0	RTAP153.6	Back w/ headset	1	1013	24.89	25.2	1.074	0.868	0.932	0.610
78	CDMA2000 BC0	RTAP153.6	Back w/ headset	1	384	24.82	25.2	1.091	0.821	0.896	0.617
79	CDMA2000 BC0	RTAP153.6	Back w/ headset	1	777	24.87	25.2	1.079	0.788	0.850	0.592

Note: Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	SAR _{10g} (W/kg)
85	WLAN2.4G	802.11b	Front	1	11	13.33	13.5	1.040	0.115	0.120	0.056
86	WLAN2.4G	802.11b	Front w/ headset	1	11	13.33	13.5	1.040	0.107	0.111	0.051
87	WLAN2.4G	802.11b	Back	1	11	13.33	13.5	1.040	0.124	0.129	0.063

Note: Per KDB 648474, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

11.4 Simultaneous Multi-band Transmission Analysis

	Position	Applicable Combination
Simultaneous Transmission	Head	GSM (voice) + CDMA (data) + WLAN
		GSM (data) + CDMA (voice) + WLAN
		GSM (voice) + WLAN
		CDMA (voice) + WLAN
		GSM (voice) + CDMA (data) + BT
		GSM (data) + CDMA (voice) + BT
		GSM (voice) + BT
		CDMA (voice) + BT
		GSM (voice) + CDMA (data)
		GSM (data) + CDMA (voice)
	Hotspot	GSM (data) + WLAN
		CDMA (data) + WLAN
	Body-worn	GSM (voice) + CDMA (data) + WLAN
		GSM (data) + CDMA (voice) + WLAN
		GSM (voice) + WLAN
		CDMA (voice) + WLAN
		GSM (data) + WLAN
		CDMA (data) + WLAN
		GSM (voice) + CDMA (data) + BT
		GSM (data) + CDMA (voice) + BT
		GSM (voice) + BT
		CDMA (voice) + BT
		GSM (data) + BT
		CDMA (data) + BT
		GSM (voice) + CDMA (data)
		GSM (data) + CDMA (voice)

Note:

1. WLAN and BT share the same antenna, and cannot transmit simultaneously.
2. Per KDB KDB 648474 D01, Bluetooth (8.03 dBm) output power $\leq P_{ref}$ and the distance to GSM transmitting antenna $\leq 2.5\text{cm}$, the maximum GSM SAR (0.539 W/kg) is $< 1.2\text{W/kg}$, simultaneous transmission consideration of GSM+ Bluetooth can be excluded.
3. Per KDB KDB 648474 D01, Bluetooth (8.03 dBm) output power $\leq 2P_{ref}$ and the distance to CDMA transmitting antenna $\geq 5\text{cm}$, therefore, stand-alone SAR is not required and the simultaneous transmission consideration of CDMA+ Bluetooth is not required
4. The maximum SAR summation is calculated based on the same configuration and test position.
5. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements.
6. If 1g-SAR scalar summation $< 1.6\text{W/kg}$, simultaneous SAR measurement is not necessary.
7. If 1g-SAR summation $> 1.6\text{W/kg}$, SPLSR calculation is necessary.

Table 11.4-A1: Head SAR analysis

	Position	Applicable Combination
Simultaneous Transmission	Head	GSM (voice) + CDMA (data) + WLAN
		GSM (data) + CDMA (voice) + WLAN
		GSM (voice) + WLAN
		CDMA (voice) + WLAN
		GSM (voice) + CDMA (data) + BT
		GSM (data) + CDMA (voice) + BT
		GSM (voice) + BT
		CDMA (voice) + BT
		GSM (voice) + CDMA (data)
		GSM (data) + CDMA (voice)

<Head SAR>

Position	Scaled GSM			Scaled CDMA			Scaled WLAN		Scaled WWAN + Scaled WLAN	Case No
	WWAN Band	Plot No	Scaled WWAN (W/kg)	WWAN Band	Plot No	Scaled WWAN (W/kg)	Plot No	Scaled WLAN (W/kg)		
Right Cheek	GSM1900 GSM	#1	0.081	CDMA BC0 RTAP 153.6	#25	0.690	#33	0.119	0.89	-
	GSM1900 GPRS	#5	0.176	CDMA BC0 RC3 SO55	#9	0.754	#33	0.119	1.05	-
Right Tilted	GSM1900 GSM	#2	0.037	CDMA BC0 RTAP 153.6	#26	0.708	#34	0.060	0.80	-
	GSM1900 GPRS	#6	0.072	CDMA BC0 RC3 SO55	#10	0.682	#34	0.060	0.81	-
Left Cheek	GSM1900 GSM	#3	0.148	CDMA BC0 RTAP 153.6	#29	1.165	#35	0.086	1.40	-
	GSM1900 GPRS	#7	0.327	CDMA BC0 RC3 SO55	#13	1.136	#35	0.086	1.55	-
Left Tilted	GSM1900 GSM	#4	0.033	CDMA BC0 RTAP 153.6	#32	1.133	#36	0.031	1.20	-
	GSM1900 GPRS	#8	0.068	CDMA BC0 RC3 SO55	#15	1.111	#36	0.031	1.21	-



Table 11.4-B1: Hotspot mode SAR analysis

	Position	Applicable Combination
Simultaneous Transmission	Hotspot	GSM (data) + WLAN
		CDMA (data) + WLAN

<Hotspot SAR>

Position	Scaled WWAN			Scaled WLAN		Scaled WWAN + Scaled WLAN	Case No
	WWAN Band	Plot No	Scaled WWAN (W/kg)	Plot No	Scaled WLAN (W/kg)		
Front	GSM1900 GPRS	#43	0.419	#85	0.12	0.54	-
	CDMA BC0 RTAP 153.6	#73	0.463	#85	0.12	0.58	-
Back	GSM1900 GPRS	#44	0.525	#87	0.129	0.65	-
	CDMA BC0 RTAP 153.6	#74	1.032	#87	0.129	1.16	-
Left Side	GSM1900 GPRS	#46	0.267			0.27	-
	CDMA BC0 RTAP 153.6	#80	0.751			0.75	-
Right Side	GSM1900 GPRS	#47	0.047	#88	0.079	0.13	-
	CDMA BC0 RTAP 153.6	#81	0.921	#88	0.079	1.00	-
Top Side	CDMA BC0 RTAP 153.6	#84	0.353			0.35	-
Bottom Side	GSM1900 GPRS	#48	0.550	#89	0.083	0.63	-

Table 11.4-C1: Body-worn SAR analysis


	Position	Applicable Combination
Simultaneous Transmission	Body-worn	GSM (voice) + CDMA (data) + WLAN
		GSM (data) + CDMA (voice) + WLAN
		GSM (voice) + WLAN
		CDMA (voice) + WLAN
		GSM (data) + WLAN
		CDMA (data) + WLAN
		GSM (voice) + CDMA (data) + BT
		GSM (data) + CDMA (voice) + BT
		GSM (voice) + BT
		CDMA (voice) + BT
		GSM (data) + BT
		CDMA (data) + BT
		GSM (voice) + CDMA (data)
		GSM (data) + CDMA (voice)

<Body-worn SAR>

Position	Scaled GSM			Scaled CDMA			Scaled WLAN		Scaled WWAN + Scaled WLAN	Case No
	WWAN Band	Plot No	Scaled WWAN (W/kg)	WWAN Band	Plot No	Scaled WWAN (W/kg)	Plot No	Scaled WLAN (W/kg)		
Front	GSM1900 GSM	#37	0.210	CDMA BC0 RTAP 153.6	#73	0.463	#85	0.120	0.79	-
	GSM1900 GPRS	#43	0.419	CDMA BC0 RC3 SO32	#61	0.495	#85	0.120	1.03	-
Back	GSM1900 GSM	#38	0.278	CDMA BC0 RTAP 153.6	#74	1.032	#87	0.129	1.44	-
	GSM1900 GPRS	#44	0.525	CDMA BC0 RC3 SO32	#62	1.125	#87	0.129	1.78	#C1-1
Front (w/ Headset)	-	-	-	-	-	-	#86	0.111	0.11	-
Back (w/ Headset)	GSM1900 GSM	#39	0.290	CDMA BC0 RTAP 153.6	#77	0.932	-	-	1.22	-
	GSM1900 GPRS	#45	0.529	CDMA BC0 RC3 SO32	#65	0.979	-	-	1.51	-

11.5 Simultaneous analysis - SPLSR calculation

Case No	Position	GSM 1900			CDMA BC0			WLAN 2.4G			SAR (W/kg)	Pair SAR (W/kg)	Distance (cm)	SPLSR	Pair SAR (W/kg)	Distance (cm)	SPLSR	Pair SAR (W/kg)	Distance (cm)	SPLSR	Volume Scan
		#44/(W/kg)			#62/(W/kg)			#87/(W/kg)			Sum	GSM+CDMA	GSM+CDMA	GSM+CDMA	GSM+WIFI	GSM+WIFI	GSM+WIFI	GSM+WIFI	CDMA+WIFI	CDMA+WIFI	CDMA+WIFI
#C1-1	Back	0.525			1.125			0.129			1.78	1.65	7.6	0.22	0.65	2.8	0.23	1.25	6.5	0.19	Not Required
		-0.011	-0.066	-0.202	-0.0215	0.009	-0.203	-0.0365	-0.054	-0.202											



Note: Per KDB 648474, if SPLSR < 0.3, simultaneously transmission SAR is not necessary.

Test Engineer : Fulu Hu and Jimmy Cheng

12. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observations is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 12.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) κ is the coverage factor

Table 12.1 Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.



Error Description	Uncertainty	Probability	Divisor	Ci	Ci	Standard	Standard
	Value (±%)	Distribution		(1g)	(10g)	Uncertainty (1g)	Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 12.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz



13. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [7] FCC KDB 447498 D01 v04, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", November 2009
- [8] FCC KDB 648474 D01 v01r05, "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", September 2008
- [9] FCC KDB 941225 D01 v02, "SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA", October 2007
- [10] FCC KDB 941225 D02 v02 "3GPP R6 HSPA and R7 HSPA+ SAR Guidance", December 2009.
- [11] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008
- [12] FCC KDB 941225 D04 v01, "Evaluating SAR for GSM/(E)GPRS Dual Transfer Mode", January 27 2010
- [13] FCC KDB 941225 D06 v01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", April 2011
- [14] FCC KDB 388624 D02, "Permit But Ask List", December 2011.



Appendix A. Plots of System Performance Check

The plots are shown as follows.



Appendix B. Plots of SAR Measurement

The plots are shown as follows.



Appendix C. DASYS Calibration Certificate

The DASYS calibration certificates are shown as follows.