

FCC RF Test Report

APPLICANT : Motorola Mobility, Inc.
EQUIPMENT : TD-SCDMA/GSM Dual-mode digit
mobile phone with BT/ Wi-Fi
BRAND NAME : Motorola
MODEL NAME : MT788
MARKETING NAME : MOTOLUXE XT MT788
TYPE NAME : M0D7B
GPPD NUMBER : 3451
FCC ID : IHDT56NY2
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Aug. 08, 2012 and completely tested on Sep. 28, 2012. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : IHDT56NY2

Page Number : 1 of 62

Report Issued Date : Oct. 12, 2012

Report Version : Rev. 01



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Testing Site.....	6
1.5 Applied Standards	6
1.6 Ancillary Equipment List	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 RF Output Power.....	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 RF Utility	10
3 TEST RESULT	11
3.1 Number of Channel Measurement	11
3.2 Hopping Channel Separation Measurement	13
3.3 Dwell Time Measurement.....	20
3.4 20dB Bandwidth Measurement	22
3.5 Peak Output Power Measurement	29
3.6 Conducted Band Edges Measurement	36
3.7 Conducted Spurious Emission Measurement	39
3.8 Radiated Band Edges and Spurious Emission Measurement	43
3.9 AC Conducted Emission Measurement.....	55
3.10 Antenna Requirements.....	60
4 LIST OF MEASURING EQUIPMENT.....	61
5 UNCERTAINTY OF EVALUATION.....	62



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR280827A	Rev. 01	Initial issue of report	Oct. 12, 2012

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	A8.1(b)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	$\leq 1\text{ w}$ for 1Mbps $\leq 125\text{ Mw}$ for 2, 3Mbps	Pass	-
3.6	15.247(d)	A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	A8.5	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.17 dB at 2483.500 MHz
3.9	15.207	Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 9.41 dB at 2.010 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Motorola Mobility, Inc.

No. 1, Wang Jing East Road, Chao Yang District, 100102 Beijing, P. R. China

1.2 Manufacturer

Huizhou BYD Electronic Co., Ltd.

Xiangshui River, Economic Development Zone, Daya Bay, Huizhou, Guangdong

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	TD-SCDMA/GSM Dual-mode digit mobile phone with BT/Wi-Fi
Brand Name	Motorola
Model Name	MT788
Marketing Name	MOTOLUXE XT MT788
Type Name	M0D7B
FCC ID	IHDT56NY2
EUT supports Radios application	GSM/EGPRS WLAN 11bgn / Bluetooth
HW Version	P1.5
SW Version	IRPMTD_6_02.33.00DDS
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 9.90 dBm (0.0098 W) Bluetooth EDR (2Mbps) : 9.50 dBm (0.0089 W) Bluetooth EDR (3Mbps) : 10.02 dBm (0.0100 W)
Antenna Type	LDS Antenna type with gain 0.50 dBi
Type of Modulation	Bluetooth 3.0 EDR : GFSK, $\pi/4$ -DQPSK, 8-DPSK

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	03CH01-KS	CO01-KS	149928/4086E-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC Public Notice DA 00-705
- ANSI C63.4-2003 and ANSI C63.10-2009
- IC RSS-210 Issue 8
- IC RSS-Gen Issue 3

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-855	KA2DIR855 A2	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
5.	Notebook	Dell	P08S	QDS-BRCM 1030	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Notebook	Acer	Trave lmate 2413Lci	QDS-BRCM 1016	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
7.	DC Power Supply	GW	GPC-60300	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	9.90 dBm	9.43 dBm	9.99 dBm
Ch39	2441MHz	9.80 dBm	9.50 dBm	10.02 dBm
Ch78	2480MHz	9.53 dBm	9.16 dBm	9.66 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
3. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and ANSI C63.10-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 KHz to 30 MHz), radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases (X plane) and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	Pretest	Pretest	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz
AC Conducted Emission	Mode 1 :GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + Camera + USB Cable (Charging from Adapter) Mode 2 :GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + MPEG4 + USB Cable (Charging from Adapter)		
Remark:			
1. For radiated TCs, the data rate was set in 3Mbps due to the highest RF output power; only the data of these modes was reported.			
2. For conducted emission, the worst case is mode 1; only the test data of this mode was reported.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

For Bluetooth function, the RF utility, "ADB" was installed in notebook which was programmed in order to make the EUT into the engineering modes to contact with Bluetooth base station for continuous transmitting and receiving signals.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure


1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW $\geq$ 1% of the span; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	3Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78


Date: 16.SEP.2012 11:19:55



Date: 16.SEP.2012 11:23:22

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation


Test Mode :	1Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1008.000	0.6000	Pass
39	2441	1002.000	0.6027	Pass
78	2480	1002.000	0.6080	Pass


Channel Separation Plot on Channel 00 - 01



Date: 15.SEP.2012 01:05:32

Channel Separation Plot on Channel 39 - 40


Date: 15.SEP.2012 01:06:13

Channel Separation Plot on Channel 77 - 78



Date: 15.SEP.2012 01:07:14




Test Mode :	2Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1008.000	0.9040	Pass
39	2441	1002.000	0.9120	Pass
78	2480	1002.000	0.9000	Pass


Channel Separation Plot on Channel 00 - 01



Date: 15.SEP.2012 01:08:27

Channel Separation Plot on Channel 39 - 40


Date: 15.SEP.2012 01:09:18

Channel Separation Plot on Channel 77 - 78



Date: 15.SEP.2012 01:10:03



Test Mode :	3Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1002.000	0.8920	Pass
39	2441	1002.000	0.8920	Pass
78	2480	1002.000	0.8960	Pass


Channel Separation Plot on Channel 00 - 01



Date: 15.SEP.2012 01:10:46




Channel Separation Plot on Channel 39 - 40



Date: 15.SEP.2012 01:11:32

Channel Separation Plot on Channel 77 - 78



Date: 15.SEP.2012 01:12:18

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output connector was connected to the spectrum analyzer through a low loss cable.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	3DH5	Temperature :	21~22℃
Test Engineer :	Lizy Li	Relative Humidity :	41~42%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
3DH5	3.60	2930.00	0.33	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. T: Package Transfer Time(us)




3DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 12.SEP.2012 18:31:00

3DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 16.SEP.2012 10:40:03

3.4 20dB Bandwidth Measurement

3.4.1 Limit of 20dB Bandwidth

Reporting only


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	21~22℃
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.900
39	2441	0.904
78	2480	0.912


20 dB Bandwidth Plot on Channel 00



Date: 16.SEP.2012 10:17:58




20 dB Bandwidth Plot on Channel 39



Date: 16.SEP.2012 10:58:18

20 dB Bandwidth Plot on Channel 78




Date: 16.SEP.2012 10:57:42



Test Mode :	2Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.356
39	2441	1.368
78	2480	1.350


20 dB Bandwidth Plot on Channel 00



Date: 16.SEP.2012 10:18:22




20 dB Bandwidth Plot on Channel 39



Date: 16.SEP.2012 10:18:28

20 dB Bandwidth Plot on Channel 78




Date: 16.SEP.2012 10:18:34



Test Mode :	3Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.338
39	2441	1.338
78	2480	1.344


20 dB Bandwidth Plot on Channel 00



Date: 16.SEP.2012 10:18:40




20 dB Bandwidth Plot on Channel 39



Date: 16.SEP.2012 10:18:45

20 dB Bandwidth Plot on Channel 78



Date: 16.SEP.2012 10:18:50

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, and 3Mbps are 0.125 watts.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power


Test Mode :	1Mbps	Temperature :	21~22℃
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	9.90	30.00	Pass
39	2441	9.80	30.00	Pass
78	2480	9.53	30.00	Pass


Peak Output Power Plot on Channel 00



Date: 12.SEP.2012 18:23:49

Peak Output Power Plot on Channel 39



Date: 12.SEP.2012 18:25:06

Peak Output Power Plot on Channel 78


Date: 12.SEP.2012 18:26:24

Test Mode :	2Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%


Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	9.43	20.97	Pass
39	2441	9.50	20.97	Pass
78	2480	9.16	20.97	Pass

Peak Output Power Plot on Channel 00


Date: 12.SEP.2012 18:24:23




Peak Output Power Plot on Channel 39



Date: 12.SEP.2012 18:25:41

Peak Output Power Plot on Channel 78




Date: 12.SEP.2012 18:26:58



Test Mode :	3Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	9.99	20.97	Pass
39	2441	10.02	20.97	Pass
78	2480	9.66	20.97	Pass


Peak Output Power Plot on Channel 00



Date: 12.SEP.2012 18:24:49



Peak Output Power Plot on Channel 39



3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 300KHz ($\geq 1\%$ span=30MHz), VBW = 300KHz ($\geq$ RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300KHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Record the results in the test report.


3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges


Test Mode :	3Mbps	Temperature :	21~22°C
Test Channel :	00 and 78	Relative Humidity :	41~42%
		Test Engineer :	Lizy Li

Low Band Edge Plot on Channel 00



Date: 16.SEP.2012 10:23:35


High Band Edge Plot on Channel 78




Date: 16.SEP.2012 10:24:38

2.6.5 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	3Mbps	Temperature :	21~22°C
Test Engineer :	Lizy Li	Relative Humidity :	41~42%

Hopping Mode Low Band Edge Plot


Date: 16.SEP.2012 11:52:33

Hopping Mode High Band Edge Plot


Date: 16.SEP.2012 11:54:53

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The transmitter output was connected to the spectrum analyzer via a low lose cable.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 KHz, VBW = 300KHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 KHz RBW.
5. Record the results in the test report.


3.7.4 Test Setup



3.7.5 Test Result


Test Mode :	3Mbps	Temperature :	21~22℃
Test Channel :	00	Relative Humidity :	41~42%
		Test Engineer :	Lizy Li

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 16.SEP.2012 10:30:59

Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz




Date: 28.SEP.2012 16:18:53




Test Mode :	3Mbps	Temperature :	21~22°C
Test Channel :	39	Relative Humidity :	41~42%
		Test Engineer :	Lizy Li

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 16.SEP.2012 10:32:03

Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz




Date: 28.SEP.2012 16:18:13




Test Mode :	3Mbps	Temperature :	21~22℃
Test Channel :	78	Relative Humidity :	41~42%
		Test Engineer :	Lizy Li

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 16.SEP.2012 10:33:07

Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz



Date: 28.SEP.2012 16:17:15

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 KHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures


1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines and fulfills ANSI C63.4-2003 and the guidelines in ANSI C63.10-2009 test site requirement.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 KHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Level = Peak Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.5dB) derived from $20 \log (\text{dwell time}/100\text{ms})$.


For example: Average level = $45.61\text{dBuV/m} - 24.5 \text{ (dB)} = 21.11\text{dBuV/m}$.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


3.8.6 Duty cycle correction factor for average measurement

3DH5 on time/100ms (One Pulse) Plot on Channel 39



Date: 28.SEP.2012 13:13:32

3DH5 on time/100ms (Count Pulses) Plot on Channel 39



Date: 28.SEP.2012 13:17:15

Note:

1. Duty cycle = on time/100 milliseconds = $2 * 2.90 / 100 = 5.80 \%$
2. Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.73 \text{ dB}$
3. 3DH5 has the highest duty cycle and is reported.

3.8.7 Test Result of Radiated Band Edges

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	00	Relative Humidity :	43~44%
		Test Engineer :	Jack Li

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.04	52.87	-21.13	74	44.86	32.86	4.23	29.08	120	300	Peak
2387.04	28.14	-25.86	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2369.76	52.75	-21.25	74	44.8	32.83	4.22	29.1	100	250	Peak
2369.76	28.02	-25.98	54	-	-	-	-	-	-	Average

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.73dB) derived from $20\log(\text{dwell time}/100\text{ms})$.

For example: Average level = 52.87dBuV/m – 24.73 (dB) = 28.14dBuV/m.

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	78	Relative Humidity :	43~44%
		Test Engineer :	Jack Li

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	68.83	-5.17	74	60.53	33.01	4.29	29	102	52	Peak
2483.5	44.10	-9.90	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	64.94	-9.06	74	56.64	33.01	4.29	29	100	210	Peak
2483.5	40.21	-13.79	54	-	-	-	-	-	-	Average

3.8.8 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	00	Relative Humidity :	43~44%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	1. 2402 MHz is fundamental signal which can be ignored. 2. Test result of emissions which are 20 dB lower than the limit is not reported per15.31.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
162.611	25.31	-18.19	43.5	45.22	9.49	0.53	29.93	-	-	Peak
242.525	33.04	-12.96	46	50.55	11.66	0.66	29.83	-	-	Peak
261.058	31.36	-14.64	46	48.37	12.17	0.68	29.86	-	-	Peak
360.448	36.14	-9.86	46	50.49	14.75	0.82	29.92	120	0	Peak
554.825	30.14	-15.86	46	40.31	18.51	1	29.68	-	-	Peak
948.761	35.16	-10.84	46	42.64	20.73	1.33	29.54	-	-	Peak
2402	109.31	-	-	101.28	32.86	4.23	29.06	100	122	Peak
2402	84.58	-	-	-	-	-	-	-	-	Average

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.73dB) derived from $20\log(\text{dwell time}/100\text{ms})$.

For example: Average level = $109.31\text{dBuV/m} - 24.73(\text{dB}) = 84.58\text{dBuV/m}$.

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	00	Relative Humidity :	43~44%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	1. 2402 MHz is fundamental signal which can be ignored. 2. Test result of emissions which are 20 dB lower than the limit is not reported per15.31.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
102.719	25.8	-17.7	43.5	44.47	10.87	0.42	29.96	-	-	Peak
261.058	25.43	-20.57	46	42.44	12.17	0.68	29.86	-	-	Peak
360.448	29.29	-16.71	46	43.64	14.75	0.82	29.92	-	-	Peak
839.182	31.96	-14.04	46	39.94	20.4	1.27	29.65	-	-	Peak
916.069	32.06	-13.94	46	39.72	20.53	1.31	29.5	-	-	Peak
952.094	34.59	-11.41	46	42.06	20.74	1.33	29.54	110	250	Peak
2402	103.94	-	-	95.91	32.86	4.23	29.06	100	181	Peak
2402	79.21	-	-	-	-	-	-	-	-	Average

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	39	Relative Humidity :	43~44%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	1. 2441 MHz is fundamental signal which can be ignored. 2. Test result of emissions which are 20 dB lower than the limit is not reported per15.31.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
165.487	25.43	-18.07	43.5	45.45	9.36	0.54	29.92	-	-	Peak
245.09	32.3	-13.7	46	49.68	11.79	0.66	29.83	-	-	Peak
348.027	37.43	-8.57	46	52.09	14.46	0.82	29.94	100	0	Peak
360.448	36.91	-9.09	46	51.26	14.75	0.82	29.92	-	-	Peak
560.693	32.44	-13.56	46	42.58	18.52	1.01	29.67	-	-	Peak
952.094	35.69	-10.31	46	43.16	20.74	1.33	29.54	-	-	Peak
2441	109.14	-	-	100.97	32.95	4.25	29.03	100	125	Peak
2441	84.41	-	-	-	-	-	-	-	-	Average

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	39	Relative Humidity :	43~44%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	1. 2441 MHz is fundamental signal which can be ignored. 2. Test result of emissions which are 20 dB lower than the limit is not reported per15.31.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
103.08	24.13	-19.37	43.5	42.8	10.87	0.42	29.96	-	-	Peak
248.552	24.44	-21.56	46	41.69	11.92	0.67	29.84	-	-	Peak
354.183	32.41	-13.59	46	46.94	14.58	0.82	29.93	-	-	Peak
549.02	32.29	-13.71	46	42.49	18.48	1	29.68	-	-	Peak
839.182	28.35	-17.65	46	36.33	20.4	1.27	29.65	-	-	Peak
952.094	35.65	-10.35	46	43.12	20.74	1.33	29.54	120	300	Peak
2441	107.34	-	-	99.17	32.95	4.25	29.03	100	182	Peak
2441	82.61	-	-	-	-	-	-	-	-	Average

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	78	Relative Humidity :	43~44%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	1. 2480 MHz is fundamental signal which can be ignored. 2. Test result of emissions which are 20 dB lower than the limit is not reported per15.31.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
102.719	26.8	-16.7	43.5	45.47	10.87	0.42	29.96	-	-	Peak
165.487	31.44	-12.06	43.5	51.46	9.36	0.54	29.92	-	-	Peak
245.09	34.87	-11.13	46	52.25	11.79	0.66	29.83	-	-	Peak
356.676	38.79	-7.21	46	53.25	14.65	0.82	29.93	111	120	Peak
560.693	30.07	-15.93	46	40.21	18.52	1.01	29.67	-	-	Peak
952.094	37.67	-8.33	46	45.14	20.74	1.33	29.54	-	-	Peak
2480	106.11	-	-	97.81	33.01	4.29	29	100	122	Peak
2480	81.38	-	-	-	-	-	-	-	-	Average

Test Mode :	3Mbps	Temperature :	19~21°C
Test Channel :	78	Relative Humidity :	43~44%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	1. 2480 MHz is fundamental signal which can be ignored. 2. Test result of emissions which are 20 dB lower than the limit is not reported per15.31.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.481	23.68	-16.32	40	40.49	12.98	0.25	30.04	-	-	Peak
84.11	30.02	-9.98	40	52.14	7.53	0.37	30.02	-	-	Peak
102.001	25.53	-17.97	43.5	44.34	10.74	0.41	29.96	-	-	Peak
248.552	31.35	-14.65	46	48.6	11.92	0.67	29.84	-	-	Peak
348.027	33.95	-12.05	46	48.61	14.46	0.82	29.94	-	-	Peak
952.094	39.06	-6.94	46	46.53	20.74	1.33	29.54	110	250	Peak
2480	103.18	-	-	94.88	33.01	4.29	29	100	180	Peak
2480	78.45	-	-	-	-	-	-	-	-	Average

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

See list of measuring instruments of this test report.

3.9.3 Test Procedures


1. The test follows the guidelines in ANSI C63.4-2003 and ANSI C63.10-2009 test site requirement.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 KHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	19~20℃
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + Camera + USB Cable (Charging from Adapter)		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS
Condition: FCC PART15C LISN-111230 LINE
Project : (FR) 280827
mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	1.63	40.58	-15.42	56.00	30.00	-0.11	10.69	QP
2	1.63	32.18	-13.82	46.00	21.60	-0.11	10.69	Average
3	1.69	40.48	-15.52	56.00	29.90	-0.11	10.69	QP
4	1.69	32.08	-13.92	46.00	21.50	-0.11	10.69	Average
5	1.76	33.29	-12.71	46.00	22.71	-0.11	10.69	Average
6	1.76	41.29	-14.71	56.00	30.71	-0.11	10.69	QP
7	1.83	32.89	-13.11	46.00	22.30	-0.11	10.70	Average
8	1.83	41.89	-14.11	56.00	31.30	-0.11	10.70	QP
9	1.96	42.89	-13.11	56.00	32.30	-0.11	10.70	QP
10	1.96	34.29	-11.71	46.00	23.70	-0.11	10.70	Average
11	2.05	33.99	-12.01	46.00	23.40	-0.11	10.70	Average
12	2.05	42.49	-13.51	56.00	31.90	-0.11	10.70	QP
13	2.17	42.60	-13.40	56.00	32.00	-0.11	10.71	QP
14	2.17	34.40	-11.60	46.00	23.80	-0.11	10.71	Average
15	2.25	42.50	-13.50	56.00	31.90	-0.11	10.71	QP
16	2.25	34.60	-11.40	46.00	24.00	-0.11	10.71	Average
17	2.37	32.51	-13.49	46.00	21.90	-0.11	10.72	Average
18	2.37	41.11	-14.89	56.00	30.50	-0.11	10.72	QP
19	2.46	33.11	-12.89	46.00	22.49	-0.11	10.73	Average
20	2.46	41.11	-14.89	56.00	30.49	-0.11	10.73	QP
21	2.55	32.02	-13.98	46.00	21.40	-0.11	10.73	Average
22	2.55	40.22	-15.78	56.00	29.60	-0.11	10.73	QP
23	2.64	31.83	-14.17	46.00	21.20	-0.11	10.74	Average
24	2.64	40.33	-15.67	56.00	29.70	-0.11	10.74	QP
25	2.75	38.74	-17.26	56.00	28.11	-0.12	10.75	QP
26	2.75	30.84	-15.16	46.00	20.21	-0.12	10.75	Average




Test Mode :	Mode 1	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + Camera + USB Cable (Charging from Adapter)		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
Condition: FCC PART15C LISN-111230 NEUTRAL
Project : (FR) 280827
mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.37	40.43	-18.04	58.47	29.90	-0.08	10.61	QP
2	0.37	37.93	-10.54	48.47	27.40	-0.08	10.61	Average
3	1.58	33.38	-12.62	46.00	22.79	-0.10	10.69	Average
4	1.58	40.68	-15.32	56.00	30.09	-0.10	10.69	QP
5	1.70	39.79	-16.21	56.00	29.21	-0.11	10.69	QP
6	1.70	34.09	-11.91	46.00	23.51	-0.11	10.69	Average
7	1.76	41.59	-14.41	56.00	31.01	-0.11	10.69	QP
8	1.76	34.19	-11.81	46.00	23.61	-0.11	10.69	Average
9	1.87	35.29	-10.71	46.00	24.70	-0.11	10.70	Average
10	1.87	41.39	-14.61	56.00	30.80	-0.11	10.70	QP
11	2.01	44.09	-11.91	56.00	33.50	-0.11	10.70	QP
12	2.01	36.59	-9.41	46.00	26.00	-0.11	10.70	Average
13	2.09	43.29	-12.71	56.00	32.70	-0.11	10.70	QP
14	2.09	35.79	-10.21	46.00	25.20	-0.11	10.70	Average
15	2.16	42.70	-13.30	56.00	32.10	-0.11	10.71	QP
16	2.16	35.40	-10.60	46.00	24.80	-0.11	10.71	Average
17	2.24	42.60	-13.40	56.00	32.00	-0.11	10.71	QP
18	2.24	35.20	-10.80	46.00	24.60	-0.11	10.71	Average
19	2.32	42.91	-13.09	56.00	32.30	-0.11	10.72	QP
20	2.32	35.41	-10.59	46.00	24.80	-0.11	10.72	Average
21	2.40	41.41	-14.59	56.00	30.80	-0.11	10.72	QP
22	2.40	34.41	-11.59	46.00	23.80	-0.11	10.72	Average
23	2.50	39.62	-16.38	56.00	29.00	-0.11	10.73	QP
24	2.50	32.62	-13.38	46.00	22.00	-0.11	10.73	Average
25	2.62	39.63	-16.37	56.00	29.00	-0.11	10.74	QP
26	2.62	32.93	-13.07	46.00	22.30	-0.11	10.74	Average
27	2.71	31.53	-14.47	46.00	20.89	-0.11	10.75	Average

Test Mode :	Mode 1	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + Camera + USB Cable (Charging from Adapter)		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
 Condition: FCC PART15C LISN-111230 NEUTRAL
 Project : (FR) 280827
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
28	2.71	39.53	-16.47	56.00	28.89	-0.11	10.75	QP
29	2.78	31.24	-14.76	46.00	20.60	-0.12	10.76	Average
30	2.78	38.34	-17.66	56.00	27.70	-0.12	10.76	QP
31	2.99	30.57	-15.43	46.00	19.91	-0.12	10.78	Average
32	2.99	38.17	-17.83	56.00	27.51	-0.12	10.78	QP



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

Non-standard connector used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Sep. 12, 2012 ~ Sep. 28, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY45101555	N/A	Aug. 22, 2012	Sep. 12, 2012 ~ Sep. 28, 2012	Aug. 21, 2013	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY44421198	N/A	Aug. 22, 2012	Sep. 12, 2012 ~ Sep. 28, 2012	Aug. 21, 2013	Conducted (TH01-KS)
DC Power Supply	GW INSTRON	GPS-3030D	E1884515	N/A	Aug. 22, 2012	Sep. 12, 2012 ~ Sep. 28, 2012	Aug. 21, 2013	Conducted (TH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 17, 2012	Sep. 12, 2012 ~ Sep. 28, 2012	Aug. 16, 2013	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 01, 2012	Sep. 12, 2012	May 31, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	060103	9kHz~30MHz	Dec. 30, 2011	Sep. 12, 2012	Dec. 29, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 30, 2011	Sep. 12, 2012	Dec. 29, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	N/A	Nov. 16, 2011	Sep. 12, 2012	Nov. 15, 2012	Conduction (CO01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 20, 2011	Sep. 12, 2012	Sep. 19, 2012	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Sep. 07, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Sep. 07, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Sep. 07, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Sep. 07, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060029	9KHz~2GHz	Jan. 06, 2012	Sep. 07, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 30, 2011	Sep. 07, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Sep. 07, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 07, 2011	Sep. 07, 2012	Nov. 06, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 11, 2011	Sep. 07, 2012	Oct. 10, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9KHz ~ 30MHz	Jul. 03, 2012	Sep. 07, 2012	Jul. 02, 2014	Radiation (03CH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 17, 2012	Sep. 07, 2012	Aug. 16, 2013	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54
--	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72
--	------