

**MOTOROLA****Portable Cellular Phone SAR Test Report**

Tests Requested By: Motorola Mobility, LLC
600 N. US Highway 45
Libertyville, IL 60048

Test Report #: 25360-1F Rev. B
Date of Report: 02-May-2013
Date of Test: 21-Mar-2013 to 30-Apr-2013
FCC ID #: IHDT56PB1
IC ID #: N/A
Generic Name: M0DA0

Test Laboratory: Motorola Mobility, LLC - ADR Test Services Laboratory
600 N. US Highway 45
Libertyville, IL 60048

Report Author: Thomas Knipple
Senior Staff Test Engineer

This laboratory is accredited to ISO/IEC 17025-2005 to perform the following tests:

Accreditation:Tests:

Electromagnetic Specific Absorption Rate

Procedures:

IEC 62209-1

RSS-102

IEEE 1528 - 2003

FCC OET Bulletin 65 (*including Supplement C*)

Australian Communications Authority Radio

Communications (Electromagnetic Radiation –
Human Exposure) Standard 2003

CENELEC EN 50360

ARIB Std. T-56 (2002)

On the following products or types of products:

Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

**Statement of
Compliance:**

Motorola declares under its sole responsibility that the portable cellular telephone model to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093) as well as with CENELEC en50360:2001 and ANSI / IEEE C95.1. It also declares that the product was tested in accordance with IEEE 1528 / CENELEC EN62209-1 (2006), along with other published guidance indicated in the references at the end of this report, as well as other appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola Mobility, LLC 2013

This test report shall not be reproduced except in full, without written approval of the laboratory. The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report. Motorola encourages all feedback, both positive and negative, on this test report.

Table of Contents

1	Introduction.....	3
2	Details of the Device Under Test.....	4
2.1	Sample Information.....	4
2.2	Antenna Description.....	4
2.3	Transmission Band Summary	5
2.4	Device Test Setup, Operating Configurations, and Conducted Power Measurements.....	6
2.4.1	LTE.....	6
2.4.2	CDMA	11
2.4.3	GSM.....	12
2.4.4	WCDMA	14
2.4.5	Wi-Fi 802.11	16
2.4.6	Bluetooth	21
2.4.7	Near-Field Communications.....	22
2.5	Transmitter power reduction conditions and modes	23
2.6	Accessories for the Device Under Test	25
2.6.1	Batteries	25
2.6.2	Body-Worn Carry Accessories	25
3	Test Equipment Used.....	26
3.1	Dosimetric Measurement System.....	26
3.2	Additional Equipment	27
3.3	Test System Validations.....	28
3.4	Test System Verifications (System Performance Checks).....	30
3.5	Simulated Tissue Dielectric Properties	32
4	Test Setup Information, SAR Measurement Results, and Analysis.....	35
4.1	Overview of Test Setup and Results	35
4.2	Head-Adjacent Exposure Results.....	36
4.3	Body-Worn Accessory Exposure Results	40
4.4	Mobile Hotspot Exposure Results.....	41
4.5	Measurement Variability Analysis.....	46
4.6	Description and Evaluation of Simultaneous Transmitters	47
5	References to Test Standards and Guidance	62

Appendix 1: SAR Distribution Plots for Test System Verification

Appendix 2: SAR Distribution Plots for Head-Adjacent Test Results

Appendix 3: SAR Distribution Plots for Body-Worn Accessory Test Results

Appendix 4: SAR Distribution Plots for Mobile Hotspot Test Results

Appendix 5: Measurement Uncertainty Budget

Appendix 6: Probe Calibration Certificates

Appendix 7: Dipole Characterization Certificates

Revision History

Revision Version	Date	Notes
Rev. 0	02-May-2013	Initial report release
Rev. A	9-May-2013	Updates for TCB inquiry
Rev. B	16-May-2013	Updates for EVDO against the head for VoIP capabilities and other TCB inquiries

1 Introduction

The Motorola Mobility ADR Test Services Laboratory has performed measurements of the maximum potential exposure to the user of the portable cellular phone covered by this test report. The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with [1], [4], [5], [9], and per FCC KDB 941225 D06 for mobile hotspot operation. The SAR values measured for the portable cellular phone are below the maximum recommended levels of 1.6 W/kg in a 1 g average set in [3] and 2.0 W/kg in a 10 g average set in [2].

For ANSI / IEEE C95.1 (1 g), the final stand-alone SAR readings for this phone are given in the table below. These measurements were performed using a DASY52™ system manufactured by Schmid & Partner Engineering AG (SPEAG), of Zurich Switzerland.

Transmit Band	Head SAR (1 g ^W /kg)	Body-Worn Accessory SAR (1 g ^W /kg)	Mobile Hotspot SAR (1 g ^W /kg)
LTE Band 4	0.77	0.40	0.92
LTE Band 13	0.45	0.19	0.55
CDMA 800	0.68	0.50	0.44
CDMA 1900	1.39	0.33	0.73
GSM 850	0.24	0.13	0.46
GSM 1900	0.71	0.14	0.68
WCDMA 850	0.29	0.11	0.71
WCDMA 1900	1.33	0.31	1.39
Wi-Fi 2.45 GHz	0.92	0.05	0.24
Wi-Fi 5.2 GHz	0.40	0.19	N/A
Wi-Fi 5.8 GHz	0.21	0.08	0.05
Bluetooth	No Testing Required		
Simultaneous SAR	1.57		

2 Details of the Device Under Test

2.1 Sample Information

Serial Number(s) (Functional Use)	LXVE110043 (LTE Band 4/13 conducted power measurements, LTE 4/13 SAR testing) LXVE110035 (CDMA conducted power measurements, CDMA SAR testing) LXVE110025 (GSM/WCDMA conducted power measurements, GSM/WCDMA SAR testing) LXVE110019 (Wi-Fi SAR testing) LXVE110010 (2.4 GHz Wi-Fi conducted power measurements, Bluetooth conducted power measurements) LXAA1W0004 (5 GHz Wi-Fi conducted power measurements)
Production Unit or Identical Prototype (47 CFR §2.908)	Identical Prototype
Device Category	Portable (Mobile Station Class B)
RF Exposure Limits	General Population / Uncontrolled

2.2 Antenna Description

Main (835/1880 MHz) Antenna


Type	Internal	
Location	Bottom Edge of Transceiver	
Dimensions	Width	7.2 mm
	Length	42 mm

LTE (780/1730 MHz) Antenna

Type	Internal	
Location	Bottom-Left Edge of Transceiver	
Dimensions	Width	18 mm
	Length	29.2 mm

Wi-Fi/Bluetooth Antenna

Type	Internal	
Location	Left Edge of Transceiver	
Dimensions	Width	25.2 mm
	Length	6 mm



2.3 Transmission Band Summary

Mode(s) of Operation	Modulation Mode(s)	Target Output Power Setting	Maximum Output Power Setting	Duty Cycle	Transmitting Frequency Range(s)
LTE Band 4	QPSK, 16QAM	23.0 dBm	24.0 dBm	1:1	1710.0 - 1755.0 MHz
LTE Band 13	QPSK, 16QAM	23.0 dBm	24.0 dBm	1:1	777.0 - 787.0 MHz
CDMA 800	QPSK	24.0 dBm	25.0 dBm	1:1	824.70 - 848.31 MHz
CDMA 1900	QPSK	24.0 dBm	25.0 dBm	1:1	1851.20 - 1908.75 MHz
GSM 850	GMSK	32.5 dBm	33.5 dBm	1:8.3	824.2 - 848.8 MHz
GPRS/EDGE 850	GMSK	32.5 dBm	33.5 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	824.2 - 848.8 MHz
EDGE 850	8PSK	26.0 dBm	28.0 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	824.2 - 848.8 MHz
GSM 900	GMSK	32.5 dBm	33.5 dBm	1:8.3	880.2 - 914.8 MHz
GPRS/EDGE 900	GMSK	32.5 dBm	33.5 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	880.2 - 914.8 MHz
EDGE 900	8PSK	26.0 dBm	28.0 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	880.2 - 914.8 MHz
GSM 1800	GMSK	29.5 dBm	30.5 dBm	1:8.3	1710.2 - 1784.8 MHz
GPRS/EDGE 1800	GMSK	29.5 dBm	30.5 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	1710.2 - 1784.8 MHz
EDGE 1800	8PSK	25.0 dBm	27.0 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	1710.2 - 1784.8 MHz
GSM 1900	GMSK	29.5 dBm	30.5 dBm	1:8.3	1850.2 - 1909.8 MHz
GPRS/EDGE 1900	GMSK	29.5 dBm	30.5 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	1850.2 - 1909.8 MHz
EDGE 1900	8PSK	25.0 dBm	27.0 dBm	1:8.3, 2:8.3, 3:8.3, 4:8.3	1850.2 - 1909.8 MHz
WCDMA 850	QPSK	22.9 dBm	24.0 dBm	1:1	826.4 - 846.6 MHz
WCDMA 900	QPSK	22.9 dBm	24.0 dBm	1:1	882.4 - 912.6 MHz
WCDMA 1900	QPSK	22.9 dBm	24.0 dBm	1:1	1852.4 - 1907.6 MHz
WCDMA 2100	QPSK	22.9 dBm	24.0 dBm	1:1	1922.4 - 1977.6 MHz
Wi-Fi 802.11b/g/n	BPSK	19.18 dBm		1:1	2412.0 - 2462.0 MHz
Wi-Fi 802.11a/n/ac	BPSK	15.60 dBm		1:1	5180.0 - 5240.0 MHz
Wi-Fi 802.11a/n/ac	BPSK	20.13 dBm		1:1	5745.0 - 5825.0 MHz
Bluetooth	GFSK	10.3 dBm		1:1	2402.0 - 2480.0 MHz

2.4 Device Test Setup, Operating Configurations, and Conducted Power Measurements

2.4.1 LTE

Technical Description

LTE Summary Information

FCC ID			IHDT56PB1
Form Factor			Portable Handset
Frequency Range(s)			See Section 2.3
Channel Bandwidth(s)			Band 4: 20, 15, 10, 5, 3, 1.4 MHz Band 13: 10, 5 MHz
Low, Middle, High Channel Numbers and Frequencies			
Low	Mid	High	Band: Channel Bandwidth
--	20175 (1732.5 MHz)	--	Band 4: 20 MHz
20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)	Band 4: 15 MHz
20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)	Band 4: 10 MHz
19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)	Band 4: 5 MHz
19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)	Band 4: 3 MHz
19956 (1710.6 MHz)	20175 (1732.5 MHz)	20394 (1754.4 MHz)	Band 4: 1.4 MHz
--	23230 (782.0 MHz)	--	Band 13: 10 MHz
--	23230 (782.0 MHz)	--	Band 13: 5 MHz
UE Category			3
Modulations Supported			QPSK, 16QAM
Description of LTE Tx and Antenna Implementation			Band 4: 1 TX/RX Antenna, 1 RX Antenna Band 13: 1 TX/RX Antenna, 1 RX Antenna
LTE Voice Available?			Yes (VoIP clients Only)
Hotspot with LTE + Wi-Fi?			Yes
Hotspot with LTE + Wi-Fi active with Voice sessions?			Yes (SVLTE with CDMA only)
LTE MPR Permanently Implemented per 3GPP TS 36.101?			Yes
A-MPR disabled for SAR Testing?			Yes
Conducted power table providing measurements across 1 RB, 50% RB and 100% RB allocations?			Yes
Table provided specifying other US wireless operating modes?			Yes
Table provided specifying maximum average conducted power for these other wireless modes?			Yes
Table provided identifying simultaneous transmission conditions?			Yes
Power Reduction used for SAR compliance?			Yes
Power Reduction used for LTE?			Yes
Power Reduction used for CDMA?			Yes
Power Reduction used for GSM/WCDMA?			No
Power Reduction used for SVLTE?			Yes
Test Equipment used			CMW500 SW version 2.1.28.9

LTE Maximum Power Reduction (MPR) conditions are defined in 3GPP 36-521, section 6.2.3.3:

6.2.3.3 Minimum conformance requirements

For UE Power Class 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2.3-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3.3-1.

Table 6.2.3.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth configuration [RB]						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For the UE maximum output power modified by MPR, the power limits specified in subclause 6.2.5.3 apply. The normative reference for this requirement is TS 36.101 clause 6.2.3.

For the device's architecture, MPR is permanently implemented. Per the chart above, the following MPR is used:

Modulation	1.4 MHz		3 MHz		5 MHz		10 MHz		15 MHz		20 MHz	
	# of RBs	MPR (dB)	# of RBs	MPR (dB)	# of RBs	MPR (dB)	# of RBs	MPR (dB)	# of RBs	MPR (dB)	# of RBs	MPR (dB)
QPSK	> 5	1	> 4	1	> 8	1	> 12	1	> 16	1	> 18	1
16 QAM	≤ 5	1	≤ 4	1	≤ 8	1	≤ 12	1	≤ 16	1	≤ 18	1
16 QAM	> 5	2	> 4	2	> 8	2	> 12	2	> 16	2	> 18	2

The table applies for any RB start value. RBs are assigned contiguously. Thus, given the maximum power limits stated in 2.2 and the MPR described above, the maximum power for the SAR test cases in channel bandwidths greater than 1.4 MHz is as follows:

Test Case	Band 4	Band 17
	Max Power (dBm)	Max Power (dBm)
QPSK, 1 RB Allocation	24.0	24.0
QPSK, 50% RB Allocation	23.0	23.0
QPSK, 100% RB Allocation	23.0	23.0
16QAM, 1 RB Allocation	23.0	23.0
16QAM, 50% RB Allocation	22.0	22.0
16QAM, 100% RB Allocation	22.0	22.0

The maximum power for the SAR test cases in a 1.4 MHz channel bandwidth is as follows:

Test Case	Band 4
	Max Power (dBm)
QPSK, 1 RB Allocation	24.0
QPSK, 50% RB Allocation	24.0
QPSK, 100% RB Allocation	23.0
16QAM, 1 RB Allocation	23.0
16QAM, 50% RB Allocation	23.0
16QAM, 100% RB Allocation	22.0

Exposure Conditions and Test Exclusions

Mode	Type	Head-Adjacent	Body-Worn Accessory	Mobile Hotspot
All Modes, QPSK modulation	Data	Tested (1)	Tested (1)	Tested
All Modes, 16QAM modulation	Data	Excluded (2)	Excluded (2)	Excluded (2)

Notes:

- (1) QPSK modulation, as a data-only mode, was tested against the Head and in Body-Worn Accessory exposure conditions to support evaluation for SVLTE and VOIP applications potentially installed and used by the end-user.
- (2) 16QAM modulation was excluded from testing per FCC KDB 941225 D05, as the maximum output power in this mode is not more than ½ dB higher than each comparable mode in QPSK and the reported SAR results for QPSK mode testing were less than 1.45 ^W/kg.

Device Test Setup

For LTE modes, the test sample was operated using transmission to a base station simulator. The base station simulator was configured per the guidance provided in FCC KDB 941225 D05, with closed-loop power control enforced to ensure the phone transmits at maximum output power.

Conducted Power Measurements**LTE Band 4**

LTE Band 4 (20 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation			QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM
Start RB			0	50	99	0	25	50	0	0	50	99	0	25	50	0
RB Allocation			1	1	1	50	50	50	100	1	1	1	50	50	50	100
Max Limit (dBm)			24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00
MPR Target (dB)			0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2
Max Limit with MPR (dBm)			24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00
Channel BW	Frequency (MHz)	Channel														
20 MHz	1732.5	20175	24.15	24.12	24.15	23.23	23.14	23.12	23.12	23.28	23.24	23.35	22.22	22.12	22.20	22.18

LTE Band 4 (15 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation		QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM	
Start RB		0	37	74	0	19	39	0	0	37	74	0	19	39	0	
RB Allocation		1	1	1	36	36	36	75	1	1	1	36	36	36	75	
Max Limit (dBm)		24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	
MPR Target (dB)		0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2	
Max Limit with MPR (dBm)		24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00	
Channel BW	Frequency (MHz)	Channel														
15 MHz	1717.5	20025	23.26	24.18	24.17	23.16	23.13	23.14	23.04	23.41	23.36	23.33	22.23	22.16	22.22	22.12
15 MHz	1732.5	20175	24.06	24.08	24.13	23.22	23.12	23.16	23.14	23.80	23.24	23.36	22.29	22.15	22.22	22.16
15 MHz	1747.5	20325	24.07	23.96	23.91	23.01	23.06	22.97	23.00	22.15	23.17	23.08	22.14	22.08	22.01	22.13

LTE Band 4 (10 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation		QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM		
Start RB		0	25	49	0	12	25	0	0	25	49	0	12	25	0	
RB Allocation		1	1	1	25	25	25	50	1	1	1	25	25	25	50	
Max Limit (dBm)		24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	
MPR Target (dB)		0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2	
Max Limit with MPR (dBm)		24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00	
Channel BW	Frequency (MHz)	Channel														
10 MHz	1715.0	20000	23.11	24.11	24.08	23.04	23.13	23.12	23.07	22.21	23.25	23.29	22.17	22.18	22.14	22.10
10 MHz	1732.5	20175	23.17	24.06	24.11	23.21	23.08	23.10	23.08	23.44	23.22	23.33	22.25	22.14	22.21	22.12
10 MHz	1750.0	20350	23.01	23.94	23.94	22.99	22.94	22.92	22.90	23.13	23.09	23.11	22.00	22.07	22.03	21.93

LTE Band 4 (5 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation		QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM	
Start RB		0	12	24	0	6	13	0	0	12	24	0	6	13	0	
RB Allocation		1	1	1	12	12	12	25	1	1	1	12	12	12	25	
Max Limit (dBm)		24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	
MPR Target (dB)		0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2	
Max Limit with MPR (dBm)		24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00	
Channel BW	Frequency (MHz)	Channel														
5 MHz	1712.5	19975	23.15	24.10	24.06	23.14	23.14	23.16	23.09	22.27	23.32	23.25	22.18	22.17	22.22	22.22
5 MHz	1732.5	20175	24.22	24.10	24.10	23.24	23.12	23.11	23.17	22.34	23.25	23.25	22.33	22.22	22.21	22.11
5 MHz	1752.5	20375	24.04	23.96	23.84	23.05	22.92	23.04	22.95	23.28	23.15	23.29	22.07	22.05	22.08	21.99

LTE Band 4 (3 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation		QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM	
Start RB		0	7	14	0	3	7	0	0	7	14	0	3	7	0	
RB Allocation		1	1	1	8	8	8	15	1	1	1	8	8	8	15	
Max Limit (dBm)		24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	
MPR Target (dB)		0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2	
Max Limit with MPR (dBm)		24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00	
Channel BW	Frequency (MHz)	Channel														
3 MHz	1711.5	19965	23.22	24.15	24.16	23.31	23.21	23.22	23.20	22.12	23.32	23.30	22.18	22.16	22.18	22.22
3 MHz	1732.5	20175	23.29	24.12	24.14	23.28	23.19	23.16	23.12	22.12	23.28	23.33	22.16	22.13	22.09	22.26
3 MHz	1753.5	20385	23.14	24.04	23.98	23.03	23.06	23.07	23.11	22.06	23.30	23.19	22.04	22.11	22.00	22.17

LTE Band 4 (1.4 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation		QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM		
Start RB		0	3	5	0	1	3	0	0	3	5	0	1	3	0	
RB Allocation		1	1	1	3	3	3	6	1	1	1	3	3	3	6	
Max Limit (dBm)		24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	
MPR Target (dB)		0	0	0	0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	
Max Limit with MPR (dBm)		24.00	24.00	24.00	24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	
Channel BW	Frequency (MHz)	Channel														
1.4 MHz	1710.6	19956	24.20	24.06	24.10	24.20	24.08	24.05	23.29	22.60	22.61	22.65	23.00	23.00	23.00	22.00
1.4 MHz	1732.5	20175	24.23	24.10	24.16	24.14	24.05	24.07	23.14	23.35	23.33	23.20	23.15	22.98	23.00	21.95
1.4 MHz	1754.4	20394	24.16	24.09	23.99	23.99	24.07	23.20	22.92	22.70	22.80	22.75	23.00	22.95	23.00	22.00

LTE Band 13

LTE Band 13 (10 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation			QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM	
Start RB			0	25	49	0	12	25	0	0	25	49	0	12	25	0
RB Allocation			1	1	1	25	25	25	50	1	1	1	25	25	25	50
Max Limit (dBm)			24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00
MPR Target (dB)			0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2
Max Limit with MPR (dBm)			24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00
Channel BW	Frequency (MHz)	Channel														
10 MHz	782.0	23230	24.27	24.31	24.38	23.31	23.28	23.27	23.23	23.44	23.46	23.51	22.26	22.29	22.31	22.21

LTE Band 13 (5 MHz Channel Bandwidth) - Measured Conducted Power (dBm)																
Modulation			QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	16QAM	16QAM	16QAM	16QAM	16QAM	16QAM
Start RB			0	12	24	0	6	13	0	0	12	24	0	6	13	0
RB Allocation			1	1	1	12	12	12	25	1	1	1	12	12	12	25
Max Limit (dBm)			24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00	24.00
MPR Target (dB)			0	0	0	-1	-1	-1	-1	-1	-1	-1	-2	-2	-2	-2
Max Limit with MPR (dBm)			24.00	24.00	24.00	23.00	23.00	23.00	23.00	23.00	23.00	23.00	22.00	22.00	22.00	22.00
Channel BW	Frequency (MHz)	Channel														
5 MHz	782.0	23230	24.29	24.27	24.30	23.28	23.32	23.35	23.35	22.80	22.80	22.81	22.19	22.23	22.22	22.32

2.4.2 CDMA

Technical Description

The phone under test contains CDMA2000 1x and CDMA2000 1xEV-DO (Rel. A) transmitters that support both voice (circuit-switched) and data (packet-switched) capabilities.

Exposure Conditions and Test Exclusions

Mode	Type	Head-Adjacent	Body-Worn Accessory	Mobile Hotspot
RC3 SO55 Loopback	Voice	Tested (1)	Excluded (2)	N/A
RC1 SO55 Loopback	Voice	Excluded (2)	Excluded (2)	N/A
TDSO SO32 FCH	Data	Excluded (2)	Tested (1)	Excluded (2)
TDSO SO32 FCH+SCH	Data	Excluded (2)	Excluded (2)	Excluded (2)
EVDO Rel. 0 (RTAP)	Data	Tested (3)	Excluded (2)	Tested (1)
EVDO Rel. A (RETAP)	Data	Excluded (2)	Excluded (2)	Excluded (2)

Notes:

- (1) Per FCC KDB 941225 D01, RC3 SO55 is tested as the default mode for Head SAR measurements, TDSO SO32 on FCH with other code channels disabled is tested as the default mode for Body SAR measurements, and EVDO Rel. 0 (RTAP) is tested as the default mode in the Mobile Hotspot SAR exposure condition as a EVDO Data Device.
- (2) Per FCC KDB 941225 D01, the noted modes were excluded from testing as each exhibited measured output power not higher than that found in the default modes for each exposure condition.
- (3) EV-DO Rev. O (RTAP), as a data-only mode, was tested against the Head to support evaluation for VOIP applications potentially installed and used by the end-user.

Device Test Setup

For CDMA modes, the test sample was operated using transmission to a base station simulator. The base station simulator was set up for the proper channel and transmit mode of operation on the phone's uplink. The transmitter power level and power control were set to "All Up Bits".

Conducted Power Measurements

Power measurements were executed per FCC KDB 941225 D01:

Measured Conducted Power (dBm) for CDMA modes							
		Loopback		Data		EVDO Rel. 0	EVDO Rel. A
Band	Channel	RC3 SO55	RC1 SO55	TDSO SO32 FCH	TDSO SO32 FCH+SCH	RTAP 153.6k	Subtype 2 RETAP
CDMA 800	1013	24.91	24.95	24.86	24.82	24.64	24.61
	384	24.87	24.90	24.80	24.78	24.59	24.54
	777	24.90	24.92	24.84	24.82	24.40	24.36
CDMA 1900	25	24.97	24.93	24.92	24.93	24.78	24.77
	600	24.94	24.92	24.91	24.91	24.94	24.94
	1175	24.88	24.87	24.85	24.83	24.75	24.74

Note that the device's system architecture does not support simultaneous voice and data during a single CDMA session to the cellular network. Operation in TDSO and EVDO modes is for data transmission only.

2.4.3 GSM

Technical Description

The phone under test contains a GSM transmitter that supports voice (circuit-switched) capability, and data (packet-switched) capabilities over GPRS/EDGE (GMSK) or EDGE (8PSK).

Exposure Conditions and Test Exclusions

Mode	Type	Head-Adjacent	Body-Worn Accessory	Mobile Hotspot
GSM (GMSK 1-Slot)	Voice	Tested	Tested	N/A
GPRS/EDGE (GMSK Multi-Slot)	Data	Tested (1) (3)	Tested (1) (3)	Tested (3)
EDGE (8PSK Multi-Slot)	Data	Excluded (2) (3)	Excluded (2) (3)	Excluded (2) (3)

Notes:

- (1) GPRS/EDGE (GMSK Multi-Slot), as a data-only mode, was tested against the Head and in Body-Worn Accessory exposure conditions to support evaluation for 3rd Party VOIP applications potentially installed and used by the end-user.
- (2) EDGE (8PSK Multi-Slot) was excluded from testing per FCC KDB 941225 D03, as the source-based time-averaged output power in this mode is lower than that measured in normal GSM voice mode and GPRS/EDGE (GMSK Multi-Slot) data modes.
- (3) GPRS/EDGE (GMSK Multi-Slot) and EDGE (8PSK Multi-Slot) utilize reduced output power as additional time slots are transmitted in the uplink frame, as demonstrated in the following table. The values noted are maximum limits, and conform to the same power tune-up tolerances noted in section 2.3 above. The multi-slot configuration that results in the highest source-based time-averaged output power from the device was chosen for testing when testing of these modes is required.

GSM Data Functionality	GPRS/EDGE Class 12 (4 uplink timeslots; 4 downlink timeslots; 5 total timeslots per frame)							
	Class B (DTM not supported)							
Mode(s) of Operation	GPRS/EDGE 850				GPRS/EDGE 1900			
Modulation	GMSK				GMSK			
Maximum TX Burst Output Power Setting (dBm)	33.5	31.0	28.75	28.0	30.5	28.0	25.75	25.0
Maximum Time Average Output Power Setting (dBm)	24.3	24.8	24.3	24.8	21.3	21.8	21.3	21.8
Duty Cycle	1:8.3	2:8.3	3:8.3	4:8.3	1:8.3	2:8.3	3:8.3	4:8.3
Transmitting Frequency Range(s)	824.2 - 848.8 MHz				1850.2 - 1909.8 MHz			
Mode(s) of Operation	EDGE 850				EDGE 1900			
Modulation	8PSK				8PSK			
Maximum TX Burst Output Power Setting (dBm)	28.0	25.5	24.0	22.5	27.0	24.5	22.75	21.5
Maximum Time Average Output Power Setting (dBm)	18.8	19.3	19.6	19.3	17.8	18.3	18.3	18.3
Duty Cycle	1:8.3	2:8.3	3:8.3	4:8.3	1:8.3	2:8.3	3:8.3	4:8.3
Transmitting Frequency Range(s)	824.2 - 848.8 MHz				1850.2 - 1909.8 MHz			

Device Test Setup

For GSM modes, the test sample was operated using transmission to a base station simulator. The base station simulator was set up for the proper channel and transmit mode of operation on the phone's uplink. The transmitter power level and power control were set to maximum at power step 5 for GSM 850 band, and power step 0 for GSM 1900 band.

Conducted Power Measurements

Band	Channel	Conducted power (dBm) for GSM modes (Burst Average Power)								
		GSM CS Voice (1 Slot)	GPRS PS Data (1 Slot)	GPRS PS Data (2 Slots)	GPRS PS Data (3 Slots)	GPRS PS Data (4 Slots)	EDGE PS Data (1 Slot)	EDGE PS Data (2 Slots)	EDGE PS Data (3 Slots)	EDGE PS Data (4 Slots)
GSM 850	128	32.44	32.21	28.87	27.60	26.12	26.62	23.79	21.98	20.68
	190	32.86	32.65	29.11	27.64	26.02	26.73	23.92	22.20	20.92
	251	32.73	32.54	28.93	27.47	26.24	26.64	23.89	22.17	20.90
GSM 1900	512	29.59	29.74	26.31	24.65	23.27	25.80	23.05	21.36	20.07
	661	29.63	29.77	26.32	24.64	23.18	25.66	23.01	21.45	20.44
	810	29.38	29.51	26.34	24.56	23.14	25.69	22.95	21.38	20.11

Band	Channel	Conducted power (dBm) for GSM modes (Source-Based Time-Averaged Power)								
		GSM CS Voice (1 Slot)	GPRS PS Data (1 Slot)	GPRS PS Data (2 Slots)	GPRS PS Data (3 Slots)	GPRS PS Data (4 Slots)	EDGE PS Data (1 Slot)	EDGE PS Data (2 Slots)	EDGE PS Data (3 Slots)	EDGE PS Data (4 Slots)
GSM 850	128	23.25	23.02	22.69	23.18	22.95	17.43	17.61	17.56	17.51
	190	23.67	23.46	22.93	23.22	22.85	17.54	17.74	17.78	17.75
	251	23.54	23.35	22.75	23.05	23.07	17.45	17.71	17.75	17.73
GSM 1900	512	20.40	20.55	20.13	20.23	20.10	16.61	16.87	16.94	16.90
	661	20.44	20.58	20.14	20.22	20.01	16.47	16.83	17.03	17.27
	810	20.19	20.32	20.16	20.14	19.97	16.50	16.77	16.96	16.94

Burst Average Power was measured using a power meter set to the appropriate profile to capture average power in the transmitting timeslot(s). Source-Based Time-Averaged Power, being related to the Burst Average Power by a fixed factor dependent on the number of time slots active in the frame, was calculated as follows (in dB), where x is the number of time slots active:

$$P_{Source} = P_{Burst} - 10 * \log \left(\frac{x}{8.3} \right)$$

CS Voice denotes circuit-switched transmission for voice call operation, and PS Data denotes packet-switched transmission for data sessions.

2.4.4 WCDMA

Technical Description

The phone under test contains a WCDMA transmitter designed per 3GPP TS 25.101, that supports both voice and data capabilities.

Exposure Conditions and Test Exclusions

Mode	Type	Head-Adjacent	Body-Worn Accessory	Mobile Hotspot
RMC	Voice/ Data	Tested	Tested	Tested
AMR	Voice/ Data	Excluded (1)	Excluded (1)	Excluded (1)
HSDPA (Rel 5) Modes	Data	Excluded (1)	Excluded (1)	Excluded (1)
HSPA (Rel 6) Modes	Data	Excluded (1)	Excluded (1)	Excluded (1)

Notes:

(1) AMR, HSDPA (Rel. 5), and HSPA (Rel. 6) were excluded from testing per FCC KDB 941225 D01, as the measured output power in these modes is not more than ¼ dB higher than that measured in RMC.

Device Test Setup

For WCDMA modes, the test sample was operated using transmission to a base station simulator. The base station simulator was set up for the proper channel and transmit mode of operation on the phone's uplink. The transmitter power level and transmit power control were set to "All 1's" for RMC and AMR modes in WCDMA or HSDPA, or inner loop power control procedures were applied to maintain maximum output power while HSUPA was active.

Conducted Power Measurements

Power measurements were executed per FCC KDB 941225 D01:

Band	Channel	Conducted power (dBm) for WCDMA modes		Conducted Power (dBm) for WCDMA – HSDPA (Rel 5) Modes				Conducted Power (dBm) for WCDMA – HSPA (HSUPA/HSDPA-Rel 6) Modes				
		RMC	AMR	Subtest 1	Subtest 2	Subtest 3	Subtest 4	Subtest 1	Subtest 2	Subtest 3	Subtest 4	Subtest 5
WCDMA 850	4132	23.17	23.16	23.15	23.13	23.14	23.09	21.30	21.62	22.09	22.11	22.17
	4180	23.16	23.12	23.17	23.19	23.21	23.21	21.50	21.53	22.10	22.11	22.16
	4233	23.15	23.13	23.17	23.15	23.17	23.16	21.15	21.29	22.12	21.75	22.11
WCDMA 1900	9262	22.17	21.56	22.16	22.06	22.11	22.10	20.58	20.56	20.94	20.99	20.99
	9400	22.08	21.98	22.00	22.02	21.94	21.94	20.43	20.48	20.88	20.87	20.63
	9538	22.21	22.29	22.10	22.26	22.19	22.22	20.73	20.82	21.24	21.17	20.53

Maximum Power Reduction (MPR)

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE transmit channel configuration	CM (dB)	MPR (dB)
For all combinations of; DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	MAX (CM-1, 0)
Note 1: CM = 1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to-average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present, the beta gains on those channels are reduced first to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done. However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a mechanism to compensate for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the device's output power is identical to the case where there is no MPR in the device.

2.4.5 Wi-Fi 802.11

Technical Description

The phone under test contains a Wi-Fi 802.11b/g/n transmitter capable of data transmission in the 2.45 GHz ISM band, and contains a Wi-Fi 802.11a/n/ac transmitter capable of data transmission in the 5 GHz U-NII bands.

Exposure Conditions and Test Exclusions

Mode	Type	Head-Adjacent	Body-Worn Accessory	Mobile Hotspot
802.11b / 802.11a	Data	Tested (1)	Tested (1)	Tested (1)
802.11g / 802.11n / 802.11ac	Data	Excluded (1)	Excluded (1)	Excluded (1)

Notes:

- (1) Per FCC KDB 248227 D01 and the April 2010 FCC/TCB Meeting Notes, the highest average output power channel for the lowest data rate for 802.11b or 802.11a was selected for SAR evaluation. Other 802.11 modes (including 802.11g and 802.11n) were not investigated when the average output powers over all channels and data rates were not more than ¼ dB higher than the tested channel in the lowest data rate of the 802.11b or 802.11a mode. The **bolded** data rates and channels in the following conducted power tables were used for SAR testing. For cases where alternate channels, higher data rates, or 802.11 modes resulted in output power more than ¼ dB higher than the tested configuration, additional SAR tests were conducted. Alternate configurations selected for additional testing are marked in **highlighted bold**, and were tested in all applicable exposure conditions.

Device Test Setup

For Wi-Fi 802.11 modes, the test sample was operated using manufacturer test mode software per guidance provided in FCC KDB 248227. The test software was set up for the proper channel, transmitter power level and transmit modes of operation on the phone's uplink.

Conducted Power Measurements

Mode	Freq [MHz]	Channel	Detector	802.11b Conducted Power [dBm]			
				Data Rate [Mbps]			
				1	2	5.5	11
802.11b	2412	1	AVG	17.03	17.06	17.22	17.09
			PEAK	19.62	19.65	19.80	19.71
802.11b	2417	2	AVG	17.07	17.04	17.03	17.05
			PEAK	19.68	19.65	19.65	19.66
802.11b	2437	6	AVG	19.16	19.18	19.14	19.14
			PEAK	21.70	21.67	21.69	21.70
802.11b	2462	11	AVG	18.31	18.11	18.24	18.25
			PEAK	20.97	20.78	20.82	20.91

Mode	Freq [MHz]	Channel	Detector	802.11g Conducted Power [dBm]							
				Data Rate [Mbps]							
				6	9	12	18	24	36	48	54
802.11g	2412	1	AVG	12.15	12.06	12.02	11.99	11.98	11.99	12.06	11.91
			PEAK	19.50	19.47	19.42	19.45	19.49	19.41	19.48	19.32
802.11g	2417	2	AVG	14.12	14.17	14.10	14.13	14.04	14.12	14.11	14.09
			PEAK	21.05	21.14	21.17	21.14	21.10	21.19	21.19	21.17
802.11g	2422	3	AVG	15.17	15.16	15.15	15.19	15.11	15.13	15.17	15.12
			PEAK	21.83	21.83	21.79	21.86	21.84	21.86	21.90	21.84
802.11g	2437	6	AVG	17.13	17.08	17.08	17.12	16.27	16.29	16.28	15.21
			PEAK	22.78	22.81	22.82	22.85	22.54	22.53	22.55	22.00
802.11g	2457	10	AVG	15.15	15.18	15.19	15.22	15.14	15.12	15.16	15.14
			PEAK	22.04	22.09	22.04	22.17	22.07	22.09	22.13	22.12
802.11g	2462	11	AVG	13.12	13.16	13.13	13.10	13.09	13.17	13.12	13.11
			PEAK	20.31	20.34	20.37	20.31	20.35	20.36	20.32	20.30

Mode	Freq	Channel	Detector	20MHz 802.11n (2.4GHz - 400ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
				7.2	14.4	21.7	28.9	43.4	57.8	65.0	72.2
802.11n	2412	1	AVG	10.95	10.91	10.94	10.92	10.94	10.95	10.93	10.99
			PEAK	18.39	18.42	18.35	18.39	18.38	18.40	18.43	18.44
802.11n	2417	2	AVG	13.14	13.12	13.09	13.09	13.13	13.16	13.11	13.18
			PEAK	20.32	20.37	20.42	20.31	20.34	20.36	20.28	20.38
802.11n	2422	3	AVG	14.23	14.22	14.19	14.19	14.18	14.23	14.27	14.18
			PEAK	21.17	21.15	21.17	21.26	21.27	21.23	21.15	21.25
802.11n	2437	6	AVG	17.13	17.11	17.16	17.08	17.14	17.14	17.12	17.17
			PEAK	22.79	22.77	22.82	22.81	22.89	22.82	22.85	22.80
802.11n	2457	10	AVG	14.28	14.27	14.24	14.25	14.30	14.28	14.23	14.24
			PEAK	21.52	21.57	21.49	21.57	21.62	21.61	21.50	21.56
802.11n	2462	11	AVG	12.00	11.95	11.96	11.98	12.02	12.03	11.96	11.99
			PEAK	19.57	19.63	19.57	19.61	19.64	19.56	19.53	19.60

Mode	Freq	Channel	Detector	20MHz 802.11n (2.4GHz - 800ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0
802.11n	2412	1	AVG	10.87	10.83	10.83	10.91	10.91	10.90	10.88	10.89
			PEAK	18.39	18.42	18.41	18.45	18.44	18.46	18.44	18.47
802.11n	2417	2	AVG	12.88	12.88	12.87	12.89	12.85	12.92	12.88	12.84
			PEAK	20.07	20.16	20.04	20.14	20.04	20.07	20.17	20.16
802.11n	2422	3	AVG	14.15	14.11	14.16	14.13	14.12	14.13	14.12	14.16
			PEAK	21.17	21.22	21.27	21.17	21.19	21.24	21.16	21.19
802.11n	2437	6	AVG	17.12	17.15	17.07	17.14	17.14	17.16	17.08	17.09
			PEAK	22.83	22.82	22.86	22.93	22.89	22.90	22.79	22.86
802.11n	2457	10	AVG	14.16	14.12	14.15	14.18	14.18	14.11	14.19	14.20
			PEAK	21.47	21.53	21.57	21.52	21.50	21.57	21.44	21.44
802.11n	2462	11	AVG	11.91	11.90	11.86	11.88	11.92	11.94	11.91	11.89
			PEAK	19.36	19.41	19.32	19.37	19.39	19.35	19.38	19.43

Mode	Freq	Channel	Detector	802.11a Conducted Power [dBm]							
				Data Rate [Mbps]							
				6	9	12	18	24	36	48	54
802.11a	5180	36	AVG	15.56	15.55	15.54	15.52	15.50	15.51	15.49	15.47
802.11a	5200	40	AVG	15.35	15.33	15.34	15.31	15.31	15.32	15.30	15.31
802.11a	5220	44	AVG	15.48	15.47	15.45	15.49	15.46	15.45	15.43	15.47
802.11a	5240	48	AVG	15.52	15.48	15.47	15.50	15.49	15.45	15.41	15.43

Mode	Freq	Channel	Detector	20MHz BW 802.11n (5GHz - 400ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
				7.2	14.4	21.7	28.9	43.3	57.8	65.0	72.2
802.11n	5180	36	AVG	15.59	15.56	15.55	15.60	15.59	15.58	15.55	15.57
802.11n	5200	40	AVG	15.31	15.28	15.35	15.35	15.30	15.30	15.31	15.26
802.11n	5220	44	AVG	15.43	15.44	15.40	15.49	15.44	15.48	15.44	15.47
802.11n	5240	48	AVG	15.49	15.50	15.47	15.46	15.53	15.43	15.41	15.40

Mode	Freq	Channel	Detector	20MHz BW 802.11n (5GHz - 800ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0
802.11n	5180	36	AVG	15.57	15.52	15.51	15.52	15.53	15.56	15.46	15.52
802.11n	5200	40	AVG	15.32	15.29	15.37	15.32	15.27	15.32	15.31	15.28
802.11n	5220	44	AVG	15.52	15.44	15.49	15.47	15.50	15.44	15.42	15.48
802.11n	5240	48	AVG	15.55	15.46	15.45	15.46	15.48	15.46	15.43	15.38

Mode	Freq	Channel	Detector	20MHz BW 802.11ac (5GHz - 400ns GI) Conducted Power [dBm]								
				Data Rate [Mbps]								
				7.2	14.4	21.7	28.9	43.3	57.8	65.0	72.2	MCS8
802.11ac	5180	36	AVG	15.41	15.43	15.40	15.42	15.46	15.45	15.41	15.42	15.40
802.11ac	5200	40	AVG	15.46	15.40	15.48	15.49	15.50	15.52	15.44	15.42	15.43
802.11ac	5220	44	AVG	15.48	15.44	15.48	15.48	15.55	15.50	15.41	15.49	15.46
802.11ac	5240	48	AVG	15.41	15.41	15.37	15.42	15.53	15.46	15.45	15.46	15.46

Mode	Freq	Channel	Detector	20MHz BW 802.11ac (5GHz - 800ns GI) Conducted Power [dBm]								
				Data Rate [Mbps]								
	[MHz]			6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0	MCS8
802.11ac	5180	36	AVG	15.59	15.58	15.69	15.65	15.61	15.74	15.44	15.59	14.58
802.11ac	5200	40	AVG	15.29	15.41	15.48	15.46	15.42	15.48	15.32	15.32	14.26
802.11ac	5220	44	AVG	15.37	15.43	15.54	15.55	15.52	15.63	15.38	15.49	14.51
802.11ac	5240	48	AVG	15.54	15.57	15.65	15.59	15.57	15.72	15.42	15.47	14.49

Mode	Freq	Channel	Detector	40MHz BW 802.11n (5GHz - 400ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			15.0	30.0	45.0	60.0	90.0	120.0	135.0	150.0
802.11n	5190	38	AVG	14.18	14.16	14.14	14.15	14.16	14.16	14.15	14.17
802.11n	5230	46	AVG	14.17	14.14	14.15	14.17	14.15	14.18	14.13	14.16

Mode	Freq	Channel	Detector	40MHz BW 802.11n (5GHz - 800ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			13.5	27.0	40.5	54.0	81.0	108.0	121.5	135.0
802.11n	5190	38	AVG	14.15	14.20	14.16	14.19	14.19	14.16	14.15	14.16
802.11n	5230	46	AVG	14.20	14.14	14.14	14.13	14.19	14.16	14.17	14.12

Mode	Freq	Channel	Detector	40MHz BW 802.11ac (5GHz - 400ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
	[MHz]			15.0	30.0	45.0	60.0	90.0	120.0	135.0	150.0	MCS8	MCS9
802.11ac	5190	38	AVG	14.01	13.94	13.91	13.92	13.82	13.85	13.90	13.89	13.02	12.01
802.11ac	5230	46	AVG	13.99	13.97	13.94	13.93	13.90	13.89	13.89	13.87	13.05	11.99

Mode	Freq	Channel	Detector	40MHz BW 802.11ac (5GHz - 800ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
	[MHz]			13.5	27.0	40.5	54.0	81.0	108.0	121.5	135.0	MCS8	MCS9
802.11ac	5190	38	AVG	14.11	14.17	14.06	14.03	13.93	14.05	13.91	13.99	13.19	12.17
802.11ac	5230	46	AVG	13.99	14.08	14.03	14.01	13.98	14.04	13.97	13.95	13.23	12.21

Mode	Freq	Channel	Detector	80MHz BW 802.11ac (5GHz - 400ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
	[MHz]			32.5	65	97.5	130	195	260	292.5	325	390	433.3
802.11ac	5210	42	AVG	14.25	14.28	14.27	14.31	14.30	14.26	14.28	14.29	14.25	12.28

Mode	Freq	Channel	Detector	80MHz BW 802.11ac (5GHz - 800ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
	[MHz]			29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac	5210	42	AVG	14.33	14.29	14.32	14.30	14.28	14.31	14.30	14.28	14.29	12.47

Mode	Freq	Channel	Detector	802.11a Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			6	9	12	18	24	36	48	54
802.11a	5745	149	AVG	20.07	20.03	19.24	19.17	19.15	18.19	17.11	16.29
			PEAK	24.12	24.10	23.81	23.80	23.84	23.49	23.02	22.63
802.11a	5765	153	AVG	20.07	20.13	19.07	19.14	19.09	18.07	17.07	16.25
			PEAK	24.05	24.05	23.72	23.82	23.78	23.41	23.01	22.56
802.11a	5785	157	AVG	20.09	20.13	19.11	19.13	19.06	18.01	16.98	16.11
			PEAK	24.02	24.02	23.72	23.71	23.72	23.43	22.92	22.45
802.11a	5805	161	AVG	20.07	20.10	19.06	19.09	19.08	18.13	17.11	16.12
			PEAK	24.01	24.04	23.71	23.74	23.73	23.42	22.96	22.51
802.11a	5825	165	AVG	20.02	20.01	19.05	19.08	19.09	18.03	17.01	16.05
			PEAK	24.01	24.02	23.73	23.75	23.72	23.37	22.95	22.47

Mode	Freq	Channel	Detector	20MHz BW 802.11n (5GHz - 400ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			7.2	14.4	21.7	28.9	43.4	57.8	65.0	72.2
802.11n	5745	149	AVG	19.23	19.34	19.32	19.16	18.26	17.14	16.20	15.23
			PEAK	24.44	24.49	24.49	24.47	24.13	23.64	23.03	22.35
802.11n	5765	153	AVG	19.28	19.26	19.23	19.20	18.19	17.05	16.15	15.18
			PEAK	24.42	24.48	24.49	24.38	24.07	23.51	22.97	22.24
802.11n	5785	157	AVG	19.17	19.18	19.24	19.22	18.08	16.96	16.15	15.11
			PEAK	24.35	24.36	24.40	24.40	23.98	23.41	22.93	22.25
802.11n	5805	161	AVG	19.23	19.22	19.23	19.21	18.26	17.05	16.25	15.28
			PEAK	24.30	24.34	24.32	24.30	24.01	23.43	22.97	22.31
802.11n	5825	165	AVG	19.25	19.26	19.23	19.22	18.21	17.01	16.26	15.26
			PEAK	24.32	24.35	24.32	24.31	23.98	23.40	22.99	22.27

Mode	Freq	Channel	Detector	20MHz BW 802.11n (5GHz - 800ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0
802.11n	5745	149	AVG	19.00	19.13	19.14	19.04	18.06	17.04	16.18	15.13
			PEAK	24.20	24.24	24.26	24.18	23.92	23.46	22.92	22.22
802.11n	5765	153	AVG	19.08	19.04	19.02	19.02	18.09	17.00	16.11	15.12
			PEAK	24.04	24.06	24.08	24.07	23.78	23.31	22.87	22.29
802.11n	5785	157	AVG	19.14	19.07	18.99	19.08	18.09	16.84	16.05	15.08
			PEAK	24.16	24.16	24.15	24.21	23.88	23.32	22.86	22.11
802.11n	5805	161	AVG	19.15	19.13	19.14	19.07	18.19	16.95	16.14	15.06
			PEAK	24.37	24.35	24.41	24.39	24.08	23.46	22.90	22.15
802.11n	5825	165	AVG	19.14	19.06	19.17	19.15	18.15	16.95	16.03	15.08
			PEAK	24.32	24.27	24.27	24.28	23.90	23.39	22.75	22.12

Mode	Freq	Channel	Detector	20MHz BW 802.11ac (5GHz - 400ns GI) Conducted Power [dBm]								
				Data Rate [Mbps]								
	[MHz]			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
802.11ac	5745	149	AVG	18.90	18.98	18.94	18.98	18.02	17.01	15.98	14.92	13.93
			PEAK	23.75	23.72	23.69	23.82	23.52	23.19	22.64	21.97	21.28
802.11ac	5765	153	AVG	18.88	18.94	18.95	19.02	17.99	17.02	15.98	14.88	13.94
			PEAK	23.79	23.74	23.72	23.83	23.52	23.25	22.67	21.94	21.30
802.11ac	5785	157	AVG	18.94	18.94	18.99	18.99	18.00	16.98	16.02	14.90	13.93
			PEAK	23.77	23.67	23.65	23.87	23.48	23.14	22.69	21.92	21.31
802.11ac	5805	161	AVG	18.87	18.99	18.93	18.96	18.03	17.00	15.98	14.93	13.97
			PEAK	23.78	23.67	23.68	23.86	23.58	23.14	22.68	22.03	21.29
802.11ac	5825	165	AVG	18.87	19.00	18.93	18.94	18.06	17.06	15.94	14.89	13.92
			PEAK	23.80	23.73	23.67	23.81	23.58	23.14	22.58	21.93	21.25

Mode	Freq	Channel	Detector	20MHz BW 802.11ac (5GHz - 800ns GI) Conducted Power [dBm]								
				Data Rate [Mbps]								
	[MHz]			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
802.11ac	5745	149	AVG	18.94	18.97	18.90	18.99	18.00	17.06	15.97	14.91	13.95
			PEAK	23.80	23.79	23.76	23.75	23.51	23.26	22.59	21.96	21.33
802.11ac	5765	153	AVG	18.95	19.02	18.91	19.03	18.04	17.02	15.97	14.90	13.91
			PEAK	23.69	23.78	23.62	23.76	23.47	23.22	22.69	21.99	21.24
802.11ac	5785	157	AVG	18.92	18.95	18.96	18.99	18.00	16.97	16.00	14.97	13.89
			PEAK	23.78	23.75	23.64	23.80	23.58	23.15	22.63	21.97	21.29
802.11ac	5805	161	AVG	18.87	18.99	18.96	18.97	17.98	17.02	15.94	14.89	13.93
			PEAK	23.81	23.72	23.68	23.78	23.59	23.13	22.68	22.00	21.28
802.11ac	5825	165	AVG	18.90	18.95	18.99	19.03	18.06	17.05	15.95	14.97	13.96
			PEAK	23.73	23.69	23.65	23.76	23.56	23.23	22.64	21.96	21.27

Mode	Freq	Channel	Detector	40MHz BW 802.11n (5GHz - 400ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			15.0	30.0	45.0	60.0	90.0	120.0	135.0	150.0
802.11n	5755	151	AVG	18.72	18.69	18.56	18.63	17.63	16.72	15.53	14.47
			PEAK	23.78	23.73	23.70	23.70	23.32	22.87	22.12	21.43
802.11n	5775	155	AVG	18.72	18.67	18.72	18.69	17.60	16.67	15.65	14.32
			PEAK	23.74	23.71	23.76	23.74	23.22	22.74	22.23	21.29
802.11n	5795	159	AVG	18.69	18.67	18.71	18.57	17.67	16.71	15.51	14.43
			PEAK	23.73	23.74	23.74	23.67	23.30	22.85	22.14	21.40
802.11n	5815	163	AVG	18.57	18.73	18.72	18.70	17.64	16.69	15.67	14.38
			PEAK	23.66	23.77	23.76	23.76	23.29	22.84	22.19	21.40

Mode	Freq	Channel	Detector	40MHz BW 802.11n (5GHz - 800ns GI) Conducted Power [dBm]							
				Data Rate [Mbps]							
	[MHz]			13.5	27.0	40.5	54.0	81.0	108.0	121.5	135.0
802.11n	5755	151	AVG	18.55	18.54	18.54	18.55	17.65	16.63	15.48	14.52
			PEAK	23.69	23.67	23.73	23.73	23.30	22.76	22.06	21.47
802.11n	5775	155	AVG	18.58	18.59	18.55	18.58	17.64	16.72	15.56	14.37
			PEAK	23.70	23.70	23.69	23.71	23.33	22.84	22.07	21.36
802.11n	5795	159	AVG	18.71	18.73	18.74	18.52	17.63	16.68	15.62	14.38
			PEAK	23.76	23.73	23.74	23.68	23.30	22.77	22.13	21.37
802.11n	5815	163	AVG	18.66	18.69	18.67	18.64	17.70	16.62	15.64	14.31
			PEAK	23.69	23.73	23.72	23.74	23.34	22.79	22.21	21.25

Mode	Freq [MHz]	Channel	Detector	40MHz BW 802.11ac (5GHz - 400ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
				15.0	30.0	45.0	60.0	90.0	120.0	135.0	150.0	MCS8	MCS9
802.11ac	5755	151	AVG	17.72	17.73	17.76	17.78	16.57	15.49	14.58	13.59	12.65	10.86
			PEAK	23.42	23.34	23.42	23.41	22.85	22.42	22.01	21.61	20.55	18.61
802.11ac	5775	155	AVG	17.73	17.73	17.80	17.79	16.58	15.55	14.55	13.59	12.68	10.85
			PEAK	23.36	23.38	23.37	23.38	22.82	22.42	22.02	21.65	20.48	18.72
802.11ac	5795	159	AVG	17.70	17.71	17.81	17.83	16.58	15.52	14.55	13.63	12.63	10.85
			PEAK	23.34	23.45	23.46	23.46	22.79	22.53	21.93	21.72	20.61	18.66
802.11ac	5815	163	AVG	17.77	17.75	17.73	17.75	16.56	15.54	14.62	13.65	12.70	10.85
			PEAK	23.48	23.29	23.39	23.42	22.92	22.51	21.94	21.62	20.49	18.57

Mode	Freq [MHz]	Channel	Detector	40MHz BW 802.11ac (5GHz - 800ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
				13.5	27.0	40.5	54.0	81.0	108.0	121.5	135.0	MCS8	MCS9
802.11ac	5755	151	AVG	17.87	17.95	17.87	17.85	16.78	15.69	14.78	13.72	12.76	11.96
			PEAK	24.09	24.25	24.11	24.04	23.60	23.14	23.15	22.06	21.70	21.02
802.11ac	5775	155	AVG	17.83	17.86	17.84	17.85	16.82	15.68	14.78	13.64	12.68	11.93
			PEAK	24.05	24.09	24.00	24.02	23.63	23.10	23.11	22.01	21.73	21.05
802.11ac	5795	159	AVG	17.88	17.93	17.90	17.84	16.70	15.69	14.76	13.76	12.81	11.98
			PEAK	24.05	23.98	24.04	24.07	23.59	23.04	23.19	22.09	21.64	21.07
802.11ac	5815	163	AVG	17.82	17.76	17.76	17.85	16.80	15.63	14.78	13.66	12.79	11.89
			PEAK	24.01	24.01	24.07	23.96	23.50	23.14	23.14	22.06	21.69	20.98

Mode	Freq [MHz]	Channel	Detector	80MHz BW 802.11ac (5GHz - 400ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
				32.5	65	97.5	130	195	260	292.5	325	MCS8	MCS9
802.11ac	5775	155	AVG	17.67	17.31	16.89	16.61	15.44	14.38	13.53	12.60	11.46	9.72
			PEAK	26.19	25.76	25.90	26.40	24.89	23.77	22.89	21.90	20.49	18.99
802.11ac	5795	159	AVG	17.59	17.19	17.01	16.63	15.32	14.27	13.69	12.56	11.50	9.59
			PEAK	26.07	25.98	26.02	26.36	25.08	23.69	22.91	21.97	20.63	18.89

Mode	Freq [MHz]	Channel	Detector	80MHz BW 802.11ac (5GHz - 800ns GI) Conducted Power [dBm]									
				Data Rate [Mbps]									
				29.3	58.5	87.8	117	175.5	234	263.3	292.5	MCS8	MCS9
802.11ac	5775	155	AVG	17.55	17.20	16.87	16.53	15.36	14.31	13.56	12.46	11.47	9.61
			PEAK	26.12	25.81	25.92	26.23	24.92	23.72	22.88	21.82	20.49	18.89
802.11ac	5795	159	AVG	17.53	17.10	16.81	16.59	15.38	14.24	13.55	12.37	11.42	9.66
			PEAK	26.22	25.67	25.86	26.22	24.91	23.79	22.93	21.79	20.46	18.80

2.4.6 Bluetooth

Technical Description

The phone under test contains a Bluetooth transmitter capable of data transmission in the 2.45 GHz ISM band.

Exposure Conditions and Test Exclusions

Mode	Type	Head-Adjacent	Body-Worn Accessory	Mobile Hotspot
All Modes	Data	Excluded (1)	Excluded (1)	Excluded (1)

Notes:

(1) Per FCC KDB 447498 D01, standalone SAR measurements of the Bluetooth transmitter in this phone were not required based on the maximum conducted power and the Bluetooth antenna-to-user separation distance. As detailed by the KDB publication, the SAR exclusion threshold for distances < 50 mm is defined by the following equation:

$$\frac{[\text{maximum power of channel, including tune – up tolerance}]_{(mW)}}{[\text{minimum test separation distance}]_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth and the most conservative antenna-to-user separation distance used in testing, standalone SAR measurements for Bluetooth were not required.

$$\frac{[10.728]_{(mW)}}{[10]_{(mm)}} \times \sqrt{2.44_{(GHz)}} = 1.7 \leq 3.0$$

Note that simultaneous SAR evaluations include estimations for Bluetooth SAR, as detailed in section 4.6 below.

Conducted Power Measurements

Frequency [MHz]	Data Rate [Mbps]	Channel Number	Peak Conducted Power [mW]
2402	1.0	0	5.879
2441	1.0	39	7.649
2480	1.0	78	8.011
2402	2.0	0	7.451
2441	2.0	39	9.694
2480	2.0	78	10.139
2402	3.0	0	7.881
2441	3.0	39	10.252
2480	3.0	78	10.728

Frequency [MHz]	Mode	Channel Number	Peak Conducted Power [mW]
2402	LE	0	5.860
2441	LE	39	7.396
2480	LE	78	8.011

2.4.7 Near-Field Communications

Technical Description

This device contains an integrated Near Field Communications (NFC) module.

Test Exclusion Evaluation

Evaluation of SAR test requirements for the NFC transmitter was performed per the guidance in FCC KDB 447498, FCC KDB 865664 and FCC KDB 648474. FCC KDB 865664 specifies that the FCC SAR test requirements are applicable to 100 MHz - 6 GHz only, but states that numerical SAR simulation may be appropriate for transmit frequencies below 100 MHz. Additionally, KDB 447498 provides guidance on test exclusion based on maximum transmit power capabilities, which this NFC transmitter falls into. Finally, KDB 648474 states that "phones with built-in NFC, wireless charging or similar functions that do not require separate SAR testing for these specific capabilities can generally be tested according to the normally required SAR measurement procedures. The SAR influence of the additional accessory hardware and functionality to the transmitters and antennas that require SAR Testing are considered during the required SAR testing; therefore, it is transparent to the testing process." Therefore, no SAR measurements of the NFC transmitter are required.

2.5 Transmitter power reduction conditions and modes

The phone utilizes reduced limits for the maximum transmit power for its transmitters when operating under the following noted conditions to ensure SAR exposure compliance is maintained. Tables of the reduced limits used for testing are given below. A complete description of this functionality is provided in the “Operational Description” contained within Exhibit 12. The implementation to trigger the reduction in power requires the device to be radiating, which prevents conducted power measurements of this functionality without modification to the unit.

For the Wi-Fi transmitter, reduced power limits are enforced when the Wi-Fi transmitter is operating simultaneously with any other transmitter(s). A table of the reduced limits used for testing is given below.

Mode(s) of Operation	Wi-Fi 2.4 GHz	Wi-Fi 5.8 GHz
Channel Ranges	1-11	149-165
Maximum Output Power (dBm)	19.18	20.13
Reduced Maximum Output Power Target (dBm)	15	15

While operating in a mobile hotspot session, a further reduced maximum power limit is enforced on the Wi-Fi 5.8 GHz transmitter. A table of the reduced limits used for testing is given below.

Mode(s) of Operation	Wi-Fi 5.8 GHz
Channel Ranges	149-165
Maximum Output Power (dBm)	20.13
Reduced Maximum Output Power Target (dBm)	11

The DUT supports Simultaneous Voice and LTE (SVLTE), allowing a 1x CDMA voice call while simultaneously providing an LTE link for data transport on the cellular network. While operating in SVLTE, *if the power on the 1x CDMA transmitter for voice is operating above 18 dBm*, a reduced maximum LTE transmit power limit is enforced to ensure SAR exposure compliance is maintained. When the power of the 1x CDMA transmitter is operating at or below 18 dBm or this combination of transmitters is not in use, the LTE transmitter operates up to its maximum power limit. Note that both conditions (1x CDMA above 18 dBm and LTE at reduced power, or 1x CDMA at or below 18 dBm with LTE at full power) are demonstrated for SAR compliance in section 6. A table of the reduced limits used for testing is given below.

Mode(s) of Operation	LTE Band 4					
Test Channel	Applicable to all channels/channel bandwidths					
Modulation	QPSK			16QAM		
RB Allocation	1 RB	50%	100%	1 RB	50%	100%
Maximum Output Power Setting (dBm)	24.0	24.0	24.0	24.0	24.0	24.0
Output Power with MPR (dBm)	24.0	23.0	23.0	23.0	22.0	22.0
Reduced Maximum Output Power Setting (dBm)	19.0	19.0	19.0	19.0	19.0	19.0

Mode(s) of Operation	LTE Band 13					
Test Channel	Applicable to all channels/channel bandwidths					
Modulation	QPSK			16QAM		
RB Allocation	1 RB	50%	100%	1 RB	50%	100%
Maximum Output Power (dBm)	24.0	24.0	24.0	24.0	24.0	24.0
Output Power with MPR (dBm)	24.0	23.0	23.0	23.0	22.0	22.0
Reduced Maximum Output Power (dBm)	20.5	20.5	20.5	20.5	20.5	20.5

The LTE transmitter may also operate as the data transport to the network during a mobile hotspot session. For operation in this state, the noted reduced power limit is strictly enforced regardless of other transmit conditions.

While operating in a mobile hotspot session, either as data transport to the network or voice transport for SVLTE during a mobile hotspot session, a reduced maximum power limit is enforced on the CDMA transmitter to ensure SAR exposure compliance is maintained. A table of the reduced limits used for testing is given below.

Mode(s) of Operation	CDMA 800	CDMA 1900
Channel Ranges	1013-777	25-1175
Maximum Output Power Setting (dBm)	25.0	25.0
Reduced Maximum Output Power Setting (dBm)	23.0	21.0

See section 6.4 for tables detailing the complete interoperation of this power limit reduction schema.

2.6 Accessories for the Device Under Test

2.6.1 Batteries

The phone tested in this report has the following battery options:

Model SNN5923A - 2200 mAH battery

The model SNN5923A battery is an internally-sealed battery contained within the DUT, and may not be removed by the end-user. This battery was used to do all of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery.

2.6.2 Body-Worn Carry Accessories

There are no body-worn accessories available for this phone at the time of testing thus the device was tested per the Supplement C testing guidelines for devices that do not have body-worn accessories. A separation distance of 25 mm between the device and the flat phantom was used for testing body-worn accessory SAR. The chosen separation distance of 25 mm is utilized in order to support any case or holder accessories offered or to be offered by Motorola for this product. The device was tested with the front and back of the device facing the phantom. Both sides of the device were tested for Body SAR for the purpose of including the SAR evaluation for body-worn accessories that support the device with either side facing the user.

3 Test Equipment Used

3.1 Dosimetric Measurement System

The Motorola Mobility ADR Test Services Laboratory utilizes a DASY52™ Dosimetric Assessment System manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All SAR measurements are taken within a shielded enclosure. The overall 10 g RSS uncertainty of the measurement system is $\pm 11\%$ (K=1) with an expanded uncertainty of $\pm 22\%$ (K=2). The overall 1 g RSS uncertainty of the measurement system is $\pm 11\%$ (K=1) with an expanded uncertainty of $\pm 22\%$ (K=2). The measurement uncertainty budget is given in Appendix 5. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4 W/kg to 10 W/kg.

The list of calibrated equipment used for the measurements is shown in the following table. All equipment was brought into service and used only during its noted calibration period, except where indicated. Equipment without a calibration period was in service for the entirety of the test period.

Description	Serial Number	Cal Date	Cal Due Date	Service Notes
DASY™ DAE V1	378	11-Apr-2012	11-Apr-2013	Measurement System 1
E-Field Probe ES3DV3	3184	25-Apr-2012	25-Apr-2013	Measurement System 1
Twin SAM Phantom V4.0	TP-1156			Measurement System 1
Twin SAM Phantom V4.0	TP-1319			Measurement System 1
MFP V5.1 C Triple Modular Flat Phantom	1101			Measurement System 1
DASY™ DAE V1	376	3-Sep-2012	3-Sep-2013	Measurement System 2
E-Field Probe ES3DV3	3124	20-Aug-2012	20-Aug-2013	Measurement System 2
Twin SAM Phantom V4.0	TP-1235			Measurement System 2
Twin SAM Phantom V4.0	TP-1136			Measurement System 2
MFP V5.1 C Triple Modular Flat Phantom	1102			Measurement System 2
DASY™ DAE V1	699	12-Sep-2012	12-Sep-2013	Measurement System 3 Removed from service 28-Mar-2013
DASY™ DAE V1	784	6-Mar-2013	6-Mar-2014	Measurement System 3 Placed into service 28-Mar-2013
E-Field Probe EX3DV4	3730	24-Aug-2012	24-Aug-2013	Measurement System 3
Twin SAM Phantom V4.0	TP-1106			Measurement System 3
Twin SAM Phantom V4.0	TP-1153			Measurement System 3
MFP V5.1 C Triple Modular Flat Phantom	1103			Measurement System 3
DASY™ DAE V1	703	11-Sep-2012	11-Sep-2013	Measurement System 4
E-Field Probe ES3DV3	3037	13-Sep-2012	13-Sep-2013	Measurement System 4
Twin SAM Phantom V4.0	TP-1132			Measurement System 4
Twin SAM Phantom V4.0	TP-1162			Measurement System 4
MFP V5.1 C Triple Modular Flat Phantom	1104			Measurement System 4
Dipole Validation Kit, D835V2	422tr	18-Mar-2011	18-Mar-2012	Calibration extension, see note.
Dipole Validation Kit, D835V2	423tr	12-Sep-2012	12-Sep-2013	
Dipole Validation Kit, D835V2	436tr	18-Mar-2011	18-Mar-2012	Calibration extension, see note.
Dipole Validation Kit, D1800V2	2d190	5-Jan-2012	5-Jan-2013	Calibration extension, see note.
Dipole Validation Kit, D1800V2	2d191	5-Jan-2012	5-Jan-2013	Calibration extension, see note.
Dipole Validation Kit, D1800V2	259tr	20-Oct-2011	20-Oct-2012	Calibration extension, see note.
Dipole Validation Kit, D2450V2	740	7-Feb-2012	7-Feb-2013	Calibration extension, see note.
Dipole Validation Kit, D5GHzV2	1088	20-May-2011	20-May-2012	Calibration extension, see note.

Note: Per FCC KDB 450824 D02, evaluation for the extension of the dipole calibration was carried out. Results are provided in Appendix 7 in addition to the original calibration certificate.

3.2 Additional Equipment

Description	Serial Number	Cal Date	Cal Due Date	Service Notes
Power Meter 437B	3125U08032	28-Aug-2012	28-Aug-2013	
Power Sensor 8481A	US37296470	2-Nov-2012	2-Nov-2013	
10 dB Attenuator 8491A	62165	24-Sep-2011	27-Sep-2013	
Signal Generator HP8648C	3847A04810	26-Sep-2011	26-Sep-2013	
Power Meter E4419B	GB39511090	12-Aug-2011	12-Aug-2013	
Power Sensor #1 - E9301A	US39211009	28-Aug-2012	28-Aug-2013	
Power Sensor #2 - E9301A	US39211013	2-Nov-2012	2-Nov-2013	
3 dB Attenuator 8491A	50577	15-Aug-2011	15-Aug-2013	
Dual Directional Coupler 778D	50790	2-Nov-2012	2-Nov-2014	
Amplifier ZHL-42-SMA	N120299-25			
Power Meter 437B	3125U08939	12-Aug-2011	12-Aug-2013	
Power Sensor 8481A	US37296475	2-Nov-2012	2-Nov-2013	
10 dB Attenuator 8491A	3929M50702	12-Sep-2011	12-Sep-2013	
Signal Generator HP8648C	3847M01245	23-Aug-2011	23-Aug-2013	
Power Meter E4419B	GB39511084	28-Mar-2011	28-Mar-2013	Removed from service 28-Mar-2013
Power Meter E4419B	GB39511087	28-Aug-2012	28-Aug-2014	Placed into service 28-Mar-2013
Power Sensor #1 - E9301A	US39210915	14-Jan-2013	14-Jan-2014	
Power Sensor #2 - E9301A	US39210916	14-Jan-2013	14-Jan-2014	
3 dB Attenuator 8491A	MY39267604	13-Oct-2011	13-Oct-2013	
Dual Directional Coupler 778D	18376	29-Aug-2012	29-Aug-2014	
Amplifier ZHL-42-SMA	N120299-23			
Signal Generator HP8648C	3847A04632	13-Aug-2011	13-Aug-2013	
Power Meter E4419B	GB39511086	4-Nov-2011	4-Nov-2013	
Power Sensor #1 - E9301A	US39211007	28-Aug-2012	28-Aug-2013	
Power Sensor #2 - E9301A	US39211008	28-Aug-2012	28-Aug-2013	
3 dB Attenuator 8491A	50555	13-Sep-2011	13-Sep-2013	
Dual Directional Coupler 778D	18621	18-Aug-2011	18-Aug-2013	
Amplifier ZHL-42-SMA	N120299-26			
Power Meter E4416A	GB41293246	5-Nov-2011	5-Nov-2013	
Power Sensor #3 - E9323A	MY444420676	29-Aug-2012	29-Aug-2013	
10 dB Attenuator 8491A	MY39267982	31-Jul-2012	31-Jul-2013	
Signal Generator N5181A	MY50143026	27-Oct-2011	27-Oct-2014	
Power Meter E4419B	GB39511088	11-Aug-2011	11-Aug-2013	
Power Sensor #1 - E9301A	US39210929	27-Jul-2012	27-Jul-2013	
Power Sensor #2 - E9301A	US39210930	27-Jun-2012	27-Jun-2013	
3 dB Attenuator 8491A	36902	13-Sep-2011	13-Sep-2013	
Dual Directional Coupler 772D	MY46151266	1-Aug-2012	1-Aug-2013	
Amplifier ZVA-183-S+	988901030 A			
Network Analyzer E5071C	MY46212851	10-May-2012	10-May-2013	
Dielectric Probe Kit DAK-3.5	1072			

3.3 Test System Validations

Per [5] and FCC KDB 865664 D01, each SAR system (including probes, system components, and software) used for device testing was validated against its performance specifications prior to deployment. These validation measurements are taken to ensure the accuracy of device test results. Validation measurements utilize reference dipoles and the required tissue-equivalent media, and include assessments of system sensitivity, probe linearity, and probe isotropy. Per FCC KDB 865664 D02, a tabulated summary of the validation results for each SAR system used in testing is given below.

DASY52™ Measurement System 1										
System Validation Measurements										
Probe	Tissue Type	f (MHz)	CW Validations				Modulated Validations			
			Date	Dielectric Parameters			Date	Mod. Type	Dielectric Parameters	
				Measured σ (S/m)	Measured ϵ_r	Result			Measured σ (S/m)	Measured ϵ_r
3184	Head	750	1/14/2013	0.876	42.76	PASS				
3184	Head	835	1/10/2013	0.919	40.99	PASS	1/11/2013	GMSK	0.915	40.926
3184	Head	1800	1/10/2013	1.336	38.94	PASS	1/11/2013	GMSK	1.342	39.026
3184	Head	1900	1/10/2013	1.443	38.49	PASS				
3184	Head	2450	1/11/2013	1.818	37.98	PASS	3/12/2013	OFDM	1.795	37.65
3184	Body	750	1/14/2013	0.980	54.73	PASS				
3184	Body	835	1/14/2013	0.978	53.83	PASS	1/11/2013	GMSK	0.98	53.925
3184	Body	1800	1/14/2013	1.450	52.38	PASS	1/11/2013	GMSK	1.579	51.544
3184	Body	1900	1/14/2013	1.568	52.00	PASS				
3184	Body	2450	1/14/2013	1.980	51.87	PASS	3/12/2013	OFDM	1.999	50.5

DASY52™ Measurement System 2										
System Validation Measurements										
Probe	Tissue Type	f (MHz)	CW Validations				Modulated Validations			
			Date	Dielectric Parameters			Date	Mod. Type	Dielectric Parameters	
				Measured σ (S/m)	Measured ϵ_r	Result			Measured σ (S/m)	Measured ϵ_r
3124	Head	750	1/16/2013	0.876	42.29	PASS				
3124	Head	835	1/16/2013	0.895	39.11	PASS	1/14/2013	GMSK	0.914	40.63
3124	Head	1800	1/15/2013	1.365	38.34	PASS	1/14/2013	GMSK	1.373	39.61
3124	Head	1900	1/15/2013	1.457	38.20	PASS				
3124	Head	2450	1/16/2013	1.812	39.28	PASS	3/12/2013	OFDM	1.795	37.65
3124	Head	2600	1/16/2013	1.971	38.77	PASS				
3124	Body	750	1/16/2013	0.967	54.55	PASS				
3124	Body	835	1/15/2013	0.989	53.55	PASS	1/15/2013	GMSK	0.99	53.547
3124	Body	1800	1/15/2013	1.448	51.40	PASS	1/14/2013	GMSK	1.45	52.38
3124	Body	1900	1/15/2013	1.568	51.03	PASS				
3124	Body	2450	1/16/2013	1.992	50.89	PASS	3/12/2013	OFDM	1.999	50.5
3124	Body	2600	1/16/2013	2.179	50.40	PASS				

DASY52™ Measurement System 3										
System Validation Measurements										
Probe	Tissue Type	f (MHz)	CW Validations				Modulated Validations			
			Date	Dielectric Parameters			Date	Mod. Type	Dielectric Parameters	
				Measured σ (S/m)	Measured ϵ_r	Result			Measured σ (S/m)	Measured ϵ_r
3730	Head	2450	1/16/2013	1.812	39.28	PASS	3/12/2013	OFDM	1.795	37.65
3730	Head	2600	1/16/2013	1.972	38.77	PASS				
3730	Head	5200	1/15/2013	4.547	35.00	PASS	3/18/2013	OFDM	4.562	35.362
3730	Head	5300	1/15/2013	4.663	34.79	PASS	3/18/2013	OFDM	4.679	35.123
3730	Head	5600	1/15/2013	4.981	34.10	PASS	3/18/2013	OFDM	5.014	34.448
3730	Head	5800	1/14/2013	5.204	33.67	PASS	3/19/2013	OFDM	5.243	34.016
3730	Body	2450	1/16/2013	1.992	50.89	PASS	3/12/2013	OFDM	1.999	50.5
3730	Body	2600	1/16/2013	2.179	50.40	PASS				
3730	Body	5200	1/14/2013	5.204	46.23	PASS	3/18/2013	OFDM	5.233	47.237
3730	Body	5300	1/14/2013	5.353	46.00	PASS	3/18/2013	OFDM	5.386	46.995
3730	Body	5600	1/14/2013	5.766	45.24	PASS	3/18/2013	OFDM	5.815	46.248
3730	Body	5800	1/14/2013	6.061	44.77	PASS	3/19/2013	OFDM	6.114	45.753

DASY52™ Measurement System 4 System Validation Measurements											
Probe	Tissue Type	f (MHz)	CW Validations				Modulated Validations				
			Date	Dielectric Parameters			Date	Mod. Type	Dielectric Parameters		Result
				Measured σ (S/m)	Measured ϵ_r	Result			Measured σ (S/m)	Measured ϵ_r	
3037	Head	750	1/8/2013	0.861	43.20	PASS					
3037	Head	835	1/7/2013	0.936	42.10	PASS	1/10/2013	GMSK	0.936	41.632	PASS
3037	Head	1800	1/7/2013	1.352	38.58	PASS	1/8/2013	GMSK	1.345	38.568	PASS
3037	Head	1900	1/7/2013	1.459	38.05	PASS					
3037	Head	2450	1/8/2013	1.822	37.87	PASS	3/12/2013	OFDM	1.795	37.65	PASS
3037	Head	2600	1/8/2013	1.974	37.32	PASS					
3037	Body	750	1/8/2013	0.911	54.83	PASS					
3037	Body	835	1/7/2013	0.997	53.94	PASS	1/8/2013	GMSK	1.00	54.83	PASS
3037	Body	1800	1/7/2013	1.443	52.70	PASS	1/8/2013	GMSK	1.43	52.459	PASS
3037	Body	1900	1/7/2013	1.567	52.25	PASS					
3037	Body	2450	1/8/2013	1.999	51.31	PASS	3/12/2013	OFDM	1.999	50.5	PASS
3037	Body	2600	1/8/2013	2.177	50.77	PASS					

3.4 Test System Verifications (System Performance Checks)

System accuracy verifications of the DASY52™ were performed using the measurement equipment listed in Section 3.1. The daily system performance check occurs within the flat section of the SAM phantom.

A SAR measurement was performed to verify the measured SAR was within $\pm 10\%$ from the target SAR indicated in Appendix 7. These frequencies are within $\pm 10\%$ of the compliance test mid-band frequency as required in [1] and [5]. The test was conducted within 24 hours prior to the measurement of the phone. Recommended limits for permittivity and conductivity, specified in [5], are shown in the table below. The obtained results from the system accuracy verification are also displayed in the table below. SAR values are normalized to 1 W forward power delivered to the dipole. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). For frequencies below 3 GHz, the simulated tissue depth was verified to be 15.0 cm $\pm$ 0.5 cm. For frequencies above 3 GHz, the simulated tissue depth was verified to be 10 cm $\pm$ 0.5 cm. Z-axis scans showing the SAR penetration are also included in Appendix 1.

DASY52™ Measurement System 1											
System Verification Measurements for Head SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
1800	Measured, 25-Mar-2013	3184	259tr	7.15	35.75	1.354	-3.3%	37.60	-6.0%	21.5	19.0
	Recommended Limits	3184	259tr		38.1	1.40	$\pm 10\%$	40.0	$\pm 10\%$	18-25	18-25

DASY52™ Measurement System 2											
System Verification Measurements for Head SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
835	Measured, 21-Mar-2013	3124	436tr	1.98	9.90	0.9287	+3.2%	40.85	-1.6%	21.5	20.0
	Measured, 27-Mar-2013	3124	436tr	2.02	10.10	0.9248	+2.8%	40.63	-2.1%	21.1	20.1
	Measured, 05-Apr-2013	3124	436tr	2.00	10.00	0.9206	+2.3%	40.43	+2.6%	22.2	20.7
	Recommended Limits	3124	436tr		9.73	0.90	$\pm 10\%$	41.5	$\pm 10\%$	18-25	18-25
1800	Measured, 27-Mar-2013	3124	2d190	7.46	37.30	1.350	-3.6%	37.21	-7.0%	21.1	19.6
	Measured, 03-Apr-2013	3124	2d190	7.55	37.75	1.347	-3.8%	36.59	-8.5%	21.6	19.6
	Measured, 05-Apr-2013	3124	2d190	7.64	38.2	1.369	-2.2%	37.17	-7.1%	22.2	19.7
	Recommended Limits	3124	2d190		39.3	1.40	$\pm 10\%$	40.0	$\pm 10\%$	18-25	18-25

DASY52™ Measurement System 3											
System Verification Measurements for Head SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
2450	Measured, 10-Apr-2013	3730	740	5.42	54.2	1.788	-0.7%	37.69	-3.9%	21.6	19.8
	Recommended Limits	3730	740		52.3	1.80	$\pm 10\%$	39.2	$\pm 10\%$	18-25	18-25
5200	Measured, 05-Apr-2013	3730	1088	7.74	77.4	4.636	-0.3%	35.52	-1.3%	21.2	19.1
	Recommended Limits	3730	1088		80.2	4.65	-5%/+10%	36.0	-10%/+5%	18-25	18-25
5800	Measured, 06-Apr-2013	3730	1088	7.96	79.6	5.324	+1.0%	34.15	-3.5%	21.4	18.7
	Recommended Limits	3730	1088		79.0	5.27	-5%/+10%	35.4	-10%/+5%	18-25	18-25

DASY52™ Measurement System 4											
System Verification Measurements for Head SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
835	Measured, 27-Mar-2013	3037	423tr	1.90	9.50	0.9443	+4.9%	41.59	+0.2%	21.1	20.7
	Recommended Limits	3037	423tr		9.22	0.90	$\pm 10\%$	41.5	$\pm 10\%$	18-25	18-25
1800	Measured, 28-Mar-2013	3037	2d191	7.67	38.35	1.368	-2.2%	37.64	-5.9%	21.4	19.6
	Measured, 30-Apr-2013	3037	2d191	7.79	38.95	1.356	-3.1%	36.89	-7.8%	22.3	20.5
	Recommended Limits	3037	2d191		39.2	1.40	$\pm 10\%$	40.0	$\pm 10\%$	18-25	18-25

DASY52™ Measurement System 1											
System Verification Measurements for Body SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
835	Measured, 30-Mar-2013	3184	422tr	1.96	9.80	0.9956	+2.6%	53.57	+3.0%	22.0	19.5
	Recommended Limits	3184	422tr		9.77	0.97	±10%	55.2	±10%	18-25	18-25
1800	Measured, 25-Mar-2013	3184	259tr	7.88	39.40	1.455	-4.3%	49.66	-6.8%	21.4	19.2
	Measured, 30-Mar-2013	3184	259tr	7.90	39.50	1.441	-5.2%	49.50	-7.1%	21.3	19.0
	Recommended Limits	3184	259tr		39.1	1.52	±10%	53.3	±10%	18-25	18-25

DASY52™ Measurement System 2											
System Verification Measurements for Body SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
835	Measured, 22-Mar-2013	3124	436tr	1.99	9.95	0.9945	+2.5%	53.81	-2.5%	22.1	19.5
	Measured, 28-Mar-2013	3124	436tr	1.96	9.80	0.9948	+2.6%	54.24	-1.7%	21.4	20.2
	Measured, 03-Apr-2013	3124	436tr	1.95	9.75	1.001	+3.2%	54.18	-1.8%	21.5	20.0
	Measured, 05-Apr-2013	3124	436tr	1.98	9.90	1.005	+3.6%	54.23	-1.8%	21.3	19.7
	Measured, 19-Apr-2013	3124	436tr	1.98	9.90	1.003	+3.4%	53.88	-2.4%	21.5	19.7
	Measured, 22-Apr-2013	3124	436tr	2.00	10.0	0.9999	+3.1%	53.31	-3.4%	22.1	19.3
	Recommended Limits	3124	436tr		10.1	0.97	±10%	55.2	±10%	18-25	18-25
1800	Measured, 27-Mar-2013	3124	2d190	7.63	38.15	1.574	+3.6%	50.43	-5.4%	21.4	19.5
	Measured, 30-Mar-2013	3124	2d190	7.75	38.75	1.441	-5.2%	49.50	-7.1%	22.1	18.8
	Measured, 02-Apr-2013	3124	2d190	7.64	38.20	1.450	-4.6%	49.31	-7.5%	21.0	19.3
	Measured, 05-Apr-2013	3124	2d190	7.76	38.80	1.455	-4.3%	49.07	-7.9%	21.6	19.6
	Measured, 18-Apr-2013	3124	2d190	7.65	38.25	1.438	-5.4%	49.39	-7.3%	22.0	19.3
	Recommended Limits	3124	2d190		37.8	1.52	±10%	53.3	±10%	18-25	18-25

DASY52™ Measurement System 3											
System Verification Measurements for Body SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
2450	Measured, 11-Apr-2013	3730	740	5.15	51.5	1.990	+2.1%	50.29	-4.6%	21.7	19.8
	Recommended Limits	3730	740		49.5	1.95	±10%	52.7	±10%	18-25	18-25
5200	Measured, 06-Apr-2013	3730	1088	7.51	75.1	5.285	-0.3%	46.78	-4.5%	21.2	18.4
	Recommended Limits	3730	1088		75.5	5.30	-5%/+10%	49.0	-10%/+5%	18-25	18-25
5800	Measured, 06-Apr-2013	3730	1088	7.21	72.1	6.183	+3.1%	45.32	-6.0%	21.4	18.6
	Measured, 09-Apr-2013	3730	1088	7.02	70.2	5.987	-0.2%	44.11	-8.5%	21.3	19.7
	Recommended Limits	3730	1088		75.4	6.00	-5%/+10%	48.2	-10%/+5%	18-25	18-25

DASY52™ Measurement System 4											
System Verification Measurements for Body SAR Measurements											
f (MHz)	Description	Probe	Dipole	Measured SAR (W/kg), 1 gram	Normalized SAR (W/kg), 1 gram	Dielectric Parameters				Ambient Temp (°C)	Tissue Temp (°C)
						Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)		
835	Measured, 28-Mar-2013	3037	423tr	1.94	9.70	0.9978	+2.9%	54.34	-1.6%	21.1	20.5
	Recommended Limits	3037	423tr		9.31	0.97	±10%	55.2	±10%	18-25	18-25
1800	Measured, 28-Mar-2013	3037	2d191	7.95	39.75	1.456	-4.2%	49.85	-6.5%	21.3	19.5
	Recommended Limits	3037	2d191		37.8	1.52	±10%	53.3	±10%	18-25	18-25

3.5 Simulated Tissue Dielectric Properties

Validation, System Performance Check, and device SAR measurements are performed using the DASY52™ system along with liquids specified to simulate head and body tissues subjected to electromagnetic exposure. The list of ingredients and the percent composition of the tissue-simulating liquids used for testing are indicated in the following table.

Ingredient	782 / 835 / 900 MHz Head	782 / 835 / 900 MHz Body	1800 MHz / 1900 MHz Head	1800 MHz / 1900 MHz Body	2450 MHz Head	2450 MHz Body	5 GHz Head	5 GHz Body
Sugar	57.0	44.9	--	--	--	--	--	--
DGBE	--	--	47.0	30.8	6.89	8.0	--	--
Water	40.45	53.06	52.62	68.8	57.95	71.8	65.52	78.66
Salt	1.45	0.94	0.38	0.4	0.15	0.2	--	--
HEC	1.0	1.0	--	--	--	--	--	--
Bact.	0.1	0.1	--	--	--	--	--	--
Triton X-100	--	--	--	--	35.02	20.0	17.24	10.67
Di(ethylene glycol) Hexyl Ether	--	--	--	--	--	--	17.24	10.67

Prior to conducting SAR measurements, the relative permittivity, ϵ_r , and conductivity, σ , of the tissue-simulating liquids were measured with a SPEAG™ DAK-3.5 Dielectric Assessment Kit across the frequency ranges of interest. These values, along with recommended targets, percent deviation from the targets, and the temperature of the simulated tissue are shown in the tables below.

For SAR measurements, the dielectric measurements from the DAK-3.5 are imported into the DASY software which performs interpolation to determine the dielectric parameters at the specific frequencies used for device testing. The DASY software also implements SAR error compensation algorithms to automatically correct the measured SAR results for deviations between the measured and target dielectric parameters. This error compensation has been verified by the lab to meet the requirements in FCC KDB 865664 D01. Therefore, where frequencies of test fall within ± 50 MHz of a calibration point of the probe used for test, the acceptable range of tissue variation is $\pm 10\%$ per FCC KDB 865664 D01 section 2.4. For test frequencies outside of ± 50 MHz of a probe calibration point, the range of tissue variation is reduced per section 2.6 part 2 of the same KDB, to ensure that tissues used in testing are within the required specification regardless of device performance. A mass density of $\rho = 1 \text{ g/cm}^3$ was entered into the system for all cases. It can be seen that the measured parameters are within tolerance of the recommended targets specified in [1] and [5].

Head Simulated-Tissue Dielectric Parameters									
Index	Date Measured	f (MHz)	Target σ (S/m)	Target ϵ_r	Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)	Temp (°C)
782	27-Mar-2013	777.0	0.90 ±10%	41.80 ±10%	0.87	-2.9%	41.3	-1.2%	20.1
		782.0	0.90 ±10%	41.78 ±10%	0.87	-2.9%	41.3	-1.3%	
		787.0	0.90 ±10%	41.75 ±10%	0.88	-1.9%	41.2	-1.4%	
835	21-Mar-2013	820.0	0.90 ±10%	41.58 ±10%	0.91	1.3%	41.0	-1.3%	20.3
		835.0	0.90 ±10%	41.50 ±10%	0.92	2.3%	40.9	-1.6%	
		849.0	0.92 ±10%	41.50 ±10%	0.93	1.7%	40.7	-2.0%	
	27-Mar-2013	820.0	0.90 ±10%	41.58 ±10%	0.93	3.5%	41.8	0.5%	20.7
		835.0	0.90 ±10%	41.50 ±10%	0.94	4.5%	41.6	0.3%	
		849.0	0.92 ±10%	41.50 ±10%	0.96	5.0%	41.4	-0.3%	
	06-Apr-2013	820.0	0.90 ±10%	41.58 ±10%	0.91	1.3%	40.5	-2.6%	19.8
		835.0	0.90 ±10%	41.50 ±10%	0.92	2.3%	40.3	-2.9%	
		849.0	0.92 ±10%	41.50 ±10%	0.94	2.8%	40.2	-3.3%	
1730	27-Mar-2013	1709.0	1.35 -5%/+10%	40.13 -10%/+5%	1.33	-1.4%	37.0	-7.9%	19.6
		1730.0	1.36 -5%/+10%	40.10 -10%/+5%	1.35	-0.8%	36.9	-8.0%	
		1755.0	1.37 -5%/+10%	40.06 -10%/+5%	1.37	-0.4%	36.8	-8.2%	
1880	25-Mar-2013	1850.0	1.40 ±10%	40.00 ±10%	1.40	0.0%	37.3	-6.7%	18.8
		1880.0	1.40 -5%/+10%	40.00 -10%/+5%	1.43	2.2%	37.2	-7.2%	
		1915.0	1.40 -5%/+10%	40.00 -10%/+5%	1.47	5.0%	37.0	-7.6%	
	28-Mar-2013	1850.0	1.40 ±10%	40.00 ±10%	1.42	1.5%	37.4	-6.5%	19.6
		1880.0	1.40 -5%/+10%	40.00 -10%/+5%	1.45	3.6%	37.3	-6.9%	
		1915.0	1.40 -5%/+10%	40.00 -10%/+5%	1.50	7.2%	37.1	-7.4%	
	05-Apr-2013	1850.0	1.40 ±10%	40.00 ±10%	1.42	1.5%	36.9	-7.8%	19.7
		1880.0	1.40 -5%/+10%	40.00 -10%/+5%	1.45	3.6%	36.7	-8.2%	
		1915.0	1.40 -5%/+10%	40.00 -10%/+5%	1.49	6.5%	36.5	-8.7%	
	30-Apr-2013	1850.0	1.40 ±10%	40.00 ±10%	1.40	0.0%	36.7	-8.3%	20.5
		1880.0	1.40 -5%/+10%	40.00 -10%/+5%	1.43	2.2%	36.6	-8.7%	
		1915.0	1.40 -5%/+10%	40.00 -10%/+5%	1.48	5.8%	36.4	-9.1%	
2450	10-Apr-2013	2412.0	1.77 ±10%	39.27 ±10%	1.75	-1.0%	37.8	-3.8%	20.0
		2450.0	1.80 ±10%	39.20 ±10%	1.79	-0.6%	37.7	-3.9%	
		2462.0	1.81 ±10%	39.18 ±10%	1.80	-0.8%	37.7	-3.9%	
5500	05-Apr-2013	5180.0	4.63 -5%/+10%	36.02 -10%/+5%	4.61	-0.5%	35.6	-1.3%	20.0
		5500.0	4.96 -5%/+10%	35.65 -10%/+5%	4.98	0.5%	34.8	-2.4%	
		5825.0	5.30 -5%/+10%	35.36 -10%/+5%	5.36	1.3%	34.1	-3.6%	

Body Simulated-Tissue Dielectric Parameters									
Index	Date Measured	f (MHz)	Target σ (S/m)	Target ϵ_r	Measured σ (S/m)	Deviation σ (%)	Measured ϵ_r	Deviation ϵ_r (%)	Temp (°C)
782	28-Mar-2013	777.0	0.97 ±10%	55.43 ±10%	0.93	-3.7%	54.8	-1.2%	20.2
		782.0	0.97 ±10%	55.41 ±10%	0.94	-2.7%	54.8	-1.2%	
		787.0	0.97 ±10%	55.39 ±10%	0.94	-2.8%	54.7	-1.3%	
	03-Apr-2013	777.0	0.97 ±10%	55.43 ±10%	0.94	-2.7%	54.7	-1.3%	20.3
		782.0	0.97 ±10%	55.41 ±10%	0.95	-1.7%	54.7	-1.4%	
		787.0	0.97 ±10%	55.39 ±10%	0.95	-1.7%	54.6	-1.4%	
835	21-Mar-2013	820.0	0.97 ±10%	55.26 ±10%	0.98	1.2%	54.0	-2.4%	20.1
		835.0	0.97 ±10%	55.20 ±10%	0.99	2.1%	53.8	-2.6%	
		849.0	0.99 ±10%	55.16 ±10%	1.01	2.4%	53.7	-2.8%	
	28-Mar-2013	820.0	0.97 ±10%	55.26 ±10%	0.98	1.2%	54.5	-1.4%	20.5
		835.0	0.97 ±10%	55.20 ±10%	1.00	3.1%	54.3	-1.6%	
		849.0	0.99 ±10%	55.16 ±10%	1.01	2.4%	54.2	-1.8%	
	30-Mar-2013	820.0	0.97 ±10%	55.26 ±10%	0.98	1.2%	53.7	-2.9%	19.1
		835.0	0.97 ±10%	55.20 ±10%	1.00	3.1%	53.6	-3.0%	
		849.0	0.99 ±10%	55.16 ±10%	1.01	2.4%	53.4	-3.2%	
	05-Apr-2013	820.0	0.97 ±10%	55.26 ±10%	0.99	2.2%	54.4	-1.7%	20.0
		835.0	0.97 ±10%	55.20 ±10%	1.01	4.2%	54.2	-1.8%	
		849.0	0.99 ±10%	55.16 ±10%	1.02	3.4%	54.1	-2.0%	
	19-Apr-2013	820.0	0.97 ±10%	55.26 ±10%	0.99	2.2%	54.0	-2.3%	19.9
		835.0	0.97 ±10%	55.20 ±10%	1.00	3.1%	53.9	-2.4%	
		849.0	0.99 ±10%	55.16 ±10%	1.02	3.4%	53.7	-2.6%	
	23-Apr-2013	820.0	0.97 ±10%	55.26 ±10%	0.98	1.2%	53.5	-3.3%	19.6
		835.0	0.97 ±10%	55.20 ±10%	0.99	2.1%	53.3	-3.5%	
		849.0	0.99 ±10%	55.16 ±10%	1.01	2.4%	53.2	-3.7%	
1730	27-Mar-2013	1709.0	1.47 -5%/+10%	53.55 -10%/+5%	1.47	0.3%	50.8	-5.3%	20.0
		1730.0	1.48 -5%/+10%	53.50 -10%/+5%	1.49	0.7%	50.7	-5.3%	
		1755.0	1.49 -5%/+10%	53.39 -10%/+5%	1.52	1.9%	50.6	-5.3%	
	30-Mar-2013	1709.0	1.47 -5%/+10%	53.55 -10%/+5%	1.47	0.3%	50.8	-5.3%	19.8
		1730.0	1.48 -5%/+10%	53.50 -10%/+5%	1.49	0.7%	50.7	-5.3%	
		1755.0	1.49 -5%/+10%	53.39 -10%/+5%	1.52	1.9%	50.6	-5.3%	
1880	25-Mar-2013	1850.0	1.52 ±10%	53.30 ±10%	1.51	-0.7%	49.4	-7.3%	19.2
		1880.0	1.52 -5%/+10%	53.30 -10%/+5%	1.55	2.0%	49.3	-7.6%	
		1915.0	1.52 -5%/+10%	53.30 -10%/+5%	1.59	4.7%	49.1	-7.9%	
	28-Mar-2013	1850.0	1.52 ±10%	53.30 ±10%	1.52	0.0%	49.7	-6.9%	19.5
		1880.0	1.52 -5%/+10%	53.30 -10%/+5%	1.56	2.7%	49.5	-7.1%	
		1915.0	1.52 -5%/+10%	53.30 -10%/+5%	1.60	5.3%	49.4	-7.4%	
	30-Mar-2013	1850.0	1.52 ±10%	53.30 ±10%	1.50	-1.4%	49.3	-7.6%	18.8
		1880.0	1.52 -5%/+10%	53.30 -10%/+5%	1.54	1.4%	49.1	-7.9%	
		1915.0	1.52 -5%/+10%	53.30 -10%/+5%	1.58	4.0%	48.9	-8.2%	
	03-Apr-2013	1850.0	1.52 ±10%	53.30 ±10%	1.49	-2.0%	49.0	-8.2%	19.7
		1880.0	1.52 -5%/+10%	53.30 -10%/+5%	1.53	0.7%	48.8	-8.4%	
		1915.0	1.52 -5%/+10%	53.30 -10%/+5%	1.58	4.0%	48.7	-8.7%	
	05-Apr-2013	1850.0	1.52 ±10%	53.30 ±10%	1.51	-0.7%	48.9	-8.4%	19.8
		1880.0	1.52 -5%/+10%	53.30 -10%/+5%	1.55	2.0%	48.7	-8.7%	
		1915.0	1.52 -5%/+10%	53.30 -10%/+5%	1.59	4.7%	48.5	-9.0%	
	18-Apr-2013	1850.0	1.52 ±10%	53.30 ±10%	1.50	-1.4%	49.2	-7.7%	19.0
		1880.0	1.52 -5%/+10%	53.30 -10%/+5%	1.53	0.7%	49.2	-7.8%	
		1915.0	1.52 -5%/+10%	53.30 -10%/+5%	1.58	4.0%	49.0	-8.1%	
2450	11-Apr-2013	2412.0	1.91 ±10%	52.75 ±10%	1.94	1.4%	50.4	-4.4%	19.8
		2450.0	1.95 ±10%	52.70 ±10%	1.99	2.1%	50.3	-4.6%	
		2462.0	1.97 ±10%	52.68 ±10%	2.00	1.7%	50.3	-4.7%	
5500	05-Apr-2013	5180.0	5.28 -5%/+10%	49.05 -10%/+5%	5.25	-0.6%	46.8	-4.6%	20.0
		5500.0	5.65 -5%/+10%	48.61 -10%/+5%	5.73	1.4%	46.0	-5.4%	
		5825.0	6.03 -5%/+10%	48.17 -10%/+5%	6.22	3.2%	45.3	-6.1%	
	06-Apr-2013	5180.0	5.28 -5%/+10%	49.05 -10%/+5%	5.31	0.6%	46.4	-5.5%	19.0
		5500.0	5.65 -5%/+10%	48.61 -10%/+5%	5.77	2.2%	45.5	-6.4%	
		5825.0	6.03 -5%/+10%	48.17 -10%/+5%	6.27	4.0%	44.7	-7.2%	
	09-Apr-2013	5180.0	5.28 -5%/+10%	49.05 -10%/+5%	5.08	-3.8%	45.6	-7.1%	19.5
		5500.0	5.65 -5%/+10%	48.61 -10%/+5%	5.54	-2.0%	44.8	-7.9%	
		5825.0	6.03 -5%/+10%	48.17 -10%/+5%	6.02	-0.2%	44.1	-8.6%	

4 Test Setup Information, SAR Measurement Results, and Analysis

4.1 Overview of Test Setup and Results

The phone was tested in the exposure configurations stipulated in [1], [4], [5], [9], and per FCC KDB 941225 D06 for mobile hotspot operation. The phone was positioned into these configurations using the device holder supplied with the DASY52™ SAR measurement system. The default settings for the SAR scans are set in accordance with FCC KDB 865664 D01 for all area scan resolutions, zoom scan resolutions and volumes, and probe positioning. Please refer to the DASY52™ manual for additional information on SAR scanning procedures and algorithms used.

The SAR measurements were performed using the SAM and Flat phantoms listed in section 3.1. The same phantoms and simulated tissues were used for the system performance checks and the device SAR measurements. Consequently the Z-axis scans included in Appendix 1 are applicable for verification of the required simulated tissue depths of 15.0 cm ± 0.5 cm for frequencies less than 3 GHz, or 10.0 cm ± 0.5 cm for frequencies greater than 3 GHz.

The SAR results shown in following tables are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to [6]. Also shown are the maximum device power, measured device power, temperature of the simulated tissue after the test, the measured drift and the scaled SAR. The exact method of scaling is:

$$\text{Scaled SAR} = (\text{Measured SAR}) * 10^{\left(\frac{(\text{Maximum Power}) - (\text{Measured Power})}{10}\right)} * 10^{\left(\frac{-\text{Drift}}{10}\right)}$$

The SAR reported at the end of the measurement process by the DASY52™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test. Note that measured SAR is scaled only in the manner which results in a more conservative scaled value, i.e. to a higher SAR value as a consequence of measured power being below the maximum allowed power, or for negative drift values.

Per FCC KDB 447498 D01, area-scan based 1 g SAR estimation was used for initial testing in all combinations of device modes and exposure conditions. The testing meets the following conditions:

- The DASY5 system was set to use the polynomial version of the algorithm that was reported in the 29th BEMS meeting in 2009.
- The maximum distance from the closest measurement point to the phantom surface was setup to be 4mm for tests < 3GHz and 2mm for tests > 3 GHz.
- The highest SAR measurements for each combination of device mode and exposure condition, and all conditions where the area scan estimation reported values greater than 1.2 W/kg, were further evaluated with a zoom scan and presented in the tables below.
- SAR system verifications must demonstrate that the verification area scan 1 g SAR estimation resulted in values within 3% of zoom scan 1 g SAR.
- No sharp gradient; SAR at 1 cm from peak > 40% of the peak value

The test conditions that produced the highest SAR values for each combination of DUT mode and exposure condition are indicated as **bold** numbers in the following tables. Plots of these tests are included in Appendices 2 through 4.

4.2 Head-Adjacent Exposure Results

Left Cheek-Touch Position												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	18.9	0.032	0.474	0.47	0.770	0.77	A38
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	18.9	0.01	0.318	0.32	0.515	0.52	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.00	0.142	0.14	0.226	0.23	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.00	0.146	0.15	0.231	0.23	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.0	0.16	0.340	0.34	0.450	0.45	A39
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	20.2	-0.02	0.237	0.24	0.312	0.31	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		19.6	-0.26	0.153	0.16	0.203	0.22	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.31	0.200	0.21	0.264	0.28	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	25.0	24.87	20.0	-0.01	0.389	0.40	0.57	0.59	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	23		20.5	-0.05	0.254	0.26	0.340	0.34	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	18		19.6	0.10	0.0742	0.07	0.0986	0.10	
EV-DO 800 Rev. 0	SNN5923A	384	836.52	23.0		21.0	-0.33	0.23	0.25	0.304	0.33	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	25.0	24.94	19.1	-0.01	0.396	0.40	0.657	0.67	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	21		19.5	0.07	0.275	0.28	0.444	0.44	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	18		18.8	-0.04	0.128	0.13	0.204	0.21	
EV-DO 1900 Rev. 0	SNN5923A	600	1880.0	21.0		20.1	-0.08	0.22	0.22	0.362	0.37	
GSM 850, CS Voice	SNN5923A	190	836.6	33.5	32.86	19.8	-0.13	0.125	0.15	0.18	0.21	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	19.8	0.05	0.113	0.18	0.166	0.26	
GSM 1900, CS Voice	SNN5923A	661	1880.0	30.5	29.63	18.6	0.12	0.177	0.22	0.293	0.36	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.3	0.08	0.173	0.26	0.286	0.43	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.8	-0.10	0.151	0.19	0.222	0.28	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	18.7	-0.01	0.256	0.40	0.427	0.67	
802.11b, 1 Mbps	SNN5923A	6	2437		19.16	19.2	0.19	0.129	0.13	0.249	0.25	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.3	0.08	0.062	0.06	0.126	0.13	
802.11a, 6 Mbps	SNN5923A	36	5200		15.56	18.5	-0.10	0.0903	0.09	0.265	0.27	
802.11a, 6 Mbps	SNN5923A	157	5785		20.09	18.5	-0.12	0.0527	0.05	0.182	0.19	
802.11a, 6 Mbps	SNN5923A	157	5785	15		18.7	-0.30	0.0574	0.06	0.157	0.17	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	-0.43	0.00575	0.01	0.0331	0.04	

Table 4-1: SAR measurement results in a head-adjacent position against the ICNIRP and ANSI SAR Limit.

Right Cheek-Touch Position												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	18.9	-0.02	0.231	0.23	0.381	0.38	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	18.9	-0.01	0.245	0.25	0.405	0.41	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		20.0	-0.03	0.086	0.09	0.129	0.13	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.05	0.083	0.08	0.124	0.12	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.2	-0.09	0.196	0.20	0.285	0.29	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	20.2	-0.07	0.155	0.16	0.224	0.23	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		20.0	0.07	0.097	0.10	0.125	0.13	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.09	0.135	0.14	0.175	0.18	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	25.0	24.87	20.0	-0.042	0.493	0.51	0.655	0.68	A40
CDMA 800, RC3 SO55	SNN5923A	384	836.52	23		20.5	-0.110	0.275	0.28	0.368	0.38	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	18		19.6	0.06	0.0776	0.08	0.105	0.11	
EV-DO 800 Rev. 0	SNN5923A	384	836.52	23.0		21.0	0.03	0.278	0.28	0.372	0.37	
CDMA 1900, RC3 SO55	SNN5923A	25	1851.3	25.0	24.97	19.1	0.00	0.774	0.78	1.27	1.28	
CDMA 1900, RC3 SO55	SNN5923A	600	1880	25.0	24.94	19.1	-0.057	0.816	0.84	1.35	1.39	A41
CDMA 1900, RC3 SO55	SNN5923A	600	1880	25.0	24.94	19.6	0.15	0.804	0.81	1.31	1.31	
CDMA 1900, RC3 SO55	SNN5923A	1175	1908.8	25.0	24.88	19.1	0.02	0.715	0.74	1.19	1.22	
CDMA 1900, RC3 SO55	SNN5923A	1175	1908.8	21		19.5	0.210	0.440	0.44	0.717	0.72	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	18		18.7	0.17	0.205	0.21	0.336	0.34	
EV-DO 1900 Rev. 0	SNN5923A	600	1880.0	21.0		20.1	0.06	0.456	0.46	0.742	0.74	
GSM 850, CS Voice	SNN5923A	190	836.6	33.5	32.86	19.8	-0.11	0.154	0.18	0.206	0.24	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	19.7	-0.017	0.126	0.20	0.169	0.27	A42
GSM 1900, CS Voice	SNN5923A	661	1880.0	30.5	29.63	18.6	0.02	0.354	0.43	0.58	0.71	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.3	0.033	0.313	0.48	0.498	0.76	A43
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.7	0.069	0.182	0.22	0.243	0.29	A44
WCDMA 1900, RMC	SNN5923A	9262	1852.4	24.0	22.17	20.3	-0.211	0.516	0.83	0.831	1.33	A45
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	18.7	-0.02	0.474	0.74	0.767	1.20	
WCDMA 1900, RMC	SNN5923A	9538	1907.6	24.0	22.21	20.3	-0.11	0.403	0.62	0.662	1.03	
802.11b, 1 Mbps	SNN5923A	1	2412		17.03	19.2	-0.16	0.333	0.35	0.711	0.74	
802.11b, 1 Mbps	SNN5923A	6	2437		19.16	19.3	-0.08	0.36	0.37	0.8	0.81	
802.11b, 1 Mbps	SNN5923A	11	2462		18.31	19.2	-0.179	0.398	0.41	0.879	0.92	A46
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.3	-0.01	0.182	0.18	0.416	0.42	
802.11a, 6 Mbps	SNN5923A	36	5200		15.56	18.5	-0.191	0.123	0.13	0.379	0.40	A47
802.11a, 6 Mbps	SNN5923A	157	5785		20.09	18.6	-0.232	0.0693	0.07	0.203	0.21	A48
802.11a, 6 Mbps	SNN5923A	157	5785	15		18.7	-0.18	0.0321	0.03	0.101	0.11	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	0.78	0.00778	0.01	0.0258	0.03	

Table 4-2: SAR measurement results in a head-adjacent position against the ICNIRP and ANSI SAR Limit.

Left 15° Tilt Position												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	18.9	0.10	0.288	0.29	0.517	0.52	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	18.9	0.13	0.291	0.29	0.520	0.52	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.05	0.089	0.09	0.151	0.15	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.18	0.094	0.09	0.158	0.16	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.0	0.11	0.161	0.16	0.230	0.23	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	20.0	-0.02	0.119	0.12	0.170	0.17	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		20.0	0.13	0.085	0.09	0.109	0.11	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.04	0.110	0.11	0.139	0.14	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	25.0	24.87	20.0	-0.04	0.28	0.29	0.405	0.42	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	23		20.5	-0.04	0.200	0.20	0.260	0.26	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	18		19.6	-0.04	0.0649	0.07	0.0844	0.09	
EV-DO 800 Rev. 0	SNN5923A	384	836.52	23.0		20.0	0.05	0.156	0.16	0.203	0.20	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	25.0	24.94	19.1	-0.08	0.341	0.35	0.587	0.61	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	21		19.5	0.00	0.211	0.21	0.345	0.35	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	18		18.7	-0.18	0.0927	0.10	0.155	0.16	
EV-DO 1900 Rev. 0	SNN5923A	600	1880.0	21.0		20.1	-0.08	0.22	0.22	0.362	0.37	
GSM 850, CS Voice	SNN5923A	190	836.6	33.5	32.86	19.7	-0.12	0.0886	0.11	0.129	0.15	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	19.9	-0.01	0.0901	0.14	0.13	0.21	
GSM 1900, CS Voice	SNN5923A	661	1880.0	30.5	29.63	18.7	-0.06	0.155	0.19	0.268	0.33	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.3	-0.09	0.176	0.27	0.3	0.47	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.8	0.10	0.106	0.13	0.153	0.19	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	18.7	-0.02	0.223	0.35	0.387	0.60	
802.11b, 1 Mbps	SNN5923A	6	2437		19.16	19.3	-0.05	0.0873	0.09	0.171	0.17	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.3	0.12	0.0343	0.03	0.0661	0.07	
802.11a, 6 Mbps	SNN5923A	36	5200		15.56	18.5	0.10	0.0679	0.07	0.308	0.31	
802.11a, 6 Mbps	SNN5923A	157	5785		20.09	18.6	-0.19	0.0658	0.07	0.194	0.20	
802.11a, 6 Mbps	SNN5923A	157	5785	15		18.7	-0.13	0.041	0.04	0.138	0.14	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	0.25	0.0247	0.02	0.0499	0.05	

Table 4-3: SAR measurement results in a head-adjacent position against the ICNIRP and ANSI SAR Limit.

Right 15° Tilt Position												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	18.9	-0.16	0.230	0.24	0.418	0.43	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	18.9	-0.02	0.254	0.26	0.440	0.44	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.03	0.089	0.09	0.152	0.15	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		20.0	0.00	0.092	0.09	0.160	0.16	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.2	-0.04	0.097	0.10	0.147	0.15	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	20.2	-0.07	0.089	0.09	0.126	0.13	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		20.0	0.08	0.060	0.06	0.076	0.08	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.04	0.081	0.08	0.102	0.10	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	25.0	24.87	20.0	-0.01	0.267	0.28	0.383	0.40	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	23		20.5	0.11	0.166	0.17	0.217	0.22	
CDMA 800, RC3 SO55	SNN5923A	384	836.52	18		19.6	-0.13	0.0481	0.05	0.0636	0.07	
EV-DO 800 Rev. 0	SNN5923A	384	836.52	23.0		21.0	-0.04	0.178	0.18	0.234	0.24	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	25.0	24.94	19.1	0.03	0.314	0.32	0.524	0.53	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	21		19.5	-0.020	0.174	0.17	0.273	0.27	
CDMA 1900, RC3 SO55	SNN5923A	600	1880.0	18		18.7	0.06	0.0799	0.08	0.127	0.13	
EV-DO 1900 Rev. 0	SNN5923A	600	1880.0	21.0		20.1	-0.07	0.196	0.20	0.31	0.32	
GSM 850, CS Voice	SNN5923A	190	836.6	33.5	32.86	19.7	0.04	0.0864	0.09	0.125	0.14	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	19.7	0.03	0.0828	0.13	0.12	0.19	
GSM 1900, CS Voice	SNN5923A	661	1880.0	30.5	29.63	18.7	0.05	0.135	0.16	0.228	0.28	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.2	0.05	0.137	0.21	0.232	0.35	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.7	0.02	0.111	0.13	0.161	0.20	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	18.6	-0.02	0.19	0.30	0.321	0.50	
802.11b, 1 Mbps	SNN5923A	6	2437		19.16	19.3	-0.09	0.158	0.16	0.339	0.35	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.3	-0.15	0.0772	0.08	0.165	0.17	
802.11a, 6 Mbps	SNN5923A	36	5200		15.56	18.4	-0.20	0.0675	0.07	0.277	0.29	
802.11a, 6 Mbps	SNN5923A	157	5785		20.09	18.6	0.09	0.0494	0.05	0.171	0.17	
802.11a, 6 Mbps	SNN5923A	157	5785	15		19.1	0.29	0.0367	0.04	0.123	0.12	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	-0.19	0.0071	0.01	0.02	0.02	

Table 4-4: SAR measurement results in a head-adjacent position against the ICNIRP and ANSI SAR Limit.

4.3 Body-Worn Accessory Exposure Results


Body-Worn Accessory Position, Front of Phone 25 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	19.4	-0.01	0.250	0.25	0.377	0.38	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	19.4	0.05	0.161	0.16	0.254	0.25	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	19.8	-0.07	0.125	0.13	0.178	0.18	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	19.8	0.04	0.076	0.08	0.108	0.11	
CDMA 800, TDSO SO32	SNN5923A	384	836.52	25.0	24.83	19.5	0.045	0.363	0.38	0.479	0.50	A52
CDMA 1900, TDSO SO32	SNN5923A	600	1880.0	25.0	24.92	18.2	0.019	0.209	0.21	0.326	0.33	A53
GSM 850, CS Voice	SNN5923A	190	836.6	33.5	32.86	20.2	-0.11	0.0594	0.07	0.0844	0.10	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.9	-0.076	0.145	0.23	0.192	0.31	A54
GSM 1900, CS Voice	SNN5923A	661	1880.0	30.5	29.63	19.5	-0.09	0.0748	0.09	0.116	0.14	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	18.1	0.0022	0.0892	0.14	0.138	0.21	A55
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	20.2	-0.011	0.0663	0.08	0.0882	0.11	A56
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	19.4	-0.05	0.118	0.19	0.19	0.30	
802.11b, 1 Mbps	SNN5923A	6	2437		19.16	19.8	0.13	0.0072	0.01	0.0162	0.02	
802.11a, 6 Mbps	SNN5923A	36	5200		15.56	18.4	0.02	0.0247	0.02	0.0584	0.06	
802.11a, 6 Mbps	SNN5923A	157	5785		20.09	19.0	-0.14	0.0152	0.02	0.0356	0.04	

Table 4-5: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

Body-Worn Accessory Position, Back of Phone 25 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	19.4	0.019	0.267	0.27	0.402	0.40	A50
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	19.4	-0.01	0.166	0.17	0.260	0.26	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	19.8	-0.052	0.137	0.14	0.185	0.19	A51
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	19.8	0.04	0.079	0.08	0.114	0.11	
CDMA 800, TDSO SO32	SNN5923A	384	836.52	25.0	24.83	19.5	0.06	0.301	0.31	0.425	0.44	
CDMA 1900, TDSO SO32	SNN5923A	600	1880.0	25.0	24.92	18.2	-0.03	0.176	0.18	0.284	0.29	
GSM 850, CS Voice	SNN5923A	190	836.6	33.5	32.86	20.5	-0.10	0.0803	0.10	0.107	0.13	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.9	0.00	0.128	0.20	0.182	0.29	
GSM 1900, CS Voice	SNN5923A	661	1880.0	30.5	29.63	19.4	-0.09	0.0732	0.09	0.116	0.14	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	18.2	0.06	0.0865	0.13	0.136	0.21	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	20.2	-0.05	0.06	0.07	0.0852	0.10	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	19.4	-0.023	0.128	0.20	0.198	0.31	A57
802.11b, 1 Mbps	SNN5923A	6	2437		19.16	19.8	-0.099	0.0283	0.03	0.0505	0.05	A58
802.11a, 6 Mbps	SNN5923A	36	5200		15.56	18.4	-0.066	0.0867	0.09	0.190	0.19	A59
802.11a, 6 Mbps	SNN5923A	157	5785		20.09	19.1	-0.106	0.0344	0.04	0.0825	0.08	A60

Table 4-6: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

4.4 Mobile Hotspot Exposure Results



Mobile Hotspot Surfaces/Edges for SAR testing						
Mode	Front	Back	Left	Right	Top	Bottom
LTE Bands 4/13	Yes	Yes	Yes	Yes	No	Yes
CDMA	Yes	Yes	Yes	Yes	No	Yes
GSM	Yes	Yes	Yes	Yes	No	Yes
WCDMA	Yes	Yes	Yes	Yes	No	Yes
Wi-Fi	Yes	Yes	Yes	No	Yes	No

Mobile Hotspot Position, Front of Phone 10 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	19.3	-0.01	0.479	0.48	0.757	0.76	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	19.3	0.02	0.390	0.39	0.615	0.62	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		19.2	-0.04	0.266	0.27	0.420	0.42	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		19.2	0.16	0.263	0.26	0.419	0.42	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.0	-0.08	0.386	0.39	0.505	0.51	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	19.3	-0.07	0.244	0.25	0.347	0.35	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		20.0	-0.31	0.171	0.18	0.224	0.24	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.04	0.191	0.19	0.252	0.25	
CDMA 800, EVDO Rel. 0 (RTAP)	SNN5923A	384	836.52	23		19.8	-0.25	0.291	0.31	0.379	0.40	
CDMA 1900, EVDO REL. 0 (RTAP)	SNN5923A	600	1880.0	21		19.3	-0.00678	0.465	0.47	0.733	0.73	A65
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.6	-0.16	0.211	0.35	0.299	0.49	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.3	-0.090	0.319	0.50	0.502	0.78	A67
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.0	-0.09	0.31	0.38	0.439	0.54	
WCDMA 1900, RMC	SNN5923A	9262	1852.4	24.0	22.17	19.0	-0.01	0.521	0.80	0.841	1.28	
WCDMA 1900, RMC	SNN5923A	9400	1880	24.0	22.08	19.0	-0.08	0.456	0.72	0.746	1.18	
WCDMA 1900, RMC	SNN5923A	9538	1907.6	24.0	22.21	19.0	-0.14	0.436	0.68	0.726	1.13	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.8	-0.09	0.0268	0.03	0.0526	0.05	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	0.20	0.00481	0.00	0.0184	0.02	

Table 4-7: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

Mobile Hotspot Position, Back of Phone 10 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	19.3	-0.04	0.565	0.57	0.905	0.91	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	19.3	0.05	0.472	0.47	0.762	0.76	
LTE B4, 20 MHz BW QPSK (100% RB)	SNN5923A	20175	1732.5	23.0	23.12	19.3	-0.02	0.452	0.45	0.734	0.74	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		19.2	0.05	0.306	0.31	0.487	0.49	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		19.2	-0.09	0.303	0.31	0.498	0.51	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	18.9	-0.02	0.320	0.32	0.446	0.45	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	19.2	0.00	0.280	0.28	0.406	0.41	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		20.0	0.06	0.176	0.18	0.243	0.24	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.09	0.207	0.21	0.287	0.29	
CDMA 800, EVDO REL. 0 (RTAP)	SNN5923A	384	836.52	23		19.8	-0.00344	0.312	0.31	0.442	0.44	A64
CDMA 1900, EVDO REL. 0 (RTAP)	SNN5923A	600	1880.0	21		19.3	0.04	0.458	0.46	0.72	0.72	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.6	-0.05	0.217	0.35	0.305	0.49	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.0	0.12	0.283	0.43	0.489	0.74	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.1	-0.02	0.283	0.34	0.398	0.49	
WCDMA 1900, RMC	SNN5923A	9262	1852.4	24.0	22.17	19.0	-0.03	0.531	0.81	0.875	1.34	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	19.0	0.04	0.49	0.76	0.841	1.31	
WCDMA 1900, RMC	SNN5923A	9538	1907.6	24.0	22.21	19.0	-0.06	0.471	0.72	0.828	1.27	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.4	-0.01	0.0545	0.05	0.114	0.11	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	-0.02	0.0125	0.01	0.0367	0.04	

Table 4-8: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

Mobile Hotspot Position, Left Edge of Phone 10 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	19.2	-0.01	0.314	0.31	0.592	0.59	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	19.2	-0.08	0.266	0.27	0.499	0.51	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		19.3	0.03	0.132	0.13	0.246	0.25	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		19.3	0.07	0.140	0.14	0.261	0.26	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.0	-0.051	0.375	0.38	0.540	0.55	A63
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	18.8	0.07	0.238	0.24	0.351	0.35	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		20.0	0.04	0.174	0.17	0.251	0.25	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		20.0	-0.02	0.194	0.19	0.279	0.28	
CDMA 800, EVDO REL. 0 (RTAP)	SNN5923A	384	836.52	23		19.8	0.03	0.104	0.10	0.152	0.15	
CDMA 1900, EVDO REL. 0 (RTAP)	SNN5923A	600	1880.0	21		19.3	0.00	0.0704	0.07	0.122	0.12	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.6	-0.03	0.186	0.30	0.276	0.44	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.0	-0.06	0.0485	0.07	0.0854	0.13	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.2	-0.02	0.277	0.34	0.411	0.50	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	19	-0.09	0.0709	0.11	0.125	0.20	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.4	-0.081	0.107	0.11	0.234	0.24	A70
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	-0.081	0.00963	0.01	0.0452	0.05	A71

Table 4-9: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

Mobile Hotspot Position, Right Edge of Phone 10 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
CDMA 800, EVDO REL. 0 (RTAP)	SNN5923A	384	836.52	23		19.8	-0.05	0.168	0.17	0.242	0.24	
CDMA 1900, EVDO REL. 0 (RTAP)	SNN5923A	600	1880.0	21		19.3	-0.04	0.31	0.31	0.52	0.52	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.7	-0.161	0.222	0.36	0.323	0.53	A66
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.0	-0.08	0.218	0.34	0.385	0.60	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.0	-0.00159	0.347	0.42	0.504	0.61	A68
WCDMA 1900, RMC	SNN5923A	9262	1852.4	24.0	22.17	20.3	0.08	0.342	0.52	0.576	0.88	
WCDMA 1900, RMC	SNN5923A	9400	1880.0	24.0	22.08	19.0	-0.03	0.322	0.50	0.568	0.89	
WCDMA 1900, RMC	SNN5923A	9538	1907.6	24.0	22.21	20.3	-0.24	0.289	0.46	0.492	0.79	

Table 4-10: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

Mobile Hotspot Position, Top Edge of Phone 10 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
802.11b, 1 Mbps	SNN5923A	6	2437	15		19.4	-0.11	0.00634	0.01	0.0141	0.01	
802.11a, 6 Mbps	SNN5923A	157	5785	11		19.1	0.48	0.000	0.00	0.000	0.00	

Table 4-11: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

Mobile Hotspot Position, Bottom Edge of Phone 10 mm from Phantom												
Mode	Battery/ Accessory	Channel	f (MHz)	DUT Power		Temp (°C)	Drift (dB)	10 g SAR value		1 g SAR value		Plot Page
				Maximum (dBm)	Measured (dBm)			Measured (W/kg)	Corrected (W/kg)	Measured (W/kg)	Corrected (W/kg)	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	24.0	24.15	19.1	-0.051	0.529	0.54	0.912	0.92	A62
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	23.0	23.23	19.1	-0.01	0.438	0.44	0.772	0.77	
LTE B4, 20 MHz BW QPSK (100% RB)	SNN5923A	20175	1732.5	23.0	23.12	19.1	-0.01	0.429	0.43	0.755	0.76	
LTE B4, 20 MHz BW QPSK (1 RB @ Low)	SNN5923A	20175	1732.5	19		19.3	0.02	0.252	0.25	0.432	0.43	
LTE B4, 20 MHz BW QPSK (50% RB @ Low)	SNN5923A	20175	1732.5	19		19.3	0.05	0.264	0.26	0.451	0.45	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	24.0	24.38	20.0	0.02	0.282	0.28	0.501	0.50	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	23.0	23.31	18.8	-0.02	0.160	0.16	0.262	0.26	
LTE B13, 10 MHz BW QPSK (1 RB @ High)	SNN5923A	23230	782	20.5		19.9	0.00	0.117	0.12	0.205	0.21	
LTE B13, 10 MHz BW QPSK (50% RB @ Low)	SNN5923A	23230	782	20.5		19.9	-0.05	0.117	0.12	0.207	0.21	
CDMA 800, EVDO REL. 0 (RTAP)	SNN5923A	384	836.52	23		19.8	0.06	0.0673	0.07	0.11	0.11	
CDMA 1900, EVDO REL. 0 (RTAP)	SNN5923A	600	1880.0	21		19.3	0.01	0.302	0.30	0.603	0.60	
GSM 850, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	190	836.6	28.0	26.02	18.7	0.04	0.0368	0.06	0.0599	0.09	
GSM 1900, GPRS Class 12 (4 Uplink Timeslots)	SNN5923A	661	1880.0	25.0	23.18	19.3	0.02	0.229	0.35	0.446	0.68	
WCDMA 850, RMC	SNN5923A	4180	836.0	24.0	23.16	19.5	0.05	0.0628	0.08	0.102	0.12	
WCDMA 1900, RMC	SNN5923A	9262	1852.4	24.0	22.17	19.0	0.05	0.346	0.53	0.713	1.09	
WCDMA 1900, RMC	SNN5923A	9400	1880	24.0	22.08	19.0	0.07	0.391	0.61	0.804	1.25	
WCDMA 1900, RMC	SNN5923A	9538	1907.6	24.0	22.21	19.0	-0.080	0.481	0.74	0.975	1.50	A69
WCDMA 1900, RMC	SNN5923A	9538	1907.6	24.0	22.21	18.7	-0.16	0.443	0.69	0.881	1.38	

Table 4-12: SAR measurement results in a body-adjacent position against the ICNIRP and ANSI SAR Limit.

4.5 Measurement Variability Analysis

Per FCC KDB 865664 D01, SAR measurement variability was assessed for each frequency band as determined by the SAR probe calibration points and tissue-equivalent mediums used for the device measurements. These additional measurements are executed after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The phone was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for these measurements, to minimize any unexpected variations in the repeated results.

SAR measurement variability was assessed using the following procedures for each frequency band:

1. If the original highest measured SAR is $< 0.8 \text{ W/kg}$, the following steps do not apply and no repeat measurements were executed.
2. If the original highest measured SAR is $\geq 0.8 \text{ W/kg}$, that measurement was repeated once.
3. If the ratio of the largest to smallest SAR for the original and first repeated measurement was > 1.2 , or if the original or first repeated measurement was $\geq 1.45 \text{ W/kg}$, the measurement was repeated a second time.
4. If the ratio of the largest to smallest SAR for the original, first repeated, or second repeated measurement was > 1.2 , and one of those measurements was $\geq 1.5 \text{ W/kg}$, the measurement was repeated a third time.


SAR Measurement Variability Results									
Mode	Exposure Condition	Channel	f (MHz)	Original Measured SAR (W/kg)	1st Repeated SAR (W/kg)	Ratio	2nd Repeated SAR (W/kg)	Ratio	3rd Repeated SAR (W/kg)
CDMA 1900, RC3 S055	Right Cheek-Touch Position	600	1880.0	1.35	1.31	1.03			
WCDMA 1900, RMC Mode	Mobile Hotspot Position, Bottom Edge of Phone 10 mm from Phantom	9538	1907.6	0.975	0.881	1.11			

Table 4-13: SAR measurement results for Variability Analysis

4.6 Description and Evaluation of Simultaneous Transmitters

Per FCC KDB 447498 D01, the necessity of simultaneous SAR testing was evaluated for the licensed and unlicensed transmitters of the phone under test.

By design some or all of the transmitters built into the phone may operate simultaneously, as described in the tables on the following pages. A simplified model of the transmit paths and a diagram of the separation distances between the transmitting antennas are provided below.



When standalone SAR test exclusion applies to a mode and antenna that transmits simultaneously with other modes and antennas, the KDB directs that the standalone SAR of that mode must be estimated for evaluation in the SAR summations.

For simultaneous SAR evaluation, Bluetooth SAR was estimated and included in all applicable SAR summations. For Body-Worn Accessory simultaneous SAR evaluation, the value used for inclusion in these summations was found to be:

$$\frac{[10.728]_{(mW)}}{[25]_{(mm)}} \times \frac{\sqrt{2.44_{(GHz)}}}{7.5} = 0.1 W/kg_{(estimated)}$$

Note that Head-Adjacent exposure configurations are not applicable to Bluetooth operation, and therefore were not considered for simultaneous evaluation. Further, Bluetooth and Wi-Fi share the same transmit path, and cannot transmit simultaneously.

A description of the power conditions or reduced limits for simultaneous transmit modes is provided in section 2.5 and in expanded detail in Exhibit 12. The notation used in the “Exposure Condition” tables is as follows for the *PWR* column:

- *MAX* indicates the transmitter in this case has no reduced power limit enforced and may operate up to its maximum power, and no conditions are contingent on this transmitter’s operation.
- *>18* and *≤18* indicate the transmitter’s power (in dBm) is monitored as a condition for enforcing the other power limit reductions in this case.
- *11, 15, 19, 20.5, 21, and 23* indicate an enforced power limit, at the value stated in dBm, on the noted transmitter for this simultaneous transmit case.

Per FCC KDB 447498 D01 section 4.3.2, when the sum of the 1 g SAR values of all simultaneously transmitting antennas and device modes in an exposure condition is within the SAR limit, that simultaneous transmission configuration may be excluded from SAR measurements. Simultaneous SAR summations for the head-adjacent, body-worn accessory, and mobile hotspot exposure conditions with the worst-case SAR transmitter configurations are presented in the following tables.

Head Exposure Conditions; Simultaneous Transmit Configurations, including Power Conditions or Reduced Limits							
Case	Transmitter #1		Transmitter #2		Transmitter #3		Notes
	Transmitter Configuration	PWR	Transmitter Configuration	PWR	Transmitter Configuration	PWR	
H1	CDMA 800	>18	LTE B4	19			SVLTE
H2	CDMA 800	≤18	LTE B4	MAX			SVLTE
H3	CDMA 800	>18	LTE B13	20.5			SVLTE
H4	CDMA 800	≤18	LTE B13	MAX			SVLTE
H5	CDMA 800	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
H6	CDMA 800	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
H7	CDMA 1900	>18	LTE B4	19			SVLTE
H8	CDMA 1900	≤18	LTE B4	MAX			SVLTE
H9	CDMA 1900	>18	LTE B13	20.5			SVLTE
H10	CDMA 1900	≤18	LTE B13	MAX			SVLTE
H11	CDMA 1900	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
H12	CDMA 1900	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
H13	GSM 850	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
H14	GSM 850	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
H15	GSM 1900	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
H16	GSM 1900	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
H17	WCDMA 850	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
H18	WCDMA 850	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
H19	WCDMA 1900	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
H20	WCDMA 1900	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
H21	CDMA 800	23	LTE B4	19	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
H22	CDMA 800	23	LTE B4	19	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
H23	CDMA 800	23	LTE B13	20.5	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
H24	CDMA 800	23	LTE B13	20.5	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
H25	CDMA 1900	21	LTE B4	19	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
H26	CDMA 1900	21	LTE B4	19	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
H27	CDMA 1900	21	LTE B13	20.5	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
H28	CDMA 1900	21	LTE B13	20.5	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
H29	LTE B4	MAX	Wi-Fi 2.4 GHz	15			VoIP while in mobile hotspot
H30	LTE B4	MAX	Wi-Fi 5 GHz	15			VoIP while in mobile hotspot
H31	LTE B13	MAX	Wi-Fi 2.4 GHz	15			VoIP while in mobile hotspot
H32	LTE B13	MAX	Wi-Fi 5 GHz	15			VoIP while in mobile hotspot
H33	GPRS/EDGE 850	MAX	Wi-Fi 2.4 GHz	15			VoIP while in mobile hotspot
H34	GPRS/EDGE 850	MAX	Wi-Fi 5 GHz	15			VoIP while in mobile hotspot
H35	GPRS/EDGE 1900	MAX	Wi-Fi 2.4 GHz	15			VoIP while in mobile hotspot
H36	GPRS/EDGE 850	MAX	Wi-Fi 5 GHz	15			VoIP while in mobile hotspot
H37	1x/EVDO 800	MAX	Wi-Fi 2.4 GHz	15			VoIP while in mobile hotspot
H38	1x/EVDO 800	MAX	Wi-Fi 2.4 GHz	15			VoIP while in mobile hotspot
H39	1x/EVDO 1900	MAX	Wi-Fi 5 GHz	15			VoIP while in mobile hotspot
H40	1x/EVDO 1900	MAX	Wi-Fi 5 GHz	15			VoIP while in mobile hotspot

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case H1	Case H3	Case H5	Case H6
Band		CDMA 800	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	CDMA 800 + LTE Band 4	CDMA 800 + LTE Band 13	CDMA 800 + Wi-Fi 2.4 GHz	CDMA 800 + Wi-Fi 5 GHz
Power Condition or Reduced Limit		>18 or MAX	19 dBm	20.5 dBm	15 dBm	15 dBm				
Position	Left Head Check	0.59	0.23	0.28	0.13	0.27	0.82	0.87	0.72	0.86
	Left Head 15° Tilt	0.42	0.16	0.14	0.07	0.31	0.58	0.56	0.49	0.73
	Right Head Check	0.68	0.13	0.18	0.42	0.40	0.81	0.86	1.1	1.08
	Right Head 15° Tilt	0.40	0.16	0.10	0.17	0.29	0.56	0.5	0.57	0.69

Table 4-14: SAR summations for simultaneous evaluation – CDMA 800 in Head Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)			1 g SAR Summations (W/kg)	
					Case H2	Case H4
Band		CDMA 800	LTE Band 4	LTE Band 13	CDMA 800 + LTE Band 4	CDMA 800 + LTE Band 13
Power Condition or Reduced Limit		≤18	MAX	MAX		
Position	Left Head Check	0.10	0.77	0.45	0.87	0.55
	Left Head 15° Tilt	0.09	0.52	0.23	0.61	0.32
	Right Head Check	0.11	0.41	0.29	0.42	0.40
	Right Head 15° Tilt	0.07	0.44	0.15	0.51	0.22

Table 4-15: SAR summations for simultaneous evaluation – CDMA 800 in Head Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case H7	Case H9	Case H11	Case H12
Band		CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	CDMA 1900 + LTE Band 4	CDMA 1900 + LTE Band 13	CDMA 1900 + Wi-Fi 2.4 GHz	CDMA 1900 + Wi-Fi 5 GHz
Power Condition or Reduced Limit		>18 or MAX	19 dBm	20.5 dBm	15 dBm	15 dBm				
Position	Left Head Check	0.67	0.23	0.28	0.13	0.27	0.9	0.95	0.8	0.94
	Left Head 15° Tilt	0.61	0.16	0.14	0.07	0.31	0.77	0.75	0.68	0.92
	Right Head Check	1.39	0.13	0.18	0.42	0.40	1.52	1.57	>1.60	>1.60
	Right Head 15° Tilt	0.53	0.16	0.10	0.17	0.29	0.69	0.63	0.7	0.82

Table 4-16: SAR summations for simultaneous evaluation – CDMA 1900 in Head Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)			1 g SAR Summations (W/kg)	
					Case H8	Case H10
Band		CDMA 1900	LTE Band 4	LTE Band 13	CDMA 1900 + LTE Band 4	CDMA 1900 + LTE Band 13
Power Condition or Reduced Limit		≤18	MAX	MAX		
Position	Left Head Check	0.21	0.77	0.45	0.98	0.66
	Left Head 15° Tilt	0.16	0.52	0.23	0.68	0.39
	Right Head Check	0.34	0.41	0.29	0.75	0.63
	Right Head 15° Tilt	0.13	0.44	0.15	0.57	0.28

Table 4-17: SAR summations for simultaneous evaluation – CDMA 1900 in Head Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case H13	Case H14	Case H15	Case H16
Band		GSM 850	GSM 1900	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	GSM 850 + Wi-Fi 2.4 GHz	GSM 850 + Wi-Fi 5 GHz	GSM 1900 + Wi-Fi 2.4 GHz	GSM 1900 + Wi-Fi 5 GHz
Power Condition or Reduced Limit		MAX	MAX	15 dBm	15 dBm				
Position	Left Head Cheek	0.21	0.36	0.13	0.27	0.34	0.48	0.49	0.63
	Left Head 15° Tilt	0.15	0.33	0.07	0.31	0.22	0.46	0.40	0.64
	Right Head Cheek	0.24	0.71	0.42	0.40	0.66	0.64	1.13	1.11
	Right Head 15° Tilt	0.14	0.28	0.17	0.29	0.31	0.43	0.45	0.57

Table 4-18: SAR summations for simultaneous evaluation – GSM in Head Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case H17	Case H18	Case H19	Case H20
Band		WCDMA 850	WCDMA 1900	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	WCDMA 850 + Wi-Fi 2.4 GHz	WCDMA 850 + Wi-Fi 5 GHz	WCDMA 1900 + Wi-Fi 2.4 GHz	WCDMA 1900 + Wi-Fi 5 GHz
Power Condition or Reduced Limit		MAX	MAX	15 dBm	15 dBm				
Position	Left Head Cheek	0.28	0.67	0.13	0.27	0.41	0.55	0.80	0.94
	Left Head 15° Tilt	0.19	0.60	0.07	0.31	0.26	0.50	0.67	0.91
	Right Head Cheek	0.29	1.33	0.42	0.40	0.71	0.69	>1.60	>1.60
	Right Head 15° Tilt	0.20	0.50	0.17	0.29	0.37	0.49	0.67	0.79

Table 4-19: SAR summations for simultaneous evaluation – WCDMA in Head Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case H21	Case H22	Case H23	Case H24
Band		CDMA 800	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	CDMA 800 + LTE Band 4 + Wi-Fi 2.4 GHz	CDMA 800 + LTE Band 4 + Wi-Fi 5.785 GHz	CDMA 800 + LTE Band 13 + Wi-Fi 2.4 GHz	CDMA 800 + LTE Band 13 + Wi-Fi 5.785 GHz
Power Condition or Reduced Limit		23 dBm	19 dBm	20.5 dBm	15 dBm	11 dBm				
Position	Left Head Cheek	0.34	0.23	0.28	0.13	0.04	0.70	0.61	0.75	0.66
	Left Head 15° Tilt	0.26	0.16	0.14	0.07	0.05	0.49	0.47	0.47	0.45
	Right Head Cheek	0.38	0.13	0.18	0.42	0.03	0.93	0.54	0.98	0.59
	Right Head 15° Tilt	0.22	0.16	0.10	0.17	0.02	0.55	0.40	0.49	0.34

Table 4-20: SAR summations for simultaneous evaluation – CDMA 800 in Head Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case H25	Case H26	Case H27	Case H28
Band		CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	CDMA 1900 + LTE Band 4 + Wi-Fi 2.4 GHz	CDMA 1900 + LTE Band 4 + Wi-Fi 5.785 GHz	CDMA 1900 + LTE Band 13 + Wi-Fi 2.4 GHz	CDMA 1900 + LTE Band 13 + Wi-Fi 5.785 GHz
Power Condition or Reduced Limit		21 dBm	19 dBm	20.5 dBm	15 dBm	11 dBm				
Position	Left Head Cheek	0.44	0.23	0.28	0.13	0.04	0.80	0.71	0.85	0.76
	Left Head 15° Tilt	0.35	0.16	0.14	0.07	0.05	0.58	0.56	0.56	0.54
	Right Head Cheek	0.72	0.13	0.18	0.42	0.03	1.27	0.88	1.32	0.93
	Right Head 15° Tilt	0.27	0.16	0.10	0.17	0.02	0.60	0.45	0.54	0.39

Table 4-21: SAR summations for simultaneous evaluation – CDMA 1900 in Head Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case H29	Case H30	Case H31	Case H32
Band		LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	LTE Band 4 +Wi-Fi 2.4 GHz	LTE Band 4 +Wi-Fi 5.785 GHz	LTE Band 13 +Wi-Fi 2.4 GHz	LTE Band 13 +Wi-Fi 5.785 GHz
Power Condition or Reduced Limit		MAX	MAX	15 dBm	11 dBm				
Position	Left Head Cheek	0.77	0.45	0.13	0.04	0.9	0.58	0.81	0.49
	Left Head 15° Tilt	0.52	0.23	0.07	0.05	0.59	0.30	0.57	0.28
	Right Head Cheek	0.41	0.29	0.42	0.03	0.83	0.71	0.44	0.32
	Right Head 15° Tilt	0.44	0.15	0.17	0.02	0.61	0.32	0.46	0.17

Table 4-22: SAR summations for simultaneous evaluation – LTE in Head Positions during VoIP and a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case H33	Case H34	Case H35	Case H36
Band		GPRS 850	GPRS 1900	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	GPRS 850 +Wi-Fi 2.4 GHz	GPRS 850 +Wi-Fi 5.785 GHz	GPRS 1900 +Wi-Fi 2.4 GHz	GPRS 1900 +Wi-Fi 5.785 GHz
Power Condition or Reduced Limit		MAX	MAX	15 dBm	11 dBm				
Position	Left Head Cheek	0.26	0.43	0.13	0.04	0.39	0.56	0.30	0.47
	Left Head 15° Tilt	0.20	0.47	0.07	0.05	0.27	0.54	0.25	0.52
	Right Head Cheek	0.27	0.76	0.42	0.03	0.69	1.18	0.30	0.79
	Right Head 15° Tilt	0.19	0.35	0.17	0.02	0.36	0.52	0.21	0.37

Table 4-23: SAR summations for simultaneous evaluation – GPRS Data in Head Positions during VoIP and a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case H37	Case H38	Case H39	Case H40
Band		EVDO 800	EVDO 1900	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	EVDO 800 +Wi-Fi 2.4 GHz	EVDO 800 +Wi-Fi 5.785 GHz	EVDO 1900 +Wi-Fi 2.4 GHz	EVDO 1900 +Wi-Fi 5.785 GHz
Power Condition or Reduced Limit		23 dBm	21 dBm	15 dBm	11 dBm				
Position	Left Head Cheek	0.33	0.43	0.13	0.04	0.46	0.37	0.56	0.47
	Left Head 15° Tilt	0.20	0.37	0.07	0.05	0.27	0.25	0.44	0.42
	Right Head Cheek	0.37	0.74	0.42	0.03	0.79	0.40	1.16	0.77
	Right Head 15° Tilt	0.24	0.32	0.17	0.02	0.41	0.26	0.49	0.34

Table 4-24: SAR summations for simultaneous evaluation – 1x RTT Data in Head Positions during VoIP and a Mobile Hotspot session

Body-Worn Accessory Exposure Conditions; Simultaneous Transmit Configurations, including Power Conditions or Reduced Limits							
Case	Transmitter #1		Transmitter #2		Transmitter #3		Notes
	Transmitter Configuration	PWR	Transmitter Configuration	PWR	Transmitter Configuration	PWR	
B1	CDMA 800	>18	LTE B4	19			SVLTE
B2	CDMA 800	≤18	LTE B4	MAX			SVLTE
B3	CDMA 800	>18	LTE B13	20.5			SVLTE
B4	CDMA 800	≤18	LTE B13	MAX			SVLTE
B5	CDMA 800	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
B6	CDMA 800	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
B7	CDMA 1900	>18	LTE B4	19			SVLTE
B8	CDMA 1900	≤18	LTE B4	MAX			SVLTE
B9	CDMA 1900	>18	LTE B13	20.5			SVLTE
B10	CDMA 1900	≤18	LTE B13	MAX			SVLTE
B11	CDMA 1900	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
B12	CDMA 1900	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
B13	GSM 850	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
B14	GSM 850	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
B15	GSM 1900	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
B16	GSM 1900	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
B17	WCDMA 850	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
B18	WCDMA 850	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
B19	WCDMA 1900	MAX	Wi-Fi 2.4 GHz	15			Voice + Background Data
B20	WCDMA 1900	MAX	Wi-Fi 5 GHz	15			Voice + Background Data
B21	CDMA 800	23	LTE B4	19	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
B22	CDMA 800	23	LTE B4	19	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
B23	CDMA 800	23	LTE B13	20.5	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
B24	CDMA 800	23	LTE B13	20.5	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
B25	CDMA 1900	21	LTE B4	19	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
B26	CDMA 1900	21	LTE B4	19	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
B27	CDMA 1900	21	LTE B13	20.5	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
B28	CDMA 1900	21	LTE B13	20.5	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
B29	CDMA 800	MAX	Bluetooth	MAX			Voice + BT (Estimated)
B30	CDMA 1900	MAX	Bluetooth	MAX			Voice + BT (Estimated)
B31	GSM 850	MAX	Bluetooth	MAX			Voice + BT (Estimated)
B32	GSM 1900	MAX	Bluetooth	MAX			Voice + BT (Estimated)
B33	WCDMA 850	MAX	Bluetooth	MAX			Voice + BT (Estimated)
B34	WCDMA 1900	MAX	Bluetooth	MAX			Voice + BT (Estimated)
B35	CDMA 800	MAX	Wi-Fi 2.4 GHz	15	Bluetooth	MAX	Voice (w/BT) + Background Data
B36	CDMA 800	MAX	Wi-Fi 5 GHz	11	Bluetooth	MAX	Voice (w/BT) + Background Data
B37	CDMA 1900	MAX	Wi-Fi 2.4 GHz	15	Bluetooth	MAX	Voice (w/BT) + Background Data
B38	CDMA 1900	MAX	Wi-Fi 5 GHz	11	Bluetooth	MAX	Voice (w/BT) + Background Data
B39	1x RTT/EVDO 800	MAX	Bluetooth	MAX			VoIP + BT (Estimated)
B40	1x RTT/EVDO 1900	MAX	Bluetooth	MAX			VoIP + BT (Estimated)
B41	GPRS/EDGE 800	MAX	Bluetooth	MAX			VoIP + BT (Estimated)
B42	GPRS/EDGE 1900	MAX	Bluetooth	MAX			VoIP + BT (Estimated)
B43	LTE B4	MAX	Bluetooth	MAX			VoIP + BT (Estimated)
B44	LTE B13	MAX	Bluetooth	MAX			VoIP + BT (Estimated)

Note that during typical operation, the power of the transmitters is controlled in the manner described in this table. The summations given in the following tables for the Body-Worn Accessory exposure conditions are shown without power conditions or reduced limits enforced, e.g. all SAR values are for transmitters operating at their maximum power levels. As the SAR summations show results below the compliance limit using values from higher-power configurations than allowed during typical operation, compliance with those reductions employed is implied.

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Cases B1, B2	Cases B3, B4	Case B5	Case B6
Band		CDMA 800	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	CDMA 800 + LTE Band 4	CDMA 800 + LTE Band 13	CDMA 800 + Wi-Fi 2.4 GHz	CDMA 800 + Wi-Fi 5 GHz
Position	Front of Phone 25 mm from Phantom	0.50	0.38	0.18	0.02	0.06	0.88	0.68	0.52	0.56
	Back of Phone 25 mm from Phantom	0.44	0.40	0.19	0.05	0.19	0.84	0.63	0.49	0.63

Table 4-25: SAR summations for simultaneous evaluation – CDMA 800 in Body-Worn Accessory Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Cases B7, B8	Cases B9, B10	Case B11	Case B12
Band		CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	CDMA 1900 + LTE Band 4	CDMA 1900 + LTE Band 13	CDMA 1900 + Wi-Fi 2.4 GHz	CDMA 1900 + Wi-Fi 5 GHz
Position	Front of Phone 25 mm from Phantom	0.33	0.38	0.18	0.02	0.06	0.71	0.51	0.35	0.39
	Back of Phone 25 mm from Phantom	0.29	0.40	0.19	0.05	0.19	0.69	0.48	0.34	0.48

Table 4-26: SAR summations for simultaneous evaluation – CDMA 1900 in Body-Worn Accessory Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case B13	Case B14	Case B15	Case B16
Band		GSM 850	GSM 1900	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	GSM 850 + Wi-Fi 2.4 GHz	GSM 850 + Wi-Fi 5 GHz	GSM 1900 + Wi-Fi 2.4 GHz	GSM 1900 + Wi-Fi 5 GHz
Position	Front of Phone 25 mm from Phantom	0.10	0.14	0.02	0.06	0.12	0.16	0.16	0.20
	Back of Phone 25 mm from Phantom	0.13	0.14	0.05	0.19	0.18	0.32	0.19	0.33

Table 4-27: SAR summations for simultaneous evaluation – GSM in Body-Worn Accessory Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)				1 g SAR Summations (W/kg)			
						Case B17	Case B18	Case B19	Case B20
Band		WCDMA 850	WCDMA 1900	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	WCDMA 850 + Wi-Fi 2.4 GHz	WCDMA 850 + Wi-Fi 5 GHz	WCDMA 1900 + Wi-Fi 2.4 GHz	WCDMA 1900 + Wi-Fi 5 GHz
Position	Front of Phone 25 mm from Phantom	0.11	0.30	0.02	0.06	0.13	0.17	0.32	0.36
	Back of Phone 25 mm from Phantom	0.10	0.31	0.05	0.19	0.15	0.29	0.36	0.50

Table 4-28: SAR summations for simultaneous evaluation – WCDMA in Body-Worn Accessory Positions

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case B21	Case B22	Case B23	Case B24
Band		CDMA 800	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	CDMA 800 + LTE Band 4 + Wi-Fi 2.4 GHz	CDMA 800 + LTE Band 4 + Wi-Fi 5.785 GHz	CDMA 800 + LTE Band 13 + Wi-Fi 2.4 GHz	CDMA 800 + LTE Band 13 + Wi-Fi 5.785 GHz
Position	Front of Phone 25 mm from Phantom	0.50	0.38	0.18	0.02	0.06	0.90	0.94	0.70	0.74
	Back of Phone 25 mm from Phantom	0.44	0.40	0.19	0.05	0.19	0.89	1.03	0.68	0.82

Table 4-29: SAR summations for simultaneous evaluation – CDMA 800 in Body-Worn Accessory Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case B25	Case B26	Case B27	Case B28
Band		CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Wi-Fi 5.785 GHz	CDMA 1900 + LTE Band 4 + Wi-Fi 2.4 GHz	CDMA 1900 + LTE Band 4 + Wi-Fi 5.785 GHz	CDMA 1900 + LTE Band 13 + Wi-Fi 2.4 GHz	CDMA 1900 + LTE Band 13 + Wi-Fi 5.785 GHz
Position	Front of Phone 25 mm from Phantom	0.33	0.38	0.18	0.02	0.06	0.73	0.77	0.53	0.57
	Back of Phone 25 mm from Phantom	0.29	0.40	0.19	0.05	0.19	0.74	0.88	0.53	0.67

Table 4-30: SAR summations for simultaneous evaluation – CDMA 1900 in Body-Worn Accessory Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)							1 g SAR Summations (W/kg)					
									Case B29	Case B30	Case B31	Case B32	Case B33	Case B34
Band		CDMA 800	CDMA 1900	GSM 850	GSM 1900	WCDMA 850	WCDMA 1900	Bluetooth (Estimated)	CDMA 800 + BT	CDMA 1900 + BT	GSM 850 + BT	GSM 1900 + BT	WCDMA 850 + BT	WCDMA 1900 + BT
Position	Front of Phone 25 mm from Phantom	0.50	0.33	0.10	0.14	0.11	0.30	0.1	0.60	0.43	0.20	0.24	0.21	0.40
	Back of Phone 25 mm from Phantom	0.44	0.29	0.13	0.14	0.10	0.31	0.1	0.54	0.39	0.23	0.24	0.20	0.41

Table 4-31: SAR summations for simultaneous evaluation – Bluetooth (Estimated) in Body-Worn Accessory Positions

Band		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case B35	Case B36	Case B37	Case B38
		CDMA 800	CDMA 1900	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	Bluetooth (Estimated)	CDMA 800 + BT + Wi-Fi 2.4 GHz	CDMA 800 + BT + Wi-Fi 5 GHz	CDMA 1900 + BT + Wi-Fi 2.4 GHz	CDMA 1900 + BT + Wi-Fi 5 GHz
Position	Front of Phone 25 mm from Phantom	0.50	0.33	0.02	0.06	0.1	0.62	0.66	0.45	0.49
	Back of Phone 25 mm from Phantom	0.44	0.29	0.05	0.19	0.1	0.59	0.73	0.44	0.58

Table 4-32: SAR summations for simultaneous evaluation – CDMA in Voice call (w/BT) and a background data session (WiFi) when in a Body-Worn Accessory Position

Band		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case B39	Case B40	Case B41	Case B42
		1x RTT 800	1x RTT 1900	GPRS 850	GPRS 1900	Bluetooth (Estimated)	1x RTT 800 + BT	1x RTT 1900 + BT	GPRS 850 + BT	GPRS 1900 + BT
Position	Front of Phone 25 mm from Phantom	0.50	0.33	0.31	0.21	0.1	0.60	0.43	0.41	0.31
	Back of Phone 25 mm from Phantom	0.44	0.29	0.29	0.21	0.1	0.54	0.39	0.39	0.31

Table 4-33: SAR summations for simultaneous evaluation – Cellular in VoIP (w/BT) and a background data session (WiFi) when in a Body-Worn Accessory Position

Band		Transmitter Stand-Alone 1 g SAR Values (W/kg)			1 g SAR Summations (W/kg)	
					Case B43	Case B44
		LTE B4	LTE B13	Bluetooth (Estimated)	LTE B4 + BT	LTE B13 + BT
Position	Front of Phone 25 mm from Phantom	0.38	0.18	0.1	0.48	0.28
	Back of Phone 25 mm from Phantom	0.40	0.19	0.1	0.50	0.29

Table 4-34: SAR summations for simultaneous evaluation – LTE in VoIP and a background data session when in a Body-Worn Accessory Position

Mobile Hotspot Exposure Conditions; Simultaneous Transmit Configurations, including Power Conditions or Reduced Limits							
Case	Transmitter #1		Transmitter #2		Transmitter #3		Notes
	Transmitter Configuration	PWR	Transmitter Configuration	PWR	Transmitter Configuration	PWR	
M1	CDMA 800	23	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M2	CDMA 800	23	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M3	CDMA 1900	21	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M4	CDMA 1900	21	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M5	LTE B4	MAX	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M6	LTE B4	MAX	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M7	LTE B13	MAX	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M8	LTE B13	MAX	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M9	GSM 850	MAX	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M10	GSM 850	MAX	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M11	GSM 1900	MAX	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M12	GSM 1900	MAX	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M13	WCDMA 850	MAX	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M14	WCDMA 850	MAX	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M15	WCDMA 1900	MAX	Wi-Fi 2.4 GHz	15			Mobile Hotspot
M16	WCDMA 1900	MAX	Wi-Fi 5.785 GHz	11			Mobile Hotspot
M17	CDMA 800	23	LTE B4	19	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
M18	CDMA 800	23	LTE B4	19	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
M19	CDMA 800	23	LTE B13	20.5	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
M20	CDMA 800	23	LTE B13	20.5	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
M21	CDMA 1900	21	LTE B4	19	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
M22	CDMA 1900	21	LTE B4	19	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot
M23	CDMA 1900	21	LTE B13	20.5	Wi-Fi 2.4 GHz	15	SVLTE during Mobile Hotspot
M24	CDMA 1900	21	LTE B13	20.5	Wi-Fi 5.785 GHz	11	SVLTE during Mobile Hotspot

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
Band		CDMA 800	CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	Case M1	Case M3	Case M5	Case M7
Power Condition or Reduced Limit		23 dBm	21 dBm	MAX	MAX	15 dBm	CDMA 800 + Wi-Fi 2.4 GHz	CDMA 1900 + Wi-Fi 2.4 GHz	LTE Band 4 + Wi-Fi 2.4 GHz	LTE Band 13 + Wi-Fi 2.4 GHz
Position	Front of Phone 10 mm from Phantom	0.40	0.73	0.76	0.51	0.05	0.45	0.78	0.81	0.56
	Back of Phone 10 mm from Phantom	0.44	0.72	0.91	0.45	0.11	0.55	0.83	1.02	0.56
	Left Edge of Phone 10 mm from Phantom	0.15	0.12	0.59	0.55	0.24	0.39	0.36	0.83	0.79
	Right Edge of Phone 10 mm from Phantom	0.24	0.52	0	0	0	0.24	0.52	0	0
	Top Edge of Phone 10 mm from Phantom	0	0	0	0	0.01	0.01	0.01	0.01	0.01
	Bottom Edge of Phone 10 mm from Phantom	0.11	0.60	0.92	0.50	0	0.11	0.60	0.92	0.50

Table 4-35: SAR summations for simultaneous evaluation – Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
Band		CDMA 800	CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 5.785 GHz	Case M2	Case M4	Case M6	Case M8
Power Condition or Reduced Limit		23 dBm	21 dBm	MAX	MAX	11 dBm	CDMA 800 + Wi-Fi 5.785 GHz	CDMA 1900 + Wi-Fi 5.785 GHz	LTE Band 4 + Wi-Fi 5.785 GHz	LTE Band 13 + Wi-Fi 5.785 GHz
Position	Front of Phone 10 mm from Phantom	0.40	0.73	0.76	0.51	0.02	0.42	0.75	0.78	0.53
	Back of Phone 10 mm from Phantom	0.44	0.72	0.91	0.45	0.04	0.48	0.76	0.95	0.49
	Left Edge of Phone 10 mm from Phantom	0.15	0.12	0.59	0.55	0.05	0.20	0.17	0.64	0.60
	Right Edge of Phone 10 mm from Phantom	0.24	0.52	0	0	0	0.24	0.52	0	0
	Top Edge of Phone 10 mm from Phantom	0	0	0	0	0.00	0.00	0.00	0.00	0.00
	Bottom Edge of Phone 10 mm from Phantom	0.11	0.60	0.92	0.50	0	0.11	0.60	0.92	0.50

Table 4-36: SAR summations for simultaneous evaluation – Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
Band		GSM 850	GSM 1900	WCDMA 850	WCDMA 1900	Wi-Fi 2.4 GHz	Case M9	Case M11	Case M13	Case M15
Power Condition or Reduced Limit		MAX	MAX	MAX	MAX	15 dBm	GSM 850 + Wi-Fi 2.4 GHz	GSM 1900 + Wi-Fi 2.4 GHz	WCDMA 850 + Wi-Fi 2.4 GHz	WCDMA 1900 + Wi-Fi 2.4 GHz
Position	Front of Phone 10 mm from Phantom	0.49	0.78	0.54	1.28	0.05	0.54	0.83	0.59	1.33
	Back of Phone 10 mm from Phantom	0.49	0.74	0.49	1.34	0.11	0.60	0.85	0.60	1.45
	Left Edge of Phone 10 mm from Phantom	0.44	0.13	0.50	0.20	0.24	0.68	0.37	0.74	0.44
	Right Edge of Phone 10 mm from Phantom	0.53	0.60	0.61	0.89	0	0.53	0.60	0.61	0.89
	Top Edge of Phone 10 mm from Phantom	0	0	0	0	0.01	0.01	0.01	0.01	0.01
	Bottom Edge of Phone 10 mm from Phantom	0.09	0.68	0.12	1.50	0	0.09	0.68	0.12	1.50

Table 4-37: SAR summations for simultaneous evaluation – Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
Band		GSM 850	GSM 1900	WCDMA 850	WCDMA 1900	Wi-Fi 5.785 GHz	Case M10	Case M12	Case M14	Case M16
Power Condition or Reduced Limit		MAX	MAX	MAX	MAX	11 dBm	GSM 850 + Wi-Fi 5.785 GHz	GSM 1900 + Wi-Fi 5.785 GHz	WCDMA 850 + Wi-Fi 5.785 GHz	WCDMA 1900 + Wi-Fi 5.785 GHz
Position	Front of Phone 10 mm from Phantom	0.49	0.78	0.54	1.28	0.02	0.51	0.80	0.56	1.30
	Back of Phone 10 mm from Phantom	0.49	0.74	0.49	1.34	0.04	0.53	0.78	0.53	1.38
	Left Edge of Phone 10 mm from Phantom	0.44	0.13	0.50	0.20	0.05	0.49	0.18	0.55	0.25
	Right Edge of Phone 10 mm from Phantom	0.53	0.60	0.61	0.89	0	0.53	0.60	0.61	0.89
	Top Edge of Phone 10 mm from Phantom	0	0	0	0	0.00	0.00	0.00	0.00	0.00
	Bottom Edge of Phone 10 mm from Phantom	0.09	0.68	0.12	1.50	0	0.09	0.68	0.12	1.50

Table 4-38: SAR summations for simultaneous evaluation – Positions during a Mobile Hotspot session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case M17	Case M19	Case M21	Case M23
Band		CDMA 800	CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 2.4 GHz	CDMA 800 + LTE Band 4 + Wi-Fi 2.4 GHz	CDMA 800 + LTE Band 13 + Wi-Fi 2.4 GHz	CDMA 1900 + LTE Band 4 + Wi-Fi 2.4 GHz	CDMA 1900 + LTE Band 13 + Wi-Fi 2.4 GHz
Power Condition or Reduced Limit		23 dBm	21 dBm	19 dBm	20.5 dBm	15 dBm				
Position	Front of Phone 10 mm from Phantom	0.40	0.73	0.42	0.25	0.05	0.87	0.70	1.20	1.03
	Back of Phone 10 mm from Phantom	0.44	0.72	0.51	0.29	0.11	1.06	0.84	1.34	1.12
	Left Edge of Phone 10 mm from Phantom	0.15	0.12	0.26	0.28	0.24	0.65	0.67	0.62	0.64
	Right Edge of Phone 10 mm from Phantom	0.24	0.52	0	0	0	0.24	0.24	0.52	0.52
	Top Edge of Phone 10 mm from Phantom	0	0	0	0	0.01	0.01	0.01	0.01	0.01
	Bottom Edge of Phone 10 mm from Phantom	0.11	0.60	0.45	0.21	0	0.56	0.32	1.05	0.81

Table 4-39: SAR summations for simultaneous evaluation – Positions during a Mobile Hotspot session with a concurrent Voice session

		Transmitter Stand-Alone 1 g SAR Values (W/kg)					1 g SAR Summations (W/kg)			
							Case M18	Case M20	Case M22	Case M24
Band		CDMA 800	CDMA 1900	LTE Band 4	LTE Band 13	Wi-Fi 5.785 GHz	CDMA 800 + LTE Band 4 + Wi-Fi 5.785 GHz	CDMA 800 + LTE Band 13 + Wi-Fi 5.785 GHz	CDMA 1900 + LTE Band 4 + Wi-Fi 5.785 GHz	CDMA 1900 + LTE Band 13 + Wi-Fi 5.785 GHz
Power Condition or Reduced Limit		23 dBm	21 dBm	19 dBm	20.5 dBm	11 dBm				
Position	Front of Phone 10 mm from Phantom	0.40	0.73	0.42	0.25	0.02	0.84	0.67	1.17	1.00
	Back of Phone 10 mm from Phantom	0.44	0.72	0.51	0.29	0.04	0.99	0.77	1.27	1.05
	Left Edge of Phone 10 mm from Phantom	0.15	0.12	0.26	0.28	0.05	0.46	0.48	0.43	0.45
	Right Edge of Phone 10 mm from Phantom	0.24	0.52	0	0	0	0.24	0.24	0.52	0.52
	Top Edge of Phone 10 mm from Phantom	0	0	0	0	0.00	0.00	0.00	0.00	0.00
	Bottom Edge of Phone 10 mm from Phantom	0.11	0.60	0.45	0.21	0	0.56	0.32	1.05	0.81


Table 4-40: SAR summations for simultaneous evaluation – Positions during a Mobile Hotspot session with a concurrent Voice session

Per the preceding analysis, the following configurations and transmitter combinations required further investigation:

- H11. Right Cheek, CDMA 1900 + Wi-Fi 2.4 GHz
- H12. Right Cheek, CDMA 1900 + Wi-Fi 5 GHz
- H19. Right Cheek, WCDMA 1900 + Wi-Fi 5 GHz
- H20. Right Cheek, WCDMA 1900 + Wi-Fi 5 GHz

The guidelines provided in FCC KDB 447498 D01 were utilized for evaluation of the need for simultaneous transmission SAR measurements. These guidelines direct that if the SAR-to-peak location separation ratio (SPLSR) for a pair of antennas is ≤ 0.04 then SAR measurement for simultaneous transmission is not required. Overlaid SAR plots, separation distances between RF peaks, and demonstration of these calculations are provided below for each noted case. Calculations of peak separation distances were evaluated per SPEAG Technical Note "Calculation of the Distance between Two Hotspot", *TN_110209_DASY_Calculate_HotSpot_Distance.pdf*.


Case H11: Right Cheek, CDMA 1900 + Wi-Fi 2.4 GHz



CDMA 1900 Right Head Cheek SAR overlaid with Wi-Fi 2.4 GHz Right Head Cheek SAR

Transmitter	1-g SAR
CDMA 1900	1.39
Wi-Fi 2.4 GHz	0.42
Sum ^{1.5}	2.43
Peak separation distance	92.1 mm
SPLSR	0.03


As the SPLSR is less than or equal to 0.04, no measurements to determine the aggregate 1-g SAR were required for this case.

Case H12: Right Cheek, CDMA 1900 + Wi-Fi 5 GHz

CDMA 1900 Right Head Cheek SAR overlaid with Wi-Fi 5 GHz Right Head Cheek SAR

Transmitter	1-g SAR
CDMA 1900	1.39
Wi-Fi 5 GHz	0.40
Sum ^{1.5}	2.39
Peak separation distance	71.2 mm
<i>SPLSR</i>	0.03


As the SPLSR is less than or equal to 0.04, no measurements to determine the aggregate 1-g SAR were required for this case.

Case H19: Right Cheek, WCDMA 1900 + Wi-Fi 2.4 GHz

WCDMA 1900 Right Head Cheek SAR overlaid with Wi-Fi 2.4 GHz Right Head Cheek SAR

Transmitter	1-g SAR
CDMA 1900	1.33
Wi-Fi 5 GHz	0.42
Sum ^{1.5}	2.31
Peak separation distance	93.3 mm
<i>SPLSR</i>	0.02

As the SPLSR is less than or equal to 0.04, no measurements to determine the aggregate 1-g SAR were required for this case.

Case H20: Right Cheek, WCDMA 1900 + Wi-Fi 5 GHz

WCDMA 1900 Right Head Cheek SAR overlaid with Wi-Fi 5 GHz Right Head Cheek SAR

Transmitter	1-g SAR
CDMA 1900	1.33
Wi-Fi 5 GHz	0.40
Sum ^{1.5}	2.27
Peak separation distance	72.1 mm
<i>SPLSR</i>	0.03

As the SPLSR is less than or equal to 0.04, no measurements to determine the aggregate 1-g SAR were required for this case.

5 References to Test Standards and Guidance

- [1] CENELEC, EN 62209-1:2006 “Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)”
- [2] CENELEC, EN 50360:2001 “Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)”.
- [3] ANSI / IEEE, C95.1 1992 Edition “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”
- [4] FCC OET Bulletin 65 Supplement C 01-01
- [5] IEEE 1528 2003 Edition “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”
- [6] ICNIRP Guidelines “Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz)”
- [7] IC RSS-102 “Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
- [8] IC Notice 2012-DRS1203 “RE: Applicability of Latest FCC RF Exposure KDB Procedures (Publication Date: October 24, 2012) and Other Procedures”
- [9] CENELEC, EN 62209-2:2010 “Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)”
- [10] FCC KDB Publication 248227 D01 v01r02 “SAR Measurement Procedures for 802.11 a/b/g Transmitters”
- [11] FCC KDB Publication 447498 D01 v05 “Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies”
- [12] FCC KDB Publication 648474 D04 v01 “SAR Evaluation Considerations for Wireless Handsets”
- [13] FCC KDB Publication 865664 D01 v01 “SAR Measurement Requirements for 100 MHz to 6 GHz”
- [14] FCC KDB Publication 865664 D02 v01 “RF Exposure Compliance Reporting and Documentation Considerations”
- [15] FCC KDB Publication 941225 D01 v02 “SAR Measurement Procedures for 3G Devices”
- [16] FCC KDB Publication 941225 D03 v01 “Recommended SAR Test Reduction Procedures for GSM/GPRS/EDGE”
- [17] FCC KDB Publication 941225 D05 v02r01 “SAR Evaluation Considerations for LTE Devices”
- [18] FCC KDB Publication 941225 D06 v01 “SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities”