



MEASUREMENT REPORT FCC Part 27 LTE

Applicant Name:
Motorola Mobility LLC
8000 West Sunrise Blvd.
Plantation, FL 33322
United States

Date of Testing:
5/17 - 6/10/2013
Test Site/Location:
PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
0Y1305290908.IHD

FCC ID :	IHDT56PE2
APPLICANT:	MOTOROLA MOBILITY LLC

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §27
EUT Type: Portable Handset
Test Device Serial No.: identical prototype [S/N: Unit 2]

Mode	Tx Frequency (MHz)	Emission Designator	Modulation	ERP/EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE Band 13	779.5 - 784.5	4M52G7D	QPSK	0.110	20.42
LTE Band 13	779.5 - 784.5	4M51W7D	16QAM	0.070	18.44
LTE Band 13	782	9M01G7D	QPSK	0.112	20.50
LTE Band 13	782	8M99W7D	16QAM	0.072	18.55
LTE Band 4	1710.7 - 1754.3	1M10G7D	QPSK	0.286	24.56
LTE Band 4	1710.7 - 1754.3	1M09W7D	16QAM	0.147	21.67
LTE Band 4	1711.5 - 1753.5	2M70G7D	QPSK	0.271	24.33
LTE Band 4	1711.5 - 1753.5	2M70W7D	16QAM	0.136	21.32
LTE Band 4	1712.5 - 1752.5	4M51G7D	QPSK	0.281	24.48
LTE Band 4	1712.5 - 1752.5	4M50W7D	16QAM	0.160	22.04
LTE Band 4	1715 - 1750	8M98G7D	QPSK	0.282	24.50
LTE Band 4	1715 - 1750	8M97W7D	16QAM	0.158	21.99
LTE Band 4	1717.5 - 1747.5	13M4G7D	QPSK	0.281	24.49
LTE Band 4	1717.5 - 1747.5	13M4W7D	16QAM	0.155	21.89
LTE Band 4	1720 - 1745	18M0G7D	QPSK	0.279	24.45
LTE Band 4	1720 - 1745	18M0W7D	16QAM	0.156	21.93

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested. I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortaez
President




FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 1 of 64

T A B L E O F C O N T E N T S

FCC PART 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES.....	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.4 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TESTS	6
3.1 MEASUREMENT PROCEDURE	6
3.1 BLOCK C FREQUENCY RANGE	6
3.2 AWS - BASE FREQUENCY BLOCKS	6
3.3 AWS - MOBILE FREQUENCY BLOCKS	6
3.4 OCCUPIED BANDWIDTH	7
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	7
3.6 PEAK-AVERAGE RATIO	7
3.7 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.8 FREQUENCY STABILITY / TEMPERATURE VARIATION	9
4.0 TEST EQUIPMENT CALIBRATION DATA	10
5.0 SAMPLE CALCULATIONS	11
6.0 TEST RESULTS.....	12
6.1 SUMMARY.....	12
6.2 EFFECTIVE RADIATED POWER (ERP)	13
6.3 EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)	14
6.4 CONDUCTED OUTPUT POWER.....	15
6.5 BAND 13 RADIATED SPURIOUS EMISSIONS	19
6.6 BAND 4 RADIATED SPURIOUS EMISSIONS	22
6.7 BAND 13 FREQUENCY STABILITY MEASUREMENTS.....	26
6.8 BAND 4 FREQUENCY STABILITY MEASUREMENTS.....	28
7.0 BAND 13 PLOTS OF EMISSIONS.....	30
8.0 BAND 4 PLOTS OF EMISSIONS.....	37
9.0 CONCLUSION.....	64

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 2 of 64



MEASUREMENT REPORT

FCC Part 27




§2.1033 General Information

APPLICANT: Motorola Mobility LLC
APPLICANT ADDRESS: 8000 West Sunrise Blvd.
 Plantation, FL 33322, United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §27
FCC ID: IHDT56PE2
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: Unit 2 ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: 5/17 - 6/10/2013
TEST REPORT S/N: 0Y1305290908.IHD

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 3 of 64

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 4 of 64

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Motorola Portable Handset FCC ID: IHDT56PE2**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

The EUT was set to continuous transmission at max power through connection to a CMW500 LTE Call Box. All modulations (QPSK, 16QAM), RB sizes and RB offsets were investigated. Worst case emissions are reported.

Additional emissions testing were performed per KDB 648474 D03 v01r02 and the additional worst case emissions are reported herein and identified as WCP. Spurious emissions measurement data was also investigated with the wireless charging pad. The handset was placed on the verified charging pad (FCC ID: A3LEPP100IJWU) under normal conditions and in a simulated call configuration. Only worst case emissions are shown in this report.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0 (BC0, BC1), 850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Band 4, 13 LTE, 802.11a/b/g/n WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

This device supports wireless charging capability with a wireless charging pad.

2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.4 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 5 of 64

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-C-2004) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168) were used in the measurement of the **Motorola Portable Handset** FCC ID: IHDT56PE2.


3.1 Block C Frequency Range

§27.5(b)(3)

Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.


3.2 AWS - Base Frequency Blocks

§27.5(h)



3.3 AWS - Mobile Frequency Blocks

§27.5(h)



FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 6 of 64

3.4 Occupied Bandwidth

§2.1049 RSS-139(2.3)

The implementation of this test is performed by the spectrum analyzer's occupied bandwidth function. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

3.5 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §27.53(f) §27.53(c.5) §27.53(h) RSS-139(6.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for 776-788 MHz band, or 1 MHz or greater for AWS band. However, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30kHz may be employed for 776-788MHz band. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed for AWS band. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.6 Peak-Average Ratio

§27.50(d.5) RSS-139(6.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. For LTE signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 7 of 64

3.7 Radiated Power and Radiated Spurious Emissions

§2.1053 §27.50(b.10) §27.50(d.4) §27.53(f) RSS-139(6.5.1)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ specified in 27.53(d)(g).

FCC ID: IHDT56PE2			FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 8 of 64		

3.8 Frequency Stability / Temperature Variation

§2.1055 §27.5(b) §27.5(h) §27.54 RSS-139(6.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block for Part 24 and 27. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency for Part 22.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 9 of 64

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	1/17/2013	Annual	1/17/2014	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/29/2013	Annual	3/29/2014	N/A
Agilent	8447D	Broadband Amplifier	5/31/2013	Annual	5/31/2014	2443A01900
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Agilent	N5183A	MXG Analog Signal Generator	1/6/2013	Annual	1/6/2014	MY50141900
Agilent	N9030A	PXA Signal Analyzer (44GHz)	1/11/2013	Annual	1/11/2014	MYS2350166
Espec	ESX-2CA	Environmental Chamber	4/16/2013	Annual	4/16/2014	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Biennial	7/22/2013	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	11/7/2012	Biennial	11/7/2014	128338
Mini-Circuits	VHF-1200+	High Pass Filter	1/17/2013	Annual	1/17/2014	30923
Mini-Circuits	VHF-3100+	High Pass Filter	1/17/2013	Annual	1/17/2014	30841
Mini-Circuits	PWR-SENS-4RMS	USB Power Sensor	4/17/2013	Annual	4/17/2014	11210140001
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	10/7/2011	Biennial	10/7/2013	103962
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	6/26/2012	Annual	6/26/2013	100071
Rohde & Schwarz	ESU26	EMI Test Receiver	2/25/2013	Annual	2/25/2014	100342
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/14/2011	Biennial	11/14/2013	9105-2404
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	11/14/2011	Biennial	11/14/2013	9105-2403
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 4-1. Test Equipment

Note:

If the "Cal Date" falls within the testing period, care was taken to ensure that the piece of equipment was used for testing after it has been calibrated.

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 10 of 64

5.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Amplitude/Angle Modulated

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Combination (Audio/Data)

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 11 of 64

6.0 TEST RESULTS

6.1 Summary

Company Name: Motorola Mobility LLC
 FCC ID: IHDT56PE2
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Result	Reference
TRANSMITTER MODE (TX)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section, 7.0, 8.0
2.1051 27.53(f) 27.53(h)	Band Edge / Conducted Spurious Emissions	$> 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Section, 7.0, 8.0
27.50(d.5)	Peak-Average Ratio	$< 13 \text{ dB}$		PASS	Section 8.0
2.1046, 27.50(b.10), 27.50(d.4)	Transmitter Conducted Output Power	N/A		PASS	Section 6.4
27.50(b.10)	Effective Radiated Power (Band 13)	$< 3 \text{ Watts max. ERP}$	RADIATED	PASS	Section 6.2
27.50(d.4)	Equivalent Isotropic Radiated Power (Band 4)	$< 1 \text{ Watts max. EIRP}$		PASS	Section 6.3
2.1053 27.53(f) 27.53(h)	Undesirable Emissions	$< 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section, 6.5, 6.6
2.1055. 27.5(b) 27.54	Frequency Stability	$< 2.5 \text{ ppm}$ (Part 22) and fundamental emissions stay within authorized frequency block (Part 24, 27)		PASS	Section, 6.7, 6.8

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0, 8.0 were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 12 of 64	

6.2 Effective Radiated Power (ERP)

§27.50(b.10)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Margin [dB]
779.50	5	QPSK	Standard	1 / 0	16.66	3.76	V	20.42	0.110	-14.35
782.00	5	QPSK	Standard	1 / 0	16.45	3.81	V	20.26	0.106	-14.51
784.50	5	QPSK	Standard	1 / 0	14.62	3.85	V	18.47	0.070	-16.30
779.50	5	16QAM	Standard	1 / 0	14.68	3.76	V	18.44	0.070	-16.33
782.00	5	16QAM	Standard	1 / 0	13.37	3.81	V	17.18	0.052	-17.59
784.50	5	16QAM	Standard	1 / 0	12.51	3.85	V	16.36	0.043	-18.41
782.00	10	QPSK	Standard	1 / 0	16.74	3.76	V	20.50	0.112	-14.27
782.00	10	16QAM	Standard	1 / 0	14.70	3.85	V	18.55	0.072	-16.22
782.00	10	QPSK	Extended w/ WCP	1 / 0	14.87	3.76	V	18.63	0.073	-16.14

Table 6-2. ERP Data (Band 13)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery and an extended battery with WCP.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the V positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 			Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 13 of 64

6.3 Equivalent Isotropic Radiated Power (EIRP)

§27.50(d.4) RSS-139(6.4)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Margin [dB]
1710.70	1.4	QPSK	Standard	1 / 0	14.37	9.89	H	24.26	0.267	-5.74
1732.50	1.4	QPSK	Standard	1 / 0	14.71	9.85	H	24.56	0.286	-5.44
1754.30	1.4	QPSK	Standard	1 / 0	13.18	9.80	H	22.98	0.199	-7.02
1710.70	1.4	16-QAM	Standard	1 / 0	11.78	9.89	H	21.67	0.147	-8.33
1732.50	1.4	16-QAM	Standard	1 / 0	11.41	9.85	H	21.26	0.134	-8.74
1754.30	1.4	16-QAM	Standard	1 / 0	10.62	9.80	H	20.42	0.110	-9.58
1711.50	3	QPSK	Standard	1 / 0	14.25	9.89	H	24.14	0.259	-5.86
1732.50	3	QPSK	Standard	1 / 0	14.48	9.85	H	24.33	0.271	-5.67
1753.50	3	QPSK	Standard	1 / 0	14.08	9.80	H	23.88	0.245	-6.12
1711.50	3	16-QAM	Standard	1 / 0	11.43	9.89	H	21.32	0.136	-8.68
1732.50	3	16-QAM	Standard	1 / 0	11.37	9.85	H	21.22	0.132	-8.78
1753.50	3	16-QAM	Standard	1 / 0	10.60	9.80	H	20.40	0.110	-9.60
1712.50	5	QPSK	Standard	1 / 24	14.59	9.89	H	24.48	0.281	-5.52
1732.50	5	QPSK	Standard	1 / 0	14.63	9.85	H	24.48	0.280	-5.52
1752.50	5	QPSK	Standard	1 / 0	13.95	9.80	H	23.75	0.237	-6.25
1712.50	5	16-QAM	Standard	1 / 24	12.12	9.89	H	22.01	0.159	-7.99
1732.50	5	16-QAM	Standard	1 / 0	12.19	9.85	H	22.04	0.160	-7.96
1752.50	5	16-QAM	Standard	1 / 0	11.39	9.80	H	21.19	0.132	-8.81
1715.00	10	QPSK	Standard	1 / 49	14.61	9.89	H	24.50	0.282	-5.50
1732.50	10	QPSK	Standard	1 / 49	14.61	9.85	H	24.46	0.279	-5.54
1750.00	10	QPSK	Standard	1 / 0	14.47	9.80	H	24.27	0.268	-5.73
1715.00	10	16-QAM	Standard	1 / 49	11.98	9.89	H	21.87	0.154	-8.13
1732.50	10	16-QAM	Standard	1 / 49	12.14	9.85	H	21.99	0.158	-8.01
1750.00	10	16-QAM	Standard	1 / 0	11.99	9.80	H	21.79	0.151	-8.21
1717.50	15	QPSK	Standard	1 / 36	14.60	9.89	H	24.49	0.281	-5.51
1732.50	15	QPSK	Standard	1 / 36	14.40	9.85	H	24.25	0.266	-5.75
1747.50	15	QPSK	Standard	1 / 0	14.54	9.80	H	24.34	0.272	-5.66
1717.50	15	16-QAM	Standard	1 / 36	12.00	9.89	H	21.89	0.155	-8.11
1732.50	15	16-QAM	Standard	1 / 36	11.92	9.85	H	21.77	0.150	-8.23
1747.50	15	16-QAM	Standard	1 / 0	12.06	9.80	H	21.86	0.154	-8.14
1720.00	20	QPSK	Standard	1 / 50	14.56	9.89	H	24.45	0.279	-5.55
1732.50	20	QPSK	Standard	1 / 50	14.49	9.85	H	24.34	0.271	-5.66
1745.00	20	QPSK	Standard	1 / 50	14.60	9.80	H	24.40	0.276	-5.60
1720.00	20	16-QAM	Standard	1 / 50	11.96	9.89	H	21.85	0.153	-8.15
1732.50	20	16-QAM	Standard	1 / 50	12.04	9.85	H	21.89	0.154	-8.11
1745.00	20	16-QAM	Standard	1 / 50	12.13	9.80	H	21.93	0.156	-8.07
1732.50	1.4	QPSK	Extended w/ WCP	1 / 0	12.33	9.85	H	22.18	0.165	-7.82

Table 6-3. EIRP Data (Band 4)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery and an extended battery with WCP.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 14 of 64

6.4 Conducted Output Power

§27.50(d.4) RSS-139(6.4)

The Motorola **Portable Handset FCC ID: IHDT56PE2** was connected to the CMW500 LTE Callbox via RF cable. Transmit power readings were taken from the CMW500. This unit was tested with a standard battery. Results are reported below.




Figure 6-1. Conducted Output Power Test Setup Diagram

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]
782.0	23230	5	QPSK	1	0	24.04
782.0	23230	5	QPSK	1	12	23.96
782.0	23230	5	QPSK	1	24	23.90
782.0	23230	5	QPSK	12	0	21.94
782.0	23230	5	QPSK	12	6	21.95
782.0	23230	5	QPSK	12	13	21.98
782.0	23230	5	QPSK	25	0	21.99
782.0	23230	5	16-QAM	1	0	22.17
782.0	23230	5	16-QAM	1	12	22.16
782.0	23230	5	16-QAM	1	24	22.06
782.0	23230	5	16-QAM	12	0	21.04
782.0	23230	5	16-QAM	12	6	21.03
782.0	23230	5	16-QAM	12	13	20.96
782.0	23230	5	16-QAM	25	0	21.01
782.0	23230	10	QPSK	1	0	24.23
782.0	23230	10	QPSK	1	25	23.94
782.0	23230	10	QPSK	1	49	23.94
782.0	23230	10	QPSK	25	0	22.00
782.0	23230	10	QPSK	25	12	22.02
782.0	23230	10	QPSK	25	25	21.91
782.0	23230	10	QPSK	50	0	21.93
782.0	23230	10	16QAM	1	0	22.34
782.0	23230	10	16QAM	1	25	22.08
782.0	23230	10	16QAM	1	49	22.08
782.0	23230	10	16QAM	25	0	21.03
782.0	23230	10	16QAM	25	12	20.99
782.0	23230	10	16QAM	25	25	20.95
782.0	23230	10	16QAM	50	0	20.95

Table 6-4. Conducted Power Data (Band 13)

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 15 of 64

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]
1710.7	19957	1.4	QPSK	1	0	23.00
1710.7	19957	1.4	QPSK	1	2	23.00
1710.7	19957	1.4	QPSK	1	5	23.04
1710.7	19957	1.4	QPSK	3	2	23.10
1710.7	19957	1.4	QPSK	6	0	21.21
1710.7	19957	1.4	16-QAM	1	0	20.58
1710.7	19957	1.4	16-QAM	1	2	20.64
1710.7	19957	1.4	16-QAM	1	5	20.68
1710.7	19957	1.4	16-QAM	3	2	21.29
1710.7	19957	1.4	16-QAM	6	0	21.21
1732.5	20175	1.4	QPSK	1	0	23.08
1732.5	20175	1.4	QPSK	1	2	23.08
1732.5	20175	1.4	QPSK	1	5	23.15
1732.5	20175	1.4	QPSK	3	2	23.06
1732.5	20175	1.4	QPSK	6	0	21.19
1732.5	20175	1.4	16-QAM	1	0	21.30
1732.5	20175	1.4	16-QAM	1	2	21.30
1732.5	20175	1.4	16-QAM	1	5	21.37
1732.5	20175	1.4	16-QAM	3	2	21.14
1732.5	20175	1.4	16-QAM	6	0	19.99
1754.3	20393	1.4	QPSK	1	0	22.95
1754.3	20393	1.4	QPSK	1	2	23.01
1754.3	20393	1.4	QPSK	1	5	22.99
1754.3	20393	1.4	QPSK	3	2	23.02
1754.3	20393	1.4	QPSK	6	0	21.13
1754.3	20393	1.4	16-QAM	1	0	20.65
1754.3	20393	1.4	16-QAM	1	2	20.64
1754.3	20393	1.4	16-QAM	1	5	20.63
1754.3	20393	1.4	16-QAM	3	2	21.25
1754.3	20393	1.4	16-QAM	6	0	20.22
1711.5	19965	3	QPSK	1	0	22.89
1711.5	19965	3	QPSK	1	7	22.87
1711.5	19965	3	QPSK	1	14	22.89
1711.5	19965	3	QPSK	8	4	20.98
1711.5	19965	3	QPSK	15	0	20.93
1711.5	19965	3	16-QAM	1	0	20.62
1711.5	19965	3	16-QAM	1	7	20.53
1711.5	19965	3	16-QAM	1	14	20.56
1711.5	19965	3	16-QAM	8	4	19.98
1711.5	19965	3	16-QAM	15	0	19.90
1732.5	20175	3	QPSK	1	0	23.15
1732.5	20175	3	QPSK	1	7	23.18
1732.5	20175	3	QPSK	1	14	23.20
1732.5	20175	3	QPSK	8	4	21.08
1732.5	20175	3	QPSK	15	0	21.14
1732.5	20175	3	16-QAM	1	0	21.30
1732.5	20175	3	16-QAM	1	7	21.34
1732.5	20175	3	16-QAM	1	14	21.38
1732.5	20175	3	16-QAM	8	4	20.11
1732.5	20175	3	16-QAM	15	0	20.23
1753.5	20385	3	QPSK	1	0	23.04
1753.5	20385	3	QPSK	1	7	23.12
1753.5	20385	3	QPSK	1	14	23.12
1753.5	20385	3	QPSK	8	4	21.11
1753.5	20385	3	QPSK	15	0	21.03
1753.5	20385	3	16-QAM	1	0	21.19
1753.5	20385	3	16-QAM	1	7	21.21
1753.5	20385	3	16-QAM	1	14	21.30
1753.5	20385	3	16-QAM	8	4	20.07
1753.5	20385	3	16-QAM	15	0	20.12

Table 6-5. Conducted Power Data (Band 4 - 1.4/3 MHz BW)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 16 of 64	

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]
1712.5	19975	5	QPSK	1	0	22.96
1712.5	19975	5	QPSK	1	12	22.97
1712.5	19975	5	QPSK	1	24	23.00
1712.5	19975	5	QPSK	12	6	21.06
1712.5	19975	5	QPSK	25	0	20.95
1712.5	19975	5	16-QAM	1	0	21.35
1712.5	19975	5	16-QAM	1	12	21.33
1712.5	19975	5	16-QAM	1	24	21.32
1712.5	19975	5	16-QAM	12	6	20.02
1712.5	19975	5	16-QAM	25	0	19.89
1732.5	20175	5	QPSK	1	0	23.21
1732.5	20175	5	QPSK	1	12	23.23
1732.5	20175	5	QPSK	1	24	23.15
1732.5	20175	5	QPSK	12	6	21.19
1732.5	20175	5	QPSK	25	0	21.07
1732.5	20175	5	16-QAM	1	0	21.32
1732.5	20175	5	16-QAM	1	12	21.40
1732.5	20175	5	16-QAM	1	24	21.36
1732.5	20175	5	16-QAM	12	6	20.21
1732.5	20175	5	16-QAM	25	0	20.12
1752.5	20375	5	QPSK	1	0	23.22
1752.5	20375	5	QPSK	1	12	23.01
1752.5	20375	5	QPSK	1	24	23.08
1752.5	20375	5	QPSK	12	6	21.09
1752.5	20375	5	QPSK	25	0	21.02
1752.5	20375	5	16-QAM	1	0	21.37
1752.5	20375	5	16-QAM	1	12	21.21
1752.5	20375	5	16-QAM	1	24	21.26
1752.5	20375	5	16-QAM	12	6	20.16
1752.5	20375	5	16-QAM	25	0	20.05
1715	20000	10	QPSK	1	0	22.99
1715	20000	10	QPSK	1	25	23.04
1715	20000	10	QPSK	1	49	23.13
1715	20000	10	QPSK	25	12	21.01
1715	20000	10	QPSK	50	0	20.87
1715	20000	10	16QAM	1	0	21.15
1715	20000	10	16QAM	1	25	21.07
1715	20000	10	16QAM	1	49	21.25
1715	20000	10	16QAM	25	12	19.97
1715	20000	10	16QAM	50	0	19.86
1732.5	20175	10	QPSK	1	0	23.05
1732.5	20175	10	QPSK	1	25	23.10
1732.5	20175	10	QPSK	1	49	23.22
1732.5	20175	10	QPSK	25	12	21.08
1732.5	20175	10	QPSK	50	0	21.03
1732.5	20175	10	16QAM	1	0	20.75
1732.5	20175	10	16QAM	1	25	20.81
1732.5	20175	10	16QAM	1	49	20.83
1732.5	20175	10	16QAM	25	12	20.11
1732.5	20175	10	16QAM	50	0	20.01
1750	20350	10	QPSK	1	0	23.12
1750	20350	10	QPSK	1	25	23.21
1750	20350	10	QPSK	1	49	23.10
1750	20350	10	QPSK	25	12	21.13
1750	20350	10	QPSK	50	0	20.89
1750	20350	10	16QAM	1	0	21.26
1750	20350	10	16QAM	1	25	21.32
1750	20350	10	16QAM	1	49	21.23
1750	20350	10	16QAM	25	12	20.15
1750	20350	10	16QAM	50	0	19.98

Table 6-6. Conducted Power Data (Band 4 - 5/10 MHz BW)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 17 of 64	

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]
1717.5	20025	15	QPSK	1	0	22.92
1717.5	20025	15	QPSK	1	36	22.95
1717.5	20025	15	QPSK	1	74	23.02
1717.5	20025	15	QPSK	36	18	21.03
1717.5	20025	15	QPSK	75	0	20.91
1717.5	20025	15	16QAM	1	0	21.00
1717.5	20025	15	16QAM	1	36	21.03
1717.5	20025	15	16QAM	1	74	21.07
1717.5	20025	15	16QAM	36	18	19.90
1717.5	20025	15	16QAM	75	0	19.89
1732.5	20175	15	QPSK	1	0	23.07
1732.5	20175	15	QPSK	1	36	23.03
1732.5	20175	15	QPSK	1	74	23.07
1732.5	20175	15	QPSK	36	18	21.00
1732.5	20175	15	QPSK	75	0	20.94
1732.5	20175	15	16QAM	1	0	21.21
1732.5	20175	15	16QAM	1	36	21.14
1732.5	20175	15	16QAM	1	74	21.17
1732.5	20175	15	16QAM	36	18	20.04
1732.5	20175	15	16QAM	75	0	20.02
1747.5	20325	15	QPSK	1	0	23.04
1747.5	20325	15	QPSK	1	36	23.02
1747.5	20325	15	QPSK	1	74	23.05
1747.5	20325	15	QPSK	36	18	21.06
1747.5	20325	15	QPSK	75	0	21.03
1747.5	20325	15	16QAM	1	0	21.21
1747.5	20325	15	16QAM	1	36	21.16
1747.5	20325	15	16QAM	1	74	21.22
1747.5	20325	15	16QAM	36	18	20.11
1747.5	20325	15	16QAM	75	0	20.03
1732.5	20175	20	QPSK	1	0	23.03
1732.5	20175	20	QPSK	1	50	23.06
1732.5	20175	20	QPSK	1	99	23.10
1732.5	20175	20	QPSK	50	25	21.01
1732.5	20175	20	QPSK	100	0	21.08
1732.5	20175	20	16QAM	1	0	21.20
1732.5	20175	20	16QAM	1	50	21.26
1732.5	20175	20	16QAM	1	99	21.25
1732.5	20175	20	16QAM	50	25	19.93
1732.5	20175	20	16QAM	100	0	20.06

Table 6-7. Conducted Power Data (Band 4 - 15/20 MHz BW)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 18 of 64	

6.5 Band 13 Radiated Spurious Emissions

§2.1053 §27.53(f)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 782.00 MHz
 MEASURED OUTPUT POWER: 20.50 dBm = 0.112 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.50 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
2346.00	-60.60	3.59	-57.01	H	77.51
3128.00	-43.80	5.20	-38.59	H	59.10
3910.00	-57.04	6.64	-50.40	H	70.90
4692.00	-68.60	7.48	-61.12	H	81.62
5474.00	-55.00	8.42	-46.58	H	67.08

Table 6-8. Radiated Spurious Data (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 19 of 64

Band 13 Radiated Spurious Emissions 1559 – 1610MHz Band §2.1053 §27.53(f)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 782.00 MHz
 MEASURED OUTPUT POWER: 20.501 dBm = 0.112 W
 MODULATION SIGNAL: QPSK
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

FREQUENCY (MHz)	EMISSION TYPE	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
1564.00	WIDEBAND	-50.94	5.67	-45.27	H	-5.27

Table 6-9. Radiated Spurious Data (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 20 of 64

Band 13 Radiated Spurious Measurements (continued)

§2.1053 §27.53(h) RSS-139(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 782.00 MHz
 MEASURED OUTPUT POWER: 18.63 dBm = 0.073 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 31.63 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
2346.00	-60.60	3.59	-57.01	H	75.64
3128.00	-71.98	5.20	-66.77	H	85.40
3910.00	-57.04	6.64	-50.40	H	69.03
4692.00	-68.60	7.48	-61.12	H	79.75
5474.00	-55.00	8.42	-46.58	H	65.21

Table 6-8. Radiated Spurious Data w/ WCP (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with extended battery charging on a wireless charging pad.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 21 of 64

6.6 Band 4 Radiated Spurious Emissions

§2.1053 §27.53(h) RSS-139(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1712.50 MHz
 MEASURED OUTPUT POWER: 24.48 dBm = 0.281 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 37.48 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3425.00	-54.63	8.09	-46.53	H	71.01
5137.50	-55.87	10.21	-45.66	H	70.14
6850.00	-80.49	11.31	-69.18	H	93.66
8562.50	-54.44	13.02	-41.42	H	65.90
10275.00	-50.51	13.01	-37.50	H	61.98
11987.50	-74.26	13.21	-61.05	H	85.53

Table 6-10. Radiated Spurious Data (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 22 of 64

Band 4 Radiated Spurious Measurements (continued)

§2.1053 §27.53(h) RSS-139(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1732.50 MHz
 MEASURED OUTPUT POWER: 24.48 dBm = 0.280 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) = 37.48$ dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3465.00	-53.48	8.26	-45.21	H	69.69
5197.50	-54.33	10.26	-44.07	H	68.55
6930.00	-80.31	11.42	-68.89	H	93.37
8662.50	-52.98	13.07	-39.92	H	64.39
10395.00	-49.39	13.12	-36.28	H	60.75
12127.50	-74.05	13.25	-60.80	H	85.28

Table 6-11. Radiated Spurious Data (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 23 of 64

Band 4 Radiated Spurious Measurements (continued)

§2.1053 §27.53(h) RSS-139(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1752.50 MHz
 MEASURED OUTPUT POWER: 23.75 dBm = 0.237 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) = 36.75$ dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3505.00	-56.16	8.40	-47.76	H	71.51
5257.50	-55.78	10.32	-45.46	H	69.22
7010.00	-80.17	11.51	-68.66	H	92.41
8762.50	-54.94	13.11	-41.83	H	65.59
10515.00	-51.39	13.20	-38.19	H	61.95
12267.50	-73.90	13.31	-60.58	H	84.34

Table 6-12. Radiated Spurious Data (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with a new/fully charged battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 24 of 64

Band 4 Radiated Spurious Measurements (continued)

§2.1053 §27.53(h) RSS-139(6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1732.50 MHz
 MEASURED OUTPUT POWER: 22.18 dBm = 0.165 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) = 35.18$ dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3465.00	-51.55	8.26	-43.28	H	65.46
5197.50	-54.43	10.26	-44.17	H	66.35
6930.00	-80.31	11.42	-68.89	H	91.07
8662.50	-79.92	13.07	-66.86	H	89.04
10395.00	-77.08	13.12	-63.96	H	86.14
12127.50	-74.05	13.25	-60.80	H	82.98

Table 6-11. Radiated Spurious Data w/ WCP (RB Size 1, RB Offset 0)

NOTES:

1. This device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported in the table above.
2. This unit was tested with extended battery charging on a wireless charging pad.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The "H" positioning is defined with the EUT lying flat on the test surface, the "H2" positioning is defined with the EUT standing up on its side, and the "V" positioning is defined with the EUT standing upright. The worst case test configuration was found with the EUT in the H positioning. The data reported in the table above was measured in this test setup.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 25 of 64

6.7 Band 13 Frequency Stability Measurements

\$2.1055 \$22.355 \$27.5(b) \$27.54

OPERATING FREQUENCY: 782,000,000 Hz

CHANNEL: 23230

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	781,999,995	-5	-0.0000006
100 %		- 30	781,999,997	-3	-0.0000004
100 %		- 20	781,999,995	-5	-0.0000006
100 %		- 10	781,999,996	-4	-0.0000005
100 %		0	781,999,993	-7	-0.0000009
100 %		+ 10	781,999,992	-8	-0.0000010
100 %		+ 20	781,999,993	-7	-0.0000009
100 %		+ 30	781,999,996	-4	-0.0000005
100 %		+ 40	781,999,994	-6	-0.0000008
100 %		+ 50	781,999,990	-10	-0.0000013
115 %	4.37	+ 20	781,999,991	-9	-0.0000012
BATT. ENDPOINT	3.27	+ 20	781,999,992	-8	-0.0000010

Table 6-13. Frequency Stability Data (Band 13)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 26 of 64	

Band 13 Frequency Stability Measurements (Cont'd)

§2.1055 §22.355 §27.5(b) §27.54




Figure 6-2. Frequency Stability Graph (Band 13)

FCC ID: IHDT56PE2			FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 27 of 64

6.8 Band 4 Frequency Stability Measurements

\$2.1055 \$27.54 RSS-139(6.3)

OPERATING FREQUENCY: 1,732,500,000 Hz

CHANNEL: 20175

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (° C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,732,499,986	-14	-0.0000008
100 %		- 30	1,732,499,986	-14	-0.0000008
100 %		- 20	1,732,499,992	-8	-0.0000005
100 %		- 10	1,732,499,988	-12	-0.0000007
100 %		0	1,732,499,997	-3	-0.0000002
100 %		+ 10	1,732,499,987	-13	-0.0000008
100 %		+ 20	1,732,499,993	-7	-0.0000004
100 %		+ 30	1,732,499,996	-4	-0.0000002
100 %		+ 40	1,732,499,997	-3	-0.0000002
100 %		+ 50	1,732,499,992	-8	-0.0000005
115 %	4.37	+ 20	1,732,499,989	-11	-0.0000006
BATT. ENDPOINT	3.27	+ 20	1,732,499,989	-11	-0.0000006

Table 6-14. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 28 of 64

Band 4 Frequency Stability Measurements (Cont'd)

§2.1055 §§27.54 RSS-139(6.3)




Figure 6-3. Frequency Stability Graph (Band 4)

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 29 of 64

7.0 BAND 13 PLOTS OF EMISSIONS

Note: All bandwidths, RB configurations, and modulations were investigated. The worst case test results are reported below.




Plot 7-1. Lower Band Edge Plot (5.0MHz QPSK - RB Size 25)




Plot 7-2. Lower Extended Band Edge Plot (5.0MHz QPSK - RB Size 25)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 30 of 64




Plot 7-3. Occupied Bandwidth Plot (5.0MHz QPSK – RB Size 25)



Plot 7-4. Occupied Bandwidth Plot (5.0MHz 16-QAM – RB Size 25)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 31 of 64




Plot 7-5. Upper Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 7-6. Upper Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 32 of 64




Plot 7-7. Lower Band Edge Plot (10.0MHz QPSK – RB Size 50)




Plot 7-8. Lower Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 33 of 64




Plot 7-9. Occupied Bandwidth Plot (10.0MHz QPSK – RB Size 50)




Plot 7-10. Occupied Bandwidth Plot (10.0MHz 16-QAM – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 34 of 64



Plot 7-11. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0)




Plot 7-12. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 35 of 64



Plot 7-13. Upper Band Edge Plot (10.0MHz QPSK – RB Size 50)



Plot 7-14. Upper Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 36 of 64

8.0 BAND 4 PLOTS OF EMISSIONS

Note: All bandwidths, RB configurations, and modulations were investigated. The worst case test results are reported below.




Plot 8-1. Lower Band Edge Plot (1.4MHz QPSK – RB Size 6)




Plot 8-2. Lower Extended Band Edge Plot (1.4MHz QPSK – RB Size 6)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 37 of 64




Plot 8-3. Occupied Bandwidth Plot (1.4MHz QPSK – RB Size 6)




Plot 8-4. Occupied Bandwidth Plot (1.4MHz 16-QAM – RB Size 6)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 38 of 64




Plot 8-5. Upper Band Edge Plot (1.4MHz QPSK – RB Size 6)




Plot 8-6. Upper Extended Band Edge Plot (1.4MHz QPSK – RB Size 6)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 39 of 64




Plot 8-7. PAR Plot (1.4MHz QPSK – RB Size 6)



Plot 8-8. PAR Plot (1.4MHz 16-QAM – RB Size 6)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 40 of 64




Plot 8-9. Lower Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 8-10. Lower Extended Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 41 of 64




Plot 8-11. Occupied Bandwidth Plot (3.0MHz QPSK – RB Size 15)




Plot 8-12. Occupied Bandwidth Plot (3.0MHz 16-QAM – RB Size 15)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 42 of 64




Plot 8-13. Upper Band Edge Plot (3.0MHz QPSK – RB Size 15)




Plot 8-14. Upper Extended Band Edge Plot (3.0MHz QPSK – RB Size 15)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 43 of 64




Plot 8-15. PAR Plot (3.0MHz QPSK – RB Size 15)




Plot 8-16. PAR Plot (3.0MHz 16-QAM – RB Size 15)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 44 of 64




Plot 8-17. Lower Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 8-18. Lower Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 45 of 64



Plot 8-19. Occupied Bandwidth Plot (5.0MHz QPSK – RB Size 25)




Plot 8-20. Occupied Bandwidth Plot (5.0MHz 16-QAM – RB Size 25)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 46 of 64




Plot 8-21. Upper Band Edge Plot (5.0MHz QPSK – RB Size 25)




Plot 8-22. Upper Extended Band Edge Plot (5.0MHz QPSK – RB Size 25)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 47 of 64




Plot 8-23. PAR Plot (5.0MHz QPSK – RB Size 25)




Plot 8-24. PAR Plot (5.0MHz 16-QAM – RB Size 25)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 48 of 64




Plot 8-25. Lower Band Edge Plot (10.0MHz QPSK – RB Size 50)




Plot 8-26. Lower Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 49 of 64




Plot 8-27. Occupied Bandwidth Plot (10.0MHz QPSK – RB Size 50)




Plot 8-28. Occupied Bandwidth Plot (10.0MHz 16-QAM – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 50 of 64




Plot 8-29. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0– Low Channel)




Plot 8-30. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – Low Channel)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 51 of 64




Plot 8-31. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 8-32. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 52 of 64



Plot 8-33. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)




Plot 8-34. Conducted Spurious Plot (10.0MHz QPSK – RB Size 1, RB Offset 0 – High Channel)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 53 of 64




Plot 8-35. Upper Band Edge Plot (10.0MHz QPSK – RB Size 50)




Plot 8-36. Upper Extended Band Edge Plot (10.0MHz QPSK – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 54 of 64




Plot 8-37. PAR Plot (10.0MHz QPSK – RB Size 50)




Plot 8-38. PAR Plot (10.0MHz 16-QAM – RB Size 50)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 55 of 64




Plot 8-39. Lower Band Edge Plot (15.0MHz QPSK – RB Size 75)




Plot 8-40. Lower Extended Band Edge Plot (15.0MHz QPSK – RB Size 75)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 56 of 64




Plot 8-41. Occupied Bandwidth Plot (15.0MHz QPSK – RB Size 75)




Plot 8-42. Occupied Bandwidth Plot (15.0MHz 16-QAM – RB Size 75)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 57 of 64




Plot 8-43. Upper Band Edge Plot (15.0MHz QPSK – RB Size 75)




Plot 8-44. Upper Extended Band Edge Plot (15.0MHz QPSK – RB Size 75)

FCC ID: IHDT56PE2	 FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset	Page 58 of 64




Plot 8-45. PAR Plot (15.0MHz QPSK – RB Size 75)




Plot 8-46. PAR Plot (15.0MHz 16-QAM – RB Size 75)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 59 of 64




Plot 8-47. Lower Band Edge Plot (20.0MHz QPSK – RB Size 100)




Plot 8-48. Lower Extended Band Edge Plot (20.0MHz QPSK – RB Size 100)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 60 of 64




Plot 8-49. Occupied Bandwidth Plot (20.0MHz QPSK – RB Size 100)




Plot 8-50. Occupied Bandwidth Plot (20.0MHz 16-QAM – RB Size 100)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 61 of 64




Plot 8-51. Upper Band Edge Plot (20.0MHz QPSK – RB Size 100)




Plot 8-52. Upper Extended Band Edge Plot (20.0MHz QPSK – RB Size 100)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 62 of 64



Plot 8-53. PAR Plot (20.0MHz QPSK – RB Size 100)



Plot 8-54. PAR Plot (20.0MHz 16-QAM – RB Size 100)

FCC ID: IHDT56PE2	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 63 of 64

9.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Motorola Portable Handset FCC ID: IHDT56PE2** complies with all the requirements of Parts 2, 27 of the FCC rules for LTE operation only.

FCC ID: IHDT56PE2		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1305290908.IHD	Test Dates: 5/17 - 6/10/2013	EUT Type: Portable Handset		Page 64 of 64