

FCC RF Test Report


APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola Mobility, LLC
MODEL NAME : 4008
FCC ID : IHDT56PG4
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 31, 2014 and testing was completed on Apr. 13, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.
TEL : 886-3-327-3456
FAX : 886-3-328-4978
FCC ID : IHDT56PG4

Page Number : 1 of 151
Report Issued Date : May 08, 2014
Report Version : Rev. 01



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	7
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	12
3 TEST RESULT	13
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	29
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	35
3.5 Band Edge Measurement.....	55
3.6 Conducted Spurious Emission Measurement	62
3.7 Field Strength of Spurious Radiation Measurement	108
3.8 Frequency Stability Measurement.....	146
4 LIST OF MEASURING EQUIPMENT	150
5 UNCERTAINTY OF EVALUATION	151



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG433114	Rev. 01	Initial issue of report	May 08, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	Under limit 28.11 dB at 7641.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



1 General Description

1.1 Applicant

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.2 Manufacturer

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola Mobility, LLC
Model Name	4008
FCC ID	IHDT56PG4
IMEI Code	359290050003775
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE WLAN 11b/g/n HT20 Bluetooth v4.0 EDR/LE
HW Version	P3A
SW Version	4.4.2 KXB20.82 66
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.17 dBm GSM1900 : 29.39 dBm WCDMA Band V : 22.59 dBm WCDMA Band II : 22.58 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.242	0.0227 ppm	250KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.059	0.0430 ppm	244KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.024	0.0132 ppm	4M18F9W
Part 24	GSM1900 GPRS class 8	GMSK	1.114	0.0319 ppm	250KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.466	0.0436 ppm	248KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.327	0.0064 ppm	4M16F9W

1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	03CH07-HY

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

'Note:


1. The maximum power levels are chosen to test as the worst case configuration as follows:
 GPRS multi-slot class 8 mode for GMSK modulation,
 EDGE multi-slot class 8 mode for 8PSK modulation,
 RMC 12.2Kbps mode for WCDMA band V,
 RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.15	32.09	32.10	29.15	29.38	29.12
GPRS class 8	32.17	32.10	32.11	29.16	29.39	29.14
GPRS class 10	29.86	29.79	29.82	26.91	27.07	26.89
GPRS class 11	27.74	27.65	27.72	25.03	25.08	24.88
GPRS class 12	26.02	25.95	25.97	22.94	22.99	22.85
EGPRS class 8	26.07	26.03	26.08	25.45	25.54	25.39
EGPRS class 10	24.02	23.91	23.93	23.36	23.42	23.28
EGPRS class 11	22.69	22.54	22.63	21.77	21.89	21.72
EGPRS class 12	20.87	20.74	20.84	19.85	19.94	19.81

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	22.59	22.50	22.51	22.38	22.35	22.58
HSDPA Subtest-1	21.49	21.55	21.52	21.33	21.47	21.60
HSDPA Subtest-2	21.43	21.53	21.51	21.32	21.43	21.59
HSDPA Subtest-3	20.91	21.05	20.97	20.85	20.88	21.02
HSDPA Subtest-4	20.95	21.04	21.02	20.82	20.89	21.07
HSUPA Subtest-1	21.12	21.34	21.36	20.95	20.96	21.16
HSUPA Subtest-2	19.95	20.12	20.18	19.71	19.74	19.96
HSUPA Subtest-3	20.52	20.72	20.79	20.41	20.50	20.71
HSUPA Subtest-4	20.20	20.39	20.45	19.59	19.73	19.88
HSUPA Subtest-5	21.34	21.48	21.52	21.21	21.24	21.44

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.17	32.10	32.11	26.07	26.03	26.08	22.59	22.50	22.51

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.16	29.39	29.14	25.45	25.54	25.39	22.38	22.35	22.58

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.32	0.28	0.32	3.20	3.12	3.16	3.24	3.28	3.24

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.28	0.32	0.28	3.08	3.12	3.04	3.44	3.40	3.20

3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Date: 13.APR.2014 09:48:47

Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Date: 13.APR.2014 09:49:42


Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Date: 13.APR.2014 09:50:32


Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Date: 13.APR.2014 10:32:07

Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Date: 13.APR.2014 10:32:59

Peak-to-Average Ratio on Channel 251 (848.8 MHz)




Date: 13.APR.2014 10:33:54




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 13.APR.2014 11:23:38


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 13.APR.2014 11:24:25



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 13.APR.2014 11:25:23




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 13.APR.2014 12:47:03


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 13.APR.2014 12:47:51



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 13.APR.2014 12:49:03




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)



Date: 13.APR.2014 14:26:14


Peak-to-Average Ratio on Channel 4182 (836.4 MHz)



Date: 13.APR.2014 14:27:27




Peak-to-Average Ratio on Channel 4233 (846.6 MHz)



Date: 13.APR.2014 14:28:33


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 13.APR.2014 13:41:05


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 13.APR.2014 13:42:19



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 13.APR.2014 13:42:51

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at the same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-7.61	31.54	21.78	0.151
836.4	-6.73	32.04	23.16	0.207
848.8	-6.60	32.59	23.84	0.242
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-16.82	32.93	13.96	0.025
836.4	-16.47	32.82	14.20	0.026
848.8	-16.19	33.62	15.28	0.034

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

GSM850 (EDGE class 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-12.95	31.54	16.44	0.044
836.4	-12.32	32.04	17.57	0.057
848.8	-12.70	32.59	17.74	0.059
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-22.38	32.93	8.40	0.007
836.4	-21.48	32.82	9.19	0.008
848.8	-22.00	33.62	9.47	0.009

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.40	-17.88	31.44	11.41	0.014
836.40	-17.00	32.04	12.89	0.020
846.60	-16.66	32.63	13.82	0.024
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.40	-26.25	32.78	4.38	0.003
836.40	-25.91	32.82	4.76	0.003
846.60	-25.00	33.4	6.25	0.004

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-16.86	45.34	28.48	0.705
1880.0	-15.87	46.01	30.14	1.033
1909.8	-15.34	45.81	30.47	1.114
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-25.35	49.22	23.87	0.244
1880.0	-25.14	50.42	25.28	0.337
1909.8	-25.08	49.00	23.92	0.247

* EIRP = LVL (dBm) + Correction Factor (dB)

GSM1900 (EDGE class 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-20.34	45.34	25.00	0.316
1880.0	-19.34	46.01	26.67	0.465
1909.8	-19.13	45.81	26.68	0.466
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-28.82	49.22	20.40	0.110
1880.0	-28.55	50.42	21.87	0.154
1909.8	-27.26	49.00	21.74	0.149

* EIRP = LVL (dBm) + Correction Factor (dB)

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1852.40	-22.26	45.37	23.11	0.205
1880.00	-21.04	46.01	24.97	0.314
1907.60	-20.73	45.87	25.14	0.327
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1852.40	-31.97	49.23	17.26	0.053
1880.00	-31.20	50.42	19.22	0.084
1907.60	-30.44	49.04	18.60	0.072

* EIRP = LVL (dBm) + Correction Factor (dB)

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	244.00	246.00	250.00	244.00	244.00	240.00
26dB BW (kHz)	312.00	310.00	316.00	300.00	292.00	284.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	250.00	246.00	246.00	244.00	244.00	248.00
26dB BW (kHz)	310.00	312.00	310.00	300.00	294.00	292.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.18	4.18	4.16
26dB BW (MHz)	4.68	4.68	4.66

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.16	4.16	4.12
26dB BW (MHz)	4.68	4.70	4.68

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
---------------	---------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 13.APR.2014 09:26:40


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 13.APR.2014 09:24:12




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 13.APR.2014 09:27:09


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 13.APR.2014 09:24:41




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 13.APR.2014 09:31:01

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 13.APR.2014 09:25:09




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 13.APR.2014 10:18:22


26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 13.APR.2014 10:09:56

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 13.APR.2014 10:16:37

26dB Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 13.APR.2014 10:10:25

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 13.APR.2014 10:19:20


26dB Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 13.APR.2014 10:10:53




Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 13.APR.2014 11:07:59


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 13.APR.2014 11:06:03


99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)


Date: 13.APR.2014 11:08:27

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 13.APR.2014 11:06:32

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 13.APR.2014 11:08:56

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 13.APR.2014 11:07:00




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 13.APR.2014 11:50:38

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 13.APR.2014 11:46:53

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 13.APR.2014 11:51:06

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 13.APR.2014 11:47:22

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 13.APR.2014 11:51:35

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 13.APR.2014 11:47:50




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 13.APR.2014 14:13:20

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 13.APR.2014 14:11:06

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 13.APR.2014 14:13:49


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 13.APR.2014 14:11:34

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 13.APR.2014 14:14:18


26dB Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 13.APR.2014 14:12:03




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 13.APR.2014 13:30:23

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 13.APR.2014 13:26:04

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 13.APR.2014 13:30:51

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 13.APR.2014 13:28:44

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 13.APR.2014 13:31:20

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 13.APR.2014 13:29:13

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 13.APR.2014 09:43:41

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 13.APR.2014 09:40:04




Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 13.APR.2014 10:27:19

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 13.APR.2014 10:23:20




Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 13.APR.2014 11:16:13

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 13.APR.2014 11:13:36




Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 13.APR.2014 12:40:15

Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 13.APR.2014 12:37:38




Band :

WCDMA Band V

Test Mode :


RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 13.APR.2014 14:22:13

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 13.APR.2014 14:19:03




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 13.APR.2014 13:37:04

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 13.APR.2014 13:34:32

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$


$$= -13\text{dBm}.$$

3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH128
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	824.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 10:06:05

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 10:06:16

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 10:06:24

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.APR.2014 10:06:33




Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 09:54:08

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 13.APR.2014 09:54:21

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 09:54:29

Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 13.APR.2014 09:54:37




Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 10:01:14

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 10:01:23

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.APR.2014 10:01:31




Band :	GSM850	Channel :	CH128
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 13.APR.2014 10:40:09


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 10:40:20




Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 13.APR.2014 10:40:29

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.APR.2014 10:40:37

Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 10:37:18

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 13.APR.2014 10:37:29



Ref 0 dBm Att 0 dB RBW 1 MHz VBW 3 MHz SWT 500 ms Marker 1 [T1] 3.03200000 GHz

Offset 23 5 dB

1 -13 dBm

1.92 dBm

Start 3 GHz 400 MHz/ Stop 7 GHz

Date: 13.APR.2014 10:37:38

Ref 0 dBm Att 0 dB RBW 1 MHz VBW 3 MHz SWT 500 ms Marker 1 [T1] -50.08 dBm 7.696000000 GHz

Offset 25 dB

1. dBm VIEW


1

Start 7 GHz Stop 9 GHz 200 MHz/

Date: 13.APR.2014 10:37:46


Band :	GSM850	Channel :	CH251
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 10:42:36

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 13.APR.2014 10:42:47

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 10:42:56

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.APR.2014 10:43:04




Band :	GSM1900	Channel :	CH512
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 11:36:03

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 13.APR.2014 11:36:11

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 11:36:22


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 13.APR.2014 11:36:30



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 13.APR.2014 11:36:38



Conducted Spurious Emission Plot between 30MHz ~ 1GHz



The screenshot displays a Spectrum Analyzer interface. At the top, a red and white logo is visible. The main display area shows a frequency spectrum from 1 GHz to 3 GHz. A prominent signal is visible at approximately 2.992 GHz, with a peak level of -30.45 dBm. The signal is labeled 'Marker 1 [T1]'. The background is a grid. The y-axis represents power in dBm, ranging from -60 to -30. The x-axis represents frequency in GHz, ranging from 1 to 3. A red horizontal line is drawn at -13 dBm, labeled 'D1 -13 dBm'. The signal is labeled '1.992' on the right side. The bottom of the screen shows the frequency range 'Start 1 GHz', '200 MHz/' (span), and 'Stop 3 GHz'.

Ref 35 dBm Att 30 dB RBW 1 MHz VBW 3 MHz SWT 300 ms Marker 1 [T1] -30.45 dBm 2.992000000 GHz


Off Set 20 dB

1.992 VIEW


D1 -13 dBm

Start 1 GHz 200 MHz/ Stop 3 GHz

Date: 13.APR.2014 11:29:06

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 11:29:19

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 13.APR.2014 11:29:27




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.APR.2014 11:29:36

Band :	GSM1900	Channel :	CH810
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 11:38:08

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 13.APR.2014 11:38:16




Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz






Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.APR.2014 11:38:44

Band :	GSM1900	Channel :	CH512
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1850.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 12:57:20

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 12:57:28

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 13.APR.2014 12:57:40

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz




Date: 13.APR.2014 12:57:49

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.APR.2014 12:57:57

Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 12:55:46

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 12:55:55

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 12:56:06

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 13.APR.2014 12:56:14



Ref 0 dBm + Att 0 dB + RBW 1 MHz Marker 1 [T1] -31.69 dBm
+ VBW 3 MHz + SWT 300 ms 15.910000000 GHz

0 Offset 33 6 dB

-10

-20

-30

-40

-50

-60

-70

-80

-90

-100

1. dBm

VIEW

Start 13.6 GHz 550 MHz/ Stop 19.1 GHz


Date: 13.APR.2014 12:56:23




Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 13.APR.2014 13:00:34

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 13:00:47

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 13.APR.2014 13:00:55




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 13.APR.2014 13:01:04


Band :	WCDMA Band V	Channel :	CH4132
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	826.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 14:34:00


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 14:34:11

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 14:34:19

Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 13.APR.2014 14:34:28


Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 14:31:27


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 14:31:39

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 14:31:47

Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 13.APR.2014 14:31:56


Band :	WCDMA Band V	Channel :	CH4233
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	846.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.APR.2014 14:38:07


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 14:38:18


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 13.APR.2014 14:38:27


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 13.APR.2014 14:38:35


Band :	WCDMA Band II	Channel :	CH9262
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1852.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 13.APR.2014 13:49:45

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 13.APR.2014 13:49:53

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 13:50:05

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 13.APR.2014 13:50:14




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.APR.2014 13:50:22

Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 13:47:30

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 13:47:39

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 13:47:50

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 13.APR.2014 13:47:59



RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz -31.83 dBm
 SWT 300 ms 15.92100000 GHz

Ref 0 dBm Att 0 dB

Offset 33.6 dB


D1 -13 dBm

1


Start 13.6 GHz 550 MHz/ Stop 19.1 GHz

Date: 13.APR.2014 13:48:07

Band :	WCDMA Band II	Channel :	CH9538
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1907.6 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.APR.2014 13:54:11

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.APR.2014 13:54:19

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.APR.2014 13:54:31


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 13.APR.2014 13:54:39



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 13.APR.2014 13:54:48

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

<Low Channel>


Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : -13 HF-EIRP(080306) HORIZONTAL
Project : FG 433114

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-47.40	-13	-34.40	-56.85	-51.4	1.53	5.53	H	Pass
2474	-54.61	-13	-41.61	-67.85	-58.7	2.06	6.15	H	Pass
3298	-54.65	-13	-41.65	-68.72	-60.1	2.48	7.93	H	Pass


Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114


Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-45.10	-13	-32.10	-56.83	-49.1	1.53	5.53	V	Pass
2474	-54.41	-13	-41.41	-68.3	-58.5	2.06	6.15	V	Pass
3298	-53.85	-13	-40.85	-69.22	-59.3	2.48	7.93	V	Pass

Band :	GSM850	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-57.10	-13	-44.10	-66.19	-61.1	1.53	5.53	H	Pass
2474	-55.61	-13	-42.61	-68.3	-59.7	2.06	6.15	H	Pass
3298	-54.75	-13	-41.75	-68.25	-60.2	2.48	7.93	H	Pass


Band :	GSM850	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-55.30	-13	-42.30	-66.8	-59.3	1.53	5.53	V	Pass
2474	-54.61	-13	-41.61	-68	-58.7	2.06	6.15	V	Pass
3298	-53.35	-13	-40.35	-68.83	-58.8	2.48	7.93	V	Pass




Band :	GSM1900	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : -13 HF-EIRP(080306) HORIZONTAL
Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3702	-54.45	-13	-41.45	-69.48	-60.6	2.59	8.74	H	Pass
5553	-49.54	-13	-36.54	-69.72	-57.2	3.04	10.70	H	Pass
7405	-43.36	-13	-30.36	-69.79	-52.1	3.28	12.02	H	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3702	-53.75	-13	-40.75	-69.64	-59.9	2.59	8.74	V	Pass
5553	-49.04	-13	-36.04	-69.41	-56.7	3.04	10.70	V	Pass
7405	-42.66	-13	-29.66	-69.49	-51.4	3.28	12.02	V	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114


Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3700	-54.62	-13	-41.62	-69.73	-60.77	2.59	8.74	H	Pass
5548	-49.19	-13	-36.19	-69.58	-56.85	3.04	10.70	H	Pass
7403	-42.00	-13	-29.00	-69.27	-50.74	3.28	12.02	H	Pass

Band :	GSM1900	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3700	-53.11	-13	-40.11	-69.28	-59.26	2.59	8.74	V	Pass
5548	-48.91	-13	-35.91	-69.24	-56.57	3.04	10.70	V	Pass
7403	-42.22	-13	-29.22	-69.18	-50.96	3.28	12.02	V	Pass

Band :	WCDMA Band V	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-58.10	-13	-45.10	-66.56	-62.1	1.53	5.53	H	Pass
2474	-55.11	-13	-42.11	-67.99	-59.2	2.06	6.15	H	Pass
3298	-53.85	-13	-40.85	-67.34	-59.3	2.48	7.93	H	Pass


Band :	WCDMA Band V	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1649	-55.80	-13	-42.80	-66.81	-59.8	1.53	5.53	V	Pass
2474	-53.71	-13	-40.71	-67.57	-57.8	2.06	6.15	V	Pass
3298	-53.45	-13	-40.45	-68.55	-58.9	2.48	7.93	V	Pass




Band :	WCDMA Band II	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : -13 HF-EIRP(080306) HORIZONTAL
Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3707	-54.20	-13	-41.20	-69.34	-60.35	2.59	8.74	H	Pass
5555	-49.21	-13	-36.21	-69.61	-56.87	3.04	10.70	H	Pass
7410	-42.39	-13	-29.39	-69.83	-51.13	3.28	12.02	H	Pass


Band :	WCDMA Band II	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3707	-52.30	-13	-39.30	-68.6	-58.45	2.59	8.74	V	Pass
5555	-49.28	-13	-36.28	-69.5	-56.94	3.04	10.70	V	Pass
7410	-42.81	-13	-29.81	-69.79	-51.55	3.28	12.02	V	Pass

<Middle Channel>


Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : -13 HF-EIRP(080306) HORIZONTAL
Project : FG 433114


Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.63	-13	-39.63	-61.57	-56.5	1.62	5.49	H	Pass
2509	-55.58	-13	-42.58	-68.13	-59.7	2.1	6.22	H	Pass
3345	-55.36	-13	-42.36	-69	-60.4	3.03	8.07	H	Pass

Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.53	-13	-35.53	-60.29	-52.4	1.62	5.49	V	Pass
2509	-55.18	-13	-42.18	-68.54	-59.3	2.1	6.22	V	Pass
3345	-53.76	-13	-40.76	-68.94	-58.8	3.03	8.07	V	Pass


Band :	GSM850	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-58.23	-13	-45.23	-67.57	-62.1	1.62	5.49	H	Pass
2509	-55.58	-13	-42.58	-68.39	-59.7	2.1	6.22	H	Pass
3345	-54.26	-13	-41.26	-68.19	-59.3	3.03	8.07	H	Pass


Band :	GSM850	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-54.93	-13	-41.93	-66.01	-58.8	1.62	5.49	V	Pass
2509	-53.98	-13	-40.98	-67.4	-58.1	2.1	6.22	V	Pass
3345	-53.96	-13	-40.96	-69.05	-59	3.03	8.07	V	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-53.50	-13	-40.50	-69.01	-59.8	2.51	8.81	H	Pass
5640	-49.49	-13	-36.49	-69.9	-57.2	2.99	10.70	H	Pass
7520	-41.97	-13	-28.97	-68.57	-50.5	3.59	12.12	H	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-52.30	-13	-39.30	-69.31	-58.6	2.51	8.81	V	Pass
5640	-48.59	-13	-35.59	-69.85	-56.3	2.99	10.70	V	Pass
7520	-42.87	-13	-29.87	-69.4	-51.4	3.59	12.12	V	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3763	-53.06	-13	-40.06	-68.48	-59.36	2.51	8.81	H	Pass
5639	-48.57	-13	-35.57	-69.4	-56.28	2.99	10.70	H	Pass
7522	-41.62	-13	-28.62	-68.94	-50.15	3.59	12.12	H	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3763	-53.33	-13	-40.33	-69.69	-59.63	2.51	8.81	V	Pass
5639	-49.08	-13	-36.08	-69.63	-56.79	2.99	10.70	V	Pass
7522	-42.48	-13	-29.48	-69.4	-51.01	3.59	12.12	V	Pass




Band :	WCDMA Band V	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : -13 HF-EIRP(080306) HORIZONTAL
Project : FG 433114

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-58.53	-13	-45.53	-67.29	-62.4	1.62	5.49	H	Pass
2509	-55.38	-13	-42.38	-68.05	-59.5	2.1	6.22	H	Pass
3345	-54.36	-13	-41.36	-68.16	-59.4	3.03	8.07	H	Pass


Band :	WCDMA Band V	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-56.43	-13	-43.43	-67.17	-60.3	1.62	5.49	V	Pass
2509	-54.18	-13	-41.18	-67.65	-58.3	2.1	6.22	V	Pass
3345	-53.06	-13	-40.06	-68.22	-58.1	3.03	8.07	V	Pass


Band :	WCDMA Band II	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3763	-53.28	-13	-40.28	-68.65	-59.58	2.51	8.81	H	Pass
5639	-48.73	-13	-35.73	-69.46	-56.44	2.99	10.70	H	Pass
7522	-42.16	-13	-29.16	-69.31	-50.69	3.59	12.12	H	Pass

Band :	WCDMA Band II	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3763	-51.70	-13	-38.70	-68.02	-58	2.51	8.81	V	Pass
5639	-48.50	-13	-35.50	-69.14	-56.21	2.99	10.70	V	Pass
7522	-41.92	-13	-28.92	-68.98	-50.45	3.59	12.12	V	Pass


<High Channel>

Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-52.82	-13	-39.82	-62.52	-56.7	1.57	5.45	H	Pass
2544	-55.54	-13	-42.54	-68.55	-59.8	2.02	6.28	H	Pass
3393	-54.40	-13	-41.40	-68.72	-60.3	2.3	8.20	H	Pass


Band :	GSM850	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114


Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-50.42	-13	-37.42	-61.84	-54.3	1.57	5.45	V	Pass
2544	-54.64	-13	-41.64	-68.31	-58.9	2.02	6.28	V	Pass
3393	-54.00	-13	-41.00	-68.93	-59.9	2.3	8.20	V	Pass

Band :	GSM850	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-57.52	-13	-44.52	-66.57	-61.4	1.57	5.45	H	Pass
2544	-55.44	-13	-42.44	-68.07	-59.7	2.02	6.28	H	Pass
3393	-54.40	-13	-41.40	-68.31	-60.3	2.3	8.20	H	Pass

Band :	GSM850	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-55.02	-13	-42.02	-66.62	-58.9	1.57	5.45	V	Pass
2544	-54.44	-13	-41.44	-67.93	-58.7	2.02	6.28	V	Pass
3393	-53.10	-13	-40.10	-68.31	-59	2.3	8.20	V	Pass


Band :	GSM1900	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114


Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3820	-52.89	-13	-39.89	-68.57	-59.3	2.47	8.88	H	Pass
5729	-48.80	-13	-35.80	-69.84	-56.5	3	10.70	H	Pass
7639	-41.92	-13	-28.92	-68.09	-50.7	3.43	12.21	H	Pass

Band :	GSM1900	Temperature :	21~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3820	-52.29	-13	-39.29	-68.36	-58.7	2.47	8.88	V	Pass
5729	-49.40	-13	-36.40	-69.92	-57.1	3	10.70	V	Pass
7639	-42.02	-13	-29.02	-67.95	-50.8	3.43	12.21	V	Pass

Band :	GSM1900	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) HORIZONTAL
 Project : FG 433114

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3819	-52.76	-13	-39.76	-68.41	-59.17	2.47	8.88	H	Pass
5730	-48.63	-13	-35.63	-69.76	-56.33	3	10.70	H	Pass
7641	-41.11	-13	-28.11	-67.46	-49.89	3.43	12.21	H	Pass




Band :	GSM1900	Temperature :	21~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH07-HY
Condition : -13 HF-EIRP(080306) VERTICAL
Project : FG 433114


Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3819	-51.72	-13	-38.72	-68.38	-58.13	2.47	8.88	V	Pass
5730	-48.53	-13	-35.53	-69.39	-56.23	3	10.70	V	Pass
7641	-43.25	-13	-30.25	-69.19	-52.03	3.43	12.21	V	Pass

Band :	WCDMA Band V	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-57.62	-13	-44.62	-66.08	-61.5	1.57	5.45	H	Pass
2544	-54.14	-13	-41.14	-67.95	-58.4	2.02	6.28	H	Pass
3393	-53.70	-13	-40.70	-68.34	-59.6	2.3	8.20	H	Pass

Band :	WCDMA Band V	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
 Condition : -13 HF-EIRP(080306) VERTICAL
 Project : FG 433114

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1696	-56.22	-13	-43.22	-67.04	-60.1	1.57	5.45	V	Pass
2544	-54.44	-13	-41.44	-68.51	-58.7	2.02	6.28	V	Pass
3393	-51.90	-13	-38.90	-67.19	-57.8	2.3	8.20	V	Pass




Band :	WCDMA Band II	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3812	-51.64	-13	-38.64	-67.21	-58.05	2.47	8.88	H	Pass
5723	-47.74	-13	-34.74	-68.84	-55.44	3	10.70	H	Pass
7627	-43.23	-13	-30.23	-69.57	-52.01	3.43	12.21	H	Pass



Band :	WCDMA Band II	Temperature :	21~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	47~50%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3812	-51.35	-13	-38.35	-67.57	-57.76	2.47	8.88	V	Pass
5723	-47.93	-13	-34.93	-68.82	-55.63	3	10.70	V	Pass
7627	-42.80	-13	-29.80	-69.26	-51.58	3.43	12.21	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25 \pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Limit (ppm)	Result
	Deviation (ppm)	Deviation (ppm)		
50	0.0227	0.0430	2.5	PASS
40	0.0203	0.0371		
30	0.0179	0.0407		
20	0.0167	0.0359		
10	0.0132	0.0347		
0	0.0167	0.0311		
-10	0.0155	0.0347		
-20	0.0179	0.0395		
-30	0.0215	0.0418		

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Limit (ppm)	Result
	Deviation (ppm)	Deviation (ppm)		
50	0.0314	0.0415	2.5	PASS
40	0.0303	0.0436		
30	0.0271	0.0404		
20	0.0298	0.0372		
10	0.0261	0.0351		
0	0.0282	0.0367		
-10	0.0314	0.0399		
-20	0.0309	0.0388		
-30	0.0319	0.0420		

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Limit (ppm)	Result
	Deviation (ppm)		
50	0.0072	2.5	PASS
40	0.0084		
30	0.0060		
20	0.0048		
10	0.0060		
0	0.0084		
-10	0.0072		
-20	0.0096		
-30	0.0132		

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Limit (ppm)	Result
	Deviation (ppm)		
50	0.0059	2.5	PASS
40	0.0053		
30	0.0037		
20	0.0043		
10	0.0048		
0	0.0053		
-10	0.0048		
-20	0.0059		
-30	0.0064		

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	4.35	0.0179	2.5	PASS
		3.80	0.0191		
		BEP	0.0167		
	EDGE class 8	4.35	0.0323		
		3.80	0.0383		
		BEP	0.0395		
GSM 1900 CH661	GPRS class 8	4.35	0.0287		
		3.80	0.0293		
		BEP	0.0303		
	EDGE class 8	4.35	0.0367		
		3.80	0.0346		
		BEP	0.0378		
WCDMA Band V CH4182	RMC 12.2Kbps	4.35	0.0060		
		3.80	0.0048		
		BEP	0.0060		
WCDMA Band II CH9400	RMC 12.2Kbps	4.35	0.0048		
		3.80	0.0043		
		BEP	0.0053		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.42 V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	Rohde & Schwarz	CMU200	117995	N/A	Aug. 01, 2013	Apr. 13, 2014	Jul. 31, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Apr. 13, 2014	Jun. 06, 2014	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 19, 2013	Apr. 13, 2014	Jul. 18, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz ~ 30GHz	Feb. 10, 2014	Apr. 12, 2014 ~ Apr. 13, 2014	Feb. 09, 2015	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 10, 2013	Apr. 12, 2014 ~ Apr. 13, 2014	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 22, 2013	Apr. 12, 2014 ~ Apr. 13, 2014	Aug. 21, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00066583	1GHz~18GHz	Aug. 02, 2013	Apr. 12, 2014 ~ Apr. 13, 2014	Aug. 01, 2014	Radiation (03CH07-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 27, 2013	Apr. 12, 2014 ~ Apr. 13, 2014	May 26, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10 MHz ~ 1000MHz	Mar. 17, 2014	Apr. 12, 2014 ~ Apr. 13, 2014	Mar. 16, 2015	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Nov. 29, 2013	Apr. 12, 2014 ~ Apr. 13, 2014	Nov. 28, 2014	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Apr. 12, 2014 ~ Apr. 13, 2014	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	M-400-0	114/8000604/	N/A	N/A	Apr. 12, 2014 ~ Apr. 13, 2014	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz- 40GHz	Oct. 03, 2013	Apr. 12, 2014 ~ Apr. 13, 2014	Oct. 02, 2014	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50
---	------