



FCC RF Test Report

APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola Mobility, LLC
MODEL NAME : 4079
FCC ID : IHDT56PK2
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Aug. 26, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : IHDT56PK2

Page Number : 1 of 5

Report Issued Date : Sep. 23, 2014

Report Version : Rev. 01

Report Template No.: BU5-FR15EWL Version 1.0



TABLE OF CONTENTS

REVISION HISTORY.....3

1 GENERAL DESCRIPTION4

1.1 Applicant.....4

1.2 Manufacturer.....4

1.3 Feature of Equipment Under Test4

1.4 Product Specification of Equipment Under Test.....5

1.5 Modification of EUT5

APPENDIX A. ORIGINAL REPORT



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR462024-03F	Rev. 01	The Bluetooth and WLAN circuitry of this variant model (4079) is identical to that of the parent product (3584), based on the product equality declaration by the manufacturer.	Sep. 23, 2014



1 General Description

1.1 Applicant

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.2 Manufacturer

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola Mobility, LLC
Model Name	4079
FCC ID	IHDT56PK2
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC 2.4GHz WLAN 11b/g/n HT20 WLAN 11ac VHT20 5 GHz WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v3.0 EDR Bluetooth v4.0 LE
HW Version	P3
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	5725 MHz ~ 5850 MHz
Antenna Type	Fixed Internal Antenna with gain 3.00 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



Appendix A. Original Report

Please refer to Sporton report number FR462024F as below.



FCC RF Test Report

APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola Mobility, LLC
MODEL NAME : 3584
FCC ID : IHDT56PK1
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Jun. 20, 2014 and testing was completed on Aug. 05, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : IHDT56PK1

Page Number : 1 of 66

Report Issued Date : Aug. 08, 2014

Report Version : Rev. 01



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 RF Power	9
2.3 Test Mode.....	12
2.4 Connection Diagram of Test System.....	14
2.5 Support Unit used in test configuration and system	15
2.6 EUT Operation Test Setup	15
2.7 Measurement Results Explanation Example.....	15
3 TEST RESULT	16
3.1 6dB Bandwidth Measurement	16
3.2 Maximum Conducted Output Power Measurement	19
3.3 Power Spectral Density Measurement	21
3.4 Unwanted Emissions Measurement.....	25
3.5 AC Conducted Emission Measurement.....	56
3.6 Frequency Stability Measurement.....	61
3.7 Automatically Discontinue Transmission	63
3.8 Antenna Requirements.....	64
4 LIST OF MEASURING EQUIPMENT	65
5 UNCERTAINTY OF EVALUATION	66



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR462024F	Rev. 01	Initial issue of report	Aug. 08, 2014



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	$\leq -17, -27$ dBm/MHz &15.209(a)	Pass	Under limit 0.30 dB at 5724.760 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.60 dB at 0.502 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.2 Manufacturer

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola Mobility, LLC
Model Name	3584
FCC ID	IHDT56PK1
IMEI Code	990005110007243
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v4.0 EDR/LE
HW Version	P2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Accessory List	
AC Adapter	Brand Name : Turbo Charger (Motorola)
	Model Name : SPN5864A
Earphone	Brand Name : Motorola
	Model Name : SJYN1181B
USB Cable	Brand Name : Motorola
	Model Name : SKN6461A
Battery	Brand Name : Motorola
	Model Name : EQ40

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	5725 MHz ~ 5850 MHz
Maximum Output Power	802.11a : 14.99 dBm / 0.0316 W 802.11n HT20 : 14.54 dBm / 0.0284 W 802.11n HT40 : 14.12 dBm / 0.0258 W 802.11ac VHT20: 14.55 dBm / 0.0285 W 802.11ac VHT40: 14.14 dBm / 0.0259 W 802.11ac VHT80: 9.59 dBm / 0.0091 W
Antenna Type	Fixed Internal Antenna with gain 3.00 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH02-HY	CO05-HY	03CH06-HY

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 644545 D01 Guidance for IEEE 802.11ac and Pre-ac Device Emissions Testing v01r02.
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01
- ♦ KDB 648474 D03 Handset Wireless Chargers Battery Covers v01r02
- ♦ ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151	5755	159	5795
	153	5765	161	5805
	155	5775	165	5825

Note: The above Frequency and Channel in boldface were 802.11n HT40.



2.2 RF Power

Channel	Frequency	5GHz 802.11a Average Power (dBm) (800ns)							
		Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 149	5745MHz	14.99	14.83	14.83	14.93	14.96	14.21	13.35	11.60
CH 157	5785MHz	14.51	14.47	14.48	14.49	14.50	14.19	13.33	11.58
CH 165	5825MHz	14.70	14.67	14.63	14.57	14.64	14.24	13.34	11.62

Channel	Frequency	5GHz 802.11a Peak Power (dBm) (800ns)							
		Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 149	5745MHz	19.94	19.74	19.92	19.89	19.83	19.77	19.69	18.65
CH 157	5785MHz	19.54	19.41	19.30	19.25	19.21	19.41	19.40	19.43
CH 165	5825MHz	19.65	19.55	19.51	19.59	19.60	19.61	19.59	19.58

Channel	Frequency	5GHz 802.11n HT20 Average Power (dBm) (800ns)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745MHz	13.65	13.56	13.63	13.53	13.57	13.40	13.40	10.49
CH 157	5785MHz	14.35	14.10	14.24	13.55	13.59	12.81	12.81	9.83
CH 165	5825MHz	14.54	14.24	14.37	13.65	13.78	12.88	12.83	9.81

Channel	Frequency	5GHz 802.11n HT20 Peak Power (dBm) (800ns)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 149	5745MHz	19.66	19.62	19.63	19.48	19.51	19.39	19.35	17.38
CH 157	5785MHz	19.43	19.31	19.21	18.81	18.86	19.06	19.02	16.89
CH 165	5825MHz	19.66	19.65	19.55	19.21	19.22	19.04	18.93	17.03



Channel	Frequency	5GHz 802.11n HT40 Average Power (dBm) (800ns)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 151	5755MHz	10.30	10.29	10.26	10.20	10.29	10.25	10.29	10.28
CH 159	5795MHz	14.12	14.06	14.05	13.94	14.00	13.06	13.16	10.14

Channel	Frequency	5GHz 802.11n HT40 Peak Power (dBm) (800ns)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 151	5755MHz	17.49	17.11	17.02	17.19	17.01	17.41	17.21	17.08
CH 159	5795MHz	19.21	19.20	19.15	18.94	18.69	18.76	18.91	16.30

Channel	Frequency	5GHz 802.11ac VHT20 Average Power (dBm) (800ns)								
		Data Rate								
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
CH 149	5745MHz	13.69	13.39	13.41	13.68	13.66	13.11	12.98	10.05	9.67
CH 157	5785MHz	14.29	14.27	14.22	13.79	13.66	13.03	13.01	10.12	9.63
CH 165	5825MHz	14.55	14.37	14.33	13.89	13.78	13.05	13.13	10.23	9.77

Channel	Frequency	5GHz 802.11ac VHT20 Peak Power (dBm) (800ns)								
		Data Rate								
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
CH 149	5745MHz	19.78	19.77	19.75	18.72	18.21	18.92	18.55	19.15	19.19
CH 157	5785MHz	19.46	19.41	19.35	19.30	19.25	19.29	19.21	19.20	19.30
CH 165	5825MHz	19.79	19.71	19.70	19.65	19.61	19.55	19.50	19.46	19.41

Channel	Frequency	5GHz 802.11ac VHT40 Average Power (dBm) (800ns)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755MHz	10.00	9.97	9.95	9.99	9.97	9.96	9.95	9.99	9.30	8.11
CH 159	5795MHz	14.14	13.88	13.90	13.77	13.80	12.86	13.02	10.05	9.18	8.06

Channel	Frequency	5GHz 802.11ac VHT40 Peak Power (dBm) (800ns)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 151	5755MHz	17.22	16.93	16.91	17.20	16.99	17.20	17.20	16.87	16.75	16.44
CH 159	5795MHz	19.34	19.30	19.21	19.20	18.89	19.03	18.79	17.19	16.71	16.49



Channel	Frequency	5GHz 802.11ac VHT80 Average Power (dBm) (800ns)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 155	5775MHZ	9.59	9.55	9.46	9.54	9.58	9.58	9.56	9.56	8.98	7.83

Channel	Frequency	5GHz 802.11ac VHT80 Peak Power (dBm) (800ns)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
CH 155	5775MHZ	16.89	16.21	16.61	16.80	16.85	16.85	16.85	16.80	16.35	16.21



2.3 Test Mode

Investigation has been done for all channels, modulations, data rates among all 5GHz bands, and only the worst results are shown in below table and following sections.

Test Cases				
Conducted TCs	Test Items	Mode	Data rate	Test Channel
	6dB Bandwidth Power Spectral Density	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0/ MCS8	L/M/H
		802.11n HT40	MCS0/ MCS8	L/M/H
		802.11ac VHT20	MCS0	L/M/H
		802.11ac VHT40	MCS0	L/M/H
		802.11ac VHT80	MCS0	M
	Output Power	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0/ MCS8	L/M/H
		802.11n HT40	MCS0/ MCS8	L/M/H
		802.11ac VHT20	MCS0	L/M/H
		802.11ac VHT40	MCS0	L/M/H
		802.11ac VHT80	MCS0	M
	Frequency Stability	802.11a	6 Mbps	L/M/H




Test Cases				
Radiated TCs	Test Items	Mode	Data rate	Test Channel
	Radiated Band Edge	802.11a	6 Mbps	L/H
		802.11n HT20	MCS0/ MCS8	L/H
		802.11n HT40	MCS0/ MCS8	L/H
		802.11ac VHT80	MCS0	M
	Radiated Spurious Emission	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0/ MCS8	L/M/H
		802.11n HT40	MCS0/ MCS8	L/M/H
		802.11ac VHT80	MCS0	M
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Adapter + Earphone + MP3			
Note	The Wireless Charger Configuration was evaluated, and found that EUT without the wireless power charger as the worst case test configuration for Radiated Spurious Emission.			

Ch. #		Band IV : 5725-5850 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5725-5850 MHz		
		802.11ac VHT20	802.11ac VHT40	802.11ac VHT80
L	Low	149	151	-
M	Middle	157	-	155
H	High	165	159	-

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	N/A
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	CHARGER PAD	SAMSUNG	EP-P100IEWE	A3LEPP100IJWU	N/A	shielded, 1.5 m

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "QRCT" make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Description of 6dB Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



**3.1.5 Test Result of 6dB Bandwidth**

Test Band :	5GHz band 4	Temperature :	21~23℃
Test Engineer :	Bill Kuo	Relative Humidity :	51~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	6 dB Bandwidth (MHz)	FCC 6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
11a	6Mbps	1	149	5745	15.12	0.5	Pass
11a	6Mbps	1	157	5785	15.12	0.5	Pass
11a	6Mbps	1	165	5825	15.32	0.5	Pass
HT20	MCS0	1	149	5745	15.12	0.5	Pass
HT20	MCS0	1	157	5785	15.12	0.5	Pass
HT20	MCS0	1	165	5825	15.12	0.5	Pass
HT40	MCS0	1	151	5755	35.12	0.5	Pass
HT40	MCS0	1	159	5795	35.12	0.5	Pass
VHT20	MCS0	1	149	5745	15.12	0.5	Pass
VHT20	MCS0	1	157	5785	15.08	0.5	Pass
VHT20	MCS0	1	165	5825	15.12	0.5	Pass
VHT40	MCS0	1	151	5755	35.12	0.5	Pass
VHT40	MCS0	1	159	5795	35.12	0.5	Pass
VHT80	MCS0	1	155	5775	75.04	0.5	Pass



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



**3.2.5 Test Result of Maximum Conducted Output Power**

Test Band :	5GHz band 4	Temperature :	21~23℃
Test Engineer :	Bill Kuo	Relative Humidity :	51~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass /Fail
11a	6Mbps	1	149	5745	0.18	14.99	30.00	3.00	Pass
11a	6Mbps	1	157	5785	0.18	14.51	30.00	3.00	Pass
11a	6Mbps	1	165	5825	0.18	14.70	30.00	3.00	Pass
HT20	MCS0	1	149	5745	0.20	13.65	30.00	3.00	Pass
HT20	MCS0	1	157	5785	0.20	14.35	30.00	3.00	Pass
HT20	MCS0	1	165	5825	0.20	14.54	30.00	3.00	Pass
HT40	MCS0	1	151	5755	0.35	10.30	30.00	3.00	Pass
HT40	MCS0	1	159	5795	0.35	14.12	30.00	3.00	Pass
VHT20	MCS0	1	149	5745	0.20	13.69	30.00	3.00	Pass
VHT20	MCS0	1	157	5785	0.20	14.29	30.00	3.00	Pass
VHT20	MCS0	1	165	5825	0.20	14.55	30.00	3.00	Pass
VHT40	MCS0	1	151	5755	0.35	10.00	30.00	3.00	Pass
VHT40	MCS0	1	159	5795	0.35	14.14	30.00	3.00	Pass
VHT80	MCS0	1	155	5775	0.73	9.59	30.00	3.00	Pass



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


1. The testing follows Method SA-2 of FCC KDB 789033 D01 General UNII Test Procedures v01r03.
 - Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
4. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.


3.3.4 Test Setup



**3.3.5 Test Result of Power Spectral Density**

Test Band :	5GHz band 4	Temperature :	21~23°C
Test Engineer :	Bill Kuo	Relative Humidity :	51~54%

Mod.	Data Rate	NTX	Channel	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass /Fail
11a	6Mbps	1	149	5745	0.18	2.22	1.03	30.00	3.00	Pass
11a	6Mbps	1	157	5785	0.18	2.22	0.82	30.00	3.00	Pass
11a	6Mbps	1	165	5825	0.18	2.22	1.12	30.00	3.00	Pass
HT20	MCS0	1	149	5745	0.20	2.22	1.24	30.00	3.00	Pass
HT20	MCS0	1	157	5785	0.20	2.22	0.33	30.00	3.00	Pass
HT20	MCS0	1	165	5825	0.20	2.22	0.56	30.00	3.00	Pass
HT40	MCS0	1	151	5755	0.35	2.22	-5.28	30.00	3.00	Pass
HT40	MCS0	1	159	5795	0.35	2.22	-2.77	30.00	3.00	Pass
VHT20	MCS0	1	149	5745	0.20	2.22	0.88	30.00	3.00	Pass
VHT20	MCS0	1	157	5785	0.20	2.22	0.35	30.00	3.00	Pass
VHT20	MCS0	1	165	5825	0.20	2.22	0.55	30.00	3.00	Pass
VHT40	MCS0	1	151	5755	0.35	2.22	-5.57	30.00	3.00	Pass
VHT40	MCS0	1	159	5795	0.35	2.22	-2.93	30.00	3.00	Pass
VHT80	MCS0	1	155	5775	0.73	2.22	-8.92	30.00	3.00	Pass



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5725-5850 MHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBμV/m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBμV/m).
- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part 15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

- (3) KDB789033 v01r03 H)2)c(i) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.



3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11a	95.83	2070	0.48	1kHz
1	802.11n HT20	95.54	1930	0.52	1kHz
1	802.11n HT40	92.23	950	1.05	3kHz
1	802.11ac VHT20	95.54	1930	0.52	1kHz
1	802.11ac VHT40	92.31	960	1.04	3kHz
1	802.11ac VHT80	84.62	462	2.16	3kHz


- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.4.6 Test Result of Radiated Band Edges

Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5709.08	70.46	-3.54	74	58.14	35.01	11.3	33.99	105	358	Peak
5724.92	77.77	-0.53	78.3	65.4	35.02	11.34	33.99	105	358	Peak
5715	50.61	-3.39	54	38.29	35.01	11.3	33.99	105	358	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5713.48	72.8	-1.2	74	60.48	35.01	11.3	33.99	100	42	Peak
5724.92	77.28	-1.02	78.3	64.91	35.02	11.34	33.99	100	42	Peak
5715	51.19	-2.81	54	38.87	35.01	11.3	33.99	100	42	Average

Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5852.8	70.54	-3.46	74	57.84	35.14	11.56	34	100	53	Peak
5850.16	51.62	-2.38	54	38.92	35.14	11.56	34	100	53	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5850.8	68.78	-5.22	74	56.08	35.14	11.56	34	100	11	Peak
5850.24	50.02	-3.98	54	37.32	35.14	11.56	34	100	11	Average



Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5713.48	71.09	-2.91	74	58.77	35.01	11.3	33.99	106	354	Peak
5724.76	78	-0.3	78.3	65.63	35.02	11.34	33.99	106	354	Peak
5714.76	50.53	-3.47	54	38.21	35.01	11.3	33.99	106	354	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5706.6	69.5	-4.5	74	57.18	35.01	11.3	33.99	100	11	Peak
5724.68	76.21	-2.09	78.3	63.84	35.02	11.34	33.99	100	11	Peak
5715	50.42	-3.58	54	38.1	35.01	11.3	33.99	100	11	Average

Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5850.8	67.24	-6.76	74	54.54	35.14	11.56	34	100	54	Peak
5850	51.67	-2.33	54	38.97	35.14	11.56	34	100	54	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5851.52	69.88	-4.12	74	57.18	35.14	11.56	34	100	324	Peak
5850	50.17	-3.83	54	37.47	35.14	11.56	34	100	324	Average



Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Channel :	151	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5710.12	68.85	-5.15	74	56.53	35.01	11.3	33.99	106	44	Peak
5724.2	71.73	-6.57	78.3	59.36	35.02	11.34	33.99	106	44	Peak
5715	52.87	-1.13	54	40.55	35.01	11.3	33.99	106	44	Average
5854.64	55.6	-22.7	78.3	42.88	35.16	11.56	34	106	44	Peak
5882.24	56.22	-17.78	74	43.44	35.18	11.6	34	106	44	Peak
5861.36	45.42	-8.58	54	32.66	35.16	11.6	34	106	44	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5713.4	69.75	-4.25	74	57.43	35.01	11.3	33.99	100	35	Peak
5721.88	69.73	-8.57	78.3	57.36	35.02	11.34	33.99	100	35	Peak
5715	52.12	-1.88	54	39.8	35.01	11.3	33.99	100	35	Average
5856.64	54.93	-23.37	78.3	42.21	35.16	11.56	34	100	35	Peak
5883.52	55.89	-18.11	74	43.11	35.18	11.6	34	100	35	Peak
5883.84	45.41	-8.59	54	32.63	35.18	11.6	34	100	35	Average



Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Channel :	159	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5725	58.66	-15.34	74	46.29	35.02	11.34	33.99	100	358	Peak
5721.64	45.35	-8.65	54	32.98	35.02	11.34	33.99	100	358	Average
5827.8	65.86	-8.14	74	53.22	35.13	11.51	34	100	358	Peak
5825.8	52.75	-1.25	54	40.11	35.13	11.51	34	100	358	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5723.72	56.98	-17.02	74	44.61	35.02	11.34	33.99	102	12	Peak
5719.56	45.29	-8.71	54	32.92	35.02	11.34	33.99	102	12	Average
5825.4	64.86	-9.14	74	52.22	35.13	11.51	34	102	12	Peak
5825.88	49.87	-4.13	54	37.23	35.13	11.51	34	102	12	Average



Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5711.64	71.07	-2.93	74	58.75	35.01	11.3	33.99	105	52	Peak
5724.52	75.7	-2.6	78.3	63.33	35.02	11.34	33.99	105	52	Peak
5714.92	49	-5	54	36.68	35.01	11.3	33.99	105	52	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5710.52	68.63	-5.37	74	56.31	35.01	11.3	33.99	100	9	Peak
5724.92	74.47	-3.83	78.3	62.1	35.02	11.34	33.99	100	9	Peak
5715	48.53	-5.47	54	36.21	35.01	11.3	33.99	100	9	Average

Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5852.88	71.24	-2.76	74	58.54	35.14	11.56	34	100	357	Peak
5850	53.24	-0.76	54	40.54	35.14	11.56	34	100	357	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5850.96	67.36	-6.64	74	54.66	35.14	11.56	34	100	359	Peak
5850	50.94	-3.06	54	38.24	35.14	11.56	34	100	359	Average



Test Mode :	802.11ac VHT40	Temperature :	23~24°C
Test Channel :	151	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5713	69	-5	74	56.68	35.01	11.3	33.99	104	64	Peak
5721	72.34	-5.96	78.3	59.97	35.02	11.34	33.99	104	64	Peak
5714.84	53.47	-0.53	54	41.15	35.01	11.3	33.99	104	64	Average
5859.68	55.21	-23.09	78.3	42.49	35.16	11.56	34	104	64	Peak
5866	55.64	-18.36	74	42.88	35.16	11.6	34	104	64	Peak
5863.92	45.47	-8.53	54	32.71	35.16	11.6	34	104	64	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5714.76	69.28	-4.72	74	56.96	35.01	11.3	33.99	100	0	Peak
5720.36	72.36	-5.94	78.3	59.99	35.02	11.34	33.99	100	0	Peak
5715	52.11	-1.89	54	39.79	35.01	11.3	33.99	100	0	Average
5858.08	56.01	-22.29	78.3	43.29	35.16	11.56	34	100	0	Peak
5863.68	56.04	-17.96	74	43.28	35.16	11.6	34	100	0	Peak
5863.2	45.34	-8.66	54	32.58	35.16	11.6	34	100	0	Average



Test Mode :	802.11ac VHT40	Temperature :	23~24°C
Test Channel :	159	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5691.4	56.04	-17.96	74	43.78	34.99	11.26	33.99	150	66	Peak
5724.44	60.91	-17.39	78.3	48.54	35.02	11.34	33.99	150	66	Peak
5712.92	45.57	-8.43	54	33.25	35.01	11.3	33.99	150	66	Average
5851.44	60.63	-17.67	78.3	47.93	35.14	11.56	34	150	66	Peak
5860.24	58.02	-15.98	74	45.26	35.16	11.6	34	150	66	Peak
5862.24	46.85	-7.15	54	34.09	35.16	11.6	34	150	66	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5708.92	63.14	-10.86	74	50.82	35.01	11.3	33.99	100	34	Peak
5715.64	63.47	-14.83	78.3	51.15	35.01	11.3	33.99	100	34	Peak
5715	46.48	-7.52	54	34.16	35.01	11.3	33.99	100	34	Average
5850.72	60.51	-17.79	78.3	47.81	35.14	11.56	34	100	34	Peak
5860.48	57.71	-16.29	74	44.95	35.16	11.6	34	100	34	Peak
5860.8	46.69	-7.31	54	33.93	35.16	11.6	34	100	34	Average



Test Mode :	802.11n VHT80	Temperature :	23~24°C
Test Channel :	155	Relative Humidity :	45~46%
Test Engineer :	Kai Wang		

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5706.6	66.04	-7.96	74	53.72	35.01	11.3	33.99	116	51	Peak
5724.2	69.46	-8.84	78.3	57.09	35.02	11.34	33.99	116	51	Peak
5712.28	52.51	-1.49	54	40.19	35.01	11.3	33.99	116	51	Average
5851.52	62.26	-16.04	78.3	49.56	35.14	11.56	34	116	51	Peak
5861.84	61	-13	74	48.24	35.16	11.6	34	116	51	Peak
5860.16	49.08	-4.92	54	36.32	35.16	11.6	34	116	51	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5706.12	65.94	-8.06	74	53.62	35.01	11.3	33.99	100	358	Peak
5717.96	66.93	-11.37	78.3	54.56	35.02	11.34	33.99	100	358	Peak
5713.24	51.79	-2.21	54	39.47	35.01	11.3	33.99	100	358	Average
5851.76	61.54	-16.76	78.3	48.84	35.14	11.56	34	100	358	Peak
5862	58.44	-15.56	74	45.68	35.16	11.6	34	100	358	Peak
5860.4	47.34	-6.66	54	34.58	35.16	11.6	34	100	358	Average

3.4.7 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5746 MHz is fundamental signal which can be ignored.. 2. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
61.86	27.04	-12.96	40	51.52	6.4	0.89	31.77	-	-	Peak
98.04	28.71	-14.79	43.5	48.85	10.52	1.09	31.75	-	-	Peak
106.14	31.59	-11.91	43.5	50.49	11.72	1.13	31.75	102	215	Peak
494.6	20.47	-25.53	46	32.2	17.75	2.44	31.92	-	-	Peak
772.5	23.8	-22.2	46	32.6	20.12	3.05	31.97	-	-	Peak
891.5	25.05	-20.95	46	32.35	20.92	3.35	31.57	-	-	Peak
5746	108.11	-	-	94.88	35.14	11.39	33.3	105	358	Peak
5746	97.83	-	-	84.6	35.14	11.39	33.3	105	358	Average
11490	46.23	-27.77	74	55.92	37.79	11.04	58.52	100	0	Peak
17235	47.36	-26.64	74	52.56	41.13	12.27	58.6	100	0	Peak



Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5746 MHz is fundamental signal which can be ignored.. 2. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
45.66	29.18	-10.82	40	50.81	9.38	0.77	31.78	145	254	Peak
52.14	27.78	-12.22	40	51.08	7.66	0.82	31.78	-	-	Peak
193.35	28.49	-15.01	43.5	49.64	9.1	1.5	31.75	-	-	Peak
637.4	23.62	-22.38	46	33.22	19.66	2.79	32.05	-	-	Peak
835.5	24.41	-21.59	46	32.38	20.65	3.18	31.8	-	-	Peak
874	25.03	-20.97	46	32.47	20.9	3.3	31.64	-	-	Peak
5746	108.07	-	-	94.84	35.14	11.39	33.3	100	42	Peak
5746	97.84	-	-	84.61	35.14	11.39	33.3	100	42	Average
11490	45.76	-28.24	74	55.45	37.79	11.04	58.52	100	0	Peak
17235	47.57	-26.43	74	52.77	41.13	12.27	58.6	100	0	Peak



Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	157	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	5786 MHz is fundamental signal which can be ignored. 17355 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5786	109.77	-	-	97.25	35.09	11.43	34	106	355	Peak
5786	99.33	-	-	86.81	35.09	11.43	34	106	355	Average
11570	45.05	-28.95	74	54.58	37.92	11.09	58.54	100	0	Peak
17355	47.18	-26.82	74	52.42	40.94	12.42	58.6	100	0	Peak

Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	157	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	5783 MHz is fundamental signal which can be ignored. 17355 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5783	104.46	-	-	91.95	35.08	11.43	34	100	14	Peak
5783	94.32	-	-	81.81	35.08	11.43	34	100	14	Average
11571	45.41	-28.59	74	54.94	37.92	11.09	58.54	100	0	Peak
17355	47.84	-26.16	74	53.08	40.94	12.42	58.6	100	0	Peak



Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	5824 MHz is fundamental signal which can be ignored. 17475 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5824	104.96	-	-	92.32	35.13	11.51	34	100	53	Peak
5824	94.81	-	-	82.17	35.13	11.51	34	100	53	Average
11649	44.87	-29.13	74	54.26	38.05	11.14	58.58	100	0	Peak
17475	47.41	-26.59	74	52.69	40.75	12.57	58.6	100	0	Peak

Test Mode :	802.11a	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	5826 MHz is fundamental signal which can be ignored. 17475 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5826	102.42	-	-	89.78	35.13	11.51	34	100	11	Peak
5826	91.99	-	-	79.35	35.13	11.51	34	100	11	Average
11649	44.16	-29.84	74	53.55	38.05	11.14	58.58	100	0	Peak
17475	47.95	-26.05	74	53.23	40.75	12.57	58.6	100	0	Peak



Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	5744 MHz is fundamental signal which can be ignored.. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
61.86	27.04	-12.96	40	51.52	6.4	0.89	31.77	-	-	Peak
98.04	28.71	-14.79	43.5	48.85	10.52	1.09	31.75	-	-	Peak
168.24	37.78	-5.72	43.5	58.1	9.82	1.61	31.75	112	325	Peak
431.6	19.82	-26.18	46	32.61	16.8	2.27	31.86	-	-	Peak
629	22.81	-23.19	46	32.29	19.78	2.79	32.05	-	-	Peak
832	24.55	-21.45	46	32.58	20.62	3.17	31.82	-	-	Peak
5744	107.72	-	-	94.49	35.14	11.39	33.3	106	354	Peak
5744	97.52	-	-	84.29	35.14	11.39	33.3	106	354	Average
11484	49.18	-24.82	74	58.87	37.79	11.04	58.52	100	0	Peak
17235	48.21	-25.79	74	53.41	41.13	12.27	58.6	100	0	Peak



Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	5747 MHz is fundamental signal which can be ignored.. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
45.66	29.18	-10.82	40	50.81	9.38	0.77	31.78	100	214	Peak
99.66	28.45	-15.05	43.5	48.3	10.8	1.1	31.75	-	-	Peak
258.96	21.33	-24.67	46	37.53	13.75	1.78	31.73	-	-	Peak
412	19.54	-26.46	46	32.75	16.4	2.22	31.83	-	-	Peak
763.4	23.44	-22.56	46	32.2	20.17	3.05	31.98	-	-	Peak
874	25.03	-20.97	46	32.47	20.9	3.3	31.64	-	-	Peak
5747	106.67	-	-	93.44	35.14	11.39	33.3	100	11	Peak
5747	96.43	-	-	83.2	35.14	11.39	33.3	100	11	Average
11490	45.66	-28.34	74	55.35	37.79	11.04	58.52	100	0	Peak
17235	47.88	-26.12	74	53.08	41.13	12.27	58.6	100	0	Peak



Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	157	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5783 MHz is fundamental signal which can be ignored. 2. 17355 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5783	105.01	-	-	92.5	35.08	11.43	34	100	54	Peak
5783	94.88	-	-	82.37	35.08	11.43	34	100	54	Average
11571	46.86	-27.14	74	56.39	37.92	11.09	58.54	100	0	Peak
17355	49.05	-24.95	74	54.29	40.94	12.42	58.6	100	0	Peak

Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	157	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5783 MHz is fundamental signal which can be ignored. 2. 17355 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5783	102.16	-	-	89.65	35.08	11.43	34	101	11	Peak
5783	91.79	-	-	79.28	35.08	11.43	34	101	11	Average
11571	45.64	-28.36	74	55.17	37.92	11.09	58.54	100	0	Peak
17355	49.77	-24.23	74	55.01	40.94	12.42	58.6	100	0	Peak

Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5823 MHz is fundamental signal which can be ignored. 2. 17475 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5823	101.08	-	-	88.44	35.13	11.51	34	100	324	Peak
5823	91.25	-	-	78.61	35.13	11.51	34	100	324	Average
11649	44.7	-29.3	74	54.09	38.05	11.14	58.58	100	0	Peak
17475	48.31	-25.69	74	53.59	40.75	12.57	58.6	100	0	Peak

Test Mode :	802.11n HT20	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5823 MHz is fundamental signal which can be ignored. 2. 17475 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5823	104.91	-	-	92.27	35.13	11.51	34	100	54	Peak
5823	94.85	-	-	82.21	35.13	11.51	34	100	54	Average
11649	45.76	-28.24	74	55.15	38.05	11.14	58.58	100	0	Peak
17475	47.63	-26.37	74	52.91	40.75	12.57	58.6	100	0	Peak



Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Channel :	151	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5753 MHz is fundamental signal which can be ignored. 2. 17265 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
98.04	28.71	-14.79	43.5	48.85	10.52	1.09	31.75	-	-	Peak
106.14	31.59	-11.91	43.5	50.49	11.72	1.13	31.75	112	235	Peak
267.06	25.23	-20.77	46	41.89	13.27	1.8	31.73	-	-	Peak
772.5	23.8	-22.2	46	32.6	20.12	3.05	31.97	-	-	Peak
832	24.55	-21.45	46	32.58	20.62	3.17	31.82	-	-	Peak
891.5	25.05	-20.95	46	32.35	20.92	3.35	31.57	-	-	Peak
5753	103.98	-	-	90.73	35.16	11.39	33.3	106	44	Peak
5753	94.11	-	-	80.86	35.16	11.39	33.3	106	44	Average
11511	45.78	-28.22	74	55.42	37.8	11.06	58.5	100	0	Peak
17265	48.02	-25.98	74	53.22	41.07	12.33	58.6	100	0	Peak



Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Channel :	151	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	5753 MHz is fundamental signal which can be ignored. 17265 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	28.16	-11.84	40	40.82	18.5	0.64	31.8	-	-	Peak
45.66	29.18	-10.82	40	50.81	9.38	0.77	31.78	100	236	Peak
99.66	28.45	-15.05	43.5	48.3	10.8	1.1	31.75	-	-	Peak
412	19.54	-26.46	46	32.75	16.4	2.22	31.83	-	-	Peak
721.4	23.18	-22.82	46	32.39	19.84	2.96	32.01	-	-	Peak
874	25.03	-20.97	46	32.47	20.9	3.3	31.64	-	-	Peak
5753	100.44	-	-	87.19	35.16	11.39	33.3	100	35	Peak
5753	90.89	-	-	77.64	35.16	11.39	33.3	100	35	Average
11511	45.17	-28.83	74	54.81	37.8	11.06	58.5	100	0	Peak
17265	49.33	-24.67	74	54.53	41.07	12.33	58.6	100	0	Peak

Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Channel :	159	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5795 MHz is fundamental signal which can be ignored. 2. 17385 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5795	103.93	-	-	91.37	35.09	11.47	34	104	52	Peak
5795	93.82	-	-	81.26	35.09	11.47	34	104	52	Average
11589	44.29	-29.71	74	53.78	37.96	11.1	58.55	100	0	Peak
17385	48.06	-25.94	74	53.29	40.89	12.48	58.6	100	0	Peak

Test Mode :	802.11n HT40	Temperature :	23~24°C
Test Channel :	159	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5795 MHz is fundamental signal which can be ignored. 2. 17385 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5795	102.1	-	-	89.54	35.09	11.47	34	100	0	Peak
5795	93.02	-	-	80.46	35.09	11.47	34	100	0	Average
11589	45.57	-28.43	74	55.06	37.96	11.1	58.55	100	0	Peak
17385	48.59	-25.41	74	53.82	40.89	12.48	58.6	100	0	Peak



Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5747 MHz is fundamental signal which can be ignored. 2. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5747	108.17	-	-	94.94	35.14	11.39	33.3	105	52	Peak
5747	97.77	-	-	84.54	35.14	11.39	33.3	105	52	Average
11490	45.64	-28.36	74	55.33	37.79	11.04	58.52	100	0	Peak
17235	49.1	-24.9	74	54.3	41.13	12.27	58.6	100	0	Peak

Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	149	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5747 MHz is fundamental signal which can be ignored. 2. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5747	107.33	-	-	94.1	35.14	11.39	33.3	100	9	Peak
5747	96.84	-	-	83.61	35.14	11.39	33.3	100	9	Average
11490	45.95	-28.05	74	55.64	37.79	11.04	58.52	100	0	Peak
17235	49	-25	74	54.2	41.13	12.27	58.6	100	0	Peak

Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	157	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5786 MHz is fundamental signal which can be ignored. 2. 17355 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5786	104.53	-	-	92.01	35.09	11.43	34	100	357	Peak
5786	94.52	-	-	82	35.09	11.43	34	100	357	Average
11571	45.61	-28.39	74	55.14	37.92	11.09	58.54	100	0	Peak
17355	48.12	-25.88	74	53.36	40.94	12.42	58.6	100	0	Peak

Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	157	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5783 MHz is fundamental signal which can be ignored. 2. 17355 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5783	101.75	-	-	89.24	35.08	11.43	34	101	11	Peak
5783	92.27	-	-	79.76	35.08	11.43	34	101	11	Average
11571	45.49	-28.51	74	55.02	37.92	11.09	58.54	100	0	Peak
17355	48.37	-25.63	74	53.61	40.94	12.42	58.6	100	0	Peak



Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	5824 MHz is fundamental signal which can be ignored. 17475 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5824	105.29	-	-	92.65	35.13	11.51	34	100	357	Peak
5824	95.11	-	-	82.47	35.13	11.51	34	100	357	Average
11649	45.27	-28.73	74	54.66	38.05	11.14	58.58	100	0	Peak
17475	48.92	-25.08	74	54.2	40.75	12.57	58.6	100	0	Peak

Test Mode :	802.11ac VHT20	Temperature :	23~24°C
Test Channel :	165	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	5823 MHz is fundamental signal which can be ignored. 17475 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5823	101.74	-	-	89.1	35.13	11.51	34	100	359	Peak
5823	91.64	-	-	79	35.13	11.51	34	100	359	Average
11649	45.49	-28.51	74	54.88	38.05	11.14	58.58	100	0	Peak
17475	49.39	-24.61	74	54.67	40.75	12.57	58.6	100	0	Peak



Test Mode :	802.11ac VHT40	Temperature :	23~24°C
Test Channel :	151	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5753 MHz is fundamental signal which can be ignored.. 2. 17265 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5753	102.9	-	-	89.65	35.16	11.39	33.3	104	64	Peak
5753	93.03	-	-	79.78	35.16	11.39	33.3	104	64	Average
11511	46.13	-27.87	74	55.77	37.8	11.06	58.5	100	0	Peak
17265	48.79	-25.21	74	53.99	41.07	12.33	58.6	100	0	Peak

Test Mode :	802.11ac VHT40	Temperature :	23~24°C
Test Channel :	151	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5753 MHz is fundamental signal which can be ignored.. 2. 17265 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5753	100.42	-	-	87.17	35.16	11.39	33.3	100	0	Peak
5753	90.61	-	-	77.36	35.16	11.39	33.3	100	0	Average
11511	46.05	-27.95	74	55.69	37.8	11.06	58.5	100	0	Peak
17265	48.39	-25.61	74	53.59	41.07	12.33	58.6	100	0	Peak



Test Mode :	802.11ac VHT40	Temperature :	23~24°C
Test Channel :	159	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	1. 5793 MHz is fundamental signal which can be ignored.. 2. 17385 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5793	98.54	-	-	85.98	35.09	11.47	34	100	58	Peak
5793	88.84	-	-	76.28	35.09	11.47	34	100	58	Average
11589	44.62	-29.38	74	54.11	37.96	11.1	58.55	100	0	Peak
17385	49.2	-24.8	74	54.43	40.89	12.48	58.6	100	0	Peak

Test Mode :	802.11ac VHT40	Temperature :	23~24°C
Test Channel :	159	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5797 MHz is fundamental signal which can be ignored.. 2. 17385 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
5797	94.25	-	-	81.69	35.09	11.47	34	100	0	Peak
5797	84.16	-	-	71.6	35.09	11.47	34	100	0	Average
11589	45.87	-28.13	74	55.36	37.96	11.1	58.55	100	0	Peak
17385	49.48	-24.52	74	54.71	40.89	12.48	58.6	100	0	Peak



Test Mode :	802.11ac VHT80	Temperature :	23~24°C
Test Channel :	155	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Horizontal
Remark :	5773 MHz is fundamental signal which can be ignored. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. - Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
61.86	26.96	-13.04	40	51.44	6.4	0.89	31.77	113	326	Peak
113.7	27.8	-15.7	43.5	46.3	12.07	1.18	31.75	-	-	Peak
268.14	24.62	-21.38	46	41.45	13.09	1.81	31.73	-	-	Peak
413.4	20.31	-25.69	46	33.47	16.45	2.22	31.83	-	-	Peak
553.4	22.54	-23.46	46	32.56	19.42	2.56	32	-	-	Peak
874	24.69	-21.31	46	32.13	20.9	3.3	31.64	-	-	Peak
5773	97.75	-	-	85.24	35.08	11.43	34	116	51	Peak
5773	88.03	-	-	75.52	35.08	11.43	34	116	51	Average
11550	45.22	-28.78	74	54.77	37.89	11.09	58.53	100	0	Peak
17325	47.48	-26.52	74	52.7	40.99	12.39	58.6	100	0	Peak



Test Mode :	802.11ac VHT80	Temperature :	23~24°C
Test Channel :	155	Relative Humidity :	45~46%
Test Engineer :	Kai Wang	Polarization :	Vertical
Remark :	1. 5773 MHz is fundamental signal which can be ignored. 2. 17235 MHz is not within a restricted band, and satisfies both the average and peak limits of 15.209. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	27.93	-12.07	40	40.59	18.5	0.64	31.8	-	-	Peak
44.85	28.26	-11.74	40	49.68	9.6	0.76	31.78	100	218	Peak
165.54	29.8	-13.7	43.5	50.1	9.88	1.57	31.75	-	-	Peak
578.6	22.8	-23.2	46	32.77	19.39	2.67	32.03	-	-	Peak
721.4	23.22	-22.78	46	32.43	19.84	2.96	32.01	-	-	Peak
784.4	24.03	-21.97	46	32.78	20.15	3.06	31.96	-	-	Peak
5773	96.66	-	-	84.15	35.08	11.43	34	100	358	Peak
5773	86.26	-	-	73.75	35.08	11.43	34	100	358	Average
11550	45.08	-28.92	74	54.63	37.89	11.09	58.53	100	0	Peak
17325	47.76	-26.24	74	52.98	40.99	12.39	58.6	100	0	Peak

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Adapter + Earphone + MP3		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	41.9	Off	L1	19.3	24.1	66.0
0.494000	42.2	Off	L1	19.4	13.9	56.1
0.558000	41.1	Off	L1	19.4	14.9	56.0
0.606000	41.6	Off	L1	19.4	14.4	56.0
1.102000	41.4	Off	L1	19.4	14.6	56.0
1.654000	37.7	Off	L1	19.5	18.3	56.0
4.806000	38.7	Off	L1	19.6	17.3	56.0
10.318000	39.4	Off	L1	19.7	20.6	60.0

Final Result : Average


Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	26.4	Off	L1	19.3	29.6	56.0
0.494000	33.6	Off	L1	19.4	12.5	46.1
0.558000	33.2	Off	L1	19.4	12.8	46.0
0.606000	29.5	Off	L1	19.4	16.5	46.0
1.102000	22.9	Off	L1	19.4	23.1	46.0
1.654000	21.0	Off	L1	19.5	25.0	46.0
4.806000	22.6	Off	L1	19.6	23.4	46.0
10.318000	25.7	Off	L1	19.7	24.3	50.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Adapter + Earphone + MP3		


Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	42.8	Off	N	19.4	23.2	66.0
0.502000	44.4	Off	N	19.4	11.6	56.0
0.558000	42.8	Off	N	19.4	13.2	56.0
0.614000	39.7	Off	N	19.4	16.3	56.0
0.798000	35.0	Off	N	19.6	21.0	56.0
1.118000	38.8	Off	N	19.5	17.2	56.0
1.750000	35.1	Off	N	19.6	20.9	56.0
2.950000	32.3	Off	N	19.5	23.7	56.0
4.854000	33.6	Off	N	19.6	22.4	56.0
8.654000	38.7	Off	N	19.7	21.3	60.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + Adapter + Earphone + MP3		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	23.3	Off	N	19.4	32.7	56.0
0.502000	33.3	Off	N	19.4	12.7	46.0
0.558000	30.5	Off	N	19.4	15.5	46.0
0.614000	31.2	Off	N	19.4	14.8	46.0
0.798000	24.7	Off	N	19.6	21.3	46.0
1.118000	26.7	Off	N	19.5	19.3	46.0
1.750000	21.4	Off	N	19.6	24.6	46.0
2.950000	21.6	Off	N	19.5	24.4	46.0
4.854000	21.0	Off	N	19.6	25.0	46.0
8.654000	22.8	Off	N	19.7	27.2	50.0

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



**3.6.5 Test Result of Frequency Stability**

Test Band :		5GHz band 4			Test Engineer :		Bill Kuo		
Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)
11a	6Mbps	1	149	5745	5745.050	0.050	8.70	20	3.4
11a	6Mbps	1	149	5745	5745.050	0.050	8.70	20	4.35
11a	6Mbps	1	149	5745	5745.025	0.025	4.35	20	3.8
11a	6Mbps	1	149	5745	5745.050	0.050	8.70	-30	3.8
11a	6Mbps	1	149	5745	5745.050	0.050	8.70	50	3.8

Note: Center Frequency = (Low Frequency + High Frequency) / 2.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Jul. 25, 2014 ~ Aug. 05, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 17, 2013	Jul. 25, 2014 ~ Aug. 05, 2014	Aug. 16, 2014	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 17, 2013	Jul. 25, 2014 ~ Aug. 05, 2014	Aug. 16, 2014	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz ~ 40GHz	Jun. 09, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	Jun. 08, 2015	Radiation (03CH06-HY)
Spectrum Analyzer	Agilent	E4408B	MY44211030	9kHz ~ 26.5GHz	Dec. 02, 2013	Aug. 02, 2014 ~ Aug. 05, 2014	Dec. 01, 2014	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESVS10	834468/0003	20MHz ~ 1000MHz	May 06, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	May 05, 2015	Radiation (03CH06-HY)
Loop Antenna	TESEQ	HLA 6120	31244	9kHz ~ 30MHz	Dec. 02, 2012	Aug. 02, 2014 ~ Aug. 05, 2014	Dec. 03, 2014	Radiation (03CH06-HY)
Bilog Antenna	Schaffner	CBL6112B	2885	30MHz ~ 2GHz	Oct. 10, 2013	Aug. 02, 2014 ~ Aug. 05, 2014	Oct. 09, 2014	Radiation (03CH06-HY)
Double Ridge Horn Antenna	EMCO	3117	00066583	1GHz ~ 18GHz	Jul. 24, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	Jul. 23, 2015	Radiation (03CH06-HY)
Amplifier	SONOMA	310N	186713	9kHz ~ 1GHz	Apr. 16, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	Apr. 15, 2015	Radiation (03CH06-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1865802	18GHz~40GHz	Jun. 09, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	Jun. 08, 2015	Radiation (03CH06-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	159075	1GHz ~ 18GHz	Apr. 21, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	Apr. 20, 2015	Radiation (03CH06-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz ~ 40GHz	Oct. 03, 2013	Aug. 02, 2014 ~ Aug. 05, 2014	Oct. 02, 2014	Radiation (03CH06-HY)
Preamplifier	Agilent	8449B	3008A01917	1GHz ~ 26.5GHz	Apr. 10, 2014	Aug. 02, 2014 ~ Aug. 05, 2014	Apr. 09, 2015	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0 ~ 360 degree	N/A	Aug. 02, 2014 ~ Aug. 05, 2014	N/A	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF780208212	1 m ~ 4 m	N/A	Aug. 02, 2014 ~ Aug. 05, 2014	N/A	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	Jul. 13, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Jul. 13, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Jul. 13, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 13, 2014	N/A	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50
---	------