


FCC SAR Test Report

APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola Mobility, LLC
MODEL NAME : 3604
FCC ID : IHDT56QA4
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Table of Contents

1. Statement of Compliance 4

2. Administration Data 5

3. Guidance Standard 5

4. Equipment Under Test (EUT) 6

 4.1 General Information 6

 4.2 Maximum Tune-up Limit..... 7

 4.3 General LTE SAR Test and Reporting Considerations 8

5. RF Exposure Limits..... 9

 5.1 Uncontrolled Environment..... 9

 5.2 Controlled Environment..... 9

6. Specific Absorption Rate (SAR).....10

 6.1 Introduction10

 6.2 SAR Definition.....10

7. System Description and Setup11

8. Measurement Procedures12

 8.1 Spatial Peak SAR Evaluation.....12

 8.2 Power Reference Measurement.....13

 8.3 Area Scan13

 8.4 Zoom Scan.....14

 8.5 Volume Scan Procedures.....14

 8.6 Power Drift Monitoring.....14

9. Test Equipment List15

10. System Verification16

 10.1 Tissue Verification16

 10.2 System Performance Check Results.....17

11. RF Exposure Positions18

 11.1 Ear and handset reference point18

 11.2 Definition of the cheek position.....19

 11.3 Definition of the tilt position.....20

 11.4 Body Worn Accessory21

 11.5 Wireless Router.....21

12. Conducted RF Output Power (Unit: dBm).....22

13. Antenna Location30

14. SAR Test Results31

 14.1 Head SAR32

 14.2 Wireless Router SAR33

 14.3 Body Worn Accessory SAR.....34

 14.4 Repeated SAR Measurement35

15. Simultaneous Transmission Analysis.....36

 15.1 Head Exposure Conditions37

 15.2 Wireless Router Exposure Conditions.....38

 15.3 Body-Worn Accessory Exposure Conditions40

 15.4 SPLSR Evaluation and Analysis.....41

16. Uncertainty Assessment43

17. References.....45

Appendix A. Plots of System Performance Check

Appendix B. Plots of High SAR Measurement

Appendix C. DASYS Calibration Certificate

Appendix D. SAR System Validation

Appendix E. WLAN/BT Reference Report



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA453016A	Rev. 01	Initial issue of report	Jul. 18, 2014
FA453016A	Rev. 02	Additional FCC request test channel.	Jul. 30, 2014
FA453016A	Rev. 03	1. Add Appendix E "WLAN/BT Reference Report". 2. Add Appendix D "SAR System Validation". 3. Corrected the EUT dimensions on section13. 4. Retest GSM1900 SAR results.	Aug. 12, 2014
FA453016A	Rev. 04	1. In section4.1, add note4 a statement. 2. Corrected the typo in the column header. 3. Corrected the system verification value and recalculation deviation.	Aug. 16, 2014
FA453016A	Rev. 05	1. Added FCC second request testing channels	Sep. 02, 2014



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility, LLC, Mobile Cellular Phone, 3604**, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary			
		Head (Separation 0mm) 1g SAR (W/kg)	Body-worn (Separation 15mm) 1g SAR (W/kg)	Wireless Router (Separation 10mm) 1g SAR (W/kg)	Highest Simultaneous Transmission 1g SAR (W/kg)
PCE	GSM850	0.61	0.58	0.91	1.59
	GSM1900	0.36	0.66	0.70	
	WCDMA Band V	0.62	0.63	0.94	
	WCDMA Band II	0.41	1.10	0.70	
	LTE Band 7	0.42	0.74	0.94	
Date of Testing:		06/24/2014 ~ 09/01/2014			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.



2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Motorola Mobility, LLC
Address	222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

Manufacturer	
Company Name	Motorola Mobility, LLC
Address	222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 941225 D01 SAR test for 3G devices v02
- FCC KDB 941225 D02 HSPA and 1x Advanced v02r02
- FCC KDB 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- FCC KDB 941225 D05 SAR for LTE Devices v02r03
- FCC KDB 941225 D06 Hotspot Mode SAR v01r01



4. Equipment Under Test (EUT)

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola Mobility, LLC
Model Name	3604
FCC ID	IHDT56QA4
IMEI Code	359283050005155
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC: 13.56 MHz
Mode	<ul style="list-style-type: none"> • GSM/GPRS/EGPRS • AMR / RMC 12.2Kbps • HSDPA • HSUPA • DC-HSDPA • LTE: QPSK, 16QAM • 802.11a/b/g/n/ac HT20/HT40/VHT20/VHT40/VHT80 • Bluetooth v3.0+EDR · Bluetooth v4.0-LE • NFC:ASK
HW Version	P2
SW Version	victara_reteu_userdebug_4.4.3_KXE21.119_25_intcfg_test-keys_reteuall_EU
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark:	
<ol style="list-style-type: none"> 1. This device supported VoIP in EGPRS, WCDMA, LTE (e.g. 3rd party VoIP). 2. While operating in body-adjacent exposure configurations during a mobile hotspot session, reduced power limits are enforced on the GSM1900, WCDMA B2, and LTE B7 transmitter. More detailed information which can be referred to “operational description”. 3. The 2.4GHz / 5GHz WLAN and Bluetooth conducted power and SAR testing results were referred to Sporton FCC SAR Test Report, Brand Name: Motorola Mobility LLC, Model Name: 3578, FCC ID: IHDT56QA1, Report No: FA442943A and also used perform transmission simultaneous analysis, more detail which can be referred to Appendix E. 4. The all of LTE Band7 SAR testing data or description of the report is not applicable in this FCC filing. 	



4.2 Maximum Tune-up Limit

Mode	Burst average power(dBm)	
	GSM 850	GSM 1900
GSM (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 2 Tx slots)	30.60	27.50
GPRS (GMSK, 3 Tx slots)	29.50	25.50
GPRS (GMSK, 4 Tx slots)	27.60	24.50
EDGE (8PSK, 1 Tx slot)	28.00	26.00
EDGE (8PSK, 2 Tx slots)	25.00	24.00
EDGE (8PSK, 3 Tx slots)	24.00	22.00
EDGE (8PSK, 4 Tx slots)	23.00	21.00

Band / Mode		Average power(dBm)	
WCDMA	Band V / II	AMR / RMC 12.2Kbps	24.00
		HSDPA Subtest-1	23.00
		DC-HSDPA Subtest-1	23.00
		HSUPA Subtest-5	23.00
LTE	Band 7	24.00	



4.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r03																																																						
FCC ID	IHDT56QA4																																																					
Equipment Name	Mobile Cellular Phone																																																					
Operating Frequency Range of each LTE transmission band	LTE Band 7: 2502.5 MHz ~ 2567.5 MHz																																																					
Channel Bandwidth	LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz																																																					
uplink modulations used	QPSK, and 16QAM																																																					
LTE Voice / Data requirements	Data only																																																					
LTE MPR permanently built-in by design	<table border="1"> <thead> <tr> <th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</th> </tr> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> </tbody> </table>								Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3								Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3																																																						
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																															
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																															
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																															
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																															
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																					
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																					
Power reduction applied to satisfy SAR compliance	Yes, When operating in hotspot mode that LTE B7 power reduction applied to satisfy SAR compliance.																																																					
Transmission (H, M, L) channel numbers and frequencies in each LTE band																																																						
LTE Band 7																																																						
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz																																															
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																														
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510																																														
M	21100	2535	21100	2535	21100	2535	21100	2535																																														
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560																																														



5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 24, 2014	Mar. 23, 2015
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Mar. 21, 2014	Mar. 20, 2015
SPEAG	2600MHz System Validation Kit	D2600V2	1070	Nov. 13, 2013	Nov. 12, 2014
SPEAG	Data Acquisition Electronics	DAE3	495	May. 19, 2014	May. 18, 2015
SPEAG	Data Acquisition Electronics	DAE4	1425	Mar. 03, 2014	Mar. 02, 2015
SPEAG	Data Acquisition Electronics	DAE3	577	May. 15, 2014	May. 14, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	May. 22, 2014	May. 21, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3954	Nov. 04, 2013	Nov. 03, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Sep. 10, 2013	Sep. 09, 2014
Wisewind	Thermometer	ETP-101	TM560	Oct. 22, 2013	Oct. 21, 2014
Wisewind	Thermometer	ETP-101	TM685	Oct. 22, 2013	Oct. 21, 2014
Wisewind	Thermometer	HTC-1	TM642	Oct. 22, 2013	Oct. 21, 2014
Anritsu	Radio Communication Analyzer	MT8820C	6201074414	Feb. 11, 2014	Feb. 10, 2015
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 27, 2014	May. 26, 2015
SPEAG	Device Holder	N/A	N/A	NCR	NCR
Agilent	Signal Generator	E4438C	MY49070755	Oct. 08, 2013	Oct. 07, 2014
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Jul. 23, 2013	Jul. 22, 2014
SPEAG	Dielectric Probe Kit	DAK-3.5	1138	Nov. 03, 2013	Nov. 02, 2014
Agilent	ENA Network Analyzer	E5071C	MY46316648	Feb. 07, 2014	Feb. 06, 2015
Anritsu	Power Meter	ML2495A	1349001	Dec. 04, 2013	Dec. 03, 2014
Anritsu	Power Sensor	MA2411B	1306099	Dec. 03, 2013	Dec. 02, 2014
R&S	Spectrum Analyzer	FSP30	101067	Nov. 20, 2013	Nov. 19, 2014
Agilent	Dual Directional Coupler	778D	50422	Note 1	
Woken	Attenuator	WK0602-XX	N/A	Note 1	
PE	Attenuator	PE7005-10	N/A	Note 1	
PE	Attenuator	PE7005- 3	N/A	Note 1	
AR	Power Amplifier	5S1G4M2	0328767	Note 1	
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	Note 1	
Mini-Circuits	Power Amplifier	ZHL-42W+	13440021344	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.



10. System Verification

10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	22.6	0.881	42.165	0.90	41.50	-2.11	1.60	±5	2014/6/25
835	Head	22.3	0.918	41.074	0.90	41.50	2.00	-1.03	±5	2014/7/27
835	Body	22.5	0.996	54.843	0.97	55.20	2.68	-0.65	±5	2014/6/24
835	Body	22.3	0.963	54.498	0.97	55.20	-0.72	-1.27	±5	2014/7/28
1900	Head	22.4	1.441	38.642	1.40	40.00	2.93	-3.39	±5	2014/6/25
1900	Head	22.6	1.446	38.297	1.40	40.00	3.29	-4.26	±5	2014/7/23
1900	Head	22.6	1.432	38.828	1.40	40.00	2.29	-2.93	±5	2014/8/12
1900	Body	22.2	1.532	52.328	1.52	53.30	0.79	-1.82	±5	2014/6/24
1900	Body	22.3	1.527	51.264	1.52	53.30	0.46	-3.82	±5	2014/6/25
1900	Body	22.3	1.544	52.320	1.52	53.30	1.58	-1.84	±5	2014/7/29
1900	Body	22.6	1.531	52.652	1.52	53.30	0.72	-1.22	±5	2014/8/12
1900	Body	22.2	1.546	52.216	1.52	53.30	1.71	-2.03	±5	2014/9/1
2600	Head	22.6	2.010	37.349	1.96	39.00	2.55	-4.23	±5	2014/6/27
2600	Head	22.5	1.970	38.084	1.96	39.00	0.51	-2.35	±5	2014/7/29
2600	Body	22.6	2.209	51.123	2.16	52.50	2.27	-2.62	±5	2014/6/26
2600	Body	22.5	2.201	52.823	2.16	52.50	1.90	0.62	±5	2014/7/29

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots in Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured SAR (W/kg)	Targeted SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
2014/6/25	835	Head	250	D835V2-499	3925	495	2.26	9.13	9.04	-0.99
2014/7/27	835	Head	250	D835V2-499	3925	495	2.22	9.13	8.88	-2.74
2014/6/24	835	Body	250	D835V2-499	3925	495	2.41	9.46	9.64	1.90
2014/7/28	835	Body	250	D835V2-499	3925	495	2.20	9.46	8.80	-6.98
2014/6/25	1900	Head	250	D1900V2-5d041	3925	495	9.77	41.00	39.08	-4.68
2014/7/23	1900	Head	250	D1900V2-5d041	3954	1425	10.20	41.00	40.80	-0.49
2014/8/12	1900	Head	250	D1900V2-5d041	3954	1425	9.99	41.00	39.96	-2.54
2014/6/24	1900	Body	250	D1900V2-5d041	3925	495	10.00	41.00	40.00	-2.44
2014/6/25	1900	Body	250	D1900V2-5d041	3925	495	10.10	41.00	40.40	-1.46
2014/7/29	1900	Body	250	D1900V2-5d041	3925	495	9.89	41.00	39.56	-3.51
2014/8/12	1900	Body	250	D1900V2-5d041	3925	495	10.40	41.00	41.60	1.46
2014/9/1	1900	Body	250	D1900V2-5d041	3931	577	9.50	41.00	38.00	-7.32
2014/6/27	2600	Head	250	D2600V2-1070	3925	495	12.90	55.60	51.60	-7.19
2014/7/29	2600	Head	250	D2600V2-1070	3925	495	13.90	58.80	55.60	-5.44
2014/6/26	2600	Body	250	D2600V2-1070	3925	495	15.00	55.70	60.00	7.72
2014/7/29	2600	Body	250	D2600V2-1070	3925	495	12.70	55.20	50.80	-7.97




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is < 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06v01r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

1. According to October 2013TCB Workshop, For GSM / EGPRS, the number of time slots to test for SAR should correspond to the highest source-based time-averaged maximum output power configuration include tune-up tolerance and considering the possibility of e.g. 3rd party VoIP operation for head and body-worn SAR testing, the EUT was set in GPRS (3Tx slots) for GSM850, GPRS (4Tx slots) for GSM1900 band due to its highest frame-average power.
2. For hotspot mode SAR testing, GPRS / EDGE should be evaluated, therefore the EUT was set in GPRS 3 Tx slots for GSM850, GPRS 4 Tx slots for GSM1900 band due to its highest frame-average power.

Band GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
	TX Channel	128	189		251	128	189	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM (GMSK, 1 Tx slot)	32.80	32.74	33.05	33.50	23.80	23.74	24.05	24.50
GPRS (GMSK, 1 Tx slot)	32.79	32.73	33.03	33.50	23.79	23.73	24.03	24.50
GPRS (GMSK, 2 Tx slots)	29.58	29.61	29.75	30.60	23.58	23.61	23.75	24.60
GPRS (GMSK, 3 Tx slots)	28.29	28.30	28.35	29.50	24.03	24.04	24.09	25.24
GPRS (GMSK, 4 Tx slots)	26.76	26.73	26.76	27.60	23.76	23.73	23.76	24.60
EDGE (8PSK, 1 Tx slot)	26.68	26.77	26.84	28.00	17.68	17.77	17.84	19.00
EDGE (8PSK, 2 Tx slots)	24.11	24.20	24.27	25.00	18.11	18.20	18.27	19.00
EDGE (8PSK, 3 Tx slots)	22.69	22.68	22.77	24.00	18.43	18.42	18.51	19.74
EDGE (8PSK, 4 Tx slots)	21.55	21.64	21.69	23.00	18.55	18.64	18.69	20.00

Band GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
	TX Channel	512	661		810	512	661	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)	29.39	29.33	29.42	30.50	20.39	20.33	20.42	21.50
GPRS (GMSK, 1 Tx slot)	29.38	29.32	29.40	30.50	20.38	20.32	20.40	21.50
GPRS (GMSK, 2 Tx slots)	26.72	26.67	26.75	27.50	20.72	20.67	20.75	21.50
GPRS (GMSK, 3 Tx slots)	25.01	24.95	25.05	25.50	20.75	20.69	20.79	21.24
GPRS (GMSK, 4 Tx slots)	23.59	23.50	23.61	24.50	20.59	20.50	20.61	21.50
EDGE (8PSK, 1 Tx slot)	25.49	25.48	25.45	26.00	16.49	16.48	16.45	17.00
EDGE (8PSK, 2 Tx slots)	22.93	22.91	22.88	24.00	16.93	16.91	16.88	18.00
EDGE (8PSK, 3 Tx slots)	21.51	21.49	21.45	22.00	17.25	17.23	17.19	17.74
EDGE (8PSK, 4 Tx slots)	20.53	20.50	20.43	21.00	17.53	17.50	17.43	18.00

<For FCC Additional Test Channel>

Band GSM850	Burst Average Power (dBm)		Tune-up Limit (dBm)	Frame-Average Power (dBm)		Tune-up Limit (dBm)
TX Channel	148			148		
Frequency (MHz)	828.2			828.2		
GPRS (GMSK, 3 Tx slots) – CS1	28.84		29.50	24.58		25.24

Band GSM1900	Burst Average Power (dBm)		Tune-up Limit (dBm)	Frame-Average Power (dBm)		Tune-up Limit (dBm)
TX Channel	561	761		561	761	
Frequency (MHz)	1860	1900		1860	1900	
GPRS (GMSK, 4 Tx slots) – CS1	23.44	23.43	24.5	20.44	20.43	21.5

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15, \beta_{HS}/\beta_c = 24/15$. For all other combinations of DPCCH, DPDCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCl
 - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15, \beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration

<WCDMA Conducted Power>

General Note:

1. SAR testing in AMR configuration is not required when the maximum average output of each RF channel for AMR 12.2Kbps is less than 0.25dB higher than that measured in RMC 12.2Kbps
2. Per KDB 941225 D02v02r02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA/DC-HSDPA output power is < 0.25dB higher than RMC, or reported SAR with RMC 12.2kbps setting is $\leq 1.2W/kg$, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded..

Band		WCDMA V			WCDMA II		
TX Channel		4132	4182	4233	9262	9400	9538
Frequency (MHz)		826.4	836.4	846.6	1852.4	1880	1907.6
3GPP Rel 99	AMR 12.2Kbps	22.95	22.92	23.01	22.81	22.88	22.84
	RMC 12.2Kbps	23.00	22.96	23.04	22.84	22.91	22.89
3GPP Rel 6	HSDPA Subtest-1	21.45	21.62	21.98	21.68	22.05	22.11
3GPP Rel 6	HSDPA Subtest-2	21.26	21.44	21.72	21.62	22.02	22.15
3GPP Rel 6	HSDPA Subtest-3	21.00	21.13	21.49	21.02	21.55	21.69
3GPP Rel 6	HSDPA Subtest-4	20.98	21.12	21.45	20.98	21.46	21.62
3GPP Rel 8	DC-HSDPA Subtest-1	21.50	21.62	21.99	21.70	22.07	22.13
3GPP Rel 8	DC-HSDPA Subtest-2	21.25	21.45	21.70	21.65	22.05	22.16
3GPP Rel 8	DC-HSDPA Subtest-3	21.01	21.13	21.50	21.05	21.50	21.60
3GPP Rel 8	DC-HSDPA Subtest-4	21.00	21.15	21.43	20.90	21.40	21.60
3GPP Rel 6	HSUPA Subtest-1	21.13	21.00	21.08	21.70	21.88	21.92
3GPP Rel 6	HSUPA Subtest-2	20.65	20.53	20.60	20.70	20.85	20.93
3GPP Rel 6	HSUPA Subtest-3	20.50	20.39	20.45	20.83	20.95	20.99
3GPP Rel 6	HSUPA Subtest-4	21.12	21.02	21.05	21.16	21.28	21.37
3GPP Rel 6	HSUPA Subtest-5	21.82	21.61	21.75	21.85	21.96	22.03

<For FCC Additional Test Channel>

Band		WCDMA V	WCDMA II	
TX Channel		4141	9300	9500
Frequency (MHz)		828.2	1860	1900
3GPP Rel 99	RMC 12.2Kbps	22.96	23.20	23.23



<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	23.43	23.24	23.10	24	0
20	QPSK	1	49	23.32	23.05	23.05		
20	QPSK	1	99	23.42	23.05	23.09		
20	QPSK	50	0	22.39	22.21	22.14	23	1
20	QPSK	50	24	22.36	22.11	22.02		
20	QPSK	50	49	22.21	22.08	22.13		
20	QPSK	100	0	22.32	22.21	22.04		
20	16QAM	1	0	22.10	22.20	21.94	23	1
20	16QAM	1	49	22.24	22.03	21.97		
20	16QAM	1	99	22.36	22.04	22.02		
20	16QAM	50	0	21.15	21.15	20.95	22	2
20	16QAM	50	24	21.29	21.05	21.00		
20	16QAM	50	49	21.40	21.04	21.06		
20	16QAM	100	0	21.23	21.16	21.02		
Channel				20825	21100	21375	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	22.95	23.04	22.92	24	0
15	QPSK	1	37	23.06	22.95	23.03		
15	QPSK	1	74	23.27	22.98	23.09		
15	QPSK	36	0	21.98	22.03	22.02	23	1
15	QPSK	36	18	22.07	22.04	22.04		
15	QPSK	36	37	22.17	22.02	22.05		
15	QPSK	75	0	22.06	22.02	22.10		
15	16QAM	1	0	21.88	21.96	21.88	23	1
15	16QAM	1	37	22.01	21.95	22.00		
15	16QAM	1	74	22.20	21.95	22.05		
15	16QAM	36	0	20.89	20.94	20.94	22	2
15	16QAM	36	18	20.99	20.96	20.98		
15	16QAM	36	37	21.18	20.95	21.02		
15	16QAM	75	0	21.07	20.93	21.01		
Channel				20800	21100	21400	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	22.96	22.89	22.96	24	0
10	QPSK	1	24	22.98	22.94	22.93		
10	QPSK	1	49	23.09	22.95	23.06		
10	QPSK	25	0	21.97	21.95	22.07	23	1
10	QPSK	25	12	21.98	22.02	22.01		
10	QPSK	25	24	22.07	22.00	22.10		
10	QPSK	50	0	22.04	22.00	22.11		
10	16QAM	1	0	21.86	21.92	21.92	23	1
10	16QAM	1	24	21.87	21.92	21.91		
10	16QAM	1	49	22.04	21.90	22.06		
10	16QAM	25	0	20.90	20.99	21.02	22	2
10	16QAM	25	12	21.01	20.96	20.97		
10	16QAM	25	24	21.11	20.97	21.06		
10	16QAM	50	0	20.96	20.94	21.06		




Channel				20775	21100	21425	Tune up Limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	22.98	22.96	22.93	24	0
5	QPSK	1	12	22.94	22.92	23.01		
5	QPSK	1	24	23.03	22.93	23.08		
5	QPSK	12	0	21.99	21.98	22.08	23	1
5	QPSK	12	6	21.93	22.01	22.08		
5	QPSK	12	11	21.99	21.99	22.11		
5	QPSK	25	0	21.93	22.01	22.06	23	1
5	16QAM	1	0	21.90	21.90	21.88		
5	16QAM	1	12	21.84	21.92	21.93		
5	16QAM	1	24	21.91	21.88	21.97	22	2
5	16QAM	12	0	21.04	20.99	21.04		
5	16QAM	12	6	20.95	20.99	21.05		
5	16QAM	12	11	20.97	20.97	21.08	22	2
5	16QAM	25	0	20.91	20.97	21.04		

<For FCC Additional Test Channel>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Tune up Limit (dBm)	MPR (dB)
Channel				20867		
Frequency (MHz)				2511.7		
20	QPSK	1	0	23.17	24.0	0

13. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤ 25mm	≤ 25mm
Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes

General Note:

- Referring to KDB 941225 D06 v01r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge



14. SAR Test Results

General Note:

1. Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
2. Per KDB 447498 D01v05r02, for each exposure position, if the highest output channel reported SAR > 0.8W/kg, other channels SAR testing is necessary.
3. According to October 2013TCB Workshop, For GSM / EGPRS, the number of time slots to test for SAR should correspond to the highest source-based time-averaged maximum output power configuration include tune-up tolerance and considering the possibility of e.g. 3rd party VoIP operation for head and body-worn SAR testing, the EUT was set in GPRS (3Tx slots) for GSM850, GPRS (4Tx slots) for GSM1900 band due to its highest frame-average power.
4. For hotspot mode SAR testing, GPRS / EDGE should be evaluated, therefore the EUT was set in GPRS 3 Tx slots for GSM850, GPRS 4 Tx slots for GSM1900 band due to its highest frame-average power.
5. Per KDB 941225 D02v02r02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA/DC-HSDPA output power is < 0.25dB higher than RMC, or reported SAR with RMC 12.2kbps setting is ≤ 1.2 W/kg, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded..
6. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
7. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
8. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
9. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is > not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
10. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is > not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.
11. Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
12. While operating in body-adjacent exposure configurations during a mobile hotspot session, reduced power limits are enforced on the GSM1900, WCDMA B2, and LTE B7 transmitter. More detailed information which can be referred to "operational description".
13. This device utilizes dynamic antenna tuning on the main antenna. Please refer to the operational description (Exhibit 12) for functionality description, and FCC the pre-test KDB inquiry (Exhibit 12A) for test guidance. Test results for this specific condition are labeled as Triggered in the Antenna Tuner column contained in the tables below.



14.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Antenna Tuner	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (3 Tx slots)	Right Cheek	non-Trigger	251	848.8	28.35	29.50	1.303	0.03	0.354	0.461
	GSM850	GPRS (3 Tx slots)	Right Cheek	Trigger	251	848.8	28.35	29.50	1.303	0.12	0.424	0.553
	GSM850	GPRS (3 Tx slots)	Right Cheek	Trigger	148	828.2	28.84	29.50	1.164	-0.07	0.502	0.584
01	GSM850	GPRS (3 Tx slots)	Right Cheek	Trigger	189	836.4	28.30	29.50	1.318	-0.03	0.465	0.613
	GSM850	GPRS (3 Tx slots)	Right Tilted	non-Trigger	251	848.8	28.35	29.50	1.303	0.06	0.217	0.283
	GSM850	GPRS (3 Tx slots)	Left Cheek	non-Trigger	251	848.8	28.35	29.50	1.303	0	0.299	0.390
	GSM850	GPRS (3 Tx slots)	Left Tilted	non-Trigger	251	848.8	28.35	29.50	1.303	-0.02	0.208	0.271
	GSM1900	GPRS (4 Tx slots)	Right Cheek	non-Trigger	810	1909.8	23.61	24.50	1.227	0.01	0.104	0.128
	GSM1900	GPRS (4 Tx slots)	Right Tilted	non-Trigger	810	1909.8	23.61	24.50	1.227	0.08	0.040	0.049
	GSM1900	GPRS (4 Tx slots)	Left Cheek	non-Trigger	810	1909.8	23.61	24.50	1.227	0.02	0.149	0.183
	GSM1900	GPRS (4 Tx slots)	Left Cheek	Trigger	810	1909.8	23.61	24.50	1.227	-0.04	0.163	0.200
	GSM1900	GPRS (4 Tx slots)	Left Cheek	Trigger	561	1860	23.44	24.50	1.276	-0.08	0.235	0.300
02	GSM1900	GPRS (4 Tx slots)	Left Cheek	Trigger	661	1880	23.50	24.50	1.259	-0.12	0.284	0.358
	GSM1900	GPRS (4 Tx slots)	Left Tilted	non-Trigger	810	1909.8	23.61	24.50	1.227	0.13	0.044	0.054

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Antenna Tuner	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Right Cheek	non-Trigger	4233	846.6	23.04	24.00	1.247	0.02	0.404	0.504
	WCDMA V	RMC 12.2Kbps	Right Cheek	Trigger	4233	846.6	23.04	24.00	1.247	0.01	0.402	0.501
	WCDMA V	RMC 12.2Kbps	Right Cheek	Trigger	4141	828.2	22.96	24.00	1.271	0.05	0.470	0.597
03	WCDMA V	RMC 12.2Kbps	Right Cheek	Trigger	4182	836.4	22.96	24.00	1.271	-0.01	0.484	0.615
	WCDMA V	RMC 12.2Kbps	Right Tilted	non-Trigger	4233	846.6	23.04	24.00	1.247	-0.02	0.232	0.289
	WCDMA V	RMC 12.2Kbps	Left Cheek	non-Trigger	4233	846.6	23.04	24.00	1.247	0.02	0.330	0.412
	WCDMA V	RMC 12.2Kbps	Left Tilted	non-Trigger	4233	846.6	23.04	24.00	1.247	0.01	0.225	0.281
	WCDMA II	RMC 12.2Kbps	Right Cheek	non-Trigger	9400	1880	22.91	24.00	1.285	-0.05	0.175	0.225
	WCDMA II	RMC 12.2Kbps	Right Tilted	non-Trigger	9400	1880	22.91	24.00	1.285	0.02	0.095	0.122
04	WCDMA II	RMC 12.2Kbps	Left Cheek	non-Trigger	9400	1880	22.91	24.00	1.285	0.07	0.320	0.411
	WCDMA II	RMC 12.2Kbps	Left Cheek	Trigger	9400	1880	22.91	24.00	1.285	0.12	0.298	0.383
	WCDMA II	RMC 12.2Kbps	Left Cheek	Trigger	9300	1860	23.20	24.00	1.202	-0.06	0.261	0.314
	WCDMA II	RMC 12.2Kbps	Left Cheek	Trigger	9500	1900	23.23	24.00	1.194	-0.13	0.284	0.339
	WCDMA II	RMC 12.2Kbps	Left Tilted	non-Trigger	9400	1880	22.91	24.00	1.285	0.04	0.092	0.118

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Antenna Tuner	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	0	Right Cheek	non-Trigger	20850	2510	23.43	24.00	1.140	0.01	0.159	0.181
	LTE Band 7	20M	QPSK	50	0	Right Cheek	non-Trigger	20850	2510	22.39	23.00	1.151	-0.05	0.136	0.157
	LTE Band 7	20M	QPSK	1	0	Right Tilted	non-Trigger	20850	2510	23.43	24.00	1.140	0.09	0.195	0.222
	LTE Band 7	20M	QPSK	50	0	Right Tilted	non-Trigger	20850	2510	22.39	23.00	1.151	-0.02	0.158	0.182
	LTE Band 7	20M	QPSK	1	0	Left Cheek	non-Trigger	20850	2510	23.43	24.00	1.140	-0.03	0.248	0.283
	LTE Band 7	20M	QPSK	50	0	Left Cheek	non-Trigger	20850	2510	22.39	23.00	1.151	-0.06	0.196	0.226
	LTE Band 7	20M	QPSK	1	0	Left Cheek	Trigger	20850	2510	23.43	24.00	1.140	-0.04	0.235	0.268
05	LTE Band 7	20M	QPSK	1	0	Left Cheek	Trigger	21100	2535	23.24	24.00	1.191	-0.07	0.355	0.423
	LTE Band 7	20M	QPSK	1	0	Left Cheek	Trigger	21333	2558.3	23.17	24.00	1.211	-0.03	0.311	0.376
	LTE Band 7	20M	QPSK	50	0	Left Cheek	Trigger	20850	2510	22.39	23.00	1.151	0	0.188	0.216
	LTE Band 7	20M	QPSK	1	0	Left Tilted	non-Trigger	20850	2510	23.43	24.00	1.140	0.03	0.139	0.158
	LTE Band 7	20M	QPSK	50	0	Left Tilted	non-Trigger	20850	2510	22.39	23.00	1.151	0.05	0.113	0.130



14.2 Wireless Router SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (3 Tx slots)	Front	1cm	OFF	251	848.8	28.35	29.50	1.303	-0.01	0.512	0.667
	GSM850	GPRS (3 Tx slots)	Back	1cm	OFF	251	848.8	28.35	29.50	1.303	0.03	0.482	0.628
	GSM850	GPRS (3 Tx slots)	Left Side	1cm	OFF	251	848.8	28.35	29.50	1.303	-0.05	0.434	0.566
	GSM850	GPRS (3 Tx slots)	Right Side	1cm	OFF	251	848.8	28.35	29.50	1.303	-0.05	0.639	0.833
	GSM850	GPRS (3 Tx slots)	Right Side	1cm	OFF	128	824.2	28.29	29.50	1.321	0	0.669	0.884
06	GSM850	GPRS (3 Tx slots)	Right Side	1cm	OFF	189	836.4	28.30	29.50	1.318	-0.01	0.692	0.912
	GSM850	GPRS (3 Tx slots)	Bottom Side	1cm	OFF	251	848.8	28.35	29.50	1.303	-0.01	0.200	0.261
	GSM1900	GPRS (4 Tx slots)	Front	1cm	ON	810	1909.8		22.00	1.000	0.05	0.482	0.482
	GSM1900	GPRS (4 Tx slots)	Back	1cm	ON	810	1909.8		22.00	1.000	0.07	0.410	0.410
	GSM1900	GPRS (4 Tx slots)	Left Side	1cm	ON	810	1909.8		22.00	1.000	0.02	0.075	0.075
	GSM1900	GPRS (4 Tx slots)	Right Side	1cm	ON	810	1909.8		22.00	1.000	-0.04	0.047	0.047
07	GSM1900	GPRS (4 Tx slots)	Bottom Side	1cm	ON	810	1909.8		22.00	1.000	0.09	0.701	0.701

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	1cm	OFF	4233	846.6	23.04	24.00	1.247	-0.01	0.569	0.710
	WCDMA V	RMC 12.2Kbps	Back	1cm	OFF	4233	846.6	23.04	24.00	1.247	0	0.529	0.660
	WCDMA V	RMC 12.2Kbps	Left Side	1cm	OFF	4233	846.6	23.04	24.00	1.247	-0.03	0.474	0.591
08	WCDMA V	RMC 12.2Kbps	Right Side	1cm	OFF	4233	846.6	23.04	24.00	1.247	0	0.754	0.941
	WCDMA V	RMC 12.2Kbps	Right Side	1cm	OFF	4132	826.4	23.00	24.00	1.259	-0.01	0.693	0.872
	WCDMA V	RMC 12.2Kbps	Right Side	1cm	OFF	4182	836.4	22.96	24.00	1.271	-0.01	0.719	0.914
	WCDMA V	RMC 12.2Kbps	Bottom Side	1cm	OFF	4233	846.6	23.04	24.00	1.247	0.04	0.224	0.279
	WCDMA II	RMC 12.2Kbps	Front	1cm	ON	9400	1880		18.50	1.000	-0.03	0.471	0.471
	WCDMA II	RMC 12.2Kbps	Back	1cm	ON	9400	1880		18.50	1.000	-0.02	0.521	0.521
	WCDMA II	RMC 12.2Kbps	Left Side	1cm	ON	9400	1880		18.50	1.000	-0.08	0.044	0.044
	WCDMA II	RMC 12.2Kbps	Right Side	1cm	ON	9400	1880		18.50	1.000	-0.09	0.027	0.027
09	WCDMA II	RMC 12.2Kbps	Bottom Side	1cm	ON	9400	1880		18.50	1.000	-0.04	0.695	0.695

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (cm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	0	Front	1cm	ON	20850	2510		20.50	1.000	0.04	0.448	0.448
	LTE Band 7	20M	QPSK	50	0	Front	1cm	ON	20850	2510		20.50	1.000	-0.02	0.481	0.481
	LTE Band 7	20M	QPSK	1	0	Back	1cm	ON	20850	2510		20.50	1.000	0.01	0.365	0.365
	LTE Band 7	20M	QPSK	50	0	Back	1cm	ON	20850	2510		20.50	1.000	-0.01	0.393	0.393
	LTE Band 7	20M	QPSK	1	0	Left Side	1cm	ON	20850	2510		20.50	1.000	-0.06	0.147	0.147
	LTE Band 7	20M	QPSK	50	0	Left Side	1cm	ON	20850	2510		20.50	1.000	0.07	0.124	0.124
	LTE Band 7	20M	QPSK	1	0	Right Side	1cm	ON	20850	2510		20.50	1.000	-0.12	0.048	0.048
	LTE Band 7	20M	QPSK	50	0	Right Side	1cm	ON	20850	2510		20.50	1.000	-0.02	0.049	0.049
	LTE Band 7	20M	QPSK	1	0	Bottom Side	1cm	ON	20850	2510		20.50	1.000	-0.08	0.830	0.830
	LTE Band 7	20M	QPSK	1	0	Bottom Side	1cm	ON	21100	2535		20.50	1.000	-0.02	0.928	0.928
	LTE Band 7	20M	QPSK	1	0	Bottom Side	1cm	ON	21350	2560		20.50	1.000	0.03	0.923	0.923
	LTE Band 7	20M	QPSK	50	0	Bottom Side	1cm	ON	20850	2510		20.50	1.000	0.03	0.881	0.881
	LTE Band 7	20M	QPSK	50	0	Bottom Side	1cm	ON	21100	2535		20.50	1.000	0	0.905	0.905
10	LTE Band 7	20M	QPSK	50	0	Bottom Side	1cm	ON	21350	2560		20.50	1.000	-0.04	0.937	0.937
	LTE Band 7	20M	QPSK	100	0	Bottom Side	1cm	ON	20850	2510		20.50	1.000	0.01	0.863	0.863



14.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Headset	Antenna Tuner	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
11	GSM850	GPRS (3 Tx slots)	Front	1.5cm		non-Trigger	251	848.8	28.35	29.50	1.303	-0.01	0.447	0.583
	GSM850	GPRS (3 Tx slots)	Front	1.5cm	Headset	Trigger	251	848.8	28.35	29.50	1.303	0.02	0.389	0.507
	GSM850	GPRS (3 Tx slots)	Front	1.5cm	Headset	Trigger	148	828.2	28.84	29.50	1.164	-0.01	0.462	0.538
	GSM850	GPRS (3 Tx slots)	Front	1.5cm	Headset	Trigger	189	836.4	28.30	29.50	1.318	0.01	0.430	0.567
	GSM850	GPRS (3 Tx slots)	Back	1.5cm		non-Trigger	251	848.8	28.35	29.50	1.303	-0.02	0.430	0.560
	GSM1900	GPRS (4 Tx slots)	Front	1.5cm		non-Trigger	810	1909.8	23.61	24.50	1.227	-0.07	0.462	0.567
	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	Headset	Trigger	810	1909.8	23.61	24.50	1.227	0.03	0.493	0.605
	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	Headset	Trigger	561	1860	23.44	24.50	1.276	0.11	0.507	0.647
	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	Headset	Trigger	661	1880	23.50	24.50	1.259	-0.16	0.514	0.647
12	GSM1900	GPRS (4 Tx slots)	Front	1.5cm	Headset	Trigger	761	1900	23.43	24.50	1.279	0.08	0.516	0.660
	GSM1900	GPRS (4 Tx slots)	Back	1.5cm		non-Trigger	810	1909.8	23.61	24.50	1.227	-0.05	0.419	0.514

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Headset	Antenna Tuner	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
13	WCDMA V	RMC 12.2Kbps	Front	1.5cm		non-Trigger	4233	846.6	23.04	24.00	1.247	0.01	0.508	0.634
	WCDMA V	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	4233	846.6	23.04	24.00	1.247	0.03	0.478	0.596
	WCDMA V	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	4141	828.2	22.96	24.00	1.271	-0.01	0.395	0.502
	WCDMA V	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	4182	836.4	22.96	24.00	1.271	-0.02	0.390	0.496
	WCDMA V	RMC 12.2Kbps	Back	1.5cm		non-Trigger	4233	846.6	23.04	24.00	1.247	0	0.469	0.585
	WCDMA II	RMC 12.2Kbps	Front	1.5cm		non-Trigger	9400	1880	22.91	24.00	1.285	-0.01	0.758	0.974
	WCDMA II	RMC 12.2Kbps	Front	1.5cm		non-Trigger	9262	1852.4	22.84	24.00	1.306	-0.02	0.694	0.906
	WCDMA II	RMC 12.2Kbps	Front	1.5cm		non-Trigger	9538	1907.6	22.89	24.00	1.291	0.01	0.770	0.994
	WCDMA II	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	9400	1880	22.91	24.00	1.285	-0.03	0.848	1.090
	WCDMA II	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	9262	1852.4	22.84	24.00	1.306	-0.04	0.802	1.048
	WCDMA II	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	9300	1860	23.20	24.00	1.202	-0.09	0.849	1.021
14	WCDMA II	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	9538	1907.6	22.89	24.00	1.291	-0.06	0.853	1.101
	WCDMA II	RMC 12.2Kbps	Back	1.5cm		non-Trigger	9400	1880	22.91	24.00	1.285	0.11	0.602	0.774

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (cm)	Headset	Antenna Tuner	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	0	Front	1.5cm		non-Trigger	20850	2510	23.43	24.00	1.140	0.03	0.646	0.737
	LTE Band 7	20M	QPSK	50	0	Front	1.5cm		non-Trigger	20850	2510	22.39	23.00	1.151	-0.01	0.515	0.593
15	LTE Band 7	20M	QPSK	1	0	Front	1.5cm	Headset	Trigger	20850	2510	23.43	24.00	1.140	-0.03	0.651	0.742
	LTE Band 7	20M	QPSK	1	0	Front	1.5cm	Headset	Trigger	21100	2535	23.24	24.00	1.191	-0.19	0.569	0.678
	LTE Band 7	20M	QPSK	1	0	Front	1.5cm	Headset	Trigger	21333	2558.3	23.17	24.00	1.211	-0.01	0.593	0.718
	LTE Band 7	20M	QPSK	50	0	Front	1.5cm	Headset	Trigger	20850	2510	22.39	23.00	1.151	0.04	0.523	0.602
	LTE Band 7	20M	QPSK	1	0	Back	1.5cm		non-Trigger	20850	2510	23.43	24.00	1.140	-0.04	0.613	0.699
	LTE Band 7	20M	QPSK	50	0	Back	1.5cm		non-Trigger	20850	2510	22.39	23.00	1.151	0.02	0.498	0.573

14.4 Repeated SAR Measurement

No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (cm)	Headset	Antenna Tuner	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	-	9538	1907.6	22.89	24.00	1.291	-0.06	0.853	-	1.101
2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Front	1.5cm	Headset	Trigger	-	9538	1907.6	22.89	24.00	1.291	-0.03	0.825	1.03	1.065
1st	LTE Band 7	20M	QPSK	50	0	-	Bottom Side	1cm	-	-	ON	21350	2560	-	20.50	1.000	-0.04	0.937	-	0.937
2nd	LTE Band 7	20M	QPSK	50	0	-	Bottom Side	1cm	-	-	ON	21350	2560	-	20.50	1.000	0.07	0.924	1.01	0.924

General Note:

1. Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8W/kg$
2. Per KDB 865664 D01v01r03, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45W/kg$, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Mobile Phone			Note
		Head	Body-worn	Wireless Router	
1.	GSM(Voice) + WLAN2.4GHz(data)	Yes	Yes		
2.	WCDMA(Voice) + WLAN2.4GHz(data)	Yes	Yes		
3.	GSM(Voice) + Bluetooth(data)	Yes	Yes		
4.	WCDMA((Voice) + Bluetooth(data)	Yes	Yes		
5.	GSM(Voice) + WLAN5GHz(data)	Yes	Yes		
6.	WCDMA((Voice) + WLAN5GHz(data)	Yes	Yes		
7.	GPRS/EDGE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
8.	WCDMA(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
9.	LTE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
10.	GPRS/EDGE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
11.	WCDMA(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
12.	LTE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
13.	GPRS/EDGE(data) + WLAN5GHz(data)	Yes	Yes	Yes	WiFi Direct
14.	WCDMA(data) + WLAN5GHz(data)	Yes	Yes	Yes	WiFi Direct
15.	LTE(data) + WLAN5GHz(data)	Yes	Yes	Yes	WiFi Direct

General Note:

1. This device supported VoIP in EGPRS, WCDMA, LTE (e.g. 3rd party VoIP).
2. The 2.4GHz / 5GHz WLAN and Bluetooth conducted power and SAR testing results were referred to Sporton FCC SAR Test Report, Brand Name: Motorola Mobility LLC, Model Name: 3578, FCC ID: IHDT56QA1, Report No: FA442943A and also used perform transmission simultaneous analysis.
3. The worst case 2.4GHz / 5GHz WLAN reported SAR for each configuration was used for SAR summation, Therefore, the following summations represent the absolute worst cases for simultaneous transmission with the WLAN.
4. Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)1.5 / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg
 - v) The SPLSR calculated results please refer to section 15.4.



15.1 Head Exposure Conditions

WWAN Band	Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No	
		WWAN	2.4GHz WLAN	2.4GHz Bluetooth					
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)					
GSM	GSM850	Right Cheek	0.613	0.788	0.189	1.40	0.80		
		Right Tilted	0.283	0.248	0.058	0.53	0.34		
		Left Cheek	0.390	0.178	0.041	0.57	0.43		
		Left Tilted	0.271	0.201	0.044	0.47	0.32		
	GSM1900	Right Cheek	0.128	0.788	0.189	0.92	0.32		
		Right Tilted	0.049	0.248	0.058	0.30	0.11		
		Left Cheek	0.358	0.178	0.041	0.54	0.40		
		Left Tilted	0.054	0.201	0.044	0.26	0.10		
WCMDA	Band V	Right Cheek	0.615	0.788	0.189	1.40	0.80		
		Right Tilted	0.289	0.248	0.058	0.54	0.35		
		Left Cheek	0.412	0.178	0.041	0.59	0.45		
		Left Tilted	0.281	0.201	0.044	0.48	0.33		
	Band II	Right Cheek	0.225	0.788	0.189	1.01	0.41		
		Right Tilted	0.122	0.248	0.058	0.37	0.18		
		Left Cheek	0.411	0.178	0.041	0.59	0.45		
		Left Tilted	0.118	0.201	0.044	0.32	0.16		
LTE	Band 7	Right Cheek	0.181	0.788	0.189	0.97	0.37		
		Right Tilted	0.222	0.248	0.058	0.47	0.28		
		Left Cheek	0.423	0.178	0.041	0.60	0.46		
		Left Tilted	0.158	0.201	0.044	0.36	0.20		

WWAN Band	Exposure Position	1	2		1+2 Summed SAR (W/kg)	SPLSR Results	Case No	
		WWAN	5.2GHz / 5.3GHz / 5.5GHz / 5.8GHz WLAN					
		SAR (W/kg)	Band	SAR (W/kg)				
GSM	GSM850	Right Cheek	0.613	5.2GHz WLAN	1.462	2.08	0.03	Case 1
		Right Tilted	0.283	5.2GHz WLAN	1.106	1.39		
		Left Cheek	0.390	5.2GHz WLAN	0.345	0.74		
		Left Tilted	0.271	5.2GHz WLAN	0.381	0.65		
	GSM1900	Right Cheek	0.128	5.2GHz WLAN	1.462	1.59		
		Right Tilted	0.049	5.2GHz WLAN	1.106	1.16		
		Left Cheek	0.358	5.2GHz WLAN	0.345	0.70		
		Left Tilted	0.054	5.2GHz WLAN	0.381	0.44		
WCMDA	Band V	Right Cheek	0.615	5.2GHz WLAN	1.462	2.08	0.04	Case 2
		Right Tilted	0.289	5.2GHz WLAN	1.106	1.40		
		Left Cheek	0.412	5.2GHz WLAN	0.345	0.76		
		Left Tilted	0.281	5.2GHz WLAN	0.381	0.66		
	Band II	Right Cheek	0.225	5.2GHz WLAN	1.462	1.69	0.04	Case 3
		Right Tilted	0.122	5.2GHz WLAN	1.106	1.23		
		Left Cheek	0.411	5.2GHz WLAN	0.345	0.76		
		Left Tilted	0.118	5.2GHz WLAN	0.381	0.50		
LTE	Band 7	Right Cheek	0.181	5.2GHz WLAN	1.462	1.64	0.02	Case 4
		Right Tilted	0.222	5.2GHz WLAN	1.106	1.33		
		Left Cheek	0.423	5.2GHz WLAN	0.345	0.77		
		Left Tilted	0.158	5.2GHz WLAN	0.381	0.54		



15.2 Wireless Router Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	2.4GHz Bluetooth				
			SAR (W/kg)	SAR (W/kg)	SAR (W/kg)				
GSM	GSM850	Front	0.667	0.077	0.024	0.74	0.69		
		Back	0.628	0.050	0.019	0.68	0.65		
		Left side	0.566	0.156	0.037	0.72	0.60		
		Right side	0.912			0.91	0.91		
		Top side		0.042	0.011	0.04	0.01		
		Bottom side	0.261			0.26	0.26		
	GSM1900	Front	0.482	0.077	0.024	0.56	0.51		
		Back	0.410	0.050	0.019	0.46	0.43		
		Left side	0.075	0.156	0.037	0.23	0.11		
		Right side	0.047			0.05	0.05		
		Top side		0.042	0.011	0.04	0.01		
		Bottom side	0.701			0.70	0.70		
WCMDA	Band V	Front	0.710	0.077	0.024	0.79	0.73		
		Back	0.660	0.050	0.019	0.71	0.68		
		Left side	0.591	0.156	0.037	0.75	0.63		
		Right side	0.941			0.94	0.94		
		Top side		0.042	0.011	0.04	0.01		
		Bottom side	0.279			0.28	0.28		
	Band II	Front	0.471	0.077	0.024	0.55	0.50		
		Back	0.521	0.050	0.019	0.57	0.54		
		Left side	0.044	0.156	0.037	0.20	0.08		
		Right side	0.027			0.03	0.03		
		Top side		0.042	0.011	0.04	0.01		
		Bottom side	0.695			0.70	0.70		
LTE	Band 7	Front	0.481	0.077	0.024	0.56	0.51		
		Back	0.393	0.050	0.019	0.44	0.41		
		Left side	0.147	0.156	0.037	0.30	0.18		
		Right side	0.049			0.05	0.05		
		Top side		0.042	0.011	0.04	0.01		
		Bottom side	0.937			0.94	0.94		



WWAN Band		Exposure Position	1	2		1+2 Summed SAR (W/kg)	SPLSR	Case No
			WWAN	5.2GHz / 5.8GHz WLAN				
			SAR (W/kg)	Band	SAR (W/kg)			
GSM	GSM850	Front	0.667	5.2GHz WLAN	0.134	0.80		
		Back	0.628	5.8GHz WLAN	0.212	0.84		
		Left side	0.566	5.2GHz WLAN	0.141	0.71		
		Right side	0.912			0.91		
		Top side		5.2GHz WLAN	0.189	0.19		
		Bottom side	0.261			0.26		
	GSM1900	Front	0.482	5.2GHz WLAN	0.134	0.62		
		Back	0.410	5.8GHz WLAN	0.212	0.62		
		Left side	0.075	5.2GHz WLAN	0.141	0.22		
		Right side	0.047			0.05		
		Top side		5.2GHz WLAN	0.189	0.19		
		Bottom side	0.701			0.70		
WCMDA	Band V	Front	0.710	5.2GHz WLAN	0.134	0.84		
		Back	0.660	5.8GHz WLAN	0.212	0.87		
		Left side	0.591	5.2GHz WLAN	0.141	0.73		
		Right side	0.941			0.94		
		Top side		5.2GHz WLAN	0.189	0.19		
		Bottom side	0.279			0.28		
	Band II	Front	0.471	5.2GHz WLAN	0.134	0.61		
		Back	0.521	5.8GHz WLAN	0.212	0.73		
		Left side	0.044	5.2GHz WLAN	0.141	0.19		
		Right side	0.027			0.03		
		Top side		5.2GHz WLAN	0.189	0.19		
		Bottom side	0.695			0.70		
LTE	Band 7	Front	0.481	5.2GHz WLAN	0.134	0.62		
		Back	0.393	5.8GHz WLAN	0.212	0.61		
		Left side	0.147	5.2GHz WLAN	0.141	0.29		
		Right side	0.049			0.05		
		Top side		5.2GHz WLAN	0.189	0.19		
		Bottom side	0.937			0.94		



15.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed SAR (W/kg)	1+3 Summed SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	2.4GHz Bluetooth				
			SAR (W/kg)	SAR (W/kg)	SAR (W/kg)				
GSM	GSM850	Front	0.583	0.072	0.011	0.66	0.59		
		Back	0.560	0.060	0.017	0.62	0.58		
		Front with Headset	0.567	0.072	0.011	0.64	0.58		
	GSM1900	Front	0.567	0.072	0.011	0.64	0.58		
		Back	0.514	0.060	0.017	0.57	0.53		
		Front with Headset	0.660	0.072	0.011	0.73	0.67		
WCMDA	Band V	Front	0.634	0.072	0.011	0.71	0.65		
		Back	0.585	0.060	0.017	0.65	0.60		
		Front with Headset	0.596	0.072	0.011	0.67	0.61		
	Band II	Front	0.994	0.072	0.011	1.07	1.01		
		Back	0.774	0.060	0.017	0.83	0.79		
		Front with Headset	1.101	0.072	0.011	1.17	1.11		
LTE	Band 7	Front	0.737	0.072	0.011	0.81	0.75		
		Back	0.699	0.060	0.017	0.76	0.72		
		Front with Headset	0.742	0.072	0.011	0.81	0.75		


WWAN Band		Exposure Position	1	2		1+2 Summed SAR (W/kg)	SPLSR	Case No
			WWAN	5.2GHz / 5.3GHz / 5.5GHz / 5.8GHz WLAN				
			SAR (W/kg)	Band	SAR (W/kg)			
GSM	GSM850	Front	0.583	5.2GHz WLAN	0.075	0.66		
		Back	0.560	5.5GHz WLAN	0.402	0.96		
		Front with Headset	0.567	5.2GHz WLAN	0.075	0.64		
	GSM1900	Front	0.567	5.2GHz WLAN	0.075	0.64		
		Back	0.514	5.5GHz WLAN	0.402	0.92		
		Front with Headset	0.660	5.2GHz WLAN	0.075	0.74		
WCMDA	Band V	Front	0.634	5.2GHz WLAN	0.075	0.71		
		Back	0.585	5.5GHz WLAN	0.402	0.99		
		Front with Headset	0.596	5.2GHz WLAN	0.075	0.67		
	Band II	Front	0.994	5.2GHz WLAN	0.075	1.07		
		Back	0.774	5.5GHz WLAN	0.402	1.18		
		Front with Headset	1.101	5.2GHz WLAN	0.075	1.18		
LTE	Band 7	Front	0.737	5.2GHz WLAN	0.075	0.81		
		Back	0.699	5.5GHz WLAN	0.402	1.10		
		Back with Headset	0.742	5.2GHz WLAN	0.075	0.82		

15.4 SPLSR Evaluation and Analysis


General Note:

- SPLSR = $(SAR_1 + SAR_2)^{1.5} / (min. \text{ separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary

Case 1	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	GSM850				X	Y	Z				
	5.2GHz WLAN	Right Cheek	0.613	0	0.0668	-0.26	-0.172	86.3	2.08	0.03	Not required
			1.462	0	0.0299	-0.338	-0.171				




Case 2	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	Band V				X	Y	Z				
	5.2GHz WLAN	Right Cheek	0.615	0	0.0671	-0.264	-0.173	82.8	2.08	0.04	Not required
			1.462	0	0.0299	-0.338	-0.171				



Case 3	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	Band II				X	Y	Z				
	5.2GHz WLAN	Right Cheek	0.225	0	0.0722	-0.304	-0.171	54.3	1.69	0.04	Not required
			1.462	0	0.0299	-0.338	-0.171				



Case 4	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	Band 7				X	Y	Z				
	5.2GHz WLAN	Right Cheek	0.181	0	0.073	-0.243	-0.167	104.4	1.64	0.02	Not required
			1.462	0	0.0299	-0.338	-0.171				



Test Engineer : San Lin, Ken Lee, Domo Hsiao, Tom Jiang, Iran Wang, and Aaron Chen

16. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) κ is the coverage factor

Table 16.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 16.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz



17. References

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992
- [3] IEEE Std. 1528-2003, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 447498 D01 v05r02, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Feb 2014
- [6] FCC KDB 648474 D04 v01r02, “SAR Evaluation Considerations for Wireless Handsets”, Dec 2013.
- [7] FCC KDB 941225 D01 v02, “SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA”, October 2007
- [8] FCC KDB 941225 D02 v02r02, “SAR Guidance for HSPA, HSPA+, DC-HSDPA and 1x-Advanced”, May 2013.
- [9] FCC KDB 941225 D03 v01, “Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE”, December 2008
- [10] FCC KDB 941225 D05 v02r03, “SAR Evaluation Considerations for LTE Devices”, Dec 2013
- [11] FCC KDB 941225 D06 v01r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", May 2013.
- [12] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014.
- [13] FCC KDB 865664 D02 v01r01, “RF Exposure Compliance Reporting and Documentation Considerations” May 2013.