


FCC SAR Test Report

APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : 4247
FCC ID : IHDT56QG1
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Administration Data	4
3. Guidance Standard	5
4. Equipment Under Test (EUT)	5
4.1 General Information	5
4.2 Maximum Tune-up Limit.....	6
4.3 General LTE SAR Test and Reporting Considerations	7
5. RF Exposure Limits.....	8
5.1 Uncontrolled Environment.....	8
5.2 Controlled Environment.....	8
6. Specific Absorption Rate (SAR).....	9
6.1 Introduction	9
6.2 SAR Definition.....	9
7. System Description and Setup	10
8. Measurement Procedures	11
8.1 Spatial Peak SAR Evaluation.....	11
8.2 Power Reference Measurement.....	12
8.3 Area Scan	12
8.4 Zoom Scan.....	13
8.5 Volume Scan Procedures.....	13
8.6 Power Drift Monitoring.....	13
9. Test Equipment List.....	14
10. System Verification	15
10.1 Tissue Verification	15
10.2 System Performance Check Results.....	16
11. RF Exposure Positions	17
11.1 Ear and handset reference point	17
11.2 Definition of the cheek position.....	18
11.3 Definition of the tilt position.....	19
11.4 Body Worn Accessory	20
11.5 Wireless Router.....	20
12. Conducted RF Output Power (Unit: dBm).....	21
13. Antenna Location	38
14. SAR Test Results	39
14.1 Head SAR	40
14.2 Hotspot SAR	43
14.3 Body Worn Accessory SAR.....	46
14.4 Repeated SAR Measurement	48
15. Simultaneous Transmission Analysis	49
15.1 Head Exposure Conditions	50
15.2 Hotspot Exposure Conditions.....	51
15.3 Body-Worn Accessory Exposure Conditions	53
16. Uncertainty Assessment	54
17. References.....	56
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA542019A	Rev. 01	Initial issue of report	May. 22, 2015



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility, LLC, Mobile Cellular Phone, 4247**, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary			Highest Simultaneous Transmission SAR (W/kg)
		Head (Separation 0mm)	Body-worn (Separation 15mm)	Wireless Router (Separation 10mm)	
		1g SAR (W/kg)			
PCE	GSM850	0.74	0.55	0.64	1.38
	GSM1900	0.39	0.46	0.97	
	WCDMA Band V	0.65	0.62	0.67	
	WCDMA Band IV	0.62	1.08	0.71	
	WCDMA Band II	0.44	0.61	1.21	
	LTE Band 12	0.50	0.63	0.90	
	LTE Band 17	0.55	0.74	0.93	
	LTE Band 5	0.63	0.56	0.68	
	LTE Band 4	0.43	0.76	1.33	
	LTE Band 2	0.73	1.10	1.33	
	LTE Band 7	0.27	1.13	0.76	
DTS	2.4GHz WLAN	0.49	0.05	0.09	1.38
DSS	Bluetooth	0.09	0.01	0.02	1.33
Date of Testing:		2015/5/2 ~ 2015/5/20			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Motorola Mobility, LLC
Address	222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

Manufacturer	
Company Name	Motorola Mobility, LLC
Address	222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States



3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02
- FCC KDB 941225 D01 3G SAR Procedures v03
- FCC KDB 941225 D05 SAR for LTE Devices v02r03
- FCC KDB 941225 D06 Hotspot Mode SAR v02

4. Equipment Under Test (EUT)

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	4247
FCC ID	IHDT56QG1
IMEI Code	355488060038609
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	• GSM/GPRS/EGPRS • RMC/AMR 12.2Kbps • HSDPA • HSUPA • LTE: QPSK, 16QAM • 802.11b/g/n HT20 • Bluetooth v3.0 with EDR • Bluetooth v4.0 with LE
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: 1. While operating in body-adjacent exposure configurations during a mobile hotspot session, reduced power limits are enforced on the WCDMA B4 and LTE B2 / B7 transmitter. More detailed information which can be referred to “operational description”.	

4.2 Maximum Tune-up Limit

Mode	Burst average power(dBm)	
	GSM 850	GSM 1900
GSM (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 2 Tx slots)	32.00	29.00
GPRS (GMSK, 3 Tx slots)	30.00	27.00
GPRS (GMSK, 4 Tx slots)	28.00	25.00
EDGE (8PSK, 1 Tx slot)	28.00	27.00
EDGE (8PSK, 2 Tx slots)	26.00	25.00
EDGE (8PSK, 3 Tx slots)	24.00	23.00
EDGE (8PSK, 4 Tx slots)	22.00	21.00

Band / Mode			Average power(dBm)
WCDMA	Band V / IV / II	AMR / RMC 12.2Kbps	24.00
		HSDPA Subtest-1	23.00
		HSUPA Subtest-5	23.00
LTE		Band 12	24.00
		Band 17	24.00
		Band 5	24.00
		Band 4	24.00
		Band 2	24.00
		Band 7	24.00

Mode			Average Power (dBm)
2.4GHz WLAN	802.11b		16.00
	802.11g	CH 1	14.00
		CH 6	15.50
		CH 11	12.00
	802.11n-HT20	CH 1	13.00
		CH 6	14.50
		CH 11	9.50
Bluetooth	v3.0 with EDR		10.00
	v4.0 with LE		1.00

4.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r03																																																										
FCC ID	IHDT56QG1																																																									
Equipment Name	Mobile Cellular Phone																																																									
Operating Frequency Range of each LTE transmission band	LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz																																																									
Channel Bandwidth	LTE Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 05: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 04: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 02: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz																																																									
Release and Category	Rel10, Cat4																																																									
uplink modulations used	QPSK, and 16QAM																																																									
LTE Voice / Data requirements	Voice and Data																																																									
LTE MPR permanently built-in by design	<table><tr><th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</th></tr><tr><th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th><th rowspan="2">MPR (dB)</th></tr><tr><th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr><tr><td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr></table>												Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3								Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3																																																										
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																																			
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																				
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																			
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																			
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																			
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																									
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																									
Power reduction applied to satisfy SAR compliance	Yes, When operating in hotspot mode that LTE B2 / B7 power reduction applied to satisfy SAR compliance.																																																									
Transmission (H, M, L) channel numbers and frequencies in each LTE band																																																										
LTE Band 12																																																										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz																																																			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																																		
L	23017	699.7	23025	700.5	23035	701.5	23060	704																																																		
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5																																																		
H	23173	715.3	23165	714.5	23155	713.5	23130	711																																																		
LTE Band 17																																																										
	Bandwidth 5 MHz				Bandwidth 10 MHz																																																					
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)																																																			
L	23755		706.5		23780		709																																																			
M	23790		710		23790		710																																																			
H	23825		713.5		23800		711																																																			
LTE Band 5																																																										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz																																																			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																																		
L	20407	824.7	20415	825.5	20425	826.5	20450	829																																																		
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5																																																		
H	20643	848.3	20635	847.5	20625	846.5	20600	844																																																		
LTE Band 4																																																										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz																																															
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																														
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720																																														
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5																																														
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745																																														
LTE Band 2																																																										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz																																															
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																														
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860																																														
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880																																														
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900																																														
LTE Band 7																																																										
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz																																																			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)																																																
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510																																																		
M	21100	2535	21100	2535	21100	2535	21100	2535																																																		
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560																																																		

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1099	Nov. 19, 2014	Nov. 18, 2015
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 20, 2015	Mar. 19, 2016
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 14, 2014	Nov. 13, 2015
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Mar. 24, 2015	Mar. 23, 2016
SPEAG	2450MHz System Validation Kit	D2450V2	924	Nov. 19, 2014	Nov. 18, 2015
SPEAG	2600MHz System Validation Kit	D2600V2	1070	Nov. 19, 2014	Nov. 18, 2015
SPEAG	Data Acquisition Electronics	DAE4	1388	Sep. 24, 2014	Sep. 23, 2015
SPEAG	Data Acquisition Electronics	DAE3	577	Oct. 06, 2014	Oct. 05, 2015
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 13, 2014	Nov. 12, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3697	Sep. 29, 2014	Sep. 28, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3578	Mar. 31, 2015	Mar. 30, 2016
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Sep. 25, 2014	Sep. 24, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3954	Nov. 21, 2014	Nov. 20, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3955	Nov. 21, 2014	Nov. 20, 2015
Wisewind	Thermometer	ETP-101	TM560	Oct. 21, 2014	Oct. 20, 2015
WonDer	Thermometer	WD-5015	TM685	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	HTC-1	TM642	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	HTC-1	TM281	Oct. 21, 2014	Oct. 20, 2015
H.M.IRIS	Thermometer	TH-08	TM658	Oct. 21, 2014	Oct. 20, 2015
Anritsu	Radio Communication Analyzer	MT8820C	6201074414	Feb. 06, 2015	Feb. 05, 2016
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 27, 2014	May. 26, 2015
Anritsu	BT Base Station	MT8852B	1350002	Dec. 12, 2014	Dec. 11, 2015
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Agilent	Signal Generator	N5181A	MY50145381	Dec. 11, 2014	Dec. 10, 2015
Agilent	ENA Network Analyzer	E5071C	MY46316648	Feb. 11, 2015	Feb. 10, 2016
SPEAG	Dielectric Probe Kit	DAK-3.5	1138	Nov. 18, 2014	Nov. 17, 2015
Anritsu	Power Meter	ML2495A	1349001	Dec. 03, 2014	Dec. 02, 2015
Anritsu	Power Sensor	MA2411B	1306099	Dec. 03, 2014	Dec. 02, 2015
R&S	Spectrum Analyzer	FSP 7	101131	Jul. 10, 2014	Jul. 09, 2015
Agilent	Dual Directional Coupler	778D	50422	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	
AR	Power Amplifier	5S1G4M2	0328767	Note 1	
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.3	0.894	42.808	0.89	41.90	0.45	2.17	±5	2015/5/10
750	MSL	22.5	0.964	57.237	0.96	55.50	0.42	3.13	±5	2015/5/9
750	MSL	22.3	0.967	57.522	0.96	55.50	0.73	3.64	±5	2015/5/11
835	HSL	22.3	0.920	42.522	0.90	41.50	2.22	2.46	±5	2015/5/11
835	MSL	22.5	0.992	57.177	0.97	55.20	2.27	3.58	±5	2015/5/10
1750	HSL	22.5	1.363	40.572	1.37	40.10	-0.51	1.18	±5	2015/5/2
1750	HSL	22.4	1.368	39.931	1.37	40.10	-0.15	-0.42	±5	2015/5/14
1750	MSL	22.3	1.459	52.898	1.49	53.40	-2.08	-0.94	±5	2015/5/4
1750	MSL	22.5	1.478	53.486	1.49	53.40	-0.81	0.16	±5	2015/5/6
1750	MSL	22.1	1.467	53.157	1.49	53.40	-1.54	-0.46	±5	2015/5/8
1750	MSL	22.4	1.473	52.385	1.49	53.40	-1.14	-1.90	±5	2015/5/14
1750	MSL	22.5	1.502	51.015	1.49	53.40	0.81	-4.47	±5	2015/5/20
1900	HSL	22.3	1.427	41.293	1.40	40.00	1.93	3.23	±5	2015/5/10
1900	HSL	22.3	1.403	39.423	1.40	40.00	0.21	-1.44	±5	2015/5/14
1900	MSL	22.4	1.560	54.780	1.52	53.30	2.63	2.78	±5	2015/5/9
1900	MSL	22.4	1.549	51.948	1.52	53.30	1.91	-2.54	±5	2015/5/15
1900	MSL	22.5	1.534	54.022	1.52	53.30	0.92	1.35	±5	2015/5/19
2450	HSL	22.3	1.856	39.220	1.80	39.20	3.11	0.05	±5	2015/5/13
2450	MSL	22.4	1.904	51.836	1.95	52.70	-2.36	-1.64	±5	2015/5/12
2600	HSL	22.5	2.002	38.410	1.96	39.00	2.14	-1.51	±5	2015/5/2
2600	MSL	22.5	2.201	52.823	2.16	52.50	1.90	0.62	±5	2015/5/5
2600	MSL	22.4	2.253	52.909	2.16	52.50	4.31	0.78	±5	2015/5/7

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2015/5/10	750	HSL	250	D750V3-1099	EX3DV4 - SN3955	DAE4 Sn1399	2.00	8.06	8.00	-0.74
2015/5/9	750	MSL	250	D750V3-1099	EX3DV4 - SN3955	DAE4 Sn1399	2.28	8.56	9.12	6.54
2015/5/11	750	MSL	250	D750V3-1099	EX3DV4 - SN3955	DAE4 Sn1399	2.29	8.56	9.16	7.01
2015/5/11	835	HSL	250	D835V2-499	EX3DV4 - SN3955	DAE4 Sn1399	2.33	9.20	9.32	1.30
2015/5/10	835	MSL	250	D835V2-499	EX3DV4 - SN3955	DAE4 Sn1399	2.32	9.30	9.28	-0.22
2015/5/2	1750	HSL	250	D1750V2-1068	EX3DV4 - SN3578	DAE4 Sn1388	8.68	36.80	34.72	-5.65
2015/5/14	1750	HSL	250	D1750V2-1068	EX3DV4 - SN3931	DAE3 Sn577	9.44	36.80	37.76	2.61
2015/5/4	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3578	DAE4 Sn1388	9.42	38.00	37.68	-0.84
2015/5/6	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3955	DAE4 Sn1399	9.20	38.00	36.80	-3.16
2015/5/8	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3955	DAE4 Sn1399	9.13	38.00	36.52	-3.89
2015/5/14	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3931	DAE3 Sn577	9.15	38.00	36.60	-3.68
2015/5/20	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3954	DAE3 Sn577	9.95	38.00	39.80	4.74
2015/5/10	1900	HSL	250	D1900V2-5d041	EX3DV4 - SN3955	DAE4 Sn1399	9.73	40.00	38.92	-2.70
2015/5/14	1900	HSL	250	D1900V2-5d041	EX3DV4 - SN3931	DAE3 Sn577	9.72	40.00	38.88	-2.80
2015/5/9	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3955	DAE4 Sn1399	9.89	39.80	39.56	-0.60
2015/5/15	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3931	DAE3 Sn577	10.00	39.80	40.00	0.50
2015/5/19	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3954	DAE3 Sn577	9.99	39.80	39.96	0.40
2015/5/13	2450	HSL	250	D2450V2-924	EX3DV4 - SN3931	DAE3 Sn577	13.10	51.90	52.40	0.96
2015/5/12	2450	MSL	250	D2450V2-924	EX3DV4 - SN3697	DAE4 Sn1388	12.40	51.40	49.60	-3.50
2015/5/2	2600	HSL	250	D2600V2-1070	EX3DV4 - SN3578	DAE4 Sn1388	14.20	56.90	56.80	-0.18
2015/5/5	2600	MSL	250	D2600V2-1070	EX3DV4 - SN3955	DAE4 Sn1399	13.60	55.30	54.40	-1.63
2015/5/7	2600	MSL	250	D2600V2-1070	EX3DV4 - SN3955	DAE4 Sn1399	14.00	55.30	56.00	1.27




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15° .
3. Rotate the handset around the horizontal line by 15° .
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06 v02 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

1. Per KDB 447498 D01v05r02, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (2Tx slots) for GSM850/GSM1900.
3. Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (2Tx slots) for GSM850/GSM1900.

Band GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM (GMSK, 1 Tx slot)	32.34	32.41	32.02	33.50	23.34	23.41	23.02	24.50
GPRS (GMSK, 1 Tx slot)	32.35	32.43	32.04	33.50	23.35	23.43	23.04	24.50
GPRS (GMSK, 2 Tx slots)	30.68	30.72	30.33	32.00	24.68	24.72	24.33	26.00
GPRS (GMSK, 3 Tx slots)	28.94	28.96	28.85	30.00	24.68	24.70	24.59	25.74
GPRS (GMSK, 4 Tx slots)	26.54	26.55	26.62	28.00	23.54	23.55	23.62	25.00
EDGE (8PSK, 1 Tx slot)	26.25	26.20	26.20	28.00	17.25	17.20	17.20	19.00
EDGE (8PSK, 2 Tx slots)	24.09	24.08	24.03	26.00	18.09	18.08	18.03	20.00
EDGE (8PSK, 3 Tx slots)	22.01	22.00	22.01	24.00	17.75	17.74	17.75	19.74
EDGE (8PSK, 4 Tx slots)	20.39	20.41	20.40	22.00	17.39	17.41	17.40	19.00

Band GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)	29.15	28.99	28.89	30.50	20.15	19.99	19.89	21.50
GPRS (GMSK, 1 Tx slot)	29.17	29.01	28.90	30.50	20.17	20.01	19.90	21.50
GPRS (GMSK, 2 Tx slots)	27.61	27.43	27.42	29.00	21.61	21.43	21.42	23.00
GPRS (GMSK, 3 Tx slots)	25.78	25.53	25.51	27.00	21.52	21.27	21.25	22.74
GPRS (GMSK, 4 Tx slots)	23.49	23.26	23.28	25.00	20.49	20.26	20.28	22.00
EDGE (8PSK, 1 Tx slot)	25.20	25.11	25.00	27.00	16.20	16.11	16.00	18.00
EDGE (8PSK, 2 Tx slots)	24.18	23.86	23.91	25.00	18.18	17.86	17.91	19.00
EDGE (8PSK, 3 Tx slots)	22.36	22.03	22.08	23.00	18.10	17.77	17.82	18.74
EDGE (8PSK, 4 Tx slots)	20.27	19.96	20.03	21.00	17.27	16.96	17.03	18.00

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

Band			WCDMA V			WCDMA II			WCDMA IV		
TX Channel			4132	4182	4233	9262	9400	9538	1312	1413	1513
Rx Channel			4357	4407	4458	9662	9800	9938	1537	1638	1738
Frequency (MHz)			826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
MPR (dB)	3GPP Rel 99	AMR 12.2Kbps	23.77	23.92	23.97	23.95	23.90	23.98	22.90	22.80	22.71
	3GPP Rel 99	RMC 12.2Kbps	23.78	23.93	23.99	23.97	23.91	23.99	22.92	22.83	22.74
0	3GPP Rel 6	HSDPA Subtest-1	22.84	22.97	22.99	22.99	22.85	22.92	21.91	21.91	21.76
0	3GPP Rel 6	HSDPA Subtest-2	22.79	22.95	22.90	22.98	22.84	22.91	21.93	21.88	21.73
0.5	3GPP Rel 6	HSDPA Subtest-3	22.35	22.47	22.48	22.49	22.42	22.48	21.48	21.39	21.14
0.5	3GPP Rel 6	HSDPA Subtest-4	22.34	22.45	22.47	22.49	22.41	22.50	21.38	21.39	21.22
0	3GPP Rel 6	HSUPA Subtest-1	22.90	22.99	23.00	22.70	22.27	22.77	21.64	21.77	21.28
2	3GPP Rel 6	HSUPA Subtest-2	21.77	21.73	21.94	21.95	21.90	21.54	20.82	20.71	20.65
1	3GPP Rel 6	HSUPA Subtest-3	21.90	21.34	22.00	21.96	21.53	21.87	20.89	20.25	20.01
2	3GPP Rel 6	HSUPA Subtest-4	21.70	21.75	21.79	21.49	21.47	21.56	21.41	21.30	21.24
0	3GPP Rel 6	HSUPA Subtest-5	22.93	22.95	22.91	22.95	22.90	22.94	22.01	21.91	21.70

<LTE Conducted Power>**General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130	24	0
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.28	23.50	23.77		
10	QPSK	1	24	23.62	23.66	23.53	23	1
10	QPSK	1	49	23.55	23.38	23.65		
10	QPSK	25	0	22.56	22.57	22.63		
10	QPSK	25	12	22.53	22.50	22.53	23	1
10	QPSK	25	24	22.57	22.46	22.64		
10	QPSK	50	0	22.55	22.48	22.67		
10	16QAM	1	0	22.68	22.86	22.90	23	1
10	16QAM	1	24	22.72	22.84	22.71		
10	16QAM	1	49	22.74	22.61	22.95		
10	16QAM	25	0	21.65	21.65	21.48	22	2
10	16QAM	25	12	21.54	21.49	21.50		
10	16QAM	25	24	21.57	21.60	21.66		
10	16QAM	50	0	21.52	21.55	21.57	24	0
Channel				23035	23095	23155		
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.54	23.63	23.47	24	0
5	QPSK	1	12	23.64	23.59	23.58		
5	QPSK	1	24	23.53	23.49	23.62		
5	QPSK	12	0	22.51	22.60	22.34	23	1
5	QPSK	12	6	22.53	22.51	22.50		
5	QPSK	12	11	22.47	22.52	22.46		
5	QPSK	25	0	22.43	22.47	22.50	23	1
5	16QAM	1	0	22.63	22.76	22.69		
5	16QAM	1	12	22.72	22.71	22.76		
5	16QAM	1	24	22.71	22.63	22.86	22	2
5	16QAM	12	0	21.46	21.52	21.41		
5	16QAM	12	6	21.49	21.53	21.52		
5	16QAM	12	11	21.53	21.51	21.48	24	0
5	16QAM	25	0	21.60	21.57	21.59		
Channel				23025	23095	23165		
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.34	23.58	23.55	24	0
3	QPSK	1	7	23.49	23.61	23.61		
3	QPSK	1	14	23.69	23.43	23.46		
3	QPSK	8	0	22.44	22.61	22.60	23	1
3	QPSK	8	4	22.74	22.54	22.55		
3	QPSK	8	7	22.60	22.63	22.57		
3	QPSK	15	0	22.54	22.55	22.56	23	1
3	16QAM	1	0	22.72	22.88	22.82		
3	16QAM	1	7	22.64	22.75	22.77		
3	16QAM	1	14	22.83	22.73	22.96	22	2
3	16QAM	8	0	21.41	21.74	21.76		
3	16QAM	8	4	21.56	21.61	21.72		
3	16QAM	8	7	21.56	21.60	21.81	22	2
3	16QAM	15	0	21.64	21.55	21.66		



Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	23.48	23.53	23.36	24	0
1.4	QPSK	1	2	23.51	23.60	23.57		
1.4	QPSK	1	5	23.50	23.56	23.54		
1.4	QPSK	3	0	23.50	23.64	23.66		
1.4	QPSK	3	1	23.65	23.58	23.76		
1.4	QPSK	3	2	23.49	23.65	23.62		
1.4	QPSK	6	0	22.47	22.65	22.60	23	1
1.4	16QAM	1	0	22.67	22.85	22.81	23	1
1.4	16QAM	1	2	22.75	22.77	22.75		
1.4	16QAM	1	5	22.69	22.92	22.56		
1.4	16QAM	3	0	22.37	22.71	22.67		
1.4	16QAM	3	1	22.61	22.73	22.79		
1.4	16QAM	3	2	22.56	22.79	22.67		
1.4	16QAM	6	0	21.45	21.59	21.54	22	2



<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				709	710	711		
10	QPSK	1	0	23.70	23.78	23.65	24	0
10	QPSK	1	24	23.54	23.54	23.57		
10	QPSK	1	49	23.74	23.62	23.71		
10	QPSK	25	0	22.69	22.57	22.55	23	1
10	QPSK	25	12	22.47	22.49	22.39		
10	QPSK	25	24	22.57	22.45	22.52		
10	QPSK	50	0	22.61	22.58	22.56	23	1
10	16QAM	1	0	22.77	23.00	22.94		
10	16QAM	1	24	22.52	22.53	22.53		
10	16QAM	1	49	22.85	22.73	22.73	22	2
10	16QAM	25	0	21.64	21.56	21.61		
10	16QAM	25	12	21.54	21.55	21.40		
10	16QAM	25	24	21.46	21.55	21.56	22	2
10	16QAM	50	0	21.50	21.57	21.46		
Channel				23755	23790	23825	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	23.66	23.72	23.53	24	0
5	QPSK	1	12	23.62	23.55	23.50		
5	QPSK	1	24	23.73	23.77	23.39		
5	QPSK	12	0	22.61	22.55	22.54	23	1
5	QPSK	12	6	22.63	22.50	22.54		
5	QPSK	12	11	22.57	22.51	22.54		
5	QPSK	25	0	22.86	22.89	22.88	23	1
5	16QAM	1	0	22.99	22.85	22.69		
5	16QAM	1	12	22.94	22.96	22.95		
5	16QAM	1	24	22.71	22.96	22.84	22	2
5	16QAM	12	0	21.53	21.53	21.54		
5	16QAM	12	6	21.54	21.54	21.53		
5	16QAM	12	11	21.62	21.53	21.60	22	2
5	16QAM	25	0	21.85	21.87	21.99		



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600	24	0
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	22.77	22.99	23.22		
10	QPSK	1	24	23.05	22.99	22.99	23	1
10	QPSK	1	49	23.02	22.89	22.92		
10	QPSK	25	0	21.90	21.86	21.87		
10	QPSK	25	12	21.89	21.86	21.95	23	1
10	QPSK	25	24	21.89	21.90	21.96		
10	QPSK	50	0	21.90	21.80	21.95		
10	16QAM	1	0	22.03	22.14	22.12	23	1
10	16QAM	1	24	22.12	22.08	22.12		
10	16QAM	1	49	22.08	22.10	22.23		
10	16QAM	25	0	20.89	20.90	20.85	22	2
10	16QAM	25	12	20.97	20.93	20.92		
10	16QAM	25	24	20.92	20.91	21.23		
10	16QAM	50	0	20.76	20.77	20.92	24	0
Channel				20425	20525	20625		
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.57	22.90	23.02	24	0
5	QPSK	1	12	22.61	22.63	23.00		
5	QPSK	1	24	22.72	22.87	22.82		
5	QPSK	12	0	21.78	21.80	21.93	23	1
5	QPSK	12	6	21.77	21.79	21.94		
5	QPSK	12	11	21.77	21.79	21.94		
5	QPSK	25	0	22.23	22.26	22.35	23	1
5	16QAM	1	0	21.91	21.95	22.23		
5	16QAM	1	12	21.99	22.02	22.15		
5	16QAM	1	24	22.34	22.45	22.60	22	2
5	16QAM	12	0	20.80	20.85	21.02		
5	16QAM	12	6	20.74	20.86	21.06		
5	16QAM	12	11	20.97	20.76	21.02	24	0
5	16QAM	25	0	21.20	21.26	21.40		
Channel				20415	20525	20635		
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.78	22.95	22.82	24	0
3	QPSK	1	7	22.86	22.89	23.01		
3	QPSK	1	14	22.88	22.74	22.96		
3	QPSK	8	0	21.72	21.82	21.99	23	1
3	QPSK	8	4	21.68	21.80	21.90		
3	QPSK	8	7	21.79	21.84	21.97		
3	QPSK	15	0	21.73	21.86	21.79	23	1
3	16QAM	1	0	21.95	22.14	22.18		
3	16QAM	1	7	21.92	21.98	22.15		
3	16QAM	1	14	22.09	22.07	22.21	22	2
3	16QAM	8	0	20.72	20.83	21.17		
3	16QAM	8	4	20.68	20.74	21.10		
3	16QAM	8	7	20.68	20.77	21.05	22	2
3	16QAM	15	0	20.60	20.64	20.87		



Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	22.66	22.86	22.95	24	0
1.4	QPSK	1	2	22.71	22.97	23.06		
1.4	QPSK	1	5	22.57	22.70	22.94		
1.4	QPSK	3	0	22.66	22.92	23.10		
1.4	QPSK	3	1	22.69	22.96	23.09		
1.4	QPSK	3	2	22.59	22.87	23.02		
1.4	QPSK	6	0	21.64	21.88	21.86	23	1
1.4	16QAM	1	0	21.98	22.11	22.18	23	1
1.4	16QAM	1	2	21.91	21.99	22.01		
1.4	16QAM	1	5	21.99	22.12	22.19		
1.4	16QAM	3	0	21.74	21.94	22.01		
1.4	16QAM	3	1	21.77	21.89	22.02		
1.4	16QAM	3	2	21.77	21.91	22.04		
1.4	16QAM	6	0	20.67	20.74	20.64	22	2



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300	24	0
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	23.29	22.95	22.88		
20	QPSK	1	49	23.11	22.88	22.83	23	1
20	QPSK	1	99	22.76	22.35	22.27		
20	QPSK	50	0	22.10	22.00	21.85		
20	QPSK	50	24	22.08	21.68	21.70	23	1
20	QPSK	50	49	21.94	21.62	21.61		
20	QPSK	100	0	21.92	21.81	21.68		
20	16QAM	1	0	22.29	22.34	22.26	23	1
20	16QAM	1	49	22.21	22.07	22.16		
20	16QAM	1	99	21.96	21.85	21.81		
20	16QAM	50	0	20.83	20.89	20.84	22	2
20	16QAM	50	24	20.96	20.70	20.69		
20	16QAM	50	49	20.80	20.68	20.73		
20	16QAM	100	0	20.91	20.61	20.67	24	0
Channel				20025	20175	20325		
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	22.78	23.02	22.68	24	0
15	QPSK	1	37	22.92	22.59	22.59		
15	QPSK	1	74	22.86	22.56	22.44		
15	QPSK	36	0	21.88	21.90	21.78	23	1
15	QPSK	36	18	21.88	21.70	21.71		
15	QPSK	36	37	21.97	21.61	21.65		
15	QPSK	75	0	21.93	21.72	21.69	23	1
15	16QAM	1	0	22.23	22.31	22.05		
15	16QAM	1	37	22.16	21.89	21.93		
15	16QAM	1	74	22.14	21.86	21.83	22	2
15	16QAM	36	0	20.86	20.90	20.76		
15	16QAM	36	18	20.69	20.59	20.61		
15	16QAM	36	37	20.66	20.51	20.57	24	0
15	16QAM	75	0	20.74	20.61	20.60		
Channel				20000	20175	20350		
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	23.06	23.03	22.80	24	0
10	QPSK	1	24	22.95	22.72	22.65		
10	QPSK	1	49	22.91	22.58	22.48		
10	QPSK	25	0	21.81	21.78	21.74	23	1
10	QPSK	25	12	21.89	21.71	21.66		
10	QPSK	25	24	21.87	21.64	21.64		
10	QPSK	50	0	21.89	21.67	21.61	23	1
10	16QAM	1	0	22.26	22.21	21.98		
10	16QAM	1	24	22.10	21.93	21.87		
10	16QAM	1	49	22.16	21.77	21.91	22	2
10	16QAM	25	0	20.79	20.93	20.66		
10	16QAM	25	12	21.00	20.72	20.60		
10	16QAM	25	24	20.97	20.55	20.58	22	2
10	16QAM	50	0	20.95	20.58	20.55		



Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	22.83	22.78	22.78	24	0
5	QPSK	1	12	22.77	22.69	22.49		
5	QPSK	1	24	22.82	22.58	22.34		
5	QPSK	12	0	21.76	21.67	21.65	23	1
5	QPSK	12	6	21.79	21.68	21.67		
5	QPSK	12	11	21.81	21.60	21.61		
5	QPSK	25	0	21.76	21.65	21.63		
5	16QAM	1	0	22.06	21.99	21.91	23	1
5	16QAM	1	12	22.01	21.89	21.88		
5	16QAM	1	24	22.05	21.86	21.77		
5	16QAM	12	0	20.72	20.69	20.62	22	2
5	16QAM	12	6	20.71	20.58	20.52		
5	16QAM	12	11	20.72	20.52	20.55		
5	16QAM	25	0	20.71	20.57	20.68		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	22.86	22.63	22.68	24	0
3	QPSK	1	7	22.82	22.61	22.51		
3	QPSK	1	14	22.85	22.48	22.50		
3	QPSK	8	0	21.82	21.78	21.76	23	1
3	QPSK	8	4	21.83	21.74	21.69		
3	QPSK	8	7	21.85	21.74	21.63		
3	QPSK	15	0	21.73	21.66	21.61		
3	16QAM	1	0	22.19	22.11	21.93	23	1
3	16QAM	1	7	22.07	21.95	21.91		
3	16QAM	1	14	22.17	22.00	21.91		
3	16QAM	8	0	20.65	20.59	20.86	22	2
3	16QAM	8	4	20.66	20.80	20.69		
3	16QAM	8	7	20.69	20.75	20.73		
3	16QAM	15	0	20.59	20.68	20.77		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	22.89	22.79	22.79	24	0
1.4	QPSK	1	2	22.80	22.71	22.60		
1.4	QPSK	1	5	22.63	22.77	22.48		
1.4	QPSK	3	0	22.69	22.72	22.49		
1.4	QPSK	3	1	22.86	22.61	22.60		
1.4	QPSK	3	2	22.76	22.61	22.76		
1.4	QPSK	6	0	21.79	21.69	21.73	23	1
1.4	16QAM	1	0	22.03	21.95	21.92	23	1
1.4	16QAM	1	2	21.99	21.86	21.90		
1.4	16QAM	1	5	21.95	21.94	21.52		
1.4	16QAM	3	0	21.83	21.91	21.73		
1.4	16QAM	3	1	21.92	21.76	21.78		
1.4	16QAM	3	2	21.90	21.76	21.75		
1.4	16QAM	6	0	20.65	20.55	20.63	22	2



<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.00	22.80	22.82		
20	QPSK	1	49	22.92	22.63	22.81	24	0
20	QPSK	1	99	22.67	22.47	22.31		
20	QPSK	50	0	21.74	21.73	21.66		
20	QPSK	50	24	21.65	21.51	21.55	23	1
20	QPSK	50	49	21.55	21.35	21.58		
20	QPSK	100	0	21.61	21.54	21.54		
20	16QAM	1	0	22.09	22.03	21.56	23	1
20	16QAM	1	49	22.21	21.64	22.10		
20	16QAM	1	99	21.67	21.56	21.74		
20	16QAM	50	0	20.66	20.56	20.66	22	2
20	16QAM	50	24	20.55	20.31	20.50		
20	16QAM	50	49	20.52	20.19	20.50		
20	16QAM	100	0	20.54	20.54	20.45		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	22.58	22.81	22.51		
15	QPSK	1	37	22.93	22.48	22.75	24	0
15	QPSK	1	74	22.64	22.45	22.51		
15	QPSK	36	0	21.81	21.81	21.67		
15	QPSK	36	18	21.79	21.56	21.57	23	1
15	QPSK	36	37	21.63	21.44	21.59		
15	QPSK	75	0	21.59	21.61	21.62		
15	16QAM	1	0	22.16	22.11	21.92	23	1
15	16QAM	1	37	22.04	21.68	21.73		
15	16QAM	1	74	21.76	21.68	21.79		
15	16QAM	36	0	20.58	20.62	20.62	22	2
15	16QAM	36	18	20.64	20.50	20.48		
15	16QAM	36	37	20.57	20.36	20.64		
15	16QAM	75	0	20.64	20.64	20.54		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	22.71	22.92	22.80		
10	QPSK	1	24	22.76	22.65	22.59	24	0
10	QPSK	1	49	22.80	22.63	22.47		
10	QPSK	25	0	21.77	21.81	21.61		
10	QPSK	25	12	21.84	21.58	21.50	23	1
10	QPSK	25	24	21.76	21.53	21.62		
10	QPSK	50	0	21.80	21.62	21.66		
10	16QAM	1	0	22.17	22.04	22.02	23	1
10	16QAM	1	24	22.01	21.73	21.75		
10	16QAM	1	49	21.92	21.79	21.91		
10	16QAM	25	0	20.66	20.68	20.71	22	2
10	16QAM	25	12	20.75	20.53	20.67		
10	16QAM	25	24	20.70	20.48	20.56		
10	16QAM	50	0	20.74	20.52	20.44		

Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	22.68	22.74	22.73	24	0
5	QPSK	1	12	22.65	22.68	22.61		
5	QPSK	1	24	22.70	22.70	22.42		
5	QPSK	12	0	21.88	21.70	21.77	23	1
5	QPSK	12	6	21.80	21.68	21.67		
5	QPSK	12	11	21.75	21.60	21.65		
5	QPSK	25	0	21.76	21.54	21.67	23	1
5	16QAM	1	0	22.00	21.89	22.41		
5	16QAM	1	12	22.06	21.80	21.93		
5	16QAM	1	24	22.10	21.82	21.85	22	2
5	16QAM	12	0	20.79	20.49	20.59		
5	16QAM	12	6	20.71	20.40	20.60		
5	16QAM	12	11	20.73	20.44	20.53	22	2
5	16QAM	25	0	20.74	20.51	20.64		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	22.80	22.77	22.71	24	0
3	QPSK	1	7	22.75	22.74	22.72		
3	QPSK	1	14	22.78	22.54	22.70		
3	QPSK	8	0	21.93	21.63	21.75	23	1
3	QPSK	8	4	21.86	21.63	21.69		
3	QPSK	8	7	21.89	21.56	21.72		
3	QPSK	15	0	21.86	21.54	21.72	23	1
3	16QAM	1	0	22.29	21.93	21.98		
3	16QAM	1	7	22.18	21.82	21.93		
3	16QAM	1	14	22.31	21.91	22.04	22	2
3	16QAM	8	0	20.85	20.57	20.54		
3	16QAM	8	4	20.78	20.46	20.51		
3	16QAM	8	7	20.80	20.38	20.53	22	2
3	16QAM	15	0	20.75	20.60	20.39		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	22.72	22.47	22.70	24	0
1.4	QPSK	1	2	22.73	22.62	22.88		
1.4	QPSK	1	5	22.67	22.55	22.67		
1.4	QPSK	3	0	22.82	22.64	22.73	23	1
1.4	QPSK	3	1	22.80	22.58	22.73		
1.4	QPSK	3	2	22.87	22.64	22.61		
1.4	QPSK	6	0	21.84	21.59	21.62	23	1
1.4	16QAM	1	0	22.01	21.77	22.03		
1.4	16QAM	1	2	22.04	21.78	21.86		
1.4	16QAM	1	5	22.00	21.87	21.94	23	1
1.4	16QAM	3	0	22.16	21.73	21.78		
1.4	16QAM	3	1	21.79	21.74	21.78		
1.4	16QAM	3	2	21.66	21.72	21.83	22	2
1.4	16QAM	6	0	20.54	20.51	20.56		



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Measured Power			Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	22.50	22.58	22.39	24	0
20	QPSK	1	49	22.29	22.43	22.37		
20	QPSK	1	99	22.16	22.49	22.19		
20	QPSK	50	0	21.36	21.41	21.39	23	1
20	QPSK	50	24	21.31	21.36	21.31		
20	QPSK	50	49	21.31	21.35	21.29		
20	QPSK	100	0	21.42	21.43	21.32	23	1
20	16QAM	1	0	21.82	21.63	21.63		
20	16QAM	1	49	21.55	21.56	21.51		
20	16QAM	1	99	21.47	21.62	21.33	22	2
20	16QAM	50	0	20.51	20.31	20.38		
20	16QAM	50	24	20.44	20.21	20.34		
20	16QAM	50	49	20.41	20.28	20.26	22	2
20	16QAM	100	0	20.37	20.44	20.34		
Channel				20825	21100	21375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	22.53	22.40	22.32	24	0
15	QPSK	1	37	22.27	22.25	22.07		
15	QPSK	1	74	22.27	22.22	22.16		
15	QPSK	36	0	21.48	21.46	21.37	23	1
15	QPSK	36	18	21.39	21.38	21.23		
15	QPSK	36	37	21.35	21.37	21.24		
15	QPSK	75	0	21.43	21.37	21.31	23	1
15	16QAM	1	0	21.82	21.69	21.62		
15	16QAM	1	37	21.60	21.52	21.40		
15	16QAM	1	74	21.60	21.55	21.38	22	2
15	16QAM	36	0	20.50	20.29	20.37		
15	16QAM	36	18	20.47	20.34	20.26		
15	16QAM	36	37	20.36	20.40	20.19	22	2
15	16QAM	75	0	20.32	20.22	20.26		
Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	22.50	22.43	22.27	24	0
10	QPSK	1	24	22.33	22.32	22.13		
10	QPSK	1	49	22.15	22.29	22.09		
10	QPSK	25	0	21.37	21.33	21.32	23	1
10	QPSK	25	12	21.38	21.32	21.18		
10	QPSK	25	24	21.36	21.38	21.18		
10	QPSK	50	0	21.37	21.42	21.21	23	1
10	16QAM	1	0	21.69	21.60	21.55		
10	16QAM	1	24	21.55	21.58	21.39		
10	16QAM	1	49	21.55	21.57	21.37	22	2
10	16QAM	25	0	20.50	20.34	20.27		
10	16QAM	25	12	20.41	20.54	20.32		
10	16QAM	25	24	20.48	20.30	20.14	22	2
10	16QAM	50	0	20.23	20.39	20.16		

Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	22.34	22.31	22.13	24	0
5	QPSK	1	12	22.31	22.30	22.03		
5	QPSK	1	24	22.17	22.14	22.11		
5	QPSK	12	0	21.37	21.27	21.18	23	1
5	QPSK	12	6	21.42	21.32	21.09		
5	QPSK	12	11	21.34	21.37	21.17		
5	QPSK	25	0	21.37	21.23	21.23	23	1
5	16QAM	1	0	21.62	21.92	21.42		
5	16QAM	1	12	21.60	21.62	21.39		
5	16QAM	1	24	21.57	21.49	21.27	22	2
5	16QAM	12	0	20.32	20.26	20.29		
5	16QAM	12	6	20.34	20.19	20.05		
5	16QAM	12	11	20.29	20.26	20.10	22	2
5	16QAM	25	0	20.43	20.35	20.11		

<2.4GHz Bluetooth>

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
- The duty factor is selected theoretical 83.3% perform Bluetooth SAR testing.

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
v3.0 with EDR	CH 00	2402	9.54	7.41	7.45
	CH 39	2441	9.73	7.63	7.69
	CH 78	2480	9.25	7.10	7.16


Mode	Channel	Frequency (MHz)	Average power (dBm)	
			GFSK	
v4.0 with LE	CH 00	2402	0.77	
	CH 19	2440	0.82	
	CH 39	2480	0.65	

<WLAN Conducted Power>
General Note:

1. Per KDB 248227 D01v02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b	CH 1	2412	1Mbps	15.31	16.00	97.16
		CH 6	2437		15.48	16.00	
		CH 11	2462		15.88	16.00	
	802.11g	CH 1	2412	6Mbps	13.57	14.00	86.73
		CH 6	2437		15.16	15.50	
		CH 11	2462		11.75	12.00	
	802.11n-HT20	CH 1	2412	MCS0	12.86	13.00	86.49
		CH 6	2437		14.30	14.50	
		CH 11	2462		9.17	9.50	

13. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	> 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

- Referring to KDB 941225 D06 v02, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

14. SAR Test Results

General Note:

- Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
- When hotspot mode is enabled, power reduction will be activated to limit the maximum power of WCDMA B4 and LTE B2 / B7.
- Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.

GSM Note:

- Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (2Tx slots) for GSM850/GSM1900.
- Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (2Tx slots) for GSM850/GSM1900.

UMTS Note:

- Per KDB 941225 D01v03, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
- Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is ≤ ¼ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

LTE Note:

- Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
- Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
- Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
- Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is > not ½ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
- Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is > not ½ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.

WLAN Note:

1. Per KDB 248227 D01v02, 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

14.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (2 Tx slots)	Right Cheek	0mm	189	836.4	30.72	32.00	1.343	0	0.307	0.412
	GSM850	GPRS (2 Tx slots)	Right Cheek	0mm	128	824.2	30.68	32.00	1.355	-0.15	0.186	0.252
01	GSM850	GPRS (2 Tx slots)	Right Cheek	0mm	251	848.8	30.33	32.00	1.469	-0.02	0.502	0.737
	GSM850	GPRS (2 Tx slots)	Right Tilted	0mm	189	836.4	30.72	32.00	1.343	-0.07	0.143	0.192
	GSM850	GPRS (2 Tx slots)	Left Cheek	0mm	189	836.4	30.72	32.00	1.343	-0.02	0.215	0.289
	GSM850	GPRS (2 Tx slots)	Left Tilted	0mm	189	836.4	30.72	32.00	1.343	0.01	0.133	0.179
	GSM1900	GPRS (2 Tx slots)	Right Cheek	0mm	512	1850.2	27.61	29.00	1.377	-0.15	0.210	0.289
	GSM1900	GPRS (2 Tx slots)	Right Tilted	0mm	512	1850.2	27.61	29.00	1.377	-0.14	0.049	0.067
	GSM1900	GPRS (2 Tx slots)	Left Cheek	0mm	512	1850.2	27.61	29.00	1.377	0.08	0.228	0.314
	GSM1900	GPRS (2 Tx slots)	Left Cheek	0mm	661	1880	27.43	29.00	1.435	0.01	0.268	0.385
02	GSM1900	GPRS (2 Tx slots)	Left Cheek	0mm	810	1909.8	27.42	29.00	1.439	-0.1	0.269	0.387
	GSM1900	GPRS (2 Tx slots)	Left Tilted	0mm	512	1850.2	27.61	29.00	1.377	0.18	0.055	0.076

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4233	846.6	23.99	24.00	1.002	-0.02	0.648	0.649
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4132	826.4	23.78	24.00	1.052	0.1	0.576	0.606
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4182	836.4	23.93	24.00	1.016	-0.01	0.556	0.565
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4233	846.6	23.99	24.00	1.002	0.08	0.414	0.415
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4233	846.6	23.99	24.00	1.002	0.05	0.559	0.560
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4233	846.6	23.99	24.00	1.002	0.09	0.374	0.375
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1312	1712.4	22.92	24.00	1.282	-0.13	0.305	0.391
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1312	1712.4	22.92	24.00	1.282	-0.1	0.121	0.155
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1312	1712.4	22.92	24.00	1.282	-0.07	0.408	0.523
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1413	1732.6	22.83	24.00	1.309	-0.01	0.389	0.509
04	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1513	1752.6	22.74	24.00	1.337	-0.01	0.467	0.624
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1312	1712.4	22.92	24.00	1.282	-0.04	0.117	0.150
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9538	1907.6	23.99	24.00	1.002	-0.02	0.343	0.344
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9538	1907.6	23.99	24.00	1.002	0.1	0.149	0.149
05	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9538	1907.6	23.99	24.00	1.002	0.05	0.438	0.439
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9262	1852.4	23.97	24.00	1.007	0.04	0.392	0.395
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9400	1880	23.91	24.00	1.021	-0.12	0.327	0.334
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9538	1907.6	23.99	24.00	1.002	0.18	0.115	0.115

**<LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1RB	0offset	Right Cheek	0mm	23130	711	23.77	24.00	1.054	-0.12	0.421	0.444
	LTE Band 12	10M	QPSK	25RB	24offset	Right Cheek	0mm	23130	711	22.64	23.00	1.086	-0.03	0.447	0.486
	LTE Band 12	10M	QPSK	1RB	0offset	Right Tilted	0mm	23130	711	23.77	24.00	1.054	-0.01	0.149	0.157
	LTE Band 12	10M	QPSK	25RB	24offset	Right Tilted	0mm	23130	711	22.64	23.00	1.086	-0.09	0.174	0.189
	LTE Band 12	10M	QPSK	1RB	0offset	Left Cheek	0mm	23130	711	23.77	24.00	1.054	0.04	0.391	0.412
06	LTE Band 12	10M	QPSK	25RB	24offset	Left Cheek	0mm	23130	711	22.64	23.00	1.086	0	0.456	0.495
	LTE Band 12	10M	QPSK	1RB	0offset	Left Tilted	0mm	23130	711	23.77	24.00	1.054	-0.02	0.174	0.183
	LTE Band 12	10M	QPSK	25RB	24offset	Left Tilted	0mm	23130	711	22.64	23.00	1.086	0	0.185	0.201
07	LTE Band 17	10M	QPSK	1RB	0offset	Right Cheek	0mm	23790	710	23.78	24.00	1.052	0.08	0.520	0.547
	LTE Band 17	10M	QPSK	25RB	0offset	Right Cheek	0mm	23780	709	22.69	23.00	1.074	-0.09	0.401	0.431
	LTE Band 17	10M	QPSK	1RB	0offset	Right Tilted	0mm	23790	710	23.78	24.00	1.052	0.01	0.314	0.330
	LTE Band 17	10M	QPSK	25RB	0offset	Right Tilted	0mm	23780	709	22.69	23.00	1.074	-0.03	0.245	0.263
	LTE Band 17	10M	QPSK	1RB	0offset	Left Cheek	0mm	23790	710	23.78	24.00	1.052	-0.06	0.474	0.499
	LTE Band 17	10M	QPSK	25RB	0offset	Left Cheek	0mm	23780	709	22.69	23.00	1.074	0	0.376	0.404
	LTE Band 17	10M	QPSK	1RB	0offset	Left Tilted	0mm	23790	710	23.78	24.00	1.052	0.12	0.216	0.227
	LTE Band 17	10M	QPSK	25RB	0offset	Left Tilted	0mm	23780	709	22.69	23.00	1.074	0.03	0.169	0.182
	LTE Band 5	10M	QPSK	1RB	0offset	Right Cheek	0mm	20600	844	23.22	24.00	1.197	0.09	0.511	0.612
08	LTE Band 5	10M	QPSK	1RB	0offset	Right Cheek	0mm	20450	829	22.77	24.00	1.327	-0.1	0.478	0.634
	LTE Band 5	10M	QPSK	1RB	0offset	Right Cheek	0mm	20525	836.5	22.99	24.00	1.262	0.18	0.501	0.632
	LTE Band 5	10M	QPSK	25RB	24offset	Right Cheek	0mm	20600	844	21.96	23.00	1.271	0.01	0.433	0.550
	LTE Band 5	10M	QPSK	1RB	0offset	Right Tilted	0mm	20600	844	23.22	24.00	1.197	0.07	0.298	0.357
	LTE Band 5	10M	QPSK	25RB	24offset	Right Tilted	0mm	20600	844	21.96	23.00	1.271	0.08	0.252	0.320
	LTE Band 5	10M	QPSK	1RB	0offset	Left Cheek	0mm	20600	844	23.22	24.00	1.197	0.1	0.392	0.469
	LTE Band 5	10M	QPSK	25RB	24offset	Left Cheek	0mm	20600	844	21.96	23.00	1.271	0.04	0.324	0.412
	LTE Band 5	10M	QPSK	1RB	0offset	Left Tilted	0mm	20600	844	23.22	24.00	1.197	-0.01	0.311	0.372
	LTE Band 5	10M	QPSK	25RB	24offset	Left Tilted	0mm	20600	844	21.96	23.00	1.271	0.09	0.250	0.318
	LTE Band 4	20M	QPSK	1RB	0offset	Right Cheek	0mm	20050	1720	23.29	24.00	1.178	0.01	0.307	0.362
09	LTE Band 4	20M	QPSK	1RB	0offset	Right Cheek	0mm	20175	1732.5	22.95	24.00	1.274	-0.09	0.336	0.428
	LTE Band 4	20M	QPSK	1RB	0offset	Right Cheek	0mm	20300	1745	22.88	24.00	1.294	-0.06	0.320	0.414
	LTE Band 4	20M	QPSK	50RB	0offset	Right Cheek	0mm	20050	1720	22.10	23.00	1.230	0.05	0.205	0.252
	LTE Band 4	20M	QPSK	1RB	0offset	Right Tilted	0mm	20050	1720	23.29	24.00	1.178	0.17	0.104	0.122
	LTE Band 4	20M	QPSK	50RB	0offset	Right Tilted	0mm	20050	1720	22.10	23.00	1.230	-0.06	0.071	0.087
	LTE Band 4	20M	QPSK	1RB	0offset	Left Cheek	0mm	20050	1720	23.29	24.00	1.178	-0.05	0.300	0.353
	LTE Band 4	20M	QPSK	50RB	0offset	Left Cheek	0mm	20050	1720	22.10	23.00	1.230	0.05	0.208	0.256
	LTE Band 4	20M	QPSK	1RB	0offset	Left Tilted	0mm	20050	1720	23.29	24.00	1.178	0.05	0.112	0.132
	LTE Band 4	20M	QPSK	50RB	0offset	Left Tilted	0mm	20050	1720	22.10	23.00	1.230	0.03	0.074	0.091
	LTE Band 2	20M	QPSK	1RB	0offset	Right Cheek	0mm	18700	1860	23.00	24.00	1.259	0.18	0.512	0.645
	LTE Band 2	20M	QPSK	50RB	0offset	Right Cheek	0mm	18700	1860	21.74	23.00	1.337	-0.12	0.267	0.357
	LTE Band 2	20M	QPSK	1RB	0offset	Right Tilted	0mm	18700	1860	23.00	24.00	1.259	-0.1	0.200	0.252
	LTE Band 2	20M	QPSK	50RB	0offset	Right Tilted	0mm	18700	1860	21.74	23.00	1.337	0	0.105	0.140
	LTE Band 2	20M	QPSK	1RB	0offset	Left Cheek	0mm	18700	1860	23.00	24.00	1.259	-0.06	0.544	0.685
10	LTE Band 2	20M	QPSK	1RB	0offset	Left Cheek	0mm	18900	1880	22.80	24.00	1.318	0.14	0.556	0.733
	LTE Band 2	20M	QPSK	1RB	0offset	Left Cheek	0mm	19100	1900	22.82	24.00	1.312	0.09	0.543	0.713
	LTE Band 2	20M	QPSK	50RB	0offset	Left Cheek	0mm	18700	1860	21.74	23.00	1.337	-0.08	0.298	0.398
	LTE Band 2	20M	QPSK	1RB	0offset	Left Tilted	0mm	18700	1860	23.00	24.00	1.259	-0.1	0.203	0.256
	LTE Band 2	20M	QPSK	50RB	0offset	Left Tilted	0mm	18700	1860	21.74	23.00	1.337	-0.04	0.111	0.148

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1RB	0offset	Right Cheek	0mm	21100	2535	22.58	24.00	1.387	-0.15	0.116	0.161
	LTE Band 7	20M	QPSK	50RB	0offset	Right Cheek	0mm	21100	2535	21.41	23.00	1.442	-0.12	0.075	0.108
	LTE Band 7	20M	QPSK	1RB	0offset	Right Tilted	0mm	21100	2535	22.58	24.00	1.387	-0.17	0.077	0.107
	LTE Band 7	20M	QPSK	50RB	0offset	Right Tilted	0mm	21100	2535	21.41	23.00	1.442	0.06	0.047	0.068
	LTE Band 7	20M	QPSK	1RB	0offset	Left Cheek	0mm	21100	2535	22.58	24.00	1.387	0.17	0.146	0.202
	LTE Band 7	20M	QPSK	1RB	0offset	Left Cheek	0mm	20850	2510	22.50	24.00	1.413	-0.14	0.163	0.230
11	LTE Band 7	20M	QPSK	1RB	0offset	Left Cheek	0mm	21350	2560	22.39	24.00	1.449	-0.04	0.184	0.267
	LTE Band 7	20M	QPSK	50RB	0offset	Left Cheek	0mm	21100	2535	21.41	23.00	1.442	0.08	0.092	0.133
	LTE Band 7	20M	QPSK	1RB	0offset	Left Tilted	0mm	21100	2535	22.58	24.00	1.387	0.03	0.032	0.044
	LTE Band 7	20M	QPSK	50RB	0offset	Left Tilted	0mm	21100	2535	21.41	23.00	1.442	0.11	0.019	0.027

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.03	0.138	0.146
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.08	0.102	0.108
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.15	0.396	0.419
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	1	2412	15.31	16.00	1.174	97.16	1.029	-0.13	0.345	0.417
12	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	6	2437	15.48	16.00	1.128	97.16	1.029	-0.1	0.425	0.494
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.04	0.196	0.208

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0mm	39	2441	9.73	10.00	1.064	0.02	0.025	0.027
	Bluetooth	1Mbps	Right Tilted	0mm	39	2441	9.73	10.00	1.064	0.06	0.019	0.020
	Bluetooth	1Mbps	Left Cheek	0mm	39	2441	9.73	10.00	1.064	-0.07	0.068	0.072
	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	9.54	10.00	1.112	-0.17	0.066	0.073
13	Bluetooth	1Mbps	Left Cheek	0mm	78	2480	9.25	10.00	1.189	-0.04	0.073	0.087
	Bluetooth	1Mbps	Left Tilted	0mm	39	2441	9.73	10.00	1.064	-0.07	0.033	0.035

14.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (2 Tx slots)	Front	10mm	OFF	189	836.4	30.72	32.00	1.343	-0.15	0.461	0.619
	GSM850	GPRS (2 Tx slots)	Front	10mm	OFF	128	824.2	30.68	32.00	1.355	-0.12	0.257	0.348
14	GSM850	GPRS (2 Tx slots)	Front	10mm	OFF	251	848.8	30.33	32.00	1.469	-0.02	0.434	0.638
	GSM850	GPRS (2 Tx slots)	Back	10mm	OFF	189	836.4	30.72	32.00	1.343	-0.03	0.430	0.577
	GSM850	GPRS (2 Tx slots)	Left Side	10mm	OFF	189	836.4	30.72	32.00	1.343	-0.16	0.090	0.121
	GSM850	GPRS (2 Tx slots)	Right Side	10mm	OFF	189	836.4	30.72	32.00	1.343	0.07	0.296	0.397
	GSM850	GPRS (2 Tx slots)	Bottom Side	10mm	OFF	189	836.4	30.72	32.00	1.343	0.01	0.106	0.142
	GSM1900	GPRS (2 Tx slots)	Front	10mm	OFF	512	1850.2	27.61	29.00	1.377	-0.17	0.659	0.908
	GSM1900	GPRS (2 Tx slots)	Front	10mm	OFF	661	1880	27.43	29.00	1.435	-0.06	0.649	0.932
15	GSM1900	GPRS (2 Tx slots)	Front	10mm	OFF	810	1909.8	27.42	29.00	1.439	-0.06	0.674	0.970
	GSM1900	GPRS (2 Tx slots)	Back	10mm	OFF	512	1850.2	27.61	29.00	1.377	0.08	0.458	0.631
	GSM1900	GPRS (2 Tx slots)	Left Side	10mm	OFF	512	1850.2	27.61	29.00	1.377	-0.04	0.102	0.140
	GSM1900	GPRS (2 Tx slots)	Right Side	10mm	OFF	512	1850.2	27.61	29.00	1.377	-0.02	0.415	0.572
	GSM1900	GPRS (2 Tx slots)	Bottom Side	10mm	OFF	512	1850.2	27.61	29.00	1.377	0.06	0.453	0.624

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	10mm	OFF	4233	846.6	23.99	24.00	1.002	0.02	0.630	0.631
16	WCDMA V	RMC 12.2Kbps	Back	10mm	OFF	4233	846.6	23.99	24.00	1.002	-0.01	0.669	0.671
	WCDMA V	RMC 12.2Kbps	Back	10mm	OFF	4132	826.4	23.78	24.00	1.052	-0.01	0.605	0.636
	WCDMA V	RMC 12.2Kbps	Back	10mm	OFF	4182	836.4	23.93	24.00	1.016	-0.02	0.544	0.553
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	OFF	4233	846.6	23.99	24.00	1.002	0	0.313	0.314
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	OFF	4233	846.6	23.99	24.00	1.002	-0.01	0.544	0.545
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	OFF	4233	846.6	23.99	24.00	1.002	0.02	0.204	0.204
	WCDMA IV	RMC 12.2Kbps	Front	10mm	ON	1312	1712.4		20.00	1.000	-0.08	0.677	0.677
	WCDMA IV	RMC 12.2Kbps	Front	10mm	ON	1413	1732.6		20.00	1.000	-0.04	0.692	0.692
17	WCDMA IV	RMC 12.2Kbps	Front	10mm	ON	1513	1752.6		20.00	1.000	-0.1	0.707	0.707
	WCDMA IV	RMC 12.2Kbps	Back	10mm	ON	1312	1712.4		20.00	1.000	-0.05	0.561	0.561
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	ON	1312	1712.4		20.00	1.000	-0.05	0.054	0.054
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	ON	1312	1712.4		20.00	1.000	-0.06	0.434	0.434
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1312	1712.4		20.00	1.000	-0.03	0.553	0.553
18	WCDMA II	RMC 12.2Kbps	Front	10mm	OFF	9538	1907.6	23.99	24.00	1.002	-0.03	1.210	1.213
	WCDMA II	RMC 12.2Kbps	Front	10mm	OFF	9262	1852.4	23.97	24.00	1.007	-0.06	1.190	1.198
	WCDMA II	RMC 12.2Kbps	Front	10mm	OFF	9400	1880	23.91	24.00	1.021	-0.15	1.140	1.164
	WCDMA II	RMC 12.2Kbps	Back	10mm	OFF	9538	1907.6	23.99	24.00	1.002	-0.11	0.755	0.757
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	OFF	9538	1907.6	23.99	24.00	1.002	-0.05	0.234	0.235
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	OFF	9538	1907.6	23.99	24.00	1.002	0.04	0.572	0.573
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	OFF	9538	1907.6	23.99	24.00	1.002	-0.05	0.851	0.853
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	OFF	9262	1852.4	23.97	24.00	1.007	-0.03	0.881	0.887
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	OFF	9400	1880	23.91	24.00	1.021	-0.02	0.845	0.863



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1RB	0offset	Front	10mm	OFF	23130	711	23.77	24.00	1.054	-0.19	0.806	0.850
	LTE Band 12	10M	QPSK	25RB	24offset	Front	10mm	OFF	23130	711	22.64	23.00	1.086	-0.13	0.711	0.772
	LTE Band 12	10M	QPSK	50RB	0offset	Front	10mm	OFF	23130	711	22.67	23.00	1.079	-0.11	0.679	0.733
19	LTE Band 12	10M	QPSK	1RB	0offset	Back	10mm	OFF	23130	711	23.77	24.00	1.054	-0.17	0.854	0.900
	LTE Band 12	10M	QPSK	25RB	24offset	Back	10mm	OFF	23130	711	22.64	23.00	1.086	-0.09	0.609	0.662
	LTE Band 12	10M	QPSK	50RB	0offset	Back	10mm	OFF	23130	711	22.67	23.00	1.079	-0.02	0.648	0.699
	LTE Band 12	10M	QPSK	1RB	0offset	Left Side	10mm	OFF	23130	711	23.77	24.00	1.054	-0.15	0.617	0.651
	LTE Band 12	10M	QPSK	25RB	24offset	Left Side	10mm	OFF	23130	711	22.64	23.00	1.086	0.11	0.508	0.552
	LTE Band 12	10M	QPSK	1RB	0offset	Right Side	10mm	OFF	23130	711	23.77	24.00	1.054	-0.04	0.278	0.293
	LTE Band 12	10M	QPSK	25RB	24offset	Right Side	10mm	OFF	23130	711	22.64	23.00	1.086	-0.06	0.284	0.309
	LTE Band 12	10M	QPSK	1RB	0offset	Bottom Side	10mm	OFF	23130	711	23.77	24.00	1.054	-0.09	0.257	0.271
	LTE Band 12	10M	QPSK	25RB	24offset	Bottom Side	10mm	OFF	23130	711	22.64	23.00	1.086	-0.16	0.345	0.375
	LTE Band 17	10M	QPSK	1RB	0offset	Front	10mm	OFF	23790	710	23.78	24.00	1.052	-0.12	0.863	0.908
	LTE Band 17	10M	QPSK	25RB	0offset	Front	10mm	OFF	23780	709	22.69	23.00	1.074	-0.07	0.675	0.725
	LTE Band 17	10M	QPSK	50RB	0offset	Front	10mm	OFF	23780	709	22.61	23.00	1.094	0.02	0.668	0.731
20	LTE Band 17	10M	QPSK	1RB	0offset	Back	10mm	OFF	23790	710	23.78	24.00	1.052	-0.12	0.879	0.925
	LTE Band 17	10M	QPSK	25RB	0offset	Back	10mm	OFF	23780	709	22.69	23.00	1.074	-0.01	0.667	0.716
	LTE Band 17	10M	QPSK	50RB	0offset	Back	10mm	OFF	23780	709	22.61	23.00	1.094	-0.01	0.628	0.687
	LTE Band 17	10M	QPSK	1RB	0offset	Left Side	10mm	OFF	23790	710	23.78	24.00	1.052	-0.08	0.628	0.661
	LTE Band 17	10M	QPSK	25RB	0offset	Left Side	10mm	OFF	23780	709	22.69	23.00	1.074	0	0.481	0.517
	LTE Band 17	10M	QPSK	1RB	0offset	Right Side	10mm	OFF	23790	710	23.78	24.00	1.052	0.1	0.317	0.333
	LTE Band 17	10M	QPSK	25RB	0offset	Right Side	10mm	OFF	23780	709	22.69	23.00	1.074	0.07	0.247	0.265
	LTE Band 17	10M	QPSK	1RB	0offset	Bottom Side	10mm	OFF	23790	710	23.78	24.00	1.052	0.03	0.340	0.358
	LTE Band 17	10M	QPSK	25RB	0offset	Bottom Side	10mm	OFF	23780	709	22.69	23.00	1.074	0.04	0.290	0.311
	LTE Band 5	10M	QPSK	1RB	0offset	Front	10mm	OFF	20600	844	23.22	24.00	1.197	-0.02	0.479	0.573
	LTE Band 5	10M	QPSK	25RB	24offset	Front	10mm	OFF	20600	844	21.96	23.00	1.271	-0.11	0.386	0.490
	LTE Band 5	10M	QPSK	1RB	0offset	Back	10mm	OFF	20600	844	23.22	24.00	1.197	-0.14	0.510	0.610
21	LTE Band 5	10M	QPSK	1RB	24offset	Back	10mm	OFF	20450	829	23.05	24.00	1.245	0.18	0.548	0.682
	LTE Band 5	10M	QPSK	1RB	0offset	Back	10mm	OFF	20525	836.5	22.99	24.00	1.262	-0.03	0.518	0.654
	LTE Band 5	10M	QPSK	25RB	24offset	Back	10mm	OFF	20600	844	21.96	23.00	1.271	-0.11	0.385	0.489
	LTE Band 5	10M	QPSK	1RB	0offset	Left Side	10mm	OFF	20600	844	23.22	24.00	1.197	0.06	0.234	0.280
	LTE Band 5	10M	QPSK	25RB	24offset	Left Side	10mm	OFF	20600	844	21.96	23.00	1.271	-0.02	0.169	0.215
	LTE Band 5	10M	QPSK	1RB	0offset	Right Side	10mm	OFF	20600	844	23.22	24.00	1.197	-0.06	0.386	0.462
	LTE Band 5	10M	QPSK	25RB	24offset	Right Side	10mm	OFF	20600	844	21.96	23.00	1.271	-0.04	0.318	0.404
	LTE Band 5	10M	QPSK	1RB	0offset	Bottom Side	10mm	OFF	20600	844	23.22	24.00	1.197	-0.01	0.167	0.200
	LTE Band 5	10M	QPSK	25RB	24offset	Bottom Side	10mm	OFF	20600	844	21.96	23.00	1.271	-0.04	0.122	0.155



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
22	LTE Band 4	20M	QPSK	1RB	0Offset	Front	10mm	OFF	20050	1720	23.29	24.00	1.178	-0.08	1.050	1.236
	LTE Band 4	20M	QPSK	1RB	0Offset	Front	10mm	OFF	20175	1732.5	22.95	24.00	1.274	-0.11	0.977	1.244
	LTE Band 4	20M	QPSK	1RB	0Offset	Front	10mm	OFF	20300	1745	22.88	24.00	1.294	-0.11	1.030	1.333
	LTE Band 4	20M	QPSK	50RB	0Offset	Front	10mm	OFF	20050	1720	22.10	23.00	1.230	-0.03	0.679	0.835
	LTE Band 4	20M	QPSK	50RB	0Offset	Front	10mm	OFF	20175	1732.5	22.00	23.00	1.259	-0.1	0.699	0.880
	LTE Band 4	20M	QPSK	50RB	0Offset	Front	10mm	OFF	20300	1745	21.85	23.00	1.303	-0.04	0.680	0.886
	LTE Band 4	20M	QPSK	100RB	0Offset	Front	10mm	OFF	20050	1720	21.92	23.00	1.282	-0.11	0.683	0.876
	LTE Band 4	20M	QPSK	1RB	0Offset	Back	10mm	OFF	20050	1720	23.29	24.00	1.178	-0.07	0.868	1.022
	LTE Band 4	20M	QPSK	1RB	0Offset	Back	10mm	OFF	20175	1732.5	22.95	24.00	1.274	-0.16	0.791	1.007
	LTE Band 4	20M	QPSK	1RB	0Offset	Back	10mm	OFF	20300	1745	22.88	24.00	1.294	-0.02	0.752	0.973
	LTE Band 4	20M	QPSK	50RB	0Offset	Back	10mm	OFF	20050	1720	22.10	23.00	1.230	0.02	0.512	0.630
	LTE Band 4	20M	QPSK	100RB	0Offset	Back	10mm	OFF	20050	1720	21.92	23.00	1.282	-0.07	0.515	0.660
	LTE Band 4	20M	QPSK	1RB	0Offset	Left Side	10mm	OFF	20050	1720	23.29	24.00	1.178	0.04	0.063	0.074
	LTE Band 4	20M	QPSK	50RB	0Offset	Left Side	10mm	OFF	20050	1720	22.10	23.00	1.230	0.18	0.041	0.050
	LTE Band 4	20M	QPSK	1RB	0Offset	Right Side	10mm	OFF	20050	1720	23.29	24.00	1.178	0.08	0.650	0.765
	LTE Band 4	20M	QPSK	50RB	0Offset	Right Side	10mm	OFF	20050	1720	22.10	23.00	1.230	-0.04	0.437	0.538
	LTE Band 4	20M	QPSK	1RB	0Offset	Bottom Side	10mm	OFF	20050	1720	23.29	24.00	1.178	0.01	0.776	0.914
	LTE Band 4	20M	QPSK	1RB	0Offset	Bottom Side	10mm	OFF	20175	1732.5	22.95	24.00	1.274	0.14	0.803	1.023
	LTE Band 4	20M	QPSK	1RB	0Offset	Bottom Side	10mm	OFF	20300	1745	22.88	24.00	1.294	0.05	0.770	0.997
	LTE Band 4	20M	QPSK	50RB	0Offset	Bottom Side	10mm	OFF	20050	1720	22.10	23.00	1.230	-0.01	0.492	0.605
	LTE Band 4	20M	QPSK	100RB	0Offset	Bottom Side	10mm	OFF	20050	1720	21.92	23.00	1.282	-0.05	0.502	0.644
23	LTE Band 2	20M	QPSK	1RB	0offset	Front	10mm	ON	18700	1860		22.00	1.000	0.1	1.320	1.320
	LTE Band 2	20M	QPSK	1RB	0offset	Front	10mm	ON	18900	1880		22.00	1.000	-0.05	1.330	1.330
	LTE Band 2	20M	QPSK	1RB	0offset	Front	10mm	ON	19100	1900		22.00	1.000	-0.1	1.290	1.290
	LTE Band 2	20M	QPSK	50RB	0offset	Front	10mm	ON	18700	1860		22.00	1.000	-0.03	0.833	0.833
	LTE Band 2	20M	QPSK	50RB	0offset	Front	10mm	ON	18900	1880		22.00	1.000	-0.11	0.830	0.830
	LTE Band 2	20M	QPSK	50RB	0offset	Front	10mm	ON	19100	1900		22.00	1.000	0.06	0.789	0.789
	LTE Band 2	20M	QPSK	100RB	0offset	Front	10mm	ON	18700	1860		22.00	1.000	-0.06	0.799	0.799
	LTE Band 2	20M	QPSK	1RB	0offset	Back	10mm	ON	18700	1860		22.00	1.000	-0.04	0.725	0.725
	LTE Band 2	20M	QPSK	50RB	0offset	Back	10mm	ON	18700	1860		22.00	1.000	-0.05	0.681	0.681
	LTE Band 2	20M	QPSK	1RB	0offset	Left Side	10mm	ON	18700	1860		22.00	1.000	0.02	0.118	0.118
	LTE Band 2	20M	QPSK	50RB	0offset	Left Side	10mm	ON	18700	1860		22.00	1.000	-0.03	0.117	0.117
	LTE Band 2	20M	QPSK	1RB	0offset	Right Side	10mm	ON	18700	1860		22.00	1.000	-0.04	0.458	0.458
	LTE Band 2	20M	QPSK	50RB	0offset	Right Side	10mm	ON	18700	1860		22.00	1.000	-0.06	0.430	0.430
	LTE Band 2	20M	QPSK	1RB	0offset	Bottom Side	10mm	ON	18700	1860		22.00	1.000	-0.04	1.080	1.080
	LTE Band 2	20M	QPSK	1RB	0offset	Bottom Side	10mm	ON	18900	1880		22.00	1.000	-0.01	1.150	1.150
	LTE Band 2	20M	QPSK	1RB	0offset	Bottom Side	10mm	ON	19100	1900		22.00	1.000	0.16	0.986	0.986
	LTE Band 2	20M	QPSK	50RB	0offset	Bottom Side	10mm	ON	18700	1860		22.00	1.000	-0.02	0.583	0.583
	LTE Band 2	20M	QPSK	100RB	0offset	Bottom Side	10mm	ON	18700	1860		22.00	1.000	0.09	0.563	0.563
	LTE Band 7	20M	QPSK	1RB	0offset	Front	10mm	ON	21100	2535		18.50	1.000	0.04	0.512	0.512
	LTE Band 7	20M	QPSK	50RB	0offset	Front	10mm	ON	21100	2535		18.50	1.000	-0.12	0.518	0.518
	LTE Band 7	20M	QPSK	1RB	0offset	Back	10mm	ON	21100	2535		18.50	1.000	-0.12	0.606	0.606
	LTE Band 7	20M	QPSK	50RB	0offset	Back	10mm	ON	21100	2535		18.50	1.000	-0.13	0.621	0.621
	LTE Band 7	20M	QPSK	1RB	0offset	Left Side	10mm	ON	21100	2535		18.50	1.000	-0.03	0.242	0.242
	LTE Band 7	20M	QPSK	50RB	0offset	Left Side	10mm	ON	21100	2535		18.50	1.000	0.12	0.247	0.247
	LTE Band 7	20M	QPSK	1RB	0offset	Right Side	10mm	ON	21100	2535		18.50	1.000	-0.17	0.029	0.029
	LTE Band 7	20M	QPSK	50RB	0offset	Right Side	10mm	ON	21100	2535		18.50	1.000	0.15	0.026	0.026
	LTE Band 7	20M	QPSK	1RB	0offset	Bottom Side	10mm	ON	21100	2535		18.50	1.000	-0.1	0.748	0.748
	LTE Band 7	20M	QPSK	1RB	0offset	Bottom Side	10mm	ON	20850	2510		18.50	1.000	-0.08	0.727	0.727
24	LTE Band 7	20M	QPSK	1RB	0offset	Bottom Side	10mm	ON	21350	2560		18.50	1.000	-0.1	0.763	0.763
	LTE Band 7	20M	QPSK	50RB	0offset	Bottom Side	10mm	ON	21100	2535		18.50	1.000	-0.1	0.744	0.744

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.03	0.045	0.048
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.1	0.080	0.085
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	11	2462	15.88	16.00	1.029	97.16	1.029	0.13	0.083	0.088
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	1	2412	15.31	16.00	1.174	97.16	1.029	0.06	0.061	0.074
25	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	6	2437	15.48	16.00	1.128	97.16	1.029	0.15	0.077	0.089
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	11	2462	15.88	16.00	1.029	97.16	1.029	0.01	0.053	0.056

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	39	2441	9.73	10.00	1.064	0	0.001	0.001
	Bluetooth	1Mbps	Back	10mm	39	2441	9.73	10.00	1.064	-0.15	0.001	0.001
26	Bluetooth	1Mbps	Right Side	10mm	39	2441	9.73	10.00	1.064	-0.12	0.019	0.020
	Bluetooth	1Mbps	Right Side	10mm	0	2402	9.54	10.00	1.112	-0.14	0.013	0.014
	Bluetooth	1Mbps	Right Side	10mm	78	2480	9.25	10.00	1.189	0.19	0.008	0.009
	Bluetooth	1Mbps	Top Side	10mm	39	2441	9.73	10.00	1.064	-0.17	0.005	0.005

14.3 Body Worn Accessory SAR
<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (2 Tx slots)	Front	15mm	189	836.4	30.72	32.00	1.343	-0.04	0.363	0.487
	GSM850	GPRS (2 Tx slots)	Front	15mm	128	824.2	30.68	32.00	1.355	-0.08	0.202	0.274
27	GSM850	GPRS (2 Tx slots)	Front	15mm	251	848.8	30.33	32.00	1.469	0.01	0.371	0.545
	GSM850	GPRS (2 Tx slots)	Back	15mm	189	836.4	30.72	32.00	1.343	-0.06	0.313	0.420
28	GSM1900	GPRS (2 Tx slots)	Front	15mm	512	1850.2	27.61	29.00	1.377	-0.09	0.337	0.464
	GSM1900	GPRS (2 Tx slots)	Front	15mm	661	1880	27.43	29.00	1.435	0.02	0.320	0.459
	GSM1900	GPRS (2 Tx slots)	Front	15mm	810	1909.8	27.42	29.00	1.439	-0.06	0.322	0.463
	GSM1900	GPRS (2 Tx slots)	Back	15mm	512	1850.2	27.61	29.00	1.377	-0.08	0.261	0.359

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	15mm	4233	846.6	23.99	24.00	1.002	0	0.595	0.596
29	WCDMA V	RMC 12.2Kbps	Back	15mm	4233	846.6	23.99	24.00	1.002	-0.03	0.619	0.620
	WCDMA V	RMC 12.2Kbps	Back	15mm	4132	826.4	23.78	24.00	1.052	0.02	0.494	0.520
	WCDMA V	RMC 12.2Kbps	Back	15mm	4182	836.4	23.93	24.00	1.016	-0.02	0.490	0.498
	WCDMA IV	RMC 12.2Kbps	Front	15mm	1312	1712.4	22.92	24.00	1.282	-0.05	0.755	0.968
	WCDMA IV	RMC 12.2Kbps	Front	15mm	1413	1732.6	22.83	24.00	1.309	-0.07	0.639	0.837
30	WCDMA IV	RMC 12.2Kbps	Front	15mm	1513	1752.6	22.74	24.00	1.337	-0.04	0.804	1.075
	WCDMA IV	RMC 12.2Kbps	Back	15mm	1312	1712.4	22.92	24.00	1.282	-0.1	0.453	0.581
	WCDMA II	RMC 12.2Kbps	Front	15mm	9538	1907.6	23.99	24.00	1.002	-0.03	0.587	0.588
31	WCDMA II	RMC 12.2Kbps	Front	15mm	9262	1852.4	23.97	24.00	1.007	-0.12	0.607	0.611
	WCDMA II	RMC 12.2Kbps	Front	15mm	9400	1880	23.91	24.00	1.021	-0.11	0.569	0.581
	WCDMA II	RMC 12.2Kbps	Back	15mm	9538	1907.6	23.99	24.00	1.002	0.01	0.325	0.326

**<LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
32	LTE Band 12	10M	QPSK	1RB	0offset	Front	15mm	23130	711	23.77	24.00	1.054	-0.08	0.601	0.634
	LTE Band 12	10M	QPSK	25RB	24offset	Front	15mm	23130	711	22.64	23.00	1.086	-0.05	0.503	0.546
	LTE Band 12	10M	QPSK	1RB	0offset	Back	15mm	23130	711	23.77	24.00	1.054	-0.02	0.470	0.496
	LTE Band 12	10M	QPSK	25RB	24offset	Back	15mm	23130	711	22.64	23.00	1.086	-0.11	0.407	0.442
	LTE Band 17	10M	QPSK	1RB	0offset	Front	15mm	23790	710	23.78	24.00	1.052	-0.09	0.674	0.709
	LTE Band 17	10M	QPSK	25RB	0offset	Front	15mm	23780	709	22.69	23.00	1.074	-0.14	0.510	0.548
33	LTE Band 17	10M	QPSK	1RB	0offset	Back	15mm	23790	710	23.78	24.00	1.052	0.04	0.703	0.740
	LTE Band 17	10M	QPSK	25RB	0offset	Back	15mm	23780	709	22.69	23.00	1.074	0.01	0.554	0.595
	LTE Band 5	10M	QPSK	1RB	0offset	Front	15mm	20600	844	23.22	24.00	1.197	0.11	0.451	0.540
	LTE Band 5	10M	QPSK	25RB	24offset	Front	15mm	20600	844	21.96	23.00	1.271	0.01	0.360	0.457
	LTE Band 5	10M	QPSK	1RB	0offset	Back	15mm	20600	844	23.22	24.00	1.197	-0.01	0.459	0.549
34	LTE Band 5	10M	QPSK	1RB	24offset	Back	15mm	20450	829	23.05	24.00	1.245	-0.03	0.451	0.561
	LTE Band 5	10M	QPSK	1RB	0offset	Back	15mm	20525	836.5	22.99	24.00	1.262	0.04	0.439	0.554
	LTE Band 5	10M	QPSK	25RB	24offset	Back	15mm	20600	844	21.96	23.00	1.271	0	0.359	0.456
	LTE Band 4	20M	QPSK	1RB	0offset	Front	15mm	20050	1720	23.29	24.00	1.178	0.12	0.569	0.670
35	LTE Band 4	20M	QPSK	1RB	0offset	Front	15mm	20175	1732.5	22.95	24.00	1.274	-0.02	0.596	0.759
	LTE Band 4	20M	QPSK	1RB	0offset	Front	15mm	20300	1745	22.88	24.00	1.294	-0.06	0.552	0.714
	LTE Band 4	20M	QPSK	50RB	0offset	Front	15mm	20050	1720	22.10	23.00	1.230	-0.04	0.393	0.483
	LTE Band 4	20M	QPSK	1RB	0offset	Back	15mm	20050	1720	23.29	24.00	1.178	-0.11	0.458	0.539
	LTE Band 4	20M	QPSK	50RB	0offset	Back	15mm	20050	1720	22.10	23.00	1.230	-0.07	0.300	0.369
	LTE Band 2	20M	QPSK	1RB	0offset	Front	15mm	18700	1860	23.00	24.00	1.259	0.14	0.832	1.047
36	LTE Band 2	20M	QPSK	1RB	0offset	Front	15mm	18900	1880	22.80	24.00	1.318	-0.04	0.832	1.097
	LTE Band 2	20M	QPSK	1RB	0offset	Front	15mm	19100	1900	22.82	24.00	1.312	-0.1	0.772	1.013
	LTE Band 2	20M	QPSK	50RB	0offset	Front	15mm	18700	1860	21.74	23.00	1.337	-0.03	0.451	0.603
	LTE Band 2	20M	QPSK	100RB	0offset	Front	15mm	18700	1860	21.61	23.00	1.377	-0.04	0.456	0.628
	LTE Band 2	20M	QPSK	1RB	0offset	Back	15mm	18700	1860	23.00	24.00	1.259	0	0.733	0.923
	LTE Band 2	20M	QPSK	1RB	0offset	Back	15mm	18900	1880	22.80	24.00	1.318	-0.17	0.773	1.019
	LTE Band 2	20M	QPSK	1RB	0offset	Back	15mm	19100	1900	22.82	24.00	1.312	-0.11	0.748	0.982
	LTE Band 2	20M	QPSK	50RB	0offset	Back	15mm	18700	1860	21.74	23.00	1.337	-0.08	0.431	0.576
	LTE Band 2	20M	QPSK	100RB	0offset	Back	15mm	18700	1860	21.61	23.00	1.377	-0.1	0.410	0.565
	LTE Band 7	20M	QPSK	1RB	0offset	Front	15mm	21100	2535	22.58	24.00	1.387	-0.1	0.484	0.671
	LTE Band 7	20M	QPSK	50RB	0offset	Front	15mm	21100	2535	21.41	23.00	1.442	-0.11	0.306	0.441
	LTE Band 7	20M	QPSK	1RB	0offset	Back	15mm	21100	2535	22.58	24.00	1.387	-0.1	0.793	1.100
37	LTE Band 7	20M	QPSK	1RB	0offset	Back	15mm	20850	2510	22.50	24.00	1.413	-0.04	0.798	1.127
	LTE Band 7	20M	QPSK	1RB	0offset	Back	15mm	21350	2560	22.39	24.00	1.449	-0.17	0.722	1.046
	LTE Band 7	20M	QPSK	50RB	0offset	Back	15mm	21100	2535	21.41	23.00	1.442	-0.06	0.467	0.673
	LTE Band 7	20M	QPSK	100RB	0offset	Back	15mm	21100	2535	21.43	23.00	1.435	-0.07	0.457	0.656

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	11	2462	15.88	16.00	1.029	97.16	1.029	-0.09	0.022	0.023
	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	11	2462	15.88	16.00	1.029	97.16	1.029	0.15	0.043	0.046
	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	1	2412	15.31	16.00	1.174	97.16	1.029	-0.09	0.041	0.050
38	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	6	2437	15.48	16.00	1.128	97.16	1.029	-0.17	0.046	0.053

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	15mm	39	2441	9.73	10.00	1.064	0	< 0.001	< 0.001
39	Bluetooth	1Mbps	Back	15mm	39	2441	9.73	10.00	1.064	-0.09	< 0.001	< 0.001
	Bluetooth	1Mbps	Back	15mm	0	2402	9.54	10.00	1.112	0	< 0.001	< 0.001
	Bluetooth	1Mbps	Back	15mm	78	2480	9.25	10.00	1.189	0	< 0.001	< 0.001

14.4 Repeated SAR Measurement

No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	LTE Band 17	10M	QPSK	1RB	0offset	Back	10mm	OFF	23790	710	23.78	24.00	1.052	-0.12	0.879	-	0.925
2nd	LTE Band 17	10M	QPSK	1RB	0offset	Back	10mm	OFF	23790	710	23.78	24.00	1.052	-0.07	0.858	1.02	0.903
1st	LTE Band 4	20M	QPSK	1RB	0Offset	Front	10mm	OFF	20050	1720	23.29	24.00	1.178	-0.08	1.050	-	1.236
2nd	LTE Band 4	20M	QPSK	1RB	0Offset	Front	10mm	OFF	20050	1720	23.29	24.00	1.178	-0.09	1.020	1.03	1.201
1st	LTE Band 2	20M	QPSK	1RB	0offset	Front	10mm	ON	18900	1880		22.00	1.000	-0.05	1.330	-	1.330
2nd	LTE Band 2	20M	QPSK	1RB	0offset	Front	10mm	ON	18900	1880		22.00	1.000	-0.11	1.260	1.06	1.260

General Note:

1. Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r03, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			Note
		Head	Body-worn	Hotspot	
1.	GSM(Voice) + WLAN2.4GHz(data)	Yes	Yes		
2.	WCDMA(Voice) + WLAN2.4GHz(data)	Yes	Yes		
3.	LTE(Voice) + WLAN2.4GHz(data)	Yes	Yes		
4.	GSM(Voice) + Bluetooth(data)	Yes	Yes		
5.	WCDMA(Voice) + Bluetooth(data)	Yes	Yes		
6.	LTE(Voice) + Bluetooth(data)	Yes	Yes		
7.	GPRS/EDGE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
8.	WCDMA(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
9.	LTE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
10.	GPRS/EDGE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
11.	WCDMA(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
12.	LTE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering

General Note:

1. This device supported VoIP in EGPRS, WCDMA, LTE (e.g. 3rd party VoIP).
2. The Scaled SAR summation is calculated based on the same configuration and test position.
3. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
4. Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation $< 1.6\text{W/kg}$.
 - ii) $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.



15.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	2.4GHz Bluetooth		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Right Cheek	0.737	0.146	0.027	0.88	0.76
		Right Tilted	0.192	0.108	0.020	0.30	0.21
		Left Cheek	0.289	0.494	0.087	0.78	0.38
		Left Tilted	0.179	0.208	0.035	0.39	0.21
	GSM1900	Right Cheek	0.289	0.146	0.027	0.44	0.32
		Right Tilted	0.067	0.108	0.020	0.18	0.09
		Left Cheek	0.387	0.494	0.087	0.88	0.47
		Left Tilted	0.076	0.208	0.035	0.28	0.11
WCDMA	WCDMA V	Right Cheek	0.649	0.146	0.027	0.80	0.68
		Right Tilted	0.415	0.108	0.020	0.52	0.44
		Left Cheek	0.560	0.494	0.087	1.05	0.65
		Left Tilted	0.375	0.208	0.035	0.58	0.41
	WCDMA IV	Right Cheek	0.391	0.146	0.027	0.54	0.42
		Right Tilted	0.155	0.108	0.020	0.26	0.18
		Left Cheek	0.624	0.494	0.087	1.12	0.71
		Left Tilted	0.150	0.208	0.035	0.36	0.19
	WCDMA II	Right Cheek	0.344	0.146	0.027	0.49	0.37
		Right Tilted	0.149	0.108	0.020	0.26	0.17
		Left Cheek	0.439	0.494	0.087	0.93	0.53
		Left Tilted	0.115	0.208	0.035	0.32	0.15
LTE	LTE Band 12	Right Cheek	0.486	0.146	0.027	0.63	0.51
		Right Tilted	0.189	0.108	0.020	0.30	0.21
		Left Cheek	0.495	0.494	0.087	0.99	0.58
		Left Tilted	0.201	0.208	0.035	0.41	0.24
	LTE Band 17	Right Cheek	0.547	0.146	0.027	0.69	0.57
		Right Tilted	0.330	0.108	0.020	0.44	0.35
		Left Cheek	0.499	0.494	0.087	0.99	0.59
		Left Tilted	0.227	0.208	0.035	0.44	0.26
	LTE Band 5	Right Cheek	0.634	0.146	0.027	0.78	0.66
		Right Tilted	0.357	0.108	0.020	0.47	0.38
		Left Cheek	0.469	0.494	0.087	0.96	0.56
		Left Tilted	0.372	0.208	0.035	0.58	0.41
	LTE Band 4	Right Cheek	0.428	0.146	0.027	0.57	0.46
		Right Tilted	0.122	0.108	0.020	0.23	0.14
		Left Cheek	0.353	0.494	0.087	0.85	0.44
		Left Tilted	0.132	0.208	0.035	0.34	0.17
	LTE Band 2	Right Cheek	0.645	0.146	0.027	0.79	0.67
		Right Tilted	0.252	0.108	0.020	0.36	0.27
		Left Cheek	0.733	0.494	0.087	1.23	0.82
		Left Tilted	0.256	0.208	0.035	0.46	0.29
	LTE Band 7	Right Cheek	0.161	0.146	0.027	0.31	0.19
		Right Tilted	0.107	0.108	0.020	0.22	0.13
		Left Cheek	0.267	0.494	0.087	0.76	0.35
		Left Tilted	0.044	0.208	0.035	0.25	0.08

15.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	2.4GHz Bluetooth		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Front	0.638	0.048	0.001	0.69	0.64
		Back	0.577	0.085	0.001	0.66	0.58
		Left side	0.121			0.12	0.12
		Right side	0.397	0.089	0.020	0.49	0.42
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.142			0.14	0.14
	GSM1900	Front	0.970	0.048	0.001	1.02	0.97
		Back	0.631	0.085	0.001	0.72	0.63
		Left side	0.140			0.14	0.14
		Right side	0.572	0.089	0.020	0.66	0.59
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.624			0.62	0.62
WCDMA	WCDMA V	Front	0.631	0.048	0.001	0.68	0.63
		Back	0.671	0.085	0.001	0.76	0.67
		Left side	0.314			0.31	0.31
		Right side	0.545	0.089	0.020	0.63	0.57
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.204			0.20	0.20
	WCDMA IV	Front	0.707	0.048	0.001	0.76	0.71
		Back	0.561	0.085	0.001	0.65	0.56
		Left side	0.054			0.05	0.05
		Right side	0.434	0.089	0.020	0.52	0.45
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.553			0.55	0.55
	WCDMA II	Front	1.213	0.048	0.001	1.26	1.21
		Back	0.757	0.085	0.001	0.84	0.76
		Left side	0.235			0.24	0.24
		Right side	0.573	0.089	0.020	0.66	0.59
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.887			0.89	0.89



WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	2.4GHz Bluetooth 1g SAR (W/kg)		
LTE	LTE Band 12	Front	0.850	0.048	0.001	0.90	0.85
		Back	0.900	0.085	0.001	0.99	0.90
		Left side	0.651			0.65	0.65
		Right side	0.309	0.089	0.020	0.40	0.33
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.375			0.38	0.38
	LTE Band 17	Front	0.908	0.048	0.001	0.96	0.91
		Back	0.925	0.085	0.001	1.01	0.93
		Left side	0.661			0.66	0.66
		Right side	0.333	0.089	0.020	0.42	0.35
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.358			0.36	0.36
	LTE Band 5	Front	0.573	0.048	0.001	0.62	0.57
		Back	0.682	0.085	0.001	0.77	0.68
		Left side	0.280			0.28	0.28
		Right side	0.462	0.089	0.020	0.55	0.48
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.200			0.20	0.20
	LTE Band 4	Front	1.333	0.048	0.001	1.38	1.33
		Back	1.022	0.085	0.001	1.11	1.02
		Left side	0.074			0.07	0.07
		Right side	0.765	0.089	0.020	0.85	0.79
		Top side		0.056	0.005	0.06	0.01
		Bottom side	1.023			1.02	1.02
	LTE Band 2	Front	1.330	0.048	0.001	1.38	1.33
		Back	0.725	0.085	0.001	0.81	0.73
		Left side	0.118			0.12	0.12
		Right side	0.458	0.089	0.020	0.55	0.48
		Top side		0.056	0.005	0.06	0.01
		Bottom side	1.150			1.15	1.15
	LTE Band 7	Front	0.518	0.048	0.001	0.57	0.52
		Back	0.621	0.085	0.001	0.71	0.62
		Left side	0.247			0.25	0.25
		Right side	0.029	0.089	0.020	0.12	0.05
		Top side		0.056	0.005	0.06	0.01
		Bottom side	0.763			0.76	0.76

15.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	2.4GHz Bluetooth		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Front	0.545	0.023	0.001	0.57	0.55
		Back	0.420	0.053	0.001	0.47	0.42
	GSM1900	Front	0.464	0.023	0.001	0.49	0.47
		Back	0.359	0.053	0.001	0.41	0.36
WCDMA	WCDMA V	Front	0.596	0.023	0.001	0.62	0.60
		Back	0.620	0.053	0.001	0.67	0.62
	WCDMA IV	Front	1.075	0.023	0.001	1.10	1.08
		Back	0.581	0.053	0.001	0.63	0.58
	WCDMA II	Front	0.611	0.023	0.001	0.63	0.61
		Back	0.326	0.053	0.001	0.38	0.33
LTE	LTE Band 12	Front	0.634	0.023	0.001	0.66	0.64
		Back	0.496	0.053	0.001	0.55	0.50
	LTE Band 17	Front	0.709	0.023	0.001	0.73	0.71
		Back	0.740	0.053	0.001	0.79	0.74
	LTE Band 5	Front	0.540	0.023	0.001	0.56	0.54
		Back	0.561	0.053	0.001	0.61	0.56
	LTE Band 4	Front	0.759	0.023	0.001	0.78	0.76
		Back	0.539	0.053	0.001	0.59	0.54
	LTE Band 2	Front	1.097	0.023	0.001	1.12	1.10
		Back	1.019	0.053	0.001	1.07	1.02
	LTE Band 7	Front	0.671	0.023	0.001	0.69	0.67
		Back	1.127	0.053	0.001	1.18	1.13

Test Engineer : Galen Zhang, Thomas Wang, Angelo Chang, Tommy Chen, Kurt Liu, Iran Wang, and Jerry Hu

16. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	$1/k^{(b)}$	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Table 16.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 16.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [3] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [4] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v2, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Mar 2015.
- [7] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [8] FCC KDB 648474 D04 v01r02, "SAR Evaluation Considerations for Wireless Handsets", Dec 2013.
- [9] FCC KDB 941225 D01 v03, "3G SAR MEAUREMENT PROCEDURES", Oct 2014
- [10] FCC KDB 941225 D05 v02r03, "SAR Evaluation Considerations for LTE Devices", Dec 2013
- [11] FCC KDB 941225 D06 v02, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2014.
- [12] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014.
- [13] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013.