



# FCC Test Report

APPLICANT : Motorola Mobility LLC.  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : 9397  
FCC ID : IHDT56VD5  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification

The product was received on May 10, 2016 and testing was completed on May 26, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Louis Wu / Manager

Approved by: Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 6

    1.5. Modification of EUT ..... 6

    1.6. Test Location ..... 7

    1.7. Applicable Standards ..... 7

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1. Test Mode ..... 8

    2.2. Connection Diagram of Test System ..... 9

    2.3. Support Unit used in test configuration and system ..... 10

    2.4. EUT Operation Test Setup ..... 10

**3. TEST RESULT ..... 11**

    3.1. Test of AC Conducted Emission Measurement ..... 11

    3.2. Test of Radiated Emission Measurement ..... 15

**4. LIST OF MEASURING EQUIPMENT ..... 19**

**5. UNCERTAINTY OF EVALUATION ..... 20**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC651022	Rev. 01	Initial issue of report	Jun. 06, 2016



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 9.70 dB at 0.158 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 8.17 dB at 950.300 MHz



# 1. General Description

## 1.1. Applicant

Motorola Mobility LLC.  
222 W. Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2. Manufacturer

Motorola Mobility LLC.  
222 W. Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	9397
FCC ID	IHDT56VD5
IMEI Code	354145070000075
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC/FM WLAN 11b/g/n HT20 Bluetooth v3.0 EDR Bluetooth v4.1 LE
HW Version	DVT2-A
SW Version	fastboot_harpia_oem_userdebug_6.0.1_MPI24.223_2173_int cfg-test-keys_oem.tar.gz
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Accessory List	
Earphone	Brand Name : Motorola
	Model Name : SJYN1181B
USB Cable	Brand Name : Motorola
	Model Name : SKN6462A
Battery 1	Brand Name : Motorola
	Model Name : SNN5976A
Battery 2	Brand Name : Motorola
	Model Name : SNN5977A



### 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 40 : 2302.5 MHz ~ 2397.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 40 : 2302.5 MHz ~ 2397.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass : 1602 MHz + n× 0.5625MHz (n=-7,-6,-5,...,0,...,6) NFC : 13.56 MHz FM : 88 MHz ~ 108 MHz
<b>Antenna Type</b>	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna NFC : Loop Antenna GPS/Glonass: Fixed Internal Antenna FM: External headset Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: QPSK (Uplink) HSDPA: 64QAM (Downlink) HSUPA: QPSK (Uplink) LTE: QPSK / 16QAM / 64QAM (Downlink Only) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/Glonass : BPSK NFC: ASK FM : FM

### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6. Test Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	CO05-HY	03CH06-HY

### 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. For FCC 15 Subpart B - Unintentional Radiators, device supporting USB interface or similar peripherals (defined as the Section 15.3 (r) Peripheral device) acting as a peripheral for personal computers shall be authorized as “The Class B personal computers and peripherals” per the Section 15.101 (a) Equipment authorization of unintentional radiators.
3. For other Unintentional Radiators features of this EUT, test reports are be issued separately.  
Per the Note of the Section 15.101, when device supports features (USB, FM Radio, digital devices...etc) more than one category of authorization, type of authorization shall be appropriately chosen for FCC 15B compliance rule, and the Section 15.101 (b), only those receivers that operate (tune) within the frequency range of 30-960 MHz, CB receivers and radar detectors are subject to the authorizations shown in paragraph (a) of the Section 15.101. However, receivers indicated as being subject to Declaration of Conformity that are contained within a transceiver, the transmitter portion of which is subject to certification, shall be authorized under the verification procedure.



## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Data application transferred mode (EUT with notebook)	☒	☒	☒

**Abbreviations:**


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1	Mode 1: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 1 + USB Cable (Data Link with Notebook) + SIM 1 Mode 2: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook) + SIM 1
Radiated Emissions < 1GHz	1	Mode 1: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 1 + USB Cable (Data Link with Notebook) + SIM 1 Mode 2: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook) + SIM 1
Radiated Emissions ≥ 1GHz	1	Mode 1: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook) + SIM 1

**Remark:**

1. The worst case of AC is mode 1; only the test data of this mode was reported.
2. The worst case of RE < 1G is mode 2; only the test data of this mode was reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook

## 2.2. Connection Diagram of Test System



Conduction & Radiation Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	-	-	-	-	-
A1	Bluetooth Earphone	Bluetooth	X	X					
A2	System Simulator	GSM/UMTS/CDMA/ WCDMA/LTE	X	X					
A3	AP router	WiFi	X	X					
No.	Setup Peripherals	Connection Type	1	2	-	-	-	-	-
C1	Notebook	USB Cable	X	X					
C1-1	iPod	USB Cable to C1	X	X					
C1-2	AP router	RJ-45 Cable to C1	X	X					
C2	Earphone	Earphone jack	X	X					
C3	SD card	SD I/O interface without Cable	X	X					

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
6.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
7.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0 m	N/A

### 2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

The EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Laptop and EUT via USB cable.



### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





### 3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	50~51%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 1 + USB Cable (Data Link with Notebook) + SIM 1		



#### Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	55.9	Off	L1	19.6	9.7	65.6
0.190000	54.1	Off	L1	19.6	9.9	64.0
0.238000	45.2	Off	L1	19.6	17.0	62.2
0.262000	43.0	Off	L1	19.6	18.4	61.4
0.294000	36.5	Off	L1	19.6	23.9	60.4
3.862000	25.5	Off	L1	19.8	30.5	56.0
4.734000	23.4	Off	L1	19.8	32.6	56.0
16.382000	25.2	Off	L1	20.5	34.8	60.0

#### Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	34.4	Off	L1	19.6	21.2	55.6
0.190000	33.9	Off	L1	19.6	20.1	54.0
0.238000	29.5	Off	L1	19.6	22.7	52.2
0.262000	24.8	Off	L1	19.6	26.6	51.4
0.294000	23.8	Off	L1	19.6	26.6	50.4
3.862000	17.6	Off	L1	19.8	28.4	46.0
4.734000	15.2	Off	L1	19.8	30.8	46.0
16.382000	16.7	Off	L1	20.5	33.3	50.0



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	50~51%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 1 + USB Cable (Data Link with Notebook) + SIM 1		



**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	51.6	Off	N	19.6	13.2	64.8
0.190000	49.5	Off	N	19.6	14.5	64.0
0.230000	46.6	Off	N	19.6	15.8	62.4
0.246000	44.3	Off	N	19.6	17.6	61.9
0.262000	40.7	Off	N	19.6	20.7	61.4
0.294000	36.7	Off	N	19.6	23.7	60.4
4.326000	19.9	Off	N	19.8	36.1	56.0
16.878000	25.0	Off	N	20.6	35.0	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	34.8	Off	N	19.6	20.0	54.8
0.190000	32.0	Off	N	19.6	22.0	54.0
0.230000	29.8	Off	N	19.6	22.6	52.4
0.246000	29.1	Off	N	19.6	22.8	51.9
0.262000	25.9	Off	N	19.6	25.5	51.4
0.294000	22.5	Off	N	19.6	27.9	50.4
4.326000	14.6	Off	N	19.8	31.4	46.0
16.878000	18.1	Off	N	20.6	31.9	50.0



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 2	Temperature :	20~23°C
Test Engineer :	Daniel Lee	Relative Humidity :	50~53%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook) + SIM 1		
Remark :	#5 is system simulator signal which can be ignored.		




Site : 03CH06-HY  
 Condition : FCC CLASS-B 3m 9120D\_1156\_150827 HORIZONTAL  
 Project : 651022  
 Power : From System  
 Memo : Mode 2

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	cm	deg	
			dB	dBuV/m	dBuV	dB/m	dB	dB			
1	30.81	24.18	-15.82	40.00	28.94	25.14	1.90	31.80	---	---	Peak
2	180.12	31.11	-12.39	43.50	45.65	15.20	1.98	31.72	---	---	Peak
3	240.60	35.49	-10.51	46.00	47.25	17.79	2.16	31.71	---	---	Peak
4	850.20	34.47	-11.53	46.00	33.78	29.11	3.31	31.73	---	---	Peak
5 *	881.70	50.83			49.78	29.29	3.36	31.60	---	---	Peak
6	897.10	34.80	-11.20	46.00	33.57	29.38	3.39	31.54	---	---	Peak
7	950.30	36.42	-9.58	46.00	33.73	30.70	3.05	31.06	100	211	Peak
8	1932.00	43.83	-30.17	74.00	71.89	26.21	6.23	60.50	---	---	Peak
9	4920.00	41.81	-32.19	74.00	58.47	31.39	11.17	59.22	---	---	Peak
10	6918.00	42.73	-31.27	74.00	56.18	35.09	11.78	60.32	---	---	Peak
11	7962.00	43.44	-30.56	74.00	53.26	37.15	12.69	59.66	---	---	Peak
12	9506.00	45.04	-28.96	74.00	53.40	38.80	13.94	61.10	---	---	Peak
13	11126.00	46.89	-27.11	74.00	50.04	40.42	15.34	58.91	100	0	Peak



Test Mode :	Mode 2	Temperature :	20~23°C
Test Engineer :	Daniel Lee	Relative Humidity :	50~53%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + Earphone + Battery 2 + USB Cable (Data Link with Notebook) + SIM 1		
Remark :	#5 is system simulator signal which can be ignored.		



Site : 03CH06-HY  
 Condition : FCC CLASS-B 3m 9120D\_1156\_150827 VERTICAL  
 Project : 651022  
 Power : From System  
 Memo : Mode 2

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg		
1	33.24	27.45	-12.55	40.00	33.32	24.02	1.91	31.80	---	---	Peak
2	182.01	30.74	-12.76	43.50	45.26	15.22	1.98	31.72	---	---	Peak
3	237.90	34.82	-11.18	46.00	46.86	17.52	2.15	31.71	---	---	Peak
4	850.20	34.02	-11.98	46.00	33.33	29.11	3.31	31.73	---	---	Peak
5 *	881.70	49.06			48.01	29.29	3.36	31.60	---	---	Peak
6	899.90	34.20	-11.80	46.00	32.94	29.40	3.39	31.53	---	---	Peak
7	950.30	37.83	-8.17	46.00	35.14	30.70	3.05	31.06	100	115	Peak
8	2000.00	50.60	-23.40	74.00	78.41	26.30	6.39	60.50	100	210	Peak
9	3128.00	47.62	-26.38	74.00	72.12	28.55	7.95	61.00	---	---	Peak
10	5330.00	41.93	-32.07	74.00	57.59	31.77	11.20	58.63	---	---	Peak
11	8558.00	44.56	-29.44	74.00	53.13	37.01	13.94	59.52	---	---	Peak
12	9356.00	45.86	-28.14	74.00	54.10	38.50	14.14	60.88	---	---	Peak
13	11452.00	46.39	-27.61	74.00	48.75	40.23	15.88	58.47	---	---	Peak



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 26, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	May 26, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	May 26, 2016	Dec. 01, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 14, 2015	May 26, 2016	Dec. 13, 2016	Conduction (CO05-HY)
Bilog Antenna	Schaffner	CBL6111C	2725	30MHz~1GHz	Nov. 17, 2015	May 22, 2016~ May 23, 2016	Nov. 16, 2016	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 07, 2016	May 22, 2016~ May 23, 2016	Jan. 06, 2017	Radiation (03CH06-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1156	1GHz~18GHz	Aug. 21, 2015	May 22, 2016~ May 23, 2016	Aug. 20, 2016	Radiation (03CH06-HY)
Preamplifier	SONOMA	310N	186713	9kHz~1GHz	Apr. 19, 2016	May 22, 2016~ May 23, 2016	Apr. 18, 2017	Radiation (03CH06-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1850117	1GHz ~ 18GHz	Jul. 01, 2015	May 22, 2016~ May 23, 2016	Jun. 30, 2016	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF780208212	1m~4m	N/A	May 22, 2016~ May 23, 2016	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0-360 degree	N/A	May 22, 2016~ May 23, 2016	N/A	Radiation (03CH06-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	May 22, 2016~ May 23, 2016	Sep. 01, 2016	Radiation (03CH06-HY)



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
-------------------------------------------------------------------------	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.00
-------------------------------------------------------------------------	------