

# FCC SAR Test Report

APPLICANT : Motorola Mobility LLC  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : 9840, 9841  
FCC ID : IHDT56VE4  
STANDARD : FCC 47 CFR Part 2 (2.1093)  
ANSI/IEEE C95.1-1992  
IEEE 1528-2013

This is a data re-used report which is only valid together with the original test report. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Prepared by: Mark Qu / Manager



Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



Table of Contents

1. Statement of Compliance ..... 4
2. Administration Data ..... 5
3. Guidance Applied..... 5
4. Equipment Under Test (EUT) Information ..... 6
4.1 General Information ..... 6
4.2 Specification of Accessory ..... 7
4.3 General LTE SAR Test and Reporting Considerations ..... 8
4.4 Re-use of Measured Data ..... 11
5. RF Exposure Limits..... 13
5.1 Uncontrolled Environment..... 13
5.2 Controlled Environment..... 13
6. Specific Absorption Rate (SAR)..... 14
6.1 Introduction ..... 14
6.2 SAR Definition..... 14
7. System Description and Setup ..... 15
7.1 E-Field Probe ..... 16
7.2 Data Acquisition Electronics (DAE) ..... 16
7.3 Phantom..... 17
7.4 Device Holder..... 18
8. Measurement Procedures ..... 19
8.1 Spatial Peak SAR Evaluation..... 19
8.2 Power Reference Measurement..... 20
8.3 Area Scan ..... 20
8.4 Zoom Scan..... 21
8.5 Volume Scan Procedures..... 21
8.6 Power Drift Monitoring..... 21
9. Test Equipment List..... 22
10. System Verification ..... 23
10.1 Tissue Simulating Liquids..... 23
10.2 Tissue Verification ..... 24
10.3 System Performance Check Results..... 25
11. RF Exposure Positions ..... 26
11.1 Ear and handset reference point ..... 26
11.2 Definition of the cheek position..... 27
11.3 Definition of the tilt position..... 28
11.4 Body Worn Accessory ..... 29
11.5 Wireless Router..... 29
12. Conducted RF Output Power (Unit: dBm)..... 30
13. SAR Test Results ..... 47
13.1 Head SAR ..... 49
13.2 Hotspot SAR ..... 51
13.3 Body Worn Accessory SAR..... 53
13.4 Repeated SAR Measurement ..... 55
14. Simultaneous Transmission Analysis ..... 56
14.1 Head Exposure Conditions ..... 57
14.2 Hotspot Exposure Conditions..... 58
14.3 Body-Worn Accessory Exposure Conditions ..... 59
15. Uncertainty Assessment ..... 60
16. References ..... 63
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASYS Calibration Certificate
Appendix D. Test Setup Photos
Appendix E. Reference Report



### Revision History

| REPORT NO.  | VERSION | DESCRIPTION             | ISSUED DATE   |
|-------------|---------|-------------------------|---------------|
| FA601212-06 | Rev. 01 | Initial issue of report | Nov. 09, 2016 |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |



**1. Statement of Compliance**

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, 9840, 9841** are as follows.

| Equipment Class  | Frequency Band |             | Highest SAR Summary     |                             |                           | Highest Simultaneous Transmission 1g SAR (W/kg) |
|------------------|----------------|-------------|-------------------------|-----------------------------|---------------------------|---|
|                  |                |             | Head (Separation 0mm)   | Body-worn (Separation 10mm) | Hotspot (Separation 10mm) |   |
|                  |                |             | 1g SAR (W/kg)           |                             |                           |   |
| Licensed         | GSM            | GSM850      | 0.27                    | 0.35                        | 0.41                      | 1.31  |
|                  |                | GSM1900     | 0.16                    | 0.65                        | 0.86                      |   |
|                  | WCDMA          | Band V      | 0.39                    | 0.42                        | 0.57                      |   |
|                  |                | Band II     | 0.42                    | 0.74                        | 0.94                      |   |
|                  | LTE            | Band 5      | 0.39                    | 0.33                        | 0.50                      |   |
|                  |                | Band 7      | 0.85                    | 0.93                        | <b>1.12</b>               |   |
|                  |                | Band 41     | 0.28                    | <b>1.12</b>                 | <b>1.12</b>               |   |
| DTS              | WLAN           | 2.4GHz WLAN | <b>0.91</b>             | 0.15                        | 0.15                      | 1.31  |
| NII              |                | 5GHz WLAN   | 0.10                    | <0.10                       | 0.11                      | 1.23  |
| DSS              | 2.4GHz Band    | Bluetooth   |                         | <0.10                       |                           | 1.16  |
| Date of Testing: |                |             | 2016/11/04 ~ 2016/11/05 |                             |                           |   |

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications



## 2. Administration Data

| Testing Site       |  |
|--------------------|--|
| Test Site          | SPORTON INTERNATIONAL (KUNSHAN) INC.   |
| Test Site Location | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.<br>TEL: +86-0512-5790-0158<br>FAX: +86-0512-5790-0958 |

| Applicant    |   |
|--------------|---|
| Company Name | Motorola Mobility LLC                               |
| Address      | 222 W, Merchandise Mart Plaza, Chicago IL 60654 USA |

| Manufacturer |   |
|--------------|---|
| Company Name | Motorola Mobility LLC                               |
| Address      | 222 W, Merchandise Mart Plaza, Chicago IL 60654 USA |

## 3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01



## 4. Equipment Under Test (EUT) Information

### 4.1 General Information

| Product Feature & Specification  |   |
|--|---|
| Equipment Name   | Mobile Cellular Phone   |
| Brand Name   | Motorola  |
| Model Name   | 9840, 9841  |
| FCC ID   | IHDT56VE4   |
| IMEI Code  | 351859080008554/351859080008562   |
| Wireless Technology and Frequency Range  | GSM850: 824.2 MHz ~ 848.8 MHz<br>GSM1900: 1850.2 MHz ~ 1909.8 MHz<br>WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz<br>WCDMA Band V: 826.4 MHz ~ 846.6 MHz<br>LTE Band 5: 824 MHz ~ 849 MHz<br>LTE Band 7: 2500 MHz ~ 2570 MHz<br>LTE Band 38: 2570 MHz ~ 2620 MHz<br>LTE Band 41: 2557.5 MHz ~ 2652.5 MHz<br>WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz<br>WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz<br>WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz<br>WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz<br>WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz |
| Mode   | <ul style="list-style-type: none"> <li>· GSM/GPRS/EGPRS</li> <li>· RMC/AMR 12.2Kbps</li> <li>· HSDPA</li> <li>· HSUPA</li> <li>· DC-HSDPA</li> <li>· HSPA+(16QAM uplink is not supported)</li> <li>· LTE: QPSK, 16QAM</li> <li>· 802.11b/g/n HT20</li> <li>· 802.11a /n HT20/HT40</li> <li>· Bluetooth v3.0 + EDR, Bluetooth v4.0 LE, Bluetooth v4.2 LE</li> </ul>  |
| HW Version   | DVT2  |
| SW Version   | NPN25.93_1146   |
| GSM / (E)GPRS Transfer mode  | Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.  |
| EUT Stage  | Identical Prototype   |
| <b>Remark:</b> <ol style="list-style-type: none"> <li>1. 802.11n-HT40 is not supported in 2.4GHz WLAN.</li> <li>2. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.</li> <li>3. This device 2.4GHz WLAN/5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only).</li> <li>4. This device does not support DTM operation.</li> <li>5. This device supports GRPS/EGRPS mode up to multi-slot class 12.</li> <li>6. When the phone is in talking mode, receiver worked, all WWAN power are full power.</li> <li>7. The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device. when front or back body worn condition is detected, GSM1900, WCDMA band 2 ,LTE Band 7 reduced power will be active. (P-sensor can't work at detecting presence of the user's body at the four edges of the device.)</li> <li>8. When WLAN hotspot worked, WWAN GSM1900, WCDMA band 2 ,LTE Band 7 reduced power will be active.</li> <li>9. This device hotspot reduced power and P-sensor reduced power level are the same. So only show one reduced power level for hotspot reduced power and P-sensor reduced power for this application.</li> <li>10. There are two different types of EUT. They are single SIM card mobile (9841) and dual SIM card mobile(9840). It is special to declare. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual Standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active). After pre-scan dual SIM card mobile and single card mobile, they have no effect on SAR distribution. So chose dual SIM card mobile to do SAR testing for this application.</li> </ol> |   |

#### 4.2 Specification of Accessory

| Specification of Accessory |                  |   |            |   |
|----------------------------|------------------|---|------------|---|
| AC Adapter                 | Brand Name       | Motorola(Salom)   | Model Name | SSW-2680US/SSW-2680UK/<br>SSW-2680EU/SSW-2680JP/<br>SSW-2680TW/SSW-2680AU |
|                            | Power Rating     | I/P: 100-240 Vac, 500mA, O/P: 5 Vdc,1600mA or 9Vdc,1600mA or 12Vdc,1200mA |            |   |
| Battery                    | Brand Name       | motorola(AmpereX)   | Model Name | HG40  |
|                            | Power Rating     | 3.8Vdc,2810/3000mAh<br>(Min/Typ)  | Type       | Li-ion  |
| USB Cable                  | Brand Name       | Motorola  | Model Name | SKN6461A  |
|                            | Signal Line Type | 1.0 meter, non-shielded cable, without ferrite core                       |            |   |
| Earphone                   | Brand Name       | Motorola<br>(Jiangxi Lianchuang)  | Model Name | MEMD1532B080008   |
|                            | Signal Line Type | 1.2 meter, non-shielded cable, without ferrite core                       |            |   |



**4.3 General LTE SAR Test and Reporting Considerations**

| Summarized necessary items addressed in KDB 941225 D05 v02r05 |   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
|---|---|------------|---|--------|--------|--------|----------|--|----------|---------|---------|-------|--------|--------|--------|------|-----|-----|-----|------|------|------|-----|--------|-----|-----|-----|------|------|------|-----|--------|-----|-----|-----|------|------|------|-----|
| FCC ID  | IHDT56VE4   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| Equipment Name  | Mobile Cellular Phone   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| Operating Frequency Range of each LTE transmission band       | LTE Band 5: 824 MHz ~ 849 MHz<br>LTE Band 7: 2500 MHz ~ 2570 MHz<br>LTE Band 38: 2570 MHz ~ 2620 MHz<br>LTE Band 41: 2557.5 MHz ~ 2652.5 MHz  |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| Channel Bandwidth   | LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz<br>LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz<br>LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz<br>LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz  |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| uplink modulations used                                       | QPSK, and 16QAM   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| LTE Voice / Data requirements                                 | Voice and Data  |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| LTE MPR permanently built-in by design                        | <p style="text-align: center;"><b>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 2</td> </tr> </tbody> </table> | Modulation | Channel bandwidth / Transmission bandwidth (RB) |        |        |        |          |  | MPR (dB) | 1.4 MHz | 3.0 MHz | 5 MHz | 10 MHz | 15 MHz | 20 MHz | QPSK | > 5 | > 4 | > 8 | > 12 | > 16 | > 18 | ≤ 1 | 16 QAM | ≤ 5 | ≤ 4 | ≤ 8 | ≤ 12 | ≤ 16 | ≤ 18 | ≤ 1 | 16 QAM | > 5 | > 4 | > 8 | > 12 | > 16 | > 18 | ≤ 2 |
| Modulation  | Channel bandwidth / Transmission bandwidth (RB)   |            |   |        |        |        | MPR (dB) |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
|   | 1.4 MHz   | 3.0 MHz    | 5 MHz   | 10 MHz | 15 MHz | 20 MHz |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| QPSK  | > 5   | > 4        | > 8   | > 12   | > 16   | > 18   | ≤ 1      |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| 16 QAM  | ≤ 5   | ≤ 4        | ≤ 8   | ≤ 12   | ≤ 16   | ≤ 18   | ≤ 1      |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| 16 QAM  | > 5   | > 4        | > 8   | > 12   | > 16   | > 18   | ≤ 2      |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| LTE A-MPR   | In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| Spectrum plots for RB configuration                           | A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.  |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| Power reduction applied to satisfy SAR compliance             | Yes, when operating in hotspot mode and P-sensor, WWAN GSM1900, WCDMA band 2, LTE band 7 power reduction applied to satisfy SAR compliance.   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| LTE Release Version   | R10, Cat 6  |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| CA Support  | Yes   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| LTE Carrier Aggregation Combinations                          | Inter-Band and Intra-Band possible combinations as below page and the detail power verification please referred to page46.  |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |
| LTE Carrier Aggregation Additional Information                | This device does not support full CA features on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink only. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. Due to carrier capability, only the combinations listed above are supported. The following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.   |            |   |        |        |        |          |  |          |         |         |       |        |        |        |      |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |        |     |     |     |      |      |      |     |





| Transmission (H, M, L) channel numbers and frequencies in each LTE band |                   |             |                  |             |                  |             |                  |             |
|---|-------------------|-------------|------------------|-------------|------------------|-------------|------------------|-------------|
| LTE Band 5  |                   |             |                  |             |                  |             |                  |             |
|   | Bandwidth 1.4 MHz |             | Bandwidth 3 MHz  |             | Bandwidth 5 MHz  |             | Bandwidth 10 MHz |             |
|   | Ch. #             | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) |
| L   | 20407             | 824.7       | 20415            | 825.5       | 20425            | 826.5       | 20450            | 829         |
| M   | 20525             | 836.5       | 20525            | 836.5       | 20525            | 836.5       | 20525            | 836.5       |
| H   | 20643             | 848.3       | 20635            | 847.5       | 20625            | 846.5       | 20600            | 844         |
| LTE Band 7  |                   |             |                  |             |                  |             |                  |             |
|   | Bandwidth 5 MHz   |             | Bandwidth 10 MHz |             | Bandwidth 15 MHz |             | Bandwidth 20 MHz |             |
|   | Ch. #             | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) |
| L   | 20775             | 2502.5      | 20800            | 2505        | 20825            | 2507.5      | 20850            | 2510        |
| M   | 21100             | 2535        | 21100            | 2535        | 21100            | 2535        | 21100            | 2535        |
| H   | 21425             | 2567.5      | 21400            | 2565        | 21375            | 2562.5      | 21350            | 2560        |
| LTE Band 38   |                   |             |                  |             |                  |             |                  |             |
|   | Bandwidth 5 MHz   |             | Bandwidth 10 MHz |             | Bandwidth 15 MHz |             | Bandwidth 20 MHz |             |
|   | Ch. #             | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) |
| L   | 37775             | 2572.5      | 37800            | 2575        | 37825            | 2577.5      | 37850            | 2580        |
| M   | 38000             | 2595        | 38000            | 2595        | 38000            | 2595        | 38000            | 2595        |
| H   | 38225             | 2617.5      | 38200            | 2615        | 38175            | 2612.5      | 38150            | 2610        |
| LTE Band 41   |                   |             |                  |             |                  |             |                  |             |
|   | Bandwidth 5 MHz   |             | Bandwidth 10 MHz |             | Bandwidth 15 MHz |             | Bandwidth 20 MHz |             |
|   | Ch. #             | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) | Ch. #            | Freq. (MHz) |
| L   | 40265             | 2557.5      | 40290            | 2560        | 40315            | 2562.5      | 40340            | 2565        |
| L   | 40585             | 2589.5      | 40590            | 2590        | 40595            | 2590.5      | 40600            | 2591        |
| M   | 40585             | 2589.5      | 40590            | 2590        | 40595            | 2590.5      | 40600            | 2591        |
| H   | 40905             | 2621.5      | 40890            | 2620        | 40885            | 2619.5      | 40870            | 2618        |
| H   | 41215             | 2652.5      | 41190            | 2650        | 41165            | 2647.5      | 41140            | 2645        |



| LTE Carrier Aggregation Combinations |             |             |             |
|--------------------------------------|-------------|-------------|-------------|
| Inter-Band Combinations              |             |             |             |
| (PCC)<br>B5                          | (SCC)<br>B7 | (PCC)<br>B7 | (SCC)<br>B5 |
| 10M + 20M                            |             | 20M + 10M   |             |
| 10M + 15M                            |             | 20M + 5M    |             |
| 10M + 10M                            |             | 20M + 3M    |             |
| 5M + 20M                             |             | 20M + 1.4M  |             |
| 5M + 15M                             |             | 15M + 10M   |             |
| 5M + 10M                             |             | 15M + 5M    |             |
| 3M + 20M                             |             | 15M + 3M    |             |
| 3M + 15M                             |             | 15M + 1.4M  |             |
| 3M + 10M                             |             | 10M + 10M   |             |
| 1.4M + 20M                           |             | 10M + 5M    |             |
| 1.4M + 15M                           |             | 10M + 3M    |             |
| 1.4M + 10M                           |             | 10M + 1.4M  |             |

| LTE Carrier Aggregation Combinations  |                |
|---------------------------------------|----------------|
| Intra-Band Combinations<br>LTE Band 7 |                |
| Contiguous                            | Non-Contiguous |
| 20M+20M                               | 20M+20M        |
| 20M+15M                               | 15M+20M        |
| 20M+10M                               | 15M+15M        |
| 15M+20M                               | 10M+15M        |
| 15M+15M                               | 10M+10M        |
| 10M+20M                               | 5M+15M         |
|                                       | 20M+15M        |
|                                       | 15M+10M        |
|                                       | 15M+5M         |



**4.4 Re-use of Measured Data**

**4.4.1 Introduction Section**

This application re-uses data collected on a similar device. The subject device of this application (Model: 9840, 9841, FCC ID: IHDT56VE4) is electrically identical to the reference device (Model: 9836, FCC ID: IHDT56VE1) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 178919 D01.

**4.4.2 Difference Section**

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration “PED” file.

For WWAN antenna 1 ,adjusted antenna match, so GSM850/1900/WCDMA Band II/V/ LTE band 5 full SAR test.

For WWAN antenna 2 is the same as the reference device (Model: 9836, FCC ID: IHDT56VE1), so LTE Band 7 only do spot check. For LTE Band 41 frequency band changed, so LTE Band 41(LTE Band 38) full SAR test.

The re-used RF data includes the following bands provided in Appendix E (Sporton RF Report No. FA601212 for the reference device Model: 9836, FCC ID: IHDT56VE1):

- LTE Band 7
- 2.4G/5GHz WLAN
- Bluetooth

Spot check for WWAN Band 7 and WLAN are performed for ensure that SAR measurement for both device are the same. So, the original SAR value can represent this application.

**4.4.3 Spot Check Verification Data Section**

| Band        | BW (MHz) | Modulation | RB Size | RB offset | Mode          | Test Position | Gap (mm) | Power Reduction | Ch.   | Freq. (MHz) | Original Model (FCC ID : IHDT56VE1 ) |                     |                        |                        | Spot Check Mode (FCC ID : IHDT56VE4 ) |                     |                        |                        | Deviation |
|-------------|----------|------------|---------|-----------|---------------|---------------|----------|-----------------|-------|-------------|--------------------------------------|---------------------|------------------------|------------------------|---------------------------------------|---------------------|------------------------|------------------------|-----------|
|             |          |            |         |           |               |               |          |                 |       |             | Average Power (dBm)                  | Tune-Up Limit (dBm) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) | Average Power (dBm)                   | Tune-Up Limit (dBm) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |           |
| WLAN 2.4GHz | -        | -          | -       | -         | 802.11b 1Mbps | Left Cheek    | -        | OFF             | 1     | 2412        | 16.39                                | 16.50               | 0.869                  | 0.914                  | 16.29                                 | 16.5                | 0.723                  | 0.778                  | -14.88%   |
| WLAN 5.8GHz | -        | -          | -       | -         | 802.11a 6Mbps | Left Cheek    | -        | OFF             | 165   | 5825        | 14.64                                | 16                  | 0.065                  | 0.103                  | 15.37                                 | 16                  | 0.073                  | 0.098                  | -4.85%    |
| LTE Band 7  | 20M      | QPSK       | 1RB     | 49Offset  | -             | Bottom Side   | 10       | ON              | 20850 | 2510        | 21.97                                | 22.50               | 0.987                  | 1.115                  | 21.45                                 | 22.50               | 0.892                  | 1.136                  | 1.88%     |
| WLAN 5.2GHz | -        | -          | -       | -         | 802.11a 6Mbps | Back          | 10       | OFF             | 40    | 5200        | 13.78                                | 15                  | 0.072                  | 0.110                  | 14.92                                 | 15                  | 0.089                  | 0.105                  | -4.55%    |
| WLAN 5.3GHz | -        | -          | -       | -         | 802.11a 6Mbps | Back          | 10       | OFF             | 56    | 5280        | 13.8                                 | 15                  | 0.051                  | 0.078                  | 15.03                                 | 15                  | 0.059                  | 0.068                  | -12.82%   |
| WLAN 5.5GHz | -        | -          | -       | -         | 802.11a 6Mbps | Back          | 10       | OFF             | 100   | 5500        | 14.92                                | 16.00               | 0.036                  | 0.053                  | 15.99                                 | 16                  | 0.041                  | 0.048                  | -9.43%    |
| Bluetooth   | -        | -          | -       | -         | 1Mbps         | Front         | 10       | OFF             | 39    | 2441        | 11.12                                | 11.5                | 0.028                  | 0.033                  | 11.25                                 | 11.5                | 0.030                  | 0.034                  | 3.03%     |

**Note:** In the table above, all the deviation of SAR test results are compliant with uncertainty budget.



**4.4.4 Reference detail Section**

| Equipment Class   | Reference FCC ID | Folder Test/RF Exposure | Report Title/Section    |
|-------------------|------------------|-------------------------|-------------------------|
| PCE               | IHDT56VE1        | RF Exposure(FA6O1212)   | All sections applicable |
| DSS               | IHDT56VE1        | RF Exposure(FA6O1212)   | All sections applicable |
| DTS (BLE)         | IHDT56VE1        | RF Exposure(FA6O1212)   | All sections applicable |
| DTS (WLAN 2.4GHz) | IHDT56VE1        | RF Exposure(FA6O1212)   | All sections applicable |
| NIII (WLAN 5GHz)  | IHDT56VE1        | RF Exposure(FA6O1212)   | All sections applicable |

## 5. RF Exposure Limits

### 5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.4        | 8.0          | 20.0                           |

**Limits for General Population/Uncontrolled Exposure (W/kg)**

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.08       | 1.6          | 4.0                            |

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## **6. Specific Absorption Rate (SAR)**

### **6.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **6.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

## 7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

**7.1 E-Field Probe**

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

**<EX3DV4 Probe>**

|                      |   |
|----------------------|---|
| <b>Construction</b>  | Symmetric design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| <b>Frequency</b>     | 10 MHz – >6 GHz<br>Linearity: ±0.2 dB (30 MHz – 6 GHz)  |
| <b>Directivity</b>   | ±0.3 dB in TSL (rotation around probe axis)<br>±0.5 dB in TSL (rotation normal to probe axis)   |
| <b>Dynamic Range</b> | 10 µW/g – >100 mW/g<br>Linearity: ±0.2 dB (noise: typically <1 µW/g)  |
| <b>Dimensions</b>    | Overall length: 337 mm (tip: 20 mm)<br>Tip diameter: 2.5 mm (body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                      |



**7.2 Data Acquisition Electronics (DAE)**

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



**Fig 5.1 Photo of DAE**



**7.3 Phantom**

**<SAM Twin Phantom>**

|                          |   |
|--------------------------|---|
| <b>Shell Thickness</b>   | 2 ± 0.2 mm;<br>Center ear point: 6 ± 0.2 mm             |
| <b>Filling Volume</b>    | Approx. 25 liters                                       |
| <b>Dimensions</b>        | Length: 1000 mm; Width: 500 mm; Height: adjustable feet |
| <b>Measurement Areas</b> | Left Hand, Right Hand, Flat Phantom                     |



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

**<ELI Phantom>**

|                        |  |
|------------------------|--|
| <b>Shell Thickness</b> | 2 ± 0.2 mm (sagging: <1%)                        |
| <b>Filling Volume</b>  | Approx. 30 liters                                |
| <b>Dimensions</b>      | Major ellipse axis: 600 mm<br>Minor axis: 400 mm |



The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

### **7.4 Device Holder**

#### **<Mounting Device for Hand-Held Transmitter>**

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

#### **<Mounting Device for Laptops and other Body-Worn Transmitters>**

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

## **8. Measurement Procedures**

The measurement procedures are as follows:

### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### **8.1 Spatial Peak SAR Evaluation**

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

**8.2 Power Reference Measurement**

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

**8.3 Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

|  | ≤ 3 GHz   | > 3 GHz  |
|--|---|--|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | 5 ± 1 mm  | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location              | 30° ± 1°  | 20° ± 1°   |
| Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$                            | ≤ 2 GHz: ≤ 15 mm<br>2 – 3 GHz: ≤ 12 mm  | 3 – 4 GHz: ≤ 12 mm<br>4 – 6 GHz: ≤ 10 mm           |
|  | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |  |

### 8.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

|  |                                    | ≤ 3 GHz  | > 3 GHz   |  |
|--|------------------------------------|--|---|--|
| Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$   |                                    | $\leq 2$ GHz: $\leq 8$ mm<br>2 – 3 GHz: $\leq 5$ mm*                                 | 3 – 4 GHz: $\leq 5$ mm*<br>4 – 6 GHz: $\leq 4$ mm*                            |  |
| Maximum zoom scan spatial resolution, normal to phantom surface  | uniform grid: $\Delta z_{Zoom}(n)$ | $\leq 5$ mm  | 3 – 4 GHz: $\leq 4$ mm<br>4 – 5 GHz: $\leq 3$ mm<br>5 – 6 GHz: $\leq 2$ mm    |  |
|  | graded grid                        | $\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $\leq 4$ mm   | 3 – 4 GHz: $\leq 3$ mm<br>4 – 5 GHz: $\leq 2.5$ mm<br>5 – 6 GHz: $\leq 2$ mm |
|  |                                    | $\Delta z_{Zoom}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$   |  |
| Minimum zoom scan volume   | x, y, z                            | $\geq 30$ mm   | 3 – 4 GHz: $\geq 28$ mm<br>4 – 5 GHz: $\geq 25$ mm<br>5 – 6 GHz: $\geq 22$ mm |  |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.<br>* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                    |  |   |  |

### 8.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



**9. Test Equipment List**

| Manufacturer  | Name of Equipment               | Type/Model    | Serial Number | Calibration |            |
|---------------|---------------------------------|---------------|---------------|-------------|------------|
|               |                                 |               |               | Last Cal.   | Due Date   |
| SPEAG         | 835MHz System Validation Kit    | D835V2        | 4d091         | 2015/11/24  | 2016/11/23 |
| SPEAG         | 1900MHz System Validation Kit   | D1900V2       | 5d118         | 2015/11/23  | 2016/11/22 |
| SPEAG         | 2600MHz System Validation Kit   | D2600V2       | 1061          | 2015/11/25  | 2016/11/24 |
| SPEAG         | Data Acquisition Electronics    | DAE4          | 1279          | 2016/4/4    | 2017/4/3   |
| SPEAG         | Data Acquisition Electronics    | DAE4          | 1210          | 2016/5/18   | 2017/5/17  |
| SPEAG         | Dosimetric E-Field Probe        | EX3DV4        | 3954          | 2015/11/27  | 2016/11/26 |
| SPEAG         | Dosimetric E-Field Probe        | EX3DV4        | 3857          | 2016/5/25   | 2017/5/24  |
| SPEAG         | SAM Twin Phantom                | QD 000 P40 CB | TP-1477       | NCR         | NCR        |
| SPEAG         | SAM Twin Phantom                | QD 000 P40 CB | TP-1479       | NCR         | NCR        |
| SPEAG         | SAM Twin Phantom                | QD 000 P40 CB | TP-1644       | NCR         | NCR        |
| SPEAG         | SAM Twin Phantom                | QD 000 P40 CB | TP-1542       | NCR         | NCR        |
| SPEAG         | Phone Positioner                | N/A           | N/A           | NCR         | NCR        |
| Anritsu       | Radio communication analyzer    | MT8820C       | 6201563814    | 2016/3/21   | 2017/3/20  |
| Agilent       | Wireless Communication Test Set | E5515C        | MY52102706    | 2016/4/22   | 2017/4/21  |
| Agilent       | ENA Series Network Analyzer     | E5071C        | MY46111157    | 2016/4/22   | 2017/4/21  |
| SPEAG         | DAK Kit                         | DAK3.5        | 1144          | 2015/11/24  | 2016/11/23 |
| R&S           | Signal Generator                | SMBV100A      | 258305        | 2016/1/20   | 2017/1/19  |
| Anritsu       | Power Sensor                    | MA2411B       | 0917070       | 2016/1/20   | 2017/1/19  |
| Anritsu       | Power Meter                     | ML2495A       | 1005002       | 2016/1/20   | 2017/1/19  |
| Anritsu       | Power Sensor                    | MA2411B       | 1339163       | 2016/1/20   | 2017/1/19  |
| Anritsu       | Power Meter                     | ML2495A       | 1435004       | 2016/1/20   | 2017/1/19  |
| R&S           | CBT BLUETOOTH TESTER            | CBT           | 101137        | 2016/8/9    | 2017/8/8   |
| R&S           | Spectrum Analyzer               | FSV7          | 101631        | 2016/8/8    | 2017/8/7   |
| ARRA          | Power Divider                   | A3200-2       | NA            | Note1       |            |
| Agilent       | Dual Directional Coupler        | 778D          | 50422         | Note1       |            |
| PASTERNAK     | Dual Directional Coupler        | PE2214-10     | N/A           | Note1       |            |
| AR            | Amplifier                       | 5S1G4         | 333096        | Note1       |            |
| mini-circuits | Amplifier                       | ZVE-3W-83+    | 162601250     | Note1       |            |
| MCL           | Attenuation1                    | BW-S10W5+     | N/A           | Note1       |            |
| MCL           | Attenuation2                    | BW-S10W5+     | N/A           | Note1       |            |
| MCL           | Attenuation3                    | BW-S10W5+     | N/A           | Note1       |            |

**General Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

## 10. System Verification

### 10.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.



Fig 10.1 Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR



**10.2 Tissue Verification**

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

| Frequency (MHz)  | Water (%) | Sugar (%) | Cellulose (%) | Salt (%) | Preventol (%) | DGBE (%) | Conductivity ( $\sigma$ ) | Permittivity ( $\epsilon_r$ ) |
|------------------|-----------|-----------|---------------|----------|---------------|----------|---------------------------|-------------------------------|
| <b>For Head</b>  |           |           |               |          |               |          |                           |                               |
| 835              | 40.3      | 57.9      | 0.2           | 1.4      | 0.2           | 0        | 0.90                      | 41.5                          |
| 1800, 1900, 2000 | 55.2      | 0         | 0             | 0.3      | 0             | 44.5     | 1.40                      | 40.0                          |
| 2600             | 54.8      | 0         | 0             | 0.1      | 0             | 45.1     | 1.96                      | 39.0                          |
| <b>For Body</b>  |           |           |               |          |               |          |                           |                               |
| 835              | 50.8      | 48.2      | 0             | 0.9      | 0.1           | 0        | 0.97                      | 55.2                          |
| 1800, 1900, 2000 | 70.2      | 0         | 0             | 0.4      | 0             | 29.4     | 1.52                      | 53.3                          |
| 2600             | 68.1      | 0         | 0             | 0.1      | 0             | 31.8     | 2.16                      | 52.5                          |

**<Tissue Dielectric Parameter Check Results>**


| Frequency (MHz) | Tissue Type | Liquid Temp. (°C) | Conductivity ( $\sigma$ ) | Permittivity ( $\epsilon_r$ ) | Conductivity Target ( $\sigma$ ) | Permittivity Target ( $\epsilon_r$ ) | Delta ( $\sigma$ ) (%) | Delta ( $\epsilon_r$ ) (%) | Limit (%) | Date      |
|-----------------|-------------|-------------------|---------------------------|-------------------------------|----------------------------------|--------------------------------------|------------------------|----------------------------|-----------|-----------|
| 835             | Head        | 22.3              | 0.926                     | 42.101                        | 0.90                             | 41.50                                | 2.89                   | 1.45                       | ±5        | 2016/11/4 |
| 1900            | Head        | 22.6              | 1.434                     | 40.674                        | 1.40                             | 40.00                                | 2.43                   | 1.69                       | ±5        | 2016/11/5 |
| 2600            | Head        | 22.8              | 2.028                     | 39.138                        | 1.96                             | 39.00                                | 3.47                   | 0.35                       | ±5        | 2016/11/4 |
| 835             | Body        | 22.8              | 0.991                     | 53.953                        | 0.97                             | 55.20                                | 2.16                   | -2.26                      | ±5        | 2016/11/4 |
| 1900            | Body        | 22.7              | 1.527                     | 53.985                        | 1.52                             | 53.30                                | 0.46                   | 1.29                       | ±5        | 2016/11/5 |
| 2600            | Body        | 22.5              | 2.233                     | 51.566                        | 2.16                             | 52.50                                | 3.38                   | -1.78                      | ±5        | 2016/11/5 |



**10.3 System Performance Check Results**

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

| Date      | Frequency (MHz) | Tissue Type | Input Power (mW) | Dipole S/N | Probe S/N | DAE S/N | Measured 1g SAR (W/kg) | Targeted 1g SAR (W/kg) | Normalized 1g SAR (W/kg) | Deviation (%) |
|-----------|-----------------|-------------|------------------|------------|-----------|---------|------------------------|------------------------|--------------------------|---------------|
| 2016/11/4 | 835             | Head        | 250              | 4d091      | 3954      | 1279    | 2.4                    | 9.14                   | 9.6                      | 5.03          |
| 2016/11/5 | 1900            | Head        | 250              | 5d118      | 3857      | 1210    | 9.91                   | 39.4                   | 39.64                    | 0.61          |
| 2016/11/4 | 2600            | Head        | 250              | 1061       | 3954      | 1279    | 13.7                   | 58.1                   | 54.8                     | -5.68         |
| 2016/11/4 | 835             | Body        | 250              | 4d091      | 3954      | 1279    | 2.34                   | 9.55                   | 9.36                     | -1.99         |
| 2016/11/5 | 1900            | Body        | 250              | 5d118      | 3857      | 1210    | 9.77                   | 40.6                   | 39.08                    | -3.74         |
| 2016/11/5 | 2600            | Body        | 250              | 1061       | 3857      | 1210    | 14                     | 54.6                   | 56                       | 2.56          |



**Fig 8.3.1 System Performance Check Setup**



**Fig 8.3.2 Setup Photo**

## 11. RF Exposure Positions

### 11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.






Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

**11.2 Definition of the cheek position**


1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width  $w_t$  of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width  $w_b$  of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.



**Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"**




**Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"**



**Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.**

**11.3 Definition of the tilt position**

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




**Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.**

### **11.4 Body Worn Accessory**

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is  $< 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.



**Fig 9.4 Body Worn Position**

### **11.5 Wireless Router**

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ( $L \times W \geq 9$  cm  $\times$  5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

## 12. Conducted RF Output Power (Unit: dBm)

### <GSM Conducted Power>

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (1Tx slots) for GSM850/GSM1900 is considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq \frac{1}{4}$  dB higher than the primary mode, SAR measurement is not required for the secondary mode
4. Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 1 Tx slot due to its highest frame-average power.

### <Full Power Mode>

| GSM850<br>TX Channel | Burst Average Power (dBm) |              |       | Tune-up<br>Limit<br>(dBm) | Frame-Average Power (dBm) |       |       | Tune-up<br>Limit<br>(dBm) |
|----------------------|---------------------------|--------------|-------|---------------------------|---------------------------|-------|-------|---------------------------|
|                      | 128                       | 189          | 251   |                           | 128                       | 189   | 251   |                           |
| Frequency (MHz)      | 824.2                     | 836.4        | 848.8 |                           | 824.2                     | 836.4 | 848.8 |                           |
| GSM 1 Tx slot        | 33.19                     | <b>33.23</b> | 33.19 | 33.50                     | 24.19                     | 24.23 | 24.19 | 24.50                     |
| GPRS 1 Tx slot       | 33.17                     | 33.21        | 33.18 | 33.50                     | 24.17                     | 24.21 | 24.18 | 24.50                     |
| GPRS 2 Tx slots      | 29.57                     | 28.98        | 28.89 | 30.00                     | 23.57                     | 22.98 | 22.89 | 24.00                     |
| GPRS 3 Tx slots      | 27.50                     | 27.44        | 27.35 | 28.00                     | 23.24                     | 23.18 | 23.09 | 23.74                     |
| GPRS 4 Tx slots      | 26.02                     | 25.36        | 25.24 | 26.50                     | 23.02                     | 22.36 | 22.24 | 23.50                     |
| EDGE 1 Tx slot       | 26.41                     | 26.37        | 26.22 | 26.50                     | 17.41                     | 17.37 | 17.22 | 17.50                     |
| EDGE 2 Tx slots      | 26.24                     | 25.84        | 25.78 | 26.50                     | 20.24                     | 19.84 | 19.78 | 20.50                     |
| EDGE 3 Tx slots      | 24.89                     | 24.80        | 24.67 | 25.50                     | 20.63                     | 20.54 | 20.41 | 21.24                     |
| EDGE 4 Tx slots      | 23.39                     | 22.74        | 22.69 | 23.50                     | 20.39                     | 19.74 | 19.69 | 20.50                     |

**Remark:** The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

| GSM1900<br>TX Channel | Burst Average Power (dBm) |       |              | Tune-up<br>Limit<br>(dBm) | Frame-Average Power (dBm) |       |        | Tune-up<br>Limit<br>(dBm) |
|-----------------------|---------------------------|-------|--------------|---------------------------|---------------------------|-------|--------|---------------------------|
|                       | 512                       | 661   | 810          |                           | 512                       | 661   | 810    |                           |
| Frequency (MHz)       | 1850.2                    | 1880  | 1909.8       |                           | 1850.2                    | 1880  | 1909.8 |                           |
| GSM 1 Tx slot         | 29.51                     | 30.09 | <b>30.19</b> | 30.50                     | 20.51                     | 21.09 | 21.19  | 21.50                     |
| GPRS 1 Tx slot        | 29.48                     | 30.05 | 30.06        | 30.50                     | 20.48                     | 21.05 | 21.06  | 21.50                     |
| GPRS 2 Tx slots       | 26.49                     | 26.53 | 26.49        | 27.00                     | 20.49                     | 20.53 | 20.49  | 21.00                     |
| GPRS 3 Tx slots       | 24.71                     | 25.12 | 24.67        | 25.50                     | 20.45                     | 20.86 | 20.41  | 21.24                     |
| GPRS 4 Tx slots       | 23.23                     | 23.05 | 22.88        | 23.50                     | 20.23                     | 20.05 | 19.88  | 20.50                     |
| EDGE 1 Tx slot        | 25.62                     | 26.02 | 25.99        | 26.50                     | 16.62                     | 17.02 | 16.99  | 17.50                     |
| EDGE 2 Tx slots       | 25.48                     | 25.40 | 25.27        | 26.00                     | 19.48                     | 19.40 | 19.27  | 20.00                     |
| EDGE 3 Tx slots       | 24.08                     | 24.43 | 24.26        | 25.00                     | 19.82                     | 20.17 | 20.00  | 20.74                     |
| EDGE 4 Tx slots       | 22.72                     | 22.41 | 22.12        | 23.00                     | 19.72                     | 19.41 | 19.12  | 20.00                     |

**Remark:** The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB



<Hotspot Reduced Power Mode>

| GSM1900<br>TX Channel | Burst Average Power (dBm) |       |        | Tune-up<br>Limit<br>(dBm) | Frame-Average Power (dBm) |       |        | Tune-up<br>Limit<br>(dBm) |
|-----------------------|---------------------------|-------|--------|---------------------------|---------------------------|-------|--------|---------------------------|
|                       | 512                       | 661   | 810    |                           | 512                       | 661   | 810    |                           |
| Frequency (MHz)       | 1850.2                    | 1880  | 1909.8 |                           | 1850.2                    | 1880  | 1909.8 |                           |
| GSM 1 Tx slot         | 28.16                     | 28.08 | 28.37  | 28.50                     | 19.16                     | 19.08 | 19.38  | 19.50                     |
| GPRS 1 Tx slot        | 28.17                     | 28.10 | 28.38  | 28.50                     | 19.17                     | 19.10 | 19.37  | 19.50                     |
| GPRS 2 Tx slots       | 24.27                     | 24.14 | 24.08  | 25.00                     | 18.27                     | 18.14 | 18.08  | 19.00                     |
| GPRS 3 Tx slots       | 22.70                     | 22.62 | 22.62  | 23.00                     | 18.44                     | 18.36 | 18.36  | 18.74                     |
| GPRS 4 Tx slots       | 21.34                     | 21.30 | 21.26  | 22.00                     | 18.34                     | 18.30 | 18.26  | 19.00                     |
| EDGE 1 Tx slot        | 25.17                     | 25.15 | 25.26  | 26.00                     | 16.17                     | 16.15 | 16.26  | 17.00                     |
| EDGE 2 Tx slots       | 22.70                     | 22.62 | 22.69  | 23.00                     | 16.70                     | 16.62 | 16.69  | 17.00                     |
| EDGE 3 Tx slots       | 21.59                     | 21.53 | 21.59  | 22.00                     | 17.33                     | 17.27 | 17.33  | 17.74                     |
| EDGE 4 Tx slots       | 20.97                     | 20.94 | 20.97  | 21.50                     | 17.97                     | 17.94 | 17.97  | 18.50                     |

**Remark:** The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

- Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB
- Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB
- Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB
- Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

**<WCDMA Conducted Power>**

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

**HSDPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each
  - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
  - iii. Set RMC 12.2Kbps + HSDPA mode.
  - iv. Set Cell Power = -86 dBm
  - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - vi. Select HSDPA Uplink Parameters
  - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
  - viii. Set Ack-Nack Repetition Factor to 3
  - ix. Set CQI Feedback Cycle (k) to 4 ms
  - x. Set CQI Repetition Factor to 2
  - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

**Table C.10.1.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH**

| Sub-test | $\beta_c$         | $\beta_d$         | $\beta_d$<br>(SF) | $\beta_c/\beta_d$ | $\beta_{HS}$<br>(Note 1,<br>Note 2) | CM (dB)<br>(Note 3) | MPR (dB)<br>(Note 3) |
|----------|-------------------|-------------------|-------------------|-------------------|-------------------------------------|---------------------|----------------------|
| 1        | 2/15              | 15/15             | 64                | 2/15              | 4/15                                | 0.0                 | 0.0                  |
| 2        | 12/15<br>(Note 4) | 15/15<br>(Note 4) | 64                | 12/15<br>(Note 4) | 24/15                               | 1.0                 | 0.0                  |
| 3        | 15/15             | 8/15              | 64                | 15/8              | 30/15                               | 1.5                 | 0.5                  |
| 4        | 15/15             | 4/15              | 64                | 15/4              | 30/15                               | 1.5                 | 0.5                  |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 24/15$  with  $\beta_{HS} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**Setup Configuration**



**HSUPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting \* :
  - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - ii. Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - iii. Set Cell Power = -86 dBm
  - iv. Set Channel Type = 12.2k + HSPA
  - v. Set UE Target Power
  - vi. Power Ctrl Mode= Alternating bits
  - vii. Set and observe the E-TFCl
  - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

**Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH**

| Sub-test | $\beta_c$      | $\beta_d$      | $\beta_d$ (SF) | $\beta_c/\beta_d$ | $\beta_{HS}$ (Note 1) | $\beta_{ec}$ | $\beta_{ed}$ (Note 5) (Note 6)               | $\beta_{ed}$ (SF) | $\beta_{ed}$ (Codes) | CM (dB) (Note 2) | MPR (dB) (Note 2) | AG Index (Note 6) | E-TFCl |
|----------|----------------|----------------|----------------|-------------------|-----------------------|--------------|--|-------------------|----------------------|------------------|-------------------|-------------------|--------|
| 1        | 11/15 (Note 3) | 15/15 (Note 3) | 64             | 11/15 (Note 3)    | 22/15                 | 209/25       | 1309/225                                     | 4                 | 1                    | 1.0              | 0.0               | 20                | 75     |
| 2        | 6/15           | 15/15          | 64             | 6/15              | 12/15                 | 12/15        | 94/75  | 4                 | 1                    | 3.0              | 2.0               | 12                | 67     |
| 3        | 15/15          | 9/15           | 64             | 15/9              | 30/15                 | 30/15        | $\beta_{ed1}: 47/15$<br>$\beta_{ed2}: 47/15$ | 4<br>4            | 2                    | 2.0              | 1.0               | 15                | 92     |
| 4        | 2/15           | 15/15          | 64             | 2/15              | 4/15                  | 2/15         | 56/75  | 4                 | 1                    | 3.0              | 2.0               | 17                | 71     |
| 5        | 15/15 (Note 4) | 15/15 (Note 4) | 64             | 15/15 (Note 4)    | 30/15                 | 24/15        | 134/15                                       | 4                 | 1                    | 1.0              | 0.0               | 21                | 81     |

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6:  $\beta_{ed}$  can not be set directly, it is set by Absolute Grant Value.

**Setup Configuration**

**DC-HSDPA 3GPP release 8 Setup Configuration:**


- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set RMC 12.2Kbps + HSDPA mode.
  - ii. Set Cell Power = -25 dBm
  - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
  - iv. Select HSDPA Uplink Parameters
  - v. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
    - a). Subtest 1:  $\beta_c/\beta_d=2/15$
    - b). Subtest 2:  $\beta_c/\beta_d=12/15$
    - c). Subtest 3:  $\beta_c/\beta_d=15/8$
    - d). Subtest 4:  $\beta_c/\beta_d=15/4$
  - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
  - vii. Set Ack-Nack Repetition Factor to 3
  - viii. Set CQI Feedback Cycle (k) to 4 ms
  - ix. Set CQI Repetition Factor to 2
  - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

**C.8.1.12 Fixed Reference Channel Definition H-Set 12**

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

| Parameter  | Unit      | Value |
|--|-----------|-------|
| Nominal Avg. Inf. Bit Rate   | kbps      | 60    |
| Inter-TTI Distance   | TTI's     | 1     |
| Number of HARQ Processes   | Processes | 6     |
| Information Bit Payload ( $N_{INF}$ )  | Bits      | 120   |
| Number Code Blocks   | Blocks    | 1     |
| Binary Channel Bits Per TTI  | Bits      | 960   |
| Total Available SML's in UE  | SML's     | 19200 |
| Number of SML's per HARQ Proc.   | SML's     | 3200  |
| Coding Rate  |           | 0.15  |
| Number of Physical Channel Codes   | Codes     | 1     |
| Modulation   |           | QPSK  |
| Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.<br>Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used. |           |       |



**Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)**

**Setup Configuration**



**<WCDMA Conducted Power>**

**General Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

**<Full Power Mode>**

| Band            |                    | WCDMA Band II |              |        | Tune-up Limit (dBm) | WCDMA Band V |       |       | Tune-up Limit (dBm) |
|-----------------|--------------------|---------------|--------------|--------|---------------------|--------------|-------|-------|---------------------|
| TX Channel      |                    | 9262          | 9400         | 9538   |                     | 4132         | 4182  | 4233  |                     |
| Rx Channel      |                    | 9662          | 9800         | 9938   |                     | 4357         | 4407  | 4458  |                     |
| Frequency (MHz) |                    | 1852.4        | 1880         | 1907.6 |                     | 826.4        | 836.4 | 846.6 |                     |
| 3GPP Rel 99     | AMR 12.2Kbps       | 22.46         | 22.96        | 22.93  | 24.00               | 22.93        | 22.81 | 22.60 | 24.00               |
| 3GPP Rel 99     | RMC 12.2Kbps       | 22.50         | <b>22.97</b> | 22.94  | 24.00               | <b>22.94</b> | 22.83 | 22.61 | 24.00               |
| 3GPP Rel 6      | HSDPA Subtest-1    | 21.66         | 22.23        | 22.20  | 22.50               | 22.29        | 22.15 | 21.92 | 22.50               |
| 3GPP Rel 6      | HSDPA Subtest-2    | 21.79         | 22.33        | 22.40  | 22.50               | 22.39        | 22.36 | 22.06 | 22.50               |
| 3GPP Rel 6      | HSDPA Subtest-3    | 21.31         | 21.97        | 21.95  | 22.00               | 21.93        | 21.89 | 21.59 | 22.00               |
| 3GPP Rel 6      | HSDPA Subtest-4    | 21.30         | 21.87        | 21.95  | 22.00               | 21.94        | 21.80 | 21.60 | 22.00               |
| 3GPP Rel 8      | DC-HSDPA Subtest-1 | 21.65         | 22.22        | 22.18  | 22.50               | 22.25        | 21.13 | 21.90 | 22.50               |
| 3GPP Rel 8      | DC-HSDPA Subtest-2 | 21.83         | 22.30        | 22.36  | 22.50               | 22.24        | 22.23 | 21.48 | 22.50               |
| 3GPP Rel 8      | DC-HSDPA Subtest-3 | 21.28         | 21.95        | 21.93  | 22.00               | 21.92        | 21.78 | 21.59 | 22.00               |
| 3GPP Rel 8      | DC-HSDPA Subtest-4 | 21.25         | 21.91        | 21.91  | 22.00               | 21.78        | 21.65 | 21.63 | 22.00               |
| 3GPP Rel 6      | HSUPA Subtest-1    | 21.72         | 22.38        | 22.26  | 22.50               | 22.37        | 22.20 | 22.00 | 22.50               |
| 3GPP Rel 6      | HSUPA Subtest-2    | 19.83         | 20.41        | 20.32  | 20.50               | 20.32        | 20.31 | 19.99 | 20.50               |
| 3GPP Rel 6      | HSUPA Subtest-3    | 20.88         | 21.38        | 21.29  | 21.50               | 21.27        | 21.18 | 20.98 | 21.50               |
| 3GPP Rel 6      | HSUPA Subtest-4    | 19.82         | 20.48        | 20.47  | 20.50               | 20.30        | 20.27 | 20.07 | 20.50               |
| 3GPP Rel 6      | HSUPA Subtest-5    | 21.70         | 22.30        | 22.20  | 22.50               | 22.20        | 22.20 | 21.90 | 22.50               |

**<Hotspot Reduced Power Mode>**

| Band            |                    | WCDMA Band II |              |        | Tune-up Limit (dBm) |
|-----------------|--------------------|---------------|--------------|--------|---------------------|
| TX Channel      |                    | 9262          | 9400         | 9538   |                     |
| Rx Channel      |                    | 9662          | 9800         | 9938   |                     |
| Frequency (MHz) |                    | 1852.4        | 1880         | 1907.6 |                     |
| 3GPP Rel 99     | AMR 12.2Kbps       | 19.15         | 19.38        | 19.27  | 20.00               |
| 3GPP Rel 99     | RMC 12.2Kbps       | 19.16         | <b>19.40</b> | 19.29  | 20.00               |
| 3GPP Rel 6      | HSDPA Subtest-1    | 18.27         | 18.64        | 18.54  | 19.00               |
| 3GPP Rel 6      | HSDPA Subtest-2    | 18.42         | 18.73        | 18.71  | 19.00               |
| 3GPP Rel 6      | HSDPA Subtest-3    | 17.96         | 18.36        | 18.27  | 19.00               |
| 3GPP Rel 6      | HSDPA Subtest-4    | 17.91         | 18.28        | 18.29  | 19.00               |
| 3GPP Rel 8      | DC-HSDPA Subtest-1 | 18.26         | 18.61        | 18.48  | 19.00               |
| 3GPP Rel 8      | DC-HSDPA Subtest-2 | 18.31         | 18.71        | 18.61  | 19.00               |
| 3GPP Rel 8      | DC-HSDPA Subtest-3 | 17.88         | 18.25        | 18.18  | 19.00               |
| 3GPP Rel 8      | DC-HSDPA Subtest-4 | 17.73         | 18.28        | 18.23  | 19.00               |
| 3GPP Rel 6      | HSUPA Subtest-1    | 18.37         | 18.77        | 18.58  | 19.00               |
| 3GPP Rel 6      | HSUPA Subtest-2    | 16.44         | 16.82        | 16.66  | 17.00               |
| 3GPP Rel 6      | HSUPA Subtest-3    | 17.51         | 17.78        | 17.60  | 18.00               |
| 3GPP Rel 6      | HSUPA Subtest-4    | 16.47         | 16.87        | 16.79  | 17.00               |
| 3GPP Rel 6      | HSUPA Subtest-5    | 18.31         | 18.71        | 18.54  | 19.00               |

**<LTE Conducted Power>****General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B5 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 38 SAR test was covered by Band 41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
  - a. the maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion
  - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band



**<Full Power Mode>**

**<LTE Band 5>**

| BW [MHz]        | Modulation | RB Size | RB Offset | Power Low Ch. / Freq. | Power Middle Ch. / Freq. | Power High Ch. / Freq. | Tune-up limit (dBm) | MPR (dB) |
|-----------------|------------|---------|-----------|-----------------------|--------------------------|------------------------|---------------------|----------|
| Channel         |            |         |           | 20450                 | 20525                    | 20600                  |                     |          |
| Frequency (MHz) |            |         |           | 829                   | 836.5                    | 844                    |                     |          |
| 10              | QPSK       | 1       | 0         | 22.73                 | 22.63                    | 22.53                  | 24.00               | 0        |
| 10              | QPSK       | 1       | 25        | 23.21                 | 23.16                    | 23.19                  |                     |          |
| 10              | QPSK       | 1       | 49        | 22.88                 | 22.87                    | 22.35                  |                     |          |
| 10              | QPSK       | 25      | 0         | 22.18                 | 22.12                    | 22.17                  | 23.00               | 1        |
| 10              | QPSK       | 25      | 12        | 22.15                 | 22.08                    | 21.91                  |                     |          |
| 10              | QPSK       | 25      | 25        | 22.15                 | 21.93                    | 21.77                  |                     |          |
| 10              | QPSK       | 50      | 0         | 22.14                 | 22.07                    | 21.83                  | 23.00               | 1        |
| 10              | 16QAM      | 1       | 0         | 22.25                 | 21.76                    | 21.81                  |                     |          |
| 10              | 16QAM      | 1       | 25        | 21.87                 | 21.99                    | 21.82                  |                     |          |
| 10              | 16QAM      | 1       | 49        | 21.83                 | 21.63                    | 21.64                  | 22.00               | 2        |
| 10              | 16QAM      | 25      | 0         | 21.25                 | 21.16                    | 20.86                  |                     |          |
| 10              | 16QAM      | 25      | 12        | 21.38                 | 21.00                    | 20.90                  |                     |          |
| 10              | 16QAM      | 25      | 25        | 21.36                 | 20.82                    | 20.77                  | 22.00               | 2        |
| 10              | 16QAM      | 50      | 0         | 21.22                 | 21.05                    | 20.83                  |                     |          |
| Channel         |            |         |           | 20425                 | 20525                    | 20625                  |                     |          |
| Frequency (MHz) |            |         |           | 826.5                 | 836.5                    | 846.5                  |                     |          |
| 5               | QPSK       | 1       | 0         | 22.81                 | 22.56                    | 22.46                  | 24.00               | 0        |
| 5               | QPSK       | 1       | 12        | 23.04                 | 23.00                    | 23.18                  |                     |          |
| 5               | QPSK       | 1       | 24        | 22.65                 | 22.66                    | 22.30                  |                     |          |
| 5               | QPSK       | 12      | 0         | 22.05                 | 22.03                    | 21.80                  | 23.00               | 1        |
| 5               | QPSK       | 12      | 7         | 22.01                 | 22.02                    | 21.84                  |                     |          |
| 5               | QPSK       | 12      | 13        | 22.00                 | 22.07                    | 21.78                  |                     |          |
| 5               | QPSK       | 25      | 0         | 22.01                 | 22.03                    | 21.77                  | 23.00               | 1        |
| 5               | 16QAM      | 1       | 0         | 21.92                 | 21.96                    | 21.71                  |                     |          |
| 5               | 16QAM      | 1       | 12        | 22.29                 | 22.12                    | 21.76                  |                     |          |
| 5               | 16QAM      | 1       | 24        | 21.89                 | 21.84                    | 21.72                  | 22.00               | 2        |
| 5               | 16QAM      | 12      | 0         | 20.97                 | 20.90                    | 20.78                  |                     |          |
| 5               | 16QAM      | 12      | 7         | 21.11                 | 21.16                    | 20.88                  |                     |          |
| 5               | 16QAM      | 12      | 13        | 21.08                 | 21.11                    | 20.97                  | 22.00               | 2        |
| 5               | 16QAM      | 25      | 0         | 21.10                 | 20.93                    | 20.79                  |                     |          |



| Channel         |       |    |    | 20415 | 20525 | 20635 | Tune-up limit (dBm) | MPR (dB) |
|-----------------|-------|----|----|-------|-------|-------|---------------------|----------|
| Frequency (MHz) |       |    |    | 825.5 | 836.5 | 847.5 |                     |          |
| 3               | QPSK  | 1  | 0  | 22.83 | 22.98 | 22.52 | 24.00               | 0        |
| 3               | QPSK  | 1  | 8  | 22.80 | 22.92 | 22.65 |                     |          |
| 3               | QPSK  | 1  | 14 | 22.67 | 22.81 | 22.34 |                     |          |
| 3               | QPSK  | 8  | 0  | 22.01 | 22.14 | 21.87 | 23.00               | 1        |
| 3               | QPSK  | 8  | 4  | 22.06 | 22.06 | 21.79 |                     |          |
| 3               | QPSK  | 8  | 7  | 22.11 | 22.12 | 21.81 |                     |          |
| 3               | QPSK  | 15 | 0  | 22.01 | 21.99 | 21.73 | 23.00               | 1        |
| 3               | 16QAM | 1  | 0  | 22.10 | 22.06 | 21.79 |                     |          |
| 3               | 16QAM | 1  | 8  | 21.97 | 21.98 | 21.83 |                     |          |
| 3               | 16QAM | 1  | 14 | 21.85 | 22.05 | 21.69 | 22.00               | 2        |
| 3               | 16QAM | 8  | 0  | 21.26 | 21.01 | 20.75 |                     |          |
| 3               | 16QAM | 8  | 4  | 21.07 | 21.04 | 20.69 |                     |          |
| 3               | 16QAM | 8  | 7  | 21.09 | 21.08 | 20.68 | 22.00               | 2        |
| 3               | 16QAM | 15 | 0  | 21.17 | 21.06 | 20.61 |                     |          |
| Channel         |       |    |    | 20407 | 20525 | 20643 | Tune-up limit (dBm) | MPR (dB) |
| Frequency (MHz) |       |    |    | 824.7 | 836.5 | 848.3 |                     |          |
| 1.4             | QPSK  | 1  | 0  | 22.91 | 22.91 | 22.64 | 24.00               | 0        |
| 1.4             | QPSK  | 1  | 3  | 22.93 | 23.00 | 22.63 |                     |          |
| 1.4             | QPSK  | 1  | 5  | 22.71 | 22.92 | 22.55 |                     |          |
| 1.4             | QPSK  | 3  | 0  | 23.09 | 23.05 | 22.89 |                     |          |
| 1.4             | QPSK  | 3  | 1  | 23.08 | 22.88 | 22.86 |                     |          |
| 1.4             | QPSK  | 3  | 3  | 22.97 | 22.93 | 22.62 | 23.00               | 1        |
| 1.4             | QPSK  | 6  | 0  | 22.08 | 22.04 | 21.75 |                     |          |
| 1.4             | 16QAM | 1  | 0  | 21.59 | 21.49 | 21.29 | 23.00               | 1        |
| 1.4             | 16QAM | 1  | 3  | 21.76 | 21.38 | 21.23 |                     |          |
| 1.4             | 16QAM | 1  | 5  | 21.78 | 21.46 | 21.20 |                     |          |
| 1.4             | 16QAM | 3  | 0  | 22.17 | 21.67 | 22.00 |                     |          |
| 1.4             | 16QAM | 3  | 1  | 22.19 | 22.11 | 22.00 |                     |          |
| 1.4             | 16QAM | 3  | 3  | 22.26 | 22.21 | 21.93 | 22.00               | 2        |
| 1.4             | 16QAM | 6  | 0  | 20.97 | 20.92 | 20.71 |                     |          |

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. "special subframe S" contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

| Uplink-downlink configuration | Downlink-to-Uplink Switch-point periodicity | Subframe number |   |   |   |   |   |   |   |   |   |
|-------------------------------|---|-----------------|---|---|---|---|---|---|---|---|---|
|                               |   | 0               | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0                             | 5 ms  | D               | S | U | U | U | D | S | U | U | U |
| 1                             | 5 ms  | D               | S | U | U | D | D | S | U | U | D |
| 2                             | 5 ms  | D               | S | U | D | D | D | S | U | D | D |
| 3                             | 10 ms                                       | D               | S | U | U | U | D | D | D | D | D |
| 4                             | 10 ms                                       | D               | S | U | U | D | D | D | D | D | D |
| 5                             | 10 ms                                       | D               | S | U | D | D | D | D | D | D | D |
| 6                             | 5 ms  | D               | S | U | U | U | D | S | U | U | D |

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

| Special subframe configuration | Normal cyclic prefix in downlink |                                |                                  | Extended cyclic prefix in downlink |                                |                                  |
|--------------------------------|----------------------------------|--------------------------------|----------------------------------|------------------------------------|--------------------------------|----------------------------------|
|                                | DwPTS                            | UpPTS                          |                                  | DwPTS                              | UpPTS                          |                                  |
|                                |                                  | Normal cyclic prefix in uplink | Extended cyclic prefix in uplink |                                    | Normal cyclic prefix in uplink | Extended cyclic prefix in uplink |
| 0                              | $6592 \cdot T_s$                 | $2192 \cdot T_s$               | $2560 \cdot T_s$                 | $7680 \cdot T_s$                   | $2192 \cdot T_s$               | $2560 \cdot T_s$                 |
| 1                              | $19760 \cdot T_s$                |                                |                                  | $20480 \cdot T_s$                  |                                |                                  |
| 2                              | $21952 \cdot T_s$                |                                |                                  | $23040 \cdot T_s$                  |                                |                                  |
| 3                              | $24144 \cdot T_s$                |                                |                                  | $25600 \cdot T_s$                  |                                |                                  |
| 4                              | $26336 \cdot T_s$                | $4384 \cdot T_s$               | $5120 \cdot T_s$                 | $7680 \cdot T_s$                   | $4384 \cdot T_s$               | $5120 \cdot T_s$                 |
| 5                              | $6592 \cdot T_s$                 |                                |                                  | $20480 \cdot T_s$                  |                                |                                  |
| 6                              | $19760 \cdot T_s$                |                                |                                  | $23040 \cdot T_s$                  |                                |                                  |
| 7                              | $21952 \cdot T_s$                |                                |                                  | $12800 \cdot T_s$                  |                                |                                  |
| 8                              | $24144 \cdot T_s$                | -                              | -                                | -                                  | -                              | -                                |
| 9                              | $13168 \cdot T_s$                | -                              | -                                | -                                  | -                              | -                                |

| <b>Special subframe (30720·T<sub>s</sub>): Normal cyclic prefix in downlink (UpPTS)</b> |                                       |                                       |   |
|---|---------------------------------------|---------------------------------------|---|
|   | <b>Special subframe configuration</b> | <b>Normal cyclic prefix in uplink</b> | <b>Extended cyclic prefix in uplink</b> |
| <b>Uplink duty factor in one special subframe</b>                                       | <b>0~4</b>                            | 7.13%                                 | 8.33%                                   |
|   | <b>5~9</b>                            | 14.3%                                 | 16.7%                                   |

| <b>Special subframe(30720·T<sub>s</sub>): Extended cyclic prefix in downlink (UpPTS)</b> |                                       |                                       |   |
|--|---------------------------------------|---------------------------------------|---|
|  | <b>Special subframe configuration</b> | <b>Normal cyclic prefix in uplink</b> | <b>Extended cyclic prefix in uplink</b> |
| <b>Uplink duty factor in one special subframe</b>  | <b>0~3</b>                            | 7.13%                                 | 8.33%                                   |
|  | <b>4~7</b>                            | 14.3%                                 | 16.7%                                   |

The highest duty factor is resulted from:

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:  $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:  $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix  $63.3\%/62.9\% = 1.006$  is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)\* Tune-up Scaling Factor\* scaling factor for extended cyclic prefix.





**<Full Power Mode>**

**<LTE Band 38>**

| BW [MHz]        | Modulation | RB Size | RB Offset | Power Low Ch. / Freq. | Power Middle Ch. / Freq. | Power High Ch. / Freq. | Tune-up limit (dBm) | MPR (dB) |
|-----------------|------------|---------|-----------|-----------------------|--------------------------|------------------------|---------------------|----------|
| Channel         |            |         |           | 37850                 | 38000                    | 38150                  |                     |          |
| Frequency (MHz) |            |         |           | 2580                  | 2595                     | 2610                   |                     |          |
| 20              | QPSK       | 1       | 0         | 22.88                 | 22.74                    | 22.68                  | 24.00               | 0        |
| 20              | QPSK       | 1       | 49        | 22.85                 | 22.84                    | 22.72                  |                     |          |
| 20              | QPSK       | 1       | 99        | 22.74                 | 22.55                    | 22.56                  |                     |          |
| 20              | QPSK       | 50      | 0         | 22.05                 | 21.92                    | 21.87                  | 23.00               | 1        |
| 20              | QPSK       | 50      | 24        | 22.03                 | 21.82                    | 21.84                  |                     |          |
| 20              | QPSK       | 50      | 50        | 22.04                 | 21.83                    | 21.77                  |                     |          |
| 20              | QPSK       | 100     | 0         | 22.06                 | 21.84                    | 21.79                  | 23.00               | 1        |
| 20              | 16QAM      | 1       | 0         | 21.37                 | 21.21                    | 21.11                  |                     |          |
| 20              | 16QAM      | 1       | 49        | 21.73                 | 21.52                    | 21.45                  |                     |          |
| 20              | 16QAM      | 1       | 99        | 21.61                 | 21.09                    | 21.36                  | 22.00               | 2        |
| 20              | 16QAM      | 50      | 0         | 21.41                 | 20.93                    | 20.84                  |                     |          |
| 20              | 16QAM      | 50      | 24        | 21.01                 | 20.82                    | 20.82                  |                     |          |
| 20              | 16QAM      | 50      | 50        | 21.03                 | 20.85                    | 20.76                  | 22.00               | 2        |
| 20              | 16QAM      | 100     | 0         | 20.98                 | 20.84                    | 20.78                  |                     |          |
| Channel         |            |         |           | 37825                 | 38000                    | 38175                  |                     |          |
| Frequency (MHz) |            |         |           | 2577.5                | 2595                     | 2612.5                 |                     |          |
| 15              | QPSK       | 1       | 0         | 22.82                 | 22.83                    | 22.73                  | 24.00               | 0        |
| 15              | QPSK       | 1       | 37        | 23.13                 | 23.08                    | 22.91                  |                     |          |
| 15              | QPSK       | 1       | 74        | 22.64                 | 22.52                    | 22.49                  |                     |          |
| 15              | QPSK       | 36      | 0         | 22.39                 | 22.10                    | 21.86                  | 23.00               | 1        |
| 15              | QPSK       | 36      | 20        | 22.07                 | 21.79                    | 21.78                  |                     |          |
| 15              | QPSK       | 36      | 39        | 22.01                 | 21.86                    | 21.72                  |                     |          |
| 15              | QPSK       | 75      | 0         | 22.09                 | 21.86                    | 21.80                  | 23.00               | 1        |
| 15              | 16QAM      | 1       | 0         | 21.99                 | 21.47                    | 21.37                  |                     |          |
| 15              | 16QAM      | 1       | 37        | 21.88                 | 21.60                    | 21.94                  |                     |          |
| 15              | 16QAM      | 1       | 74        | 21.41                 | 21.20                    | 21.56                  | 22.00               | 2        |
| 15              | 16QAM      | 36      | 0         | 21.08                 | 21.03                    | 20.96                  |                     |          |
| 15              | 16QAM      | 36      | 20        | 21.09                 | 20.83                    | 20.78                  |                     |          |
| 15              | 16QAM      | 36      | 39        | 21.07                 | 21.12                    | 21.02                  | 22.00               | 2        |
| 15              | 16QAM      | 75      | 0         | 21.07                 | 20.93                    | 20.78                  |                     |          |



| Channel         |       |    |    | 37800  | 38000 | 38200  | Tune-up limit (dBm) | MPR (dB) |
|-----------------|-------|----|----|--------|-------|--------|---------------------|----------|
| Frequency (MHz) |       |    |    | 2575   | 2595  | 2615   |                     |          |
| 10              | QPSK  | 1  | 0  | 22.91  | 22.67 | 22.67  | 24.00               | 0        |
| 10              | QPSK  | 1  | 25 | 23.29  | 22.94 | 22.88  |                     |          |
| 10              | QPSK  | 1  | 49 | 22.93  | 22.69 | 22.59  |                     |          |
| 10              | QPSK  | 25 | 0  | 22.12  | 21.84 | 21.80  | 23.00               | 1        |
| 10              | QPSK  | 25 | 12 | 22.06  | 21.83 | 21.77  |                     |          |
| 10              | QPSK  | 25 | 25 | 22.05  | 21.81 | 21.77  |                     |          |
| 10              | QPSK  | 50 | 0  | 22.05  | 21.82 | 21.76  | 23.00               | 1        |
| 10              | 16QAM | 1  | 0  | 21.50  | 21.52 | 21.17  |                     |          |
| 10              | 16QAM | 1  | 25 | 21.79  | 21.46 | 21.44  |                     |          |
| 10              | 16QAM | 1  | 49 | 21.43  | 21.25 | 21.44  | 22.00               | 2        |
| 10              | 16QAM | 25 | 0  | 21.29  | 21.04 | 21.01  |                     |          |
| 10              | 16QAM | 25 | 12 | 21.30  | 20.99 | 21.02  |                     |          |
| 10              | 16QAM | 25 | 25 | 21.24  | 20.98 | 20.96  | 22.00               | 2        |
| 10              | 16QAM | 50 | 0  | 21.04  | 20.79 | 20.82  |                     |          |
| Channel         |       |    |    | 37775  | 38000 | 38225  | Tune-up limit (dBm) | MPR (dB) |
| Frequency (MHz) |       |    |    | 2572.5 | 2595  | 2617.5 |                     |          |
| 5               | QPSK  | 1  | 0  | 22.75  | 22.58 | 22.47  | 24.00               | 0        |
| 5               | QPSK  | 1  | 12 | 23.52  | 22.73 | 22.78  |                     |          |
| 5               | QPSK  | 1  | 24 | 22.79  | 22.46 | 22.45  |                     |          |
| 5               | QPSK  | 12 | 0  | 22.38  | 21.73 | 21.73  | 23.00               | 1        |
| 5               | QPSK  | 12 | 7  | 22.12  | 21.75 | 21.71  |                     |          |
| 5               | QPSK  | 12 | 13 | 22.09  | 21.76 | 21.71  |                     |          |
| 5               | QPSK  | 25 | 0  | 22.02  | 21.77 | 21.71  | 23.00               | 1        |
| 5               | 16QAM | 1  | 0  | 21.83  | 21.57 | 21.37  |                     |          |
| 5               | 16QAM | 1  | 12 | 21.98  | 21.66 | 21.57  |                     |          |
| 5               | 16QAM | 1  | 24 | 21.74  | 21.48 | 21.36  | 22.00               | 2        |
| 5               | 16QAM | 12 | 0  | 21.05  | 21.03 | 20.97  |                     |          |
| 5               | 16QAM | 12 | 7  | 21.13  | 20.79 | 20.76  |                     |          |
| 5               | 16QAM | 12 | 13 | 21.38  | 21.03 | 20.72  | 22.00               | 2        |
| 5               | 16QAM | 25 | 0  | 21.28  | 21.01 | 20.95  |                     |          |



<LTE Band 41>

| BW [MHz]        | Modulation | RB Size | RB Offset | Power Low Ch. / Freq. | Power Middle Low Ch. / Freq. | Power Middle High Ch. / Freq. | Power High Ch. / Freq. | Tune-up limit (dBm) | MPR (dB) |
|-----------------|------------|---------|-----------|-----------------------|------------------------------|-------------------------------|------------------------|---------------------|----------|
| Channel         |            |         |           | 40340                 | 40600                        | 40870                         | 41140                  |                     |          |
| Frequency (MHz) |            |         |           | 2565                  | 2591                         | 2618                          | 2645                   |                     |          |
| 20              | QPSK       | 1       | 0         | 23.76                 | 23.53                        | 23.43                         | 23.04                  | 24.00               | 0        |
| 20              | QPSK       | 1       | 49        | 23.89                 | 23.55                        | 23.52                         | 23.36                  |                     |          |
| 20              | QPSK       | 1       | 99        | 23.58                 | 23.39                        | 22.95                         | 23.03                  |                     |          |
| 20              | QPSK       | 50      | 0         | 22.96                 | 22.90                        | 22.75                         | 22.55                  | 23.00               | 1        |
| 20              | QPSK       | 50      | 24        | 22.95                 | 22.88                        | 22.69                         | 22.49                  |                     |          |
| 20              | QPSK       | 50      | 50        | 22.90                 | 22.77                        | 22.45                         | 22.29                  |                     |          |
| 20              | QPSK       | 100     | 0         | 22.88                 | 22.74                        | 22.60                         | 22.38                  | 23.00               | 1        |
| 20              | 16QAM      | 1       | 0         | 22.64                 | 22.22                        | 22.23                         | 21.71                  |                     |          |
| 20              | 16QAM      | 1       | 49        | 22.60                 | 22.84                        | 22.25                         | 22.06                  |                     |          |
| 20              | 16QAM      | 1       | 99        | 22.46                 | 22.29                        | 21.86                         | 21.87                  | 22.00               | 2        |
| 20              | 16QAM      | 50      | 0         | 21.75                 | 21.76                        | 21.73                         | 21.22                  |                     |          |
| 20              | 16QAM      | 50      | 24        | 21.80                 | 21.84                        | 21.68                         | 21.26                  |                     |          |
| 20              | 16QAM      | 50      | 50        | 21.86                 | 21.70                        | 21.53                         | 21.48                  | 22.00               | 2        |
| 20              | 16QAM      | 100     | 0         | 21.88                 | 21.83                        | 21.50                         | 21.15                  |                     |          |
| Channel         |            |         |           | 40315                 | 40595                        | 40885                         | 41165                  |                     |          |
| Frequency (MHz) |            |         |           | 2562.5                | 2590.5                       | 2619.5                        | 2647.5                 |                     |          |
| 15              | QPSK       | 1       | 0         | 23.74                 | 23.56                        | 23.51                         | 22.99                  | 24.00               | 0        |
| 15              | QPSK       | 1       | 37        | 23.88                 | 23.83                        | 23.54                         | 23.36                  |                     |          |
| 15              | QPSK       | 1       | 74        | 23.76                 | 23.45                        | 23.20                         | 23.21                  |                     |          |
| 15              | QPSK       | 36      | 0         | 22.94                 | 22.95                        | 22.65                         | 22.31                  | 23.00               | 1        |
| 15              | QPSK       | 36      | 20        | 22.86                 | 22.90                        | 22.47                         | 22.29                  |                     |          |
| 15              | QPSK       | 36      | 39        | 22.87                 | 22.72                        | 22.50                         | 22.53                  |                     |          |
| 15              | QPSK       | 75      | 0         | 22.99                 | 22.73                        | 22.56                         | 22.47                  | 23.00               | 1        |
| 15              | 16QAM      | 1       | 0         | 22.71                 | 22.31                        | 22.20                         | 21.78                  |                     |          |
| 15              | 16QAM      | 1       | 37        | 22.69                 | 22.42                        | 22.55                         | 22.44                  |                     |          |
| 15              | 16QAM      | 1       | 74        | 22.53                 | 22.39                        | 22.19                         | 21.77                  | 22.00               | 2        |
| 15              | 16QAM      | 36      | 0         | 21.80                 | 21.93                        | 21.73                         | 21.24                  |                     |          |
| 15              | 16QAM      | 36      | 20        | 21.96                 | 21.86                        | 21.54                         | 21.42                  |                     |          |
| 15              | 16QAM      | 36      | 39        | 21.89                 | 21.86                        | 21.44                         | 21.37                  | 22.00               | 2        |
| 15              | 16QAM      | 75      | 0         | 21.89                 | 21.82                        | 21.50                         | 21.33                  |                     |          |



| Channel         |       |    |    | 40290  | 40590  | 40890  | 41190  | Tune-up limit (dBm) | MPR (dB) |
|-----------------|-------|----|----|--------|--------|--------|--------|---------------------|----------|
| Frequency (MHz) |       |    |    | 2560   | 2590   | 2620   | 2650   |                     |          |
| 10              | QPSK  | 1  | 0  | 23.80  | 23.61  | 23.35  | 23.12  | 24.00               | 0        |
| 10              | QPSK  | 1  | 25 | 23.80  | 23.71  | 23.23  | 23.16  |                     |          |
| 10              | QPSK  | 1  | 49 | 23.77  | 23.53  | 23.20  | 23.09  |                     |          |
| 10              | QPSK  | 25 | 0  | 22.81  | 22.74  | 22.58  | 22.28  | 23.00               | 1        |
| 10              | QPSK  | 25 | 12 | 22.94  | 22.89  | 22.51  | 22.29  |                     |          |
| 10              | QPSK  | 25 | 25 | 22.93  | 22.75  | 22.46  | 22.31  |                     |          |
| 10              | QPSK  | 50 | 0  | 22.97  | 22.76  | 22.50  | 22.35  | 23.00               | 1        |
| 10              | 16QAM | 1  | 0  | 22.49  | 22.25  | 22.20  | 21.84  |                     |          |
| 10              | 16QAM | 1  | 25 | 22.75  | 22.59  | 22.53  | 22.09  |                     |          |
| 10              | 16QAM | 1  | 49 | 22.47  | 22.28  | 22.01  | 21.83  | 22.00               | 2        |
| 10              | 16QAM | 25 | 0  | 21.80  | 21.86  | 21.85  | 21.48  |                     |          |
| 10              | 16QAM | 25 | 12 | 21.79  | 21.89  | 21.74  | 21.47  |                     |          |
| 10              | 16QAM | 25 | 25 | 21.83  | 21.83  | 21.90  | 21.45  | 22.00               | 2        |
| 10              | 16QAM | 50 | 0  | 21.80  | 21.84  | 21.59  | 21.23  |                     |          |
| 10              | 16QAM | 50 | 0  | 21.80  | 21.84  | 21.59  | 21.23  |                     |          |
| Channel         |       |    |    | 40265  | 40585  | 40905  | 41215  | Tune-up limit (dBm) | MPR (dB) |
| Frequency (MHz) |       |    |    | 2557.5 | 2589.5 | 2621.5 | 2652.5 |                     |          |
| 5               | QPSK  | 1  | 0  | 23.58  | 23.46  | 23.14  | 22.97  | 24.00               | 0        |
| 5               | QPSK  | 1  | 12 | 23.85  | 23.63  | 23.43  | 23.29  |                     |          |
| 5               | QPSK  | 1  | 24 | 23.70  | 23.39  | 23.04  | 22.93  |                     |          |
| 5               | QPSK  | 12 | 0  | 22.89  | 22.66  | 22.47  | 22.31  | 23.00               | 1        |
| 5               | QPSK  | 12 | 7  | 22.91  | 22.69  | 22.45  | 22.28  |                     |          |
| 5               | QPSK  | 12 | 13 | 22.94  | 22.73  | 22.57  | 22.33  |                     |          |
| 5               | QPSK  | 25 | 0  | 22.87  | 22.69  | 22.51  | 22.26  | 23.00               | 1        |
| 5               | 16QAM | 1  | 0  | 22.51  | 22.23  | 21.99  | 22.10  |                     |          |
| 5               | 16QAM | 1  | 12 | 22.99  | 22.40  | 22.44  | 22.03  |                     |          |
| 5               | 16QAM | 1  | 24 | 22.69  | 22.23  | 22.19  | 21.80  | 22.00               | 2        |
| 5               | 16QAM | 12 | 0  | 21.90  | 21.79  | 21.51  | 21.26  |                     |          |
| 5               | 16QAM | 12 | 7  | 21.89  | 21.83  | 21.58  | 21.22  |                     |          |
| 5               | 16QAM | 12 | 13 | 21.86  | 21.68  | 21.40  | 21.25  | 22.00               | 2        |
| 5               | 16QAM | 25 | 0  | 21.88  | 21.73  | 21.90  | 21.45  |                     |          |



**LTE Carrier Aggregation Conducted Power**

**General Note:**

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink carrier aggregation only. Uplink carrier aggregation is not supported. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band. For SCC DL RB size and offset will base on the PCC corresponding RB allocation.
- vi. For inter-band CA, the SCC selected highest bandwidth and near the middle of its transmission band. For SCC DL RB size and offset will base on the PCC corresponding RB allocation.



| Configure  |                | PCC      |          |             |         |        | SCC          |          |          |             | Power   |                          |                         |
|------------|----------------|----------|----------|-------------|---------|--------|--------------|----------|----------|-------------|---------|--------------------------|-------------------------|
|            |                | LTE Band | BW (MHz) | Freq. (MHz) | Channel | UL# RB | UL RB Offset | LTE Band | BW (MHz) | Freq. (MHz) | Channel | LTE Rel 10 Tx.Power(dBm) | LTE Rel 8 Tx.Power(dBm) |
| Inter-Band | Band 5         | 10M      | 829      | 20450       | 1       | 25     | Band 7       | 20M      | 2655     | 3100        | 23.18   | 23.21                    |                         |
|            | Band 5         | 10M      | 836.5    | 20525       | 1       | 25     | Band 7       | 20M      | 2655     | 3100        | 23.13   | 23.16                    |                         |
|            | Band 5         | 10M      | 844      | 20600       | 1       | 25     | Band 7       | 20M      | 2655     | 3100        | 23.11   | 23.19                    |                         |
|            | Band 7         | 20M      | 2510     | 20850       | 1       | 49     | Band 5       | 10M      | 881.5    | 2525        | 22.65   | 22.66                    |                         |
|            | Band 7         | 20M      | 2535     | 21100       | 1       | 49     | Band 5       | 10M      | 881.5    | 2525        | 22.91   | 22.99                    |                         |
|            | Band 7         | 20M      | 2560     | 21350       | 1       | 49     | Band 5       | 10M      | 881.5    | 2525        | 23.26   | 23.28                    |                         |
| Intra-Band | Contiguous     | Band 7   | 20M      | 2510        | 20850   | 1      | 49           | Band 7   | 20M      | 2650        | 3050    | 22.63                    | 22.66                   |
|            |                | Band 7   | 20M      | 2535        | 21100   | 1      | 49           | Band 7   | 20M      | 2635        | 2900    | 22.95                    | 22.99                   |
|            |                | Band 7   | 20M      | 2535        | 21100   | 1      | 49           | Band 7   | 20M      | 2675        | 3300    | 22.96                    | 22.99                   |
|            |                | Band 7   | 20M      | 2560        | 21350   | 1      | 49           | Band 7   | 20M      | 2660        | 3150    | 23.25                    | 23.28                   |
|            | Non-Contiguous | Band 7   | 20M      | 2510        | 20850   | 1      | 49           | Band 7   | 20M      | 2680        | 3350    | 22.61                    | 22.66                   |
|            |                | Band 7   | 20M      | 2535        | 21100   | 1      | 49           | Band 7   | 20M      | 2680        | 3350    | 22.95                    | 22.99                   |
|            |                | Band 7   | 20M      | 2560        | 21350   | 1      | 49           | Band 7   | 20M      | 2630        | 2850    | 23.26                    | 23.28                   |
|            |                | Band 7   | 20M      | 2560        | 21350   | 1      | 49           | Band 7   | 20M      | 2655        | 3100    | 23.21                    | 23.28                   |

| Configure  |                | PCC      |          |             |         |        | SCC          |          |          |             | Power   |                          |                         |
|------------|----------------|----------|----------|-------------|---------|--------|--------------|----------|----------|-------------|---------|--------------------------|-------------------------|
|            |                | LTE Band | BW (MHz) | Freq. (MHz) | Channel | UL# RB | UL RB Offset | LTE Band | BW (MHz) | Freq. (MHz) | Channel | LTE Rel 10 Tx.Power(dBm) | LTE Rel 8 Tx.Power(dBm) |
| Inter-Band | Band 5         | 10M      | 829      | 20450       | 1       | 25     | Band 7       | 20M      | 2655     | 3100        | 23.17   | 23.21                    |                         |
|            | Band 5         | 10M      | 836.5    | 20525       | 1       | 25     | Band 7       | 20M      | 2655     | 3100        | 23.13   | 23.16                    |                         |
|            | Band 5         | 10M      | 844      | 20600       | 1       | 25     | Band 7       | 20M      | 2655     | 3100        | 23.16   | 23.19                    |                         |
|            | Band 7         | 20M      | 2510     | 20850       | 1       | 49     | Band 5       | 10M      | 881.5    | 2525        | 21.92   | 21.97                    |                         |
|            | Band 7         | 20M      | 2535     | 21100       | 1       | 49     | Band 5       | 10M      | 881.5    | 2525        | 22.31   | 22.33                    |                         |
|            | Band 7         | 20M      | 2560     | 21350       | 1       | 49     | Band 5       | 10M      | 881.5    | 2525        | 22.38   | 22.41                    |                         |
| Intra-Band | Contiguous     | Band 7   | 20M      | 2510        | 20850   | 1      | 49           | Band 7   | 20M      | 2650        | 3050    | 21.91                    | 21.97                   |
|            |                | Band 7   | 20M      | 2535        | 21100   | 1      | 49           | Band 7   | 20M      | 2635        | 2900    | 22.28                    | 22.33                   |
|            |                | Band 7   | 20M      | 2535        | 21100   | 1      | 49           | Band 7   | 20M      | 2675        | 3300    | 22.31                    | 22.33                   |
|            |                | Band 7   | 20M      | 2560        | 21350   | 1      | 49           | Band 7   | 20M      | 2660        | 3150    | 22.40                    | 22.41                   |
|            | Non-Contiguous | Band 7   | 20M      | 2510        | 20850   | 1      | 49           | Band 7   | 20M      | 2680        | 3350    | 21.96                    | 21.97                   |
|            |                | Band 7   | 20M      | 2535        | 21100   | 1      | 49           | Band 7   | 20M      | 2680        | 3350    | 22.31                    | 22.33                   |
|            |                | Band 7   | 20M      | 2560        | 21350   | 1      | 49           | Band 7   | 20M      | 2630        | 2850    | 22.38                    | 22.41                   |
|            |                | Band 7   | 20M      | 2560        | 21350   | 1      | 49           | Band 7   | 20M      | 2655        | 3100    | 22.39                    | 22.41                   |



## **13. SAR Test Results**

### **General Note:**

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
  - $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8$ W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$  W/kg, SAR testing with a headset connected to the handset is not required.

### **GSM Note:**

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (1Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode, SAR measurement is not required for the secondary mode.
3. Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 1 Tx slot due to its highest frame-average power.

### **UMTS Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq 1/4$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.



**LTE Note:**

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B5 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 38 SAR test was covered by Band 41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
  - a. The maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion.
  - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.





**13.1 Head SAR**

**<GSM SAR>**

| Plot No. | Band    | Mode           | Test Position | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------|----------------|---------------|-----------------|-----|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | GSM850  | GPRS 1 Tx slot | Right Cheek   | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | 0.12             | 0.183                  | 0.196                  |
|          | GSM850  | GPRS 1 Tx slot | Right Tilted  | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.17            | 0.165                  | 0.176                  |
| 01       | GSM850  | GPRS 1 Tx slot | Left Cheek    | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | 0.01             | 0.250                  | <b>0.267</b>           |
|          | GSM850  | GPRS 1 Tx slot | Left Tilted   | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.04            | 0.152                  | 0.162                  |
| 02       | GSM1900 | GPRS 1 Tx slot | Right Cheek   | OFF             | 810 | 1909.8      | 30.06               | 30.50               | 1.107                  | -0.03            | 0.148                  | <b>0.164</b>           |
|          | GSM1900 | GPRS 1 Tx slot | Right Tilted  | OFF             | 810 | 1909.8      | 30.06               | 30.50               | 1.107                  | -0.17            | 0.065                  | 0.072                  |
|          | GSM1900 | GPRS 1 Tx slot | Left Cheek    | OFF             | 810 | 1909.8      | 30.06               | 30.50               | 1.107                  | 0.07             | 0.096                  | 0.106                  |
|          | GSM1900 | GPRS 1 Tx slot | Left Tilted   | OFF             | 810 | 1909.8      | 30.06               | 30.50               | 1.107                  | 0.15             | 0.035                  | 0.039                  |

**<WCDMA SAR>**

| Plot No. | Band          | Mode         | Test Position | Power Reduction | Ch.  | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------------|--------------|---------------|-----------------|------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | WCDMA Band V  | RMC 12.2Kbps | Right Cheek   | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | -0.07            | 0.218                  | 0.278                  |
|          | WCDMA Band V  | RMC 12.2Kbps | Right Tilted  | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | -0.05            | 0.198                  | 0.253                  |
| 03       | WCDMA Band V  | RMC 12.2Kbps | Left Cheek    | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | 0.06             | 0.307                  | <b>0.392</b>           |
|          | WCDMA Band V  | RMC 12.2Kbps | Left Tilted   | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | -0.08            | 0.175                  | 0.223                  |
| 04       | WCDMA Band II | RMC 12.2Kbps | Right Cheek   | OFF             | 9400 | 1880        | 22.97               | 24.00               | 1.268                  | 0.02             | 0.331                  | <b>0.420</b>           |
|          | WCDMA Band II | RMC 12.2Kbps | Right Tilted  | OFF             | 9400 | 1880        | 22.97               | 24.00               | 1.268                  | -0.03            | 0.144                  | 0.183                  |
|          | WCDMA Band II | RMC 12.2Kbps | Left Cheek    | OFF             | 9400 | 1880        | 22.97               | 24.00               | 1.268                  | 0.18             | 0.295                  | 0.374                  |
|          | WCDMA Band II | RMC 12.2Kbps | Left Tilted   | OFF             | 9400 | 1880        | 22.97               | 24.00               | 1.268                  | -0.1             | 0.093                  | 0.118                  |



<LTE SAR>

| Plot No. | Band       | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|------------|----------|------------|---------|-----------|---------------|-----------------|-------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Right Cheek   | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.05             | 0.206                  | 0.250                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Right Cheek   | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.01             | 0.087                  | 0.107                  |
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Right Tilted  | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | -0.12            | 0.135                  | 0.164                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Right Tilted  | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | -0.05            | 0.061                  | 0.075                  |
| 05       | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Left Cheek    | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.08             | 0.320                  | <b>0.388</b>           |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Left Cheek    | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.13             | 0.140                  | 0.171                  |
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Left Tilted   | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | -0.11            | 0.180                  | 0.218                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Left Tilted   | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.08             | 0.082                  | 0.100                  |

| Plot No. | Band        | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|-------------|----------|------------|---------|-----------|---------------|-----------------|-------|-------------|---------------------|---------------------|------------------------|--------------|---------------------------|------------------|------------------------|------------------------|
| 06       | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Right Cheek   | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | -0.01            | 0.268                  | <b>0.277</b>           |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Right Cheek   | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.12             | 0.169                  | 0.172                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Right Tilted  | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | -0.1             | 0.087                  | 0.090                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Right Tilted  | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | -0.04            | 0.051                  | 0.052                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Left Cheek    | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.04             | 0.151                  | 0.156                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Left Cheek    | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.08             | 0.102                  | 0.104                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Left Tilted   | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | -0.05            | 0.142                  | 0.147                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Left Tilted   | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | -0.01            | 0.081                  | 0.082                  |

### 13.2 Hotspot SAR

#### <GSM SAR>

| Plot No. | Band    | Mode            | Test Position | Gap (mm) | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------|-----------------|---------------|----------|-----------------|-----|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | GSM850  | GPRS 1 Tx slots | Front         | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.02            | 0.324                  | 0.346                  |
|          | GSM850  | GPRS 1 Tx slots | Back          | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.19            | 0.295                  | 0.315                  |
| 07       | GSM850  | GPRS 1 Tx slots | Left Side     | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.02            | 0.383                  | <b>0.409</b>           |
|          | GSM850  | GPRS 1 Tx slots | Right Side    | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | 0.02             | 0.208                  | 0.222                  |
|          | GSM850  | GPRS 1 Tx slots | Bottom Side   | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | 0.02             | 0.198                  | 0.212                  |
|          | GSM1900 | GPRS 1 Tx slot  | Front         | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | -0.04            | 0.634                  | 0.652                  |
|          | GSM1900 | GPRS 1 Tx slot  | Back          | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | 0.13             | 0.415                  | 0.427                  |
|          | GSM1900 | GPRS 1 Tx slot  | Left Side     | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | -0.12            | 0.064                  | 0.066                  |
|          | GSM1900 | GPRS 1 Tx slot  | Right Side    | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | 0.04             | 0.045                  | 0.046                  |
|          | GSM1900 | GPRS 1 Tx slot  | Bottom Side   | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | -0.15            | 0.750                  | 0.771                  |
| 08       | GSM1900 | GPRS 1 Tx slot  | Bottom Side   | 10       | ON              | 512 | 1850.2      | 28.17               | 28.50               | 1.079                  | -0.02            | 0.793                  | <b>0.856</b>           |
|          | GSM1900 | GPRS 1 Tx slot  | Bottom Side   | 10       | ON              | 661 | 1880        | 28.1                | 28.50               | 1.096                  | -0.09            | 0.773                  | 0.848                  |

#### <WCDMA SAR>

| Plot No. | Band          | Mode         | Test Position | Gap (mm) | Power Reduction | Ch.  | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------------|--------------|---------------|----------|-----------------|------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | WCDMA Band V  | RMC 12.2Kbps | Front         | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | 0.02             | 0.327                  | 0.417                  |
|          | WCDMA Band V  | RMC 12.2Kbps | Back          | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | -0.16            | 0.332                  | 0.424                  |
| 09       | WCDMA Band V  | RMC 12.2Kbps | Left Side     | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | -0.02            | 0.449                  | <b>0.573</b>           |
|          | WCDMA Band V  | RMC 12.2Kbps | Right Side    | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | 0.13             | 0.296                  | 0.378                  |
|          | WCDMA Band V  | RMC 12.2Kbps | Bottom Side   | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | 0.02             | 0.196                  | 0.250                  |
|          | WCDMA Band II | RMC 12.2Kbps | Front         | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | -0.03            | 0.641                  | 0.736                  |
|          | WCDMA Band II | RMC 12.2Kbps | Back          | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | 0.12             | 0.449                  | 0.516                  |
|          | WCDMA Band II | RMC 12.2Kbps | Left Side     | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | -0.1             | 0.074                  | 0.085                  |
|          | WCDMA Band II | RMC 12.2Kbps | Right Side    | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | 0.11             | 0.051                  | 0.059                  |
|          | WCDMA Band II | RMC 12.2Kbps | Bottom Side   | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | -0.13            | 0.779                  | 0.894                  |
| 10       | WCDMA Band II | RMC 12.2Kbps | Bottom Side   | 10       | ON              | 9262 | 1852.4      | 19.16               | 20.00               | 1.213                  | -0.14            | 0.778                  | <b>0.944</b>           |
|          | WCDMA Band II | RMC 12.2Kbps | Bottom Side   | 10       | ON              | 9538 | 1880        | 19.29               | 20.00               | 1.178                  | -0.16            | 0.780                  | 0.919                  |



<LTE SAR>

| Plot No. | Band       | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Gap (mm) | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|------------|----------|------------|---------|-----------|---------------|----------|-----------------|-------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Front         | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.01             | 0.269                  | 0.326                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Front         | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.02             | 0.140                  | 0.171                  |
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Back          | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.01             | 0.267                  | 0.324                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Back          | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.02             | 0.143                  | 0.175                  |
| 11       | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Left Side     | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.07             | 0.408                  | 0.495                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Left Side     | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.13             | 0.182                  | 0.223                  |
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Right Side    | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.13             | 0.209                  | 0.254                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Right Side    | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.06             | 0.096                  | 0.117                  |
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Bottom Side   | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0                | 0.202                  | 0.245                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Bottom Side   | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.04             | 0.087                  | 0.107                  |

| Plot No. | Band        | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Gap (mm) | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|-------------|----------|------------|---------|-----------|---------------|----------|-----------------|-------|-------------|---------------------|---------------------|------------------------|--------------|---------------------------|------------------|------------------------|------------------------|
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.02             | 0.745                  | 0.769                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.09             | 0.966                  | 1.078                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40870 | 2618        | 23.52               | 24.00               | 1.117                  | 62.9         | 1.006                     | 0.14             | 0.938                  | 1.054                  |
| 12       | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 41140 | 2645        | 23.36               | 24.00               | 1.159                  | 62.9         | 1.006                     | 0.14             | 0.963                  | 1.123                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.19             | 0.815                  | 0.827                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 40600 | 2591        | 22.90               | 23.00               | 1.023                  | 62.9         | 1.006                     | 0.01             | 0.802                  | 0.826                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 40870 | 2618        | 22.75               | 23.00               | 1.059                  | 62.9         | 1.006                     | 0.1              | 0.821                  | 0.875                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 41140 | 2645        | 22.55               | 23.00               | 1.109                  | 62.9         | 1.006                     | 0.01             | 0.760                  | 0.848                  |
|          | LTE Band 41 | 20M      | QPSK       | 100RB   | 0Offset   | Front         | 10       | OFF             | 40340 | 2565        | 22.88               | 23.00               | 1.028                  | 62.9         | 1.006                     | 0.08             | 0.797                  | 0.824                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.03             | 0.748                  | 0.772                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.01             | 0.765                  | 0.854                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 40870 | 2618        | 23.52               | 24.00               | 1.117                  | 62.9         | 1.006                     | 0.08             | 0.761                  | 0.855                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 41140 | 2645        | 23.36               | 24.00               | 1.159                  | 62.9         | 1.006                     | 0.03             | 0.781                  | 0.910                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.17             | 0.789                  | 0.801                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 40600 | 2591        | 22.90               | 23.00               | 1.023                  | 62.9         | 1.006                     | -0.06            | 0.781                  | 0.804                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 40870 | 2618        | 22.75               | 23.00               | 1.059                  | 62.9         | 1.006                     | -0.05            | 0.808                  | 0.861                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 41140 | 2645        | 22.55               | 23.00               | 1.109                  | 62.9         | 1.006                     | -0.15            | 0.770                  | 0.859                  |
|          | LTE Band 41 | 20M      | QPSK       | 100RB   | 0Offset   | Back          | 10       | OFF             | 40340 | 2565        | 22.88               | 23.00               | 1.028                  | 62.9         | 1.006                     | -0.03            | 0.750                  | 0.776                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Left Side     | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | -0.19            | 0.097                  | 0.100                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Left Side     | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.12             | 0.094                  | 0.095                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Right Side    | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.1              | 0.522                  | 0.539                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Right Side    | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.18             | 0.496                  | 0.504                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Bottom Side   | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.16             | 0.903                  | 0.932                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Bottom Side   | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.13             | 0.755                  | 0.842                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Bottom Side   | 10       | OFF             | 40870 | 2618        | 23.52               | 24.00               | 1.117                  | 62.9         | 1.006                     | 0.11             | 0.629                  | 0.707                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Bottom Side   | 10       | OFF             | 41140 | 2645        | 23.36               | 24.00               | 1.159                  | 62.9         | 1.006                     | 0.01             | 0.468                  | 0.546                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Bottom Side   | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.002            | 0.900                  | 0.914                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Bottom Side   | 10       | OFF             | 40600 | 2591        | 22.90               | 23.00               | 1.023                  | 62.9         | 1.006                     | 0.01             | 0.750                  | 0.772                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Bottom Side   | 10       | OFF             | 40870 | 2618        | 22.75               | 23.00               | 1.059                  | 62.9         | 1.006                     | 0.1              | 0.614                  | 0.654                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Bottom Side   | 10       | OFF             | 41140 | 2645        | 22.55               | 23.00               | 1.109                  | 62.9         | 1.006                     | -0.12            | 0.459                  | 0.512                  |
|          | LTE Band 41 | 20M      | QPSK       | 100RB   | 0Offset   | Bottom Side   | 10       | OFF             | 40340 | 2565        | 22.88               | 23.00               | 1.028                  | 62.9         | 1.006                     | 0.19             | 0.862                  | 0.891                  |



**13.3 Body Worn Accessory SAR**

**<GSM SAR>**

| Plot No. | Band    | Mode            | Test Position | Gap (mm) | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------|-----------------|---------------|----------|-----------------|-----|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
| 13       | GSM850  | GPRS 1 Tx slots | Front         | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.02            | 0.324                  | <b>0.346</b>           |
|          | GSM850  | GPRS 1 Tx slots | Back          | 10       | OFF             | 189 | 836.4       | 33.21               | 33.50               | 1.069                  | -0.19            | 0.295                  | 0.315                  |
| 14       | GSM1900 | GPRS 1 Tx slot  | Front         | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | -0.04            | 0.634                  | <b>0.652</b>           |
|          | GSM1900 | GPRS 1 Tx slot  | Back          | 10       | ON              | 810 | 1909.8      | 28.38               | 28.50               | 1.028                  | 0.13             | 0.415                  | 0.427                  |

**<WCDMA SAR>**

| Plot No. | Band          | Mode         | Test Position | Gap (mm) | Power Reduction | Ch.  | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------------|--------------|---------------|----------|-----------------|------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|          | WCDMA Band V  | RMC 12.2Kbps | Front         | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | 0.02             | 0.327                  | 0.417                  |
| 15       | WCDMA Band V  | RMC 12.2Kbps | Back          | 10       | OFF             | 4132 | 826.4       | 22.94               | 24.00               | 1.276                  | -0.16            | 0.332                  | <b>0.424</b>           |
| 16       | WCDMA Band II | RMC 12.2Kbps | Front         | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | -0.03            | 0.641                  | <b>0.736</b>           |
|          | WCDMA Band II | RMC 12.2Kbps | Back          | 10       | ON              | 9400 | 1880        | 19.40               | 20.00               | 1.148                  | 0.12             | 0.449                  | 0.516                  |



<LTE SAR>

| Plot No. | Band       | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Gap (mm) | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|------------|----------|------------|---------|-----------|---------------|----------|-----------------|-------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
| 17       | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Front         | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.01             | 0.269                  | 0.326                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Front         | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.02             | 0.140                  | 0.171                  |
|          | LTE Band 5 | 10M      | QPSK       | 1RB     | 25Offset  | Back          | 10       | OFF             | 20525 | 836.5       | 23.16               | 24.00               | 1.213                  | 0.01             | 0.267                  | 0.324                  |
|          | LTE Band 5 | 10M      | QPSK       | 25RB    | 0Offset   | Back          | 10       | OFF             | 20525 | 836.5       | 22.12               | 23.00               | 1.225                  | 0.02             | 0.143                  | 0.175                  |

| Plot No. | Band        | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Gap (mm) | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|-------------|----------|------------|---------|-----------|---------------|----------|-----------------|-------|-------------|---------------------|---------------------|------------------------|--------------|---------------------------|------------------|------------------------|------------------------|
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.02             | 0.745                  | 0.769                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.09             | 0.966                  | 1.078                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40870 | 2618        | 23.52               | 24.00               | 1.117                  | 62.9         | 1.006                     | 0.14             | 0.938                  | 1.054                  |
| 12       | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 41140 | 2645        | 23.36               | 24.00               | 1.159                  | 62.9         | 1.006                     | 0.14             | 0.963                  | 1.123                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.19             | 0.815                  | 0.827                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 40600 | 2591        | 22.90               | 23.00               | 1.023                  | 62.9         | 1.006                     | 0.01             | 0.802                  | 0.826                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 40870 | 2618        | 22.75               | 23.00               | 1.059                  | 62.9         | 1.006                     | 0.1              | 0.821                  | 0.875                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Front         | 10       | OFF             | 41140 | 2645        | 22.55               | 23.00               | 1.109                  | 62.9         | 1.006                     | 0.01             | 0.760                  | 0.848                  |
|          | LTE Band 41 | 20M      | QPSK       | 100RB   | 0Offset   | Front         | 10       | OFF             | 40340 | 2565        | 22.88               | 23.00               | 1.028                  | 62.9         | 1.006                     | 0.08             | 0.797                  | 0.824                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 40340 | 2565        | 23.89               | 24.00               | 1.026                  | 62.9         | 1.006                     | 0.03             | 0.748                  | 0.772                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.01             | 0.765                  | 0.854                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 40870 | 2618        | 23.52               | 24.00               | 1.117                  | 62.9         | 1.006                     | 0.08             | 0.761                  | 0.855                  |
|          | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Back          | 10       | OFF             | 41140 | 2645        | 23.36               | 24.00               | 1.159                  | 62.9         | 1.006                     | 0.03             | 0.781                  | 0.910                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 40340 | 2565        | 22.96               | 23.00               | 1.009                  | 62.9         | 1.006                     | 0.17             | 0.789                  | 0.801                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 40600 | 2591        | 22.90               | 23.00               | 1.023                  | 62.9         | 1.006                     | -0.06            | 0.781                  | 0.804                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 40870 | 2618        | 22.75               | 23.00               | 1.059                  | 62.9         | 1.006                     | -0.05            | 0.808                  | 0.861                  |
|          | LTE Band 41 | 20M      | QPSK       | 50RB    | 0Offset   | Back          | 10       | OFF             | 41140 | 2645        | 22.55               | 23.00               | 1.109                  | 62.9         | 1.006                     | -0.15            | 0.770                  | 0.859                  |
|          | LTE Band 41 | 20M      | QPSK       | 100RB   | 0Offset   | Back          | 10       | OFF             | 40340 | 2565        | 22.88               | 23.00               | 1.028                  | 62.9         | 1.006                     | -0.03            | 0.750                  | 0.776                  |



13.4 Repeated SAR Measurement

| No. | Band        | BW (MHz) | Modulation | RB Size | RB offset | Test Position | Gap (mm) | Power Reduction | Ch.   | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Ratio | Reported 1g SAR (W/kg) |
|-----|-------------|----------|------------|---------|-----------|---------------|----------|-----------------|-------|-------------|---------------------|---------------------|------------------------|--------------|---------------------------|------------------|------------------------|-------|------------------------|
| 1st | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.09             | 0.966                  | 1     | 1.078                  |
| 2nd | LTE Band 41 | 20M      | QPSK       | 1RB     | 49Offset  | Front         | 10       | OFF             | 40600 | 2591        | 23.55               | 24.00               | 1.109                  | 62.9         | 1.006                     | 0.14             | 0.963                  | 1.003 | 1.075                  |

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8W/kg$ .
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45W/kg$ , only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured* SAR.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

**14. Simultaneous Transmission Analysis**

| NO. | Simultaneous Transmission Configurations | Portable Handset |           |         | Note      |
|-----|--|------------------|-----------|---------|-----------|
|     |  | Head             | Body-worn | Hotspot |           |
| 1.  | GSM Voice + WLAN2.4GHz                   | Yes              | Yes       |         |           |
| 2.  | GPRS/EDGE + WLAN2.4GHz                   | Yes              | Yes       | Yes     | Hotspot   |
| 3.  | WCDMA + WLAN2.4GHz                       | Yes              | Yes       | Yes     | Hotspot   |
| 4.  | LTE + WLAN2.4GHz                         | Yes              | Yes       | Yes     | Hotspot   |
| 5.  | GSM Voice + WLAN5.3/5.5GHz               | Yes              | Yes       |         |           |
| 6.  | GPRS/EDGE + WLAN5.3/5.5GHz               | Yes              | Yes       |         | WWAN VoIP |
| 7.  | WCDMA + WLAN5.3/5.5GHz                   | Yes              | Yes       |         | WWAN VoIP |
| 8.  | LTE + WLAN5.3/5.5GHz                     | Yes              | Yes       |         | WWAN VoIP |
| 9.  | GSM Voice + WLAN5.2/5.8GHz               | Yes              | Yes       | Yes     |           |
| 10. | GPRS/EDGE + WLAN5.2/5.8GHz               | Yes              | Yes       | Yes     | WWAN VoIP |
| 11. | WCDMA + WLAN5.2/5.8GHz                   | Yes              | Yes       | Yes     | WWAN VoIP |
| 12. | LTE + WLAN5.2/5.8GHz                     | Yes              | Yes       | Yes     | WWAN VoIP |
| 13. | GSM Voice + WLAN5GHz+Bluetooth           |                  | Yes       |         |           |
| 14. | GPRS/EDGE + WLAN5GHz+Bluetooth           |                  | Yes       |         | WWAN VoIP |
| 15. | WCDMA + WLAN5GHz+Bluetooth               |                  | Yes       |         | WWAN VoIP |
| 16. | LTE + WLAN5GHz+Bluetooth                 |                  | Yes       |         | WWAN VoIP |

**General Note:**

1. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.
2. EUT will choose each GSM, WCDMA, and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. For simultaneously transmission SAR analysis, WWAN SAR values only considered the worst position which we did perform SAR testing on FA6O1212-06, WLAN SAR were leverage from the parent model which referred to the test report number FA6O1212
4. The Scaled SAR summation is calculated based on the same configuration and test position.
5. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - i) Scalar SAR summation < 1.6W/kg.
  - ii)  $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
  - iii) If  $SPLSR \leq 0.04$ , simultaneously transmission SAR measurement is not necessary.
  - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.





**14.1 Head Exposure Conditions**

| WWAN Band |         | Exposure Position | 1                | 2                | 3                | 1+2<br>Summed<br>1g SAR<br>(W/kg) | 1+3<br>Summed<br>1g SAR<br>(W/kg) | SPLSR | Case No |
|-----------|---------|-------------------|------------------|------------------|------------------|-----------------------------------|-----------------------------------|-------|---------|
|           |         |                   | WWAN             | 2.4GHz<br>WLAN   | 5GHz<br>WLAN     |                                   |                                   |       |         |
|           |         |                   | 1g SAR<br>(W/kg) | 1g SAR<br>(W/kg) | 1g SAR<br>(W/kg) |                                   |                                   |       |         |
| GSM       | GSM850  | Right Cheek       | 0.196            | 0.386            | 0.102            | 0.58                              | 0.30                              |       |         |
|           |         | Right Tilted      | 0.176            | 0.914            | 0.102            | 1.09                              | 0.28                              |       |         |
|           |         | Left Cheek        | 0.267            | 0.914            | 0.102            | 1.18                              | 0.37                              |       |         |
|           |         | Left Tilted       | 0.162            | 0.516            | 0.045            | 0.68                              | 0.21                              |       |         |
|           | GSM1900 | Right Cheek       | 0.164            | 0.386            | 0.102            | 0.55                              | 0.27                              |       |         |
|           |         | Right Tilted      | 0.072            | 0.914            | 0.102            | 0.99                              | 0.17                              |       |         |
|           |         | Left Cheek        | 0.106            | 0.914            | 0.102            | 1.02                              | 0.21                              |       |         |
|           |         | Left Tilted       | 0.039            | 0.516            | 0.045            | 0.56                              | 0.08                              |       |         |
| WCDMA     | Band V  | Right Cheek       | 0.278            | 0.386            | 0.102            | 0.66                              | 0.38                              |       |         |
|           |         | Right Tilted      | 0.253            | 0.914            | 0.102            | 1.17                              | 0.36                              |       |         |
|           |         | Left Cheek        | 0.392            | 0.914            | 0.102            | <b>1.31</b>                       | 0.49                              |       |         |
|           |         | Left Tilted       | 0.223            | 0.516            | 0.045            | 0.74                              | 0.27                              |       |         |
|           | Band II | Right Cheek       | 0.420            | 0.386            | 0.102            | 0.81                              | 0.52                              |       |         |
|           |         | Right Tilted      | 0.183            | 0.914            | 0.102            | 1.10                              | 0.29                              |       |         |
|           |         | Left Cheek        | 0.374            | 0.914            | 0.102            | 1.29                              | 0.48                              |       |         |
|           |         | Left Tilted       | 0.118            | 0.516            | 0.045            | 0.63                              | 0.16                              |       |         |
| LTE       | Band 5  | Right Cheek       | 0.250            | 0.386            | 0.102            | 0.64                              | 0.35                              |       |         |
|           |         | Right Tilted      | 0.164            | 0.914            | 0.102            | 1.08                              | 0.27                              |       |         |
|           |         | Left Cheek        | 0.388            | 0.914            | 0.102            | 1.30                              | 0.49                              |       |         |
|           |         | Left Tilted       | 0.218            | 0.516            | 0.045            | 0.73                              | 0.26                              |       |         |
|           | Band 41 | Right Cheek       | 0.277            | 0.386            | 0.102            | 0.66                              | 0.38                              |       |         |
|           |         | Right Tilted      | 0.090            | 0.914            | 0.102            | 1.00                              | 0.19                              |       |         |
|           |         | Left Cheek        | 0.156            | 0.914            | 0.102            | 1.07                              | 0.26                              |       |         |
|           |         | Left Tilted       | 0.147            | 0.516            | 0.045            | 0.66                              | 0.19                              |       |         |



**14.2 Hotspot Exposure Conditions**

| WWAN Band | Exposure Position | 1             | 2             | 3             | 1+2 Summed 1g SAR (W/kg) | 1+3 Summed 1g SAR (W/kg) | SPLSR | Case No |  |
|-----------|-------------------|---------------|---------------|---------------|--------------------------|--------------------------|-------|---------|--|
|           |                   | WWAN          | 2.4GHz WLAN   | 5GHz WLAN     |                          |                          |       |         |  |
|           |                   | 1g SAR (W/kg) | 1g SAR (W/kg) | 1g SAR (W/kg) |                          |                          |       |         |  |
| GSM       | GSM850            | Front         | 0.346         | 0.146         | 0.109                    | 0.49                     | 0.46  |         |  |
|           |                   | Back          | 0.315         | 0.146         | 0.109                    | 0.46                     | 0.42  |         |  |
|           |                   | Left side     | 0.409         |               |                          | 0.41                     | 0.41  |         |  |
|           |                   | Right side    | 0.222         | 0.146         | 0.109                    | 0.37                     | 0.33  |         |  |
|           |                   | Top side      |               | 0.146         | 0.109                    | 0.15                     | 0.11  |         |  |
|           |                   | Bottom side   | 0.212         |               |                          | 0.21                     | 0.21  |         |  |
|           | GSM1900           | Front         | 0.652         | 0.146         | 0.109                    | 0.80                     | 0.76  |         |  |
|           |                   | Back          | 0.427         | 0.146         | 0.109                    | 0.57                     | 0.54  |         |  |
|           |                   | Left side     | 0.066         |               |                          | 0.07                     | 0.07  |         |  |
|           |                   | Right side    | 0.046         | 0.146         | 0.109                    | 0.19                     | 0.16  |         |  |
|           |                   | Top side      |               | 0.146         | 0.109                    | 0.15                     | 0.11  |         |  |
|           |                   | Bottom side   | 0.856         |               |                          | 0.86                     | 0.86  |         |  |
| WCDMA     | Band V            | Front         | 0.417         | 0.146         | 0.109                    | 0.56                     | 0.53  |         |  |
|           |                   | Back          | 0.424         | 0.146         | 0.109                    | 0.57                     | 0.53  |         |  |
|           |                   | Left side     | 0.573         |               |                          | 0.57                     | 0.57  |         |  |
|           |                   | Right side    | 0.378         | 0.146         | 0.109                    | 0.52                     | 0.49  |         |  |
|           |                   | Top side      |               | 0.146         | 0.109                    | 0.15                     | 0.11  |         |  |
|           |                   | Bottom side   | 0.250         |               |                          | 0.25                     | 0.25  |         |  |
|           | Band II           | Front         | 0.736         | 0.146         | 0.109                    | 0.88                     | 0.85  |         |  |
|           |                   | Back          | 0.516         | 0.146         | 0.109                    | 0.66                     | 0.63  |         |  |
|           |                   | Left side     | 0.085         |               |                          | 0.09                     | 0.09  |         |  |
|           |                   | Right side    | 0.059         | 0.146         | 0.109                    | 0.21                     | 0.17  |         |  |
|           |                   | Top side      |               | 0.146         | 0.109                    | 0.15                     | 0.11  |         |  |
|           |                   | Bottom side   | 0.944         |               |                          | 0.94                     | 0.94  |         |  |
| LTE       | Band 5            | Front         | 0.326         | 0.146         | 0.109                    | 0.47                     | 0.44  |         |  |
|           |                   | Back          | 0.324         | 0.146         | 0.109                    | 0.47                     | 0.43  |         |  |
|           |                   | Left side     | 0.495         |               |                          | 0.50                     | 0.50  |         |  |
|           |                   | Right side    | 0.254         | 0.146         | 0.109                    | 0.40                     | 0.36  |         |  |
|           |                   | Top side      |               | 0.146         | 0.109                    | 0.15                     | 0.11  |         |  |
|           |                   | Bottom side   | 0.245         |               |                          | 0.25                     | 0.25  |         |  |
|           | Band 41           | Front         | 1.123         | 0.146         | 0.109                    | 1.27                     | 1.23  |         |  |
|           |                   | Back          | 0.910         | 0.146         | 0.109                    | 1.06                     | 1.02  |         |  |
|           |                   | Left side     | 0.100         |               |                          | 0.10                     | 0.10  |         |  |
|           |                   | Right side    | 0.539         | 0.146         | 0.109                    | 0.69                     | 0.65  |         |  |
|           |                   | Top side      |               | 0.146         | 0.109                    | 0.15                     | 0.11  |         |  |
|           |                   | Bottom side   | 0.932         |               |                          | 0.93                     | 0.93  |         |  |



**14.3 Body-Worn Accessory Exposure Conditions**

| WWAN Band |         | Exposure Position | 1             | 2             | 3             | 4                       | 1+2 Summed 1g SAR (W/kg) | 1+3 Summed 1g SAR (W/kg) | 1+4 Summed 1g SAR (W/kg) | 1+3+4 Summed 1g SAR (W/kg) | SPLSR | Case No |
|-----------|---------|-------------------|---------------|---------------|---------------|-------------------------|--------------------------|--------------------------|--------------------------|----------------------------|-------|---------|
|           |         |                   | WWAN          | 2.4GHz WLAN   | 5GHz WLAN     | Bluetooth               |                          |                          |                          |                            |       |         |
|           |         |                   | 1g SAR (W/kg) | 1g SAR (W/kg) | 1g SAR (W/kg) | Bluetooth 1g SAR (W/kg) |                          |                          |                          |                            |       |         |
| GSM       | GSM850  | Front             | 0.346         | 0.146         | 0.077         | 0.033                   | 0.49                     | 0.42                     | 0.38                     | 0.46                       |       |         |
|           |         | Back              | 0.315         | 0.146         | 0.077         | 0.026                   | 0.46                     | 0.39                     | 0.34                     | 0.42                       |       |         |
|           | GSM1900 | Front             | 0.652         | 0.146         | 0.077         | 0.033                   | 0.80                     | 0.73                     | 0.69                     | 0.76                       |       |         |
|           |         | Back              | 0.427         | 0.146         | 0.077         | 0.026                   | 0.57                     | 0.50                     | 0.45                     | 0.53                       |       |         |
| WCDMA     | Band V  | Front             | 0.417         | 0.146         | 0.077         | 0.033                   | 0.56                     | 0.49                     | 0.45                     | 0.53                       |       |         |
|           |         | Back              | 0.424         | 0.146         | 0.077         | 0.026                   | 0.57                     | 0.50                     | 0.45                     | 0.53                       |       |         |
|           | Band II | Front             | 0.736         | 0.146         | 0.077         | 0.033                   | 0.88                     | 0.81                     | 0.77                     | 0.85                       |       |         |
|           |         | Back              | 0.516         | 0.146         | 0.077         | 0.026                   | 0.66                     | 0.59                     | 0.54                     | 0.62                       |       |         |
| LTE       | Band 5  | Front             | 0.326         | 0.146         | 0.077         | 0.033                   | 0.47                     | 0.40                     | 0.36                     | 0.44                       |       |         |
|           |         | Back              | 0.324         | 0.146         | 0.077         | 0.026                   | 0.47                     | 0.40                     | 0.35                     | 0.43                       |       |         |
|           | Band 41 | Front             | 1.123         | 0.146         | 0.077         | 0.033                   | 1.27                     | 1.20                     | 1.16                     | 1.23                       |       |         |
|           |         | Back              | 0.910         | 0.146         | 0.077         | 0.026                   | 1.06                     | 0.99                     | 0.94                     | 1.01                       |       |         |

Test Engineer : Nick Hu

## 15. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

| Uncertainty Distributions          | Normal                     | Rectangular   | Triangular    | U-Shape       |
|------------------------------------|----------------------------|---------------|---------------|---------------|
| Multi-plying Factor <sup>(a)</sup> | 1/ $\kappa$ <sup>(b)</sup> | 1/ $\sqrt{3}$ | 1/ $\sqrt{6}$ | 1/ $\sqrt{2}$ |

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $\kappa$  is the coverage factor

**Table 15.1. Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

| Error Description                 | Uncertainty Value (±%) | Probability | Divisor | (Ci) 1g | (Ci) 10g | Standard Uncertainty (1g) (±%) | Standard Uncertainty (10g) (±%) |
|-----------------------------------|------------------------|-------------|---------|---------|----------|--------------------------------|---------------------------------|
| <b>Measurement System</b>         |                        |             |         |         |          |                                |                                 |
| Probe Calibration                 | 6.0                    | N           | 1       | 1       | 1        | 6.0                            | 6.0                             |
| Axial Isotropy                    | 4.7                    | R           | 1.732   | 0.7     | 0.7      | 1.9                            | 1.9                             |
| Hemispherical Isotropy            | 9.6                    | R           | 1.732   | 0.7     | 0.7      | 3.9                            | 3.9                             |
| Boundary Effects                  | 1.0                    | R           | 1.732   | 1       | 1        | 0.6                            | 0.6                             |
| Linearity                         | 4.7                    | R           | 1.732   | 1       | 1        | 2.7                            | 2.7                             |
| System Detection Limits           | 1.0                    | R           | 1.732   | 1       | 1        | 0.6                            | 0.6                             |
| Modulation Response               | 3.2                    | R           | 1.732   | 1       | 1        | 1.8                            | 1.8                             |
| Readout Electronics               | 0.3                    | N           | 1       | 1       | 1        | 0.3                            | 0.3                             |
| Response Time                     | 0.0                    | R           | 1.732   | 1       | 1        | 0.0                            | 0.0                             |
| Integration Time                  | 2.6                    | R           | 1.732   | 1       | 1        | 1.5                            | 1.5                             |
| RF Ambient Noise                  | 3.0                    | R           | 1.732   | 1       | 1        | 1.7                            | 1.7                             |
| RF Ambient Reflections            | 3.0                    | R           | 1.732   | 1       | 1        | 1.7                            | 1.7                             |
| Probe Positioner                  | 0.4                    | R           | 1.732   | 1       | 1        | 0.2                            | 0.2                             |
| Probe Positioning                 | 2.9                    | R           | 1.732   | 1       | 1        | 1.7                            | 1.7                             |
| Max. SAR Eval.                    | 2.0                    | R           | 1.732   | 1       | 1        | 1.2                            | 1.2                             |
| <b>Test Sample Related</b>        |                        |             |         |         |          |                                |                                 |
| Device Positioning                | 3.0                    | N           | 1       | 1       | 1        | 3.0                            | 3.0                             |
| Device Holder                     | 3.6                    | N           | 1       | 1       | 1        | 3.6                            | 3.6                             |
| Power Drift                       | 5.0                    | R           | 1.732   | 1       | 1        | 2.9                            | 2.9                             |
| Power Scaling                     | 0.0                    | R           | 1.732   | 1       | 1        | 0.0                            | 0.0                             |
| <b>Phantom and Setup</b>          |                        |             |         |         |          |                                |                                 |
| Phantom Uncertainty               | 6.1                    | R           | 1.732   | 1       | 1        | 3.5                            | 3.5                             |
| SAR correction                    | 0.0                    | R           | 1.732   | 1       | 0.84     | 0.0                            | 0.0                             |
| Liquid Conductivity Repeatability | 0.2                    | N           | 1       | 0.78    | 0.71     | 0.1                            | 0.1                             |
| Liquid Conductivity (target)      | 5.0                    | R           | 1.732   | 0.78    | 0.71     | 2.3                            | 2.0                             |
| Liquid Conductivity (mea.)        | 2.5                    | R           | 1.732   | 0.78    | 0.71     | 1.1                            | 1.0                             |
| Temp. unc. - Conductivity         | 3.4                    | R           | 1.732   | 0.78    | 0.71     | 1.5                            | 1.4                             |
| Liquid Permittivity Repeatability | 0.15                   | N           | 1       | 0.23    | 0.26     | 0.0                            | 0.0                             |
| Liquid Permittivity (target)      | 5.0                    | R           | 1.732   | 0.23    | 0.26     | 0.7                            | 0.8                             |
| Liquid Permittivity (mea.)        | 2.5                    | R           | 1.732   | 0.23    | 0.26     | 0.3                            | 0.4                             |
| Temp. unc. - Permittivity         | 0.83                   | R           | 1.732   | 0.23    | 0.26     | 0.1                            | 0.1                             |
| <b>Combined Std. Uncertainty</b>  |                        |             |         |         |          | 11.4%                          | 11.4%                           |
| <b>Coverage Factor for 95 %</b>   |                        |             |         |         |          | K=2                            | K=2                             |
| <b>Expanded STD Uncertainty</b>   |                        |             |         |         |          | 22.9%                          | 22.7%                           |

**Table 15.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz**

| Error Description                 | Uncertainty Value (±%) | Probability | Divisor | (Ci) 1g | (Ci) 10g | Standard Uncertainty (1g) (±%) | Standard Uncertainty (10g) (±%) |
|-----------------------------------|------------------------|-------------|---------|---------|----------|--------------------------------|---------------------------------|
| <b>Measurement System</b>         |                        |             |         |         |          |                                |                                 |
| Probe Calibration                 | 6.55                   | N           | 1       | 1       | 1        | 6.6                            | 6.6                             |
| Axial Isotropy                    | 4.7                    | R           | 1.732   | 0.7     | 0.7      | 1.9                            | 1.9                             |
| Hemispherical Isotropy            | 9.6                    | R           | 1.732   | 0.7     | 0.7      | 3.9                            | 3.9                             |
| Boundary Effects                  | 2.0                    | R           | 1.732   | 1       | 1        | 1.2                            | 1.2                             |
| Linearity                         | 4.7                    | R           | 1.732   | 1       | 1        | 2.7                            | 2.7                             |
| System Detection Limits           | 1.0                    | R           | 1.732   | 1       | 1        | 0.6                            | 0.6                             |
| Modulation Response               | 3.2                    | R           | 1.732   | 1       | 1        | 1.8                            | 1.8                             |
| Readout Electronics               | 0.3                    | N           | 1       | 1       | 1        | 0.3                            | 0.3                             |
| Response Time                     | 0.0                    | R           | 1.732   | 1       | 1        | 0.0                            | 0.0                             |
| Integration Time                  | 2.6                    | R           | 1.732   | 1       | 1        | 1.5                            | 1.5                             |
| RF Ambient Noise                  | 3.0                    | R           | 1.732   | 1       | 1        | 1.7                            | 1.7                             |
| RF Ambient Reflections            | 3.0                    | R           | 1.732   | 1       | 1        | 1.7                            | 1.7                             |
| Probe Positioner                  | 0.4                    | R           | 1.732   | 1       | 1        | 0.2                            | 0.2                             |
| Probe Positioning                 | 6.7                    | R           | 1.732   | 1       | 1        | 3.9                            | 3.9                             |
| Max. SAR Eval.                    | 4.0                    | R           | 1.732   | 1       | 1        | 2.3                            | 2.3                             |
| <b>Test Sample Related</b>        |                        |             |         |         |          |                                |                                 |
| Device Positioning                | 3.0                    | N           | 1       | 1       | 1        | 3.0                            | 3.0                             |
| Device Holder                     | 3.6                    | N           | 1       | 1       | 1        | 3.6                            | 3.6                             |
| Power Drift                       | 5.0                    | R           | 1.732   | 1       | 1        | 2.9                            | 2.9                             |
| Power Scaling                     | 0.0                    | R           | 1.732   | 1       | 1        | 0.0                            | 0.0                             |
| <b>Phantom and Setup</b>          |                        |             |         |         |          |                                |                                 |
| Phantom Uncertainty               | 6.6                    | R           | 1.732   | 1       | 1        | 3.8                            | 3.8                             |
| SAR correction                    | 0.0                    | R           | 1.732   | 1       | 0.84     | 0.0                            | 0.0                             |
| Liquid Conductivity Repeatability | 0.2                    | N           | 1       | 0.78    | 0.71     | 0.1                            | 0.1                             |
| Liquid Conductivity (target)      | 5.0                    | R           | 1.732   | 0.78    | 0.71     | 2.3                            | 2.0                             |
| Liquid Conductivity (mea.)        | 2.5                    | R           | 1.732   | 0.78    | 0.71     | 1.1                            | 1.0                             |
| Temp. unc. - Conductivity         | 3.4                    | R           | 1.732   | 0.78    | 0.71     | 1.5                            | 1.4                             |
| Liquid Permittivity Repeatability | 0.15                   | N           | 1       | 0.23    | 0.26     | 0.0                            | 0.0                             |
| Liquid Permittivity (target)      | 5.0                    | R           | 1.732   | 0.23    | 0.26     | 0.7                            | 0.8                             |
| Liquid Permittivity (mea.)        | 2.5                    | R           | 1.732   | 0.23    | 0.26     | 0.3                            | 0.4                             |
| Temp. unc. - Permittivity         | 0.83                   | R           | 1.732   | 0.23    | 0.26     | 0.1                            | 0.1                             |
| <b>Combined Std. Uncertainty</b>  |                        |             |         |         |          | 12.5%                          | 12.5%                           |
| <b>Coverage Factor for 95 %</b>   |                        |             |         |         |          | K=2                            | K=2                             |
| <b>Expanded STD Uncertainty</b>   |                        |             |         |         |          | 25.1%                          | 25.0%                           |

**Table 15.3. Uncertainty Budget for frequency range 3 GHz to 6 GHz**



## 16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [13] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015



**Appendix A. Plots of System Performance Check**

The plots are shown as follows.



### System Check\_Head\_835MHz

**DUT: D835V2 - SN:4d091**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL\_835 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.926 \text{ S/m}$ ;  $\epsilon_r = 42.101$ ;  $\rho = 1000 \text{ kg/m}^3$


Ambient Temperature :  $23.6 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.3 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.1, 10.1, 10.1); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM2; Type: SAM; Serial: TP-1542
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $2.96 \text{ W/kg}$

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $49.77 \text{ V/m}$ ; Power Drift =  $-0.01 \text{ dB}$   
Peak SAR (extrapolated) =  $3.11 \text{ W/kg}$   
**SAR(1 g) =  $2.4 \text{ W/kg}$ ; SAR(10 g) =  $1.66 \text{ W/kg}$**   
Maximum value of SAR (measured) =  $2.82 \text{ W/kg}$



### System Check\_Head\_1900MHz

**DUT: D1900V2 - SN:5d118**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL\_1900 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.434$  S/m;  $\epsilon_r = 40.674$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.85, 7.85, 7.85); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.4 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.91 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 18.3 W/kg

**SAR(1 g) = 9.91 W/kg; SAR(10 g) = 5.13 W/kg**

Maximum value of SAR (measured) = 14.3 W/kg



0 dB = 14.3 W/kg = 11.55 dBW/kg

### System Check\_Head\_2600MHz

**DUT: D2600V2 - SN:1061**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL\_2600 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.028$  S/m;  $\epsilon_r = 39.138$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(7.28, 7.28, 7.28); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 21.1 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 70.13 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 29.1 W/kg

**SAR(1 g) = 13.7 W/kg; SAR(10 g) = 6.06 W/kg**

Maximum value of SAR (measured) = 21.0 W/kg



0 dB = 12.1 W/kg = 13.22 dBW/kg

### System Check\_Body\_835MHz

#### DUT: D835V2 - SN:4d091


Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium: MSL\_835 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.991 \text{ S/m}$ ;  $\epsilon_r = 53.953$ ;  $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature :  $23.5 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.8 \text{ }^\circ\text{C}$

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $2.88 \text{ W/kg}$

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $47.24 \text{ V/m}$ ; Power Drift =  $-0.08 \text{ dB}$   
Peak SAR (extrapolated) =  $2.90 \text{ W/kg}$   
**SAR(1 g) =  $2.34 \text{ W/kg}$ ; SAR(10 g) =  $1.66 \text{ W/kg}$**   
Maximum value of SAR (measured) =  $2.72 \text{ W/kg}$



0 dB =  $2.72 \text{ W/kg}$  =  $4.35 \text{ dBW/kg}$

### System Check\_Body\_1900MHz

#### DUT: D1900V2 - SN:5d118


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.527$  S/m;  $\epsilon_r = 53.985$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.55, 7.55, 7.55); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 14.0 W/kg

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 84.86 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 17.6 W/kg  
**SAR(1 g) = 9.77 W/kg; SAR(10 g) = 5.1 W/kg**  
Maximum value of SAR (measured) = 14.0 W/kg



0 dB = 14.0 W/kg = 11.46 dBW/kg

### System Check\_MSL\_2600MHz

**DUT: D2600V2 - SN:1061**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: MSL\_2600 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.233$  S/m;  $\epsilon_r = 51.566$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.13, 7.13, 7.13); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 22.1 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 71.32 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 30.4 W/kg

**SAR(1 g) = 14 W/kg; SAR(10 g) = 6.18 W/kg**

Maximum value of SAR (measured) = 22.0 W/kg



0 dB = 22.0 W/kg = 13.42 dBW/kg



**Appendix B. Plots of SAR Measurement**

The plots are shown as follows.

### 01\_GSM850\_GPRS 1 Tx slot\_Left Cheek\_0mm\_Ch189

Communication System: UID 0, General GSM (0); Frequency: 836.4 MHz; Duty Cycle: 1:8.3

Medium: HSL\_835 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.927$  S/m;  $\epsilon_r = 42.087$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.1, 10.1, 10.1); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM2; Type: SAM; Serial: TP-1542
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch189/Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.296 W/kg



**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.673 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.289 W/kg

**SAR(1 g) = 0.250 W/kg; SAR(10 g) = 0.203 W/kg**

Maximum value of SAR (measured) = 0.270 W/kg



0 dB = 0.270 W/kg = -5.69 dBW/kg



### 02\_GSM 1900\_GSM 1 Tx slot\_Right Cheek\_0mm\_Ch810


Communication System: UID 0, General GSM (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900 Medium parameters used:  $f = 1909.8$  MHz;  $\sigma = 1.445$  S/m;  $\epsilon_r = 40.625$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.85, 7.85, 7.85); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch810/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.177 W/kg

**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 3.628 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 0.200 W/kg  
**SAR(1 g) = 0.148 W/kg; SAR(10 g) = 0.081 W/kg**  
Maximum value of SAR (measured) = 0.167 W/kg



0 dB = 0.167 W/kg = -7.77 dBW/kg

### 03\_WCDMA V\_RMC 12.2Kbps\_Left Cheek\_0mm\_Ch4132


Communication System: UID 0, UMTS (0); Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: HSL\_835 Medium parameters used (interpolated):  $f = 826.4$  MHz;  $\sigma = 0.917$  S/m;  $\epsilon_r = 42.217$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.3 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.1, 10.1, 10.1); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM2; Type: SAM; Serial: TP-1542
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch4132/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.354 W/kg

**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 7.123 V/m; Power Drift = 0.06 dB  
Peak SAR (extrapolated) = 0.358 W/kg  
**SAR(1 g) = 0.307 W/kg; SAR(10 g) = 0.247 W/kg**  
Maximum value of SAR (measured) = 0.335 W/kg



0 dB = 0.335 W/kg = -4.75 dBW/kg

### 04\_WCDMA II\_RMC 12.2Kbps\_Right Cheek\_0mm\_Ch9400


Communication System: UID 0, UMTS (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.412$  S/m;  $\epsilon_r = 40.769$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.85, 7.85, 7.85); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch9400/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.388 W/kg

**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 5.602 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 0.449 W/kg  
**SAR(1 g) = 0.331 W/kg; SAR(10 g) = 0.181 W/kg**  
Maximum value of SAR (measured) = 0.371 W/kg



0 dB = 0.371 W/kg = -4.31 dBW/kg

**05\_LTE Band 5\_10M\_QPSK\_1RB\_25Offset\_Left Cheek\_0mm\_Ch20525**



Communication System: UID 0, FDD\_LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_835 Medium parameters used (interpolated):  $f = 836.5$  MHz;  $\sigma = 0.927$  S/m;  $\epsilon_r = 42.086$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.1, 10.1, 10.1); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM2; Type: SAM; Serial: TP-1542
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch20525/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.355 W/kg

**Ch20525/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 6.638 V/m; Power Drift = 0.08 dB  
Peak SAR (extrapolated) = 0.373 W/kg  
**SAR(1 g) = 0.320 W/kg; SAR(10 g) = 0.258 W/kg**  
Maximum value of SAR (measured) = 0.346 W/kg



0 dB = 0.346 W/kg = -4.61 dBW/kg

**06\_LTE Band 41\_20M\_QPSK\_1RB\_49Offset\_Right Cheek\_0mm\_Ch40340**

Communication System: UID 0, TDD\_LTE (0); Frequency: 2565 MHz; Duty Cycle: 1:1.59  
Medium: HSL\_2600 Medium parameters used:  $f = 2565$  MHz;  $\sigma = 1.987$  S/m;  $\epsilon_r = 39.273$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(7.28, 7.28, 7.28); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch40340/Area Scan (81x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.431 W/kg



**Ch40340/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.07 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.370 W/kg

**SAR(1 g) = 0.268 W/kg; SAR(10 g) = 0.159 W/kg**

Maximum value of SAR (measured) = 0.333 W/kg



0 dB = 0.333 W/kg = -4.78 dBW/kg

### 07\_GSM 850\_GSM 1 Tx slot\_Left Side\_10mm\_Ch189

Communication System: UID 0, General GSM (0); Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_835 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.992$  S/m;  $\epsilon_r = 53.938$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.8 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch189/Area Scan (41x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.465 W/kg


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.11 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.450 W/kg

**SAR(1 g) = 0.383 W/kg; SAR(10 g) = 0.287 W/kg**

Maximum value of SAR (measured) = 0.431 W/kg



0 dB = 0.431 W/kg

**08\_GSM 1900\_GSM 1 Tx slot\_Bottom Side\_10mm\_Ch512**


Communication System: UID 0, General GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_1900 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.471$  S/m;  $\epsilon_r = 54.167$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.55, 7.55, 7.55); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch512/Area Scan (31x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.31 W/kg

**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 28.35 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 1.36 W/kg  
**SAR(1 g) = 0.793 W/kg; SAR(10 g) = 0.414 W/kg**  
Maximum value of SAR (measured) = 1.10 W/kg



0 dB = 1.10 W/kg = 0.41 dBW/kg

**09\_WCDMA V\_RMC 12.2Kbps\_Left Side\_10mm\_Ch4132**


Communication System: UID 0, UMTS (0); Frequency: 826.4 MHz; Duty Cycle: 1:1  
 Medium: MSL\_835 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.982$  S/m;  $\epsilon_r = 54.034$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.8 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch4132/Area Scan (41x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
 Maximum value of SAR (interpolated) = 0.549 W/kg

**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 21.41 V/m; Power Drift = -0.02 dB  
 Peak SAR (extrapolated) = 0.527 W/kg  
**SAR(1 g) = 0.449 W/kg; SAR(10 g) = 0.336 W/kg**  
 Maximum value of SAR (measured) = 0.505 W/kg





### 10\_WCDMA II\_RMC 12.2Kbps\_Bottom Side\_10mm\_Ch9262

Communication System: UID 0, UMTS (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL\_1900\_161027 Medium parameters used:  $f = 1852.4$  MHz;  $\sigma = 1.473$  S/m;  $\epsilon_r = 54.158$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.55, 7.55, 7.55); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch9262/Area Scan (41x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg


**Ch9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.13 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.778 W/kg; SAR(10 g) = 0.403 W/kg**

Maximum value of SAR (measured) = 1.09 W/kg



0 dB = 1.09 W/kg = 0.37 dBW/kg

### 11\_LTE Band 5\_10M\_QPSK\_1RB\_25Offset\_Left Side\_10mm\_Ch20525

Communication System: UID 0, FDD\_LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: MSL\_835 Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.992 \text{ S/m}$ ;  $\epsilon_r = 53.936$ ;  $\rho = 1000$

$\text{kg/m}^3$

Ambient Temperature :  $23.5 \text{ }^\circ\text{C}$  ; Liquid Temperature :  $22.8 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch20525/Area Scan (41x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $0.219 \text{ W/kg}$



**Ch20525/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $13.66 \text{ V/m}$ ; Power Drift =  $0.07 \text{ dB}$

Peak SAR (extrapolated) =  $0.499 \text{ W/kg}$

**SAR(1 g) =  $0.408 \text{ W/kg}$ ; SAR(10 g) =  $0.298 \text{ W/kg}$**

Maximum value of SAR (measured) =  $0.447 \text{ W/kg}$



0 dB =  $0.447 \text{ W/kg}$

**12\_LTE Band 41\_20M\_QPSK\_1RB\_49Offset\_Front\_10mm\_Ch41140**

Communication System: UID 0, TDD\_LTE (0); Frequency: 2645 MHz; Duty Cycle: 1:1.59  
 Medium: MSL\_2600 Medium parameters used:  $f = 2645$  MHz;  $\sigma = 2.299$  S/m;  $\epsilon_r = 51.383$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C


DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.13, 7.13, 7.13); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch41140/Area Scan (81x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
 Maximum value of SAR (interpolated) = 1.34 W/kg

**Ch41140/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 6.659 V/m; Power Drift = 0.14 dB  
 Peak SAR (extrapolated) = 1.89 W/kg  
**SAR(1 g) = 0.963 W/kg; SAR(10 g) = 0.502 W/kg**  
 Maximum value of SAR (measured) = 1.39 W/kg

**Ch41140/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 6.659 V/m; Power Drift = 0.14 dB  
 Peak SAR (extrapolated) = 1.58 W/kg  
**SAR(1 g) = 0.824 W/kg; SAR(10 g) = 0.443 W/kg**  
 Maximum value of SAR (measured) = 1.17 W/kg



0 dB = 1.39 W/kg = 1.43 dBW/kg

### 13\_GSM 850\_GSM 1 Tx slot\_Front\_10mm\_Ch189

Communication System: UID 0, General GSM (0); Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_835 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.992$  S/m;  $\epsilon_r = 53.938$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.8 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch189/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.383 W/kg



**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.57 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.348 W/kg

**SAR(1 g) = 0.324 W/kg; SAR(10 g) = 0.268 W/kg**

Maximum value of SAR (measured) = 0.344 W/kg



0 dB = 0.344 W/kg = -4.63 dBW/kg

### 14\_GSM 1900\_GSM 1 Tx slot\_Front\_10mm\_Ch810


Communication System: UID 0, General GSM (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_1900 Medium parameters used:  $f = 1909.8$  MHz;  $\sigma = 1.539$  S/m;  $\epsilon_r = 53.953$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.55, 7.55, 7.55); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch810/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.913 W/kg

**Ch810/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 5.652 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 1.11 W/kg  
**SAR(1 g) = 0.634 W/kg; SAR(10 g) = 0.322 W/kg**  
Maximum value of SAR (measured) = 0.899 W/kg



0 dB = 0.899 W/kg = -0.46 dBW/kg

### 15\_WCDMA V\_RMC 12.2Kbps\_Back\_10mm\_Ch4132


Communication System: UID 0, UMTS (0); Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium: MSL\_835 Medium parameters used:  $f = 826.4$  MHz;  $\sigma = 0.982$  S/m;  $\epsilon_r = 54.034$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.8 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch4132/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.391 W/kg

**Ch4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 19.35 V/m; Power Drift = -0.16 dB  
Peak SAR (extrapolated) = 0.359 W/kg  
**SAR(1 g) = 0.332 W/kg; SAR(10 g) = 0.276 W/kg**  
Maximum value of SAR (measured) = 0.354 W/kg



0 dB = 0.354 W/kg = -4.51 dBW/kg

### 16\_WCDMA II\_RMC 12.2Kbps\_Front\_10mm\_Ch9400


Communication System: UID 0, UMTS (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium: MSL\_1900 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.504$  S/m;  $\epsilon_r = 54.057$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.55, 7.55, 7.55); Calibrated: 2016.5.25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2016.5.18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch9400/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.812 W/kg

**Ch9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 5.599 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 1.11 W/kg  
**SAR(1 g) = 0.641 W/kg; SAR(10 g) = 0.333 W/kg**  
Maximum value of SAR (measured) = 0.902 W/kg



0 dB = 0.902 W/kg = -0.45 dBW/kg

### 17\_LTE Band 5\_10M\_QPSK\_1RB\_25Offset\_Fron\_10mm\_Ch20525

Communication System: UID 0, FDD\_LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: MSL\_835 Medium parameters used:  $f = 836.5$  MHz;  $\sigma = 0.992$  S/m;  $\epsilon_r = 53.936$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3954; ConvF(10.17, 10.17, 10.17); Calibrated: 2015.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1279; Calibrated: 2016.4.4
- Phantom: SAM1; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch20525/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.378 W/kg



**Ch20525/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.40 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.354 W/kg

**SAR(1 g) = 0.269 W/kg; SAR(10 g) = 0.171 W/kg**

Maximum value of SAR (measured) = 0.318 W/kg



0 dB = 0.318 W/kg = -4.98 dBW/kg