

# FCC SAR Test Report

APPLICANT : Motorola Mobility LLC  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : 10713  
FCC ID : IHDT56WC5  
STANDARD : FCC 47 CFR Part 2 (2.1093)  
ANSI/IEEE C95.1-1992  
IEEE 1528-2013

We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.



Prepared by: Mark Qu / Manager



Approved by: Jones Tsai / Manager

**Sporton International (KunShan) INC.**  
**No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China**



**Table of Contents**

**1. Statement of Compliance ..... 4**

**2. Administration Data ..... 5**

**3. Guidance Applied..... 5**

**4. Equipment Under Test (EUT) Information ..... 6**

    4.1 General Information ..... 6

    4.2 General LTE SAR Test and Reporting Considerations ..... 7

**5. Re-use of Measured Data ..... 8**

    5.1 Introduction Section ..... 8

    5.2 Difference Section..... 8

    5.3 Spot Check Verification Data Section..... 9

    5.4 Reference detail Section ..... 9

**6. Simultaneous Transmission Analysis.....10**

    6.1 Head Exposure Conditions Head Exposure Conditions ..... 11

    6.2 Hotspot Exposure Conditions.....12

    6.3 Body-Worn Accessory Exposure Conditions ..... 14

**Appendix A. Reference Report**





**1. Statement of Compliance**

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, 10713** are as follows.

Equipment Class	Frequency Band		Highest SAR Summary			Highest Simultaneous Transmission 1g SAR (W/kg)
			Head (Separation 0mm)	Hotspot (Separation 10mm)	Body-worn (Separation 10mm)	
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.52	<b>1.20</b>	<b>1.20</b>	1.56
		GSM1900	0.27	0.41	0.41	
	WCDMA	Band V	0.35	0.68	0.68	
		Band II	0.55	0.78	0.78	
	LTE	Band 5	0.38	0.75	0.75	
		Band 7	0.36	0.69	0.69	
		Band 38	0.22	0.40	0.39	
DTS	WLAN	2.4GHz WLAN	<b>1.10</b>	0.27	0.27	1.56
Date of Testing:			2017/2/22 ~ 2017/3/7			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



## 2. Administration Data

Testing Site	
Test Site	Sporton International (KunShan) INC.
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

**4. Equipment Under Test (EUT) Information**

**4.1 General Information**

Product Feature & Specification	
<b>Equipment Name</b>	Mobile Cellular Phone
<b>Brand Name</b>	Motorola
<b>Model Name</b>	10713
<b>FCC ID</b>	IHDT56WC5
<b>Wireless Technology and Frequency Range</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
<b>Mode</b>	<ul style="list-style-type: none"> <li>· GSM/GPRS/EGPRS</li> <li>· RMC/AMR 12.2Kbps</li> <li>· HSDPA</li> <li>· HSUPA</li> <li>· DC-HSDPA</li> <li>· HSPA+</li> <li>· LTE</li> <li>· 802.11b/g/n HT20</li> <li>· Bluetooth v3.0 + EDR, Bluetooth v4.0 LE, Bluetooth v4.1 LE, Bluetooth v4.2 LE</li> <li>· NFC</li> </ul>
<b>HW Version</b>	WKGMA1A4-3
<b>SW Version</b>	woods- userdebug 7.0 NMA25.27 314 intcfg,test-keys
<b>GSM / (E)GPRS Transfer mode</b>	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
<b>EUT Stage</b>	Identical Prototype
<b>Remark:</b>	
<ol style="list-style-type: none"> <li>1. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.</li> <li>2. 802.11n-HT40 is not supported in 2.4GHz WLAN.</li> <li>3. This device 2.4GHz WLAN support hotspot operation.</li> <li>4. This device does not support DTM operation and support GRPS/EGRPS mode up to multi-slot class 12.</li> <li>5. This product has two kinds of battery options, the capacity are the same only different manufacturer, therefore RF exposure evaluation only selected battery1 performed SAR testing.</li> </ol>	



**4.2 General LTE SAR Test and Reporting Considerations**

Summarized necessary items addressed in KDB 941225 D05 v02r05																																															
FCC ID	IHDT56WC5																																														
Equipment Name	Mobile Cellular Phone																																														
Operating Frequency Range of each LTE transmission band	LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz																																														
Channel Bandwidth	LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz																																														
Uplink Modulations Used	QPSK, and 16QAM																																														
LTE Voice / Data requirements	Voice and Data																																														
LTE MPR Permanently Built-in by Design	<table border="1"> <thead> <tr> <th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3</th> </tr> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (RB)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 2</td> </tr> </tbody> </table>	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3								Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3																																															
Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																														
Spectrum Plots for RB Configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																														
LTE Release Version	R9, Cat 4																																														
CA Support	Not Supported																																														

Transmission (H, M, L) channel numbers and frequencies in each LTE band								
LTE Band 5								
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844
LTE Band 7								
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510
M	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560
LTE Band 38								
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580
M	38000	2595	38000	2595	38000	2595	38000	2595
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610



## **5. Re-use of Measured Data**

### **5.1 Introduction Section**

This application re-uses data collected on a similar device. The subject device of this application (Model: 10713, FCC ID: IHDT56WC5) is electrically identical to the reference device (Model: 10714, FCC ID: IHDT56WC6) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 178919 D01.

### **5.2 Difference Section**

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration "PED" file.

The re-used RF data includes the following bands provided in Appendix A (Sporton RF Report No. FA711913 for the reference device Model: 10714, FCC ID: IHDT56WC6):

- GSM850/1900,
- WCDMA Band V/II,
- LTE Band 5/7/38
- 2.4G WLAN
- Bluetooth

Spot check for WWAN and WLAN are performed for ensure that SAR measurement for both device are the same. So, the original SAR value can represent this application.



**5.3 Spot Check Verification Data Section**

Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Original model (FCC ID: IHDT56WC6)				Spot check model (FCC ID: IHDT56WC5)				Deviation
										Average Power (dBm)	Tune-Up Limit (dBm)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Average Power (dBm)	Tune-Up Limit (dBm)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	
WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Right Tilted	0	6	2437	18.36	18.50	1.060	1.095	18.36	18.50	1.050	1.084	-1.00%
GSM 850	-	-	-	-	GPRS 4 Tx slots	Back	10	128	824.2	28.85	29.5	1.030	1.196	28.85	29.5	0.936	1.087	-9.11%
GSM1900	-	-	-	-	GPRS 4 Tx slots	Back	10	810	1909.8	26	26.5	0.361	0.405	26	26.5	0.360	0.404	-0.25%
WCDMA Band V	-	-	-	-	RMC 12.2Kbps	Back	10	4182	836.4	22.99	23.5	0.608	0.684	22.99	23.5	0.579	0.651	-4.82%
WCDMA Band II	-	-	-	-	RMC 12.2Kbps	Back	10	9538	1907.6	23.16	23.5	0.720	0.779	23.16	23.5	0.591	0.639	-17.97%
LTE Band 5	10M	QPSK	1RB	Offset	-	Back	10	20525	836.5	23.25	24.5	0.562	0.749	23.25	24.5	0.540	0.720	-3.87%
LTE Band 7	20M	QPSK	1RB	Offset	-	Front	10	21350	2560	23.42	24	0.605	0.691	23.42	24	0.627	0.717	3.76%
LTE Band 38	20M	QPSK	1RB	Offset	-	Bottom Side	10	38000	2595	22.77	23.5	0.334	0.398	22.77	23.5	0.383	0.456	14.57%

Note: In the table above, all the deviation of SAR test results are compliant with uncertainty budget.

**5.4 Reference detail Section**

Equipment Class	Reference FCC ID	Folder Test/RF Exposure	Report Title/Section
PCE (2G/3G/4G)	IHDT56WC6	RF Exposure(FA711913)	All sections applicable
DTS (BLE)	IHDT56WC6	RF Exposure(FA711913)	All sections applicable
DSS (BER)	IHDT56WC6	RF Exposure(FA711913)	All sections applicable
DTS (WLAN)	IHDT56WC6	RF Exposure(FA711913)	All sections applicable



### 6. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Mobile Cellular Phone			Note
		Head	Body-worn	Hotspot	
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Hotspot
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Hotspot
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Hotspot
5.	GSM Voice + Bluetooth		Yes		
6.	GPRS/EDGE + Bluetooth		Yes		WWAN VoIP
7.	WCDMA + Bluetooth		Yes		WWAN VoIP
8.	LTE + Bluetooth		Yes		WWAN VoIP



**6.1 Head Exposure Conditions Head Exposure Conditions**

WWAN Band		Exposure Position	1	2	1+2 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	
			1g SAR (W/kg)	1g SAR (W/kg)	
GSM	GSM850	Right Cheek	0.502	1.016	1.52
		Right Tilted	0.409	1.095	1.50
		Left Cheek	0.521	0.536	1.06
		Left Tilted	0.344	0.557	0.90
	GSM1900	Right Cheek	0.267	1.016	1.28
		Right Tilted	0.136	1.095	1.23
		Left Cheek	0.165	0.536	0.70
		Left Tilted	0.128	0.557	0.69
WCDMA	Band V	Right Cheek	0.323	1.016	1.34
		Right Tilted	0.196	1.095	1.29
		Left Cheek	0.349	0.536	0.89
		Left Tilted	0.172	0.557	0.73
	Band II	Right Cheek	0.545	1.016	<b>1.56</b>
		Right Tilted	0.229	1.095	1.32
		Left Cheek	0.279	0.536	0.82
		Left Tilted	0.223	0.557	0.78
LTE	Band 5	Right Cheek	0.343	1.016	1.36
		Right Tilted	0.287	1.095	1.38
		Left Cheek	0.375	0.536	0.91
		Left Tilted	0.193	0.557	0.75
	Band 7	Right Cheek	0.334	1.016	1.35
		Right Tilted	0.286	1.095	1.38
		Left Cheek	0.362	0.536	0.90
		Left Tilted	0.272	0.557	0.83
	Band 38	Right Cheek	0.176	1.016	1.19
		Right Tilted	0.126	1.095	1.22
		Left Cheek	0.215	0.536	0.75
		Left Tilted	0.164	0.557	0.72

**6.2 Hotspot Exposure Conditions**

WWAN Band		Exposure Position	1	2	1+2 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	
			1g SAR (W/kg)	1g SAR (W/kg)	
GSM	GSM850	Front	0.808	0.272	1.08
		Back	1.196	0.272	1.47
		Left side	1.144	0.272	1.42
		Right side	0.846		0.85
		Top side		0.272	0.27
		Bottom side	0.102		0.10
	GSM1900	Front	0.292	0.272	0.56
		Back	0.405	0.272	0.68
		Left side	0.107	0.272	0.38
		Right side	0.293		0.29
		Top side		0.272	0.27
		Bottom side	0.368		0.37
WCDMA	Band V	Front	0.459	0.272	0.73
		Back	0.684	0.272	0.96
		Left side	0.541	0.272	0.81
		Right side	0.440		0.44
		Top side		0.272	0.27
		Bottom side	0.075		0.08
	Band II	Front	0.509	0.272	0.78
		Back	0.779	0.272	1.05
		Left side	0.201	0.272	0.47
		Right side	0.643		0.64
		Top side		0.272	0.27
		Bottom side	0.699		0.70

WWAN Band		Exposure Position	1	2	1+2 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	
			1g SAR (W/kg)	1g SAR (W/kg)	
LTE	Band 5	Front	0.520	0.272	0.79
		Back	0.749	0.272	1.02
		Left side	0.619	0.272	0.89
		Right side	0.529		0.53
		Top side		0.272	0.27
		Bottom side	0.085		0.09
	Band 7	Front	0.691	0.272	0.96
		Back	0.593	0.272	0.87
		Left side	0.358	0.272	0.63
		Right side	0.224		0.22
		Top side		0.272	0.27
		Bottom side	0.645		0.65
	Band 38	Front	0.388	0.272	0.66
		Back	0.362	0.272	0.63
		Left side	0.251	0.272	0.52
		Right side	0.140		0.14
		Top side		0.272	0.27
		Bottom side	0.398		0.40



**6.3 Body-Worn Accessory Exposure Conditions**

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	Bluetooth		
			1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)		
GSM	GSM850	Front	0.808	0.272	0.105	1.08	0.91
		Back	1.196	0.272	0.105	1.47	1.30
	GSM1900	Front	0.292	0.272	0.105	0.56	0.40
		Back	0.405	0.272	0.105	0.68	0.51
WCDMA	Band V	Front	0.459	0.272	0.105	0.73	0.56
		Back	0.684	0.272	0.105	0.96	0.79
	Band II	Front	0.509	0.272	0.105	0.78	0.61
		Back	0.779	0.272	0.105	1.05	0.88
LTE	Band 5	Front	0.520	0.272	0.105	0.79	0.63
		Back	0.749	0.272	0.105	1.02	0.85
	Band 7	Front	0.691	0.272	0.105	0.96	0.80
		Back	0.593	0.272	0.105	0.87	0.70
	Band 38	Front	0.388	0.272	0.105	0.66	0.49
		Back	0.362	0.272	0.105	0.63	0.47

Test Engineer : Nick Hu



## ***Appendix A. Reference Report***

Please refer to Sporton report number FA711913 which is issued separately.