



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : 10873
FCC ID : IHDT56WK2
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jun. 17, 2017 and testing was completed on Jul. 18, 2017. We, Sporton International (KunShan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1. GENERAL DESCRIPTION5

 1.1. Applicant.....5

 1.2. Manufacturer5

 1.3. Product Feature of Equipment Under Test5

 1.4. Product Specification of Equipment Under Test6

 1.5. Specification of Accessory7

 1.6. Modification of EUT7

 1.7. Test Location8

 1.8. Applicable Standards8

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....9

 2.1. Test Mode9

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system.....11

 2.4. EUT Operation Test Setup12

3. TEST RESULT.....13

 3.1. Test of AC Conducted Emission Measurement13

 3.2. Test of Radiated Emission Measurement17

4. LIST OF MEASURING EQUIPMENT21

5. UNCERTAINTY OF EVALUATION22

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 11.04 dB at 0.476 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 6.14 dB at 259.50 MHz



1. General Description

1.1. Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	10873
FCC ID	IHDT56WK2
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/ HSPA+ (16QAM uplink is not supported)/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0 + EDR/ Bluetooth v 4.0 LE/ Bluetooth v4.1 LE/ Bluetooth v4.2 LE/ Bluetooth v5.0 LE
IMEI Code	Conduction: 351899080032071/351899080032089 Radiation: 351899080031917/351899080031925
HW Version	DVT2
SW Version	NPW26.75
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 26 : 814.7 MHz ~ 848.3 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5580 MHz and 5660 MHz ~ 5700 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 26 : 859.7 MHz ~ 893.3 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5580 MHz and 5660 MHz ~ 5700 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass: 1602 MHz + n× 0.5625MHz (n=-7,-6,-5,...0,...,6) NFC : 13.56 MHz FM : 87.5 MHz ~ 108 MHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN : Loop Antenna Bluetooth : Loop Antenna GPS/Glonass: Internal Loop Antenna NFC : Frame Loop Antenna FM: External Headset Earphone
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink)

	HSUPA : QPSK (Uplink) HSPA+ : 16QAM (16QAM uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/Glonass : BPSK NFC: ASK FM
--	--

1.5. Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola(Salom)	Model Name	SC-22
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc or 9Vdc or 12Vdc, 3000mA or 1600mA or 1200mA		
AC Adapter 2	Brand Name	Motorola(Chenyang)	Model Name	SC-22
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc or 9Vdc or 12Vdc, 3000mA or 1600mA or 1200mA		
AC Adapter 3	Brand Name	Motorola(LiteOn)	Model Name	SC-22
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc or 9Vdc or 12Vdc, 3000mA or 1600mA or 1200mA		
Battery	Brand Name	Motorola (SUNWODA)	Model Name	HX40
	Power Rating	3.8Vdc,2810mAh	Type	Li-ion
Earphone	Brand Name	Motorola (Cosonic)	Model Name	SH38C16617
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
USB Cable 1	Brand Name	Motorola (Saibao)	Model Name	SKN6473A
	Signal Line Type	1.1 meter, shielded cable, without core		
USB Cable 2	Brand Name	Motorola (Foxlink)	Model Name	SKN6473A
	Signal Line Type	1.1 meter, shielded cable, without core		
USB Cable 3	Brand Name	Motorola (Cabletech)	Model Name	SKN6473A
	Signal Line Type	1.1 meter, shielded cable, without core		

1.6. Modification of EUT

No modifications are made to the EUT during all test items.



1.7. Test Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No is CN5013.

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	CO01-KS	03CH02-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. For FCC 15 Subpart B - Unintentional Radiators, device supporting USB interface or similar peripherals (defined as the Section 15.3 (r) Peripheral device) acting as a peripheral for personal computers shall be authorized as "The Class B personal computers and peripherals" per the Section 15.101 (a) Equipment authorization of unintentional radiators.
3. For other Unintentional Radiators features of this EUT, test reports are be issued separately.
Per the Note of the Section 15.101, when device supports features (USB, FM Radio, digital devices...etc) more than one category of authorization, type of authorization shall be appropriately chosen for FCC 15B compliance rule, and the Section 15.101 (b), only those receivers that operate (tune) within the frequency range of 30-960 MHz, CB receivers and radar detectors are subject to the authorizations shown in paragraph (a) of the Section 15.101. However, receivers indicated as being subject to Declaration of Conformity that are contained within a transceiver, the transmitter portion of which is subject to certification, shall be authorized under the verification procedure.



2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: LTE Band 5 Idle + Earphone + WLAN Idle(2.4G) + Bluetooth Idle + USB Cable 1 (Data Link with Notebook) + GPS Rx + Battery + SIM1
	Mode 2: LTE Band 5 Idle + Earphone + WLAN Idle(5G) + Bluetooth Idle + USB Cable 2 (Data Link with Notebook) + GPS Rx + Battery + SIM2
	Mode 3: LTE Band 5 Idle + Earphone + WLAN Idle(2.4G) + Bluetooth Idle + USB Cable 3 (Data Link with Notebook) + GPS Rx + Battery + SIM1
Radiated Emissions < 1GHz	Mode 1: LTE Band 5 Idle + Earphone + WLAN Idle(5G) + Bluetooth Idle + USB Cable 1 (Data Link with Notebook) + GPS Rx + Battery + SIM1
	Mode 2: LTE Band 5 Idle + Earphone + WLAN Idle(2.4G) + Bluetooth Idle + USB Cable 2 (Data Link with Notebook) + GPS Rx + Battery + SIM2
	Mode 3: LTE Band 5 Idle + Earphone + WLAN Idle(5G) + Bluetooth Idle + USB Cable 3 (Data Link with Notebook) + GPS Rx + Battery + SIM1
Radiated Emissions ≥ 1GHz	Mode 1: LTE Band 5 Idle + Earphone + WLAN Idle(5G) + Bluetooth Idle + USB Cable 3 (Data Link with Notebook) + GPS Rx + Battery + SIM 1
Remark:	
<ol style="list-style-type: none"> 1. The worst case of AC is mode 1; only the test data of this mode was reported. 2. The worst case of RE < 1G is mode 3; only the test data of this mode was reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 	

2.2. Connection Diagram of Test System





2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	GPS Station	ADIVIE	MP9000	N/A	N/A	Unshielded, 1.8m
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
4.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
5.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
6.	Notebook	Lenovo	G480	PRC4	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
7.	Bluetooth Earphone	Samsung	HS3000	A3LHS3000	N/A	N/A
8.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
9.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
10.	iPod	Apple	MC525 ZP/A	DoC	Shielded, 1.0m	N/A
11.	SD Card	Kingston	MicroSD HC	FCC DoC	N/A	N/A
12.	SD Card	Kingston	8GB	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive GPS signals.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 5 Idle + Earphone + WLAN Idle(2.4G) + Bluetooth Idle + USB Cable 1 (Data Link with Notebook) + GPS Rx + Battery + SIM1		




Site : CO01-KS
Condition : FCC CLASS-B LISN-L-161017-060103 LINE

mode : Mode 1
: 351899080032071/351899080032089 #5

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.160	38.07	-27.40	65.47	27.20	0.49	10.38	QP
2	0.160	23.77	-31.70	55.47	12.90	0.49	10.38	Average
3	0.168	37.11	-27.97	65.08	26.30	0.44	10.37	QP
4	0.168	22.31	-32.77	55.08	11.50	0.44	10.37	Average
5	0.176	36.06	-28.62	64.68	25.30	0.40	10.36	QP
6	0.176	21.36	-33.32	54.68	10.60	0.40	10.36	Average
7	0.207	32.20	-31.12	63.32	21.60	0.27	10.33	QP
8	0.207	21.80	-31.52	53.32	11.20	0.27	10.33	Average
9	0.442	35.06	-21.96	57.02	24.60	0.27	10.19	QP
10 *	0.442	34.66	-12.36	47.02	24.20	0.27	10.19	Average
11	0.481	34.66	-21.66	56.32	24.20	0.27	10.19	QP
12	0.481	32.76	-13.56	46.32	22.30	0.27	10.19	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 5 Idle + Earphone + WLAN Idle(2.4G) + Bluetooth Idle + USB Cable 1 (Data Link with Notebook) + GPS Rx + Battery + SIM1		



Site : CO01-KS
Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL

mode : Mode 1
: 351899080032071/351899080032089 #5

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.154	39.03	-26.75	65.78	28.30	0.34	10.39	QP
2	0.154	28.23	-27.55	55.78	17.50	0.34	10.39	Average
3	0.161	37.32	-28.11	65.43	26.60	0.34	10.38	QP
4	0.161	23.92	-31.51	55.43	13.20	0.34	10.38	Average
5	0.169	36.30	-28.69	64.99	25.59	0.34	10.37	QP
6	0.169	23.00	-31.99	54.99	12.29	0.34	10.37	Average
7	0.178	34.99	-29.60	64.59	24.30	0.33	10.36	QP
8	0.178	21.99	-32.60	54.59	11.30	0.33	10.36	Average
9	0.206	32.26	-31.10	63.36	21.60	0.33	10.33	QP
10	0.206	21.96	-31.40	53.36	11.30	0.33	10.33	Average
11	0.476	36.17	-20.24	56.41	25.60	0.38	10.19	QP
12 *	0.476	35.37	-11.04	46.41	24.80	0.38	10.19	Average



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	24~25°C
Test Engineer :	Fuquan Wu	Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 5 Idle + Earphone + WLAN Idle(5G) + Bluetooth Idle + USB Cable 3 (Data Link with Notebook) + GPS Rx + Battery + SIM 1		
Remark :	#7 is system simulator signal which can be ignored.		




Condition : FCC CLASS-B 3m LF_ANT41909_6 HORIZONTAL

Mode : Mode 3
 IMEI : 351899080031917/351899080031925
 Plane : Y
 : #2

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	23.63	-16.37	40.00	30.25	25.10	0.25	31.97	---	---	Peak
2	174.72	32.93	-10.57	43.50	46.40	16.58	1.38	31.43	---	---	Peak
3	259.50	39.86	-6.14	46.00	51.23	18.13	1.74	31.24	100	150	Peak
4	345.50	37.75	-8.25	46.00	46.84	20.04	2.08	31.21	---	---	Peak
5	497.40	32.90	-13.10	46.00	38.70	23.01	2.42	31.23	---	---	Peak
6	750.10	33.03	-12.97	46.00	35.21	26.00	3.03	31.21	---	---	Peak
7	881.00	39.98			39.64	28.17	3.34	31.17	---	---	Peak
8	2348.00	44.76	-29.24	74.00	68.78	27.24	5.59	56.85	---	---	Peak
9	4178.00	44.58	-29.42	74.00	64.68	30.19	7.19	57.48	---	---	Peak
10	6172.00	45.08	-28.92	74.00	59.83	33.37	8.59	56.71	---	---	Peak
11	8502.00	40.84	-33.16	74.00	48.82	37.20	9.61	54.79	---	---	Peak
12	10352.00	49.38	-24.62	74.00	56.60	38.68	10.53	56.43	---	---	Peak
13	13166.00	49.86	-24.14	74.00	55.11	39.71	12.12	57.08	100	150	Peak



Test Mode :	Mode 3	Temperature :	24~25°C
Test Engineer :	Fuquan Wu	Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 5 Idle + Earphone + WLAN Idle(5G) + Bluetooth Idle + USB Cable 3 (Data Link with Notebook) + GPS Rx + Battery + SIM 1		
Remark :	#6 is system simulator signal which can be ignored.		



Condition : FCC CLASS-B 3m LF_ANT41909_6 VERTICAL

Mode : Mode 3
IMEI : 351899080031917/351899080031925
Plane : Y
 : #2

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	175.53	34.62	-8.88	43.50	48.15	16.52	1.38	31.43	100	250	Peak
2	263.55	33.77	-12.23	46.00	44.98	18.27	1.75	31.23	---	---	Peak
3	298.92	33.54	-12.46	46.00	43.44	19.47	1.85	31.22	---	---	Peak
4	471.50	34.16	-11.84	46.00	40.88	22.18	2.36	31.26	---	---	Peak
5	708.80	32.64	-13.36	46.00	35.10	25.84	2.95	31.25	---	---	Peak
6	881.70	41.33	---	---	40.98	28.18	3.34	31.17	---	---	Peak
7	983.90	30.78	-23.22	54.00	29.41	29.17	3.53	31.33	---	---	Peak
8	2372.00	49.84	-24.16	74.00	73.69	27.37	5.59	56.81	100	250	Peak
9	3988.00	43.45	-30.55	74.00	63.86	29.90	7.22	57.53	---	---	Peak
10	5984.00	45.92	-28.08	74.00	60.76	33.07	8.47	56.38	---	---	Peak
11	8346.00	37.80	-36.20	74.00	46.18	37.23	9.45	55.06	---	---	Peak
12	10356.00	46.72	-27.28	74.00	53.94	38.68	10.53	56.43	---	---	Peak
13	13463.00	48.63	-25.37	74.00	53.26	40.24	12.24	57.11	---	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 20, 2017	Jul. 05, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Jul. 05, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Jul. 05, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Jul. 05, 2017	Oct. 12, 2017	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 09, 2016	Jul. 18, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44G,MAX 30dB	Apr. 18, 2017	Jul. 18, 2017	Apr. 17, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz-2GHz	Aug. 20, 2016	Jul. 18, 2017	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Jul. 18, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz ~40GHz	Feb. 15, 2017	Jul. 18, 2017	Feb. 14, 2018	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18~40GHz	Oct. 13, 2016	Jul. 18, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 09, 2016	Jul. 18, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1-26.5GHz Gain 30dB	Oct. 13, 2016	Jul. 18, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Jul. 18, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jul. 18, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jul. 18, 2017	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required.



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3dB
---	-------