



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT1924-3
FCC ID : IHDT56XA6
STANDARD : 47 CFR Part 2, 22(H), 27(M)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 22, 2017 and completely tested on Jan. 25, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI/TIA-603-E and the testing has shown the tested sample to be in compliance with the applicable technical standards. This report contains data that were produced under subcontract by Laboratory SPORTON INTERNATIONAL INC.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

***No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China***



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Specification of Accessory	7
1.7 Re-use of Measured Data	8
1.8 Maximum EIRP Power, Frequency Tolerance, and Emission Designator	9
1.9 Testing Location	10
1.10 Applicable Standards.....	11
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	12
2.1 Test Mode	12
2.2 Connection Diagram of Test System.....	13
2.3 Support Unit used in test configuration and system	13
2.4 Measurement Results Explanation Example.....	13
2.5 Frequency List of Low/Middle/High Channels	14
3 CONDUCTED TEST ITEMS	15
3.1 Measuring Instruments	15
3.2 Test Setup	15
3.3 Test Result of Conducted Test	15
3.4 Conducted Output Power and EIRP	16
3.5 Peak-to-Average Ratio	17
3.6 Occupied Bandwidth	18
3.7 Conducted Band Edge	19
3.8 Conducted Spurious Emission	21
3.9 Frequency Stability	22
4 RADIATED TEST ITEMS	23
4.1 Measuring Instruments	23
4.2 Test Setup	23
4.3 Test Result of Radiated Test	23
4.4 Radiated Spurious Emission	24
5 LIST OF MEASURING EQUIPMENT	25
6 UNCERTAINTY OF EVALUATION	26
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	
APPENDIX D. REFERENCE REPORT	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG7D2201-01B	Rev. 01	Initial issue of report	Mar. 06, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 38) (Band 41)	EIRP < 2Watt	PASS	-
3.5	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§27.53(m)(4)	Conducted Band Edge Measurement (Band 38) (Band 41)	§27.53(m)(4)	PASS	-
3.8	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 38) (Band 41)	< 55+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 38) (Band 41)	< 55+10log ₁₀ (P[Watts])	PASS	Under limit 16.53 dB at 7758.000 MHz



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1924-3
FCC ID	IHDT56XA6
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+(16 QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v3.0+EDR/ Bluetooth v4.0 LE/ Bluetooth v4.1 LE/ Bluetooth v4.2 LE
IMEI Code	Conducted: 351876090030956/351876090030964 Radiation: 351876090027473/ 351876090027481
HW Version	DVT1B
SW Version	ahannah-userdebug 8.0.0 OPP27.60 924 intcfg,test-keys
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz
Rx Frequency	LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz
Bandwidth	LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 7 : 5MHz/ 10MHz / 15MHz / 20MHz LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 41 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 38 : 23.54 dBm LTE Band 41 : 23.76 dBm
Antenna Gain	LTE Band 38 : 0.48 dBi LTE Band 41 : 0.55 dBi
Type of Modulation	QPSK / 16QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Acbel)	Model Name	SPN5945A C-P35
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 1(EU)	Brand Name	Motorola (Acbel)	Model Name	SPN5944A C-P36
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 1(UK)	Brand Name	Motorola (Acbel)	Model Name	SPN5940A C-P37
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 1(IN)	Brand Name	Motorola (Acbel)	Model Name	SA18C19493 C-P49
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 2(US)	Brand Name	Motorola (Salom)	Model Name	SSW-2919UMTJ C-P35 SPN5945A
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 2(EU)	Brand Name	Motorola (Salom)	Model Name	SSW-2919EU C-P36 SPN5944A
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 2(UK)	Brand Name	Motorola (Salom)	Model Name	SSW-2919UK C-P37 SPN5940A
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5Vdc, 2000mA		
Battery	Brand Name	Motorola (Amperex)	Model Name	HE50
	Power Rating	3.8Vdc,4850/5000mAh	Type	Li-ion
Earphone	Brand Name	Motorola (NEW Leaders)	Model Name	NLD-EM300V-01SF
	Signal Line Type	1.2 meter, non-shielded cable, without ferrite core		
USB Cable	Brand Name	Motorola (Saibao)	Model Name	SLQ-A081A
	Signal Line Type	1.0 meter, non-shielded cable, without ferrite core		



1.7 Re-use of Measured Data

1.7.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: XT1924-3, FCC ID: IHDT56XA6) is electrically identical to the reference device (Model: XT1924-4, XT1924-5, FCC ID: IHDT56XA5) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 178919 D01.

1.7.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., some difference of population/depopulation to enable support of different cellular bands, please refer to the Product Equality Declaration.

The re-used RF data includes the following bands provided in Appendix D (Sporton RF Report No. FG7D2201B for the reference device Model: XT1924-4, XT1924-5, FCC ID: IHDT56XA5):

1.7.3 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, spot check measurements were performed on the subject device for radiated spurious emission, Conducted Band-edge and Conducted spurious emission, the test result were consistent with FCC ID: IHDT56XA5 and added new Band 38/41 to full test.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination that verification test data are sufficient to support it.

1.7.4 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
PCE (2G/3G)	IHDT56XA5	Part22H.24E (FG7D2201A)	All sections applicable for GSM 850/1900/WCDMA Band II/V
PCE (LTE)	IHDT56XA5	Part22H.24E.27L.27M (FG7D2201B)	All sections applicable for LTE Band 5/7



1.8 Maximum EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 38		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2572.5 ~ 2617.5	4M50G7D	-	0.2472	4M53W7D	-	0.1782
10	2575.0 ~ 2615.0	9M09G7D	0.0018	0.2443	9M09W7D	-	0.1746
15	2577.5 ~ 2612.5	13M5G7D	-	0.2523	13M4W7D	-	0.1807
20	2580.0 ~ 2610.0	18M4G7D	-	0.2472	18M3W7D	-	0.1762
LTE Band 41		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2537.5 ~ 2652.5	4M52G7D	-	0.2547	4M49W7D	-	0.1754
10	2540.0 ~ 2650.0	9M01G7D	0.0022	0.2432	9M03W7D	-	0.1687
15	2542.5 ~ 2647.5	13M5G7D	-	0.2449	13M4W7D	-	0.1782
20	2545.0 ~ 2645.0	18M3G7D	-	0.2698	18M3W7D	-	0.1807

1.9 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.	
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	TH01-KS	630927

SPORTON INTERNATIONAL INC. is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and under the FCC-recognized accredited testing laboratories by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No.58, Aly. 75, Ln. 564 Wenhua 3rd Rd. Guishan Dist. Taoyuan City Taiwan TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	03CH12-HY	TW0007	214511

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. Test data subcontracted: radiated spurious emissions in section 4.4 of this report.



1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 27(M)
- ♦ ANSI/TIA-603-E
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
	38	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Peak-to-Average Ratio	38	-	-				✓	✓	✓	✓		✓	✓	✓	✓
	41	-	-				✓	✓	✓	✓		✓	✓	✓	✓
26dB and 99% Bandwidth	38	-	-	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
Conducted Band Edge	38	-	-	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
Conducted Spurious Emission	38	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
Frequency Stability	38	-	-		✓			✓				✓		✓	
	41	-	-		✓			✓				✓		✓	
E.I.R.P.	38	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
Radiated Spurious Emission	38	-	-	✓	✓	✓	✓	✓		✓				✓	
	41	-	-	✓	✓	✓	✓	✓		✓				✓	
Note	- The mark “✓” means that this configuration is chosen for testing - The mark “-” means that this bandwidth is not supported. - The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different BW/RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

$Offset = RF \text{ cable loss.}$

Following shows an offset computation example with cable loss 5.4 dB.

Example :

$Offset(dB) = RF \text{ cable loss}(dB).$

$= 5.4 \text{ (dB)}$

2.5 Frequency List of Low/Middle/High Channels

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5

LTE Band 41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	40140	40640	41140
	Frequency	2545	2595	2645
15	Channel	40115	40640	41165
	Frequency	2542.5	2595	2647.5
10	Channel	40090	40640	41190
	Frequency	2540	2595	2650
5	Channel	40065	40640	41215
	Frequency	2537.5	2595	2652.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and EIRP

3.4.1 Description of the Conducted Output Power Measurement and EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 38, and Band 41.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 4.1 and 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq$ 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Offset has included the duty factor for LTE Band 38/41. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle.
9. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

10. For LTE Band 38, 41, the other 40 dB, and 55 dB have additionally applied same calculation above.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 38,41:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Offset has included the duty factor for LTE Band 38/41. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle.
9. Taking the record of maximum spurious emission.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10 \log (P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10 \log (P)]$ (dB)
= $[30 + 10 \log (P)]$ (dBm) - $[43 + 10 \log (P)]$ (dB)
= -13dBm.
12. For Band 38, 41
The limit line is derived from $55 + 10 \log (P)$ dB below the transmitter power P(Watts)
= $P(W) - [55 + 10 \log (P)]$ (dB)
= $[30 + 10 \log (P)]$ (dBm) - $[55 + 10 \log (P)]$ (dB)
= -25dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v03 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v03 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 38, 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-E Section 2.2.12.
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)\text{dB}$ below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

13. For Band 38, 41:

The limit line is derived from $55 + 10\log(P)\text{dB}$ below the transmitter power P(Watts)
 $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
 $ERP \text{ (dBm)} = EIRP - 2.15$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Dec. 28, 2017~ Jan. 25, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Radio communication analyzer	Anritsu	MT8820C	6201300652	2G/3G/LTE_ full band	Aug. 08, 2017	Dec. 28, 2017~ Jan. 25, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Thermal Chamber	Hongzhan	LP-150U	HZ014011440	-40~+150°C 20%~95%RH	Apr. 18, 2017	Dec. 28, 2017~ Jan. 25, 2018	Apr. 17, 2018	Conducted (TH01-KS)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VS WR : 2.5:1 max	Jul. 18, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Jul. 17, 2018	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&008	35413&02	30MHz~1GHz	Dec. 18, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Dec. 17, 2018	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 20, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Oct. 19, 2018	Radiation (03CH12-HY)
Hygrometer	TECEPEL	DTM-303B	TP140349	N/A	Oct. 12, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Oct. 11, 2018	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 23, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Mar. 22, 2018	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Jan. 12, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Jan. 11, 2018	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	NCR	Jan. 03, 2018 ~ Jan. 05, 2018	NCR	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-450 0-B	N/A	1m~4m	NCR	Jan. 03, 2018 ~ Jan. 05, 2018	NCR	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	NCR	Jan. 03, 2018 ~ Jan. 05, 2018	NCR	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 27, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Apr. 26, 2018	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9030A	MY52350276	3Hz~44GHz	Mar. 23, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Mar. 22, 2018	Radiation (03CH12-HY)

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.4 dB
---	--------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.0 dB
---	--------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.25	23.17	23.27
20	1	49		23.18	23.45	23.34
20	1	99		23.29	23.19	23.14
20	50	0		22.23	22.29	22.25
20	50	24		22.21	22.24	22.22
20	50	50		22.21	22.12	22.14
20	100	0		22.22	22.24	22.23
20	1	0	16-QAM	21.72	21.67	21.98
20	1	49		21.84	21.94	21.98
20	1	99		21.85	21.96	21.62
20	50	0		21.25	21.31	21.33
20	50	24		21.25	21.15	21.11
20	50	50		21.2	21.11	21.12
20	100	0		21.21	21.26	21.23
15	1	0	QPSK	23.23	23.15	23.16
15	1	37		23.5	23.52	23.54
15	1	74		23.36	23.44	23.13
15	36	0		22.2	22.23	22.15
15	36	20		22.25	22.22	22.3
15	36	39		22.16	22.07	22.05
15	75	0		22.26	22.1	22.06
15	1	0	16-QAM	21.74	21.68	21.7
15	1	37		21.92	22.07	22.09
15	1	74		21.55	22.02	21.75
15	36	0		21.18	21.13	21.17
15	36	20		21.16	21.06	21.13
15	36	39		21.03	21.1	21.1
15	75	0		21.23	21.28	21.13



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.37	23.22	23.32
10	1	25		23.28	23.3	23.24
10	1	49		23.21	23.4	23.27
10	25	0		22.15	22.26	22.24
10	25	12		22.25	22.28	22.23
10	25	25		22.2	22.02	22.09
10	50	0		22.19	22.14	22.15
10	1	0	16-QAM	21.71	21.63	21.86
10	1	25		21.94	21.69	21.9
10	1	49		21.71	21.67	21.58
10	25	0		21.37	21.36	21.42
10	25	12		21.41	21.5	21.35
10	25	25		21.25	21.24	20.95
10	50	0		21.14	21.13	21.1
5	1	0	QPSK	23.1	23.14	23.11
5	1	12		23.37	23.45	23.23
5	1	24		23.28	23.07	23.09
5	12	0		22.07	22	22.16
5	12	7		22.08	22.07	22.22
5	12	13		22.15	22.07	22.23
5	25	0		22.09	21.99	22.18
5	1	0	16-QAM	21.92	21.52	21.9
5	1	12		21.94	22.03	22.03
5	1	24		21.84	21.81	21.87
5	12	0		21.04	21.25	21.21
5	12	7		21.17	21.14	21.22
5	12	13		21.35	21.02	21.25
5	25	0		21.26	21.19	21.36



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.12	23.15	23.08
20	1	49		23.29	23.28	23.76
20	1	99		23.24	23.16	23.02
20	50	0		22.18	22.08	22.19
20	50	24		22.08	22.01	22.07
20	50	50		22.04	22.08	21.94
20	100	0		22.08	22.15	22.11
20	1	0	16-QAM	21.75	21.58	21.81
20	1	49		22.02	21.98	21.74
20	1	99		21.5	21.85	21.48
20	50	0		20.98	21.01	21.06
20	50	24		21.02	21.03	20.96
20	50	50		21.09	20.95	20.94
20	100	0		21.13	21.15	20.93
15	1	0	QPSK	23.1	22.91	23.03
15	1	37		23.32	23.15	23.34
15	1	74		23.1	23.18	22.94
15	36	0		22.13	21.91	22.07
15	36	20		22.15	22.12	22.09
15	36	39		22.1	22.13	21.88
15	75	0		22.11	22.1	21.93
15	1	0	16-QAM	21.69	21.68	21.8
15	1	37		21.76	21.88	21.96
15	1	74		21.44	21.57	21.63
15	36	0		21.05	20.85	20.99
15	36	20		20.96	21.06	20.94
15	36	39		20.94	21.08	20.86
15	75	0		21.09	21.25	21.01



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.21	23.23	23.06
10	1	25		23.31	23.18	23.25
10	1	49		23.06	23.18	23.14
10	25	0		22.12	22.01	22.04
10	25	12		22.08	22.05	21.99
10	25	25		21.94	22.01	21.78
10	50	0		22.12	22.08	21.92
10	1	0	16-QAM	21.54	21.68	21.66
10	1	25		21.71	21.68	21.72
10	1	49		21.55	21.65	21.18
10	25	0		21.25	21.04	21.07
10	25	12		21.28	21.15	21.14
10	25	25		21.11	21.15	20.96
10	50	0		21.08	21.05	21.03
5	1	0	QPSK	23.19	23.08	23.07
5	1	12		23.51	23.22	23.3
5	1	24		23.17	23.25	23.02
5	12	0		22.16	22.01	21.99
5	12	7		22.16	22.08	21.96
5	12	13		22.13	22.13	21.82
5	25	0		22.08	22.12	21.87
5	1	0	16-QAM	21.69	21.67	21.44
5	1	12		21.89	21.58	21.72
5	1	24		21.67	21.68	21.51
5	12	0		20.97	21.35	20.77
5	12	7		21.05	21.02	20.74
5	12	13		20.97	21.08	20.88
5	25	0		21.07	21.21	21.08

**EIRP**

LTE Band 38 ($G_T - L_C = 0.48$ dBi) QPSK									
Bandwidth	5M			10M			15M		
Channel	37775	38000	38225	37800	38000	38200	37825	38000	38175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2572.5	2595	2617.5	2575	2595	2615	2577.5	2595	2612.5
(MHz)									
Conducted Power (dBm)	23.37	23.45	23.23	23.21	23.40	23.27	23.50	23.52	23.54
Conducted Power (Watts)	0.2173	0.2213	0.2104	0.2094	0.2188	0.2123	0.2239	0.2249	0.2259
EIRP(dBm)	23.85	23.93	23.71	23.69	23.88	23.75	23.98	24.00	24.02
EIRP(Watts)	0.2427	0.2472	0.2350	0.2339	0.2443	0.2371	0.2500	0.2512	0.2523

LTE Band 38 ($G_T - L_C = 0.48$ dBi) QPSK			
Bandwidth	20M		
Channel	37850	38000	38150
	(Low)	(Mid)	(High)
Frequency	2580	2595	2610
(MHz)			
Conducted Power (dBm)	23.18	23.45	23.34
Conducted Power (Watts)	0.2080	0.2213	0.2158
EIRP(dBm)	23.66	23.93	23.82
EIRP(Watts)	0.2323	0.2472	0.2410



LTE Band 38 ($G_T - L_C = 0.48$ dBi) 16QAM									
Bandwidth	5M			10M			15M		
Channel	37775	38000	38225	37800	38000	38200	37825	38000	38175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2572.5	2595	2617.5	2575	2595	2615	2577.5	2595	2612.5
(MHz)									
Conducted Power (dBm)	21.94	22.03	22.03	21.94	21.69	21.90	21.92	22.07	22.09
Conducted Power (Watts)	0.1563	0.1596	0.1596	0.1563	0.1476	0.1549	0.1556	0.1611	0.1618
EIRP(dBm)	22.42	22.51	22.51	22.42	22.17	22.38	22.40	22.55	22.57
EIRP(Watts)	0.1746	0.1782	0.1782	0.1746	0.1648	0.1730	0.1738	0.1799	0.1807

LTE Band 38 ($G_T - L_C = 0.48$ dBi) 16QAM			
Bandwidth	20M		
Channel	37850	38000	38150
	(Low)	(Mid)	(High)
Frequency	2580	2595	2610
(MHz)			
Conducted Power (dBm)	21.72	21.67	21.98
Conducted Power (Watts)	0.1486	0.1469	0.1578
EIRP(dBm)	22.20	22.15	22.46
EIRP(Watts)	0.1660	0.1641	0.1762

LTE Band 41 ($G_T - L_C = 0.55$ dBi) QPSK									
Bandwidth	5M			10M			15M		
Channel	40065	40640	41215	40090	40640	41190	40115	40640	41165
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2537.5	2595	2652.5	2540	2595	2650	2542.5	2595	2647.5
(MHz)									
Conducted Power (dBm)	23.51	23.22	23.30	23.31	23.18	23.25	23.32	23.15	23.34
Conducted Power (Watts)	0.2244	0.2099	0.2138	0.2143	0.2080	0.2113	0.2148	0.2065	0.2158
EIRP(dBm)	24.06	23.77	23.85	23.86	23.73	23.80	23.87	23.70	23.89
EIRP(Watts)	0.2547	0.2382	0.2427	0.2432	0.2360	0.2399	0.2438	0.2344	0.2449

LTE Band 41 ($G_T - L_C = 0.55$ dBi) QPSK			
Bandwidth	20M		
Channel	40140	40640	41140
	(Low)	(Mid)	(High)
Frequency	2545	2595	2645
(MHz)			
Conducted Power (dBm)	23.29	23.28	23.76
Conducted Power (Watts)	0.2133	0.2128	0.2377
EIRP(dBm)	23.84	23.83	24.31
EIRP(Watts)	0.2421	0.2415	0.2698

LTE Band 41 ($G_T - L_C = 0.55$ dBi) 16QAM									
Bandwidth	5M			10M			15M		
Channel	40065	40640	41215	40090	40640	41190	40115	40640	41165
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency	2537.5	2595	2652.5	2540	2595	2650	2542.5	2595	2647.5
(MHz)									
Conducted Power (dBm)	21.89	21.58	21.72	21.71	21.68	21.72	21.76	21.88	21.96
Conducted Power (Watts)	0.1545	0.1439	0.1486	0.1483	0.1472	0.1486	0.1500	0.1542	0.1570
EIRP(dBm)	22.44	22.13	22.27	22.26	22.23	22.27	22.31	22.43	22.51
EIRP(Watts)	0.1754	0.1633	0.1687	0.1683	0.1671	0.1687	0.1702	0.1750	0.1782

LTE Band 41 ($G_T - L_C = 3.06$ dBi) 16QAM			
Bandwidth	20M		
Channel	40140	40640	41140
	(Low)	(Mid)	(High)
Frequency	2545	2595	2645
(MHz)			
Conducted Power (dBm)	22.02	21.98	21.74
Conducted Power (Watts)	0.1592	0.1578	0.1493
EIRP(dBm)	22.57	22.53	22.29
EIRP(Watts)	0.1807	0.1791	0.1694

**Peak-to-Average Ratio**


Mode	LTE Band 38 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.35	5.94	5.83	6.00	PASS
Middle CH	4.64	5.04	5.54	6.61	
Highest CH	4.41	6.70	5.59	6.35	

Mode	LTE Band 41 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.7	5.04	5.07	5.8	PASS
Middle CH	5.77	4.96	5.65	6.14	
Highest CH	4.61	5.48	5.16	5.83	




LTE Band 38 / 20MHz / QPSK


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 38 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 28 DEC 2017 17:35:57

Lowest Channel / Full RB




Date: 28 DEC 2017 17:36:06

Middle Channel / 1RB




Date: 28 DEC 2017 17:36:21

Middle Channel / Full RB




Date: 28 DEC 2017 17:36:31

Highest Channel / 1RB



Date: 28 DEC 2017 17:36:47

Highest Channel / Full RB




Date: 28 DEC 2017 17:37:20




LTE Band 41 / 20MHz / QPSK


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 41 / 20MHz / 16QAM


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



**26dB Bandwidth**


Mode	LTE Band 38 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.89	4.93	9.69	9.63	14.33	15.76	20.22	20.10
Middle CH	-	-	-	-	4.92	4.92	9.65	9.75	14.36	14.54	20.18	20.10
Highest CH	-	-	-	-	4.91	4.83	9.69	9.63	14.42	14.21	20.10	20.18

Mode	LTE Band 41 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.88	4.97	9.63	9.93	14.24	14.24	20.06	20.1
Middle CH	-	-	-	-	4.99	4.81	9.77	9.75	14.51	14.12	20.18	20.06
Highest CH	-	-	-	-	4.87	5.02	9.79	9.63	14.3	14.27	20.18	19.98




LTE Band 38

Lowest Channel / 5MHz / QPSK




Date: 28 DEC 2017 17:26:42

Lowest Channel / 5MHz / 16QAM




Date: 28 DEC 2017 17:26:52

Middle Channel / 5MHz / QPSK




Date: 28 DEC 2017 17:27:24

Middle Channel / 5MHz / 16QAM




Date: 28 DEC 2017 17:27:35

Highest Channel / 5MHz / QPSK



Date: 28 DEC 2017 17:28:07

Highest Channel / 5MHz / 16QAM




Date: 28 DEC 2017 17:28:17




LTE Band 38

Lowest Channel / 10MHz / QPSK




Date: 28 DEC 2017 17:28:49

Lowest Channel / 10MHz / 16QAM




Date: 28 DEC 2017 17:29:00

Middle Channel / 10MHz / QPSK




Date: 28 DEC 2017 17:29:32

Middle Channel / 10MHz / 16QAM




Date: 28 DEC 2017 17:29:42

Highest Channel / 10MHz / QPSK



Date: 28 DEC 2017 17:30:14

Highest Channel / 10MHz / 16QAM




Date: 28 DEC 2017 17:30:25




LTE Band 38


Lowest Channel / 15MHz / QPSK




Lowest Channel / 15MHz / 16QAM




Middle Channel / 15MHz / QPSK




Middle Channel / 15MHz / 16QAM



Highest Channel / 15MHz / QPSK




Highest Channel / 15MHz / 16QAM






LTE Band 38


Lowest Channel / 20MHz / QPSK




Lowest Channel / 20MHz / 16QAM




Middle Channel / 20MHz / QPSK




Middle Channel / 20MHz / 16QAM



Highest Channel / 20MHz / QPSK




Highest Channel / 20MHz / 16QAM






LTE Band 41

Lowest Channel / 5MHz / QPSK




Date: 30 DEC 2017 12:27:27

Lowest Channel / 5MHz / 16QAM




Date: 30 DEC 2017 12:27:10

Middle Channel / 5MHz / QPSK




Date: 30 DEC 2017 12:26:10

Middle Channel / 5MHz / 16QAM




Date: 30 DEC 2017 12:26:41

Highest Channel / 5MHz / QPSK



Date: 30 DEC 2017 12:25:46

Highest Channel / 5MHz / 16QAM




Date: 30 DEC 2017 12:25:32




LTE Band 41

Lowest Channel / 10MHz / QPSK




Date: 30 DEC 2017 13:16:45

Lowest Channel / 10MHz / 16QAM




Date: 30 DEC 2017 13:17:54

Middle Channel / 10MHz / QPSK




Date: 30 DEC 2017 13:19:16

Middle Channel / 10MHz / 16QAM




Date: 30 DEC 2017 13:18:36

Highest Channel / 10MHz / QPSK



Date: 30 DEC 2017 13:20:03

Highest Channel / 10MHz / 16QAM




Date: 30 DEC 2017 13:20:40




LTE Band 41

Lowest Channel / 15MHz / QPSK




Date: 30 DEC 2017 14:40:29

Lowest Channel / 15MHz / 16QAM




Date: 30 DEC 2017 14:41:09

Middle Channel / 15MHz / QPSK




Date: 30 DEC 2017 14:42:08

Middle Channel / 15MHz / 16QAM




Date: 30 DEC 2017 14:41:42

Highest Channel / 15MHz / QPSK



Date: 30 DEC 2017 14:43:18

Highest Channel / 15MHz / 16QAM




Date: 30 DEC 2017 14:44:00




LTE Band 41

Lowest Channel / 20MHz / QPSK




Date: 30 DEC 2017 14:50:20

Lowest Channel / 20MHz / 16QAM




Date: 30 DEC 2017 14:50:48

Middle Channel / 20MHz / QPSK




Date: 30 DEC 2017 14:51:38

Middle Channel / 20MHz / 16QAM




Date: 30 DEC 2017 14:51:17

Highest Channel / 20MHz / QPSK



Date: 30 DEC 2017 14:52:25

Highest Channel / 20MHz / 16QAM



Date: 30 DEC 2017 14:52:54

**Occupied Bandwidth**


Mode	LTE Band 38 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.49	4.53	8.97	9.01	13.40	13.43	18.26	18.14
Middle CH	-	-	-	-	4.49	4.50	8.97	9.03	13.46	13.43	18.26	18.26
Highest CH	-	-	-	-	4.50	4.50	9.09	9.09	13.46	13.40	18.42	18.30

Mode	LTE Band 41 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.52	4.49	8.97	9.03	13.4	13.4	18.22	18.26
Middle CH	-	-	-	-	4.49	4.48	9.01	8.99	13.46	13.43	18.3	18.26
Highest CH	-	-	-	-	4.51	4.49	8.99	8.99	13.43	13.4	18.18	18.22




LTE Band 38


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM

