FCC RF Test Report

APPLICANT : Motorola Mobility LLC EQUIPMENT : Mobile Cellular Phone

BRAND NAME : Motorola

MODEL NAME : XT1929-8

FCC ID : IHDT56XE3

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION: (DSS) Spread Spectrum Transmitter

This is a variant report. The product was received on Jan. 18, 2018 and testing was completed on Mar. 14, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 1 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Testing Laboratory 1190

Report No.: FR811821-07A

TABLE OF CONTENTS

		N HISTORY					
SUI	SUMMARY OF TEST RESULT4						
1	GENE	RAL DESCRIPTION	5				
	1.1	Applicant	5				
	1.2	Manufacturer	5				
	1.3	Product Feature of Equipment Under Test	5				
	1.4	Product Specification of Equipment Under Test	7				
	1.5	Modification of EUT	7				
	1.6	Testing Location	8				
	1.7	Applicable Standards	8				
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	9				
	2.1	Carrier Frequency Channel	9				
	2.2	Test Mode	.10				
	2.3	Connection Diagram of Test System	.11				
	2.4	Support Unit used in test configuration and system	.11				
	2.5	EUT Operation Test Setup	.11				
3	TEST	RESULT	.12				
	3.1	Output Power Measurement	.12				
	3.2	Radiated Band Edges and Spurious Emission Measurement	.13				
	3.3	Antenna Requirements	.17				
4	LIST	OF MEASURING EQUIPMENT	.18				
5	UNCE	RTAINTY OF EVALUATION	.19				
API	PENDI	X A. CONDUCTED TEST RESULTS					
API	PENDI	X B. RADIATED SPURIOUS EMISSION					
API	PENDI	X C. RADIATED SPURIOUS EMISSION PLOTS					
API	PENDI	X D. DUTY CYCLE PLOTS					

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 2 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No. : FR811821-07A

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR811821-07A	Rev. 01	Initial issue of report	Mar. 16, 2018

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 3 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
-	15.247(a)(1)	Number of Channels	≥ 15Chs	Not Required	-
-	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Not Required	-
-	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Not Required	-
-	15.247(a)(1)	20dB Bandwidth	NA	Not Required	1
-	-	99% Bandwidth	-	Not Required	-
3.1	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	1
-	15.247(d)	Conducted Band Edges	≤ 20dBc	Not Required	-
-	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Not Required	-
3.2	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.25 dB at 38.100 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Required	-
3.3	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-
Remark: Not required means after assessing, test items are not necessary to carry out.					

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3

Page Number : 4 of 19 Report Issued Date: Mar. 16, 2018 : Rev. 01 Report Version

Report No. : FR811821-07A

1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	t Mobile Cellular Phone			
Brand Name	Motorola			
Model Name	XT1929-8			
FCC ID	IHDT56XE3			
Sample 1	EUT with Dua	I SIM		
Sample 2	EUT with Sing	gle SIM		
	Conducted	IMEI 1: 354105090012138		
IMEI Code	Conducted	IMEI 2: 354105090012146		
I IVIEI Code	Dodiction.	IMEI 1: 354105090023036		
	Radiation:	IMEI 2: 354105090023044		
	GSM/EGPRS	/WCDMA/HSPA/LTE/GNSS/NFC		
	WLAN 11b/g/n HT20			
EUT supports Radios application	WLAN 11a/n HT20/HT40			
	WLAN 11ac VHT20/VHT40/VHT80			
	Bluetooth BR/EDR/LE			
HW Version	DVT2			
EUT Stage	Identical Prototype			

Remark:

- 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. This is a variant report. All the test cases were performed on original report which can be referred to Sporton Report Number FR811821-02A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 5 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

	Accessory List					
	Brand Name: Motorola					
AC Adapter 1	Model Name: SC-23 SPN5971A					
•	Manufacturer: Salom					
	Brand Name: Motorola					
AC Adapter 2	Model Name: SC-23 SPN5989A					
	Manufacturer: Chenyang					
	Brand Name: Motorola					
AC Adapter 3	Model Name: SC-24 SPN5972A					
	Manufacturer: Salom					
	Brand Name: Motorola					
AC Adapter 4	Model Name: SC-24 SPN5990A					
	Manufacturer: Chenyang					
	Brand Name: Motorola					
Battery	Model Name: JS40					
	Manufacturer: SUNWODA					
Farnhana	Brand Name: Motorola					
Earphone	Model Name: SH38C16618					
	Brand Name: Motorola					
C2Audio Cable 1	Model Name: SC18C27844					
	Manufacturer: Luxshare					
	Brand Name: Motorola					
C2Audio Cable 2	Model Name: SC18C27845					
	Manufacturer : Cabletech					
USB Cable 1	Brand Name: Cabletech					
USB Cable 1	Model Name: SKN6473A					
USB Cable 2	Brand Name: FOXLINK					
USB Cable 2	Model Name: SKN6473A 17195-C 0403532					
USB Cable 3	Brand Name: SAIBAO					
Cable 3	Model Name: SKN6473A 17214-C 1127044					
USB Cable 4	Brand Name: Luxshare					
	Model Name: SKN6473A 17227-C 1126538					

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 6 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No. : FR811821-07A

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification			
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz		
Number of Channels 79			
Carrier Frequency of Each Channel	ch Channel 2402+n*1 MHz; n=0~78		
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 13.01 dBm (0.0200 W) Bluetooth EDR (2Mbps) : 12.42 dBm (0.0175 W) Bluetooth EDR (3Mbps) : 12.75 dBm (0.0188 W)		
Antenna Type / Gain	Internal Antenna with gain -5.00 dBi		
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK		

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 7 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Report No.: FR811821-07A

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978			
Test Site No.	Sporton Site No.			
rest site No.	03CH12-HY			

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 8 of 19

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 16, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: IHDT56XE3 Report Template No.: BU5-FR15CBT Version 2.0

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
2400-2483.5 MHz	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 9 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases						
		Data Rate / Modulation					
Test Item	Bluetooth BR 1Mbps	Bluetooth EDR 2Mbps	Bluetooth EDR 3Mbps				
	GFSK	π/4-DQPSK	8-DPSK				
Conducted	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz				
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz				
Test Cases	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz				
Radiated	Bluetooth BR 1Mbps GFSK						
Test Cases	Mode 1: CH78_2480 MHz						

Remark:

- 1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.
- 2. For Radiated Test Cases, The tests were performance with USB Cable 1 Type C and Sample 1.


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 10 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
I 1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	E335	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility "QRCT" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 11 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

3 Test Result

3.1 Output Power Measurement

3.1.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.5.
- 1. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Measure the conducted output power with cable loss and record the results in the test report.
- 4. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.1.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 12 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

3.2 Radiated Band Edges and Spurious Emission Measurement

3.2.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 13 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

3.2.3 Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 4. Set to the maximum power setting and enable the EUT transmit continuously.
- 5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).

Duty cycle = On time/100 milliseconds

On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.


Average Emission Level = Peak Emission Level + 20*log(Duty cycle)

- 6. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.78dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.2.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 15 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

For radiated emissions above 1GHz



3.2.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.2.7 Duty Cycle

Please refer to Appendix D.

3.2.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 16 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

3.3 Antenna Requirements

3.3.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.3.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.3.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 17 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	al No. Characteristics Calibration Date		Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 26, 2017	Feb. 08, 2018~ Feb. 21, 2018	Sep. 25, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	0846202	300MHz~40GH z	Sep. 26, 2017	Feb. 08, 2018~ Feb. 21, 2018	Sep. 25, 2018	Conducted (TH05-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Mar. 08, 2018~ Mar. 14, 2018	Jul. 17, 2018	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-0 6	35414&AT- N0602	30MHz~1GHz	Oct. 14, 2017	Mar. 08, 2018~ Mar. 14, 2018	Oct. 13, 2018	Radiation (03CH12-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Mar. 08, 2018~ Mar. 14, 2018	Nov. 22, 2019	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 25, 2017	Mar. 08, 2018~ Mar. 14, 2018	Dec. 24, 2018	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-132 8	1GHz ~ 18GHz	Oct. 20, 2017	Mar. 08, 2018~ Mar. 14, 2018	Oct. 19, 2018	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 23, 2017	Mar. 08, 2018~ Mar. 14, 2018	Mar. 22, 2018	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY532701 48	1GHz~26.5GHz	Jan. 15, 2018	Mar. 08, 2018~ Mar. 14, 2018	Jan. 14, 2019	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800	2025787	1GHZ~18GHZ	Feb. 13, 2017	Mar. 08, 2018~ Mar. 14, 2018	Feb. 12, 2019	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Mar. 08, 2018~ Mar. 14, 2018	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Mar. 08, 2018~ Mar. 14, 2018	N/A	Radiation (03CH12-HY)
Attenuator	Fairview Microwave	SA18S5W-10	n/a	10db	Mar. 24, 2017	Mar. 08, 2018~ Mar. 14, 2018	Mar. 23, 2018	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 576	18GHz ~ 40GHz	Apr. 27, 2017	Mar. 08, 2018~ Mar. 14, 2018	Apr. 26, 2018	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz~44GHz	Oct. 19, 2017	Mar. 08, 2018~ Mar. 14, 2018	Oct. 18, 2018	Radiation (03CH12-HY)

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 18 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.10
or 95% (U = 2UC(y))	

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5.20
of 95% (U = 2Uc(y))	5.20

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	4.70
of 95% (U = 2Uc(y))	4.70

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: IHDT56XE3 Page Number : 19 of 19
Report Issued Date : Mar. 16, 2018
Report Version : Rev. 01

Report No.: FR811821-07A

Report Number : FR811821-07A

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Lena Lo	Temperature:	21~25	°C
Test Date:	2018/2/8~2018/2/21	Relative Humidity:	51~54	%

TEST RESULTS DATA

Peak Power Table

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
	0	1	13.01	20.97	Pass
DH1	39	1	11.70	20.97	Pass
	78	1	11.68	20.97	Pass
	0	1	12.42	20.97	Pass
2DH1	39	1	11.03	20.97	Pass
	78	1	11.16	20.97	Pass
	0	1	12.75	20.97	Pass
3DH1	39	1	11.43	20.97	Pass
	78	1	11.49	20.97	Pass

TEST RESULTS DATA

Average Power Table (Reporting Only)

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
	0	1	12.84	1.85
DH3	39	1	11.54	1.85
	78 1		11.51	1.85
	0	1	10.55	5.12
2DH1	39	1	8.88	5.12
	78	1	9.37	5.12
	0	1	10.50	5.12
3DH1	39	1	8.86	5.12
	78	1	9.40	5.12

Appendix B. Radiated Spurious Emission

Test Engineer :	Watt Tseng, Karl Hou, and Nick Yu	Temperature :	22~23°C
rest Engineer.		Relative Humidity :	59~61%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

ВТ	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
	*	2480	104.89	-	-	105	27.36	4.09	31.56	299	57	Р	Н
	*	2480	80.11	-	-	-	-	-	-	-	-	Α	Н
		2483.6	53.51	-20.94	74	53.15	27.36	4.11	31.56	299	57	Р	Н
		2483.6	28.73	-25.27	54	-	-	-	-	-	-	Α	Н
DT													Н
BT CU 70													Н
CH 78 2480MHz	*	2480	104.17	-	-	104.28	27.36	4.09	31.56	157	107	Р	٧
2400WII 12	*	2480	79.39	-	-	-	-	-	-	-	-	Α	٧
		2483.52	53.15	-20.85	74	53.24	27.36	4.11	31.56	157	107	Р	٧
		2483.52	28.37	-25.63	54	-	-	-	-	-	-	Α	٧
													V
													V
Remark		o other spurious		Dook and	I Average lim	it line							

All results are PASS against Peak and Average limit line.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978

2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

вт	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	i -	
		4960	40.11	-33.89	74	66.36	31.63	6.26	64.63	100	0	Р	Н
		4960	15.33	-38.67	54	-	-	-	-	-	-	Α	Н
ВТ		7440	44.53	-29.47	74	64.87	36.47	7.75	64.88	100	0	Р	Н
		7440	19.75	-34.25	54	-	-	-	-	-	-	Α	Н
CH 78 2480MHz		4960	43.77	-30.23	74	70.02	31.63	6.26	64.63	100	0	Р	V
240UIVI MZ		4960	18.99	-35.01	54	-	-	-	-	-	-	Α	V
		7440	44.44	-29.56	74	64.78	36.47	7.75	64.88	100	0	Р	V
		7440	19.66	-34.34	54	-	-	-	-	-	-	Α	V
Remark		o other spuriou		1			1			ı	1	1	1
	2. A	2. All results are PASS against Peak and Average limit line.											

TEL: 886-3-327-3456 FAX: 886-3-328-4978

Emission below 1GHz

2.4GHz BT (LF)

вт	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		67.53	31.95	-8.05	40	49.75	11.9	0.68	30.43			Р	Н
		71.58	30.41	-9.59	40	47.95	12.16	0.68	30.43			Р	Н
		170.94	37.81	-5.69	43.5	51.56	15.3	1.09	30.31	100	0	Р	Н
		347.6	31.63	-14.37	46	39.99	20.12	1.5	30.06			Р	Н
		479.2	31.05	-14.95	46	35.61	23.44	1.77	29.83			Р	Н
		553.4	31.23	-14.77	46	33.48	25.45	1.9	29.72			Р	Н
													Н
													Н
													Н
													Н
													Н
2.4GHz													Н
BT LF		38.1	36.75	-3.25	40	46.32	20.26	0.48	30.29	100	0	Р	V
LF		69.69	32.73	-7.27	40	50.46	11.97	0.68	30.43			Р	V
		119.64	37.78	-5.72	43.5	49.96	17.27	0.89	30.37			Р	٧
		348.3	28.45	-17.55	46	36.78	20.15	1.5	30.06			Р	٧
		480.6	27.09	-18.91	46	31.63	23.46	1.77	29.83			Р	V
		559.7	27.62	-18.38	46	29.25	26.07	1.9	29.71			Р	٧
													V
													٧
													V
													V
													V
													V

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978

Note symbol

Report No. : FR811821-07A

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

SPORTON INTERNATIONAL INC. Page Number : B4 of B5

TEL: 886-3-327-3456 FAX: 886-3-328-4978

A calculation example for radiated spurious emission is shown as below:

Report No.: FR811821-07A

: B5 of B5

ВТ	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
ВТ		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 00													
2402MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

- 1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- 2. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

SPORTON INTERNATIONAL INC. Page Number

TEL: 886-3-327-3456 FAX: 886-3-328-4978



Appendix C. Radiated Spurious Emission Plots

Toot Engineer	Watt Tseng, Karl Hou, and Nick Yu	Temperature :	22~23°C
Test Engineer :		Relative Humidity :	59~61%

Report No.: FR811821-07A


Note symbol

-L	Low channel location	
-R	High channel location	


SPORTON INTERNATIONAL INC. Page Number : C1 of C5

TEL: 886-3-327-3456 FAX: 886-3-328-4978

2.4GHz 2400~2483.5MHz BT (Band Edge @ 3m)




TEL: 886-3-327-3456 FAX: 886-3-328-4978



TEL: 886-3-327-3456 FAX: 886-3-328-4978


2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)



TEL: 886-3-327-3456 FAX: 886-3-328-4978

Emission below 1GHz 2.4GHz BT (LF)




TEL: 886-3-327-3456 FAX: 886-3-328-4978

Report No.: FR811821-07A


Appendix D. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



Date: 13.MAR.2018 06:33:41

on time (Count Pulses) Plot on Channel 39



Date: 13.MAR.2018 06:34:16

Note:

- 1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.88 / 100 = 5.76 %
- 2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.78 dB
- 3. **DH5** has the highest duty cycle worst case and is reported.



Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

2.88 ms x 20 channels = 57.6 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100ms / 57.6ms] = 2 hops

Thus, the maximum possible ON time:

2.88 ms x 2 = 5.76 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

 $20 \times log(5.76 \text{ ms}/100\text{ms}) = -24.78 \text{ dB}$

TEL: 886-3-327-3456 FAX: 886-3-328-4978