



# FCC RF Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT1929-5  
**FCC ID** : IHDT56XE5  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)

This is a variant report. The product was received on Jan. 18, 2018 and testing was completed on Mar. 08, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : IHDT56XE5

Page Number : 1 of 24

Report Issued Date : Mar. 14, 2018

Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 2.0



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test ..... 5

    1.4 Product Specification of Equipment Under Test ..... 7

    1.5 Modification of EUT ..... 8

    1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator ..... 8

    1.7 Testing Location ..... 9

    1.8 Applicable Standards ..... 9

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 10**

    2.1 Test Mode..... 10

    2.2 Connection Diagram of Test System ..... 11

    2.3 Support Unit used in test configuration ..... 12

    2.4 Measurement Results Explanation Example ..... 12

    2.5 Frequency List of Low/Middle/High Channels..... 13

**3 CONDUCTED TEST RESULT..... 14**

    3.1 Measuring Instruments..... 14

    3.2 Test Setup ..... 14

    3.3 Test Result of Conducted Test..... 14

    3.4 Conducted Output Power and ERP/EIRP ..... 15

    3.5 Peak-to-Average Ratio ..... 16

    3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 17

    3.7 Conducted Band Edge ..... 18

    3.8 Conducted Spurious Emission ..... 19

    3.9 Frequency Stability..... 20

**4 RADIATED TEST ITEMS ..... 21**

    4.1 Measuring Instruments..... 21

    4.2 Test Setup ..... 21

    4.3 Test Result of Radiated Test..... 21

    4.4 Field Strength of Spurious Radiation Measurement ..... 22

**5 LIST OF MEASURING EQUIPMENT ..... 23**

**6 UNCERTAINTY OF EVALUATION ..... 24**

**APPENDIX A. TEST RESULTS OF CONDUCTED TEST**

**APPENDIX B. TEST RESULTS OF ERP/EIRP AND RADIATED TEST**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 19.88 dB at 5730.000 MHz



# 1 General Description

## 1.1 Applicant

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2 Manufacturer

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1929-5
FCC ID	IHDT56XE5
IMEI Code	Conducted : IMEI 1: 354106090006195 IMEI 2: 354106090006203
	Radiation : IMEI 1: 354106090008035 IMEI 2: 354106090008043
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/GNSS/NFC WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT2
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a variant report. Except Conducted test item for GSM850, Radiated Spurious Emission, Conducted Output Power, Equivalent Isotropic Radiated Power, and Effective Radiated Power, FG811821-04A report reuses test data from the FG811821A report.



Accessory List	
AC Adapter 1	Brand Name : Motorola
	Model Name : SC-28 SPN5997A
	Manufacturer : Salom
AC Adapter 2	Brand Name : Motorola
	Model Name : SC-28 SPN5976A
	Manufacturer : Salom
AC Adapter 3	Brand Name : Motorola
	Model Name : SC-28 SPN5998A
	Manufacturer : Cliptech Manufacturer : Chenyang
Battery	Brand Name : Motorola
	Model Name : JS40
	Manufacturer : SUNWODA
Earphone	Brand Name : Motorola
	Model Name : SH38C16618
C2Audio Cable 1	Brand Name : Motorola
	Model Name : SC18C27844
	Manufacturer : Luxshare
C2Audio Cable 2	Brand Name : Motorola
	Model Name : SC18C27845
	Manufacturer : Cabletech
USB Cable 1	Brand Name : Cabletech
	Model Name : SKN6473A
USB Cable 2	Brand Name : FOXLINK
	Model Name : SKN6473A 17195-C 0403532
USB Cable 3	Brand Name : SAIBAO
	Model Name : SKN6473A 17214-C 1127044
USB Cable 4	Brand Name : Luxshare
	Model Name : SKN6473A 17227-C 1126538



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	<b>GSM/GPRS/EDGE:</b> 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz <b>WCDMA:</b> Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	<b>GSM/GPRS/EDGE:</b> 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz <b>WCDMA:</b> Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	<b>GSM/GPRS/EDGE:</b> 850: 32.63 dBm 1900: 29.49 dBm <b>WCDMA:</b> Band V: 22.67 dBm Band II: 22.68 dBm
<b>Antenna Type</b>	Fixed Internal Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK (Uplink) HSDPA: 64QAM (Downlink) HSUPA: QPSK (Uplink)



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	Frequency Range (MHz)	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	824.2 ~848.8	GSM850 GPRS class 8	GMSK	0.3076	0.0155 ppm	245KGXW
Part 22	824.2 ~848.8	GSM850 EDGE class 8	8PSK	0.0687	0.0203 ppm	249KG7W
Part 22	826.4 ~846.6	WCDMA Band V RMC 12.2Kbps	BPSK	0.0310	-	-
Part 24	1850.2 ~1909.8	GSM1900 GPRS class 8	GMSK	0.5483	-	-
Part 24	1850.2 ~1909.8	GSM1900 EDGE class 8	8PSK	0.2118	-	-
Part 24	1852.4 ~ 1907.6	WCDMA Band II RMC 12.2Kbps	BPSK	0.1143	-	-



### 1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
<b>Test Site No.</b>	<b>Sporton Site No.</b>
	TH03-HY

<b>Test Site</b>	SPORTON INTERNATIONAL INC.
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd., Kwei-Shan District, Tao Yuan City, Taiwan R.O.C. TEL: +886-3-327-0868 FAX: +886-3-327-0855
<b>Test Site No.</b>	<b>Sporton Site No. :</b>
	03CH13-HY

### 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II
3. All modes and data rates and positions were investigated.


Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
GSM 1900	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>	-
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	-
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	-


**Remark:** All the radiated test cases were performance with Adapter 1 and USB Cable 1.

## 2.2 Connection Diagram of Test System

<EUT Standalone>



<EUT with Adapter>





### 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m

### 2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



## 2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6


### 3 Conducted Test Result

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



## **3.5 Peak-to-Average Ratio**

### **3.5.1 Description of the PAR Measurement**

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### **3.5.2 Test Procedures**

1. The testing follows FCC KDB 971168 D01 v03 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.  
Record the maximum PAPR level associated with a probability of 0.1%.



### 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## **3.7 Conducted Band Edge**

### **3.7.1 Description of Conducted Band Edge Measurement**

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### **3.7.2 Test Procedures**

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## **3.8 Conducted Spurious Emission**

### **3.8.1 Description of Conducted Spurious Emission Measurement**

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### **3.8.2 Test Procedures**

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



### 3.9 Frequency Stability

#### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.



## 4.4 Field Strength of Spurious Radiation Measurement

### 4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 26, 2017	Feb. 24, 2018	Jun. 25, 2018	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Nov. 16, 2016	Feb. 24, 2018	Nov. 15, 2018	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL883644	Voltage:0~20V; Current:0~5A	Nov. 22, 2016	Feb. 24, 2018	Nov. 21, 2018	Conducted (TH03-HY)
Base Station (Measure)	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Aug. 09, 2017	Feb. 24, 2018	Aug. 08, 2018	Conducted (TH03-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	Jul. 17, 2018	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 21, 2016	Mar. 06, 2018 ~ Mar. 08, 2018	Dec. 20, 2018	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800N 1D01N-06	40103&07	30MHz to 1GHz	Jan. 10, 2018	Mar. 06, 2018 ~ Mar. 08, 2018	Jan. 09, 2019	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jun. 15, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	Jun. 14, 2018	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590074	1GHz~18GHz	May 22, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	May 21, 2018	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Feb. 02, 2018	Mar. 06, 2018 ~ Mar. 08, 2018	Feb. 01, 2019	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 15, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	Mar. 14, 2018	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Mar. 06, 2018 ~ Mar. 08, 2018	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Mar. 06, 2018 ~ Mar. 08, 2018	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Mar. 06, 2018 ~ Mar. 08, 2018	N/A	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz- 40GHz	Nov. 10, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	Nov. 09, 2018	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	Nov. 26, 2018	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Mar. 17, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	Mar. 16, 2018	Radiation (03CH13-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 22, 2017	Mar. 06, 2018 ~ Mar. 08, 2018	May 21, 2018	Radiation (03CH13-HY)



## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.07
---	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.48
---	------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.92
---	------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	31.59	32.37	32.57	29.48	29.38	29.27
GPRS class 8	31.58	32.35	<b>32.63</b>	<b>29.49</b>	29.37	29.25
GPRS class 10	30.21	31.00	31.03	28.35	28.29	28.29
GPRS class 11	28.08	29.01	29.61	26.42	26.42	26.51
GPRS class 12	26.31	27.21	27.93	24.60	24.60	24.77
EGPRS class 8	26.04	25.93	<b>26.12</b>	<b>25.36</b>	<b>25.36</b>	<b>25.36</b>
EGPRS class 10	24.77	24.68	24.92	24.20	24.20	24.24
EGPRS class 11	23.02	22.98	23.20	22.55	22.55	22.62
EGPRS class 12	21.33	21.34	21.51	20.95	20.95	21.02

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	<b>22.67</b>	22.66	22.66	22.44	22.52	<b>22.68</b>
HSDPA Subtest-1	21.23	21.21	21.21	21.00	21.06	21.20
HSDPA Subtest-2	21.21	21.19	21.21	21.02	21.06	21.20
HSDPA Subtest-3	21.21	21.19	21.21	20.96	21.06	21.20
HSDPA Subtest-4	21.21	21.19	21.19	20.96	21.06	21.20
HSUPA Subtest-1	21.68	21.42	21.64	21.42	21.02	21.43
HSUPA Subtest-2	19.66	19.67	19.65	19.43	19.48	19.64
HSUPA Subtest-3	20.65	20.63	20.63	20.43	20.53	20.66
HSUPA Subtest-4	19.66	19.65	19.64	19.42	19.53	19.64
HSUPA Subtest-5	21.17	21.16	21.13	21.01	21.00	21.16









## A2. GSM

### Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.36	3.52	PASS
Middle CH	0.32	3.32	
Highest CH	0.32	3.28	




GSM850 (GPRS class 8)	GSM850 (EDGE class 8)																
<p align="center"><b>Lowest Channel</b></p>  <p>Center 824.2 MHz    20 dB    Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 30.52 dBm Peak 30.95 dBm Crest 0.43 dB</p> <table border="1"> <tr><td>10 %</td><td>0.24 dB</td></tr> <tr><td>1 %</td><td>0.32 dB</td></tr> <tr><td>.1 %</td><td>0.36 dB</td></tr> <tr><td>.01 %</td><td>0.36 dB</td></tr> </table> <p>Date: 24.FEB.2018 13:40:11</p>	10 %	0.24 dB	1 %	0.32 dB	.1 %	0.36 dB	.01 %	0.36 dB	<p align="center"><b>Lowest Channel</b></p>  <p>Center 824.2 MHz    20 dB    Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.56 dBm Peak 28.20 dBm Crest 3.63 dB</p> <table border="1"> <tr><td>10 %</td><td>2.88 dB</td></tr> <tr><td>1 %</td><td>3.44 dB</td></tr> <tr><td>.1 %</td><td>3.52 dB</td></tr> <tr><td>.01 %</td><td>3.60 dB</td></tr> </table> <p>Date: 7.MAR.2018 16:35:11</p>	10 %	2.88 dB	1 %	3.44 dB	.1 %	3.52 dB	.01 %	3.60 dB
10 %	0.24 dB																
1 %	0.32 dB																
.1 %	0.36 dB																
.01 %	0.36 dB																
10 %	2.88 dB																
1 %	3.44 dB																
.1 %	3.52 dB																
.01 %	3.60 dB																
<p align="center"><b>Middle Channel</b></p>  <p>Center 836.4 MHz    20 dB    Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.20 dBm Peak 31.58 dBm Crest 0.38 dB</p> <table border="1"> <tr><td>10 %</td><td>0.20 dB</td></tr> <tr><td>1 %</td><td>0.28 dB</td></tr> <tr><td>.1 %</td><td>0.32 dB</td></tr> <tr><td>.01 %</td><td>0.36 dB</td></tr> </table> <p>Date: 24.FEB.2018 13:40:26</p>	10 %	0.20 dB	1 %	0.28 dB	.1 %	0.32 dB	.01 %	0.36 dB	<p align="center"><b>Middle Channel</b></p>  <p>Center 836.4 MHz    20 dB    Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.86 dBm Peak 28.27 dBm Crest 3.41 dB</p> <table border="1"> <tr><td>10 %</td><td>2.76 dB</td></tr> <tr><td>1 %</td><td>3.20 dB</td></tr> <tr><td>.1 %</td><td>3.32 dB</td></tr> <tr><td>.01 %</td><td>3.36 dB</td></tr> </table> <p>Date: 7.MAR.2018 16:36:18</p>	10 %	2.76 dB	1 %	3.20 dB	.1 %	3.32 dB	.01 %	3.36 dB
10 %	0.20 dB																
1 %	0.28 dB																
.1 %	0.32 dB																
.01 %	0.36 dB																
10 %	2.76 dB																
1 %	3.20 dB																
.1 %	3.32 dB																
.01 %	3.36 dB																
<p align="center"><b>Highest Channel</b></p>  <p>Center 848.8 MHz    20 dB    Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.45 dBm Peak 31.79 dBm Crest 0.34 dB</p> <table border="1"> <tr><td>10 %</td><td>0.20 dB</td></tr> <tr><td>1 %</td><td>0.28 dB</td></tr> <tr><td>.1 %</td><td>0.32 dB</td></tr> <tr><td>.01 %</td><td>0.36 dB</td></tr> </table> <p>Date: 24.FEB.2018 13:41:01</p>	10 %	0.20 dB	1 %	0.28 dB	.1 %	0.32 dB	.01 %	0.36 dB	<p align="center"><b>Highest Channel</b></p>  <p>Center 848.8 MHz    20 dB    Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.15 dBm Peak 28.48 dBm Crest 3.33 dB</p> <table border="1"> <tr><td>10 %</td><td>2.72 dB</td></tr> <tr><td>1 %</td><td>3.16 dB</td></tr> <tr><td>.1 %</td><td>3.28 dB</td></tr> <tr><td>.01 %</td><td>3.32 dB</td></tr> </table> <p>Date: 7.MAR.2018 16:36:35</p>	10 %	2.72 dB	1 %	3.16 dB	.1 %	3.28 dB	.01 %	3.32 dB
10 %	0.20 dB																
1 %	0.28 dB																
.1 %	0.32 dB																
.01 %	0.36 dB																
10 %	2.72 dB																
1 %	3.16 dB																
.1 %	3.28 dB																
.01 %	3.32 dB																



**26dB Bandwidth**


Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.316	0.299
Middle CH	0.310	0.300
Highest CH	0.307	0.299





## Occupied Bandwidth

Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.245	0.249
Middle CH	0.243	0.244
Highest CH	0.241	0.245







**Conducted Band Edge**

**GSM850 (GPRS class 8)**

**Lowest Band Edge**




**Highest Band Edge**




**GSM850 (EDGE class 8)**

**Lowest Band Edge**









**Highest Band Edge**





# Conducted Spurious Emission

GSM850 (GPRS class 8)	GSM850 (EDGE class 8)																																																																								
Lowest Channel	Lowest Channel																																																																								
 <table border="1" data-bbox="207 660 670 739"> <thead> <tr> <th>Start [Hz]</th> <th>Stop [Hz]</th> <th>RBW [Hz]</th> <th>Freq [Hz]</th> <th>Power [dBm]</th> <th>Limit [dBm]</th> </tr> </thead> <tbody> <tr> <td>35,000 M</td> <td>820,000 M</td> <td>1,000 M</td> <td>76,572500 M</td> <td>-44.45</td> <td>-31.45</td> </tr> <tr> <td>855,000 M</td> <td>1,000 G</td> <td>1,000 M</td> <td>925,542500 M</td> <td>-42.91</td> <td>-29.91</td> </tr> <tr> <td>1,000 G</td> <td>3,000 G</td> <td>1,000 M</td> <td>2,472500 G</td> <td>-39.94</td> <td>-26.94</td> </tr> <tr> <td>3,000 G</td> <td>7,000 G</td> <td>1,000 M</td> <td>4,092500 G</td> <td>-39.50</td> <td>-26.50</td> </tr> <tr> <td>7,000 G</td> <td>9,000 G</td> <td>1,000 M</td> <td>7,665000 G</td> <td>-36.64</td> <td>-23.64</td> </tr> </tbody> </table> <p>Date: 24.FEB.2018 13:38:08</p>	Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]	35,000 M	820,000 M	1,000 M	76,572500 M	-44.45	-31.45	855,000 M	1,000 G	1,000 M	925,542500 M	-42.91	-29.91	1,000 G	3,000 G	1,000 M	2,472500 G	-39.94	-26.94	3,000 G	7,000 G	1,000 M	4,092500 G	-39.50	-26.50	7,000 G	9,000 G	1,000 M	7,665000 G	-36.64	-23.64	 <table border="1" data-bbox="861 660 1324 739"> <thead> <tr> <th>Start [Hz]</th> <th>Stop [Hz]</th> <th>RBW [Hz]</th> <th>Freq [Hz]</th> <th>Power [dBm]</th> <th>Limit [dBm]</th> </tr> </thead> <tbody> <tr> <td>35,000 M</td> <td>820,000 M</td> <td>1,000 M</td> <td>819,802500 M</td> <td>-35.54</td> <td>-20.54</td> </tr> <tr> <td>855,000 M</td> <td>1,000 G</td> <td>1,000 M</td> <td>876,931252 M</td> <td>-43.48</td> <td>-30.48</td> </tr> <tr> <td>1,000 G</td> <td>3,000 G</td> <td>1,000 M</td> <td>2,978500 G</td> <td>-42.30</td> <td>-29.20</td> </tr> <tr> <td>3,000 G</td> <td>7,000 G</td> <td>1,000 M</td> <td>5,179000 G</td> <td>-39.13</td> <td>-26.13</td> </tr> <tr> <td>7,000 G</td> <td>9,000 G</td> <td>1,000 M</td> <td>8,175000 G</td> <td>-36.32</td> <td>-23.32</td> </tr> </tbody> </table> <p>Date: 7.MAR.2018 16:29:46</p>	Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]	35,000 M	820,000 M	1,000 M	819,802500 M	-35.54	-20.54	855,000 M	1,000 G	1,000 M	876,931252 M	-43.48	-30.48	1,000 G	3,000 G	1,000 M	2,978500 G	-42.30	-29.20	3,000 G	7,000 G	1,000 M	5,179000 G	-39.13	-26.13	7,000 G	9,000 G	1,000 M	8,175000 G	-36.32	-23.32
Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]																																																																				
35,000 M	820,000 M	1,000 M	76,572500 M	-44.45	-31.45																																																																				
855,000 M	1,000 G	1,000 M	925,542500 M	-42.91	-29.91																																																																				
1,000 G	3,000 G	1,000 M	2,472500 G	-39.94	-26.94																																																																				
3,000 G	7,000 G	1,000 M	4,092500 G	-39.50	-26.50																																																																				
7,000 G	9,000 G	1,000 M	7,665000 G	-36.64	-23.64																																																																				
Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]																																																																				
35,000 M	820,000 M	1,000 M	819,802500 M	-35.54	-20.54																																																																				
855,000 M	1,000 G	1,000 M	876,931252 M	-43.48	-30.48																																																																				
1,000 G	3,000 G	1,000 M	2,978500 G	-42.30	-29.20																																																																				
3,000 G	7,000 G	1,000 M	5,179000 G	-39.13	-26.13																																																																				
7,000 G	9,000 G	1,000 M	8,175000 G	-36.32	-23.32																																																																				
Middle Channel	Middle Channel																																																																								
 <table border="1" data-bbox="207 1178 670 1256"> <thead> <tr> <th>Start [Hz]</th> <th>Stop [Hz]</th> <th>RBW [Hz]</th> <th>Freq [Hz]</th> <th>Power [dBm]</th> <th>Limit [dBm]</th> </tr> </thead> <tbody> <tr> <td>35,000 M</td> <td>820,000 M</td> <td>1,000 M</td> <td>575,100000 M</td> <td>-44.18</td> <td>-31.18</td> </tr> <tr> <td>855,000 M</td> <td>1,000 G</td> <td>1,000 M</td> <td>930,862506 M</td> <td>-42.89</td> <td>-29.89</td> </tr> <tr> <td>1,000 G</td> <td>3,000 G</td> <td>1,000 M</td> <td>2,726000 G</td> <td>-42.31</td> <td>-29.31</td> </tr> <tr> <td>3,000 G</td> <td>7,000 G</td> <td>1,000 M</td> <td>5,190000 G</td> <td>-39.75</td> <td>-26.75</td> </tr> <tr> <td>7,000 G</td> <td>9,000 G</td> <td>1,000 M</td> <td>7,337000 G</td> <td>-36.60</td> <td>-23.60</td> </tr> </tbody> </table> <p>Date: 24.FEB.2018 13:38:58</p>	Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]	35,000 M	820,000 M	1,000 M	575,100000 M	-44.18	-31.18	855,000 M	1,000 G	1,000 M	930,862506 M	-42.89	-29.89	1,000 G	3,000 G	1,000 M	2,726000 G	-42.31	-29.31	3,000 G	7,000 G	1,000 M	5,190000 G	-39.75	-26.75	7,000 G	9,000 G	1,000 M	7,337000 G	-36.60	-23.60	 <table border="1" data-bbox="861 1178 1324 1256"> <thead> <tr> <th>Start [Hz]</th> <th>Stop [Hz]</th> <th>RBW [Hz]</th> <th>Freq [Hz]</th> <th>Power [dBm]</th> <th>Limit [dBm]</th> </tr> </thead> <tbody> <tr> <td>35,000 M</td> <td>820,000 M</td> <td>1,000 M</td> <td>406,040000 M</td> <td>-44.17</td> <td>-31.17</td> </tr> <tr> <td>855,000 M</td> <td>1,000 G</td> <td>1,000 M</td> <td>917,920004 M</td> <td>-43.59</td> <td>-30.59</td> </tr> <tr> <td>1,000 G</td> <td>3,000 G</td> <td>1,000 M</td> <td>2,998000 G</td> <td>-41.81</td> <td>-28.81</td> </tr> <tr> <td>3,000 G</td> <td>7,000 G</td> <td>1,000 M</td> <td>5,003000 G</td> <td>-39.36</td> <td>-26.36</td> </tr> <tr> <td>7,000 G</td> <td>9,000 G</td> <td>1,000 M</td> <td>7,634500 G</td> <td>-36.87</td> <td>-23.87</td> </tr> </tbody> </table> <p>Date: 7.MAR.2018 16:30:35</p>	Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]	35,000 M	820,000 M	1,000 M	406,040000 M	-44.17	-31.17	855,000 M	1,000 G	1,000 M	917,920004 M	-43.59	-30.59	1,000 G	3,000 G	1,000 M	2,998000 G	-41.81	-28.81	3,000 G	7,000 G	1,000 M	5,003000 G	-39.36	-26.36	7,000 G	9,000 G	1,000 M	7,634500 G	-36.87	-23.87
Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]																																																																				
35,000 M	820,000 M	1,000 M	575,100000 M	-44.18	-31.18																																																																				
855,000 M	1,000 G	1,000 M	930,862506 M	-42.89	-29.89																																																																				
1,000 G	3,000 G	1,000 M	2,726000 G	-42.31	-29.31																																																																				
3,000 G	7,000 G	1,000 M	5,190000 G	-39.75	-26.75																																																																				
7,000 G	9,000 G	1,000 M	7,337000 G	-36.60	-23.60																																																																				
Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]																																																																				
35,000 M	820,000 M	1,000 M	406,040000 M	-44.17	-31.17																																																																				
855,000 M	1,000 G	1,000 M	917,920004 M	-43.59	-30.59																																																																				
1,000 G	3,000 G	1,000 M	2,998000 G	-41.81	-28.81																																																																				
3,000 G	7,000 G	1,000 M	5,003000 G	-39.36	-26.36																																																																				
7,000 G	9,000 G	1,000 M	7,634500 G	-36.87	-23.87																																																																				
Highest Channel	Highest Channel																																																																								
 <table border="1" data-bbox="207 1695 670 1774"> <thead> <tr> <th>Start [Hz]</th> <th>Stop [Hz]</th> <th>RBW [Hz]</th> <th>Freq [Hz]</th> <th>Power [dBm]</th> <th>Limit [dBm]</th> </tr> </thead> <tbody> <tr> <td>35,000 M</td> <td>820,000 M</td> <td>1,000 M</td> <td>795,112500 M</td> <td>-44.95</td> <td>-31.95</td> </tr> <tr> <td>855,000 M</td> <td>1,000 G</td> <td>1,000 M</td> <td>855,181250 M</td> <td>-37.45</td> <td>-24.45</td> </tr> <tr> <td>1,000 G</td> <td>3,000 G</td> <td>1,000 M</td> <td>1,097500 G</td> <td>-38.83</td> <td>-25.83</td> </tr> <tr> <td>3,000 G</td> <td>7,000 G</td> <td>1,000 M</td> <td>3,027000 G</td> <td>-39.85</td> <td>-26.85</td> </tr> <tr> <td>7,000 G</td> <td>9,000 G</td> <td>1,000 M</td> <td>7,912500 G</td> <td>-36.73</td> <td>-23.73</td> </tr> </tbody> </table> <p>Date: 24.FEB.2018 13:39:49</p>	Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]	35,000 M	820,000 M	1,000 M	795,112500 M	-44.95	-31.95	855,000 M	1,000 G	1,000 M	855,181250 M	-37.45	-24.45	1,000 G	3,000 G	1,000 M	1,097500 G	-38.83	-25.83	3,000 G	7,000 G	1,000 M	3,027000 G	-39.85	-26.85	7,000 G	9,000 G	1,000 M	7,912500 G	-36.73	-23.73	 <table border="1" data-bbox="861 1695 1324 1774"> <thead> <tr> <th>Start [Hz]</th> <th>Stop [Hz]</th> <th>RBW [Hz]</th> <th>Freq [Hz]</th> <th>Power [dBm]</th> <th>Limit [dBm]</th> </tr> </thead> <tbody> <tr> <td>35,000 M</td> <td>820,000 M</td> <td>1,000 M</td> <td>731,322500 M</td> <td>-43.96</td> <td>-30.96</td> </tr> <tr> <td>855,000 M</td> <td>1,000 G</td> <td>1,000 M</td> <td>877,765002 M</td> <td>-43.35</td> <td>-30.35</td> </tr> <tr> <td>1,000 G</td> <td>3,000 G</td> <td>1,000 M</td> <td>2,901500 G</td> <td>-41.98</td> <td>-28.98</td> </tr> <tr> <td>3,000 G</td> <td>7,000 G</td> <td>1,000 M</td> <td>4,951000 G</td> <td>-39.06</td> <td>-26.06</td> </tr> <tr> <td>7,000 G</td> <td>9,000 G</td> <td>1,000 M</td> <td>8,351500 G</td> <td>-36.29</td> <td>-23.29</td> </tr> </tbody> </table> <p>Date: 7.MAR.2018 16:33:48</p>	Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]	35,000 M	820,000 M	1,000 M	731,322500 M	-43.96	-30.96	855,000 M	1,000 G	1,000 M	877,765002 M	-43.35	-30.35	1,000 G	3,000 G	1,000 M	2,901500 G	-41.98	-28.98	3,000 G	7,000 G	1,000 M	4,951000 G	-39.06	-26.06	7,000 G	9,000 G	1,000 M	8,351500 G	-36.29	-23.29
Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]																																																																				
35,000 M	820,000 M	1,000 M	795,112500 M	-44.95	-31.95																																																																				
855,000 M	1,000 G	1,000 M	855,181250 M	-37.45	-24.45																																																																				
1,000 G	3,000 G	1,000 M	1,097500 G	-38.83	-25.83																																																																				
3,000 G	7,000 G	1,000 M	3,027000 G	-39.85	-26.85																																																																				
7,000 G	9,000 G	1,000 M	7,912500 G	-36.73	-23.73																																																																				
Start [Hz]	Stop [Hz]	RBW [Hz]	Freq [Hz]	Power [dBm]	Limit [dBm]																																																																				
35,000 M	820,000 M	1,000 M	731,322500 M	-43.96	-30.96																																																																				
855,000 M	1,000 G	1,000 M	877,765002 M	-43.35	-30.35																																																																				
1,000 G	3,000 G	1,000 M	2,901500 G	-41.98	-28.98																																																																				
3,000 G	7,000 G	1,000 M	4,951000 G	-39.06	-26.06																																																																				
7,000 G	9,000 G	1,000 M	8,351500 G	-36.29	-23.29																																																																				



**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GPRS class 8)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0072	0.0203	PASS
40	Normal Voltage	0.0155	0.0036	
30	Normal Voltage	0.0084	0.0191	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0036	0.0155	
0	Normal Voltage	0.0132	0.0096	
-10	Normal Voltage	0.0036	0.0108	
-20	Normal Voltage	0.0024	0.0072	
-30	Normal Voltage	0.0155	0.0036	
20	Maximum Voltage	0.0036	0.0024	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0060	0.0012	

**Note:**

1. Normal Voltage = 3.8 V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block.



## Appendix B. Test Results of ERP/EIRP and Radiated Test

### ERP/EIRP

Channel	Mode	Conducted		ERP	
		Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	GSM850	31.58	1.4388	23.83	0.2415
Middle	GPRS class 8	32.35	1.7179	24.60	0.2884
Highest	(GT - LC = -5.6 dB)	32.63	1.8323	24.88	0.3076
Lowest	GSM850	26.04	0.4018	18.29	0.0675
Middle	EDGE class 8	25.93	0.3917	18.18	0.0658
Highest	(GT - LC = -5.6 dB)	26.12	0.4093	18.37	0.0687
Lowest	WCDMA Band V	22.67	0.1849	14.92	0.0310
Middle	RMC 12.2Kbps	22.66	0.1845	14.91	0.0310
Highest	(GT - LC = -5.6 dB)	22.66	0.1845	14.91	0.0310
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900	29.49	0.8892	27.39	0.5483
Middle	GPRS class 8	29.37	0.8650	27.27	0.5333
Highest	(GT - LC = -2.1 dB)	29.25	0.8414	27.15	0.5188
Lowest	GSM1900	25.36	0.3436	23.26	0.2118
Middle	EDGE class 8	25.36	0.3436	23.26	0.2118
Highest	(GT - LC = -2.1 dB)	25.36	0.3436	23.26	0.2118
Lowest	WCDMA Band II	22.44	0.1754	20.34	0.1081
Middle	RMC 12.2Kbps	22.52	0.1786	20.42	0.1102
Highest	(GT - LC = -2.1 dB)	22.68	0.1854	20.58	0.1143
Limit	EIRP < 2W	Result		PASS	



**Radiated Spurious Emission**

**Part22H GPRS850**

GPRS 850									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-45.29	-13	-32.29	-59.9	-50.68	1.23	8.76	H
	2472	-54.57	-13	-41.57	-72.29	-61.46	1.44	10.48	H
	3296	-54.97	-13	-41.97	-76	-62.91	1.70	11.79	H
									H
									H
									H
	1648	-42.58	-13	-29.58	-57.19	-47.97	1.23	8.76	V
	2472	-54.89	-13	-41.89	-72.61	-61.78	1.44	10.48	V
	3296	-55.18	-13	-42.18	-76.21	-63.12	1.70	11.79	V
									V
									V
									V
Middle	1672	-45.30	-13	-32.30	-59.98	-50.77	1.24	8.85	H
	2508	-57.39	-13	-44.39	-75.28	-64.31	1.44	10.51	H
	3344	-54.48	-13	-41.48	-75.64	-62.52	1.74	11.93	H
									H
									H
									H
	1672	-42.54	-13	-29.54	-57.22	-48.01	1.24	8.85	V
	2508	-57.78	-13	-44.78	-75.67	-64.70	1.44	10.51	V
	3344	-54.35	-13	-41.35	-75.51	-62.39	1.74	11.93	V
									V
									V
									V



Highest	1696	-50.81	-13	-37.81	-65.55	-56.36	1.24	8.94	H
	2544	-57.53	-13	-44.53	-75.58	-64.47	1.44	10.54	H
	3392	-54.65	-13	-41.65	-76.19	-62.79	1.78	12.08	H
									H
									H
									H
									H
	1696	-40.92	-13	-27.92	-55.66	-46.47	1.24	8.94	V
	2544	-57.99	-13	-44.99	-76.04	-64.93	1.44	10.54	V
	3392	-54.94	-13	-41.94	-76.24	-63.08	1.78	12.08	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



**Part22H EDGE850**

EDGE 850									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-48.62	-13	-35.62	-63.23	-54.01	1.23	8.76	H
	2472	-58.16	-13	-45.16	-75.88	-65.05	1.44	10.48	H
	3296	-55.31	-13	-42.31	-76.34	-63.25	1.70	11.79	H
									H
									H
									H
									H
	1648	-45.20	-13	-32.20	-59.81	-50.59	1.23	8.76	V
	2472	-58.18	-13	-45.18	-75.9	-65.07	1.44	10.48	V
	3296	-55.25	-13	-42.25	-76.28	-63.19	1.70	11.79	V
									V
									V
									V
									V
Middle	1672	-51.15	-13	-38.15	-65.83	-56.62	1.24	8.85	H
	2512	-57.96	-13	-44.96	-75.85	-64.88	1.44	10.51	H
	3344	-54.97	-13	-41.97	-76.13	-63.01	1.74	11.93	H
									H
									H
									H
									H
	1672	-47.18	-13	-34.18	-61.86	-52.65	1.24	8.85	V
	2512	-57.80	-13	-44.80	-75.69	-64.72	1.44	10.51	V
	3344	-54.87	-13	-41.87	-76.03	-62.91	1.74	11.93	V
									V
									V
									V
									V



Highest	1696	-52.32	-13	-39.32	-67.06	-57.87	1.24	8.94	H
	2544	-56.81	-13	-43.81	-74.86	-63.75	1.44	10.54	H
	3392	-55.04	-13	-42.04	-76.34	-63.18	1.78	12.08	H
									H
									H
									H
									H
	1696	-42.26	-13	-29.26	-57	-47.81	1.24	8.94	V
	2544	-57.83	-13	-44.83	-75.88	-64.77	1.44	10.54	V
	3392	-54.97	-13	-41.97	-76.27	-63.11	1.78	12.08	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



**Part22H WCDMA850**

WCDMA 850									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1652	-60.71	-13	-47.71	-75.35	-66.11	1.23	8.78	H
	2480	-58.07	-13	-45.07	-75.79	-64.97	1.44	10.48	H
	3306	-55.51	-13	-42.51	-76.58	-63.47	1.71	11.82	H
									H
									H
									H
									H
	1652	-60.63	-13	-47.63	-75.27	-66.03	1.23	8.78	V
	2480	-57.87	-13	-44.87	-75.59	-64.77	1.44	10.48	V
	3306	-55.25	-13	-42.25	76.32	-63.21	1.71	11.82	V
									V
									V
									V
									V
Middle	1672	-60.73	-13	-47.73	-75.41	-66.20	1.24	8.85	H
	2509	-57.16	-13	-44.16	-75.05	-64.08	1.44	10.51	H
	3346	-55.20	-13	-42.20	-76.36	-63.24	1.74	11.94	H
									H
									H
									H
									H
	1672	-60.18	-13	-47.18	-74.86	-65.65	1.24	8.85	V
	2509	-57.67	-13	-44.67	-75.56	-64.59	1.44	10.51	V
	3346	-54.81	-13	-41.81	-75.97	-62.85	1.74	11.94	V
									V
									V
									V
									V



Highest	1693	-60.71	-13	-47.71	-75.45	-66.25	1.24	8.93	H
	2540	-57.75	-13	-44.75	-75.8	-64.69	1.44	10.53	H
	3386	-55.10	-13	-42.10	-76.36	-63.23	1.78	12.06	H
									H
									H
									H
									H
	1693	-60.73	-13	-47.73	-75.47	-66.27	1.24	8.93	V
	2540	-57.77	-13	-44.77	-75.82	-64.71	1.44	10.53	V
	3386	-55.22	-13	-42.22	-76.48	-63.35	1.78	12.06	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



**Part24E GPRS1900**

GPRS 1900									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-43.09	-13	-30.09	-64.95	-53.40	1.97	12.28	H
	5548	-33.70	-13	-20.70	-61.69	-43.82	2.14	12.27	H
	7403	-41.63	-13	-28.63	-76.17	-49.63	2.17	10.17	H
									H
									H
									H
									H
	3700	-38.96	-13	-25.96	-60.82	-49.27	1.97	12.28	V
	5548	-34.79	-13	-21.79	-62.78	-44.91	2.14	12.27	V
	7403	-41.49	-13	-28.49	-76.03	-49.49	2.17	10.17	V
									V
									V
									V
									V
Middle	3763	-47.44	-13	-34.44	-69.39	-57.68	2.01	12.24	H
	5639	-33.20	-13	-20.20	-61.44	-43.47	2.12	12.39	H
	7518	-41.47	-13	-28.47	-76.19	-49.42	2.11	10.06	H
									H
									H
									H
									H
	3763	-39.90	-13	-26.90	-61.85	-50.14	2.01	12.24	V
	5639	-34.81	-13	-21.81	-63.05	-45.08	2.12	12.39	V
	7518	-41.40	-13	-28.40	-76.12	-49.35	2.11	10.06	V
									V
									V
									V
									V



Highest	3819	-41.21	-13	-28.21	-63.23	-51.38	2.04	12.21	H
	5730	-32.88	-13	-19.88	-61.39	-43.30	2.10	12.52	H
	7634	-40.84	-13	-27.84	-75.74	-49.21	2.11	10.48	H
									H
									H
									H
									H
	3819	-50.27	-13	-37.27	-72.29	-60.44	2.04	12.21	V
	5730	-33.29	-13	-20.29	-61.8	-43.71	2.10	12.52	V
	7634	-41.19	-13	-28.19	-76.09	-49.56	2.11	10.48	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



**Part24E EDGE1900**

EDGE 1900									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-43.52	-13	-30.52	-65.38	-53.83	1.97	12.28	H
	5548	-38.11	-13	-25.11	-66.1	-48.23	2.14	12.27	H
	7400	-41.67	-13	-28.67	-76.17	-49.67	2.18	10.18	H
									H
									H
									H
									H
	3700	-42.46	-13	-29.46	-64.32	-52.77	1.97	12.28	V
	5550	-41.00	-13	-28.00	-68.99	-51.13	2.14	12.27	V
	7400	-41.61	-13	-28.61	-76.11	-49.61	2.18	10.18	V
									V
									V
									V
									V
Middle	3763	-51.16	-13	-38.16	-73.11	-61.40	2.01	12.24	H
	5639	-37.74	-13	-24.74	-65.98	-48.01	2.12	12.39	H
	7522	-41.49	-13	-28.49	-76.24	-49.45	2.11	10.08	H
									H
									H
									H
									H
	3763	-43.03	-13	-30.03	-64.98	-53.27	2.01	12.24	V
	5639	-38.35	-13	-25.35	-66.59	-48.62	2.12	12.39	V
	7522	-41.44	-13	-28.44	-76.19	-49.40	2.11	10.08	V
									V
									V
									V
									V



Highest	3819	-52.71	-13	-39.71	-74.73	-62.88	2.04	12.21	H
	5730	-37.61	-13	-24.61	-66.12	-48.03	2.10	12.52	H
	7634	-41.18	-13	-28.18	-76.08	-49.55	2.11	10.48	H
									H
									H
									H
									H
	3819	-41.10	-13	-28.10	-63.12	-51.27	2.04	12.21	V
	5730	-38.24	-13	-25.24	-66.75	-48.66	2.10	12.52	V
	7634	-40.54	-13	-27.54	-75.44	-48.91	2.11	10.48	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



**Part24E WCDMA1900**

WCDMA 1900									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-53.37	-13	-40.37	-75.23	-63.68	1.97	12.28	H
	5555	-46.30	-13	-33.30	-74.28	-56.43	2.14	12.28	H
	7410	-41.56	-13	-28.56	-76.1	-49.55	2.17	10.16	H
									H
									H
									H
									H
	3700	-48.38	-13	-35.38	-70.24	-58.69	1.97	12.28	V
	5555	-46.37	-13	-33.37	-74.35	-56.50	2.14	12.28	V
	7410	-41.64	-13	-28.64	-76.18	-49.63	2.17	10.16	V
									V
									V
									V
									V
Middle	3763	-54.19	-13	-41.19	-76.14	-64.43	2.01	12.24	H
	5639	-45.87	-13	-32.87	-74.11	-56.14	2.12	12.39	H
	7522	-41.40	-13	-28.40	-76.15	-49.36	2.11	10.08	H
									H
									H
									H
									H
	3763	-49.29	-13	-36.29	-71.24	-59.53	2.01	12.24	V
	5639	-45.98	-13	-32.98	-74.22	-56.25	2.12	12.39	V
	7522	-41.19	-13	-28.19	-75.94	-49.15	2.11	10.08	V
									V
									V
									V
									V



Highest	3812	-54.13	-13	-41.13	-76.12	-64.31	2.03	12.21	H
	5723	-45.88	-13	-32.88	-74.39	-56.29	2.10	12.51	H
	7627	-41.05	-13	-28.05	-75.95	-49.39	2.11	10.46	H
									H
									H
									H
									H
	3812	-49.10	-13	-36.10	-71.09	-59.28	2.03	12.21	V
	5723	-45.19	-13	-32.19	-73.7	-55.60	2.10	12.51	V
	7627	-41.11	-13	-28.11	-76.01	-49.45	2.11	10.46	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.