



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : T-Mobile
MODEL NAME : XT1965-T
FCC ID : IHDT56XN4
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Feb. 01, 2019 and testing was completed on Feb. 21, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Specification of Accessory 7

 1.7. Test Location 8

 1.8. Applicable Standards 8

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1. Test Mode 9

 2.2. Connection Diagram of Test System 11

 2.3. Support Unit used in test configuration and system 11

 2.4. EUT Operation Test Setup 12

3. TEST RESULT 13

 3.1. Test of AC Conducted Emission Measurement 13

 3.2. Test of Radiated Emission Measurement 17

4. LIST OF MEASURING EQUIPMENT 22

5. UNCERTAINTY OF EVALUATION 23

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|----------|-----------------------|-----------------|--------|---|
| 3.1 | 15.107 | AC Conducted Emission | < 15.107 limits | PASS | Under limit 9.06 dB at 13.560 MHz |
| 3.2 | 15.109 | Radiated Emission | < 15.109 limits | PASS | Under limit 5.88 dB at 46.490 MHz |



1. General Description

1.1. Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|---|
| Equipment | Mobile Cellular Phone |
| Brand Name | T-Mobile |
| Model Name | XT1965-T |
| FCC ID | IHDT56XN4 |
| EUT supports Radios application | CDMA/EVDO/GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC/GNSS/FM Receiver |
| IMEI Code | Conduction: 355572090012583 Radiation: 355572090012476 354133100003541 |
| HW Version | PVT |
| SW Version | PCW29.81 |
| EUT Stage | Identical Prototype |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

| Standards-related Product Specification | |
|---|--|
| Tx Frequency | GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 814.7 MHz ~ 848.3 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz LTE Band 71: 665.5 MHz ~ 695.5MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz CDMA2000 BC10: 817.9 MHz ~ 823.1 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz |
| Rx Frequency | GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7 MHz ~ 1994.3 MHz LTE Band 26 : 859.7 MHz ~ 893.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 66 : 2110.7 MHz~ 2199.3 MHz LTE Band 71: 619.5 MHz ~ 649.5MHz CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz CDMA2000 BC10: 862.9 MHz ~ 868.1 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; |



| | |
|---------------------------|--|
| | <p>5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz NFC : 13.56 MHz FM: 88 MHz - 108 MHz</p> |
| Antenna Type | <p>WWAN : Internal Antenna WLAN : Internal Antenna Bluetooth : Internal Antenna GNSS: Internal Antenna NFC : loop Antenna FM : External Handset Antenna</p> |
| Type of Modulation | <p>GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM(uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK FM</p> |

WLAN operation in 5600 MHz ~ 5650 MHz is notched.

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Specification of Accessory

| Specification of Accessory | | | | |
|----------------------------|-------------------------|---|-------------------|------------|
| AC Adapter 1 | Brand Name | Motorola (Salom) | Model Name | SC-31 |
| | Power Rating | I/P: 100-240 Vac, 800mA O/P: 5Vdc,3000mA; 9Vdc,3000mA | | |
| AC Adapter 2 | Brand Name | Motorola (Acbel) | Model Name | SC-31 |
| | Power Rating | I/P: 100-240 Vac, 800mA O/P: 5Vdc,3000mA; 9Vdc,3000mA | | |
| Battery | Brand Name | Motorola(Amperex) | Model Name | JG40 |
| | Power Rating | 3.8Vdc,3000mAh | Type | Li-ion |
| USB Cable | Brand Name | Motorola (Cabletech) | Model Name | SC18C47591 |
| | Signal Line Type | 1.0 meter, shielded cable, without ferrite core | | |



1.7. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

| | | | |
|---------------------------|---|----------------------------|---------------------------------------|
| Test Site | Sporton International (Kunshan) Inc. | | |
| Test Site Location | No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958 | | |
| Test Site No. | Sporton Site No. | FCC designation No. | FCC Test Firm Registration No. |
| | CO01-KS 03CH02-KS | CN5013 | 630927 |

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


| Test Items | Function Type |
|-----------------------|---|
| AC Conducted Emission | Mode 1: GSM850 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable(Charging from Adapter 1) + Earphone |
| | Mode 2: GSM1900 Rx + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable(Charging from Adapter 2) + Earphone |
| | Mode 3: CDMA BC10 Rx(Low) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4+ USB Cable(Charging from Adapter 1) + Earphone |
| | Mode 4: LTE Band 12 RX(Middle) + Bluetooth Idle + WLAN (5G) Idle + NFC On + USB Cable(Charging from Adapter 1) + Earphone |
| | Mode 5: LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx(98MHz) + USB Cable(Charging from Adapter 1) + Earphone |
| | Mode 6: LTE Band 71 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable (Data Link with Notebook) + Earphone |
| Radiated Emissions | Mode 1: GSM850 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable(Charging from Adapter 1) + Earphone + SIM 1 |
| | Mode 2: GSM1900 Rx + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable(Charging from Adapter 2) + Earphone + SIM 2 |
| | Mode 3: CDMA BC10 Rx(Low) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4+ USB Cable(Charging from Adapter 2) + Earphone + SIM 1 |
| | Mode 4: LTE Band 12 RX(Middle) + Bluetooth Idle + WLAN (5G) Idle + NFC On + USB Cable(Charging from Adapter 2) + Earphone + SIM 2 |
| | Mode 5: LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx(98MHz) + USB Cable(Charging from Adapter 2) + Earphone + SIM 1 |
| | Mode 6: LTE Band 71 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable (Data Link with Notebook) + Earphone + SIM 2 |



Remark:

1. The worst case of AC is mode 4; only the test data of this mode is reported.
2. The worst case of RE is mode 6; only the test data of this mode is reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook..
4. GNSS Rx = Galileo + GLONASS + GPS
5. Pre-scanned Low/Middle/High channel for GSM850/CDMABC10/LTE Band 12/13/71, FM Rx, the worst channel was recorded in this report.

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model Name | FCC ID | Data Cable | Power Cord |
|------|-------------------------|------------|------------|-------------|------------------|--|
| 1. | System Simulator | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8m |
| 2. | Signal Generator | R&S | GSS7000 | NA | NA | Unshielded, 1.8m |
| 3. | Vector Signal Generator | R&S | SMBV100A | 258305 | N/A | N/A |
| 4. | WLAN AP | D-Link | DIR-855 | KA2DIR855A2 | N/A | Unshielded, 1.8m |
| 5. | WLAN AP | TP-LINK | TL-WDR5600 | N/A | N/A | Unshielded, 1.8m |
| 6. | Bluetooth Earphone | Lenovo | LBH308 | N/A | N/A | N/A |
| 7. | Bluetooth Earphone | Lenovo | LYEJ02LM | N/A | N/A | N/A |
| 8. | Notebook | Lenovo | YOGA S730 | N/A | N/A | AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m |
| 9. | Notebook | DELL | MT320 | N/A | N/A | AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m |
| 10. | SD Card | Kingston | 8GB | N/A | N/A | N/A |
| 11. | SD Card | SanDisk | Uitra | N/A | N/A | N/A |
| 12. | Hard Disk | Lenovo | LH310 | N/A | Shielded, 1.2m | N/A |
| 13. | Earphone | Lenovo | SH100 | N/A | Unshielded, 1.2m | N/A |



2.4. EUT Operation Test Setup

The EUT was in GSM or CDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on MPEG4 function.
5. Turn on FM receiver function to make the EUT receive continuous signals from FM station
6. Turn on NFC function



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

| Frequency of emission (MHz) | Conducted limit (dBuV) | |
|--------------------------------|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

| | | | |
|-----------------|---------------|---------------------|-------------|
| Test Engineer : | Amos Zhang | Temperature : | 25.3~26.2°C |
| | | Relative Humidity : | 38~40% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Line |




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L-181013-060103 LINE
 Project : (FC) 920101
 mode : Mode 4
 : 355572090012583 #5

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|------|--------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.469 | 40.67 | -15.87 | 56.54 | 30.20 | 0.23 | 10.24 | QP |
| 2 | 0.469 | 25.07 | -21.47 | 46.54 | 14.60 | 0.23 | 10.24 | Average |
| 3 | 0.647 | 35.97 | -20.03 | 56.00 | 25.50 | 0.23 | 10.24 | QP |
| 4 | 0.647 | 25.67 | -20.33 | 46.00 | 15.20 | 0.23 | 10.24 | Average |
| 5 | 1.229 | 37.08 | -18.92 | 56.00 | 26.60 | 0.25 | 10.23 | QP |
| 6 | 1.229 | 23.78 | -22.22 | 46.00 | 13.30 | 0.25 | 10.23 | Average |
| 7 | 1.628 | 37.08 | -18.92 | 56.00 | 26.60 | 0.25 | 10.23 | QP |
| 8 | 1.628 | 23.78 | -22.22 | 46.00 | 13.30 | 0.25 | 10.23 | Average |
| 9 | 10.233 | 41.09 | -18.91 | 60.00 | 30.51 | 0.24 | 10.34 | QP |
| 10 | 10.233 | 32.19 | -17.81 | 50.00 | 21.61 | 0.24 | 10.34 | Average |
| 11 | 12.716 | 38.28 | -21.72 | 60.00 | 27.60 | 0.31 | 10.37 | QP |
| 12 | 12.716 | 30.88 | -19.12 | 50.00 | 20.20 | 0.31 | 10.37 | Average |
| 13 | 13.560 | 45.81 | -14.19 | 60.00 | 35.10 | 0.33 | 10.38 | QP |
| 14 * | 13.560 | 40.61 | -9.39 | 50.00 | 29.90 | 0.33 | 10.38 | Average |



| | | | |
|-----------------|---------------|---------------------|-------------|
| Test Engineer : | Amos Zhang | Temperature : | 25.3~26.2°C |
| | | Relative Humidity : | 38~40% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Neutral |



Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-181013-060103 NEUTRAL
 Project : (FC) 920101
 mode : Mode 4
 : 355572090012583 #5

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|------|--------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.476 | 41.03 | -15.38 | 56.41 | 30.60 | 0.19 | 10.24 | QP |
| 2 | 0.476 | 29.03 | -17.38 | 46.41 | 18.60 | 0.19 | 10.24 | Average |
| 3 | 1.191 | 39.34 | -16.66 | 56.00 | 28.90 | 0.21 | 10.23 | QP |
| 4 | 1.191 | 28.64 | -17.36 | 46.00 | 18.20 | 0.21 | 10.23 | Average |
| 5 | 1.662 | 38.65 | -17.35 | 56.00 | 28.20 | 0.22 | 10.23 | QP |
| 6 | 1.662 | 29.75 | -16.25 | 46.00 | 19.30 | 0.22 | 10.23 | Average |
| 7 | 1.908 | 38.05 | -17.95 | 56.00 | 27.60 | 0.22 | 10.23 | QP |
| 8 | 1.908 | 30.05 | -15.95 | 46.00 | 19.60 | 0.22 | 10.23 | Average |
| 9 | 10.963 | 40.86 | -19.14 | 60.00 | 30.30 | 0.21 | 10.35 | QP |
| 10 | 10.963 | 34.46 | -15.54 | 50.00 | 23.90 | 0.21 | 10.35 | Average |
| 11 | 13.560 | 44.84 | -15.16 | 60.00 | 34.20 | 0.26 | 10.38 | QP |
| 12 * | 13.560 | 40.94 | -9.06 | 50.00 | 30.30 | 0.26 | 10.38 | Average |
| 13 | 19.428 | 41.41 | -18.59 | 60.00 | 30.61 | 0.32 | 10.48 | QP |
| 14 | 19.428 | 35.11 | -14.89 | 50.00 | 24.31 | 0.32 | 10.48 | Average |



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

| | | | |
|-----------------|---|---------------------|------------|
| Test Engineer : | IMP Xu | Temperature : | 21~22°C |
| | | Relative Humidity : | 41~42% |
| Test Distance : | 3m | Polarization : | Horizontal |
| Remark : | #6 is system simulator signal which can be ignored. | | |




Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 23182-3M HORIZONTAL
 Project : (FC)920101
 Mode : 6

| | Freq | Level | Over Limit | Limit Line | ReadAntenna Level | Cable Factor | Preamp Loss | A/Pos | T/Pos | Remark | |
|-----|-----------|--------|------------|------------|-------------------|--------------|-------------|-------|-------|--------|------|
| | MHz | dBuV/m | dB | dBuV/m | dBuV | dB/m | dB | dB | cm | deg | |
| 1 | 30.000 | 19.77 | -20.23 | 40.00 | 26.64 | 24.50 | 0.61 | 31.98 | --- | --- | Peak |
| 2 | 180.350 | 24.72 | -18.78 | 43.50 | 40.08 | 15.20 | 1.36 | 31.92 | --- | --- | Peak |
| 3 | 240.490 | 35.80 | -10.20 | 46.00 | 48.67 | 17.40 | 1.68 | 31.95 | 100 | 0 | Peak |
| 4 | 299.660 | 27.59 | -18.41 | 46.00 | 38.77 | 19.00 | 1.82 | 32.00 | --- | --- | Peak |
| 5 | 539.250 | 25.08 | -20.92 | 46.00 | 31.32 | 23.63 | 2.45 | 32.32 | --- | --- | Peak |
| 6 * | 634.310 | 46.04 | | | 50.62 | 24.94 | 2.86 | 32.38 | --- | --- | Peak |
| 7 | 718.700 | 26.59 | -19.41 | 46.00 | 30.49 | 25.34 | 3.07 | 32.31 | --- | --- | Peak |
| 8 | 2248.000 | 42.45 | -31.55 | 74.00 | 43.23 | 31.05 | 4.89 | 36.72 | --- | --- | Peak |
| 9 | 3416.000 | 45.64 | -28.36 | 74.00 | 42.58 | 33.41 | 6.04 | 36.39 | --- | --- | Peak |
| 10 | 6336.000 | 45.84 | -28.16 | 74.00 | 39.25 | 34.86 | 8.49 | 36.76 | --- | --- | Peak |
| 11 | 7304.000 | 47.29 | -26.71 | 74.00 | 39.21 | 35.89 | 9.12 | 36.93 | --- | --- | Peak |
| 12 | 9648.000 | 45.75 | -28.25 | 74.00 | 35.25 | 37.37 | 10.85 | 37.72 | --- | --- | Peak |
| 13 | 11772.000 | 45.53 | -28.47 | 74.00 | 30.85 | 39.58 | 11.71 | 36.61 | --- | --- | Peak |



| | | | |
|-----------------|---|---------------------|----------|
| Test Engineer : | IMP Xu | Temperature : | 21~22°C |
| | | Relative Humidity : | 41~42% |
| Test Distance : | 3m | Polarization : | Vertical |
| Remark : | #6 is system simulator signal which can be ignored. | | |



Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 23182-3M VERTICAL
 Project : (FC)920101
 Mode : 6

| | Freq | Level | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | A/Pos | T/Pos | Remark |
|-----|-----------|--------|------------|------------|-------------------|----------------|------------|---------------|-------|-------|--------|
| | MHz | dBuV/m | dB | dBuV/m | dBuV | dB/m | dB | dB | cm | deg | |
| 1 ! | 46.490 | 34.12 | -5.88 | 40.00 | 49.72 | 15.62 | 0.72 | 31.94 | 100 | 0 | Peak |
| 2 | 71.710 | 25.80 | -14.20 | 40.00 | 44.17 | 12.67 | 0.88 | 31.92 | --- | --- | Peak |
| 3 | 263.770 | 26.68 | -19.32 | 46.00 | 37.72 | 19.19 | 1.76 | 31.99 | --- | --- | Peak |
| 4 | 359.800 | 25.09 | -20.91 | 46.00 | 34.69 | 20.57 | 1.92 | 32.09 | --- | --- | Peak |
| 5 | 544.100 | 28.33 | -17.67 | 46.00 | 33.24 | 24.80 | 2.62 | 32.33 | --- | --- | Peak |
| 6 ! | 633.340 | 42.95 | | | 47.55 | 24.93 | 2.85 | 32.38 | --- | --- | Peak |
| 7 | 883.600 | 27.57 | -18.43 | 46.00 | 29.02 | 26.70 | 3.42 | 31.57 | --- | --- | Peak |
| 8 | 1912.000 | 44.99 | -29.01 | 74.00 | 47.62 | 29.73 | 4.42 | 36.78 | --- | --- | Peak |
| 9 | 4240.000 | 45.63 | -28.37 | 74.00 | 39.63 | 35.51 | 7.34 | 36.85 | --- | --- | Peak |
| 10 | 6424.000 | 44.77 | -29.23 | 74.00 | 38.12 | 34.87 | 8.48 | 36.70 | --- | --- | Peak |
| 11 | 7456.000 | 46.36 | -27.64 | 74.00 | 38.17 | 35.98 | 9.22 | 37.01 | --- | --- | Peak |
| 12 | 10809.000 | 45.45 | -28.55 | 74.00 | 33.02 | 38.79 | 11.36 | 37.72 | --- | --- | Peak |
| 13 | 14409.000 | 45.25 | -28.75 | 74.00 | 27.80 | 40.77 | 12.78 | 36.10 | --- | --- | Peak |



4. List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|-----------------------------------|--------------|-------------------|------------------|----------------------------|------------------|---------------|---------------|-----------------------|
| EMI Receiver | R&S | ESC17 | 100768 | 9kHz~7GHz; | Apr. 19, 2018 | Feb. 20, 2019 | Apr. 18, 2019 | Conduction (CO01-KS) |
| AC LISN | MessTec | AN3016 | 060103 | 9kHz~30MHz | Oct. 12, 2018 | Feb. 20, 2019 | Oct. 11, 2019 | Conduction (CO01-KS) |
| AC LISN (for auxiliary equipment) | MessTec | AN3016 | 060105 | 9kHz~30MHz | Nov. 22, 2018 | Feb. 20, 2019 | Nov. 21, 2019 | Conduction (CO01-KS) |
| AC Power Source | Chroma | 61602 | ABP0000008 11 | AC 0V~300V, 45Hz~1000Hz | Oct. 12, 2018 | Feb. 20, 2019 | Oct. 11, 2019 | Conduction (CO01-KS) |
| EMI Test Receiver | R&S | ESR7 | 101403 | 9kHz~7GHz;Ma x 30dBm | Aug. 08, 2018 | Feb. 21, 2019 | Aug. 07, 2019 | Radiation (03CH02-KS) |
| EXA Spectrum Analyzer | Keysight | N9010A | MY55150208 | 10Hz-44G,MAX 30dB | Oct. 10, 2018 | Feb. 21, 2019 | Oct. 09, 2019 | Radiation (03CH02-KS) |
| Bilog Antenna | TeseQ | CBL6112D | 23182 | 30MHz-2GHz | Dec. 29, 2018 | Feb. 21, 2019 | Dec. 28, 2019 | Radiation (03CH02-KS) |
| Double Ridge Horn Antenna | ETS-Lindgren | 3117 | 75959 | 1GHz~18GHz | Jan. 27, 2019 | Feb. 21, 2019 | Jan. 26, 2020 | Radiation (03CH02-KS) |
| SHF-EHF Horn | Schwarzbeck | BBHA 9170 | BBHA170249 | 15GHz~40GHz | Jan. 05, 2019 | Feb. 21, 2019 | Jan. 04, 2020 | Radiation (03CH02-KS) |
| Amplifier | SONOMA | 310N | 187289 | 9KHz-1GHz | Aug. 06, 2018 | Feb. 21, 2019 | Aug. 05, 2019 | Radiation (03CH02-KS) |
| Amplifier | Keysight | 83017A | MY53270203 | 500MHz~26.5G Hz | Apr. 18, 2018 | Feb. 21, 2019 | Apr. 17, 2019 | Radiation (03CH02-KS) |
| Amplifier | MITEQ | TTA1840-35-H G | 2014749 | 18~40GHz | Jan. 14, 2019 | Feb. 21, 2019 | Jan. 13, 2020 | Radiation (03CH02-KS) |
| AC Power Source | Chroma | 61601 | 61601000247 3 | N/A | NCR | Feb. 21, 2019 | NCR | Radiation (03CH02-KS) |
| Turn Table | MF | MF7802 | N/A | 0~360 degree | NCR | Feb. 21, 2019 | NCR | Radiation (03CH02-KS) |
| Antenna Mast | MF | MF7802 | N/A | 1 m~4 m | NCR | Feb. 21, 2019 | NCR | Radiation (03CH02-KS) |

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 2.9 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 4.8 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 5.2 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 40000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 5.0 dB |
|---|--------|