



FCC TEST REPORT

FCC ID : IHDT56YJ2
Equipment : Mobile Cellular Phone
Brand Name : Motorola
Model Name : XT2061-3
Applicant : Motorola Mobility, LLC
222 W Merchandise Mart Plaza, Suite 1800,
Chicago, IL 60654, United States
Manufacturer : Motorola Mobility, LLC
222 W Merchandise Mart Plaza, Suite 1800,
Chicago, IL 60654, United States
Standard : FCC 47 CFR FCC Part 15 Subpart B Class B

The product was received on Jan. 16, 2020 and testing was started from Jan. 22, 2020 and completed on Jan. 30, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report..... 3

Summary of Test Result..... 4

1. General Description 5

 1.1. Product Feature of Equipment Under Test 5

 1.2. Product Specification of Equipment Under Test 6

 1.3. Modification of EUT 8

 1.4. Test Location 9

 1.5. Applicable Standards 9

2. Test Configuration of Equipment Under Test 10

 2.1. Test Mode 10

 2.2. Connection Diagram of Test System 12

 2.3. Support Unit used in test configuration and system..... 13

 2.4. EUT Operation Test Setup 13

3. Test Result 14

 3.1. Test of AC Conducted Emission Measurement 14

 3.2. Test of Radiated Emission Measurement 16

4. List of Measuring Equipment..... 18

5. Uncertainty of Evaluation 19

Appendix A. AC Conducted Emission Test Result

Appendix B. Radiated Emission Test Result



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.107	AC Conducted Emission	Pass	Under limit 6.11 dB at 0.449 MHz
3.2	15.109	Radiated Emission	Pass	Under limit 4.56 dB at 40.670 MHz for Quasi-Peak

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Dara Chiu

Report Producer: Jessie Ho



1. General Description

1.1. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2061-3
FCC ID	IHDT56YJ2
IMEI Code	Conduction : IMEI: 359124100005417 Radiation : IMEI: 359124100005367
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/ GNSS/NFC/WPC WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 WLAN 11ax HE20/HE40/HE80 Bluetooth BR/EDR/LE
HW Version	DVT2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Accessory List	
AC Adapter 1	Brand Name : Motorola
	Model Name : SC-51 (SA18C30116)
	Manufacturer : Chenyang
AC Adapter 2	Brand Name : Motorola
	Model Name : SC-51 (SA18C62985)
	Manufacturer : Acbel
Battery	Brand Name : ATL
	Model Name : LW50
USB Cable 1	Brand Name : Motorola
	Model Name : SC18C24367
	Manufacturer : Saibao
USB Cable 2	Brand Name : Motorola
	Model Name : SC18C24368
	Manufacturer : Luxshare



1.2. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 25: 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 824.7 MHz ~ 848.3 MHz LTE Band 30: 2307.5 MHz ~ 2312.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz LTE Band 71: 665.5 MHz ~ 695.5 MHz 5G NR Band n5: 826.5 MHz ~ 846.5 MHz 5G NR Band n66: 1712.5 MHz ~ 1777.5 MHz 5G NR Band n71: 665.5 MHz ~ 695.5 MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac/ax: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5580 MHz and 5660 MHz ~ 5700 MHz; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz



Standards-related Product Specification	
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV: 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2: 1930.7 MHz ~ 1989.3 MHz LTE Band 4: 2110.7 MHz ~ 2154.3 MHz LTE Band 5: 869.7 MHz ~ 893.3 MHz LTE Band 7: 2622.5 MHz ~ 2687.5 MHz LTE Band 12: 729.7 MHz ~ 745.3 MHz LTE Band 13: 748.5 MHz ~ 753.5 MHz LTE Band 17: 736.5 MHz ~ 743.5 MHz LTE Band 25: 1930.7 MHz ~ 1994.3 MHz LTE Band 26: 869.7 MHz ~ 893.3 MHz LTE Band 30: 2352.5 MHz ~ 2357.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz LTE Band 66: 2110.7 MHz ~ 2199.3 MHz LTE Band 71: 619.5 MHz ~ 649.5 MHz 5G NR Band n5: 871.5 MHz ~ 891.5 MHz 5G NR Band n66: 2112.5 MHz ~ 2197.5 MHz 5G NR Band n71: 619.5 MHz ~ 649.5 MHz CDMA 2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA 2000 BC1: 1931.25 MHz ~ 1988.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac/ax: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5580 MHz and 5660 MHz ~ 5700 MHz; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 ~ 1610 MHz (GPS/Glonass/Galileo/BDS) NFC : 13.56 MHz WPC: 80 kHz ~ 300 kHz
Antenna Type	WWAN: Fixed Internal Antenna WLAN: <Ant. 1>: ILA Antenna <Ant. 2>: ILA Antenna Bluetooth: ILA Antenna GPS/Glonass/Galileo/BDS: ILA Antenna NFC: Ferrite + FPC Antenna WPC: Flex Pattern Antenna



Standards-related Product Specification	
Type of Modulation	GSM / GPRS: GMSK EGPRS: GMSK for MCS 0 ~ 4 & 8PSK for MCS5 ~9 WCDMA: QPSK (Uplink) HSDPA: 64QAM (Downlink) / HSUPA : QPSK (Uplink) CDMA2000 : QPSK LTE: QPSK / 16QAM / 64QAM 5G NR: QPSK / 16QAM / 64QAM 802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) Bluetooth LE: GFSK Bluetooth (1Mbps): GFSK Bluetooth (2Mbps): $\pi/4$ -DQPSK Bluetooth (3Mbps): 8-DPSK GPS/Glonass/Galileo/BDS: BPSK NFC: ASK WPC: load

1.3. Modification of EUT

No modifications are made to the EUT during all test items.



1.4. Test Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	CO05-HY

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH10-HY

FCC designation No.: TW1093 and TW1098

1.5. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ FCC 47 CFR FCC Part 15 Subpart B Class B
- ◆ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + Camera (Front) + Earphone + Battery + USB Cable 1 (Charging from Adapter 1)
	Mode 2: CDMA2000 BC0 (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + Camera (Rear) + Earphone + Battery + USB Cable 2 (Charging from Adapter 2)
	Mode 3: WCDMA Band V (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG4 + Earphone + Battery + USB Cable 1 (Charging from Adapter 1)
	Mode 4: LTE Band 12 (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + NFC On + Earphone + Battery + USB Cable 2 (Charging from Adapter 2)
	Mode 5: LTE Band 13 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + GPS Rx + Earphone + Battery + USB Cable 1 (Data Link with Notebook)
	Mode 6: LTE Band 26 (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + MPEG4 + Earphone + Battery + USB Cable 2 (Data Link with Notebook)
	Mode 7: LTE Band 71 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG4 + Earphone + Battery + WPC Charging pad + USB Cable (Charging from Adapter)



Test Items	Function Type
Radiated Emissions	Mode 1 : GSM850 (Low Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + Camera (Front) + Earphone + Battery + USB Cable 1 (Charging from Adapter 1)
	Mode 2 : CDMA2000 BC0 (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + Camera (Rear) + Earphone + Battery + USB Cable 2 (Charging from Adapter 2)
	Mode 3 : WCDMA Band V (Low Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG4 + Earphone + Battery + USB Cable 1 (Charging from Adapter 1)
	Mode 4 : LTE Band 12 (High Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + NFC On + Earphone + Battery + USB Cable 2 (Charging from Adapter 2)
	Mode 5 : LTE Band 13 (Low Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + GPS Rx + Earphone + Battery + USB Cable 1 (Data Link with Notebook)
	Mode 6 : LTE Band 26 (Low Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + MPEG4 + Earphone + Battery + USB Cable 2 (Data Link with Notebook)
	Mode 7 : LTE Band 71 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG4 + Earphone + Battery + WPC Charging pad + USB Cable (Charging from Adapter)
Remark: <ol style="list-style-type: none">1. The worst case of AC is mode 7; only the test data of this mode was reported.2. The worst case of RE is mode 4; only the test data of this mode was reported.3. For radiation emission after pre-scanned the cellular band between 30MHz ~ 960MHz (GSM850/WCDMA Band V/CDMA BC0/LTE Band 12/13/26/71); only the worst case for cellular band test data of this mode was reported.4. Data Link with Notebook means data application transferred mode between EUT and Notebook.	

2.2. Connection Diagram of Test System



Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	3	4	5	6	7
A1	BT Earphone	Bluetooth	X	X	X	X	X	X	X
A2	System Simulator	GSM/UMTS/CDMA/WCDMA/LTE	X	X	X	X	X	X	X
A3	GPS Station	GPS	-	-	-	-	X	-	-
A4	AP router	WiFi	X	X	X	X	X	X	X
A5	WPC pad	WPC	-	-	-	-	-	-	X
No.	Power Source	Connection Type	1	2	3	4	5	6	7
B1	AC : 120V/60Hz	AC Power Cable	X	X	X	X	-	-	X
B2	Power from system	AC Power Cable	-	-	-	-	X	X	-
No.	Setup Peripherals	Connection Type	1	2	3	4	5	6	7
C1	Notebook	USB Cable	-	-	-	-	X	X	-
C1-1	iPod	USB Cable to C1	-	-	-	-	X	X	-
C1-2	AP router	RJ-45 Cable to C1	-	-	-	-	X	X	-
C2	Earphone	Earphone jack	X	X	X	X	X	X	X

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
4.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
5.	Wireless Charger Stand	Samsung	EP-N5200	N/A	N/A	N/A
6.	Adapter	N/A	N/A	N/A	N/A	N/A
7.	USB Cable	N/A	N/A	N/A	N/A	N/A
8.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
9.	Earphone	Motorola	SH38C37773	N/A	Shielded, 1.0 m	N/A
10.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
11.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
12.	Notebook	DELL	Latitude E3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
13.	Notebook	DELL	Latitude 5480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
14.	LG Charging pad	LG	WCD-110	FCC DoC	Shielded, 0.5 m	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or EDGE or HSDPA or LTE or CDMA2000 idle mode during the testing. The EUT was synchronized with the BCCH, and had been continuous receiving mode by setting paging reorganization of the system simulator.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test:

1. Data application is transferred between Laptop and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive continuous signals from GPS station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.
5. Turn on NFC function.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1. Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2. Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3. Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4. Test Setup



3.1.5. Test Result of AC Conducted Emission

Please refer to Appendix A.



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission

Please refer to Appendix B.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 22, 2019	Jan. 22, 2020	Oct. 21, 2020	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35413 & 02	30MHz~1GHz	Feb. 12, 2019	Jan. 22, 2020	Feb. 11, 2020	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1325	1GHz~18GHz	Oct. 09, 2019	Jan. 22, 2020	Oct. 08, 2020	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JAP00101800-30-10P	160118550004	1GHz~18GHz	Sep. 27, 2019	Jan. 22, 2020	Sep. 26, 2020	Radiation (03CH10-HY)
Signal Analyzer	R&S	FSV3044	101010	10Hz~44GHz	Nov. 11, 2019	Jan. 22, 2020	Nov. 10, 2020	Radiation (03CH10-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jan. 22, 2020	N/A	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jan. 22, 2020	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Jan. 22, 2020	N/A	Radiation (03CH10-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Jan. 22, 2020	N/A	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290045	20MHz~8.4GHz	Jan. 18, 2020	Jan. 22, 2020	Jan. 17, 2021	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	30MHz~1GHz	Nov. 07, 2019	Jan. 22, 2020	Nov. 06, 2020	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	1GHz~18GHz	Nov. 07, 2019	Jan. 22, 2020	Nov. 06, 2020	Radiation (03CH10-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 27, 2020~Jan. 30, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jan. 27, 2020~Jan. 30, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 19, 2019	Jan. 27, 2020~Jan. 30, 2020	Mar. 18, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Jan. 27, 2020~Jan. 30, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jan. 27, 2020~Jan. 30, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jan. 27, 2020~Jan. 30, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jan. 27, 2020~Jan. 30, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jan. 27, 2020~Jan. 30, 2020	Jan. 01, 2021	Conduction (CO05-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.0
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3
---	-----




Appendix A. AC Conducted Emission Test Results

Test Engineer :	Howard Huang and Tom Lee	Temperature :	21~24°C
		Relative Humidity :	40~49%

EUT Information

Report NO : 9D0635-01
 Test Mode : Mode 7
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.153375	---	32.90	55.82	22.92	L1	OFF	19.5
0.153375	47.47	---	65.82	18.35	L1	OFF	19.5
0.166920	---	35.20	55.11	19.91	L1	OFF	19.5
0.166920	48.82	---	65.11	16.29	L1	OFF	19.5
0.420990	---	40.16	47.43	7.27	L1	OFF	19.5
0.420990	44.97	---	57.43	12.46	L1	OFF	19.5
0.450690	---	40.51	46.86	6.35	L1	OFF	19.5
0.450690	46.03	---	56.86	10.83	L1	OFF	19.5
0.478500	---	37.65	46.37	8.72	L1	OFF	19.5
0.478500	43.58	---	56.37	12.79	L1	OFF	19.5
0.611250	---	31.59	46.00	14.41	L1	OFF	19.5
0.611250	37.63	---	56.00	18.37	L1	OFF	19.5
0.870270	---	29.57	46.00	16.43	L1	OFF	19.5
0.870270	35.49	---	56.00	20.51	L1	OFF	19.5
1.533300	---	28.05	46.00	17.95	L1	OFF	19.6
1.533300	35.39	---	56.00	20.61	L1	OFF	19.6
4.089480	---	31.55	46.00	14.45	L1	OFF	19.6
4.089480	35.46	---	56.00	20.54	L1	OFF	19.6
4.344990	---	32.25	46.00	13.75	L1	OFF	19.6
4.344990	37.46	---	56.00	18.54	L1	OFF	19.6
4.599960	---	32.30	46.00	13.70	L1	OFF	19.6

4.599960	36.83	---	56.00	19.17	L1	OFF	19.6
13.285500	---	29.11	50.00	20.89	L1	OFF	19.8
13.285500	35.74	---	60.00	24.26	L1	OFF	19.8
17.373750	---	29.82	50.00	20.18	L1	OFF	19.8
17.373750	37.06	---	60.00	22.94	L1	OFF	19.8
28.879620	---	35.11	50.00	14.89	L1	OFF	19.8
28.879620	40.16	---	60.00	19.84	L1	OFF	19.8

EUT Information

Report NO : 9D0635-01
 Test Mode : Mode 7
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.164400	---	34.38	55.24	20.86	N	OFF	19.6
0.164400	45.90	---	65.24	19.34	N	OFF	19.6
0.193380	---	32.10	53.89	21.79	N	OFF	19.6
0.193380	42.94	---	63.89	20.95	N	OFF	19.6
0.389760	---	36.58	48.07	11.49	N	OFF	19.6
0.389760	40.08	---	58.07	17.99	N	OFF	19.6
0.418830	---	40.52	47.47	6.95	N	OFF	19.6
0.418830	45.20	---	57.47	12.27	N	OFF	19.6
0.449250	---	40.78	46.89	6.11	N	OFF	19.6
0.449250	45.87	---	56.89	11.02	N	OFF	19.6
0.475170	---	37.02	46.42	9.40	N	OFF	19.6
0.475170	43.44	---	56.42	12.98	N	OFF	19.6
0.613410	---	32.11	46.00	13.89	N	OFF	19.6
0.613410	35.98	---	56.00	20.02	N	OFF	19.6
0.873690	---	29.66	46.00	16.34	N	OFF	19.6
0.873690	35.61	---	56.00	20.39	N	OFF	19.6
1.361940	---	30.07	46.00	15.93	N	OFF	19.6
1.361940	32.70	---	56.00	23.30	N	OFF	19.6
3.067080	---	31.89	46.00	14.11	N	OFF	19.7
3.067080	36.46	---	56.00	19.54	N	OFF	19.7
4.344720	---	33.02	46.00	12.98	N	OFF	19.7

4.344720	37.45	---	56.00	18.55	N	OFF	19.7
4.600590	---	33.05	46.00	12.95	N	OFF	19.7
4.600590	37.35	---	56.00	18.65	N	OFF	19.7
5.110170	---	32.23	50.00	17.77	N	OFF	19.8
5.110170	36.02	---	60.00	23.98	N	OFF	19.8
5.367570	---	33.83	50.00	16.17	N	OFF	19.8
5.367570	37.60	---	60.00	22.40	N	OFF	19.8
16.729350	---	31.07	50.00	18.93	N	OFF	20.2
16.729350	36.46	---	60.00	23.54	N	OFF	20.2
28.623750	---	35.42	50.00	14.58	N	OFF	20.6
28.623750	39.72	---	60.00	20.28	N	OFF	20.6



Appendix B. Radiated Emission Test Result

Test Engineer :	Donny Tang	Temperature :	23~24°C
		Relative Humidity :	51~53%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY
 Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL
 Project : 9D0635-01
 Power : 120Vac/60Hz
 Mode : 4

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	40.67	21.92	-18.08	40.00	34.59	19.13	0.68	32.48	---	---	Peak
2	271.53	30.41	-15.59	46.00	41.95	18.87	1.78	32.19	---	---	Peak
3	298.69	37.84	-8.16	46.00	48.92	19.20	1.88	32.16	100	116	Peak
4	325.85	31.72	-14.28	46.00	42.33	19.62	1.96	32.19	---	---	Peak
5	406.36	29.52	-16.48	46.00	37.56	22.05	2.21	32.30	---	---	Peak
6 *	743.50	51.56			52.69	28.17	3.01	32.31	---	---	Peak
7	959.26	32.87	-13.13	46.00	29.00	31.29	3.47	30.89	---	---	Peak
8	2658.00	39.22	-34.78	74.00	67.19	27.72	6.27	61.96	---	---	Peak
9	4966.00	42.03	-31.97	74.00	64.66	31.26	8.70	62.59	---	---	Peak
10	6932.00	45.68	-28.32	74.00	63.80	35.16	10.18	63.46	---	---	Peak
11	7296.00	47.03	-26.97	74.00	63.17	36.59	10.83	63.56	---	---	Peak
12	10410.00	50.14	-23.86	74.00	61.81	39.72	12.42	63.81	---	---	Peak
13	11350.00	50.17	-23.83	74.00	60.89	39.70	13.05	63.47	100	183	Peak



Test Engineer :	Donny Tang	Temperature :	23~24°C
		Relative Humidity :	51~53%
Test Distance :	3m	Polarization :	Vertical
Remark :	#5 is system simulator signal which can be ignored.		



Site : 03CH10-HY
 Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL
 Project : 9D0635-01
 Power : 120Vac/60Hz
 Mode : 4

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	33.88	23.63	-16.37	40.00	32.45	23.05	0.61	32.48	---	---	Peak
2	40.67	35.44	-4.56	40.00	48.11	19.13	0.68	32.48	100	56	QP
3	298.69	32.50	-13.50	46.00	43.58	19.20	1.88	32.16	---	---	Peak
4	325.85	30.30	-15.70	46.00	40.91	19.62	1.96	32.19	---	---	Peak
5 *	743.50	54.00			55.13	28.17	3.01	32.31	---	---	Peak
6	869.05	29.37	-16.63	46.00	28.63	29.20	3.29	31.75	---	---	Peak
7	952.47	31.70	-14.30	46.00	28.11	31.10	3.45	30.96	---	---	Peak
8	2844.00	38.63	-35.37	74.00	65.92	28.28	6.47	62.04	---	---	Peak
9	4994.00	41.59	-32.41	74.00	64.07	31.38	8.74	62.60	---	---	Peak
10	6926.00	45.33	-28.67	74.00	63.47	35.15	10.17	63.46	---	---	Peak
11	7514.00	46.69	-27.31	74.00	63.05	36.47	10.77	63.60	---	---	Peak
12	9612.00	50.04	-23.96	74.00	63.21	38.92	12.60	64.69	100	196	Peak
13	11370.00	49.40	-24.60	74.00	60.06	39.74	13.07	63.47	---	---	Peak

—————THE END—————