



# FCC Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT2063-2  
**FCC ID** : IHDT56YU1  
**STANDARD** : 47 CFR Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on Jan. 22, 2020 and testing was completed on Apr. 25, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

*Jason Jia*

Reviewed by: Jason Jia / Supervisor

*James Huang*

Approved by: James Huang / Manager



**Sporton International (Kunshan) Inc.**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 6

    1.5. Modification of EUT ..... 8

    1.6. Test Location ..... 8

    1.7. Test Software ..... 8

    1.8. Applicable Standards ..... 9

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 10**

    2.1. Test Mode ..... 10

    2.2. Connection Diagram of Test System ..... 11

    2.3. Support Unit used in test configuration and system ..... 12

    2.4. EUT Operation Test Setup ..... 12

**3. TEST RESULT ..... 13**

    3.1. Test of AC Conducted Emission Measurement ..... 13

    3.2. Test of Radiated Emission Measurement ..... 17

**4. LIST OF MEASURING EQUIPMENT ..... 22**

**5. UNCERTAINTY OF EVALUATION ..... 23**

**APPENDIX A. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC010812-01	Rev. 01	Initial issue of report	May 20, 2020



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 8.23 dB at 0.194 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 9.53 dB at 42.610 MHz

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1. General Description

## 1.1. Applicant

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2. Manufacturer

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2063-2
FCC ID	IHDT56YU1
EUT supports Radios application	CDMA/GSM/WCDMA/LTE/5G NR/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11 a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver/GNSS
IMEI Code	Conduction/Radiation: 355526110004996
HW Version	PVT1
SW Version	QPD30.102
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 814.7 MHz ~ 848.3 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz LTE Band 71: 665.5 MHz ~ 695.5MHz 5G NR n2: 1852.5 MHz ~ 1907.5 MHz 5G NR n5: 826.5 MHz ~ 846.5 MHz 5G NR n12: 701.5 MHz ~ 713.5 MHz 5G NR n25: 1852.5 MHz ~ 1912.5 MHz 5G NR n41: 2506 MHz ~ 2680 MHz 5G NR n66: 1712.5 MHz ~ 1777.5 MHz 5G NR n71: 665.5 MHz ~ 695.5MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz CDMA2000 BC10: 817.9 MHz ~ 823.1 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7 MHz ~ 1994.3 MHz LTE Band 26 : 859.7 MHz ~ 893.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz



	<p>LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz          LTE Band 66 : 2110.7 MHz~ 2199.3 MHz          LTE Band 71: 619.5 MHz ~ 649.5MHz          5G NR n2: 1932.5 MHz ~ 1987.5 MHz          5G NR n5: 871.5 MHz ~ 891.5 MHz          5G NR n12: 731.5 MHz ~ 743.5 MHz          5G NR n25: 1932.5 MHz ~ 1992.5 MHz          5G NR n41: 2506 MHz ~ 2680 MHz          5G NR n66: 2112.5 MHz~ 2197.5 MHz          5G NR n71: 619.5 MHz ~ 649.5MHz          CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz          CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz          CDMA2000 BC10: 862.9 MHz ~ 868.1 MHz          802.11b/g/n: 2412 MHz ~ 2462 MHz          802.11a/n/ac: 5180 MHz ~ 5240 MHz;                            5260 MHz ~ 5320 MHz;                            5500 MHz ~ 5700 MHz                            5745 MHz ~ 5825 MHz          Bluetooth: 2402 MHz ~ 2480 MHz          GNSS : 1559 MHz ~ 1610 MHz          NFC : 13.56 MHz          FM : 88 MHz ~ 108 MHz</p>
<b>Antenna Type</b>	<p>WWAN : Fixed Internal Antenna          WLAN : Ant. 1: Loop Antenna                    Ant. 2: IFA Antenna          Bluetooth : Loop Antenna          GNSS: Loop Antenna          NFC : Ferrite+FPC Antenna          FM : External Handset Antenna</p>
<b>Type of Modulation</b>	<p>GSM: GMSK          GPRS: GMSK          EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK          WCDMA : BPSK (Uplink)          HSDPA/DC-HSDPA : QPSK (Uplink)          HSUPA : QPSK (Uplink)          HSPA+ : 16QAM (16QAM uplink is not supported)          DC-HSDPA : 64QAM          LTE: QPSK / 16QAM / 64QAM          5G NR:          DFT-s-OFDM (Pi/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM)          CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM)          CDMA2000 1xRTT: QPSK          CDMA2000 1xEV-DO: QPSK/8PSK          802.11b : DSSS (DBPSK / DQPSK / CCK)          802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)          Bluetooth LE : GFSK          Bluetooth (1Mbps) : GFSK          Bluetooth (2Mbps) :<math>\pi/4</math>-DQPSK          Bluetooth (3Mbps) : 8-DPSK          GNSS : BPSK          NFC: ASK          FM: FM</p>



Note: GNSS Rx = GLONASS + GPS + Galileo

### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6. Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (Chenyang)	Model Name	SC-51
AC Adapter 2	Brand Name	Motorola (Acbel)	Model Name	SC-51
Battery	Brand Name	Motorola(ATL)	Model Name	LR50
USB Cable 1	Brand Name	Motorola (Sai bao)	Model Name	SC18C24367
USB Cable 2	Brand Name	Motorola (Luxshare)	Model Name	SC18C24368

### 1.7. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN1257	314309

### 1.8. Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24



## **1.9. Applicable Standards**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


The EUT uses a USB interface and microprocessor operating 800MHz which is the maximum frequency used.

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 (High) Rx + Bluetooth Idle + WLAN 2.4G Idle + Camera(Front) + Earphone + Battery + USB Cable1(Charging from Adapter1)
	Mode 2: LTE B12 (Low) Rx + Bluetooth Idle + WLAN 5G Idle + Camera(Rear) + Earphone + Battery + USB Cable2(Charging from Adapter2)
	Mode 3: LTE B13 (Middle) Rx + Bluetooth Idle + WLAN 2.4G Idle + fingerprint + Earphone + Battery + USB Cable1(Charging from Adapter1)
	Mode 4: LTE B26 (Low) Rx + Bluetooth Idle + WLAN 5G Idle + MPEG4 + Earphone + Battery + USB Cable2(Charging from Adapter2)
	Mode 5: LTE B71 (Middle) Rx + Bluetooth Idle + WLAN 2.4G Idle + GPS + Earphone + Battery + USB Cable1(Charging from Adapter1)
	Mode 6: EN-DC 2A_n5A (Low) Rx + Bluetooth Idle + WLAN 5G Idle + Camera(Front) + Earphone + Battery + USB Cable1(Data Link with Notebook)
	Mode 7: EN-DC 2A_n71A (Low) Rx + Bluetooth Idle + WLAN 2.4G Idle + Camera(Rear) + Earphone + Battery + USB Cable2(Data Link with Notebook)
Radiated Emissions	Mode 1: GSM850 (Middle) Rx + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Rear) + Earphone + Battery + USB Cable1(Charging from Adapter1)
	Mode 2: LTE B12 (Middle) Rx + Bluetooth Idle + WLAN 5G Idle + Camera(Front) + Earphone + Battery + USB Cable2(Charging from Adapter2)
	Mode 3: LTE B13 (Middle) Rx + Bluetooth Idle + WLAN Idle(2.4G) + fingerprint + Earphone + Battery + USB Cable1(Charging from Adapter1)
	Mode 4: LTE B26 (Middle) Rx + Bluetooth Idle + WLAN 5G Idle + MPEG4 + Earphone + Battery + USB Cable2(Charging from Adapter2)
	Mode 5: LTE B71 (Middle) Rx + Bluetooth Idle + WLAN Idle(2.4G) + GPS + Earphone + Battery + USB Cable1(Charging from Adapter1)
	Mode 6: EN-DC 2A_n5A (Middle) Rx + Bluetooth Idle + WLAN 5G Idle + FM 88MHz + Earphone + Battery + USB Cable1(Data Link with Notebook)
	Mode 7: EN-DC 2A_n71A (Middle) Rx + Bluetooth Idle + WLAN Idle(2.4G) + NFC on + Earphone + Battery + USB Cable2(Data Link with Notebook)

**Remark:**

1. The worst case of AC is mode 5; only the test data of this mode is reported.
2. The worst case of RE is mode 2; only the test data of this mode is reported.
3. Data Link with Notebook / PC means data application transferred mode between EUT and Notebook / PC.
4. Pre-scanned Low/Middle/High channel for GSM 850/WCDMA B5/LTE Band 5/12/13/17/26/71/5G NR n5/n12/n71, the worst channel was recorded in this report.

**2.2.Connection Diagram of Test System**



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	SD Card	Kingston	8GB	N/A	N/A	N/A
2.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Notebook	Lenovo	V130-141KB001	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
5.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
6.	Hard disk	KINGSHARE	S64G8A18X003	N/A	N/A	N/A
7.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
8.	WLAN AP	ASUS	AC66U	N/A	N/A	Unshielded,1.8m
9.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
10.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
11.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
12.	LTE Base Station	Anritus	MT8820C	N/A	N/A	Unshielded,1.8m
13.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
14.	5G NR Base Station	Anritus	MT8000A	N/A	N/A	Unshielded,1.8m
15.	Signal Generator	R&S	SMBV100A	N/A	N/A	Unshielded,1.8m
16.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A

### 2.4. EUT Operation Test Setup

The EUT was in GSM or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
5. Turn on FM function to make the EUT receive continuous signals from FM station.



### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-L-191028-060105 LINE  
 Project : (FC) 010812-01  
 mode : Mode 5  
 : 355526110004996 #10

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.153	57.10	-8.72	65.82	46.60	0.03	10.47	QP
2	0.153	39.10	-16.72	55.82	28.60	0.03	10.47	Average
3 *	0.194	55.61	-8.23	63.84	45.20	0.04	10.37	QP
4	0.194	36.01	-17.83	53.84	25.60	0.04	10.37	Average
5	0.214	54.00	-9.05	63.05	43.61	0.04	10.35	QP
6	0.214	32.00	-21.05	53.05	21.61	0.04	10.35	Average
7	0.270	48.97	-12.15	61.12	38.60	0.05	10.32	QP
8	0.270	31.97	-19.15	51.12	21.60	0.05	10.32	Average
9	0.437	40.61	-16.50	57.11	30.30	0.06	10.25	QP
10	0.437	23.91	-23.20	47.11	13.60	0.06	10.25	Average
11	13.127	38.91	-21.09	60.00	28.20	0.33	10.38	QP
12	13.127	30.91	-19.09	50.00	20.20	0.33	10.38	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-191028-060105 NEUTRAL  
 Project : (FC) 010812-01  
 mode : Mode 5  
 : 355526110004996 #10

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.200	48.54	-15.08	63.62	38.10	0.08	10.36	QP
2	0.200	34.04	-19.58	53.62	23.60	0.08	10.36	Average
3	0.223	42.73	-19.97	62.70	32.30	0.08	10.35	QP
4	0.223	26.03	-26.67	52.70	15.60	0.08	10.36	Average
5	1.810	37.86	-18.14	56.00	27.50	0.13	10.23	QP
6	1.810	26.66	-19.34	46.00	16.30	0.13	10.23	Average
7	3.364	37.19	-18.81	56.00	26.79	0.15	10.25	QP
8	3.364	27.59	-18.41	46.00	17.19	0.15	10.25	Average
9	13.479	40.32	-19.68	60.00	29.60	0.34	10.38	QP
10	13.479	32.02	-17.98	50.00	21.30	0.34	10.38	Average
11	18.524	39.93	-20.07	60.00	28.89	0.57	10.47	QP
12	18.524	27.23	-22.77	50.00	16.19	0.57	10.47	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### **3.2.3. Test Procedures**


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Jack Guo	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 49922-3M HORIZONTAL  
 Project : (FC)010812-01  
 Mode : 2  
 IMEI : 355526110004996#10  
 Battery : 16%

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	34.85	17.73	-22.27	40.00	26.86	22.10	0.73	31.96	---	---	Peak
2	95.96	20.27	-23.23	43.50	35.35	15.72	1.13	31.93	---	---	Peak
3	172.59	22.89	-20.61	43.50	37.04	16.25	1.52	31.92	---	---	Peak
4	207.51	23.26	-20.24	43.50	37.84	15.65	1.68	31.91	---	---	Peak
5	295.78	20.70	-25.30	46.00	31.55	19.25	1.97	32.07	---	---	Peak
6	737.13	35.09			36.21	28.04	3.11	32.27	---	---	Peak
7	931.13	28.08	-17.92	46.00	25.47	30.27	3.51	31.17	100	0	Peak
8	2736.00	39.71	-34.29	74.00	33.79	32.37	6.00	32.45	---	---	Peak
9	4808.00	43.76	-30.24	74.00	32.87	34.20	8.09	31.40	---	---	Peak
10	7800.00	46.17	-27.83	74.00	31.45	35.90	10.84	32.02	---	---	Peak
11	11520.00	45.85	-28.15	74.00	26.46	38.30	13.60	32.51	---	---	Peak
12	14904.00	46.11	-27.89	74.00	22.35	39.90	15.61	31.75	---	---	Peak
13	17478.00	47.19	-26.81	74.00	21.27	41.30	16.54	31.92	---	---	Peak



Test Engineer :	Jack Guo	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		



Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m LF 49922-3M VERTICAL  
 Project : (FC)010812-01  
 Mode : 2  
 IMEI : 355526110004996#10  
 Battery : 16%

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	42.61	30.47	-9.53	40.00	43.60	18.08	0.74	31.95	100	0 Peak	
2	95.96	22.26	-21.24	43.50	37.34	15.72	1.13	31.93	---	---	Peak
3	111.48	21.14	-22.36	43.50	35.42	16.43	1.22	31.93	---	---	Peak
4	169.68	20.79	-22.71	43.50	34.81	16.38	1.52	31.92	---	---	Peak
5	467.47	22.79	-23.21	46.00	29.13	23.45	2.44	32.23	---	---	Peak
6 !	737.13	41.21			42.33	28.04	3.11	32.27	---	---	Peak
7	933.07	28.93	-17.07	46.00	26.23	30.33	3.52	31.15	---	---	Peak
8	2616.00	41.22	-32.78	74.00	35.63	32.37	5.87	32.65	---	---	Peak
9	4232.00	43.93	-30.07	74.00	34.75	33.40	7.67	31.89	---	---	Peak
10	7792.00	47.29	-26.71	74.00	32.57	35.90	10.84	32.02	---	---	Peak
11	10530.00	44.88	-29.12	74.00	26.02	37.77	13.00	31.91	---	---	Peak
12	12906.00	46.25	-27.75	74.00	24.73	39.00	14.31	31.79	---	---	Peak
13	16416.00	46.84	-27.16	74.00	20.57	41.23	16.73	31.69	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 14, 2020	Apr. 24, 2020	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 18, 2019	Apr. 24, 2020	Oct. 17, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 28, 2019	Apr. 24, 2020	Oct. 27, 2020	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 18, 2019	Apr. 24, 2020	Oct. 17, 2020	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Oct. 18, 2019	Apr. 25, 2020	Oct. 17,2020	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct.18, 2019	Apr. 25, 2020	Oct. 17, 2020	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May 30, 2019	Apr. 25, 2020	May 29, 2020	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 27, 2019	Apr. 25, 2020	Apr. 26, 2020	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Apr. 25, 2020	Nov. 09, 2020	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 08, 2020	Apr. 25, 2020	Jan. 07, 2021	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2019	Apr. 25, 2020	Aug. 05, 2020	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5G Hz	Oct. 18, 2019	Apr. 25, 2020	Oct. 17, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Apr. 25, 2020	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Apr. 25, 2020	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Apr. 25, 2020	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.9 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.9 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1 dB
---	--------