




3.6.6 Test Result of Conducted Hopping Mode Band Edges


<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 21.APR.2020 11:41:50

Hopping Mode High Band Edge Plot




Date: 21.APR.2020 11:57:29




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 21.APR.2020 12:02:32

Hopping Mode High Band Edge Plot




Date: 21.APR.2020 12:11:31




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 21.APR.2020 12:27:40

Hopping Mode High Band Edge Plot



Date: 21.APR.2020 12:35:54

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup






3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 21.APR.2020 11:43:40


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 11:44:07




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 21.APR.2020 11:54:00


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 11:54:27




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 21.APR.2020 11:58:38

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 21.APR.2020 11:59:08




<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 21.APR.2020 12:04:59


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 12:05:27




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 21.APR.2020 12:08:35


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 12:09:04




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 21.APR.2020 12:12:59

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 21.APR.2020 12:13:28




<3Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 21.APR.2020 12:29:03


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 12:29:31




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 21.APR.2020 12:32:35


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 12:33:02




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 21.APR.2020 12:38:09

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 21.APR.2020 12:38:35



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1\text{GHz}$; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix D.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 02, 2019	Apr. 17, 2020~ Apr. 21, 2020	Nov. 01, 2020	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 08, 2020	Apr. 17, 2020~ Apr. 21, 2020	Jan. 07, 2021	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 08, 2020	Apr. 17, 2020~ Apr. 21, 2020	Jan. 07, 2021	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY57290157	3Hz~8.5GHz;Max 30dBm	Jul. 18, 2019	Apr. 09, 2020	Jul. 17, 2020	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44GHz	Apr. 16, 2019	Apr. 09, 2020	Apr. 15, 2020	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 10, 2019	Apr. 09, 2020	Nov. 09, 2020	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	May 30, 2019	Apr. 09, 2020	May 29, 2020	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 27, 2019	Apr. 09, 2020	Apr. 26, 2020	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2020	Apr. 09, 2020	Jan. 07, 2021	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2019	Apr. 09, 2020	Aug. 05, 2020	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jun. 05, 2019	Apr. 09, 2020	Jun. 04, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Aug. 16, 2019	Apr. 09, 2020	Aug. 15, 2020	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 15, 2019	Apr. 09, 2020	Apr. 14, 2020	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 09, 2020	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 09, 2020	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 09, 2020	NCR	Radiation (03CH06-KS)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	NCR	May 04, 2020	NCR	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	May 04, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	May 04, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	May 04, 2020	Nov. 14, 2020	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	May 04, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	May 04, 2020	Jan. 01, 2021	Conduction (CO05-HY)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.7dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------



Appendix A. Conducted Test Results

Bluetooth

Test Engineer:	weller liu	Temperature:	20~26	°C
Test Date:	2020/4/17~2020/4/21	Relative Humidity:	40~51	%

TEST RESULTS DATA**20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (kHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	1.022	0.885	1002.900	0.6811	Pass
DH	1Mbps	1	39	2441	1.022	0.885	1011.600	0.6811	Pass
DH	1Mbps	1	78	2480	1.016	0.885	1002.900	0.6773	Pass
2DH	2Mbps	1	0	2402	1.281	1.187	998.600	0.8539	Pass
2DH	2Mbps	1	39	2441	1.276	1.181	1002.900	0.8509	Pass
2DH	2Mbps	1	78	2480	1.281	1.190	998.600	0.8539	Pass
3DH	3Mbps	1	0	2402	1.289	1.184	994.200	0.8596	Pass
3DH	3Mbps	1	39	2441	1.281	1.178	1002.900	0.8539	Pass
3DH	3Mbps	1	78	2480	1.285	1.178	998.600	0.8567	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.9116	0.31	0.4	Pass
AFH	20	53.33	2.9116	0.16	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	13.54	20.97	Pass
	39	1	13.67	20.97	Pass
	78	1	13.46	20.97	Pass

2DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	13.18	20.97	Pass
	39	1	13.15	20.97	Pass
	78	1	13.12	20.97	Pass

3DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH1	0	1	13.18	20.97	Pass
	39	1	13.18	20.97	Pass
	78	1	13.36	20.97	Pass


TEST RESULTS DATA**Number of Hopping Frequency**

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	79	> 15	Pass



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Howard Huang	Temperature :	21~25°C
		Relative Humidity :	41~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.163500	---	31.14	55.28	24.14	L1	OFF	19.6
0.163500	42.25	---	65.28	23.03	L1	OFF	19.6
0.500460	---	31.81	46.00	14.19	L1	OFF	19.6
0.500460	39.94	---	56.00	16.06	L1	OFF	19.6
0.573000	---	33.53	46.00	12.47	L1	OFF	19.6
0.573000	40.69	---	56.00	15.31	L1	OFF	19.6
0.590820	---	29.59	46.00	16.41	L1	OFF	19.6
0.590820	37.51	---	56.00	18.49	L1	OFF	19.6
0.945600	---	30.60	46.00	15.40	L1	OFF	19.6
0.945600	38.07	---	56.00	17.93	L1	OFF	19.6
1.130820	---	29.76	46.00	16.24	L1	OFF	19.6
1.130820	38.19	---	56.00	17.81	L1	OFF	19.6
1.200750	---	29.64	46.00	16.36	L1	OFF	19.6
1.200750	37.43	---	56.00	18.57	L1	OFF	19.6
1.326390	---	29.88	46.00	16.12	L1	OFF	19.6
1.326390	39.60	---	56.00	16.40	L1	OFF	19.6
5.430660	---	27.32	50.00	22.68	L1	OFF	19.8
5.430660	31.31	---	60.00	28.69	L1	OFF	19.8
13.892730	---	31.67	50.00	18.33	L1	OFF	20.2
13.892730	42.56	---	60.00	17.44	L1	OFF	20.2



Test Engineer :	Howard Huang	Temperature :	21~25°C
		Relative Humidity :	41~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
14.185500	---	31.63	50.00	18.37	L1	OFF	20.2
14.185500	42.26	---	60.00	17.74	L1	OFF	20.2
14.487000	---	32.22	50.00	17.78	L1	OFF	20.2
14.487000	43.28	---	60.00	16.72	L1	OFF	20.2
14.761500	---	33.15	50.00	16.85	L1	OFF	20.2
14.761500	44.51	---	60.00	15.49	L1	OFF	20.2
15.027000	---	32.69	50.00	17.31	L1	OFF	20.2
15.027000	43.81	---	60.00	16.19	L1	OFF	20.2
15.171000	---	32.07	50.00	17.93	L1	OFF	20.2
15.171000	42.88	---	60.00	17.12	L1	OFF	20.2
15.265500	---	31.68	50.00	18.32	L1	OFF	20.2
15.265500	42.34	---	60.00	17.66	L1	OFF	20.2
15.366750	---	31.16	50.00	18.84	L1	OFF	20.2
15.366750	41.32	---	60.00	18.68	L1	OFF	20.2
15.491220	---	30.63	50.00	19.37	L1	OFF	20.2
15.491220	40.51	---	60.00	19.49	L1	OFF	20.2



Test Engineer :	Howard Huang	Temperature :	21~25°C
		Relative Humidity :	41~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.339810	---	28.22	49.21	20.99	N	OFF	19.6
0.339810	36.73	---	59.21	22.48	N	OFF	19.6
0.498120	---	30.93	46.03	15.10	N	OFF	19.6
0.498120	39.03	---	56.03	17.00	N	OFF	19.6
0.545280	---	29.02	46.00	16.98	N	OFF	19.6
0.545280	37.97	---	56.00	18.03	N	OFF	19.6
0.565350	---	34.01	46.00	11.99	N	OFF	19.6
0.565350	40.83	---	56.00	15.17	N	OFF	19.6
1.189500	---	28.37	46.00	17.63	N	OFF	19.6
1.189500	36.49	---	56.00	19.51	N	OFF	19.6
1.328280	---	29.02	46.00	16.98	N	OFF	19.6
1.328280	37.21	---	56.00	18.79	N	OFF	19.6
3.844500	---	26.66	46.00	19.34	N	OFF	19.7
3.844500	31.40	---	56.00	24.60	N	OFF	19.7
14.163000	---	31.75	50.00	18.25	N	OFF	20.2
14.163000	42.55	---	60.00	17.45	N	OFF	20.2



Test Engineer :	Howard Huang	Temperature :	21~25°C
		Relative Humidity :	41~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
14.284500	---	31.73	50.00	18.27	N	OFF	20.2
14.284500	42.62	---	60.00	17.38	N	OFF	20.2
14.534250	---	31.84	50.00	18.16	N	OFF	20.2
14.534250	42.78	---	60.00	17.22	N	OFF	20.2
14.671500	---	32.06	50.00	17.94	N	OFF	20.2
14.671500	43.04	---	60.00	16.96	N	OFF	20.2
14.822250	---	32.33	50.00	17.67	N	OFF	20.2
14.822250	43.33	---	60.00	16.67	N	OFF	20.2
14.896500	---	32.32	50.00	17.68	N	OFF	20.2
14.896500	43.31	---	60.00	16.69	N	OFF	20.2
15.014850	---	32.16	50.00	17.84	N	OFF	20.2
15.014850	43.09	---	60.00	16.91	N	OFF	20.2
15.195750	---	31.66	50.00	18.34	N	OFF	20.2
15.195750	42.18	---	60.00	17.82	N	OFF	20.2
15.292500	---	31.24	50.00	18.76	N	OFF	20.2
15.292500	41.39	---	60.00	18.61	N	OFF	20.2

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2333.53	55.96	-18.04	74	48.23	31.97	7.2	31.44	145	53	P	H
		2333.53	31.17	-22.83	54	-	-	-	-	-	-	A	H
	*	2402	104.86	-	-	96.97	32	7.3	31.41	145	53	P	H
	*	2402	80.07	-	-	-	-	-	-	-	-	A	H
		2353.29	55.96	-18.04	74	48.07	32.07	7.25	31.43	128	111	P	V
		2353.29	31.17	-22.83	54	-	-	-	-	-	-	A	V
	*	2402	103.18	-	-	95.29	32	7.3	31.41	128	111	P	V
	*	2402	78.39	-	-	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		2498.44	56.02	-17.98	74	47.68	32.2	7.52	31.38	100	133	P	H
		2498.44	31.23	-22.77	54	-	-	-	-	-	-	A	H
	*	2480	104.39	-	-	96.03	32.27	7.48	31.39	100	133	P	H
	*	2480	79.6	-	-	-	-	-	-	-	-	A	H
		2490.58	56.16	-17.84	74	47.83	32.2	7.52	31.39	119	114	P	V
		2490.58	31.37	-22.63	54	-	-	-	-	-	-	A	V
	*	2480	103.89	-	-	95.53	32.27	7.48	31.39	119	114	P	V
	*	2480	79.1	-	-	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BT (Harmonic @ 3m)

Table with 14 columns: BT, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include BT CH 00 (2402MHz), BT CH 39 (2441MHz), and BT CH 78 (2480MHz).



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		30	21.08	-18.92	40	27.97	25.1	1.11	33.1			P	H
		96.93	23.5	-20	43.5	39.13	15.71	1.64	32.98			P	H
		109.54	25.34	-18.16	43.5	39.72	17	1.7	33.08			P	H
		236.61	27.93	-18.07	46	41.17	17.17	2.42	32.83			P	H
		301.6	28.97	-17.03	46	39.51	19.42	2.74	32.7	100	0	P	H
		946.65	28.03	-17.97	46	24.55	30.89	4.7	32.11			P	H
		30.97	30.89	-9.11	40	38.3	24.57	1.1	33.08	100	12	P	V
		54.25	28.2	-11.8	40	46.7	13.4	1.28	33.18			P	V
		81.41	23.96	-16.04	40	41.77	13.72	1.53	33.06			P	V
		111.48	25.05	-18.45	43.5	39.31	17.11	1.71	33.08			P	V
		259.89	22.75	-23.25	46	32.59	20.4	2.54	32.78			P	V
		459.71	25.25	-20.75	46	30.92	23.27	3.32	32.26			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)


For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.