



FCC RADIO TEST REPORT

FCC ID : IHDT56ZB1
Equipment : Mobile Cellular Phone
Brand Name : Motorola
Model Name : XT2071-2, XT2071-3, XT2071-5
Applicant : Motorola Mobility, LLC
222 W Merchandise Mart Plaza, Suite 1800,
Chicago, IL 60654, United States
Manufacturer : Motorola Mobility, LLC
222 W Merchandise Mart Plaza, Suite 1800,
Chicago, IL 60654, United States
Standard : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)

The product was received on May 22, 2020 and testing was started from Jun. 13, 2020 and completed on Jul. 22, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Product Specification of Equipment Under Test	7
1.3 Modification of EUT	7
1.4 Testing Location	8
1.5 Applicable Standards	9
2 Test Configuration of Equipment Under Test	10
2.1 Test Mode.....	10
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	11
2.5 Frequency List of Low/Middle/High Channels	12
3 Conducted Test Result	13
3.1 Measuring Instruments.....	13
3.2 Conducted Output Power and ERP/EIRP	14
3.3 Peak-to-Average Ratio	15
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	16
3.5 Conducted Band Edge	17
3.6 Conducted Spurious Emission	18
3.7 Frequency Stability	19
4 Radiated Test Items	20
4.1 Measuring Instruments.....	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test.....	21
4.4 Field Strength of Spurious Radiation Measurement	22
5 List of Measuring Equipment.....	23
6 Uncertainty of Evaluation	25
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of ERP/EIRP and Radiated Test	



History of this test report

Report No.	Version	Description	Issued Date
FG051232-02A	01	Initial issue of report	Aug. 06, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
	§22.913 (a)(2)	Effective Radiated Power (GSM850) (WCDMA Band V) (CDMA BC0)		
	§24.232 (c)	Equivalent Isotropic Radiated Power (GSM1900) (WCDMA Band II) (CDMA BC1)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (WCDMA Band IV)		
3.3	§24.232 (d)	Peak-to-Average Ratio	Pass	
3.4	§2.1049	Occupied Bandwidth (GSM850) (WCDMA Band V) (CDMA BC0) (GSM1900) (WCDMA Band II) (CDMA BC1) (WCDMA Band IV)	Pass	-
	§22.917 (b)			
	§24.238 (b)			
	§27.53 (g)			
3.5	§2.1051	Band Edge Measurement (GSM850) (WCDMA Band V) (CDMA BC0) (GSM1900) (WCDMA Band II) (CDMA BC1) (WCDMA Band IV)	Pass	-
	§22.917 (a)			
	§24.238 (a)			
	§27.53 (g)			
3.6	§2.1051	Conducted Emission (GSM850) (WCDMA Band V) (CDMA BC0) (GSM1900) (WCDMA Band II) (CDMA BC1) (WCDMA Band IV)	Pass	-
	§22.917 (a)			
	§24.238 (a)			
	§27.53 (g)			
3.7	§2.1055	Frequency Stability Temperature & Voltage	Pass	-
	§22.355			
	§24.235			
	§27.54			
4.4	§2.1053	Field Strength of Spurious Radiation (GSM850) (WCDMA Band V) (CDMA BC0) (GSM1900) (WCDMA Band II) (CDMA BC1) (WCDMA Band IV)	Pass	Under limit 32.47 dB at 1648.000 MHz
	§22.917 (a)			
	§24.238 (a)			
	§27.53 (h)			

Remark:

- Not required means after assessing, test items are not necessary to carry out.
- Except CDMA BC1 test data is carrying out, this is a spot check data report and data performed in appendix of this report are chosen from the worst case of the original FCC ID report. All the test cases were performed on original report which can be referred to Sporton Report Number FG051232A.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Vivian Hsu



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2071-2, XT2071-3, XT2071-5
FCC ID	IHDT56ZB1
IMEI Code	Conducted : IMEI 1: 353590110017517 IMEI 2: 353590110017525 IMEI 1: 353590110023770 IMEI 2: 353590110023788 Radiation : IMEI 1: 353590110017517 IMEI 2: 353590110017525
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/ GNSS/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Accessory List	
AC Adapter 1 (US)	Brand Name : Motorola
	Model Name : SC-51
	Manufacturer : Chenyang
AC Adapter 1 (EU)	Brand Name : Motorola
	Model Name : SC-52
	Manufacturer : Chenyang
AC Adapter 1 (UK)	Brand Name : Motorola
	Model Name : SC-53UK
	Manufacturer : Chenyang
AC Adapter 1 (AR)	Brand Name : Motorola
	Model Name : SC-56
	Manufacturer : Chenyang
AC Adapter 1 (AU)	Brand Name : Motorola
	Model Name : SC-55AU
	Manufacturer : Chenyang
AC Adapter 2 (US)	Brand Name : Motorola
	Model Name : SC-51
	Manufacturer : Acbel
AC Adapter 2 (EU)	Brand Name : Motorola
	Model Name : SC-52
	Manufacturer : Acbel
AC Adapter 2 (AR)	Brand Name : Motorola
	Model Name : SC-56
	Manufacturer : Acbel
AC Adapter 3 (IN)	Brand Name : Motorola
	Model Name : SC-54
	Manufacturer : Salom
Battery 1	Brand Name : Motorola
	Model Name : LS30
	Manufacturer : ATL
Battery 2	Brand Name : Motorola
	Model Name : LS40
	Manufacturer : ATL
Standard 3.5mm Headset 1	Brand Name : Motorola
	Model Name : SH38C37773
	Manufacturer : Lianyun
Standard 3.5mm Headset 2	Brand Name : Motorola
	Model Name : SH38C44959
	Manufacturer : Lianyun
USB-C to 3.5mm headset adaptor 1	Brand Name : Motorola
	Model Name : SC18C27844
USB-C to 3.5mm headset adaptor 2	Brand Name : Motorola
	Model Name : SC18C27845
USB Cable 1	Brand Name : Motorola
	Model Name : SC18C24367
	Manufacturer : Saibao
USB Cable 2	Brand Name : Motorola
	Model Name : SC18C24368
	Manufacturer : Luxshare

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM: GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz CDMA/EV-DO BC0: 824.70 MHz ~ 848.31 MHz BC1: 1851.25 MHz ~ 1908.75 MHz
Rx Frequency	GSM: GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz CDMA/EV-DO BC0: 869.70 MHz ~ 893.31 MHz BC1: 1931.25 MHz ~ 1988.75 MHz
Maximum Output Power to Antenna	GSM: GSM850: 32.42 dBm GSM1900: 28.90 dBm WCDMA: Band V: 23.23 dBm Band II: 23.06 dBm Band IV: 23.20 dBm CDMA/EV-DO BC0: 24.17 dBm BC1: 24.22 dBm
Antenna Type	Fixed Internal Antenna
Antenna Gain	Cellular Band: -4.7 dBi PCS Band: -2 dBi AWS Band: -1.9 dBi
Type of Modulation	GSM / GPRS: GMSK EGPRS: GMSK for MCS 0 ~ 4 & 8PSK for MCS5 ~9 WCDMA: QPSK (Uplink) HSDPA: 64QAM (Downlink) / HSUPA : QPSK (Uplink) CDMA2000 : QPSK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY
Test Engineer	Oscar Chi
Temperature	25.7°C
Relative Humidity	54.6%

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH11-HY
Test Engineer	Cookie Ku, Fu Chen and Troye Hsieh
Temperature	19~26.9°C
Relative Humidity	50~68.9%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007



1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z and Accessory (Earphone or Adapter). The worst cases (Close Mode with PT Antenna: Y Plane with Adapter for CDMA BC0 (1xEVDO), Z Plane with Adapter for GPRS 850 / EDGE 850 / WDMA Band V / CDMA BC0 (1xRTT) ; Open Mode with PT Antenna: Y Plane with Adapter for GPRS 1900 / EDGE 1900 / WCDMA Band II / CDMA BC1 (1xRTT), Z Plane with Adapter for WCDMA Band IV and Z Plane with Adapter for CDMA BC1 (1xEVDO)) were recorded in this report.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V and CDMA BC0
2. 30 MHz to 18000 MHz for WCDMA Band IV
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II and CDMA BC1


All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM850	■ GSM Link ■ EDGE Class 8 Link	-
GSM1900	■ GSM Link ■ EDGE Class 8 Link	-
WCDMA Band V	■ RMC 12.2Kbps Link	-
WCDMA Band II	■ RMC 12.2Kbps Link	-
WCDMA Band IV	■ RMC 12.2Kbps Link	-
CDMA BC0	■ 1xRTT Link ■ 1xEV-DO Rev. A Link	-
CDMA BC1	■ 1xRTT Link ■ 1xEV-DO Rev. A Link	■ 1xRTT Link ■ 1xEV-DO Rev. A Link

Remark: All the radiated test cases were performed with AC Adapter 1 (US), USB Cable 1, and SIM 1.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example:

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6
CDMA2000 BC0	Channel	1013	384	777
	Frequency	824.7	836.52	848.31
CDMA2000 BC1	Channel	25	600	1175
	Frequency	1851.25	1880.0	1908.75

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V and CDMA BC0

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II and CDMA BC1

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
5. Record the maximum PAPR level associated with a probability of 0.1%.

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

22.355

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

24.235 & 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated emissions below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 26, 2020	Jul. 01, 2020~ Jul. 22, 2020	Mar. 25, 2021	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 04, 2019	Jul. 01, 2020~ Jul. 22, 2020	Sep. 03, 2020	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 26, 2019	Jul. 01, 2020~ Jul. 22, 2020	Nov. 25, 2020	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~4A	Oct. 09, 2019	Jul. 01, 2020~ Jul. 22, 2020	Oct. 08, 2020	Conducted (TH03-HY)
Base Station (Measure)	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Aug. 23, 2019	Jul. 01, 2020~ Jul. 22, 2020	Aug. 22, 2020	Conducted (TH03-HY)
Power Divider	Warison	WCOU-0.4-26. 5S-20	#A	N/A	Nov. 06, 2019	Jul. 01, 2020~ Jul. 22, 2020	Nov. 05, 2020	Conducted (TH03-HY)
Preamplifier	EMCE	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Jun. 13, 2020~ Jul. 16, 2020	Dec. 12, 2020	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 03, 2019	Jun. 13, 2020~ Jul. 16, 2020	Dec. 02, 2020	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917057 6	18GHz- 40GHz	May 22, 2020	Jun. 13, 2020~ Jul. 16, 2020	May 21, 2021	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 12, 2019	Jun. 13, 2020~ Jul. 16, 2020	Oct. 11, 2020	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Nov. 04, 2019	Jun. 13, 2020~ Jul. 16, 2020	Nov. 03, 2020	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jun. 13, 2020~ Jul. 16, 2020	Dec. 25, 2020	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 13, 2019	Jun. 13, 2020~ Jul. 16, 2020	Nov. 12, 2020	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03K	1710001800 054002	1GHz~18GHz	Feb. 07, 2020	Jun. 13, 2020~ Jul. 16, 2020	Feb. 06, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 28, 2019	Jun. 13, 2020~ Jul. 16, 2020	Oct. 27, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-1080 -1200-15000-6 OSS	SN2	1.2GHz High Pass Filter	Sep. 15, 2019	Jun. 13, 2020~ Jul. 16, 2020	Sep. 14, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700 -3000-18000-6 OSS	SN3	3GHz High Pass	Sep. 15, 2019	Jun. 13, 2020~ Jul. 16, 2020	Sep. 14, 2020	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 13, 2020~ Jul. 16, 2020	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jun. 13, 2020~ Jul. 16, 2020	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jun. 13, 2020~ Jul. 16, 2020	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Jun. 13, 2020~ Jul. 16, 2020	N/A	Radiation (03CH11-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTN-303B	TP161237	N/A	Oct. 25, 2019	Jun. 13, 2020~ Jul. 16, 2020	Oct. 24, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 12, 2010	Jun. 13, 2020~ Jul. 16, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 12, 2010	Jun. 13, 2020~ Jul. 16, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 12, 2010	Jun. 13, 2020~ Jul. 16, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 12, 2010	Jun. 13, 2020~ Jul. 16, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	Aug. 27, 2019	Jun. 13, 2020~ Jul. 16, 2020	Aug. 26, 2020	Radiation (03CH11-HY)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.09
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.95
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

<PT Antenna>

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	32.03	32.25	32.42	28.90	28.77	28.52
GPRS class 8	32.16	32.15	32.42	28.90	28.70	28.55
GPRS class 10	30.99	30.69	30.52	28.61	28.44	28.36
GPRS class 11	29.77	29.69	29.83	26.67	26.52	26.60
GPRS class 12	27.52	27.02	27.43	24.72	24.61	24.70
EGPRS class 8	25.69	25.65	25.53	24.75	24.72	24.54
EGPRS class 10	24.77	24.61	24.60	23.58	23.48	23.51
EGPRS class 11	22.99	23.07	22.83	21.89	21.70	21.89
EGPRS class 12	21.64	21.72	21.28	20.53	20.74	20.66

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	23.04	23.23	23.17	23.06	22.93	22.83
HSDPA Subtest-1	21.96	21.98	21.94	22.16	21.92	21.99
HSDPA Subtest-2	21.93	21.75	21.86	22.21	21.92	21.95
HSDPA Subtest-3	21.42	21.49	21.05	21.68	21.41	21.43
HSDPA Subtest-4	21.41	21.17	21.43	21.74	21.50	21.35
HSUPA Subtest-1	21.89	22.04	21.96	22.26	21.95	22.00
HSUPA Subtest-2	19.88	19.86	19.90	20.26	19.92	19.99
HSUPA Subtest-3	20.85	20.93	20.85	21.24	20.93	21.04
HSUPA Subtest-4	19.87	19.92	19.85	20.27	20.03	19.90
HSUPA Subtest-5	21.97	21.82	21.87	22.21	21.92	22.00



Conducted Power (*Unit: dBm)			
Band	WCDMA Band IV		
Channel	1312	1413	1513
Frequency	1712.4	1732.6	1752.6
RMC 12.2K	23.20	23.14	23.15
HSDPA Subtest-1	22.02	22.03	21.98
HSDPA Subtest-2	22.07	22.13	22.02
HSDPA Subtest-3	21.63	21.63	21.52
HSDPA Subtest-4	21.58	21.57	21.56
HSUPA Subtest-1	22.07	22.04	21.97
HSUPA Subtest-2	20.01	20.08	20.02
HSUPA Subtest-3	21.07	21.01	21.02
HSUPA Subtest-4	20.10	20.12	20.00
HSUPA Subtest-5	22.06	22.02	22.55

Conducted Power (*Unit: dBm)						
Band	CDMA 2000 BC0			CDMA 2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1 SO55	24.03	24.15	24.12	23.95	23.97	24.11
1xRTT RC3 SO55	24.06	24.16	24.14	24.07	24.00	24.06
1xRTT RC3 SO32 (+ F-SCH)	24.05	24.14	24.14	24.06	24.00	24.09
1xRTT RC3 SO32 (+SCH)	24.05	24.12	24.14	24.08	24.01	24.08
1xEVDO RTAP 153.6Kbps	24.12	24.17	24.10	24.19	24.15	24.22
1xEVDO RETAP 4096Bits	24.11	24.13	24.08	24.15	24.14	24.20



A2. CDMA

Peak-to-Average Ratio

Mode	CDMA BC1	CDMA BC1	Limit: 13dB
Mod.	1xRTT	1xEV-DO Rev. A	Result
Lowest CH	4.20	3.84	PASS
Middle CH	3.96	3.84	
Highest CH	4.16	3.84	



CDMA BC1 (1xRTT)	CDMA BC1 (1xEV-DO Rev. A)
Lowest Channel	Lowest Channel
Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz, Center: 1.85125 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.79 dBm Peak 27.08 dBm Crest 4.29 dB 10 % 2.52 dB 1 % 4.04 dB .1 % 4.20 dB .01 % 4.28 dB Date: 1.JUL.2020 15:08:43	Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz, Center: 1.85125 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 23.85 dBm Peak 27.78 dBm Crest 3.93 dB 10 % 2.48 dB 1 % 3.76 dB .1 % 3.84 dB .01 % 3.88 dB Date: 1.JUL.2020 12:35:52
Middle Channel	Middle Channel
Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz, Center: 1.88 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.20 dBm Peak 26.30 dBm Crest 4.10 dB 10 % 2.48 dB 1 % 3.80 dB .1 % 3.96 dB .01 % 4.04 dB Date: 1.JUL.2020 15:09:11	Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz, Center: 1.88 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 23.87 dBm Peak 27.78 dBm Crest 3.91 dB 10 % 2.48 dB 1 % 3.72 dB .1 % 3.84 dB .01 % 3.88 dB Date: 1.JUL.2020 12:36:19
Highest Channel	Highest Channel
Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz, Center: 1.90875 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 21.73 dBm Peak 25.95 dBm Crest 4.22 dB 10 % 2.48 dB 1 % 3.96 dB .1 % 4.16 dB .01 % 4.24 dB Date: 1.JUL.2020 15:09:46	Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz, Center: 1.90875 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 23.88 dBm Peak 27.78 dBm Crest 3.90 dB 10 % 2.48 dB 1 % 3.72 dB .1 % 3.84 dB .01 % 3.88 dB Date: 1.JUL.2020 12:36:41


**26dB Bandwidth**

Mode	CDMA BC1 26dB BW(MHz)	CDMA BC1 26dB BW(MHz)
Mod.	1xRTT	1xEV-DO Rev. A
Lowest CH	1.43	1.44
Middle CH	1.43	1.44
Highest CH	1.43	1.43




CDMA BC1 (1xRTT)

Lowest Channel




Date: 1.JUL.2020 14:31:40

Middle Channel




Date: 1.JUL.2020 14:37:10


Highest Channel




Date: 1.JUL.2020 14:39:52

CDMA BC1 (1xEV-DO Rev. A)
Lowest Channel


Date: 1.JUL.2020 11:50:35

Middle Channel


Date: 1.JUL.2020 11:56:34

Highest Channel


Date: 1.JUL.2020 12:00:43




Occupied Bandwidth

Mode	CDMA BC1 99% OBW(MHz)	CDMA BC1 99% OBW(MHz)
Mod.	1xRTT	1xEV-DO Rev. A
Lowest CH	1.28	1.28
Middle CH	1.28	1.28
Highest CH	1.28	1.27


CDMA BC1 (1xRTT)

Lowest Channel




Date: 1.JUL.2020 14:32:26

Middle Channel



Date: 1.JUL.2020 14:37:47


Highest Channel



Date: 1.JUL.2020 14:40:26


CDMA BC1 (1xEV-DO Rev. A)

Lowest Channel




Date: 1.JUL.2020 11:52:06

Middle Channel




Date: 1.JUL.2020 11:58:10


Highest Channel




Date: 1.JUL.2020 12:02:23

**Conducted Band Edge****CDMA BC1 (1xRTT)****Lowest Band Edge**


Date: 1.JUL.2020 14:35:12

Highest Band Edge

Date: 1.JUL.2020 14:43:24

CDMA BC1 (1xEV-DO Rev. A)**Lowest Band Edge**

Date: 1.JUL.2020 11:55:00

Highest Band Edge


Date: 1.JUL.2020 12:05:15



Conducted Spurious Emission


CDMA BC1 (1xRTT)

Lowest Channel




Date: 1.JUL.2020 14:36:04

Middle Channel



Date: 1.JUL.2020 14:38:43

Highest Channel




Date: 1.JUL.2020 14:44:14




CDMA BC1 (1xEV-DO Rev. A)

Lowest Channel




Date: 1.JUL.2020 11:51:29

Middle Channel



Date: 1.JUL.2020 11:57:29

Highest Channel



Date: 1.JUL.2020 12:06:19

Frequency Stability

Test Conditions	Middle Channel	CDMA BC1 (1xRTT)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0016	PASS
40	Normal Voltage	0.0011	
30	Normal Voltage	0.0021	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0032	
0	Normal Voltage	0.0043	
-10	Normal Voltage	0.0096	
-20	Normal Voltage	0.0404	
-30	Normal Voltage	0.0362	
20	Maximum Voltage	0.0005	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0011	

Test Conditions	Middle Channel	CDMA BC1 (1xEV-DO Rev. A)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0234	PASS
40	Normal Voltage	0.0245	
30	Normal Voltage	0.0032	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0021	
0	Normal Voltage	0.0000	
-10	Normal Voltage	0.0011	
-20	Normal Voltage	0.0037	
-30	Normal Voltage	0.0011	
20	Maximum Voltage	0.0043	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0032	

Note:

1. Normal Voltage = 4V ; Battery End Point (BEP) = 3.5 V ; Maximum Voltage = 4.45 V
2. The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of ERP/EIRP and Radiated Test

ERP/EIRP

<PT Antenna>

Channel	Mode	Conducted		ERP	
		Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	GSM850 GSM (GT - LC = -4.7 dB)	32.03	1.5959	25.18	0.3296
Middle		32.25	1.6788	25.40	0.3467
Highest		32.42	1.7458	25.57	0.3606
Lowest	GSM850 EDGE class 8 (GT - LC = -4.7 dB)	25.69	0.3707	18.84	0.0766
Middle		25.65	0.3673	18.80	0.0759
Highest		25.53	0.3573	18.68	0.0738
Lowest	WCDMA Band V RMC 12.2Kbps (GT - LC = -4.7 dB)	23.04	0.2014	16.19	0.0416
Middle		23.23	0.2104	16.38	0.0435
Highest		23.17	0.2075	16.32	0.0429
Lowest	CDMA BC0 1xRTT (GT - LC = -4.7 dB)	24.06	0.2547	17.21	0.0526
Middle		24.16	0.2606	17.31	0.0538
Highest		24.14	0.2594	17.29	0.0536
Lowest	CDMA BC0 1xEV-DO (GT - LC = -4.7 dB)	24.12	0.2582	17.27	0.0533
Middle		24.17	0.2612	17.32	0.0540
Highest		24.10	0.2570	17.25	0.0531
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GSM (GT - LC = -2 dB)	28.90	0.7762	26.90	0.4898
Middle		28.77	0.7534	26.77	0.4753
Highest		28.52	0.7112	26.52	0.4487
Lowest	GSM1900 EDGE class 8 (GT - LC = -2 dB)	24.75	0.2985	22.75	0.1884
Middle		24.72	0.2965	22.72	0.1871
Highest		24.54	0.2844	22.54	0.1795
Lowest	WCDMA Band II RMC 12.2Kbps (GT - LC = -2 dB)	23.06	0.2023	21.06	0.1276
Middle		22.93	0.1963	20.93	0.1239
Highest		22.83	0.1919	20.83	0.1211
Lowest	CDMA BC1 1xRTT (GT - LC = -2 dB)	23.95	0.2483	21.95	0.1567
Middle		23.97	0.2495	21.97	0.1574
Highest		24.11	0.2576	22.11	0.1626
Lowest	CDMA BC1 1xEV-DO (GT - LC = -2 dB)	24.19	0.2624	22.19	0.1656
Middle		24.15	0.2600	22.15	0.1641
Highest		24.22	0.2642	22.22	0.1667
Limit	EIRP < 2W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	WCDMA Band IV RMC 12.2Kbps (GT - LC = -1.9 dB)	23.20	0.2089	21.30	0.1349
Middle		23.14	0.2061	21.24	0.1330
Highest		23.15	0.2065	21.25	0.1334
Limit	EIRP < 1W	Result		PASS	

**Radiated Spurious Emission**

<Close Mode>

<PT Antenna>

<Ant. 1>

GPRS 850

GPRS 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-47.76	-13	-34.76	-58.3	-54.71	0.53	9.63	H
	2472	-60.47	-13	-47.47	-74.4	-68.45	0.65	10.78	H
	3296	-58.17	-13	-45.17	-74.86	-67.25	0.76	11.99	H
									H
									H
									H
									H
	1648	-46.25	-13	-33.25	-56.49	-53.2	0.53	9.63	V
	2472	-59.35	-13	-46.35	-73.83	-67.33	0.65	10.78	V
	3296	-58.11	-13	-45.11	-74.77	-67.19	0.76	11.99	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**EDGE 850**

EDGE 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-47.43	-13	-34.43	-57.97	-54.38	0.53	9.63	H
	2472	-59.46	-13	-46.46	-73.41	-67.44	0.65	10.78	H
	3296	-58.28	-13	-45.28	-74.97	-67.36	0.76	11.99	H
									H
									H
									H
									H
	1648	-45.47	-13	-32.47	-55.71	-52.42	0.53	9.63	V
	2472	-59.39	-13	-46.39	-73.87	-67.37	0.65	10.78	V
	3296	-58.25	-13	-45.25	-74.91	-67.33	0.76	11.99	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**WCDMA 850**

WCDMA 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1652	-62.68	-13	-49.68	-73.22	-69.64	0.53	9.63	H
	2479	-60.60	-13	-47.60	-74.57	-68.58	0.65	10.78	H
	3305	-58.29	-13	-45.29	-74.98	-67.4	0.76	12.02	H
									H
									H
									H
									H
	1652	-62.89	-13	-49.89	-73.14	-69.85	0.53	9.63	V
	2479	-59.85	-13	-46.85	-74.31	-67.83	0.65	10.78	V
	3305	-58.45	-13	-45.45	-75.09	-67.56	0.76	12.02	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**CDMA BC0(1xRTT)**

CDMA BC0(1xRTT)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-62.34	-13	-49.34	-73	-69.34	0.53	9.68	H
	2509	-60.37	-13	-47.37	-74.34	-68.37	0.66	10.81	H
	3345	-58.03	-13	-45.03	-74.8	-67.25	0.76	12.14	H
									H
									H
									H
									H
	1672	-62.55	-13	-49.55	-72.81	-69.55	0.53	9.68	V
	2509	-59.42	-13	-46.42	-73.79	-67.42	0.66	10.81	V
	3345	-58.45	-13	-45.45	-75.01	-67.67	0.76	12.14	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<Open Mode>

<PT Antenna>

<Ant. 1>

CDMA BC0(1xEVDO)

CDMA BC0(1xEVDO)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1649	-62.12	-13	-49.12	-72.66	-69.07	0.53	9.63	H
	2474	-60.09	-13	-47.09	-74.04	-68.07	0.65	10.78	H
	3298	-58.05	-13	-45.05	-74.74	-67.14	0.76	11.99	H
									H
									H
									H
									H
	1649	-62.52	-13	-49.52	-72.76	-69.47	0.53	9.63	V
	2474	-59.64	-13	-46.64	-74.11	-67.62	0.65	10.78	V
	3298	-58.23	-13	-45.23	-74.89	-67.32	0.76	11.99	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**GPRS 1900**

GPRS 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	3820	-57.65	-13	-44.65	-75.33	-69.43	0.69	12.47	H
	5730	-54.57	-13	-41.57	-76.97	-66.64	0.99	13.06	H
	7640	-52.00	-13	-39.00	-77.69	-61.61	1.18	10.79	H
									H
									H
									H
									H
	3820	-56.33	-13	-43.33	-75.23	-68.11	0.69	12.47	V
	5730	-54.59	-13	-41.59	-77.2	-66.66	0.99	13.06	V
	7640	-51.79	-13	-38.79	-77.25	-61.4	1.18	10.79	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**EDGE 1900**

EDGE 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	3820	-57.66	-13	-44.66	-75.34	-69.44	0.69	12.47	H
	5730	-55.24	-13	-42.24	-77.64	-67.31	0.99	13.06	H
	7640	-51.60	-13	-38.60	-77.29	-61.21	1.18	10.79	H
									H
									H
									H
									H
	3820	-56.42	-13	-43.42	-75.32	-68.2	0.69	12.47	V
	5730	-54.96	-13	-41.96	-77.57	-67.03	0.99	13.06	V
	7640	-52.08	-13	-39.08	-77.54	-61.69	1.18	10.79	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**WCDMA 1900**

WCDMA 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	3816	-57.99	-13	-44.99	-75.67	-69.78	0.69	12.47	H
	5723	-54.94	-13	-41.94	-77.35	-67.01	0.99	13.07	H
	7630	-51.78	-13	-38.78	-77.47	-61.36	1.18	10.76	H
									H
									H
									H
									H
	3816	-56.37	-13	-43.37	-75.26	-68.16	0.69	12.47	V
	5723	-54.41	-13	-41.41	-77.02	-66.48	0.99	13.07	V
	7630	-51.63	-13	-38.63	-77.05	-61.21	1.18	10.76	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**CDMA BC1(1xRTT)**

CDMA BC1(1xRTT)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-56.76	-13	-43.76	-74.16	-68.55	0.72	12.52	H
	5553	-54.22	-13	-41.22	-76.61	-66.39	1.00	13.17	H
	7405	-51.61	-13	-38.61	-77.14	-61	1.18	10.57	H
									H
									H
									H
	3702	-55.63	-13	-42.63	-74.23	-67.42	0.72	12.52	V
	5553	-53.66	-13	-40.66	-76.14	-65.83	1.00	13.17	V
	7405	-51.52	-13	-38.52	-76.85	-60.91	1.18	10.57	V
									V
									V
									V
Middle	3760	-56.50	-13	-43.50	-74.06	-68.31	0.69	12.50	H
	5640	-53.87	-13	-40.87	-76.2	-66	0.98	13.12	H
	7520	-51.58	-13	-38.58	-77	-60.86	1.18	10.46	H
									H
									H
									H
	3760	-54.74	-13	-41.74	-73.5	-66.55	0.69	12.50	V
	5640	-53.81	-13	-40.81	-76.32	-65.94	0.98	13.12	V
	7520	-51.15	-13	-38.15	-76.62	-60.43	1.18	10.46	V
									V
									V
									V



Highest	3817	-56.36	-13	-43.36	-74.04	-68.15	0.69	12.47	H
	5726	-53.78	-13	-40.78	-76.18	-65.85	0.99	13.06	H
	7635	-50.97	-13	-37.97	-76.66	-60.56	1.18	10.78	H
									H
									H
									H
									H
	3817	-55.11	-13	-42.11	-74.01	-66.9	0.69	12.47	V
	5726	-53.58	-13	-40.58	-76.19	-65.65	0.99	13.06	V
	7635	-51.46	-13	-38.46	-76.9	-61.05	1.18	10.78	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**CDMA BC1(1xEVDO)**

CDMA BC1(1xEVDO)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-54.98	-13	-41.98	-72.38	-66.77	0.72	12.52	H
	5553	-53.71	-13	-40.71	-76.09	-65.88	1.00	13.17	H
	7404	-51.91	-13	-38.91	-77.44	-61.3	1.18	10.57	H
									H
									H
									H
	3702	-51.73	-13	-38.73	-70.33	-63.52	0.72	12.52	V
	5553	-54.27	-13	-41.27	-76.74	-66.44	1.00	13.17	V
	7404	-52.24	-13	-39.24	-77.57	-61.63	1.18	10.57	V
									V
									V
									V
Middle	3762	-54.14	-13	-41.14	-71.7	-65.95	0.69	12.50	H
	5640	-53.85	-13	-40.85	-76.18	-65.98	0.98	13.12	H
	7520	-51.51	-13	-38.51	-76.92	-60.79	1.18	10.46	H
									H
									H
									H
	3762	-50.52	-13	-37.52	-69.28	-62.33	0.69	12.50	V
	5640	-53.86	-13	-40.86	-76.37	-65.99	0.98	13.12	V
	7520	-51.25	-13	-38.25	-76.71	-60.53	1.18	10.46	V
									V
									V
									V



Highest	3816	-54.48	-13	-41.48	-72.16	-66.27	0.69	12.47	H
	5724	-54.20	-13	-41.20	-76.61	-66.27	0.99	13.07	H
	7632	-51.31	-13	-38.31	-77	-60.9	1.18	10.77	H
									H
									H
									H
									H
	3816	-50.15	-13	-37.15	-69.04	-61.94	0.69	12.47	V
	5724	-54.28	-13	-41.28	-76.89	-66.35	0.99	13.07	V
	7632	-51.66	-13	-38.66	-77.08	-61.25	1.18	10.77	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**WCDMA 1700**

WCDMA 1700									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	3505	-57.44	-13	-44.44	-75.07	-69.26	0.78	12.60	H
	5257	-56.92	-13	-43.92	-78.25	-68.62	1.01	12.71	H
	7010	-52.64	-13	-39.64	-77	-62.76	1.17	11.28	H
									H
									H
									H
									H
	3505	-56.67	-13	-43.67	-75.26	-68.49	0.78	12.60	V
	5257	-56.96	-13	-43.96	-78.44	-68.66	1.01	12.71	V
	7010	-52.19	-13	-39.19	-76.89	-62.31	1.17	11.28	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

—————THE END—————