

**SUBMITTED MEASURED DATA INDEX**

EXHIBIT	MEASUREMENT
6A	RF Power Output
6B	Audio Response
6C	Post Limiter Low Pass Filter Response - Graph
6D	Signaling Channel Audio Roll-Off Filter Response - Graph
6E1	Modulation Limiting (Compander In Wide Mode) - Graph
6E2	Modulation Limiting (Compander Out Wide Mode) - Graph
6F1	Occupied Bandwidth, Audio - Photograph
6F2	Occupied Bandwidth, Audio and SAT - Graph
6F3	Occupied Bandwidth, Wideband Data - Graph
6F4	Occupied Bandwidth, Signaling Tone and SAT - Graph
6F5	Occupied Bandwidth, Digital Mode - Graph
6G1	Conducted Spurious and Harmonic Emissions, Analog Mode - Graph
6G2	Conducted Spurious and Harmonic Emissions, Digital Mode - Graph
6H1	Radiated Spurious and Harmonic Emissions, Analog Mode - Graph
6H2	Radiated Spurious and Harmonic Emissions, Digital Mode - Graph
6J1	Frequency Change vs. Temperature, Analog Mode
6J2	Frequency Change vs. Temperature, Digital Mode
6K1	Frequency Change vs. Supply Voltage, Analog Mode- Graph
6K2	Frequency Change vs. Supply Voltage, Digital Mode - Graph

**RF POWER OUTPUT DATA**

The input supply to the transmitter was set at 3.6 Volts. The RF power output was measured with the indicated voltage and current applied into the final RF amplifying device(s).

**ANALOG MODE**

Measured RF output: 0.331W

Measured DC voltage: 3.6V

Measured DC current: 550mA.

Measured RF input: 3.46mW

**DIGITAL MODE**

In Digital Mode the values measured for RF Output, DC Current and RF Input Power are all average values which reflect a 100% transmit duty cycle in CDMA operation.

Measured RF output: 0.326W

Measured DC voltage: 3.6V

Measured DC current: 580mA.

Measured RF input: 2.98mW

**EFFECTIVE RADIATED POWER**

Since the unit is intended for use with a provided antenna (and “non standard” RF connector), EIRP is measured. The dipole antenna substitution method was used. The result indicated is the maximum EIRP found over the channels and radio orientations tested.

Maximum Effective Radiated Power: Analog Mode 26.0 dBm (0.398 W)


Maximum Effective Isotropic Radiated Power: Digital Mode 27.8 dBm (0.603 W)

**AUDIO RESPONSE -GRAPH**

Signature:

Date:


**Tx Audio Response -- Wide Mode**



**POST LIMITER LOW PASS FILTER RESPONSE -GRAPH**

Signature:


Date:




**SIGNALING CHANNEL AUDIO ROLL-OFF FILTER RESPONSE - GRAPH**

Signature:


Date:



**MODULATION LIMITING (COMPANDOR IN) -GRAPH**



**MODULATION LIMITING (COMPANDOR OUT) -GRAPH**




**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F8W**

DEVIATION OF THE CARRIER WITH 2500 Hz. AUDIO MODULATION

HORIZONTAL SCALE = 20 kHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 30dBm)  
 RESOLUTION BANDWIDTH =1000 Hz  
 VIDEO BANDWIDTH =1000 Hz  
 AUDIO LEVEL = 16 dB GREATER THAN LEVEL REQUIRED TO PRODUCE +/- 6 kHz  
 POWER LEVEL = 0.306W

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with the 2500 Hz. Tone, 16 dB greater than that required to produce +/- 6 kHz modulation. Photograph the sideband display while it is superimposed upon the unmodulated carrier.



SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or  $63 + 10 \log_{10}$  (mean output power in Watts) dB, whichever is the smaller attenuation.


**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F8W**

DEVIATION OF THE CARRIER WITH 2500 Hz AUDIO MODULATION AND SUPERVISORY AUDIO TONE

HORIZONTAL SCALE = 20 kHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 30dBm)  
 RESOLUTION BANDWIDTH = 1000 Hz  
 VIDEO BANDWIDTH = 1000 Hz  
 POWER LEVEL = 0.292W

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain the unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with signaling tone and 2500 Hz tone, 16 dB greater than that required to produce +/- 6kHz of deviation add SAT with +/- 2kHz of deviation. Photograph the sideband display while it is superimposed upon the unmodulated carrier.



SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or 63 + 10 log10 (mean output power in Watts) dB, whichever is the smaller attenuation.


**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F1D**

DEVIATION OF THE CARRIER WITH WIDE BAND DATA

HORIZONTAL SCALE = 20 kHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 30dBm)  
 RESOLUTION BANDWIDTH = 1000 Hz  
 VIDEO BANDWIDTH = 1000 Hz  
 POWER LEVEL = 0.332W

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain the unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with wide band data with +/- 8 kHz. Photograph the sideband display while it is superimposed upon the unmodulated carrier.



SPEC LIMITS

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90 kHz, the sideband is at least 45 dB below the carrier.
- c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or 63+10 log<sub>10</sub> (mean output power in Watts) dB, whichever is the smaller attenuation.


**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F1D**

DEVIATION OF THE CARRIER WITH 10 kHz SIGNALING TONE AND SUPERVISORY AUDIO TONE

HORIZONTAL SCALE = 20 kHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (REFERENCE LEVEL = 30dBm)  
 RESOLUTION BANDWIDTH = 1000 Hz  
 VIDEO BANDWIDTH = 1000 Hz  
 POWER LEVEL = 0.286W

MEASURED DATA:

1. Instantaneous Deviation Control set for a maximum of +/- 12 kHz
2. Tune and adjust to obtain the unmodulated carrier on the spectrum analyzer. Save trace of the unmodulated carrier.
3. Modulate the transmitter with signaling tone with +/- 8 kHz deviation and add SAT with +/- 2kHz of deviation. Photograph the sideband display while it is superimposed upon the unmodulated carrier.



**SPEC LIMITS**

- a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45 kHz, the sideband is at least 26 dB below the carrier.
- b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90 kHz, the sideband is at least 45 dB below the carrier.
- c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60 dB below the carrier or 63+10 log10 (mean output power in Watts) dB, whichever is the smaller attenuation.


**BANDWIDTH MEASUREMENT DATA FOR TRANSMITTER TYPES F9W**

DEVIATION OF THE CARRIER WITH OQPSK MODULATION

HORIZONTAL SCALE = 1MHz / DIVISION  
 VERTICAL SCALE = 10 dB / DIVISION (ATTENUATION)  
 RESOLUTION BANDWIDTH = 30 kHz  
 VIDEO BANDWIDTH = 100 Hz  
 POWER LEVEL = 0.316W (Average Power in transmitter)

MEASURED DATA:


1. Modulate the transmitter with OQPSK modulation, using pseudo random data. Obtain image on spectrum analyzer.




COMMENTS:

Modulation products in a bandwidth of 30 kHz ,centered +/- 1.25 MHz from the channel center frequency should be at least 45 dB and should be at least 42 dB below the mean output power level.


**ANALOG CONDUCTED SPURIOUS AND HARMONIC EMISSIONS - GRAPH**



**DIGITAL CONDUCTED SPURIOUS AND HARMONIC EMISSIONS - GRAPH**



**ANALOG RADIATED SPURIOUS AND HARMONIC EMISSIONS - GRAPH**




**Transmitter Radiated Spurious Emissions**

Log Pages:  
Date: 6/11/1999

- Carrier Power: 0.54 W to 4.8 mW in 4 dB steps.
- Carrier Frequency: 824.01 to 848.99 MHz in 10 kHz steps
- \* Each reported emission reflects the highest absolute level found among all power levels, channels, power amplifier configurations tested.
- \* All emissions not reported are more than 20 dB below the FCC specification
- \* No signals greater than -80 dBm were found in the 869 to 894 MHz band
- \* Spectrum was searched from 30 kHz to the 10th Harmonic of the transmitter

**DIGITAL RADIATED SPURIOUS AND HARMONIC EMISSIONS -GRAPH**




**Transmitter Radiated Spurious Emissions**


Log Pages:  
Date: 6/11/1999

- Carrier Power: 0.34 W to 0.00001 mW .
- Carrier Frequency: 1851.25 to 1908.75 MHz in 50 KHz steps
- \* Each reported emission reflects the highest absolute level found among all power levels, channels, power amplifier configurations tested.
- \* All emissions not reported are more than 20 dB below the FCC specification
- \* No signals greater than -80 dBm were found in the 1930 to 1990 MHz band
- \* Spectrum was searched from 30 kHz to the 10th Harmonic of the transmitter


**Frequency Change vs. Temperature (Wide Mode)-Graph**



**Frequency Change vs. Temperature (Digital Mode)-Graph**



**Frequency Change vs. Supply Voltage (Wide Mode)-Graph**



**Frequency Change vs. Supply Voltage (Digital Mode)-Graph**

