



MOTOROLA

PERSONAL COMMUNICATIONS SECTOR

**PRODUCT SAFETY AND COMPLIANCE
EMC LABORATORY**

EMC TEST REPORT

Test Report Number – 7267-1

Report Date – August 6, 2002

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Signature 

Name: Kirby Munroe

Title: Compliance Engineer

Date : 8/6/2002

This report must not be reproduced, except in full, without written approval from this laboratory.

THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.

A2LA Certificate Number: 1846-01



Table of Contents

<u>Description</u>	<u>Page</u>
Test Report Details	4
Applicable Standards	4
Summary of Testing	5
General and Special Conditions	5
Equipment and Cable Configurations	5
Measuring Equipment and Calibration Information	6
Measurement Procedures and Data	
RF Power Output	7
Radiated Power (ERP)	8
Modulation Characteristics	
Transmit Audio Frequency Response	9
Post Limiter Filter Attenuation	9
Modulation Limiting vs. Modulation Input Voltage	10
Occupied Bandwidth	11
AMPS Un-modulated Carrier	12
AMPS Supervisory Audio Tone	12
AMPS Voice	13
AMPS Signaling Tone	13
AMPS 10kb/s Wideband Data	14
TDMA 800 Reference Plot	15
TDMA 800 Mid Band Plot	15
TDMA 800 Lower Band Edge	16
TDMA 800 Upper Band Edge	16
Spurious Emissions at Antenna Terminals	17
AMPS Tabular and Graphical Data	18
AMPS Cellular Base Station Frequency Range Plot	19
TDMA 800 Tabular and Graphical Data	20
TDMA 800 Cellular Base Station Frequency Range Plot	21
Field Strength of Spurious Emissions	22
AMPS Tabular and Graphical Data	23
TDMA 800 Tabular and Graphical Data	24
Frequency Stability	25
AMPS Tabular and Graphical Data	26
TDMA 800 Tabular and Graphical Data	27
Field Strength of Spurious Emissions From Unintentional Radiators	28
AMPS Tabular and Graphical Data	29
TDMA 800 Tabular and Graphical Data	30

<u>Description</u>	<u>Page</u>
Appendix A - Radiated Emissions Test Setup Photos	
Figure A.1 – Radiated Emissions Measurement	31
Figure A.2 – Substitution Measurement	31

Test Report Details

Tests Performed By: Motorola Personal Communications Sector
Product Safety and Compliance Group
1500 Gateway Boulevard
Boynton Beach, FL 33426
PH (561) 739-2179 Fax (561) 739-2131
FCC Registration Number: 100000
Industry Canada Number: IC3908

Tests Requested By: Motorola Inc.
RODOVIA SP-340, KM.128.7 A
JAGUARIUNA, SP
13820-000
BRAZIL

Product Type: Cellular Phone

Signaling Capability: Analog, TDMA 800

Model Number: SJWF0136AA

Serial Numbers: 52FCE032, 52FCE02D, 52FCE02A

Received Date: 7/25/2002

Testing Start Date: 7/26/2002

Testing Complete Date: 8/2/2002

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

- Part 15 Subpart B – Unintentional Radiators
- Part 22 Subpart H - Public Mobile Services
- Part 24 - Personal Communications Services
- Part 90 - Private Land Mobile Radio Service

Applicable Standards: TIA EIA 137-A, ANSI 63.4 2000, RSS-118, RSS-128

Summary of Testing

Test #	Test Name	Pass/Fail
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	NA
3	Modulation Characteristics	Pass
4	Occupied Bandwidth	Pass
5	Spurious Emissions at Antenna Terminal	Pass
6	Field Strength of Spurious Emissions	Pass
7	Frequency Stability	Pass
8	Field Strength of Spurious Emissions from Unintentional Radiators	Pass

Test #	Test Name	Margin with respect to the Limit
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	NA
3	Modulation Characteristics	NA
4	Occupied Bandwidth	NA
5	Spurious Emissions at Antenna Terminal	19.2 dB
6	Field Strength of Spurious Emissions	22.6 dB
7	Frequency Stability	213 Hz
8	Field Strength of Spurious Emissions from Unintentional Radiators	2.1 dB

The margin with respect to the limit is the minimum margin for all modes and bands. () indicates the margin at which the product exceeds the limit.

General and Special Conditions

The EUT was tested using a fully charged battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment with an average temperature of 22° C and relative humidity of 50%.

Equipment and Cable Configurations

The EUT was tested in a stand-alone configuration that is representative of typical use.

Measuring Equipment and Calibration Information

Manufacturer	Item	Item Version/	Serial	CALIBRATION
Name	Name	Model #	Number	DUE DATE
	Description			
Rohde & Schwarz	EMI Test Receiver	ESI26	838386/010	2/26/2003
Hewlett Packard	EMC Analyzer	E7405	US3944019	10/11/2002
Hewlett Packard	RF Amplifier	8347A	3307A02001	12/20/2002
Hewlett Packard	Pre-Amplifier	8449B	3008A01343	12/20/2002
ETS	DRG Horn Antenna	3115	6222	9/23/2002
A.H. Systems Inc.	DRG Horn Antenna	SAS-200/571	265	8/21/2002
A.H. Systems Inc.	DRG Horn Antenna	SAS-200/571	365	11/14/2002
ETS	Log-Periodic Antenna	3148	1188	12/6/2002
ETS	Log-Periodic Antenna	3148	1189	1/2/2003
ETS	Biconical Antenna	3110B	3369	12/15/2002
ETS	Biconical Antenna	3110B	3370	10/16/2002
Compliance Design	Biconical Antenna	B100	385	7/16/2003
Compliance Design	Biconical Antenna	B200	312	7/22/2003
Compliance Design	Biconical Antenna	B300	321	7/22/2003
Attenuator	Weinschel	AS-6	6675	10/10/2002
Attenuator	Weinschel	AS-6	6677	11/10/2002
Rohde & Schwarz	Mobile Test Set	CMD 80	DE29008	10/18/2002
Hewlett Packard	Signal Generator	83623B	3844A01195	1/16/2003
Thermotron	Environmental Chamber	S-4	31580	12/20/2002

All equipment is on a one-year calibration cycle.

Measurement Procedures and Data

RF POWER OUTPUT

Measurement Procedure

The RF output port of the equipment under test is directly coupled to the input of the 8650 series Gigatronics power meter through a specialized RF connector. The power meter is set for Burst Average Power mode (BAP). The power output is measured for all channels.

CFR Part 2.1046

Measurement Results

* Data supplied by SAR Lab

ANALOG

Frequency (MHz)	Power (dBm)
824.04	25.40
836.52	25.46
848.97	25.49

TDMA 800

Frequency (MHz)	Power (dBm)
824.04	27.53
836.52	27.49
848.97	27.51

RADIATED POWER (ERP)

Measurement Procedure

The phone was tested in Harvard Chamber 1, which is a 16' cubical anechoic chamber with a 2-axis positioner system that permits taking complete spherical scans of the AUT's radiation patterns. For all tests, the phone was supported in a free-space type environment, vertically oriented in the chamber. Tests were done for AMPS 800 frequency (824.04) (836.52Mhz)and (848.97) PCS 1900 frequency(1850.04) (1879.98) and (1909.92) and AMPS Analog frequency(824.04) (836.52 MHz) and (848.97) with antenna stubby

TDMA measurements were made with the phone placed in a call using the HP 8920 mobile station test set. The phone was weakly coupled to the test set and configured to transmit in full data rate mode. Radiated power was measured at every 15 degree step from theta=0 to 165 degrees and phi=0 to 360 degrees. The radiated power was measured using a Gigatronics 8542C power meter in "Burst Avg" mode. From these measurements, the software calculates the angle at which maximum radiated power occurs for each case, and the radiated power at this angle was extracted from the data. The max radiated power results for the IHDT5CA1 follows, as EIRP in dBm. To get ERP (effective radiated power referenced to a half-wave dipole), subtract 2.1 dB from these numbers.

Measurement Results

AMPS 800 TDMA:

824.04 MHz	27.52 dBm EIRP
836.52 MHz:	27.53 dBm EIRP
848.97 MHz:	28.12 dBm EIRP

AMPS 800 Analog :

824.04 MHz	24.40 dBm EIRP
836.52 MHz	23.55 dBm EIRP
848.97 MHz	24.22 dBm EIRP

MAXIMUM:

AMPS 800 TDMA:	EIRP is 28.12 dBm (26.02 dBm, 0.42 Watts ERP)
AMPS Analog:	EIRP is 24.40 .dBm (22.30 dBm, 0.17Watts ERP)


MODULATION CHARACTERISTICS

CFR Part 2.1047, 22.915


Measurement Results -AMPS

* Data supplied by product group



Transmit Audio Frequency Response



Post Limiter Filter Attenuation



Modulation Limiting vs. Modulation Input Voltage



OCCUPIED BANDWIDTH

CFR Part 2.1049, 22.917

Measurement Procedure

The RF output port of the equipment under test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. The amplitude of the spectrum analyzer is corrected for the attenuator and any other applicable losses. The analyzer is set for Peak Detector and each trace is set for Max Hold. A fully charged battery was used for the supply voltage.


The middle channel within the designated frequency block was measured. For digital modulation, the lower and upper band edge plots are displayed.

Measurement Results


Attached

Measurement Results – AMPS


AMPS - Unmodulated Carrier – 836.52 MHz




AMPS - Supervisory Audio Tone – 836.52 MHz




AMPS – Voice – 836.52 MHz



AMPS – Signaling Tone – 836.52 MHz




AMPS – 10kb/s Wideband Data – 836.52 MHz




Measurement Results – TDMA 800

TDMA 800 – Reference Level Plot – 836.52 MHz



TDMA 800 – 836.52 MHz



TDMA 800 – Lower Band Edge – 824.04 MHz – 30.01 dBm



TDMA 800 – Upper Band Edge - 848.97 MHz – 29.67 dBm



SPURIOUS EMISSIONS AT ANTENNA TERMINALS

CFR Part 2.1051, 22.917

Measurement Procedure

The RF output port of the Equipment Under Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

The spectrum was investigated from the lowest frequency signal generated, without going below 9 kHz, up to at least the tenth harmonic of the fundamental or 40 GHz, whichever is lower.


Measurements were made at the middle channel within the frequency band and within the base station frequency range (869-894 MHz) for cellular.

Measurement Results

Attached

Measurement Results
Modulation: AMPS


Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-37.6
3rd harmonic	-13	-37.8
4th harmonic	-13	-39.7
5th harmonic	-13	*
6th harmonic	-13	-68.0
7th harmonic	-13	-54.4
8th harmonic	-13	-53.7
9th harmonic	-13	-57.7
10th harmonic	-13	-59.8



Notes:


1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

AMPS – Cellular Base Station Frequency Range – 836.52 MHz – 24.82 dBm



Measurement Results
Modulation: TDMA 800


Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-32.6
3rd harmonic	-13	-32.2
4th harmonic	-13	-48.1
5th harmonic	-13	-66.2
6th harmonic	-13	*
7th harmonic	-13	-61.9
8th harmonic	-13	-45.0
9th harmonic	-13	-42.8
10th harmonic	-13	-50.1



Notes:

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

TDMA 800–Cellular Base Station Frequency Range–836.52 MHz–29.72 dBm



FIELD STRENGTH OF SPURIOUS EMISSIONS

CFR Part 2.1053, 22.917

Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum reading on the spectrum analyzer. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The equipment under test is then replaced with a substitution antenna fed by a signal generator. With the signal generator tuned to a particular spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters to obtain a maximum reading at the spectrum analyzer. The output of the signal generator is then adjusted until a reading identical to that obtained with the actual transmitter is achieved.

The power in dBm of each spurious emission is calculated by correcting the signal generator level for cable loss and gain of the substitution antenna referenced to a dipole. A fully charged battery was used for the supply voltage.


Photographs of the radiated test set-up including substitution are enclosed in Appendix A.

Measurement Results

Attached

Measurement Results
Modulation: AMPS

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	-47.5	-44.0
3rd harmonic	-13	-42.9	-44.0
4th harmonic	-13	-52.2	-48.4
5th harmonic	-13	-45.8	-46.1
6th harmonic	-13	-52.9	-54.0
7th harmonic	-13	-51.3	-52.1
8th harmonic	-13	-45.2	-44.9
9th harmonic	-13	*	-49.3
10th harmonic	-13	*	*




Notes:

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

Measurement Results
Modulation: TDMA 800

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	-40.4	-35.7
3rd harmonic	-13	-38.5	-35.6
4th harmonic	-13	-50.8	-50.3
5th harmonic	-13	-44.4	-42.7
6th harmonic	-13	-48.9	-46.9
7th harmonic	-13	-47.3	-43.4
8th harmonic	-13	-46.7	-40.4
9th harmonic	-13	-48.1	-49.3
10th harmonic	-13	*	*



Notes:

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid and high channels at maximum power.
3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

FREQUENCY STABILITY

CFR Part 2.1055, 22.355

Measurement Procedure

The equipment under test is placed in an environmental chamber. The antenna port of the Equipment Under Test is directly coupled to the input of the measurement equipment through a specialized RF connector. A power supply is attached as the primary voltage supply.

Frequency measurements are made at the extremes of the temperature range -30°C to $+60^{\circ}\text{C}$ and at intervals of 10°C with the primary supply voltage set to the nominal battery operating voltage. A period of time sufficient to stabilize all components of the equipment is allowed at each frequency measurement. The maximum variation of frequency is measured.

At room temperature, the primary supply voltage is reduced to the battery operating endpoint of the equipment under test. The maximum variation of frequency is measured.

Measurement Results


Attached

Measurement Results
Modulation: AMPS

Frequency Stability

Mode: Analog Operating Frequency: 836.52 MHz
 Channel: 384 Deviation Limit (PPM): 2.5ppm

Temperature C	Frequency Error HZ	Frequency Error (PPM)	Voltage (%)	Voltage (VDC)
-30 C	-181.00	-0.216	100%	3.80
-20 C	-174.00	-0.208	100%	3.80
-10 C	-168.00	-0.201	100%	3.80
0 C	-188.00	-0.225	100%	3.80
10 C	-182.00	-0.218	100%	3.80
20 C	-184.00	-0.220	100%	3.80
30 C	-192.00	-0.230	100%	3.80
40 C	-182.00	-0.218	100%	3.80
50 C	-192.00	-0.230	100%	3.80
60 C	-196.00	-0.234	100%	3.80
20 C	-201.00	-0.240	Battery Endpoint	3.40




Measurement Results
Modulation: TDMA 800

Frequency Stability

Mode: TDMA 800 **Operating Frequency:** 836.52 MHz
Channel: 384 **Deviation Limit (PPM):** 0.359ppm (+/-300 Hz)

Temperature C	Frequency Error HZ	Frequency Error (PPM)	Voltage (%)	Voltage (VDC)
-30 C	66.00	0.079	100%	3.80
-20 C	68.00	0.081	100%	3.80
-10 C	55.00	0.066	100%	3.80
0 C	66.00	0.079	100%	3.80
10 C	23.00	0.027	100%	3.80
20 C	51.00	0.061	100%	3.80
30 C	84.00	0.100	100%	3.80
40 C	87.00	0.104	100%	3.80
50 C	84.00	0.100	100%	3.80
60 C	85.00	0.102	100%	3.80
20 C	47.00	0.056	Battery Endpoint	3.40



FIELD STRENGTH OF EMISSIONS FROM UNINTENTIONAL RADIATORS

CFR Part 15.109

Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each radiated emission, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum peak reading on the spectrum analyzer. The radiated emissions are then measured using an EMI receiver employing a CISPR quasi-peak detector function below 1000 MHz and an average detector function above 1000 MHz. This is repeated for both horizontal and vertical polarizations of the receive antenna. A fully charged battery was used for the supply voltage.

The field strength of each radiated emission is calculated by correcting the EMI receiver level for cable loss, amplifier gain, and antenna correction factors.


Field Strength (dBuV/m) = EMI Receiver Level (dBuV) + Cable Loss (dB) -
Amplifier Gain (dB) + Antenna Correction Factor (1/m)

Measurement Results

Attached

Measurement Results
Modulation: AMPS

Frequency (MHz)	FCC Maximum Limit (dBuV/m)	Horizontal Measured Field Strength (dBuV/m)	Vertical Measured Field Strength (dBuV/m)
Local Oscillator	54	*	*
2nd harmonic	54	*	*
3rd harmonic	54	*	42.8
4th harmonic	54	51.9	51.4
5th harmonic	54	*	*
6th harmonic	54	*	*




Notes:

- * Indicates the spurious emission could not be detected due to noise limitations or ambients.
- Each emission reported reflects the highest absolute level at the specific frequency for the low, mid, and high channels.

Measurement Results
Modulation: TDMA 800


Frequency (MHz)	FCC Maximum Limit (dBuV/m)	Horizontal Measured Field Strength (dBuV/m)	Vertical Measured Field Strength (dBuV/m)
Local Oscillator	54	*	*
2nd harmonic	54	*	*
3rd harmonic	54	*	42.4
4th harmonic	54	49.3	47.7
5th harmonic	54	*	*
6th harmonic	54	*	*




Notes:

1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. Each emission reported reflects the highest absolute level at the specific frequency for the low, mid, and high channels.

Appendix A – Radiated Emissions Test Setup Photos



A.1 Radiated Emissions Measurement



A.2 Substitution Measurement

End of Test Report