



February 4, 2000
Supplement to SAR Test Report for Motorola portable cellular phone (FCC ID IHDT5ZG1).

Prepared by:
Paul Moller
Motorola Personal Communications Sector Product Safety Laboratory
Libertyville, Illinois

Contents

- 1) Introduction
- 2) Applicable Regulations
- 3) Description of Test Sample
- 4) Description of Motorola SAR Test Facility
- 5) Test Sample Conditions
- 6) Method of Measurement
- 7) Measurement Uncertainty
- 8) SAR Test Results
- 9) SAR in the Hand Measurements
- 10) Body Worn Configuration
- 11) Battery Options™
- 12) Summary

Appendix A: Included data

Appendix B: Included data for Body Worn Configuration

Appendix C: Printout from the Dasy™ measurement system validation test

1. Introduction

The Motorola Personal Communications Sector Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of portable cellular phone FCC ID IHDT5ZG1. The Specific Absorption Rate (SAR) of this product was measured. This report details the test setup and equipment as well as the results of those tests.

2. Applicable Regulations

Federal Communications Commission rule §2.1093(d)(2), the ANSI/IEEE C95.1 1992 and the NCRP Report Number 86 specify the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20cm of the user in the uncontrolled environment.

3. Description of Test Sample

A prototype unit serial number FC8E6081 was measured. This unit is identical in physical construction, maximum radiated power levels and antenna structure to units that will be in production. It transmits in the frequency range of 824 to 849 MHz using AMPS and TDMA modes. The unit is equipped with a fixed antenna that serves as both a receive and transmit antenna. The antenna has a single operating position as shown in figures 1 and 2.



Figure 1.



Figure 2.

Figure 3 shows the test unit as it is placed onto the Motorola phantom. For the purposes of the actual SAR tests the Motorola phantom head is tilted on its side by 90 degrees so that a vertically oriented measurement probe can easily scan an area where the phone is in close contact with the phantom and the SAR will be the highest.



Figure 3. Phone against side of Phantom Head.

4. SAR Test Facility

The Motorola test facility utilized for the SAR testing of this product is the Personal Communications Sector Product Safety Laboratory, in Libertyville Illinois. The laboratory utilizes a Dosimetric Assessment System (Dasy™) SAR measurement system manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. This system utilizes a computer controlled six axis robot to move a measurement probe to measure the SAR. A photo of the Dasy™ system with the Motorola phantom is shown in figure 4. Probe serial number 1391 was used for the measurements. It was calibrated at SPEAG™, and has a calibration date October 6, 1999. Dipole Validation Kit type D835V2, serial number 414 was used to validate the system accuracy. The validation SAR value is 8.56 mW/g normalized to 1 Watt, and the Dasy™ system used for the test phone measured 8.88 mW/g normalized to 1 Watt. This is within the required accuracy, and thus the measured SAR values are considered correct. See appendix C for printout of the validation test from the Dasy™ measurement system.

The measurement methodology is described in IEEE Transactions on Vehicular Technology, vol. 44, no. 3, August 1995, titled Electromagnetic Energy Exposure of Simulated users of Portable

Cellular Telephones. The Dasy™ system is operated per the instructions in the Dasy™ Users Manual. The manual is available directly from SPEAG™.



Figure 4. Dasy™ System

5. Test Sample Conditions

For the purposes of these tests the subject phone was positioned on the measurement phantom per the instructions in the Motorola users manual for the subject phone. The position used for the tests is the 3-point contact position. In this position the test sample contacts the phantom's ear and cheek and is positioned with a repeatability of better than $\pm 6\%$. Since the antenna is not located on the center of the phone, the SAR was measured with the phone on both the left and right side talk positions (See figure 3). Due to the construction of the phone, the base of the antenna is 23 mm away from the phantom for the left side head, which is the closest.

The test sample is capable of operation in a test mode that allows control of the transmitter without the need to place actual phone calls. This guarantees that the unit does not change its transmitter power, and that the resultant SAR values will not be affected by external connections. For the purposes of this test the unit is commanded to test mode and manually set to the proper channel, transmitter power level and transmit mode of operation. Since the test sample uses the 1/3 duty cycle of the TDMA system while in digital mode, the crest factor (the ratio between peak and average power) is set to 3 for these tests. When the test sample was tested in analog mode the

crest factor was set to 1. The phone is then placed in the SAR measurement system with a fully charged battery. At the end of each test the Dasy™ system measures the drift of the SAR at a fixed point in the phantom so as to ensure that the test sample has not changed in transmitter power. For the purposes of these tests, the transmitter was operated at the highest transmitter output and with the phone on both left and right side talk positions

6. Method of Measurement

The system is instructed to scan as much of the face of the phone as is in close proximity to the phantom. Using the information gained about the general region of highest SAR, the system then automatically scans a smaller area centered around the location of peak spatial SAR. During this scan the system automatically measures the fall off of electric field strength as the measurement probe is moved away from the inner surface of the phantom in the direction of the local normal to the phantom surface. Using appropriate probe calibration techniques, the SAR in 1 gram of phantom tissue is then calculated. The phantom head, shown in figure 3, was filled with a liquid having relative dielectric constant equal to 49.7 and conductivity equal to 0.88 S/m. This mixture is a good dielectric equivalent of the gray matter of the human brain. The composition of the liquid mixture is as follows: 42.5% water; 55.6.0% sugar; 0.8% salt, 1% HEC; and 0.1% bactericide

7. Measurement Uncertainty

The overall RSS uncertainty of the measurement system is $\pm 12.0\%$. The breakdown of the individual uncertainties is as follows:

Probe Uncertainty	$\pm\%$
Isotropy error	7.2
Calibration error	3.3
Spatial resolution	0.5
SAR Evaluation	
Conductivity measurement	5.0
Environmental errors	1.0
Peak SAR Evaluation	
Probe positioning	1.0
Volumetric averaging	4.2
Device positioning	6.0

8. SAR Test Results

Figure 5 shows the phone overlaid with a typical contour plot. The phone is placed on the phantom's head with the center of the phone's speaker at the center of the ear, and the center line of the phone extends downward to the center of the phantom's mouth. The same orientation and phone position are used for left and right side talk positions.

The maximum SAR level for the Motorola portable cellular phone (FCC ID IHDT5ZG1) is 1.06 W/kg and was found on the right side head. A full data set output of two test conditions with the highest SAR values from the Dasy™ measurement system is included as appendix A. The test conditions included are indicated as bold numbers in the following table. All other test conditions measured lower SAR values than those included. Note that digital mode SAR data was

measured only for the test condition that resulted in the highest analog SAR value. This is because the only difference between analog and digital modes that can impact SAR is the average transmitter power.

Analog Channel	Left Head	Right Head	Conducted Power (mW)
991	0.95	1.06	313
384	0.84	0.96	322
799	0.33	0.59	309

TDMA Channel	Left Head	Right Head	Conducted Power (mW)
991		0.73	564
384			557
799			556



Figure 5. Contour Plot Overlaid on Face of Phone.

9. SAR in the Hand Measurements

The Motorola Portable cellular phone (FCC ID IHDT5ZG1) was measured for total radiated power in the presence of a human phantom complete with a hand holding the phone. The phone was positioned on a full body measurement phantom per the instructions in the Motorola users manual for the subject phone. Total radiated power was measured without a hand holding the phone, and then as a second measurement with a phantom hand holding the phone in a normal position. One can see the placement of the phantom hand relative to the subject phone in figure 7. The phantom hand has the same dimensions as a real human hand, and is made of a pliable shell that is filled with tissue simulant. The tissue simulant is the same as is used in the head phantom. The dielectric constant is 43.0 and the conductivity is 0.85 S/m. The composition of the liquid mixture is as follows: 42.5% water; 55.6.0% sugar; 0.8% salt, 1% HEC; and 0.1% bactericide. The phantom is placed inside of an anechoic chamber capable of performing full spherical scans of the phones radiation characteristics, specifically total radiated power. The difference in total radiated with and without the phantom hand is then measured for both the antenna retracted and extended cases.

This difference in total radiated power is then the maximum power that is deposited in the hand. The phone was set to transmit on maximum power (0.32 Watt) in analog mode and maximum power (0.56 Watt) in TDMA mode.

Federal Communications Commission rule §2.1093(d)(2), the ANSI/IEEE C95.1 1992 and the NCRP Report Number 86 specify the maximum exposure limit in the hand of 4 W/kg as averaged over any 10 grams of tissue for portable devices being used within 20cm of the user in the uncontrolled environment. More than 40mW of total power deposited in the hand would be required for the limit of 4 W/kg averaged over 10 grams to be exceeded. The maximum total power deposited in the hand for the test unit was 15mW. Since the total power deposited in the hand for the test phone is less than 40 mW, the standard is not exceeded. Included are two pictures. Figure 7 shows the subject phone in the normal talk position with the phantom hand in the test position. Figure 8 shows the full body phantom in the anechoic chamber.



Figure 7. Simulated Hand Against Phantom Head.




Figure 8. Phantom in Anechoic Chamber.

10. Body Worn Configuration

The cellular phone (FCC ID IHDT5ZG1) can be used in a body-worn configuration using the supplied belt clip. We have performed an evaluation to show RF exposure compliance when used the supplied belt clip. Figure 9 shows the test unit as it is placed onto the phantom. The phantom was filled with a liquid having relative dielectric constant equal to 51.9 and conductivity equal to 1.1 S/m. The composition of the liquid mixture is as follows: 52.5% water; 45.0% sugar; 1.3% salt, 1% HEC; and 0.2% bactericide. The 1900MHz phantom was filled with a liquid having relative dielectric constant equal to 40.7 and conductivity equal to 1.83 S/m. The composition of the liquid mixture is as follows: 45.9% water; 53.0% sugar; 0% salt, 1% HEC; and 0.1% bactericide.



Figure 9. Phone In Supplied Belt Clip Against Phantom

The following table shows the SAR values for the body worn condition for using the supplied belt clip. A full data set output of the test condition with the highest SAR values from the Dasy™ measurement system is included as appendix B. The test condition included is indicated as a bold number in the following table. All other test conditions measured lower SAR values than those included. The location of highest SAR was the area on the phone near the antenna.

Analog Channel	Belt Clip
991	0.90
384	1.25
799	0.90

11. Battery Options

The cellular phone (FCC ID IHDT5ZG1) does have several battery options when used in a body-worn configuration. There are two 'main' battery options that fit in the pocket of the upper portion of the phone which, when the phone is closed and placed in the supplied belt clip. The batteries do not change the distance between the phone and body, thus the SAR should not be affected.

12. Summary

The SAR values found for the portable cellular phone (FCC ID IHDT5ZG1) are below the maximum recommended levels of 1.6 W/kg.

Appendix A

The following pages are printouts from the Dasy™ measurement system of the data as indicated.

s/n FC8E6081

Ch#: 991 Pwr: Step 02

Mindy Right Head Phantom; Right Head Section; Position: (80°,180°); Frequency: 824 MHz


Probe: ET3DV6 - SN1391; ConvF(6.18,6.18,6.18); Crest factor: 1.0; Brain 836MHz : $\sigma = 0.88$ mho/m $\epsilon_r = 49.7$ $\rho = 1.00$ g/cm³

Cube 5x5x7: SAR (1g): 1.06 mW/g, SAR (10g): 0.761 mW/g, (Worst-case extrapolation)

Coarse: Dx = 10.0, Dy = 10.0, Dz = 0.0

Penetration depth: 18.9 (15.1, 23.4) [mm]

Powerdrift: -0.01 dB



s/n FC8E6081

Ch#: 991 Pwr Step: 02

Mork(left) Phantom; Left Head Section; Position: (80°,180°); Frequency: 824 MHz


Probe: ET3DV6 - SN1391; ConvF(6.18,6.18,6.18); Crest factor: 1.0; Brain 836MHz : $\sigma = 0.93$ mho/m $\epsilon_r = 46.8$ $\rho = 1.00$ g/cm³

Cube 5x5x7: SAR (1g): 0.953 mW/g, SAR (10g): 0.685 mW/g, (Worst-case extrapolation)

Coarse: Dx = 8.0, Dy = 8.0, Dz = 0.0

Penetration depth: 19.8 (16.9, 22.3) [mm]

Powerdrift: 0.06 dB



s/n FC8E6081

Ch#: 991 Pwr Step: 02

Mindy Right Head!!!! Phantom; Right Head Section; Position: (80°,180°); Frequency: 824 MHz



Probe: ET3DV6 - SN1391; ConvF(6.18,6.18,6.18); Crest factor: 1.0; Brain 836MHz : $\sigma = 0.88$ mho/m $\epsilon_r = 49.7$ $\rho = 1.00$ g/cm³

Cube 5x5x7: SAR (1g): 0.726 mW/g, SAR (10g): 0.511 mW/g, (Worst-case extrapolation)

Coarse: Dx = 10.0, Dy = 10.0, Dz = 0.0

Penetration depth: 17.4 (14.4, 21.3) [mm]

Powerdrift: 0.14 dB

SAR_{Tot} [mW/g]

Appendix B

The following pages are printouts from the Dasy™ measurement system of the data as indicated

s/n FC8E6081

Ch#: 384 Pwr Step: 02

Validation Chamber 1, Goofy Phantom; Flat Phantom Section; Position: (80°,220°); Frequency: 837 MHz


Probe: ET3DV6 - SN1391; ConvF(6.18,6.18,6.18); Crest factor: 1.0; Muscle 835 MHz: $\sigma = 1.10$ mho/m $\epsilon_r = 51.9$ $\rho = 1.00$ g/cm³

Cube 5x5x7: SAR (1g): 1.25 mW/g, SAR (10g): 0.868 mW/g, (Worst-case extrapolation)

Coarse: Dx = 12.0, Dy = 12.0, Dz = 0.0

Penetration depth: 14.8 (12.3, 17.4) [mm]

Powerdrift: 0.08 dB



Appendix C

The following page is the printout from the Dasy™ measurement system validation tests

Dipole 835 Mhz

835MHz Dipole Validation Dipole Sn# 414 / forward 248 mW

Validation Chamber 1, Goofy; Flat Phantom

Probe: ET3DV6 - SN1391; ConvF(6.18,6.18,6.18); Crest factor: 1.0; Brain 835 MHz : $\sigma = 0.80$ mho/m $\epsilon_r = 41.6$ $\rho = 1.00$ g/cm³

Cubes (2): Peak: 3.50 mW/g ± 0.10 dB, SAR (1g): 2.22 mW/g ± 0.09 dB, SAR (10g): 1.47 mW/g ± 0.08 dB, (Worst-case extrapolation)

Penetration depth: 13.0 (11.2, 15.5) [mm]

Powerdrift: 0.08 dB

