

ELITE ELECTRONIC ENGINEERING INC.
1516 CENTRE CIRCLE
DOWNERS GROVE, ILLINOIS 60515-1082

ELITE PROJECT: 31533

DATES TESTED: October 28 through
November 1, 2002

TEST PERSONNEL: Richard E. King EMC Engineer

TEST SPECIFICATION: FCC "Code of Federal Regulations" Title 47 Part
15, Subpart C, Section 15.247 for Frequency
Hopping Spread Spectrum Intentional Radiators
Operating within the 2400-2483.5MHz band

ENGINEERING TEST REPORT NO. 31533-01

MEASUREMENTS OF RF EMISSIONS

FROM THE MODEL BT0406AJ08 IN-VEHICLE BLUETOOTH MODULE

FOR: Motorola
Rolling Meadows, Illinois

PURCHASE ORDER NO.: NP554941

Report By:

Richard E. King
Richard E. King
EMC Engineer

Approved By:

Raymond J. Klouda
Raymond J. Klouda
Registered Professional
Engineer of Illinois - 44894

TABLE OF CONTENTS

	PAGE
1.0 INTRODUCTION	4
1.1 Description of Test Item	4
1.2 Purpose	4
1.3 Deviations, Additions and Exclusions	4
1.4 Applicable Documents	4
1.5 Subcontractor Identification	4
2.0 TEST ITEM SETUP AND OPERATION	5
3.0 TEST SITE AND INSTRUMENTATION	5
3.1 Test Site	5
3.2 Test Instrumentation	5
4.0 REQUIREMENTS, PROCEDURES AND RESULTS	5
4.1 Power Line Conducted Emissions	5
4.2 Carrier Frequency Separation	5
4.3 Number of Hopping Frequencies	6
4.4 Time of Occupancy (Dwell Time)	7
4.5 20 dB Bandwidth	7
4.6 Peak Output Power	8
4.7 Band-edge Compliance	9
4.8 Spurious Emissions	10
4.9 Power Spectral Density	11
5.0 CONCLUSION	12
6.0 CERTIFICATION	12
EQUIPMENT LIST	13

ADMINISTRATIVE DATA AND SUMMARY OF TESTS

DESCRIPTION OF TEST ITEM: Frequency Hopping Spread Spectrum
Transmitter

MODEL NO. :BT0406AJ08 SERIAL NO.: 00E00C49565E

FCC ID NO. : None given.

MANUFACTURER: Motorola

APPLICABLE

SPECIFICATION: FCC "Code of Federal Regulations", Title 47, Part 15,
Subpart C, Sec. 15.247

TEST PERFORMED BY: ELITE ELECTRONIC ENGINEERING INC.
Downers Grove, Illinois 60515

DATES TESTED: October 28 through November 1, 2002

PERSONNEL (OPERATORS, OBSERVERS, AND CO-ORDINATORS):

WITNESS: No Motorola personnel were present during the testing.

ELITE ELECTRONIC: Richard E. King

ELITE JOB NO.: 31533

ABSTRACT: The model BT0406AJ08 In-vehicle Bluetooth Module Transmitter meets the requirements of the FCC "Code of Federal Regulations", Title 47, Part 15, Subpart C, Section 15.247 for bluetooth spread spectrum transmitters. The carrier frequency separation, number of hopping frequencies, time of occupancy (dwell time), 20 dB bandwidth, peak output power, band-edge compliance, and spurious emissions and power spectral density were measured and found to comply with the requirements.

See the test results and data pages for more details.

MEASUREMENT OF RF EMISSIONS

FROM A MODEL BT0406AJ08 IN-VEHICLE BLUETOOTH MODULE TRANSMITTER

1.0 INTRODUCTION:

1.1 **DESCRIPTION OF TEST ITEM:** This report presents the results of the RF emissions measurements performed for the model BT0406AJ08 In-Vehicle Bluetooth Module spread spectrum transmitter, (hereinafter referred to as the test item). The tests were performed for Motorola located in Elk Grove Village, Illinois.

The test item is a frequency hopping spread spectrum transceiver used for in vehicle bluetooth applications. It operates in the frequency band 2400 to 2483.5MHz.

1.2 **PURPOSE:** The test series was performed to determine if the test item would meet the selected requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.247 for intentional radiators.

1.3 **DEVIATIONS, ADDITIONS AND EXCLUSIONS:** There were no deviations from the test requirements.

1.4 **APPLICABLE DOCUMENTS:** The following documents of the exact issue designated form part of this document to the extent specified herein:

Federal Communications Commission (FCC) "Code of Federal Regulations", Title 47, Part 15, dated 1 October 2001

FCC Public Notice, DA 00-705, "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems", Released March 30, 2000

1.5 **SUBCONTRACTOR IDENTIFICATION:** This series of tests was performed by the Elite Electronic Engineering Inc., of Downers Grove,

Illinois.

2.0 TEST ITEM SETUP AND OPERATION:

For all tests the test item was placed on a 0.8 meter high non-conductive table. The 7.0VDC was supplied to the test item from a power supply. The test item is supplied with an internal antenna.

3.0 TEST SITE AND INSTRUMENTATION:

3.1 TEST SITE: All tests were performed at Elite's facility in Downers Grove, Illinois. All tests were performed in a hybrid anechoic/ferrite tile shielded enclosure.

3.2 TEST INSTRUMENTATION: A list of the test equipment used can be found on Table I. All equipment was calibrated per the instruction manuals supplied by the manufacturer.

4.0 REQUIREMENTS, PROCEDURES AND RESULTS:

4.1 POWER LINE CONDUCTED EMISSIONS:

4.1.1 REQUIREMENT: This requirement does not apply since the test item receives 7.0VDC from the vehicle's power supply. There are no operation modes where the transmitter can be connected to the AC power public utilities, and therefore, the conducted emissions test are not required.

4.2 CARRIER FREQUENCY SEPARATION:

4.2.1 REQUIREMENTS: Per section 15.247 (a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

4.2.2 PROCEDURES: The test item was setup inside the chamber. With the hopping function enabled, the test item was allowed

to transmit continuously.

The resolution bandwidth (RBW) was set to \geq to 1% of the span. The peak detector and 'Max-Hold' function was engaged. The span was set wide enough to capture the peaks of at least two adjacent channels. When the trace had stabilized after multiple scans. The marker-delta function was used to determine the separation between the peaks of the adjacent channels. The analyzer's display was plotted using a 'screen dump' utility.

4.2.3 RESULTS: Data page 15 shows the carrier frequency separation. As can be seen from this plot, the separation is 1.005MHz which is greater than the 20dB bandwidth (940kHz).

4.3 NUMBER OF HOPPING FREQUENCIES:

4.3.1 REQUIREMENTS: Per section 15.247(a)(1)(ii), frequency hopping systems shall use at least 75 hopping frequencies.

4.3.2 PROCEDURE: The test item was setup inside the chamber. With the hopping function enabled, the test item was allowed to transmit continuously.

The resolution bandwidth (RBW) was set to \geq to 1% of the span. The peak detector and 'Max-Hold' function was engaged. The span was set wide enough to capture the entire frequency band of operation.

When the trace had stabilized after multiple scans. The number of hopping frequencies was counted. The analyzer's display was plotted using a 'screen dump' utility.

4.3.3 RESULTS: Data page 16 shows the number of hopping frequencies. As can be seen from this plot, the number of frequencies is 79 which is greater than the minimum required of 75.

4.4 TIME OF OCCUPANCY (DWELL TIME):

4.4.1 REQUIREMENTS: Per section 15.247(a)(1)(ii), the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

4.4.2 PROCEDURE: The test item was setup inside the chamber. With the hopping function enabled, the test item was allowed to transmit continuously.

The resolution bandwidth (RBW) was set to 1 MHz. The peak detector and 'Max-Hold' function was engaged. With the span set to 0Hz, the sweep time was adjusted to capture a single event in order to measure the dwell time per hop. Then, the sweep time was expanded to capture the average time between hops. When the trace had stabilized after multiple scans, the time between hops was measured. The analyzer's display was plotted using a 'screen dump' utility.

The dwell time in a 30 second period was then calculated from dwell time per hop divided by time between hops then multiplied by 30 seconds. The dwell time in a 30 second period was then divided by the number of frequency hopping channels to give the dwell time of a single frequency hopping channel.

4.4.3 RESULTS: Data pages 17 and 18 show the plots for the time of occupancy (dwell time). As can be seen from the plots, the time of occupancy can be determined by a 374.9 usec burst every 99.0 msec's multiplied by a 30 second period. This calculated value is equal to .0113 seconds which is less than the 0.4 seconds allowed.

4.5 20 dB BANDWIDTH:

4.5.1 REQUIREMENTS: Per section 15.247(a)(1)(ii), the

maximum 20dB bandwidth of the hopping channel is 1MHz.

4.5.2 PROCEDURE: The test item was setup inside the chamber. With the hopping function disabled, the test item was allowed to transmit continuously. The frequency hopping channel was set separately to low, middle, and high hopping channels. The resolution bandwidth (RBW) was set to \geq to 1% of the 20 dB BW.

The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. The analyzer's display was plotted using a 'screen dump' utility.

4.5.3 RESULTS: The plots on pages 19 through 21 show that the maximum 20 dB bandwidth was 0.940 MHz. The 20 dB bandwidth was less than the 1.0MHz maximum requirement.

4.6 PEAK OUTPUT POWER:

4.6.1 REQUIREMENTS: This requirement applies only to the transmit mode of operation. Per section 15.247(b) the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.6.2 PROCEDURES: Since the antenna was an integrated antenna the equivalent isotropic radiated power (EIRP) was computed from the radiated field strength measurements at 3 meters.

The spectrum analyzer bandwidth was set to 1 MHz which is greater than the 20dB bandwidth of the transmitter. A double ridged waveguide antenna was positioned 3 meters from the test item. The maximum meter reading was recorded for the vertical and horizontal

receiver antenna polarity while rotating the test item through 360 degrees. The EIRP was calculated for the low, middle and high hopping frequencies.

4.6.3 RESULTS: The results are presented on data page 22. The maximum EIRP measured from the transmitter was -14.5 dBm. Therefore, the transmitter meets the De Facto 36 dBm limit. Only one type of antenna is supplied with the test item.

4.7 BAND-EDGE COMPLIANCE:

4.7.1 REQUIREMENTS: Per section 15.247(c), the emissions at the band-edges must be at least 20dB below the highest level measured within the band. In addition, the radiated emissions which fall in the restricted band beginning at 2483.5 MHz, must meet the general limits of 15.209

4.7.2 PROCEDURE: The same data recorded for the low and high hopping frequencies from the 20 dB bandwidth measurements was used to demonstrate compliance with the 20 dB band-edge requirements.

For the radiated emissions which fall in the restricted band the "marker-delta" method described in Public Notice DA 00-705 was used. Initially radiated measurements were performed at the fundamentals of the highest hopping frequencies using 1 MHz bandwidth. For the measurements the "delta" required to meet the general limit was calculated.

Next, the band-edge emissions were plotted using peak detector and 100 kHz bandwidth. The "delta" limit was applied to this plot to determine compliance at the band-edge.

4.7.3 RESULTS: Data pages 23 through 26 show the band-edge

compliance results using the marker-delta method. As can be seen from this plots, the emissions at the band-edge in the restricted band are within the general limits.

4.8 SPURIOUS EMISSIONS:

4.8.1 REQUIREMENTS: Per section 15.247(c), the spurious emissions in any 100 kHz BW outside the frequency band must be at least 20dB below the highest 100 kHz BW level measured within the band. In addition, the radiated emissions which fall in the restricted bands must meet the general limits of 15.209.

4.8.2 PROCEDURES: Since the test item was supplied with a permanently attached antenna, the spurious emissions compliance was evaluated against the radiated emissions levels for unrestricted bands as well as the restricted bands.

The radiated tests were performed in a 32ft. x 20ft. x 18ft. hybrid absorber lined semi-anechoic test chamber. With the exception of the floor, the reflective surfaces of the shielded chamber are lined with ferrite tiles on the walls and ceiling. The floor of the chamber is used as the ground plane. The chamber complies with ANSI 63.4 and CISPR 16 requirements for site attenuation.

Preliminary radiated measurements are performed to determine the frequencies where the significant emissions might be found. With the test item at one set position and the measurement antenna at a set height (i.e. without maximizing), the radiated emissions were measured using peak detection with 100 kHz BW. This data was then automatically plotted up through 18 GHz. Frequency range 18 to 24 GHz was checked manually but not plotted.

Next, the harmonic or spurious emissions falling in the restricted bands were measured up through the 10th harmonic. For these measurements, the measurement bandwidths were set to 1 MHz RBW. The analyzer was set to linear mode with 10 Hz VBW in order to simulate an average detector. A pre-amplifier was used to increase the receiver sensitivity.

4.8.3 RESULTS: The preliminary emissions levels were plotted. These plots are presented on Data Pages 27 through 35. This plot shows that the spurious emissions were at least 20 dB below the level of the fundamental.

The harmonics and any other emissions that fall in the restricted frequency bands were then re-measured manually. This data is shown in the tables on data Pages 36 through 38. The field intensities levels for the harmonics in the restricted band were within the limit.

A block diagram of the test item orientation position is shown in Figure 1.

4.9 POWER SPECTRAL DENSITY:

4.9.1 REQUIREMENTS: Per section 15.247(d), the peak power spectral density from the intentional radiator shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.9.2 PROCEDURE: The test item was setup inside the chamber. The test item was put into acquisition mode.

The resolution bandwidth (RBW) was initially set to 3MHz to set the EIRP reference level. Knowing the EIRP peak level, the result of this plot was used to determine the 8dBm limit.

The resolution bandwidth (RBW) was set to 3kHz, the sweep time was set to the span divided by 3kHz (1MHz/3kHz = 333 seconds). The peak detector and 'Max-Hold' function was engaged. The analyzer's display was plotted using a 'screen dump' utility.

4.9.3 RESULTS: Data page 39 shows the power spectral density results. As can be seen from this plot, the peak power density is less than 8dBm in a 3kHz band during any time interval of continuous transmission.

5.0 CONCLUSION:

The Motorola model BT0406AJ08 In-Vehicle Bluetooth Module does meet the limits imposed by the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.247 for bluetooth spread spectrum transmitters.

6.0 CERTIFICATION:

Elite Electronic Engineering Inc. certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the test specification.

The data presented in this test report pertains to the test item at the test date. Any electrical or mechanical modification made to the test item subsequent to the specified test date will serve to invalidate the data and void this certification.

This report must not be used to claim product endorsement by NVLAP or any agency of the US Government.

ENGINEERING TEST REPORT NO. 31533-01

TABLE I: TEST EQUIPMENT LIST


ELITE ELECTRONIC ENG. INC.

Page: 1


Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Cal Inv	Due Date
Equipment Type: ACCESSORIES, MISCELLANEOUS								
XZG0	ATTENUATOR/SWITCH DRIVER	HEWLETT PACKARD	11713A	3439A02724	---			N/A
Equipment Type: AMPLIFIERS								
APH0	POWER AMPLIFIER	HEWLETT PACKARD	11975A	2304A00322	2-8GHZ			NOTE 1
APK0	PRE-AMPLIFIER	HEWLETT PACKARD	8449B	3008A00662	1-26.5GHZ	02/22/02	12	02/22/03
Equipment Type: ANTENNAS								
NTA0	BILOG ANTENNA	CHASE EMC LTD.	BIL0G CBL611	2057	0.03-2GHZ	06/25/02	12	06/25/03
NW10	RIDGED WAVE GUIDE	AEL	H1498	153	2-18GHZ	08/09/02	12	08/09/03
Equipment Type: ATTENUATORS								
T2D6	20DB, 25W ATTENUATOR - ESD	WEINSCHEL	46-20-43	AY9245	DC-18GHZ	02/04/02	12	02/04/03
Equipment Type: CONTROLLERS								
CDD2	COMPUTER	HEWLETT PACKARD	D4171A#ABA	US61654645	---			N/A
CDG1	COMPUTER	HEWLETT PACKARD	D5893T	US91465296	---			N/A
CDS0	COMPUTER	GATEWAY	MFATXPNT NMZ	0028483109	1.8 GHZ			N/A
CMA0	MULTI-DEVICE CONTROLLER	EMCO	2090	9701-1213	---			N/A
Equipment Type: METERS								
MAA0	AC AMMETER	WESTON	904	14562	750MA	05/11/02	12	05/11/03
MPAA	THERMISTOR MOUNT	HEWLETT PACKARD	8478B	1144A08340	0.01-18GHZ	09/04/02	12	09/04/03
Equipment Type: PRINTERS AND PLOTTERS								
HRE1	LASER JET 5P	HEWLETT PACKARD	C3150A	USHB061052	---			N/A
HRG1	LASERJET 2100XI	HEWLETT PACKARD	C4170A	USCD047809	---			N/A
HRLO	PRINTER LASERJET 2200D	HEWLETT PACKARD	C7058A	CNGRG86288	---			N/A
Equipment Type: RECEIVERS								
RAC1	SPECTRUM ANALYZER	HEWLETT PACKARD	85660B	3407A08369	100HZ-22GHZ	01/18/02	12	01/18/03
RACB	RF PRESELECTOR	HEWLETT PACKARD	85685A	3506A01491	20HZ-2GHZ	01/18/02	12	01/18/03
RAE1	SPECTRUM ANALYZER (DCC-CEM	HEWLETT PACKARD	85660A	2209A01336	100HZ-22GHZ	02/14/02	12	02/14/03
RAF3	QUASIPeAK ADAPTER	HEWLETT PACKARD	85650A	3303A01775	0.01-1000MHZ	01/18/02	12	01/18/03
Equipment Type: FREQUENCY MIXERS								
RAH0	FREQUENCY MIXER	HEWLETT PACKARD	11970K	2332A00270	18-26GHZ			N/A

Cal. Interval: Listed in Months I/O: Initial Only N/A: Not Applicable
 Note 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.

ETR 31533-01
Figure 1



Radiated Emissions Worst Case Horizontal Polarization



Radiated Emissions Worst Case Vertical Polarization


ELITE ELECTRONIC ENGINEERING Inc.

MKR ^ 1.005 MHz
-0.20 dB

hp

REF 107.0 dBuV ATTEN 10 dB

10 dB/



SPAN 5.00 MHz
SWP 20.0 msec

UBW 1 MHz

CENTER 2.441 00 GHz
RES BW 100 kHz(i)


ELITE ELECTRONIC ENGINEERING Inc.

MKR 2.480 58 GHz
72.20 dBuV

hp REF 107.0 dBuV

ATTEN 10 dB

10 dB/



MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08
SN : 00E00C49565E
TEST PERFORMED : FCC 15.247 NUMBER OF HOPPING FREQ
MODE : FREQ HOPPING ENABLED
NOTES : FULL POWER


R. KING
29 Oct 2002
10:09:52

START 2.400 0 GHz
RES BW 1 MHz (i)
STOP 2.485 0 GHz
SWP 20.0 msec
UBW 3 MHz

ELITE ELECTRONIC ENGINEERING Inc.

MKR ^ 374.9 usec
-0.20 dB

hp 10 dB/
REF 107.0 dBuV ATTEN 10 dB




ETR 31533-01

ELITE ELECTRONIC ENGINEERING Inc.

MKR ^ 99.00 msec
0.00 dB

REF 107.0 dBuV ATTEN 10 dB

hp
10 dB/



ETR 31533-01

CENTER 2.41000 GHz
RES BW 1 MHz(i)

UBW 3 MHz

SPAN 0 Hz
SWP 500 msec

ELITE ELECTRONIC ENGINEERING Inc.

MKR ^ 940 kHz
-0.60 dB


hp

10 dB/

DL
40.6
dBuV

REF 107.0 dBuV ATTEN 10 dB

MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08
SERIAL NUMBER : 00E00C49565E
TEST PERFORMED : FCC 15.247 20dB BANDWIDTH
MODE : TRANSMIT @ 2402.0MHz
NOTES : FULL POWER



R. KING
29 Oct 2002
14:42:01

SPAN 5.00 MHz
SWP 37.5 msec

VBW 300 kHz


CENTER 2.402 00 GHz
RES BW 30 kHz(i)

ELITE ELECTRONIC ENGINEERING Inc.

MKR ^ 940 kHz
-0.30 dB

hp
10 dB/
OFFSET
-20.0
dB
DL
42.5
dBuV

REF 107.0 dBuV ATTEN 10 dB



ETR 31533-01

SPAN 5.00 MHz
SWP 375 msec

UBW 100 kHz

CENTER 2.480 00 GHz
RES BW 10 kHz(i)

ELITE ELECTRONIC ENGINEERING Inc.

MKR ^ 935 kHz
0.60 dB

hp REF 107.0 dBuV ATTEN 10 dB


MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08
SERIAL NUMBER : 00E00C49565E
TEST PERFORMED: FCC 15.247 20dB BANDWIDTH
MODE : TRANSMIT @ 2441.0MHz
NOTES : FULL POWER

R. KING
29 Oct 2002
14:49:39

10 dB/
DL 38.8
dBuV

DL 38.8
dBuV

ETR 31533-01



SPAN 5.00 MHz
SWP 375 msec

VBW 100 kHz

CENTER 2.441 00 GHz
RES BW 10 kHz(i)



PEAK OUTPUT POWER

SPECIFICATION : FCC 15C (15.247)
MANUFACTURER : MOTOROLA INC.
MODEL No. : BT0406AJ08
SERIAL No. : 00E00C49565E
NOTES :
TEST DATE : OCTOBER 31, 2002

Freq. (MHz)	Ant. Pol.	F.I. (dBuV/m)	Conv. FI to EIRP	EIRP Total (dbm)	EIRP Limit (dBm)
2402.0	H	73.4	95	-21.6	36
	V	77.1	95	-17.9	36
2441.0	H	71.2	95	-23.8	36
	V	75.3	95	-19.7	36
2480.0	H	76.6	95	-18.4	36
	V	80.5	95	-14.5	36

CHECKED BY: Richard E. King
Richard E. King

ETR 31533-01

ELITE ELECTRONIC ENGINEERING Inc.

MKR 2.40196 GHz
69.60 dBuV

hp

REF 100.0 dBuV

ATTEN 10 dB

10 dB/


MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08
SN : 00E00C49565E

R. KING
29 Oct 2002
09:46:13

OFFSET
-20.0
dB

TEST PERFORMED : FCC 15.247 BAND EDGE COMPLIANCE
MODE : TRANSMIT @ 2402.0MHz
NOTES : FULL POWER

DL 49.6
dBuV



SPAN 10.0 MHz
SWP 20.0 msec

VBW 1 MHz

CENTER 2.4000 GHz
RES BW 100 kHz (i)

ELITE ELECTRONIC ENGINEERING Inc.

MKR 2.401 94 GHz
70.40 dBuV

hp

10 dB/


OFFSET
-20.0
dB

DL
50.4
dBuV

REF 107.0 dBuV ATTEN 10 dB

MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08
SN : 00E00C49565E
TEST PERFORMED : FCC 15.247 BAND EDGE COMPLIANCE
MODE : TRANSMIT @ 2402.0MHz
NOTES : FULL POWER

R. KING
29 Oct 2002
10:01:43



ETR 31533-01


24 of 39

CENTER 2.400 0 GHz RES BW 100 kHz(i) UBW 1 MHz SPAN 10.0 MHz
SWP 20.0 msec

ELITE ELECTRONIC ENGINEERING Inc.

MKR 2.479 95 GHz
73.40 dBuV

REF 107.0 dBuV
ATTEN 10 dB



R. KING
29 Oct 2002
13:18:43

MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08
SN : 00E00C49565E
TEST PERFORMED : FCC 15.247 BAND EDGE COMPLIANCE
MODE : TRANSMIT @ 2480.0MHz
NOTES : FULL POWER

BAND EDGE LIMIT

Radiated Ref w/100kHz = 79.3 dBuV/m
General Limit = 54
Delta = 25.3 dB

ETR 31533-01

hp

10 dB/

DL 53.9
dBuV

CENTER 2.483 5 GHz
RES BW 100 kHz(i) UBW 3 MHz SPAN 10.0 MHz
SWP 20.0 msec

ELITE ELECTRONIC ENGINEERING Inc.

MKR 2.479 94 GHz
80.50 dBuV

REF 107.0 dBuV ATTEN 10 dB


hp

10 dB/

MANUFACTURER : MOTOROLA INC.
 MODEL : BT0406AJ08
 SN : 00E00C49565E
 TEST PERFORMED : FCC 15.247 BANDEDGE COMPLIANCE
 MODE : FREQ. HOPPING ENABLED
 NOTES : FULL POWER RADIATED

R. KING
1 Nov 2002
09:44:16

DL 55.2 dBuV



ETD3533-01

CENTER 2.483 5 GHz RES BW 100 kHz(i) UBW 1 MHz SPAN 10.0 MHz SWP 20.0 msec


ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

JKAB 07/18/02

UNIEM RUN RUN 4

TEST : RADIATED NARROWBAND EMISSIONS
 SPEC : FCC 15.247 PRELIM RAD EMISSIONS
 MANUFACTURER : MOTOROLA INC.
 MODEL No. : BT0406AJ08
 S/N : 00E00C49565E
 MODE : TRANSMIT @ 2402.0MHz
 DATE TESTED : 1 Nov 2002 13:58:54 R. KING
 NOTES :
 ANT POLARITY : VERTICAL



RADIATED NARROWBAND EMISSIONS - dBu/m

27 of 39

START = 30

FREQUENCY - MHz

100


STOP = 1000

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

WKAB 07/18/02

UNIU_EM_RUN RUN 3



RADIATED NARROWBAND EMISSIONS - dBu/m

28 of 39

START = 1000

FREQUENCY - MHz


STOP = 2000

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIV_EM_RUN RUN 1

UKA0 07/18/02



TEST : RADIATED NARROWBAND EMISSIONS
 SPEC : PRELIMIN RADIATED EMISSIONS
 MANUFACTURER : MOTOROLA INC
 MODEL No. : 8T0406AJ08
 S/N : 00E00C49565E
 MODE : TRANSMIT @ 2402.0MHz
 DATE TESTED : 29 Oct 2002 14:10:07 R. KING
 NOTES :
 ANT POLARITY : VERTICAL

RADIATED NARROWBAND EMISSIONS - dBu/m

29 of 39

START = 2000

FREQUENCY - MHz

10000

STOP = 18000


ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

WKAB 07/18/02

UNIU_EM RUN RUN 4

TEST : RADIATED NARROWBAND EMISSIONS
 SPEC : FCC 15.247 PRELIM RAD EMISSIONS
 MANUFACTURER : MOTOROLA INC.
 MODEL No. : BT0406AJ08
 S/N : 00E00C49565E
 MODE : TRANSMIT @ 2441.0MHz
 DATE TESTED : 1 Nov 2002 14:02:00 R. KING
 NOTES :
 ANT POLARITY : VERTICAL



RADIATED NARROWBAND EMISSIONS - dBu/m

30 of 39

START = 30

FREQUENCY - MHz

100


STOP = 1000

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIU_EM RUN RUN 3

WJAB 07/18/02



TEST : RADIATED NARROWBAND EMISSIONS
 SPEC : FCC 15.247 PRELIM RAD EMISSIONS
 MANUFACTURER : MOTOROLA INC.
 MODEL No. : BT0406AJ08
 S/N : 00E00C49565E
 MODE : TRANSMIT @ 2441.0MHz
 DATE TESTED : 1 Nov 2002 11:43:51 R. KING
 NOTES :
 ANT POLARITY : VERTICAL

RADIATED NARROWBAND EMISSIONS - dBu/m

31 of 39

START = 1000

FREQUENCY - MHz


STOP = 2000

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIU_EH RUN RUN 1

UKA0 07/18/02



RADIATED NARROWBAND EMISSIONS - dBu/m

32 of 39

START = 2000

FREQUENCY - MHz

10000

STOP = 18000


ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIU_EM RUN RUN 4

UKA0 07/18/02

TEST : RADIATED NARROWBAND EMISSIONS
 SPEC : FCC 15.247 PRELIM RAD EMISSIONS
 MANUFACTURER : MOTOROLA INC.
 MODEL No. : BT0406AJ08
 S/N : 00E00C49565E
 MODE : TRANSMIT @ 2480.0MHz
 DATE TESTED : 1 Nov 2002 14:09:36 R. KING
 NOTES :
 ANT POLARITY : VERTICAL



RADIATED NARROWBAND EMISSIONS - dBu/m

33 of 39

START = 30

FREQUENCY - MHz

100


STOP = 1000

ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNTV_EM RUN RUN 3

UKA0 07/18/02



34 of 39


ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UKA0 07/18/02

UNIV_EM RUN RUN 1

TEST : RADIATED NARROWBAND EMISSIONS
 SPEC : PRELIMIN RADIATED EMISSIONS
 MANUFACTURER : MOTOROLA INC
 MODEL No. : BT0406AJ08
 S/N : 00E00C49565E
 MODE : TRANSMIT @ 2480.0MHz
 DATE TESTED : 29 Oct 2002 14:01:32 R. KING
 NOTES :
 ANT POLARITY : VERTICAL



RADIATED NARROWBAND EMISSIONS - dBu/m

35 of 39

START = 2000

FREQUENCY - MHz

10000

STOP = 18000

ETR No. 31533-01
DATA SHEET



MANUFACTURER : MOTORLOLA INC.
 MODEL No. : BT0406AJ08
 SERIAL No. : 00E00C49565E
 SPECIFICATION : FCC-15C Spurious Radiated Emissions
 DATE : OCTOBER 28, 2002
 NOTES : TRANSMITTING @ 2402.0 MHz
 : TEST DISTANCE IS 3 METERS

FREQ MHz	ANT POL	MTR RDG dBuV		BW	ANT FAC	CABLE LOSS	PRE AMP	TOTAL dBuV/m	TOTAL uV/m	LIMIT uV
2402.0	H	75.2		1M/3M	30.9	3.2	-35.9	73.4	4698.9	
	V	78.9		1M/3M	30.9	3.2	-35.9	77.1	7194.5	
4804.0	H	30.4	AMB	1M/10	33.8	5.8	-35.1	34.9	55.3	500.0
	V	30.3	AMB	1M/10	33.8	5.8	-35.1	34.8	54.7	500.0
12010.0	H	33.1	AMB	1M/10	41.6	8.6	-35.4	47.9	249.5	500.0
	V	33.2	AMB	1M/10	41.6	8.6	-35.4	48.0	251.2	500.0
19216.0	H	12.43	AMB	1M/10	40.3	0.0	0.0	52.7	433.0	500.0
	V	12.5	AMB	1M/10	40.3	0.0	0.0	52.8	436.5	500.0

CHECKED BY: Richard E. King
Richard E. King



ETR No. 31533-01
DATA SHEET

MANUFACTURER : MOTORLOLA INC.
 MODEL No. : BT0406AJ08
 SERIAL No. : 00E00C49565E
 SPECIFICATION : FCC-15C Spurious Radiated Emissions
 DATE : OCTOBER 28, 2002
 NOTES : TRANSMITTING @ 2441.0 MHz
 : TEST DISTANCE IS 3 METERS

FREQ MHz	ANT POL	MTR RDG dBuV		BW	ANT FAC	CABLE LOSS	PRE AMP	TOTAL dBuV/m	TOTAL uV/m	LIMIT uV
2441.0	H	73.0		1M/3M	30.9	3.2	-35.9	71.2	3647.5	
	V	77.1		1M/3M	30.9	3.2	-35.9	75.3	5847.9	
4882.0	H	30.3	AMB	1M/10	33.8	5.8	-35.1	34.8	54.7	500.0
	V	30.0	AMB	1M/10	33.8	5.8	-35.1	34.5	52.8	500.0
7323.0	H	32.6	AMB	1M/10	38.0	6.8	-35.3	42.1	127.4	500.0
	V	32.5	AMB	1M/10	38.0	6.8	-35.3	42.0	125.9	500.0
12205.0	H	32.6	AMB	1M/10	41.6	8.6	-34.9	47.9	249.5	500.0
	V	32.7	AMB	1M/10	41.6	8.6	-34.9	48.0	251.2	500.0
19528.0	H	12.8	AMB	1M/10	40.3	0.0	0.0	53.1	449.8	500.0
	V	12.8	AMB	1M/10	40.3	0.0	0.0	53.1	453.9	500.0

CHECKED BY: Richard E. King
Richard E. King



ETR No. 31533-01
DATA SHEET

MANUFACTURER : MOTORLOLA INC.
 MODEL No. : BT0406AJ08
 SERIAL No. : 00E00C49565E
 SPECIFICATION : FCC-15C Spurious Radiated Emissions
 DATE : OCTOBER 28, 2002
 NOTES : Transmitting @ 2480.0MHz
 : TEST DISTANCE IS 3 METERS

FREQ	ANT	MTR		ANT	CABLE	PRE	TOTAL	TOTAL	LIMIT	
MHz	POL	RDG		FAC	LOSS	AMP	dBuV/m	uV/m	uV	
		dBuV	BW							
2480.0	H	78.4		1M/3M	30.9	3.2	-35.9	76.6	6792.0	
	V	82.3		1M/3M	30.9	3.2	-35.9	80.5	10641.4	
4960.0	H	29.6	AMB	1M/10	33.8	5.8	-35.1	34.1	50.5	500.0
	V	29.7	AMB	1M/10	33.8	5.8	-35.1	34.2	51.1	500.0
7440.0	H	33.0	AMB	1M/10	38.0	6.8	-34.4	43.4	147.9	500.0
	V	33.1	AMB	1M/10	38.0	6.8	-34.4	43.5	149.6	500.0
12400.0	H	32.6	AMB	1M/10	41.6	8.6	-34.2	48.6	270.4	500.0
	V	32.5	AMB	1M/10	41.6	8.6	-34.2	48.5	266.1	500.0
19840.0	H	12.5	AMB	1M/10	40.3	0.0	0.0	52.8	436.5	500.0
	V	12.4	AMB	1M/10	40.3	0.0	0.0	52.7	431.5	500.0
22320.0	H	12.2	AMB	1M/10	40.4	0.0	0.0	52.6	425.6	500.0
	V	12.4	AMB	1M/10	40.4	0.0	0.0	52.8	434.0	500.0

CHECKED BY: Richard E. King
Richard E. King

ELITE ELECTRONIC ENGINEERING Inc.

MKR 2.441 013 GHz
-48.20 dBm

hp

REF 18.0 dBm ATTEN 30 dB

10 dB/

MANUFACTURER : MOTOROLA INC.
MODEL : BT0406AJ08

R. KING
29 Oct 2002
16:33:25

OFFSET

-20.0

dB

SERIAL NUMBER : 00E08G49565E

TEST PERFORMED: FCC 15.247 POWER SPECTRAL DENSITY

MODE : INQUIRY

8 dBm Limit

NOTES

: FULL POWER MAXIMIZED


DL

8.0

dBm

ETR 31533-01

-40.8 dBm ERP



39 of 39

CENTER 2.441 00 GHz

RES BW 3 kHz(i)

VBW 30 kHz

SPAN 1.00 MHz

SWP 333 sec