



MOBILE DEVICES BUSINESS

**PRODUCT SAFETY AND COMPLIANCE
EMC LABORATORY**

EMC TEST REPORT

Test Report Number – 20139-1 Supplement

Report Date – October 5, 2006

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Signature: 

Name: Albert J. Patapack

Title: EMC Engineer

Date: October 5, 2006

This report must not be reproduced, except in full, without written approval from this laboratory.

THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.

A2LA Certificate Number: 1651-01/2518-02

Table of Contents

<u>Description</u>	<u>Page</u>
Test Report Details	3
Applicable Standards	3
Summary of Testing	4
General and Special Conditions	4
Equipment and Cable Configuration	5
Measurement Procedures and Data	6

Test Report Details

Tests Performed By: Motorola Mobile Devices business (MDb)
Product Safety and Compliance Group
600 North US Hwy 45
Libertyville, IL 60048
PH (847) 523-6167 Fax (847) 523-4538
Motorola MDb FRN: 0004321311
FCC Registration Number: 316588
Industry Canada Number: IC3908-1

Tests Requested By: Motorola Inc.
Mobile Devices business
600 North US Hwy 45
Libertyville, IL 60048

Signaling Capability: GSM 1900, EDGE, Bluetooth

FCC ID : IHDT6GD2

Serial Numbers: LVE04J0010, LVE04J0018, LVE04J0006

Testing Complete Date: October 5, 2006

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47:

 X Part 15 Subpart B – Unintentional Radiators

Applicable Standards: ANSI 63.4 2003

Summary of Testing

<u>Test #</u>	<u>Test Name</u>	<u>Pass/Fail</u>
1	Field Strength of Spurious Emissions from Unintentional Radiators	Pass
2	AC Line Conducted Emissions	Pass

<u>Test #</u>	<u>Test Name</u>	<u>Margin with respect to the Limit</u>
1	Field Strength of Spurious Emissions from Unintentional Radiators	see results
2	AC Line Conducted Emissions	see results

The margin with respect to the limit is the minimum margin for all modes and bands.

General and Special Conditions

The EUT was tested using a fully charged battery.
 All testing was done in an indoor controlled environment with an average temperature of 22° C and relative humidity of 50%.

Equipment List

Manufacturer	Equipment Type	Model No.	Serial Number	Calibration Due Date
Rohde Schwarz	Receiver	ESI26	100001	3/08/07
Rohde Schwarz	Receiver	ESI40	100226	6/05/07
A.H. Systems Inc.	DRG Horn Antenna	SAS 200/571	365	5/12/07
ETS	Log-Periodic Antenna	3148	1188	5/12/07
ETS	Biconical Antenna	3110B	3370	3/03/07
Attenuator	Weinschel	AS-6	6675	1/10/07
Attenuator	Weinschel	AS-6	6677	11/14/06
ETS	LISN	3810/2NM	00062907	5/10/07
ETS	LISN	3810/2NM	00062912	5/10/07
Dell	Laptop Computer	M20	NA	NA
Iomega	Zip Drive	Z250S	P9HM1992CK	NA
Olympus	Camera	D-600L	4020727	NA

All equipment is on a one-year calibration cycle.

The Dell M20 Laptop Computer, the Iomega Z250S Zip Drive and the Olympus D-600L Camera are labeled as DoC.

Measurement Procedures and Data

FIELD STRENGTH OF EMISSIONS FROM UNINTENTIONAL RADIATORS

Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table on the turntable center. For each radiated emission, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum peak reading on the spectrum analyzer. The final radiated emissions are then measured using an EMI receiver employing a CISPR quasi-peak detector function below 1000 MHz and an average detector function above 1000 MHz. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The field strength of each radiated emission is calculated by correcting the EMI receiver level for cable loss, amplifier gain, and antenna correction factors.

$$\text{Field Strength (dBuV/m)} = \text{EMI Receiver Level (dBuV)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)} + \text{Antenna Correction Factor (1/m)}$$

Test Setup

The EUT and the host equipment were setup according to the procedures in ANSI C63.4-2003. The EUT was connected to a laptop computer using a USB data cable. The USB data cable is 1 m in length. The parallel and the serial ports of the computer were populated. The EUT was communicating with the laptop computer continuously.

Measurement Results

Operating Mode – Rx Mode, Data Transfer Mode.

30 MHz – 1000 MHz

Frequency MHz	Level dBuV/m	Measured dBuV	Transd dB	Cables dB	Limit dBuV/m	Margin dB	Height cm	Angle deg	Pol.
30.88	37.09	15.99	13.3	7.8	40	2.9	100	232	VERT
31.00	38.1	17	13.3	7.8	40	1.9	100	141	VERT
31.16	37.79	16.7	13.3	7.8	40	2.2	100	67	VERT
31.36	37.58	16.58	13.2	7.8	40	2.4	100	70	VERT
34.36	36.22	15.98	12.4	7.8	40	3.8	100	205	VERT
34.88	36.12	15.98	12.3	7.8	40	3.9	100	159	VERT
147.28	39.79	16.63	13.1	10.1	43.5	3.7	100	218	VERT
191.40	38.68	12.67	15.5	10.5	43.5	4.8	100	348	VERT
196.36	35.84	10.07	15.2	10.6	43.5	7.7	100	237	HORI
915.76	39.71	-0.61	24.4	15.9	46	6.3	137	104	HORI
952.20	39.4	-0.56	23.9	16.1	46	6.6	150	279	HORI

Above 1 GHz

Frequency MHz	Level dBuV/m	Measured dBuV	Transd dB	Gain dB	Limit dBuV/m	Margin dB	Height cm	Angle deg	Pol.
1122.3	36.85	21.77	23.8	8.8	53.9	17	334	332	VERT
1126.2	35.53	20.37	23.9	8.7	53.9	18.4	134	307	VERT
1946.7	39.54	17.65	28.1	6.2	53.9	14.4	100	200	HORI
1975.6	39.7	17.48	28.2	6	53.9	14.2	134	286	VERT
1992.3	39.73	17.3	28.4	6	53.9	14.2	134	0	VERT
2001.8	40.2	17.26	28.9	6	53.9	13.7	129	52	HORI

Notes: Worst Case emissions reported.

Peak Radiated Data for Emissions Above 1GHz

Frequency MHz	Level dBuV/m	Angle deg	Height cm	Pol.
1122.2445	50.26	75	300	VER
1126.2525	50.29	329	100	VER
1945.8918	51.23	194	100	HOR
1975.9519	51.89	302	100	VER
1977.9559	50.8	77	100	HOR
1993.988	51.45	18	100	VER
1995.992	51.23	113	100	VER
2000	50.82	71	100	HOR

AC LINE CONDUCTED EMISSIONS

Measurement Procedure

Measured levels of ac power line conducted emission shall be the radio-noise voltage from the line probe or across the 50 Ω LISN port, where permitted, terminated into a 50 Ω noise meter, or where permitted or required, the radio-noise current on the power line sensed by a current probe.

All radio-noise voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN. Equipment shall be tested with power cords that are normally supplied using an LISN, the 50 Ω measuring port is terminated by a 50 Ω radio-noise meter or a 50 Ω resistive load. All other ports are terminated in 50 Ω .

Detectors - Quasi Peak and Average Detector


Test Setup

The EUT and the host equipment were setup according to the procedures in ANSI C63.4-2003. The EUT was connected to a laptop computer using a USB data cable. The USB data cable is 1 m in length. The parallel and the serial ports of the computer were populated. The EUT was communicating with the laptop computer continuously.


Measurement Results

See attached:

Part15 AC Line -Line



Part15 AC Line - Neutral



End of Test Report