



MOBILE DEVICES BUSINESS

**PRODUCT SAFETY AND COMPLIANCE
EMC LABORATORY**


EMC TEST REPORT

Test Report Number – 20986-1 Supplement

Report Date – September 11, 2007

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Signature: 

Name: Thanigaiselvan Palaniswami

Title: EMC Engineer

Date: September 11, 2007

This report must not be reproduced, except in full, without written approval from this laboratory.

THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY
A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.

A2LA Certificate Number: 2518-02

Table of Contents

<u>Description</u>	<u>Page</u>
Test Report Details	3
Applicable Standards	3
Summary of Testing	4
General and Special Conditions	4
Equipment List	5
Measurement Procedures and Data	6

Test Report Details

Tests Performed By: Motorola Mobile Devices Business (MDb)
Product Safety and Compliance Group
600 North US Hwy 45
Libertyville, IL 60048
PH (847) 523-6167 Fax (847) 523-4538
Motorola MDb FRN: 0004321311
FCC Registration Number: 316588
Industry Canada Number: IC3908-1

Tests Requested By: Motorola Inc.
Mobile Devices Business
600 North US Hwy 45
Libertyville, IL 60048

Product Type: Cellular Phone

Signaling Capability: GSM 1900, Bluetooth

FCC ID: IHDT6GM2

Serial Numbers: 356893010010856, 356893010010864,
356893010011243, 356893010010880

Testing Complete Date: September 06, 2007

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47:

 X Part 15 Subpart B – Unintentional Radiators

Applicable Standards: ANSI 63.4 2003

Summary of Testing

<u>Test #</u>	<u>Test Name</u>	<u>Pass/Fail</u>
1	Field Strength of Spurious Emissions from Unintentional Radiators	Pass
2	AC Line Conducted Emissions	Pass
<u>Test #</u>	<u>Test Name</u>	<u>Margin with respect to the Limit</u>
1	Field Strength of Spurious Emissions from Unintentional Radiators	see results
2	AC Line Conducted Emissions	see results

The margin with respect to the limit is the minimum margin for all modes and bands.

General and Special Conditions

The EUT was tested using a fully charged battery.

All testing was done in an indoor controlled environment with an average temperature of 22° C and relative humidity of 50%.

Equipment List

Manufacturer	Equipment Type	Model No.	Serial Number	Calibration Due Date
Rohde Schwarz	Receiver	ESI26	100001	5/02/08
Rohde Schwarz	Receiver	ESI40	838786/010	3/19/08
A.H. Systems Inc.	DRG Horn Antenna	3115	6222	3/21/08
ETS	Log-Periodic Antenna	3148	1189	9/12/07
ETS	Biconical Antenna	3110B	3369	9/12/07
Attenuator	Weinschel	AS-6	6675	1/31/08
Attenuator	Weinschel	AS-6	6677	6/21/08
ETS	LISN	3810/2NM	00062907	5/02/08
ETS	LISN	3810/2NM	00062912	5/02/08
Dell	Laptop Computer	M20	NA	NA
Iomega	Zip Drive	Z250S	P9HM1992CK	NA
Olympus	Camera	D-600L	4020727	NA

All equipment is on a one-year calibration cycle.

The Dell M20 Laptop Computer, the Iomega Z250S Zip Drive and the Olympus D-600L Camera are labeled as DoC.

Measurement Procedures and Data

FIELD STRENGTH OF EMISSIONS FROM UNINTENTIONAL RADIATORS

Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table on the turntable center. For each radiated emission, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum peak reading on the spectrum analyzer. The final radiated emissions are then measured using an EMI receiver employing a CISPR quasi-peak detector function below 1000 MHz and an average detector function above 1000 MHz. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The field strength of each radiated emission is calculated by correcting the EMI receiver level for cable loss, amplifier gain, and antenna correction factors.

$$\text{Field Strength (dBuV/m)} = \text{EMI Receiver Level (dBuV)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)} + \text{Antenna Correction Factor (1/m)}$$

Test Setup

The EUT and the host equipment were setup according to the procedures in ANSI C63.4-2003. The EUT was connected to a laptop computer using a USB data cable. The USB data cable is 1 m in length. The parallel and the serial ports of the computer were populated. The EUT was communicating with the laptop computer continuously.

Measurement Results

Operating Mode – Rx Mode, Data Transfer Mode.

30 MHz – 1000 MHz

Frequency	Level	Measured	Transd	Cables	Limit	Margin	Height	Angle	Pol.
MHz	dBuV/m	dBuV	dB	dB	dBuV/m	dB	cm	deg	
188.48	28.93	3.19	15.3	10.5	43.5	14.6	149	293	VERT
191.48	24.74	-1.27	15.5	10.5	43.5	18.8	199	283	VERT
196.04	29.67	3.41	15.7	10.6	43.5	13.8	250	257	VERT
573	31.37	-1.48	18.9	14	46	14.6	250	0	VERT
909.2	39.27	-0.56	23.9	15.9	46	6.7	204	3	HORI
951.04	39.04	-0.51	23.5	16	46	7	350	359	HORI

Above 1 GHz

Frequency	Level	Measured	Transd	Gain	Limit	Margin	Height	Angle	Pol.
MHz	dBuV/m	dBuV	dB	dB	dBuV/m	dB	cm	deg	
1795.8	40.46	19.81	26.8	6.1	53.9	13.4	380	256	VERT
1833.5	40.53	19.52	26.9	5.9	53.9	13.4	250	126	VERT
1915.5	41.04	19.38	27.2	5.5	53.9	12.9	400	283	VERT
1922.1	41.04	19.37	27.2	5.5	53.9	12.9	380	261	VERT
1945.9	41.28	19.4	27.4	5.5	53.9	12.6	268	114	HORI
1977.9	41.43	19.65	27.2	5.4	53.9	12.5	400	191	VERT
1985.1	41.93	19.65	27.7	5.4	53.9	12	150	148	HORI
1985.8	41.45	19.66	27.2	5.4	53.9	12.4	150	75	VERT
1991.9	42.04	19.7	27.7	5.4	53.9	11.9	269	216	HORI
1995.4	41.63	19.82	27.2	5.4	53.9	12.3	248	252	VERT

Notes: Worst Case emissions reported.

Peak Radiated Data for Emissions Above 1GHz

Frequency	Level	Angle	Height	Pol.
MHz	dBuV/m	deg	cm	
1795.5912	52.86	239	400	VER
1833.6673	52.67	104	300	VER
1915.8317	52.91	267	400	VER
1923.8477	53.14	239	400	VER
1945.8918	52.28	208	300	HOR
1977.9559	52.07	135	300	HOR
1985.9719	53.71	126	200	HOR
1991.984	52.5	328	200	VER
1995.992	53.02	44	400	VER

AC LINE CONDUCTED EMISSIONS

Measurement Procedure

Measured levels of ac power line conducted emission shall be the radio-noise voltage from the line probe or across the 50 Ω LISN port, where permitted, terminated into a 50 Ω noise meter, or where permitted or required, the radio-noise current on the power line sensed by a current probe.

All radio-noise voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN. Equipment shall be tested with power cords that are normally supplied using an LISN, the 50 Ω measuring port is terminated by a 50 Ω radio-noise meter or a 50 Ω resistive load. All other ports are terminated in 50 Ω .

Detectors - Quasi Peak and Average Detector


Test Setup

The EUT and the host equipment were setup according to the procedures in ANSI C63.4-2003. The EUT was connected to a laptop computer using a USB data cable. The USB data cable is 1 m in length. The parallel and the serial ports of the computer were populated. The EUT was communicating with the laptop computer continuously.


Measurement Results

See attached:

Part15 AC Line –Line



Part15 AC Line - Neutral



End of Test Report