



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

**Mobile Phone-based Navigation System T805, Mobile Smart phone-based
Navigation System T815**

Model: SYN2126A; SYN2127A

Trade Name: Motorola

Prepared for

Motorola, Inc.

Mobile Devices, 600 N.U.S. Highway 45, Libertyville

Prepared by

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

NO. 5, JINAO INDUSTRIAL PARK, NO. 35 JUKENG ROAD,

DASHUIKENG VILLAGE, GUANLAN TOWN, BAOAN

DISTRICT, SHENZHEN, CHINA

TEL: 86-755-28055000

FAX: 86-755-28055221



LAB CODE:200577-0

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION	3
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	6
3.5 DESCRIPTION OF TEST MODES	6
4. INSTRUMENT CALIBRATION.....	7
5. FACILITIES AND ACCREDITATIONS	8
5.1 FACILITIES	8
5.2 EQUIPMENT	8
5.3 LABORATORY ACCREDITATIONS AND LISTING	8
6. SETUP OF EQUIPMENT UNDER TEST	9
6.1 SETUP CONFIGURATION OF EUT	9
6.2 SUPPORT EQUIPMENT	9
7. FCC PART 15.247 REQUIREMENTS.....	10
7.1 PEAK POWER	10
7.2 PEAK POWER SPECTRAL DENSITY	11
7.3 BAND EDGES MEASUREMENT.....	14
7.4 FREQUENCY SEPARATION	19
7.5 NUMBER OF HOPPING FREQUENCY	22
7.6 SPURIOUS EMISSIONS	24
7.7 POWERLINE CONDUCTED EMISSIONS	46
APPENDIX 1 PHOTOGRPHS OF TEST SETUP.....	49



1. TEST RESULT CERTIFICATION

Applicant: Motorola, Inc.
Mobile Devices, 600 N.U.S. Highway 45, Libertyville

Equipment Under Test: Mobile Phone-based Navigation System T805, Mobile Smart
phone-based Navigation System T815

Trade Name: Motorola

Model: SYN2126A; SYN2127A

Date of Test: March 09~April 23, 2007

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Tested By: Maya You

Clinton Kao / Manager
COMPLIANCE CERTIFICATION
SERVICES (SHENZHEN) INC.

Reviewed By:

Eric Wong / Assistant manager
COMPLIANCE CERTIFICATION
SERVICES (SHENZHEN) INC.



2. EUT DESCRIPTION

Product	Mobile Phone-based Navigation System T805, Mobile Smart phone-based Navigation System T815
Trade Name	Motorola
Model Number	SYN2126A; SYN2127A
Model Discrepancy	The products are identical except that the appearance colors are different.
Power Supply	DC 3.7V Powered by lithium battery; DC 5V Powered by the notebook; DC 5V Powered by the Adapter; DC 5V Powered by the car charger
Frequency Range	2402 ~ 2480 MHz
Transmit Power	4.68 dBm
Modulation Technique	FHSS
Number of Channels	79 Channels
Antenna Specification	Gain: 2dBi (max)
Temperature Range	0 ~ +55°C

Note: This submittal(s) (test report) is intended for FCC ID: IHDT6HA1 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2003. Radiated testing was performed at an antenna to EUT distance 3 meters.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003.

3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) are chosen for full testing.

The field strength of spurious radiation emission was measured in the following position: EUT stand-up position (Y mode) and lie-down position (X, Z mode) The following data show only the worst case setup.

The worst case (X axis) was reported.



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 5, Jinao industrial park, No.35 Jukeng Road, Dashuikeng Village, Guanlan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4: 2003 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200577-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
Notebook	IBM	992F2VG	DoC	N/A	N/A	Unshielded 1.8m
Mobile telephone	NOKIA	7610	QVVRH-51	N/A	N/A	N/A
Adapter 1	MOTOROLA	FMP5185B	N/A	N/A	N/A	Unshielded 1.80m
Adapter 2	MOTOROLA	FMP5202A	N/A	N/A	N/A	Unshielded 1.75m
Car Charge	MOTOROLA	SYN1630A	N/A	N/A	N/A	Unshielded 2.00m
USB Cable	N/A	SKN6371C	N/A	N/A	N/A	Shielded 1.00m

Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*



7. FCC PART 15.247 REQUIREMENTS

7.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
RF Power Meter & Sensor	Anritsu	ML2487A	6K00001491	02/23/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	408	060	468	0.00294	1	PASS
Md	2441	354	060	414	0.00259		PASS
Hgh	2480	288	060	348	0.00223		PASS



7.2 PEAK POWER SPECTRAL DENSITY

LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
Low	2402	-5.97	0.60	-5.37	8.00	PASS
Mid	2441	-5.56	0.60	-4.96		PASS
High	2480	-5.71	0.60	-5.11		PASS




Test Plot

PPSD (CH Low)

Agilent 15:07:03 Apr 19, 2007

R T

Mkr1 2.401 982 4 GHz
-5.37 dBm




PPSD (CH Mid)

Agilent 15:05:00 Apr 19, 2007

R T

Mkr1 2.440 981 9 GHz
-4.96 dBm





PPSD (CH High)

Agilent 15:02:50 Apr 19, 2007

R T

Mkr1 2.479 981 9 GHz

-5.11 dBm

Ref 10.6 dBm

#Atten 20 dB

#Peak

Log

10

dB/

Offst

0.6

dB

DI

8.0

dBm

LgAv

W1 S2

S3 FC

£(f):

f>50k

Swp


Center 2.480 000 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)



7.3 BAND EDGES MEASUREMENT


LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.



Test Data


Band Edges (CH-Low)

Detector mode: Peak

Polarity: Vertical

Agilent 15:51:02 Apr 19, 2007

R T




Detector mode: Average

Polarity: Vertical

Agilent 15:51:32 Apr 19, 2007

R T





Detector mode: Peak

Polarity: Horizontal

Agilent 16:00:26 Apr 19, 2007

R T

Mkr1 2.390 0 GHz
49.36 dB μ V

Ref 117 dB μ V

#Atten 20 dB

#Peak

Log

10

dB/

DI

74.0

dB μ V

LgAv

M1 S2

S3 FC

E(f):

FTun

Swp

Start 2.310 0 GHz

Stop 2.420 0 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 1 ms (601 pts)

Detector mode: Average

Polarity: Horizontal

Agilent 16:00:52 Apr 19, 2007

R T

Mkr1 2.390 0 GHz
37.80 dB μ V

Ref 117 dB μ V

#Atten 20 dB

#Peak

Log

10

dB/

DI

54.0

dB μ V

LgAv

M1 S2

S3 FC

E(f):

FTun

Swp

Start 2.310 0 GHz

Stop 2.420 0 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 8.577 s (601 pts)



Band Edges (CH-High)

Detector mode: Peak

Polarity: Vertical

Agilent 15:53:20 Apr 19, 2007

R T

Mkr1 2.483 50 GHz
53.93 dB μ V

Ref 117 dB μ V


#Atten 20 dB

#Peak
Log
10
dB/

DI
74.0
dB μ V
LgAv

M1 S2
S3 FC

E(f):
FTun
Swp



Start 2.450 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 1 ms (601 pts)

Detector mode: Average

Polarity: Vertical

Agilent 15:53:38 Apr 19, 2007

R T

Mkr1 2.483 50 GHz
42.08 dB μ V

Ref 117 dB μ V


#Atten 20 dB

#Peak
Log
10
dB/

DI
54.0
dB μ V
LgAv

M1 S2
S3 FC

E(f):
FTun
Swp



Start 2.450 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 3.899 s (601 pts)



Detector mode: Peak

Polarity: Horizontal

Agilent 15:57:32 Apr 19, 2007

R T

Mkr1 2.483 50 GHz
52.30 dB μ V

Ref 117 dB μ V


#Atten 20 dB

#Peak
Log
10
dB/

DI
74.0
dB μ V
LgAv

M1 S2
S3 FC

E(f):
FTun
Swp



Start 2.450 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 1 ms (601 pts)

Detector mode: Average

Polarity: Horizontal

Agilent 15:57:54 Apr 19, 2007

R T

Mkr1 2.483 50 GHz
40.74 dB μ V

Ref 117 dB μ V


#Atten 20 dB

#Peak
Log
10
dB/

DI
54.0
dB μ V
LgAv

M1 S2
S3 FC

E(f):
FTun
Swp



Start 2.450 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 3.899 s (601 pts)



7.4 FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2007

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW, VBW=30kHz, Adjust Span to 5 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

Channel Separation (MHz)	Limit (kHz)	Result
1.0	840kHz (20dB BW, Max)	Pass




Test Plot

Measurement of Channel Separation

Agilent 14:54:19 Apr 19, 2007

R T

▲ Mkr2 1.000 MHz
-0.04 dB




Test Plot

20 dB bandwidth(CH Mid)

Agilent 14:20:13 Apr 19, 2007

R T

▲ Mkr1 840 kHz
-0.09 dB





20 dB bandwidth(CH Low)

Agilent 14:19:10 Apr 19, 2007

R T

Mkr1 840 kHz

0.27 dB

Ref 117.6 dBμV

#Atten 20 dB

#Peak

Log

10

dB/

Offst

0.6

dB

DI

92.6

dBμV

LgAv

M1 S2

S3 FC

£(f):

f>50k

Swp

Center 2.402 000 GHz

#Res BW 30 kHz

#VBW 30 kHz

Span 3 MHz

Sweep 4.04 ms (601 pts)

20 dB bandwidth (CH High)

Agilent 14:21:25 Apr 19, 2007

R T

Mkr1 840 kHz

0.04 dB

Ref 117.6 dBμV

#Atten 20 dB

#Peak

Log

10

dB/

Offst

0.6

dB

DI

92.1

dBμV

LgAv

M1 S2

S3 FC

£(f):

f>50k

Swp

Center 2.480 000 GHz

#Res BW 30 kHz

#VBW 30 kHz

Span 3 MHz

Sweep 4.04 ms (601 pts)



7.5 NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = 250s and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = 250s.
4. Set the spectrum analyzer as RBW, VBW=100kHz,
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS




Test Plot

Channel Number

2.4 GHz – 2.441 GHz

Agilent 15:42:29 Apr 19, 2007


R L



2.441 GHz – 2.4835 GHz

Agilent 15:43:37 Apr 19, 2007

R T





7.6 TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

No non-compliance noted

Test Data

DH 1

CH Low: $0.42 * (1600/2)/79 * 31.6 = 134.4$ (ms)

CH Mid: $0.42 * (1600/2)/79 * 31.6 = 134.4$ (ms)

CH High: $0.42 * (1600/2)/79 * 31.6 = 134.4$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.42	134.4	31.60	400.00	PASS
Mid	0.42	134.4	31.60		PASS
High	0.42	134.4	31.60		PASS

DH 3

CH Low: $1.67 * (1600/4)/79 * 31.6 = 267.2$ (ms)

CH Mid: $1.67 * (1600/4)/79 * 31.6 = 267.2$ (ms)

CH High: $1.68 * (1600/4)/79 * 31.6 = 268.8$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.67	267.2	31.60	400.00	PASS
Mid	1.67	267.2	31.60		PASS
High	1.68	268.8	31.60		PASS

DH 5

CH Low: $2.93 * (1600/6)/79 * 31.6 = 312.5$ (ms)

CH Mid: $2.92 * (1600/6)/79 * 31.6 = 311.5$ (ms)

CH High: $2.93 * (1600/6)/79 * 31.6 = 312.5$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.93	312.5	31.60	400.00	PASS
Mid	2.92	311.5	31.60		PASS
High	2.93	312.5	31.60		PASS



Test Plot


DH 1

(CH Low)

Agilent 10:26:54 Apr 25, 2007

R T


Δ Mkr1 416.7 μs
-0.04 dB



Agilent 10:27:13 Apr 25, 2007

R T

Δ Mkr1 1.25 ms
-0.01 dB






(CH Mid)

Agilent 10:33:13 Apr 25, 2007

R T


Δ Mkr1 416.7 μs
-0.13 dB



Agilent 10:33:28 Apr 25, 2007

R T

Δ Mkr1 1.25 ms
0.02 dB






(CH High)

Agilent 10:35:00 Apr 25, 2007

R T


Δ Mkr1 416.7 μs
-0.12 dB



Agilent 10:35:15 Apr 25, 2007

R T

Δ Mkr1 1.25 ms
0.03 dB






DH 3

(CH Low)

Agilent 10:28:21 Apr 25, 2007

R T


Δ Mkr1 1.667 ms
-0.11 dB



Agilent 10:28:41 Apr 25, 2007

R T

Δ Mkr1 2.5 ms
0.01 dB






(CH Mid)

Agilent 10:32:26 Apr 25, 2007

R T


▲ Mkr1 1.667 ms
-0.10 dB



Agilent 10:32:46 Apr 25, 2007

R T

▲ Mkr1 2.5 ms
0.04 dB






(CH High)

Agilent 10:35:43 Apr 25, 2007

R T


▲ Mkr1 1.683 ms
0.33 dB



Agilent 10:36:01 Apr 25, 2007

R T

▲ Mkr1 2.5 ms
0.04 dB






DH5

(CH Low)

Agilent 10:29:56 Apr 25, 2007

R T


▲ Mkr1 2.933 ms
-0.07 dB



Agilent 10:30:13 Apr 25, 2007

R T

▲ Mkr1 3.75 ms
-0.01 dB






(CH Mid)

Agilent 10:31:36 Apr 25, 2007

R T


▲ Mkr1 2.917 ms
-0.12 dB



Agilent 10:31:53 Apr 25, 2007

R T

▲ Mkr1 3.75 ms
0.00 dB






(CH High)

Agilent 10:36:33 Apr 25, 2007

R T


▲ Mkr1 2.933 ms
-0.14 dB



Agilent 10:36:49 Apr 25, 2007

R T

▲ Mkr1 3.75 ms
0.01 dB





SPURIOUS EMISSIONS

7.7 Conducted Measurement

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted




Test Plot

CH Low

30MHz – 2.9GHz

Agilent 14:27:43 Apr 19, 2007


R T



2.9GHz – 26.5GHz

Agilent 14:28:25 Apr 19, 2007

T






CH Mid

30MHz – 2.9GHz

Agilent 14:25:02 Apr 19, 2007


R T



2.9GHz – 26.5GHz

Agilent 14:26:40 Apr 19, 2007

R T






CH High

30MHz – 2.9GHz

Agilent 14:23:25 Apr 19, 2007


R T



2.9GHz – 26.5GHz

Agilent 14:24:03 Apr 19, 2007

R T





7.7.2 Radiated Emissions

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


MEASUREMENT EQUIPMENT USED


966 RF CHAMBER 2				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
PSA Spectrum Analyzer	Agilent	E4446A	US44300399	02/05/2008
EMI Test Receiver	R&S	ESCI	1166.5950 03	01/13/2008
Pre-Amplifier	MITEQ	N/A	AFS42-00102650-42-10P-42	02/14/2008
Bilog Antenna	SCHWAZBECK	CBL6143	5082	06/09/2007
Turn Table	EMCO	2081-1.21	N/A	N.C.R
Antenna Tower	CT	N/A	N/A	N.C.R
Controller	CT	N/A	N/A	N.C.R
RF Comm. Test set	HP	8920B	US36142090	N.C.R
Site NSA	C&C	N/A	N/A	06/09/2007
Horn Antenna	TRC	N/A	N/A	03/04/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

Below 1 GHz



Above 1 GHz**TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

**TEST RESULTS****Below 1 GHz****Operation Mode:** Normal**Test Date:** April 17, 2007**Temperature:** 25°C**Tested by:** Maya**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
75.000	V	Peak	52.01	-17.17	34.84	40.00	-5.16
109.200	V	Peak	42.77	-16.01	26.76	43.50	-16.74
122.700	V	Peak	50.75	-16.68	34.07	43.50	-9.43
127.650	V	Peak	48.80	-16.63	32.17	43.50	-11.33
142.500	V	Peak	44.41	-16.34	28.07	43.50	-15.43
163.650	V	Peak	49.14	-14.98	34.16	43.50	-9.34
41.700	H	Peak	37.12	-12.35	24.77	40.00	-15.23
49.800	H	Peak	41.29	-15.42	25.87	40.00	-14.13
55.200	H	Peak	45.51	-16.47	29.04	40.00	-10.96
190.650	H	Peak	37.18	-14.57	22.61	43.50	-20.89
601.000	H	Peak	29.94	-5.65	24.29	46.00	-21.71
799.333	H	Peak	29.39	-3.85	25.54	46.00	-20.46

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****Operation Mode:** TX(CH Low)**Test Date:** March 09, 2007**Temperature:** 25°C**Tested by:** Maya**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1060.00	V	53.68	---	-11.84	41.84	---	74.00	54.00	-12.16	Peak
1600.00	V	54.64	---	-9.03	45.61	---	74.00	54.00	-8.39	Peak
1863.33	V	51.49	---	-8.00	43.49	---	74.00	54.00	-10.51	Peak
4808.33	V	47.74	---	0.65	48.39	---	74.00	54.00	-5.61	Peak
N/A										
1603.33	H	57.73	---	-9.01	48.72	---	74.00	54.00	-5.28	Peak
1856.66	H	51.83	---	-8.02	43.81	---	74.00	54.00	-10.19	Peak
2226.66	H	50.93	---	-6.56	44.37	---	74.00	54.00	-9.63	Peak
4958.33	H	47.25	---	0.91	48.16	---	74.00	54.00	-5.84	Peak
N/A										

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

**Operation Mode:** TX (CH Mid)**Test Date:** March 09, 2007**Temperature:** 25°C**Tested by:** Maya**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1326.66	V	52.98	---	-10.37	42.61	---	74.00	54.00	-11.39	Peak
1590.00	V	53.36	---	-9.07	44.29	---	74.00	54.00	-9.71	Peak
1626.66	V	53.60	---	-8.92	44.68	---	74.00	54.00	-9.32	Peak
4883.33	V	46.27	---	0.78	47.05	---	74.00	54.00	-6.95	Peak
N/A										
1593.33	H	53.10	---	-9.05	44.05	---	74.00	54.00	-9.95	Peak
1626.66	H	57.03	---	-8.92	48.11	---	74.00	54.00	-5.89	Peak
2736.66	H	50.20	---	-4.82	45.38	---	74.00	54.00	-8.62	Peak
4800.00	H	46.25	---	0.64	46.89	---	74.00	54.00	-7.11	Peak
N/A										

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.



Operation Mode: TX(CH High)

Test Date: March 09, 2007

Temperature: 25°C

Tested by: Maya

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1060.00	V	57.59	---	-11.84	45.75	---	74.00	54.00	-8.25	Peak
1593.33	V	53.63	---	-9.05	44.58	---	74.00	54.00	-9.42	Peak
1653.33	V	54.47	---	-8.82	45.65	---	74.00	54.00	-8.35	Peak
4916.66	V	46.24	---	0.84	47.08	---	74.00	54.00	-6.92	Peak
N/A										
1066.66	H	55.29	---	-11.80	43.49	---	74.00	54.00	-10.51	Peak
1590.00	H	52.60	---	-9.07	43.53	---	74.00	54.00	-10.47	Peak
1653.33	H	59.15	---	-8.82	50.33	---	74.00	54.00	-3.67	Peak
4808.33	H	46.87	---	0.65	47.52	---	74.00	54.00	-6.48	Peak
N/A										

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

7.8 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site G				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESCI EMI TEST RECEIV.ESCI	ROHDE&SCHWARZ	1166.5950 03	100088	02/05/2008
LISN	EMCO	3825/2	1371	02/05/2008
LISN	EMCO	3825/2	8901-1459	02/05/2008

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

**TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Operation Mode: TX+RX**Test Date:** April 17, 2007**Temperature:** 25°C**Humidity:** 67% RH**Tested by:** Maya**USB Cable**

FREQ MHz	PEAK RAW dBuV	Q.P. RAW dBuV	AVG RAW dBuV	Q.P. Limit dBuV	AVG Limit dBuV	Q.P. Margin dB	AVG Margin dB	NOTE
0.224	53.81	48.96	38.81	63.88	53.88	-14.92	-15.07	L1
0.305	53.26	49.01	42.04	61.55	51.55	-12.54	-9.51	L1
0.698	49.95	43.81	35.95	56.00	46.00	-12.19	-10.05	L1
0.991	50.00	46.19	36.40	56.00	46.00	-9.81	-9.60	L1
10.376	44.97	38.46	31.81	60.00	50.00	-21.54	-18.19	L1
14.368	35.24	---	---	60.00	50.00	---	-14.76	L1
0.157	60.06	53.42	43.83	65.79	55.79	-12.37	-11.96	L2
0.253	48.12	40.31	31.05	63.03	53.03	-22.72	-21.98	L2
0.309	52.55	48.16	40.89	61.45	51.45	-13.29	-10.56	L2
0.728	47.27	38.26	29.34	56.00	46.00	-17.74	-16.66	L2
9.206	44.94	38.43	31.34	60.00	50.00	-21.57	-18.66	L2
23.955	28.31	21.93	15.84	60.00	50.00	-38.07	-34.16	L2

Adaptor (FMP5185B)

FREQ MHz	PEAK RAW dBuV	Q.P. RAW dBuV	AVG RAW dBuV	Q.P. Limit dBuV	AVG Limit dBuV	Q.P. Margin dB	AVG Margin dB	NOTE
0.253	48.67	44.34	32.90	63.03	53.03	-18.69	-20.13	L1
0.587	40.74	34.88	25.44	56.00	46.00	-21.12	-20.56	L1
1.021	41.38	34.99	25.29	56.00	46.00	-21.01	-20.71	L1
2.521	43.02	36.81	27.69	56.00	46.00	-19.19	-18.31	L1
4.364	45.09	39.15	29.60	56.00	46.00	-16.85	-16.40	L1
5.527	48.52	42.68	32.28	60.00	50.00	-17.32	-17.72	L1
0.175	47.61	---	---	65.26	55.26	---	-7.65	L2
0.253	44.86	---	---	63.03	53.03	---	-8.17	L2
0.316	40.78	---	---	61.23	51.23	---	-10.45	L2
1.658	36.47	---	---	56.00	46.00	---	-9.53	L2
2.472	38.82	---	---	56.00	46.00	---	-7.18	L2
5.358	43.89	---	---	60.00	50.00	---	-6.11	L2

Adaptor (FMP5202A)

FREQ MHz	PEAK RAW dBuV	Q.P. RAW dBuV	AVG RAW dBuV	Q.P. Limit dBuV	AVG Limit dBuV	Q.P. Margin dB	AVG Margin dB	NOTE
0.257	47.66	44.45	32.91	62.93	52.93	-18.48	-20.02	L1
0.402	43.26	38.28	31.87	58.80	48.80	-20.52	-16.93	L1
0.765	41.94	36.06	28.59	56.00	46.00	-19.94	-17.41	L1
1.013	41.61	35.31	28.09	56.00	46.00	-20.69	-17.91	L1
2.472	40.69	34.41	24.85	56.00	46.00	-21.59	-21.15	L1
22.977	35.88	29.50	20.87	60.00	50.00	-30.50	-29.13	L1
0.253	43.17	---	---	63.03	53.03	---	-9.86	L2
0.327	41.57	---	---	60.92	50.92	---	-9.35	L2
0.390	39.18	---	---	59.11	49.11	---	-9.93	L2
0.698	37.14	---	---	56.00	46.00	---	-8.86	L2
2.488	39.08	---	---	56.00	46.00	---	-6.92	L2
23.490	34.53	---	---	60.00	50.00	---	-15.47	L2


Note:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. “---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9KHz.
5. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

APPENDIX 1

PHOTOGRPHS OF TEST SETUP

Radiated Emission Set up Photos



Conducted Emission Set Up Photos

USB



Adapter (FMP5185B)



Adapter (FMP5202A)