

EXHIBIT 6

Voltages and Currents into Final Amplifying Devices

Exhibit Summary:

EXHIBIT 6 below contains the voltages and currents applied to the TX Driver and TX Final Power Amplifier for the entire mobile station operating power range.

Power Step	Power Output Spec. (dBm)	Power Output Meas. (dBm)	Vcc Driver (VDC)	Ic Driver (mA)	Vcc Final (VDC)	Ic Final (A)
0	30 +/-2	29.8	6.0	2.43	6.0	0.527
1	28 +/-3	28.3	6.0	1.64	6.0	0.487
2	26 +/-3	26.3	6.0	1.27	6.0	0.356
3	24 +/-2	24.3	6.0	1.09	6.0	0.318
4	22 +/-3	22.3	6.0	0.84	6.0	0.268
5	20 +/-3	20.3	6.0	0.73	6.0	0.227
6	18 +/-3	18.6	6.0	0.70	6.0	0.198
7	16 +/-3	16.1	6.0	0.55	6.0	0.179
8	14 +/-3	14.3	6.0	0.50	6.0	0.160
9	12 +/-4	12.7	6.0	0.45	6.0	0.146
10	10 +/-4	10.2	6.0	0.40	6.0	0.130
11	8 +/-4	8.3	6.0	0.34	6.0	0.099
12	6 +/-4	6.9	6.0	0.29	6.0	0.077
13	4 +/-4	5.2	6.0	0.21	6.0	0.061
14	2 +/-4	4.7	6.0	0.16	6.0	0.053
15	0 +/-4	4.2	6.0	0.10	6.0	0.044