

Declaration on radiation safety standard conformance - MPE Evaluation

To whom it may concern:

Agere Systems Nederland B.V.
Zadelstede 1-10
3431 JZ Nieuwegein
The Netherlands

declares that the following product

Description: 2.4 GHz Low Power RLAN transceiver
 FCC ID: IMRWLPCE2411R
 Manufacturer: Agere Systems Nederland B.V.
 Brand: Agere
 Type/model number: PC24E-11-FC/R
 External antenna: Telex 2417NL

has an e.i.r.p. of less than 21.5 dBi (142 mW, including a maximum antenna gain of +6.5 dBi), which means that the minimum distance for which the limit of 1.0 mW/cm² of power density (Table 1 in 47 CFR §1.1310) is not exceeded can be calculated as follows :

$$S = \frac{EIRP}{4 * \pi * R^2} \quad (\text{power density without reflection})$$

$$S = \frac{2^2 * EIRP}{4 * \pi * R^2} \quad (\text{power density with 100\% reflection})$$

$$S = \frac{2^2 * EIRP}{4 * \pi * R^2} = \frac{142 \text{ mW}}{\pi * (R)^2}$$

$$S = 1 = \frac{142 \text{ mW}}{\pi * (R)^2}$$

$$R = \sqrt{(142 \text{ mW} / \pi)} = 6.7 \text{ cm.}$$

This means that according to the Supplement C (edition 01-01) to OET Bulletin 65 (edition 97-01) the equipment can fulfil the requirements on power density for general population/uncontrolled exposure and therefore can fulfil the requirements of FCC Part 15.247(b) (4) at a separation distance of at least 6.7 cm between the user and the antenna.

The user/installation manual will contain the following RF Exposure statements:

"To comply with FCC RF exposure compliance requirements, the following antenna installation and device operating configurations must be satisfied:

- with mobile configurations using approved external antenna, a separation distance of at least 20cm (8 inches) shall be maintained between the antenna and the user. The transmitter shall not be co-located with other transmitters or antennae."*

Name: W. Kerkhof
 Position held: Regulatory Compliance